

FCC RF Test Report

APPLICANT : CT Asia
EQUIPMENT : Mobile Phone
BRAND NAME : BLU
MODEL NAME : Life Play
FCC ID : YHLBLULIFEPLAY
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on May 08, 2013 and completely tested on May 30, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.

TABLE OF CONTENTS

| | |
|---|-----------|
| REVISION HISTORY..... | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1 GENERAL DESCRIPTION | 5 |
| 1.1 Applicant..... | 5 |
| 1.2 Manufacturer | 5 |
| 1.3 Feature of Equipment Under Test..... | 5 |
| 1.4 Product Specification of Equipment Under Test | 6 |
| 1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator | 7 |
| 1.6 Testing Site | 7 |
| 1.7 Applied Standards | 7 |
| 2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST | 8 |
| 2.1 Test Mode..... | 8 |
| 2.2 Connection Diagram of Test System | 11 |
| 2.3 Support Unit used in test configuration and system..... | 11 |
| 2.4 Measurement Results Explanation Example | 11 |
| 3 TEST RESULT..... | 12 |
| 3.1 Conducted Output Power Measurement..... | 12 |
| 3.2 Peak-to-Average Ratio | 14 |
| 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement | 22 |
| 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... | 28 |
| 3.5 Band Edge Measurement..... | 48 |
| 3.6 Conducted Spurious Emission Measurement | 61 |
| 3.7 Field Strength of Spurious Radiated Measurement | 77 |
| 3.8 Frequency Stability for Temperature and Voltage Measurement | 92 |
| 4 LIST OF MEASURING EQUIPMENT | 97 |
| 5 UNCERTAINTY OF EVALUATION | 98 |
| APPENDIX A. PHOTOGRAPHS OF EUT | |
| APPENDIX B. SETUP PHOTOGRAPHS | |

REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|-------------------------|---------------|
| FG350801 | Rev. 01 | Initial issue of report | Jun. 13, 2013 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|-------------------------------------|---|--|--------|--|
| 3.1 | §2.1046 | Conducted Output Power | N/A | PASS | - |
| 3.2 | §24.232(d) | Peak-to-Average Ratio | < 13 dB | PASS | - |
| 3.3 | §22.913(a)(2) | Effective Radiated Power | < 7 Watts | PASS | - |
| 3.3 | §24.232(c) | Equivalent Isotropic Radiated Power | < 2 Watts | PASS | - |
| 3.4 | §2.1049 §22.917(b) §24.238(b) | 99% Occupied Bandwidth and 26dB Bandwidth | N/A | PASS | - |
| 3.5 | §2.1051 §22.917(a) §24.238(a) | Band Edge Measurement | $< 43 + 10 \log_{10}(P[\text{Watts}])$ | PASS | - |
| 3.6 | §2.1051 §22.917(a) §24.238(a) | Conducted Spurious Emission | $< 43 + 10 \log_{10}(P[\text{Watts}])$ | PASS | - |
| 3.7 | §2.1053 §22.917(a) §24.238(a) | Field Strength of Spurious Radiated | $< 43 + 10 \log_{10}(P[\text{Watts}])$ | PASS | Under limit 22.10 dB at 1672.000 MHz |
| 3.8 | §2.1055 §22.355 §24.235 | Frequency Stability for Temperature and Voltage | < 2.5 ppm | PASS | - |

1 General Description

1.1 Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Gionee Communication Equipment Co., Ltd.

21/F, Times Technology Building, No. 7028, Shennan Avenue, Futian District, Shenzhen, China

1.3 Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|---|
| Equipment | Mobile Phone |
| Brand Name | BLU |
| Model Name | Life Play |
| FCC ID | YHLBLULIFEPLAY |
| EUT supports Radios application | GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/ WLAN 11bgn/Bluetooth |
| HW Version | LIFE PLAY_Mainboard_P1 |
| SW Version | BLU_L100a_V07_GENERIC |
| EUT Stage | Production Unit |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

| Product Specification subjective to this standard | |
|---|---|
| Tx Frequency | GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz |
| Rx Frequency | GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz |
| Maximum Output Power to Antenna | GSM850 : 32.48 dBm GSM1900 : 29.15 dBm WCDMA Band V : 22.91 dBm WCDMA Band II : 22.69 dBm |
| Antenna Type | Fixed Internal Antenna |
| Type of Modulation | GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA/DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) DC-HSDPA: 64QAM (Downlink Only) HSPA+: 16QAM (Uplink) |

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

| FCC Rule | System | Type of Modulation | Maximum ERP/EIRP (W) | Frequency Tolerance (% , Hz, ppm) | Emission Designator |
|----------|----------------------------|--------------------|----------------------|-----------------------------------|---------------------|
| Part 22 | GSM850 GSM | GMSK | 0.8279 | 0.02 ppm | 248KGXW |
| Part 22 | GSM850 EDGE 8 | 8PSK | 0.2046 | 0.02 ppm | 244KG7W |
| Part 22 | WCDMA Band V RMC 12.2Kbps | QPSK | 0.0986 | 0.02 ppm | 4M18F9W |
| Part 24 | GSM1900 GSM | GMSK | 1.2331 | 0.01 ppm | 250KGXW |
| Part 24 | GSM1900 EDGE 8 | 8PSK | 0.5808 | 0.02 ppm | 246KG7W |
| Part 24 | WCDMA Band II RMC 12.2Kbps | QPSK | 0.2871 | 0.01 ppm | 4M20F9W |

1.6 Testing Site

| | | | |
|---------------------------|--|-----------|--------------------------------|
| Test Site | SPORTON INTERNATIONAL (SHENZHEN) INC. | | |
| Test Site Location | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398 | | |
| Test Site No. | Sporton Site No. | | FCC/IC Registration No. |
| | TH01-SZ | 03CH01-SZ | 831040 |

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

| Test Modes | | |
|----------------------|---|---|
| Band | Radiated TCs | Conducted TCs |
| GSM 850 | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link |
| GSM 1900 | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link | <ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link |
| WCDMA Band V | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link |
| WCDMA Band II | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link | <ul style="list-style-type: none"> ■ RMC 12.2Kbps Link |

Note: The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

For SIM1 Card

| Conducted Power (*Unit: dBm) | | | | | | |
|------------------------------|--------|-------|-------|---------|--------|--------|
| Band | GSM850 | | | GSM1900 | | |
| Channel | 128 | 189 | 251 | 512 | 661 | 810 |
| Frequency | 824.2 | 836.4 | 848.8 | 1850.2 | 1880.0 | 1909.8 |
| GSM | 32.42 | 32.48 | 32.45 | 29.14 | 29.11 | 29.15 |
| GPRS 8 | 32.41 | 32.47 | 32.44 | 29.11 | 29.08 | 29.14 |
| GPRS 10 | 31.74 | 31.80 | 31.79 | 28.31 | 28.27 | 28.34 |
| GPRS 11 | 30.11 | 30.16 | 30.15 | 26.75 | 26.74 | 26.79 |
| GPRS 12 | 29.13 | 29.19 | 29.18 | 25.97 | 26.02 | 26.08 |
| EGPRS 8 | 27.00 | 27.04 | 27.00 | 25.40 | 25.52 | 25.48 |
| EGPRS 10 | 25.61 | 25.65 | 25.68 | 24.20 | 24.28 | 24.32 |
| EGPRS 11 | 23.17 | 23.19 | 23.20 | 21.60 | 21.62 | 21.60 |
| EGPRS 12 | 21.95 | 22.00 | 22.05 | 20.25 | 20.33 | 20.32 |


| Conducted Power (*Unit: dBm) | | | | | | |
|------------------------------|--------------|-------|-------|---------------|--------|--------|
| Band | WCDMA Band V | | | WCDMA Band II | | |
| Channel | 4132 | 4182 | 4233 | 9262 | 9400 | 9538 |
| Frequency | 826.4 | 836.4 | 846.6 | 1852.4 | 1880.0 | 1907.6 |
| RMC 12.2Kbps | 22.83 | 22.65 | 22.91 | 22.69 | 22.57 | 22.32 |
| HSDPA Subtest-1 | 21.89 | 21.87 | 21.98 | 21.78 | 21.74 | 21.58 |
| HSDPA Subtest-2 | 21.87 | 21.85 | 21.94 | 21.69 | 21.65 | 21.47 |
| HSDPA Subtest-3 | 21.54 | 21.44 | 21.57 | 21.41 | 21.33 | 21.21 |
| HSDPA Subtest-4 | 21.48 | 21.40 | 21.51 | 21.30 | 21.29 | 21.10 |
| DC-HSDPA Subtest-1 | 21.57 | 21.68 | 21.15 | 22.12 | 21.96 | 21.51 |
| DC-HSDPA Subtest-2 | 21.52 | 21.65 | 21.14 | 22.11 | 21.94 | 21.49 |
| DC-HSDPA Subtest-3 | 21.24 | 21.26 | 20.74 | 21.63 | 21.50 | 21.07 |
| DC-HSDPA Subtest-4 | 21.22 | 21.25 | 20.73 | 21.61 | 21.49 | 21.02 |
| HSUPA Subtest-1 | 20.39 | 20.35 | 20.48 | 20.28 | 20.24 | 20.14 |
| HSUPA Subtest-2 | 19.26 | 19.21 | 19.34 | 19.17 | 19.11 | 19.02 |
| HSUPA Subtest-3 | 20.29 | 20.13 | 20.24 | 20.22 | 20.22 | 20.11 |
| HSUPA Subtest-4 | 19.27 | 19.28 | 19.24 | 19.23 | 19.15 | 19.01 |
| HSUPA Subtest-5 | 20.61 | 20.59 | 20.67 | 20.55 | 20.56 | 20.45 |
| HSPA+ (16QAM) Subtest-1 | 18.55 | 18.69 | 18.72 | 20.56 | 20.40 | 20.01 |

For SIM2 Card

| Conducted Power (*Unit: dBm) | | | | | | |
|------------------------------|--------|-------|-------|---------|--------|--------|
| Band | GSM850 | | | GSM1900 | | |
| Channel | 128 | 189 | 251 | 512 | 661 | 810 |
| Frequency | 824.2 | 836.4 | 848.8 | 1850.2 | 1880.0 | 1909.8 |
| GSM | 32.42 | 32.48 | 32.45 | 29.14 | 29.11 | 29.15 |
| GPRS 8 | 32.41 | 32.47 | 32.44 | 29.11 | 29.08 | 29.11 |
| GPRS 10 | 31.74 | 31.80 | 31.79 | 28.31 | 28.27 | 28.32 |
| GPRS 11 | 30.11 | 30.16 | 30.15 | 26.75 | 26.74 | 26.79 |
| GPRS 12 | 29.13 | 29.19 | 29.18 | 25.97 | 26.02 | 26.08 |
| EGPRS 8 | 27.00 | 27.03 | 27.00 | 25.40 | 25.51 | 25.47 |
| EGPRS 10 | 25.60 | 25.60 | 25.65 | 24.18 | 24.25 | 24.30 |
| EGPRS 11 | 23.15 | 23.18 | 23.20 | 21.55 | 21.61 | 21.60 |
| EGPRS 12 | 21.91 | 22.00 | 22.02 | 20.23 | 20.31 | 20.31 |

| Conducted Power (*Unit: dBm) | | | | | | |
|------------------------------|--------------|-------|-------|---------------|--------|--------|
| Band | WCDMA Band V | | | WCDMA Band II | | |
| Channel | 4132 | 4182 | 4233 | 9262 | 9400 | 9538 |
| Frequency | 826.4 | 836.4 | 846.6 | 1852.4 | 1880.0 | 1907.6 |
| RMC 12.2Kbps | 22.82 | 22.64 | 22.90 | 22.69 | 22.57 | 22.32 |
| HSDPA Subtest-1 | 21.87 | 21.86 | 21.96 | 21.76 | 21.72 | 21.57 |
| HSDPA Subtest-2 | 21.85 | 21.83 | 21.92 | 21.67 | 21.63 | 21.45 |
| HSDPA Subtest-3 | 21.52 | 21.42 | 21.56 | 21.39 | 21.31 | 21.20 |
| HSDPA Subtest-4 | 21.46 | 21.38 | 21.49 | 21.28 | 21.27 | 21.08 |
| DC-HSDPA Subtest-1 | 21.56 | 21.67 | 21.14 | 22.11 | 21.95 | 21.50 |
| DC-HSDPA Subtest-2 | 21.51 | 21.64 | 21.13 | 22.10 | 21.93 | 21.48 |
| DC-HSDPA Subtest-3 | 21.23 | 21.25 | 20.73 | 21.62 | 21.49 | 21.06 |
| DC-HSDPA Subtest-4 | 21.21 | 21.24 | 20.72 | 21.60 | 21.48 | 21.01 |
| HSUPA Subtest-1 | 20.38 | 20.34 | 20.46 | 20.27 | 20.22 | 20.13 |
| HSUPA Subtest-2 | 19.24 | 19.19 | 19.32 | 19.15 | 19.09 | 19.00 |
| HSUPA Subtest-3 | 20.27 | 20.12 | 20.22 | 20.21 | 20.21 | 20.11 |
| HSUPA Subtest-4 | 19.25 | 19.26 | 19.23 | 19.21 | 19.13 | 18.99 |
| HSUPA Subtest-5 | 20.59 | 20.58 | 20.65 | 20.55 | 20.55 | 20.44 |
| HSPA+ (16QAM) Subtest-1 | 18.53 | 18.67 | 18.70 | 20.55 | 20.39 | 20.00 |

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1. | DC Power Supply | TOPWORD | 3303DR | N/A | N/A | Unshielded, 1.8 m |
| 2. | System Simulator | Agilent | E5515C | N/A | N/A | Unshielded, 1.8 m |

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

| Cellular Band | | | | | | | | | |
|-------------------------------|--------------|--------------|---------------|-----------------|--------------|---------------|-----------------------------|---------------|----------------|
| Modes | GSM850 (GSM) | | | GSM850 (EDGE 8) | | | WCDMA Band V (RMC 12.2Kbps) | | |
| Channel | 128 (Low) | 189 (Mid) | 251 (High) | 128 (Low) | 189 (Mid) | 251 (High) | 4132 (Low) | 4182 (Mid) | 4233 (High) |
| Frequency (MHz) | 824.2 | 836.4 | 848.8 | 824.2 | 836.4 | 848.8 | 826.4 | 836.4 | 846.6 |
| Conducted Power (dBm) | 32.42 | 32.48 | 32.45 | 27.00 | 27.04 | 27.00 | 22.83 | 22.65 | 22.91 |
| Conducted Power (Watts) | 1.75 | 1.77 | 1.76 | 0.50 | 0.51 | 0.50 | 0.19 | 0.18 | 0.20 |

| PCS Band | | | | | | | | | |
|-------------------------------|---------------|--------------|---------------|------------------|--------------|---------------|------------------------------|---------------|----------------|
| Modes | GSM1900 (GSM) | | | GSM1900 (EDGE 8) | | | WCDMA Band II (RMC 12.2Kbps) | | |
| Channel | 512 (Low) | 661 (Mid) | 810 (High) | 512 (Low) | 661 (Mid) | 810 (High) | 9262 (Low) | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 | 1852.4 | 1880 | 1907.6 |
| Conducted Power (dBm) | 29.14 | 29.11 | 29.15 | 25.40 | 25.52 | 25.48 | 22.69 | 22.57 | 22.32 |
| Conducted Power (Watts) | 0.82 | 0.81 | 0.82 | 0.35 | 0.36 | 0.35 | 0.19 | 0.18 | 0.17 |

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup




3.2.5 Test Result of Peak-to-Average Ratio

| PCS Band | | | | | | | | | |
|-------------------------------|---------------|--------------|---------------|------------------|--------------|---------------|---------------------------------|---------------|----------------|
| Modes | GSM1900 (GSM) | | | GSM1900 (EDGE 8) | | | WCDMA Band II (RMC 12.2Kbps) | | |
| Channel | 512 (Low) | 661 (Mid) | 810 (High) | 512 (Low) | 661 (Mid) | 810 (High) | 9262 (Low) | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 | 1852.4 | 1880 | 1907.6 |
| Peak-to-Average Ratio (dB) | 0.27 | 0.27 | 0.27 | 2.97 | 2.88 | 2.70 | 3.24 | 2.84 | 2.56 |


3.2.6 Test Result (Plots) of Peak-to-Average Ratio

| | | | |
|--------|----------|-------------|----------|
| Band : | GSM 1900 | Test Mode : | GSM Link |
|--------|----------|-------------|----------|

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 20.MAY.2013 03:14:40




| | | | |
|--------|----------|-------------|-------------|
| Band : | GSM 1900 | Test Mode : | EDGE 8 Link |
|--------|----------|-------------|-------------|

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Date: 20.MAY.2013 03:31:07

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 20.MAY.2013 03:34:36


Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 20.MAY.2013 03:31:37

| | | | |
|---------------|---------------|--------------------|-------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link |
|---------------|---------------|--------------------|-------------------|

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean 23.17 dBm
Peak 26.72 dBm
Crest 3.56 dB

10 % 1.96 dB
1 % 2.80 dB
.1 % 3.24 dB
.01 % 3.44 dB

Date: 19.MAY.2013 17:40:58

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean 22.86 dBm
Peak 25.95 dBm
Crest 3.09 dB

10 % 1.72 dB
1 % 2.44 dB
.1 % 2.84 dB
.01 % 3.00 dB

Date: 19.MAY.2013 17:37:57

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 19.MAY.2013 17:40:07

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

| GSM850 (GSM) Radiated Power ERP | | | | | | |
|--|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -19.22 | -48.12 | 0.00 | -1.08 | 27.82 | 0.6053 |
| 836.40 | -18.68 | -48.28 | 0.00 | -0.93 | 28.67 | 0.7362 |
| 848.80 | -18.41 | -48.35 | 0.00 | -0.76 | 29.18 | 0.8279 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -35.12 | -47.97 | 0.00 | -1.08 | 11.77 | 0.0150 |
| 836.40 | -34.05 | -48.01 | 0.00 | -0.93 | 13.03 | 0.0201 |
| 848.80 | -33.19 | -48.05 | 0.00 | -0.76 | 14.10 | 0.0257 |

| GSM850 (EDGE 8) Radiated Power ERP | | | | | | |
|---|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -25.33 | -48.12 | 0.00 | -1.08 | 21.71 | 0.1483 |
| 836.40 | -24.66 | -48.28 | 0.00 | -0.93 | 22.69 | 0.1858 |
| 848.80 | -24.48 | -48.35 | 0.00 | -0.76 | 23.11 | 0.2046 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.20 | -41.30 | -47.97 | 0.00 | -1.08 | 5.59 | 0.0036 |
| 836.40 | -40.17 | -48.01 | 0.00 | -0.93 | 6.91 | 0.0049 |
| 848.80 | -39.42 | -48.05 | 0.00 | -0.76 | 7.87 | 0.0061 |

| WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP | | | | | | |
|--|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40 | -28.25 | -48.12 | 0.00 | -1.08 | 18.79 | 0.0757 |
| 836.40 | -29.48 | -48.28 | 0.00 | -0.93 | 17.87 | 0.0612 |
| 846.60 | -27.65 | -48.35 | 0.00 | -0.76 | 19.94 | 0.0986 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 826.40 | -43.76 | -47.97 | 0.00 | -1.08 | 3.13 | 0.0021 |
| 836.40 | -44.79 | -48.01 | 0.00 | -0.93 | 2.29 | 0.0017 |
| 846.60 | -42.63 | -48.05 | 0.00 | -0.76 | 4.66 | 0.0029 |

3.3.6 Test Result of EIRP

| GSM1900 (GSM) Radiated Power EIRP | | | | | | |
|--|----------|----------|----------|----------|------------|----------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -23.84 | -51.88 | 0.00 | 1.96 | 30.00 | 1.0000 |
| 1880.00 | -25.03 | -52.99 | 0.00 | 2.00 | 29.96 | 0.9908 |
| 1909.80 | -25.47 | -54.28 | 0.00 | 1.98 | 30.79 | 1.1995 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -23.82 | -52.13 | 0.00 | 1.96 | 30.27 | 1.0641 |
| 1880.00 | -25.14 | -53.17 | 0.00 | 2.00 | 30.03 | 1.0069 |
| 1909.80 | -25.20 | -54.13 | 0.00 | 1.98 | 30.91 | 1.2331 |

| GSM1900 (EDGE 8) Radiated Power EIRP | | | | | | |
|---|----------|----------|----------|----------|------------|----------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -27.60 | -51.88 | 0.00 | 1.96 | 26.24 | 0.4207 |
| 1880.00 | -28.57 | -52.99 | 0.00 | 2.00 | 26.42 | 0.4385 |
| 1909.80 | -28.95 | -54.28 | 0.00 | 1.98 | 27.31 | 0.5383 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.20 | -27.47 | -52.13 | 0.00 | 1.96 | 26.62 | 0.4592 |
| 1880.00 | -28.37 | -53.17 | 0.00 | 2.00 | 26.80 | 0.4786 |
| 1909.80 | -28.47 | -54.13 | 0.00 | 1.98 | 27.64 | 0.5808 |

| WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP | | | | | | |
|---|---------------------|---------------------|---------------------|---------------------|-----------------------|---------------------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40 | -29.84 | -51.88 | 0.00 | 1.96 | 24.00 | 0.2512 |
| 1880.00 | -31.30 | -52.99 | 0.00 | 2.00 | 23.69 | 0.2339 |
| 1907.60 | -31.98 | -54.28 | 0.00 | 1.98 | 24.28 | 0.2679 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1852.40 | -29.78 | -52.13 | 0.00 | 1.96 | 24.31 | 0.2698 |
| 1880.00 | -31.30 | -53.17 | 0.00 | 2.00 | 23.87 | 0.2438 |
| 1907.60 | -31.53 | -54.13 | 0.00 | 1.98 | 24.58 | 0.2871 |

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

3.4.4 Test Setup



3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

| Cellular Band | | | | | | |
|-----------------|--------------|--------------|---------------|-----------------|--------------|---------------|
| Modes | GSM850 (GSM) | | | GSM850 (EDGE 8) | | |
| Channel | 128 (Low) | 189 (Mid) | 251 (High) | 128 (Low) | 189 (Mid) | 251 (High) |
| Frequency (MHz) | 824.2 | 836.4 | 848.8 | 824.2 | 836.4 | 848.8 |
| 99% OBW (KHz) | 248.00 | 244.00 | 244.00 | 244.00 | 244.00 | 244.00 |
| 26dB BW (KHz) | 316.00 | 316.00 | 318.00 | 300.00 | 306.00 | 304.00 |

| PCS Band | | | | | | |
|-----------------|---------------|--------------|---------------|------------------|--------------|---------------|
| Modes | GSM1900 (GSM) | | | GSM1900 (EDGE 8) | | |
| Channel | 512 (Low) | 661 (Mid) | 810 (High) | 512 (Low) | 661 (Mid) | 810 (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 | 1850.2 | 1880 | 1909.8 |
| 99% OBW (KHz) | 248.00 | 244.00 | 250.00 | 244.00 | 246.00 | 246.00 |
| 26dB BW (KHz) | 316.00 | 310.00 | 310.00 | 308.00 | 302.00 | 302.00 |


| Cellular Band | | | |
|-----------------|-----------------------------|------------|-------------|
| Modes | WCDMA Band V (RMC 12.2Kbps) | | |
| Channel | 4132 (Low) | 4182 (Mid) | 4233 (High) |
| Frequency (MHz) | 826.4 | 836.4 | 846.6 |
| 99% OBW (MHz) | 4.18 | 4.18 | 4.18 |
| 26dB BW (MHz) | 4.72 | 4.72 | 4.72 |

| PCS Band | | | |
|-----------------|------------------------------|------------|-------------|
| Modes | WCDMA Band II (RMC 12.2Kbps) | | |
| Channel | 9262 (Low) | 9400 (Mid) | 9538 (High) |
| Frequency (MHz) | 1852.4 | 1880 | 1907.6 |
| 99% OBW (MHz) | 4.16 | 4.16 | 4.20 |
| 26dB BW (MHz) | 4.70 | 4.72 | 4.72 |

3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


| | | | |
|---------------|---------|--------------------|----------|
| Band : | GSM 850 | Test Mode : | GSM Link |
|---------------|---------|--------------------|----------|

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 18.MAY.2013 19:10:05

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 18.MAY.2013 19:02:15

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 18.MAY.2013 19:09:00

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 18.MAY.2013 19:05:30

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 18.MAY.2013 19:07:28


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 18.MAY.2013 19:06:25


| | | | |
|--------|---------|-------------|-------------|
| Band : | GSM 850 | Test Mode : | EDGE 8 Link |
|--------|---------|-------------|-------------|

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 19.MAY.2013 15:27:40

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 19.MAY.2013 14:59:24

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 19.MAY.2013 15:15:55

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 19.MAY.2013 14:57:05

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 19.MAY.2013 15:08:34

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 19.MAY.2013 15:01:03




| | | | |
|--------|----------|-------------|----------|
| Band : | GSM 1900 | Test Mode : | GSM Link |
|--------|----------|-------------|----------|

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 18.MAY.2013 20:19:56

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 18.MAY.2013 20:13:32

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 18.MAY.2013 20:18:27

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 18.MAY.2013 20:12:31

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 18.MAY.2013 20:17:15

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 18.MAY.2013 20:15:35




| | | | |
|--------|----------|-------------|-------------|
| Band : | GSM 1900 | Test Mode : | EDGE 8 Link |
|--------|----------|-------------|-------------|

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 19.MAY.2013 19:13:52

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 19.MAY.2013 18:46:28

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 19.MAY.2013 19:06:40

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 19.MAY.2013 18:49:08

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 19.MAY.2013 18:53:53


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 19.MAY.2013 18:51:31


| | | | |
|--------|--------------|-------------|-------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link |
|--------|--------------|-------------|-------------------|

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 19.MAY.2013 18:06:12

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 19.MAY.2013 17:53:53

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 19.MAY.2013 18:03:43

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 19.MAY.2013 17:54:54

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 19.MAY.2013 17:58:10

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 19.MAY.2013 17:56:12




| | | | |
|--------|---------------|-------------|-------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link |
|--------|---------------|-------------|-------------------|

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 20.MAY.2013 11:11:29

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 20.MAY.2013 11:07:53

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 20.MAY.2013 11:10:24

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 20.MAY.2013 11:07:04

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 20.MAY.2013 11:09:35

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 20.MAY.2013 11:08:27

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

| | | | |
|----------------------------|-----------|---------------------------------|-----------|
| Band : | GSM850 | Test Mode : | GSM Link |
| Correction Factor : | 0.25dB | Maximum 26dB Bandwidth : | 0.318MHz |
| Band Edge : | -14.77dBm | Measurement Value : | -15.02dBm |

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 18.MAY.2013 18:56:15

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-15.02\text{dBm} + 0.25\text{dB} = -14.77\text{dBm}$

| | | | |
|----------------------------|-----------|---------------------------------|-----------|
| Band : | GSM850 | Test Mode : | GSM Link |
| Correction Factor : | 0.25dB | Maximum 26dB Bandwidth : | 0.318MHz |
| Band Edge : | -16.82dBm | Measurement Value : | -17.07dBm |


Higher Band Edge Plot on Channel 251 (848.8 MHz)



Date: 18.MAY.2013 18:57:42

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


| | | | |
|----------------------------|-----------|---------------------------------|-------------|
| Band : | GSM850 | Test Mode : | EDGE 8 Link |
| Correction Factor : | 0.09dB | Maximum 26dB Bandwidth : | 0.306MHz |
| Band Edge : | -20.12dBm | Measurement Value : | -20.21dBm |

Lower Band Edge Plot on Channel 128 (824.2 MHz)


Date: 19.MAY.2013 15:36:41

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


| | | | |
|----------------------------|-----------|---------------------------------|-------------|
| Band : | GSM850 | Test Mode : | EDGE 8 Link |
| Correction Factor : | 0.09dB | Maximum 26dB Bandwidth : | 0.306MHz |
| Band Edge : | -20.37dBm | Measurement Value : | -20.46dBm |

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 19.MAY.2013 15:38:32

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

| | | | |
|----------------------------|-----------|---------------------------------|-----------|
| Band : | GSM1900 | Test Mode : | GSM Link |
| Correction Factor : | 0.23dB | Maximum 26dB Bandwidth : | 0.316MHz |
| Band Edge : | -16.34dBm | Measurement Value : | -16.57dBm |


Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 18.MAY.2013 20:29:38

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

| | | | |
|----------------------------|-----------|---------------------------------|-----------|
| Band : | GSM1900 | Test Mode : | GSM Link |
| Correction Factor : | 0.23dB | Maximum 26dB Bandwidth : | 0.316MHz |
| Band Edge : | -19.05dBm | Measurement Value : | -19.28dBm |


Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 18.MAY.2013 20:28:19

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

| | | | |
|----------------------------|-----------|---------------------------------|-------------|
| Band : | GSM1900 | Test Mode : | EDGE 8 Link |
| Correction Factor : | 0.11dB | Maximum 26dB Bandwidth : | 0.308MHz |
| Band Edge : | -23.87dBm | Measurement Value : | -23.98dBm |


Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 19.MAY.2013 19:16:18

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

| | | | |
|----------------------------|-----------|---------------------------------|-------------|
| Band : | GSM1900 | Test Mode : | EDGE 8 Link |
| Correction Factor : | 0.11dB | Maximum 26dB Bandwidth : | 0.308MHz |
| Band Edge : | -24.11dBm | Measurement Value : | -24.22dBm |


Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 19.MAY.2013 19:22:41

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


| | | | |
|----------------------------|--------------|---------------------------------|-------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link |
| Correction Factor : | -3.26dB | Maximum 26dB Bandwidth : | 4.72MHz |
| Band Edge : | -25.87dBm | Measurement Value : | -22.61dBm |

Lower Band Edge Plot on Channel 4132 (826.4 MHz)


Date: 19.MAY.2013 18:09:53

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


| | | | |
|----------------------------|--------------|---------------------------------|-------------------|
| Band : | WCDMA Band V | Test Mode : | RMC 12.2Kbps Link |
| Correction Factor : | -3.26dB | Maximum 26dB Bandwidth : | 4.72MHz |
| Band Edge : | -24.80dBm | Measurement Value : | -21.54dBm |

Higher Band Edge Plot on Channel 4233 (846.6 MHz)


Date: 19.MAY.2013 18:13:02

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


| | | | |
|----------------------------|---------------|---------------------------------|-------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link |
| Correction Factor : | -3.26dB | Maximum 26dB Bandwidth : | 4.72MHz |
| Band Edge : | -24.58dBm | Measurement Value : | -21.32dBm |

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)


Date: 19.MAY.2013 17:18:24

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

| | | | |
|----------------------------|---------------|---------------------------------|-------------------|
| Band : | WCDMA Band II | Test Mode : | RMC 12.2Kbps Link |
| Correction Factor : | -3.26dB | Maximum 26dB Bandwidth : | 4.72MHz |
| Band Edge : | -24.24dBm | Measurement Value : | -20.98dBm |

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)


Date: 19.MAY.2013 17:23:00

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Spurious Emission


| | | | |
|--------------------|----------|--------------------|-----------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | GSM Link | Frequency : | 836.4 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 18.MAY.2013 19:16:17


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 18.MAY.2013 19:52:26


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 18.MAY.2013 19:44:57


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 18.MAY.2013 19:51:09

| | | | |
|--------------------|-------------|--------------------|-----------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | EDGE 8 Link | Frequency : | 836.4 MHz |


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 19.MAY.2013 15:44:31

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 19.MAY.2013 15:47:45

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 19.MAY.2013 15:51:04

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 19.MAY.2013 15:51:57


| | | | |
|--------------------|----------|--------------------|------------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | GSM Link | Frequency : | 1880.0 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 18.MAY.2013 20:03:41

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 18.MAY.2013 20:04:17


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 18.MAY.2013 19:59:47

Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 18.MAY.2013 20:00:28

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 18.MAY.2013 20:02:16


| | | | |
|--------------------|-------------|--------------------|------------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | EDGE 8 Link | Frequency : | 1880.0 MHz |

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 19.MAY.2013 16:29:43

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 19.MAY.2013 16:35:23


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 19.MAY.2013 19:29:32

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 19.MAY.2013 19:36:07

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 19.MAY.2013 16:24:20

| | | | |
|--------------------|-------------------|--------------------|-----------|
| Band : | WCDMA Band V | Channel : | CH4182 |
| Test Mode : | RMC 12.2Kbps Link | Frequency : | 836.4 MHz |


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 19.MAY.2013 18:17:21

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 19.MAY.2013 18:20:00

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 19.MAY.2013 18:21:00

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 19.MAY.2013 18:22:00

| | | | |
|--------------------|-------------------|--------------------|------------|
| Band : | WCDMA Band II | Channel : | CH9400 |
| Test Mode : | RMC 12.2Kbps Link | Frequency : | 1880.0 MHz |


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 19.MAY.2013 17:26:01

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 19.MAY.2013 17:28:12

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 19.MAY.2013 17:31:27

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 19.MAY.2013 17:32:42

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 19.MAY.2013 17:34:00

3.7 Field Strength of Spurious Radiated Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


3.7.6 Test Result of Field Strength of Spurious Radiated

| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM850 | Temperature : | 24~25°C |
| Test Mode : | GSM Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 1672 | -37.71 | -13 | -24.71 | -54.51 | -40.68 | 0.88 | 6.00 | H | Pass |
| 2510 | -45.18 | -13 | -32.18 | -68.14 | -47.79 | 1.08 | 5.84 | H | Pass |
| 3345 | -57.54 | -13 | -44.54 | -68.14 | -61.91 | 1.14 | 7.66 | H | Pass |
| 4182 | -54.26 | -13 | -41.26 | -69.02 | -59.53 | 1.37 | 8.79 | H | Pass |


| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM850 | Temperature : | 24~25°C |
| Test Mode : | GSM Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF EIRP V 130101 VERTICAL

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1672 | -35.10 | -13 | -22.10 | -49.13 | -38.07 | 0.88 | 6.00 | V | Pass |
| 2510 | -48.19 | -13 | -35.19 | -68.66 | -50.80 | 1.08 | 5.84 | V | Pass |
| 3345 | -54.03 | -13 | -41.03 | -65.86 | -58.40 | 1.14 | 7.66 | V | Pass |
| 4182 | -54.04 | -13 | -41.04 | -69.26 | -59.31 | 1.37 | 8.79 | V | Pass |


| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM850 | Temperature : | 24~25°C |
| Test Mode : | EDGE 8 Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL


| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1672 | -43.84 | -13 | -30.84 | -59.90 | -46.81 | 0.88 | 6.00 | H | Pass |
| 2510 | -44.10 | -13 | -31.10 | -67.49 | -46.71 | 1.08 | 5.84 | H | Pass |
| 3345 | -58.89 | -13 | -45.89 | -69.49 | -63.26 | 1.14 | 7.66 | H | Pass |
| 4182 | -54.11 | -13 | -41.11 | -68.87 | -59.38 | 1.37 | 8.79 | H | Pass |

| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM850 | Temperature : | 24~25°C |
| Test Mode : | EDGE 8 Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1672 | -36.11 | -13 | -23.11 | -50.13 | -39.08 | 0.88 | 6.00 | V | Pass |
| 2510 | -47.31 | -13 | -34.31 | -68.08 | -49.92 | 1.08 | 5.84 | V | Pass |
| 3345 | -55.25 | -13 | -42.25 | -67.08 | -59.62 | 1.14 | 7.66 | V | Pass |
| 4182 | -53.29 | -13 | -40.29 | -68.51 | -58.56 | 1.37 | 8.79 | V | Pass |


| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM1900 | Temperature : | 24~25°C |
| Test Mode : | GSM Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF_EIRP_H_130101 HORIZONTAL

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -59.07 | -13 | -46.07 | -71.22 | -59.07 | 1.28 | 8.02 | H | Pass |
| 5636 | -51.86 | -13 | -38.86 | -69.85 | -51.86 | 1.58 | 10.00 | H | Pass |
| 7520 | -50.26 | -13 | -37.26 | -72.2 | -50.26 | 1.78 | 12.10 | H | Pass |


| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 24~25°C |
| Test Mode : | GSM Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF EIRP V 130101 VERTICAL

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -55.17 | -13 | -42.17 | -70.2 | -55.17 | 1.28 | 8.02 | V | Pass |
| 5636 | -50.26 | -13 | -37.26 | -67.34 | -50.26 | 1.58 | 10.00 | V | Pass |
| 7520 | -49.75 | -13 | -36.75 | -72 | -49.75 | 1.78 | 12.10 | V | Pass |


| | | | |
|------------------------|--|----------------------------|------------|
| Band : | GSM1900 | Temperature : | 24~25°C |
| Test Mode : | EDGE 8 Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF ETRP H 130101 HORIZONTAL.

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -57.81 | -13 | -44.81 | -69.96 | -57.81 | 1.28 | 8.02 | H | Pass |
| 5636 | -53.09 | -13 | -40.09 | -71.08 | -53.09 | 1.58 | 10.00 | H | Pass |
| 7520 | -50.09 | -13 | -37.09 | -72.03 | -50.09 | 1.78 | 12.10 | H | Pass |


| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 24~25°C |
| Test Mode : | EDGE 8 Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF EIRP V 130101 VERTICAL


| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -55.39 | -13 | -42.39 | -70.42 | -55.39 | 1.28 | 8.02 | V | Pass |
| 5636 | -53.96 | -13 | -40.96 | -71.04 | -53.96 | 1.58 | 10.00 | V | Pass |
| 7520 | -49.98 | -13 | -36.98 | -72.23 | -49.98 | 1.78 | 12.10 | V | Pass |

| | | | |
|------------------------|--|----------------------------|------------|
| Band : | WCDMA Band V | Temperature : | 24~25°C |
| Test Mode : | RMC 12.2Kbps Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1672 | -52.97 | -13 | -39.97 | -66.52 | -55.94 | 0.88 | 6.00 | H | Pass |
| 2510 | -47.36 | -13 | -34.36 | -69.77 | -49.97 | 1.08 | 5.84 | H | Pass |
| 3345 | -57.95 | -13 | -44.95 | -68.55 | -62.32 | 1.14 | 7.66 | H | Pass |
| 4182 | -54.86 | -13 | -41.86 | -69.62 | -60.13 | 1.37 | 8.79 | H | Pass |

| | | | |
|------------------------|--|----------------------------|----------|
| Band : | WCDMA Band V | Temperature : | 24~25°C |
| Test Mode : | RMC 12.2Kbps Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 1672 | -53.87 | -13 | -40.87 | -65.29 | -56.84 | 0.88 | 6.00 | V | Pass |
| 2510 | -50.10 | -13 | -37.10 | -69.96 | -52.71 | 1.08 | 5.84 | V | Pass |
| 3345 | -57.57 | -13 | -44.57 | -69.40 | -61.94 | 1.14 | 7.66 | V | Pass |
| 4182 | -54.02 | -13 | -41.02 | -69.24 | -59.29 | 1.37 | 8.79 | V | Pass |


| | | | |
|------------------------|--|----------------------------|------------|
| Band : | WCDMA Band II | Temperature : | 24~25°C |
| Test Mode : | RMC 12.2Kbps Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF EIRP H 130101 HORIZONTAL

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3756 | -50.94 | -13 | -37.94 | -63.76 | -52.83 | 1.28 | 8.02 | H | Pass |
| 5640 | -53.40 | -13 | -40.40 | -71.39 | -53.4 | 1.58 | 10.00 | H | Pass |
| 7520 | -50.40 | -13 | -37.40 | -72.34 | -50.4 | 1.78 | 12.10 | H | Pass |

| | | | |
|------------------------|--|----------------------------|----------|
| Band : | WCDMA Band II | Temperature : | 24~25°C |
| Test Mode : | RMC 12.2Kbps Link + USB Cable (Charging from Adapter) + Earphone + SIM 1 | Relative Humidity : | 54~56% |
| Test Engineer : | John Zheng | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-SZ
Condition : -13DBM HF EIRP V 130101 VERTICAL

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|-------------------------|--------------------------|----------------------------|-----------------------------|-----------------------|--------|
| 3760 | -50.54 | -13 | -37.54 | -65.57 | -50.54 | 1.28 | 8.02 | V | Pass |
| 5640 | -53.38 | -13 | -40.38 | -70.46 | -53.38 | 1.58 | 10.00 | V | Pass |
| 7520 | -50.54 | -13 | -37.54 | -72.79 | -50.54 | 1.78 | 12.10 | V | Pass |

3.8 Frequency Stability for Temperature and Voltage Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

| | | | |
|----------------------|---------|--------------------|-----------|
| Band : | GSM 850 | Channel : | 189 |
| Limit (ppm) : | 2.5 | Frequency : | 836.4 MHz |

| Temperature (°C) | GSM | | EDGE 8 | | Result |
|------------------|-----------------|-----------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | 15 | 0.02 | 12 | 0.01 | PASS |
| -20 | 13 | 0.02 | 12 | 0.01 | |
| -10 | 14 | 0.02 | 11 | 0.01 | |
| 0 | 13 | 0.02 | 10 | 0.01 | |
| 10 | 12 | 0.01 | 9 | 0.01 | |
| 20 | 8 | 0.01 | 8 | 0.01 | |
| 30 | 10 | 0.01 | 10 | 0.01 | |
| 40 | 13 | 0.02 | 9 | 0.01 | |
| 50 | 15 | 0.02 | 11 | 0.01 | |
| 55 | 16 | 0.02 | 13 | 0.02 | |

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

| | | | |
|----------------------|----------|--------------------|------------|
| Band : | GSM 1900 | Channel : | 661 |
| Limit (ppm) : | 2.5 | Frequency : | 1880.0 MHz |

| Temperature (°C) | GSM | | EDGE 8 | | Result |
|------------------|-----------------|-----------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -26 | -0.01 | 38 | 0.02 | PASS |
| -20 | -25 | -0.01 | 35 | 0.02 | |
| -10 | -23 | -0.01 | 36 | 0.02 | |
| 0 | -22 | -0.01 | 29 | 0.02 | |
| 10 | -23 | -0.01 | 25 | 0.01 | |
| 20 | -19 | -0.01 | 21 | 0.01 | |
| 30 | -21 | -0.01 | 25 | 0.01 | |
| 40 | -22 | -0.01 | 27 | 0.01 | |
| 50 | -19 | -0.01 | 24 | 0.01 | |
| 55 | -22 | -0.01 | 28 | 0.01 | |

| | | | |
|----------------------|--------------|--------------------|-----------|
| Band : | WCDMA Band V | Channel : | 4182 |
| Limit (ppm) : | 2.5 | Frequency : | 836.4 MHz |

| Temperature (°C) | RMC 12.2Kbps | | Result |
|------------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | 16 | 0.02 | PASS |
| -20 | 15 | 0.02 | |
| -10 | 13 | 0.02 | |
| 0 | 14 | 0.02 | |
| 10 | 12 | 0.01 | |
| 20 | 11 | 0.01 | |
| 30 | 11 | 0.01 | |
| 40 | 10 | 0.01 | |
| 50 | 11 | 0.01 | |
| 55 | 13 | 0.02 | |

| | | | |
|----------------------|---------------|--------------------|------------|
| Band : | WCDMA Band II | Channel : | 9400 |
| Limit (ppm) : | 2.5 | Frequency : | 1880.0 MHz |

| Temperature (°C) | RMC 12.2Kbps | | Result |
|------------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | 22 | 0.01 | PASS |
| -20 | 20 | 0.01 | |
| -10 | 21 | 0.01 | |
| 0 | 20 | 0.01 | |
| 10 | 18 | 0.01 | |
| 20 | 19 | 0.01 | |
| 30 | 20 | 0.01 | |
| 40 | 19 | 0.01 | |
| 50 | 20 | 0.01 | |
| 55 | 18 | 0.01 | |

3.8.7 Test Result of Voltage Variation

| Band & Channel | Mode | Voltage (Volt) | Freq. Dev. (Hz) | Deviation (ppm) | Limit (ppm) | Result |
|-------------------------|-----------------|----------------|-----------------|-----------------|-------------|--------|
| GSM 850 CH189 | GSM | 3.7 | 8 | 0.01 | 2.5 | PASS |
| | | BEP | 9 | 0.01 | | |
| | | 4.2 | 11 | 0.01 | | |
| | EDGE 8 | 3.7 | 9 | 0.01 | | |
| | | BEP | 9 | 0.01 | | |
| | | 4.2 | 11 | 0.01 | | |
| GSM 1900 CH661 | GSM | 3.7 | -19 | -0.01 | | |
| | | BEP | -18 | -0.01 | | |
| | | 4.2 | -20 | -0.01 | | |
| | EDGE 8 | 3.7 | 21 | 0.01 | | |
| | | BEP | 22 | 0.01 | | |
| | | 4.2 | 25 | 0.01 | | |
| WCDMA Band V CH4182 | RMC 12.2Kbps | 3.7 | 11 | 0.01 | | |
| | | BEP | 11 | 0.01 | | |
| | | 4.2 | 12 | 0.01 | | |
| WCDMA Band II CH9400 | RMC 12.2Kbps | 3.7 | 19 | 0.01 | | |
| | | BEP | 20 | 0.01 | | |
| | | 4.2 | 19 | 0.01 | | |

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.

4 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---------------------------|--------------|-----------|-----------------|----------------------|------------------|-------------------------------|---------------|-----------------------|
| Spectrum Analyzer | R&S | FSP30 | 101400 | 9kHz~30GHz | Mar. 28, 2013 | May 18, 2013~ May 20, 2013 | Mar. 27, 2014 | Conducted (TH01-SZ) |
| System Simulator | Agilent | E5515C | MY50264168 | GSM/WCDMA /CDMA2000 | Oct. 09, 2012 | May 18, 2013~ May 20, 2013 | Oct. 08, 2013 | Conducted (TH01-SZ) |
| DC Power Supply | TOPWORD | 3303DR | N/A714621 | N/A | Mar. 28, 2013 | May 18, 2013~ May 20, 2013 | Mar. 27, 2014 | Conducted (TH01-SZ) |
| Thermal Chamber | Hongzhan | LP-150U | HD20120425 | N/A | Mar. 28, 2013 | May 18, 2013~ May 20, 2013 | Mar. 27, 2014 | Conducted (TH01-SZ) |
| ESCI TEST Receiver | R&S | ESCI | 100724 | 9K-3GHz | Mar. 28, 2013 | May 30, 2013 | Mar. 27, 2014 | Radiation (03CH01-SZ) |
| Spectrum Analyzer | R&S | FSP30 | 101362 | 9kHz~30GHz | Oct. 11, 2012 | May 30, 2013 | Oct. 10, 2013 | Radiation (03CH01-SZ) |
| Bilog Antenna | SCHAFFNER | CBL6112B | 2614 | 30Mhz~2Ghz | Nov. 03, 2012 | May 30, 2013 | Nov. 02, 2013 | Radiation (03CH01-SZ) |
| Double Ridge Horn Antenna | ETS Lindgren | 3117 | 00119436 | 1GHz~18GHz | Oct. 12, 2012 | May 30, 2013 | Oct. 11, 2013 | Radiation (03CH01-SZ) |
| Amplifier | ADVANTEST | BB525C | E9007003 | 9K-3000MHz GAIN 30db | Mar. 28, 2013 | May 30, 2013 | Mar. 27, 2014 | Radiation (03CH01-SZ) |
| Amplifier | Yiai | AV3860B | 04030 | 2GHz~26.5GHz | Mar. 28, 2013 | May 30, 2013 | Mar. 27, 2014 | Radiation (03CH01-SZ) |
| SHF-EHF-Horn | Schwarzbeck | BBHA9170 | BBHA917024 g | 14Ghz~40Ghz | Nov. 23, 2012 | May 30, 2013 | Nov. 22, 2013 | Radiation (03CH01-SZ) |
| HFH2-Z2 Loop Antenna | R&S | HFH2-Z2 | 100321 | 9KHZ-30MHZ | Oct. 22, 2012 | May 30, 2013 | Oct. 21, 2013 | Radiation (03CH01-SZ) |
| System Simulator | Agilent | E5515C | MY50264168 | GSM/WCDMA /CDMA2000 | Oct. 09, 2012 | May 30, 2013 | Oct. 08, 2013 | Radiation (03CH01-SZ) |

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|--|------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 2.54 |
|--|------|

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

| | |
|---|------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 4.72 |
|---|------|



Appendix A. Photographs of EUT

Please refer to Sporton report number EP350801 as below.