UMTS-FDD Band II   (Part 24E)

Band II - Low Channel-1

Band II - Low Channel-2

Band II - Middle Channel-1

Band II - Middle Channel-2

Band II - High Channel-1

Band II - High Channel-2

UMTS-FDD Band IV (Part 27)

Band IV - Low Channel-1

Band IV - Low Channel-2

Band IV - Middle Channel-1

Band IV - Middle Channel-2

Band IV - High Channel-1

Band IV - High Channel-2

HSUPA:

UMTS-FDD Band V (Part 22H)

Band V - Low Channel-1

Band V - Low Channel-2

Band V - Middle Channel-1

Band V - Middle Channel-2

Band V - High Channel-1

Band V - High Channel-2

UMTS-FDD Band II   (Part 24E)

Band II - Low Channel-1

Band II - Low Channel-2

Band II - Middle Channel-1

Band II - Middle Channel-2

Band II - High Channel-1

Band II - High Channel-2

UMTS-FDD Band IV (Part 27)

Band IV - Low Channel-1

Band IV - Low Channel-2

Band IV - Middle Channel-1

Band IV - Middle Channel-2

Band IV - High Channel-1

Band IV - High Channel-2

HSDPA:

**UMTS-FDD Band V (Part 22H)**


Band V - Low Channel-1

Band V - Low Channel-2

Band V - Middle Channel-1

Band V - Middle Channel-2

Band V - High Channel-1

Band V - High Channel-2

UMTS-FDD Band II (Part 24E)

Band II - Low Channel-1

Band II - Low Channel-2

Band II - Middle Channel-1

Band II - Middle Channel-2

Band II - High Channel-1

Band II - High Channel-2

UMTS-FDD Band IV (Part 27)

Band IV - Low Channel-1

Band IV - Low Channel-2

Band IV - Middle Channel-1

Band IV - Middle Channel-2

Band IV - High Channel-1

Band IV - High Channel-2

## 6.6 Spurious Radiated Emissions

Temperature	25 ºC
Relative Humidity	50%
Atmospheric Pressure	1008mbar
Test date :	August 08, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☑
Test setup			
Test Procedure		1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBµV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)	

Remark	
Result	☑ Pass ☐ Fail

Test Data ☑Yes   ☐N/A

Test Plot ☐Yes (See below) ☑N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.42	V	7.95	0.78	-36.25	-13	-23.25
1648.4	-44.58	H	7.95	0.78	-37.41	-13	-24.41
325.7	-53.39	V	6.4	0.26	-47.25	-13	-34.25
605.2	-51.39	H	6.8	0.37	-44.96	-13	-31.96

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-41.77	V	7.95	0.78	-34.6	-13	-21.6
1673.2	-44.46	H	7.95	0.78	-37.29	-13	-24.29
327	-54.43	V	6.4	0.26	-48.29	-13	-35.29
611.5	-52.72	H	6.8	0.37	-46.29	-13	-33.29

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-42.91	V	7.95	0.78	-35.74	-13	-22.74
1697.6	-44.07	H	7.95	0.78	-36.9	-13	-23.9
316.9	-51.41	V	6.4	0.26	-45.27	-13	-32.27
605.8	-53.94	H	6.8	0.37	-47.51	-13	-34.51

Note:

*1, The testing has been conformed to 10*848.8MHz=8,488MHz*
2, All other emissions more than 30 dB below the limit
3,GSM voice , GPRS and EGPRS mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-50.14	V	10.25	2.73	-42.62	-13	-29.62
3700.4	-48.98	H	10.25	2.73	-41.46	-13	-28.46
326.1	-53.38	V	6.4	0.26	-47.24	-13	-34.24
597.1	-52.83	H	6.8	0.37	-46.4	-13	-33.4

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-47.03	V	10.25	2.73	-39.51	-13	-26.51
3760	-49.93	H	10.25	2.73	-42.41	-13	-29.41
332	-53.75	V	6.4	0.26	-47.61	-13	-34.61
606.9	-53.98	H	6.8	0.37	-47.55	-13	-34.55

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.21	V	10.36	2.73	-40.58	-13	-27.58
3819.6	-47.06	H	10.36	2.73	-39.43	-13	-26.43
328	-55.17	V	6.4	0.26	-49.03	-13	-36.03
605.9	-51.83	H	6.8	0.37	-45.4	-13	-32.4

Note:

1, The testing has been conformed to 10*1909.8MHz=19,098MHz

2, All other emissions more than 30 dB below the limit

3,GSM voice , GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.39	V	7.95	0.78	-39.22	-13	-26.22
1652.8	-47.33	H	7.95	0.78	-40.16	-13	-27.16
324.5	-51.35	V	6.4	0.26	-45.21	-13	-32.21
600.6	-52.67	H	6.8	0.37	-46.24	-13	-33.24

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-44.5	V	7.95	0.78	-37.33	-13	-24.33
1670	-46.85	H	7.95	0.78	-39.68	-13	-26.68
327.7	-52.42	V	6.4	0.26	-46.28	-13	-33.28
601	-52.65	H	6.8	0.37	-46.22	-13	-33.22

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-48.77	V	7.95	0.78	-41.6	-13	-28.6
1693.2	-47.49	H	7.95	0.78	-40.32	-13	-27.32
327.3	-54.02	V	6.4	0.26	-47.88	-13	-34.88
602	-51.67	H	6.8	0.37	-45.24	-13	-32.24

Note:

1, The testing has been conformed to 10*846.6MHz=8,466MHz
2, All other emissions more than 30 dB below the limit
3,RMC , HSUPA and HSDPA mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band II   (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-50.58	V	10.25	2.73	-43.06	-13	-30.06
3704.8	-48.46	H	10.25	2.73	-40.94	-13	-27.94
326.5	-53.57	V	6.4	0.26	-47.43	-13	-34.43
609.9	-54.72	H	6.8	0.37	-48.29	-13	-35.29

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-50.21	V	10.25	2.73	-42.69	-13	-29.69
3760	-51.36	H	10.25	2.73	-43.84	-13	-30.84
328.3	-52.21	V	6.4	0.26	-46.07	-13	-33.07
609.7	-52.56	H	6.8	0.37	-46.13	-13	-33.13

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.59	V	10.36	2.73	-40.96	-13	-27.96
3815.2	-50.58	H	10.36	2.73	-42.95	-13	-29.95
329.6	-54.74	V	6.4	0.26	-48.6	-13	-35.6
601.5	-52.66	H	6.8	0.37	-46.23	-13	-33.23

Note:

1, The testing has been conformed to 10*1907.6MHz=19,076MHz
2, All other emissions more than 30 dB below the limit
3,RMC , HSUPA and HSDPA mode were investigated. The results above show only the worse cases
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.15	V	10.07	0.96	-37.04	-13	-24.04
3424.8	-47.45	H	10.07	0.96	-38.34	-13	-25.34
322.7	-58.15	V	6.4	0.26	-52.01	-13	-39.01
742.9	-53.09	H	7.1	0.42	-46.41	-13	-33.41

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-46.06	V	10.09	0.96	-36.93	-13	-23.93
3480	-46.72	H	10.09	0.96	-37.59	-13	-24.59
323.6	-56.41	V	6.4	0.26	-50.27	-13	-37.27
740.4	-52.58	H	7.1	0.42	-45.9	-13	-32.9

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-47.01	V	10.09	0.97	-37.89	-13	-24.89
3505.2	-45.75	H	10.09	0.97	-36.63	-13	-23.63
318.6	-56.63	V	6.4	0.26	-50.49	-13	-37.49
730.8	-51.06	H	7.1	0.42	-44.38	-13	-31.38

Note:

*1, The testing has been conformed to 10*1752.6MHz=17,526MHz*
2, All other emissions more than 30 dB below the limit
3,RMC , HSUPA and HSDPA mode were investigated. The results above show only the worse cases.
4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

6.7 Band Edge

Temperature	25 °C
Relative Humidity	55%
Atmospheric Pressure	1012mbar
Test date :	July 10, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.	☑
Test setup		Base Station　　Spectrum Analyzer　　EUT	
Procedure		- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.	
Remark			
Result		☑ Pass　　☐ Fail	

Test Data　☑ Yes　　☐ N/A

Test Plot　☑ Yes (See below)　　☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.977	-16.865	-13
849.003	-15.316	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.995	-17.130	-13
1910.004	-16.973	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.997	-16.706	-13
849.020	-17.264	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.994	-16.542	-13
1910.018	-17.709	-13

EGPRS (MCS5):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.996	-17.897	-13
849.020	-17.485	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.996	-17.827	-13
1910.016	-16.390	-13

RCM:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.70	-33.707	-13
849.06	-27.040	-13

UMTS-FDD Band II   (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.70	-31.089	-13
1910.26	-30.226	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.69	-31.949	-13
1755.27	-29.914	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.73	-33.227	-13
849.27	-26.050	-13

UMTS-FDD Band II   (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.88	-30.350	-13
1910.27	-29.998	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1708.71	-32.237	-13
1755.22	-33.045	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.67	-34.840	-13
849.27	-25.254	-13

UMTS-FDD Band II   (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.69	-29.350	-13
1910.51	-29.950	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.99	-31.109	-13
1756.19	-31.527	-13

GSM Voice:

Test Plots

Cellular Band - Low Channel

Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log

(3.20/3)=4.0+0.3=4.3dB

Note: Offset=Cable loss (4.0) + 10log

(3.11/3)=4.0+0.2=4.2dB

PCS Band - Low Channel

PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log

(3.11/3)=4.5+0.2=4.7dB

Note: Offset=Cable loss (4.0) + 10log

(3.16/3)=4.5+0.2=4.7dB

GPRS:

Test Plots

Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log

(3.22/3)=4.0+0.3=4.3dB

Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log

(3.16/3)=4.0+0.2=4.2dB

PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log

(3.16/3)=4.5+0.2=4.7dB

PCS Band - High Channel

Note: Offset=Cable loss (4.5) + 10log

(3.14/3)=4.5+0.2=4.7dB

EGPRS (MCS5):

Test Plots

Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log

(3.11/3)=4.0+0.2=4.2dB

Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log

(3.10/3)=4.0+0.2=4.2dB

PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log

(3.21/3)=4.5+0.3=4.8dB

PCS Band - High Channel

Note: Offset=Cable loss (4.5) + 10log

(3.11/3)=4.5+0.2=4.7dB

RMC:

UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log (46.71/30)=4.0+1.9=5.9 dB

UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log (46.93/30)=4.0+1.9=5.9dB

UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log (46.88/30)=4.5+1.9=6.4 dB

UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log (47.10/30)=4.5+2.0=6.5 dB

UMTS-FDD Band IV - Low Channel	UMTS-FDD Band IV - High Channel
Note: Offset=Cable loss (4.5) + 10log (46.86/30)=4.5+1.9=6.4dB	Note: Offset=Cable loss (4.0) + 10log (46.76/30)=4.5+1.9=6.4dB

HSUPA:

UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log

(46.84/30)=4.0+1.9=5.9 dB

UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log

(46.81/30)=4.0+1.9=5.9 dB

UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log

(46.69/30)=4.5+1.9=6.4 dB

UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log

(47.21/30)=4.5+2.0=6.5dB

UMTS-FDD Band IV - Low Channel	UMTS-FDD Band IV - High Channel
Note: Offset=Cable loss (4.5) + 10log (46.63/30)=4.5+1.9=6.4dB	Note: Offset=Cable loss (4.5) + 10log (46.81/30)=4.5+1.9=6.4dB

HSDPA:

UMTS-FDD Band V - Low Channel

UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log

(46.59/30)=4.0+1.9=5.9dB

Note: Offset=Cable loss (4.0) + 10log

(46.85/30)=4.0+1.9=5.9 dB

UMTS-FDD Band II - Low Channel

UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log

(47.06/30)=4.5+2.0=6.5dB

Note: Offset=Cable loss (4.5) + 10log

(46.91/30)=4.5+1.9=6.4 dB