


# FCC Test Report


APPLICANT : CT Asia  
EQUIPMENT : Mobile phone  
BRAND NAME : BLU  
MODEL NAME : Janet L  
FCC ID : YHLBLUJANETL  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification

The product was received on Aug. 27, 2014 and testing was completed on Sep. 24, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2003 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



---

Reviewed by: Louis Wu / Manager

---

Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL (SHENZHEN) INC.**

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District,  
Shenzhen, Guangdong, P.R.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Feature of Equipment Under Test.....	5
1.4. Product Specification of Equipment Under Test .....	5
1.5. Modification of EUT .....	6
1.6. Test Site .....	6
1.7. Applied Standards .....	6
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
2.1. Test Mode .....	7
2.2. Connection Diagram of Test System .....	9
2.3. Support Unit used in test configuration and system.....	10
2.4. EUT Operation Test Setup .....	11
<b>3. TEST RESULT .....</b>	<b>12</b>
3.1. Test of AC Conducted Emission Measurement .....	12
3.2. Test of Radiated Emission Measurement .....	18
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>22</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>23</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC482701	Rev. 01	Initial issue of report	Oct. 16, 2014



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 12.33 dB at 3.700 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 0.88 dB at 300.000 MHz for Quasi-Peak

## 1. General Description

### 1.1. Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

### 1.2. Manufacturer

Tinno Mobile Technology Corp.

4/F, H-3 Building, OCT Eastern industrial Park, No.1 XiangShan East Road., Nan Shan District, Shenzhen, P.R.China

### 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	Janet L
FCC ID	YHLBLUJANETL
EUT supports Radios application	GSM/Bluetooth v3.0 + EDR
HW Version	V1.0
SW Version	BLU_Tornado_V02_Generic
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4. Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900 : 1850.2 MHz ~ 1909.8MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850 : 869.2 MHz ~ 893.8 MHz GSM1900 : 1930.2 MHz ~ 1989.8 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Antenna Type	WWAN : IFA Antenna Bluetooth : IFA Antenna
Type of Modulation	GSM: GMSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK

## 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6. Test Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.		FCC Registration No.
	CO01-SZ	03CH01-SZ	831040

## 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	Note 1
2.	Data application transferred mode (EUT connected with notebook)	☒	☒	☒

**Abbreviations:**

- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz


**Note 1:** Testing for this mode is not required or not the worst case.

**Remark:** For signal above 1GHz, the worst case was test item 2.


Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + Camera + SIM 1<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + MP3 + SIM 1<Fig.1> Mode 3: GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1<Fig.2>
Radiated Emissions < 1GHz	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + Camera + SIM 1<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + MP3 + SIM 1<Fig.1> Mode 3: GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1<Fig.2>
Radiated Emissions ≥ 1GHz	2	Mode 1: GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1<Fig.2>
<b>Remark:</b> <ol style="list-style-type: none"> <li>The worst case of AC is mode 2, and the USB Link mode of AC is mode 3, the test data of these modes are reported.</li> <li>The worst case of RE &lt; 1G is mode 3; only the test data of this mode was reported.</li> <li>Link with notebook means data application transferred mode between EUT and notebook.</li> </ol>		



## 2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>

## 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Agilent	8960	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
4.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
5.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2m DC O/P: Shielded, 1.8 m
6.	iPod	Apple	MC690 ZP/A	FCC DoC	Shielded, 1.2 m	N/A

## **2.4. EUT Operation Test Setup**

The EUT was in GSM idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone, and the following programs installed in the EUT were programmed during the test.

1. Execute the program, "Winthrax" under WIN7 installed in notebook for files transfer with EUT via USB cable.
2. Execute "Music Player" to play MP3 file.
3. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test Setup






## 3.1.5 Test Result of AC Conducted Emission





Test Mode :	Mode 2	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + MP3 + SIM 1		




Site : C001-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC)482701  
Mode : Mode 2  
IMEI : 353919026914295/353924026850598

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	2.42	30.39	-15.61	46.00	19.79	0.40	10.20	Average
2	2.42	39.49	-16.51	56.00	28.89	0.40	10.20	QP
3	2.61	30.31	-15.69	46.00	19.70	0.41	10.20	Average
4	2.61	39.41	-16.59	56.00	28.80	0.41	10.20	QP
5	3.03	32.34	-13.66	46.00	21.71	0.42	10.21	Average
6	3.03	41.64	-14.36	56.00	31.01	0.42	10.21	QP
7	3.22	32.95	-13.05	46.00	22.30	0.43	10.22	Average
8	3.22	42.05	-13.95	56.00	31.40	0.43	10.22	QP
9 *	3.70	33.67	-12.33	46.00	23.00	0.45	10.22	Average
10	3.70	42.37	-13.63	56.00	31.70	0.45	10.22	QP
11	4.09	31.99	-14.01	46.00	21.30	0.46	10.23	Average
12	4.09	40.99	-15.01	56.00	30.30	0.46	10.23	QP
13	4.55	30.51	-15.49	46.00	19.80	0.48	10.23	Average
14	4.55	39.61	-16.39	56.00	28.90	0.48	10.23	QP
15	4.93	29.03	-16.97	46.00	18.30	0.49	10.24	Average
16	4.93	38.13	-17.87	56.00	27.40	0.49	10.24	QP



Test Mode :	Mode 3	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1		




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_L\_20140304 LINE  
Project : (FC)482701  
Mode : Mode 3  
IMEI : 353919026914295/353924026850598

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	21.47	-34.00	55.47	10.90	0.22	10.35	Average
2	0.16	41.17	-24.30	65.47	30.60	0.22	10.35	QP
3	0.17	22.54	-32.18	54.72	12.00	0.22	10.32	Average
4	0.17	39.04	-25.68	64.72	28.50	0.22	10.32	QP
5	0.19	24.22	-29.62	53.84	13.70	0.22	10.30	Average
6 *	0.19	42.22	-21.62	63.84	31.70	0.22	10.30	QP
7	0.21	22.11	-30.99	53.10	11.60	0.23	10.28	Average
8	0.21	37.51	-25.59	63.10	27.00	0.23	10.28	QP
9	0.27	20.67	-30.36	51.03	10.20	0.25	10.22	Average
10	0.27	32.37	-28.66	61.03	21.90	0.25	10.22	QP
11	0.31	20.66	-29.36	50.02	10.20	0.26	10.20	Average
12	0.31	31.66	-28.36	60.02	21.20	0.26	10.20	QP





Test Mode :	Mode 3	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1		



Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC) 482701  
Mode : Mode 3  
IMEI : 353919026914295/353924026850598

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	18.87	-36.60	55.47	8.19	0.33	10.35	Average
2 *	0.16	43.97	-21.50	65.47	33.29	0.33	10.35	QP
3	0.17	19.45	-35.45	54.90	8.79	0.33	10.33	Average
4	0.17	38.65	-26.25	64.90	27.99	0.33	10.33	QP
5	0.19	18.83	-35.15	53.98	8.21	0.32	10.30	Average
6	0.19	36.13	-27.85	63.98	25.51	0.32	10.30	QP
7	0.21	15.21	-38.06	53.27	4.61	0.32	10.28	Average
8	0.21	34.61	-28.66	63.27	24.01	0.32	10.28	QP
9	0.25	18.79	-32.99	51.78	8.21	0.34	10.24	Average
10	0.25	38.69	-23.09	61.78	28.11	0.34	10.24	QP
11	5.42	27.73	-22.27	50.00	17.00	0.48	10.25	Average
12	5.42	31.93	-28.07	60.00	21.20	0.48	10.25	QP

## **3.2. Test of Radiated Emission Measurement**

### **3.2.1. Limit of Radiated Emission**

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<b>Frequency (MHz)</b>	<b>Field Strength (microvolts/meter)</b>	<b>Measurement Distance (meters)</b>
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### **3.2.2. Measuring Instruments**


The measuring equipment is listed in the section 4 of this test report.

### **3.2.3. Test Procedures**


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





## 3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	23~25°C
Test Engineer :	Kaer Huang	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1		




Site : 03CH01-SZ  
Condition : FCC CLASS-B 3m LF\_ANT\_131026 HORIZONTAL  
Project : (FC) 482701  
Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 P	72.12	35.36	-4.64	40.00	59.45	4.63	1.21	29.93	---	Peak
2 !	240.06	43.56	-2.44	46.00	59.88	11.35	2.26	29.93	253	35 QP
3 Q	300.00	45.12	-0.88	46.00	60.23	12.30	2.52	29.93	125	45 QP
4 !	323.80	44.49	-1.51	46.00	58.02	13.78	2.62	29.93	125	87 QP
5	407.80	39.34	-6.66	46.00	50.06	16.26	2.94	29.92	---	Peak
6	624.10	36.53	-9.47	46.00	44.07	18.60	3.78	29.92	---	Peak
7	2978.00	27.29	-46.71	74.00	29.74	32.97	10.95	46.37	---	Peak
8	4998.00	32.88	-41.12	74.00	31.81	34.20	13.00	46.13	---	Peak
9	6528.00	36.54	-37.46	74.00	34.67	33.99	14.82	46.94	---	Peak
10	8996.00	39.11	-34.89	74.00	32.63	36.38	16.07	45.97	---	Peak
11	9948.00	43.31	-30.69	74.00	35.62	36.93	17.60	46.84	---	Peak
12	12582.00	43.22	-30.78	74.00	35.52	38.05	18.86	49.21	---	Peak



Test Mode :	Mode 3	Temperature :	23~25°C
Test Engineer :	Kaer Huang	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Vertical
Function Type :	GSM850 Idle + USB Cable (Data Link with Notebook) + Bluetooth Idle + SIM 1		



Site : 03CH01-SZ  
Condition : FCC CLASS-B 3m LF\_ANT\_131026 VERTICAL  
Project : (FC) 482701  
Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	167.97	38.95	-4.55	43.50	58.44	8.58	1.87	29.94	---	---	Peak
2	204.15	29.12	-14.38	43.50	47.73	9.24	2.08	29.93	---	---	Peak
3 P	300.00	42.55	-3.45	46.00	57.66	12.30	2.52	29.93	---	---	Peak
4 !	311.90	44.86	-1.14	46.00	59.12	13.10	2.57	29.93	183	65	QP
5 Q	335.70	44.95	-1.05	46.00	58.02	14.20	2.66	29.93	125	87	QP
6 !	612.20	42.52	-3.48	46.00	50.11	18.60	3.73	29.92	---	---	Peak
7	2714.00	26.15	-47.85	74.00	29.57	32.72	10.14	46.28	---	---	Peak
8	4958.00	33.57	-40.43	74.00	32.69	34.12	12.95	46.19	---	---	Peak
9	6682.00	35.10	-38.90	74.00	33.32	33.90	14.85	46.97	---	---	Peak
10	8982.00	39.33	-34.67	74.00	32.84	36.38	16.08	45.97	---	---	Peak
11	10020.00	43.84	-30.16	74.00	36.10	36.98	17.71	46.95	---	---	Peak
12	12502.00	42.37	-31.63	74.00	34.63	37.93	18.99	49.18	---	---	Peak

## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Sep. 24, 2014	Feb. 20, 2015	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Mar. 04, 2014	Sep. 24, 2014	Mar. 03, 2015	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Mar. 04, 2014	Sep. 24, 2014	Mar. 03, 2015	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	61602000089 1	100Vac~250Vac	Dec. 17, 2013	Sep. 24, 2014	Dec. 16, 2014	Conduction (CO01-SZ)
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Sep. 15, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2014	Sep. 15, 2014	May 25, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TESEQ	CBL 6112D	23188	30MHz~2GHz	Oct. 26, 2013	Sep. 15, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 26, 2013	Sep. 15, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz	Feb. 21, 2014	Sep. 15, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 08, 2014	Sep. 15, 2014	May 07, 2015	Radiation (03CH01-SZ)
AC Source(AVR)	Chroma	61601	61601000198 5	100Vac~250Vac	Mar. 25, 2014	Sep. 15, 2014	Mar. 24, 2015	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	Sep. 15, 2014	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	Sep. 15, 2014	NCR	Radiation (03CH01-SZ)

## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.3
--	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	3.9
--	-----