



PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSDPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSUPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)



6.6 Spurious Radiated Emissions

Temperature	25°C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	April 19, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>
Test setup			
Test Procedure	<ol style="list-style-type: none"> 1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>		

Remark		
Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	V	-30.28	-13	-17.28
1648.4	H	-30.37	-13	-17.37
340.21	V	-33.87	-13	-20.87
280.79	H	-35.25	-13	-22.25

Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	V	-30.99	-13	-17.99
1673.2	H	-24.58	-13	-11.58
540.62	V	-37.73	-13	-24.73
233.38	H	-41.25	-13	-28.25

High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	V	-28.43	-13	-15.43
1697.6	H	-24.54	-13	-11.54
397.85	V	-33.63	-13	-20.63
204.55	H	-40.75	-13	-27.75

Note:

- 1, The testing has been conformed to $10 * 848.8 \text{ MHz} = 8,488 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, EGPRS and GPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	V	-33.75	-13	-20.75
3700.4	H	-38.55	-13	-25.55
552.92	V	-40.76	-13	-27.76
629.52	H	-34.82	-13	-21.82

Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	V	-33.63	-13	-20.63
3760	H	-36.87	-13	-23.87
572.41	V	-35.81	-13	-22.81
697.32	H	-36.21	-13	-23.21

High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	V	-33.94	-13	-20.94
3819.6	H	-29.66	-13	-16.66
239.74	V	-42.59	-13	-29.59
406.08	H	-36.88	-13	-23.88

Note:

- 1, The testing has been conformed to $10 \times 1909.8\text{MHz} = 19,098\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, EGPRS and GPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	V	-35.05	-13	-22.05
1652.8	H	-26.27	-13	-13.27
518.12	V	-37.22	-13	-24.22
302.32	H	-41.95	-13	-28.95

Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	V	-27.42	-13	-14.42
1670	H	-26.68	-13	-13.68
776.39	V	-42	-13	-29
317.57	H	-41.34	-13	-28.34

High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	V	-35.94	-13	-22.94
1693.2	H	-31.15	-13	-18.15
475.28	V	-34.96	-13	-21.96
737.6	H	-36.01	-13	-23.01

Note:

- 1, The testing has been conformed to $10 \times 846.6\text{MHz} = 8,466\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	V	-34.94	-13	-21.94
3704.8	H	-36.8	-13	-23.8
728.25	V	-36.59	-13	-23.59
309.63	H	-40.18	-13	-27.18

Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	V	-34.08	-13	-21.08
3760	H	-32.26	-13	-19.26
441.32	V	-42.63	-13	-29.63
309.86	H	-38.95	-13	-25.95

High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	V	-31.75	-13	-18.75
3815.2	H	-35.69	-13	-22.69
785.12	V	-34.95	-13	-21.95
618.2	H	-40.11	-13	-27.11

Note:

- 1, The testing has been conformed to $10 * 1907.6\text{MHz} = 19,076\text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case
- 5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	V	-32.14	-13	-19.14
3424.8	H	-27.76	-13	-14.76
715.03	V	-38.91	-13	-25.91
687.47	H	-39.05	-13	-26.05

Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	V	-32.36	-13	-19.36
3480	H	-28.15	-13	-15.15
496.2	V	-34.59	-13	-21.59
327.91	H	-41.81	-13	-28.81

High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	V	-23.38	-13	-10.38
3505.2	H	-29.68	-13	-16.68
407.19	V	-39.31	-13	-26.31
419.37	H	-42.23	-13	-29.23

Note:

- 1, The testing has been conformed to 10*1752.6MHz=17,526MHz
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

6.7 Band Edge

Temperature	25°C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	April 19, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup		<p style="text-align: center;"> Base Station Spectrum Analyzer EUT </p>	
Procedure		<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 	
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A
Test Plot Yes (See below) N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.990	-15.835	-13
849.023	-17.728	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.996	-14.259	-13
1910.020	-15.363	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.990	-14.377	-13
849.023	-13.248	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.982	-17.351	-13
1910.021	-16.921	-13

EGPRS (MCS 1):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.996	-13.468	-13
849.019	-13.726	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.997	-14.518	-13
1910.019	-17.407	-13

RMC:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.89	-27.730	-13
849.94	-28.049	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.68	-28.196	-13
1910.34	-32.446	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.07	-21.989	-13
1755.10	-25.114	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.98	-25.963	-13
850.00	-29.004	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.160	-27.350	-13
1910.84	-29.863	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1708.98	-23.906	-13
1755.10	-26.832	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.96	-26.496	-13
849.94	-28.049	-13

UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.82	-27.622	-13
1910.34	-29.516	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.02	-23.755	-13
1755.11	-25.218	-13


GSM Voice:

Test Plots




GPRS:

Test Plots





EGPRS (MCS1):

Test Plots



RMC:

 <p>Agilent Spectrum Analyzer - Swept SA Marker 1 823.890000000 MHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6 dB Ref 30.00 dBm 10 dB/div Log Center 824.000 MHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>	 <p>Agilent Spectrum Analyzer - Swept SA Marker 1 849.940000000 MHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6 dB Ref 30.00 dBm 10 dB/div Log Center 849.000 MHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>
<p>UMTS-FDD Band V - Low Channel</p>	<p>UMTS-FDD Band V - High Channel</p>
<p>Note: Offset=Cable loss (4.0) + 10log (46.73/30)=4.0+1.9=6.0dB</p>	<p>Note: Offset=Cable loss (4.0) + 10log (46.53/30)=4.0+2.0=6.0dB</p>
 <p>Agilent Spectrum Analyzer - Swept SA Marker 1 1.849680000000 GHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6.5 dB Ref 30.00 dBm 10 dB/div Log Center 1.850000 GHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>	 <p>Agilent Spectrum Analyzer - Swept SA Marker 1 1.910340000000 GHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6.5 dB Ref 30.00 dBm 10 dB/div Log Center 1.910000 GHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>
<p>UMTS-FDD Band II - Low Channel</p>	<p>UMTS-FDD Band II - High Channel</p>
<p>Note: Offset=Cable loss (4.5) + 10log (46.73/30)=4.5+2.0=6.5 dB</p>	<p>Note: Offset=Cable loss (4.5) + 10log (46.47/30)=4.5+2.0=6.5 dB</p>




UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log
 $(46.79/30)=4.5+1.9=6.4 \text{ dB}$

UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.0) + 10log
 $(4669/30)=4.5+1.9=6.4 \text{ dB}$

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.59/30)=4.0+2.0=6dB

UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(46.55/30)=4.0+2.0=6dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(46.66/30)=4.5+2.0=6.5dB

UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(46.67/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel	UMTS-FDD Band IV - High Channel
Note: Offset=Cable loss (4.5) + 10log $(46.66/30)=4.5+1.9=6.4 \text{ dB}$	Note: Offset=Cable loss (4.0) + 10log $(46.86/30)=4.5+1.9=6.4 \text{ dB}$

HSUPA:


 <p>Marker 1 823.960000000 MHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6 dB Ref 30.00 dBm 10 dB/div Log Center 824.000 MHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>	 <p>Marker 1 849.940000000 MHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6 dB Ref 30.00 dBm 10 dB/div Log Center 849.000 MHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>
UMTS-FDD Band V - Low Channel	UMTS-FDD Band V - High Channel
Note: Offset=Cable loss (4.0) + 10log (46.49/30)=4.0+2.0=6 dB	Note: Offset=Cable loss (4.0) + 10log (46.66/30)=4.0+2.0=6dB
 <p>Marker 1 1.84880000000 GHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6.5 dB Ref 30.00 dBm 10 dB/div Log Center 1.84880000000 GHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>	 <p>Marker 1 1.910340000000 GHz PNO: Wide IF-Gain:Low Trig: Free Run Atten: 34 dB Avg Type: Log-Pwr Avg Hold>100/100 Ref Offset 6.5 dB Ref 30.00 dBm 10 dB/div Log Center 1.910340000000 GHz #Res BW 30 kHz #VBW 30 kHz Sweep 13.40 ms (1001 pts) MSG STATUS</p>
UMTS-FDD Band II - Low Channel	UMTS-FDD Band II - High Channel
Note: Offset=Cable loss (4.5) + 10log (46.66/30)=4.5+2.0=6.5dB	Note: Offset=Cable loss (4.5) + 10log (46.64/30)=4.5+2.0=6.5 dB



6.8 Frequency Stability

Temperature	25°C
Relative Humidity	57%
Atmospheric Pressure	1015mbar
Test date :	April 19, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th> <th>Base, fixed (ppm)</th> <th>Mobile ≤ 3 watts (ppm)</th> <th>Mobile ≤ 3 watts (ppm)</th> </tr> </thead> <tbody> <tr> <td>25 to 50</td> <td>20.0</td> <td>20.0</td> <td>50.0</td> </tr> <tr> <td>50 to 450</td> <td>5.0</td> <td>5.0</td> <td>50.0</td> </tr> <tr> <td>45□to 512</td> <td>2.5</td> <td>5.0</td> <td>□0</td> </tr> <tr> <td>821 to 896</td> <td>1.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>928 to □29.</td> <td>5.0</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>929 to 960.</td> <td>1.5</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>2110 to 2220</td> <td>10.0</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45□to 512	2.5	5.0	□0	821 to 896	1.5	2.5	2.5	928 to □29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45□to 512	2.5	5.0	□0																																
821 to 896	1.5	2.5	2.5																																
928 to □29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup		 <p>The diagram illustrates the test setup. A green rectangular box labeled "Base Station" has two black legs at the bottom and a blue circle on its right side. A horizontal line extends from the blue circle to a blue rectangular box labeled "EUT". This "EUT" box is situated within a dashed rectangular frame labeled "Thermal Chamber" at the bottom.</p>																																	

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within ±0.00025% ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	19	0.0227	2.5
0		17	0.0203	2.5
10		17	0.0203	2.5
20		13	0.0155	2.5
30		16	0.0191	2.5
40		17	0.0203	2.5
50		22	0.0263	2.5
55		18	0.0215	2.5
25		20	0.0239	2.5
	4.35	17	0.0203	2.5
	3.45			

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	12	0.0064	2.5
0		15	0.0080	2.5
10		13	0.0069	2.5
20		13	0.0069	2.5
30		15	0.0080	2.5
40		15	0.0080	2.5
50		18	0.0096	2.5
55		17	0.0090	2.5
25		18	0.0096	2.5
	4.35	19	0.0101	2.5
	3.45			

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{dc})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	15	0.0180	2.5
0		15	0.0180	2.5
10		18	0.0216	2.5
20		14	0.0168	2.5
30		12	0.0144	2.5
40		8	0.0096	2.5
50		19	0.0228	2.5
55		13	0.0156	2.5
25		18	0.0216	2.5
	4.35	16	0.0192	2.5
	3.45			

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{dc})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	18	0.0096	2.5
0		18	0.0096	2.5
10		17	0.0090	2.5
20		16	0.0085	2.5
30		15	0.0080	2.5
40		17	0.0090	2.5
50		21	0.0112	2.5
55		19	0.0101	2.5
25		18	0.0096	2.5
	4.35	16	0.0085	2.5
	3.45			

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1733$ MHz				
Temperature (°C)	Power Supplied (V _{dc})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	22	0.0263	2.5
0		15	0.0180	2.5
10		17	0.0204	2.5
20		16	0.0192	2.5
30		16	0.0192	2.5
40		15	0.0180	2.5
50		19	0.0228	2.5
55		21	0.0251	2.5
25	4.35	20	0.0240	2.5
	3.45	17	0.0204	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/14/2017	09/13/2018	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/07/2017	10/06/2018	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/22/2018	03/21/2019	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/26/2017	05/25/2018	<input checked="" type="checkbox"/>

Test Report	18070322-FCC-R1
Page	88 of 105

Tunable Notch Filter	3NF-800/1000-S	AA4	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-1000/2000-S	AM 4	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>


Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Lable View



EUT - Front View



EUT - Rear View

