

FCC RF Test Report

APPLICANT : CT Asia
EQUIPMENT : Mobile Phone
BRAND NAME : BLU
MODEL NAME : Vivo 4.65 HD
FCC ID : YHLBLUVIVO465
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 18, 2012 and completely tested on Jan. 03, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	6
1.4 Product Specification of Equipment Under Test	6
1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.6 Testing Site	7
1.7 Applied Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration and system.....	12
2.4 Measurement Results Explanation Example	12
3 TEST RESULT	13
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	23
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	29
3.5 Band Edge Measurement.....	49
3.6 Conducted Spurious Emission Measurement	62
3.7 Field Strength of Spurious Radiation Measurement	78
3.8 Frequency Stability Measurement.....	93
4 LIST OF MEASURING EQUIPMENT	98
5 UNCERTAINTY OF EVALUATION	99
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG2D1808	Rev. 01	Initial issue of report	Jan. 09, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	N/A	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 34.63 dB at 5640.000 MHz
3.8	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Gionee Communication Equipment Co., Ltd.

21/F, Times Technology Building, No. 7028, Shennan Avenue, Futian District, Shenzhen, China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	BLU
Model Name	Vivo 4.65 HD
FCC ID	YHLBLUVIVO465
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/WLAN 11bgn/Bluetooth
HW Version	S80_Mainboard_P2
SW Version	S80_0202_V0903
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.22 dBm GSM1900 : 30.05 dBm WCDMA Band V : 22.75 dBm WCDMA Band II : 23.28 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK/8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	1.2331	0.02 ppm	246KGXW
Part 22	GSM850 EDGE 8	8PSK	0.3673	0.02 ppm	250KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1517	0.01 ppm	4M20F9W
Part 24	GSM1900 GSM	GMSK	1.9011	0.03 ppm	250KGXW
Part 24	GSM1900 EDGE 8	8PSK	0.8017	0.03 ppm	248KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.4887	0.01 ppm	4M20F9W

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-KS	03CH01-KS	149928/4086E-1

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v01
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5
- ♦ NOTICE 2012-DRS0126

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. Per the section 2.2.3 of Notice of 2012-DRS0126, " Receivers Excluded from Industry Canada Requirements", only radio communication receivers operating in stand-alone mode within the band 30-960 MHz and scanner receivers are subject to Industry Canada requirements.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note: The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

For SIM Card 1


Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM (1 Uplink)	32.22	32.14	32.12	30.00	30.05	29.92
GPRS 8 (1 Uplink) – CS1	32.20	32.13	32.11	29.99	30.04	29.91
GPRS 10 (2 Uplink) – CS1	31.47	31.39	31.38	29.07	29.14	29.01
GPRS 11 (3 Uplink) – CS1	29.77	29.68	29.66	27.36	27.41	27.29
GPRS 12 (4 Uplink) – CS1	28.67	28.58	28.57	26.52	26.58	26.47
EDGE 8 (8PSK, 1 Uplink) – MCS5	25.94	25.92	25.89	25.67	25.66	25.44
EDGE 10 (8PSK, 2 Uplink) – MCS5	24.85	24.83	24.81	24.55	24.56	24.41
EDGE 11 (8PSK, 3 Uplink) – MCS5	22.63	22.62	22.55	22.55	22.40	22.15
EDGE 12 (8PSK, 4 Uplink) – MCS5	21.34	21.27	21.19	20.90	21.10	20.94

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
AMR 12.2k	22.69	22.71	22.73	23.01	23.25	23.11
RMC 12.2k	22.70	22.73	22.75	23.04	23.28	23.13
HSDPA Subtest-1	21.53	21.60	21.72	21.01	21.28	21.11
HSDPA Subtest-2	21.54	21.59	21.73	21.09	21.24	21.15
HSDPA Subtest-3	21.22	21.27	21.32	20.69	20.97	20.77
HSDPA Subtest-4	21.33	21.37	21.39	20.71	20.95	20.76
HSUPA Subtest-1	21.54	21.50	21.57	20.88	21.08	21.00
HSUPA Subtest-2	20.01	20.04	20.11	19.97	20.16	20.01
HSUPA Subtest-3	20.71	20.75	20.80	21.04	21.17	21.11
HSUPA Subtest-4	20.16	20.19	20.21	19.99	20.28	20.19
HSUPA Subtest-5	21.61	21.63	21.67	21.01	21.28	21.14

For SIM Card 2

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM (1 Uplink)	32.21	32.13	32.11	29.99	30.04	29.90
GPRS 8 (1 Uplink) – CS1	32.20	32.13	32.11	29.98	30.03	29.90
GPRS 10 (2 Uplink) – CS1	31.47	31.38	31.37	29.06	29.12	29.01
GPRS 11 (3 Uplink) – CS1	29.76	29.66	29.64	27.36	27.41	27.28
GPRS 12 (4 Uplink) – CS1	28.66	28.58	28.56	26.51	26.58	26.47
EDGE 8 (8PSK, 1 Uplink) – MCS5	25.93	25.91	25.88	25.61	25.65	25.43
EDGE 10 (8PSK, 2 Uplink) – MCS5	24.84	24.81	24.80	24.54	24.55	24.40
EDGE 11 (8PSK, 3 Uplink) – MCS5	22.62	22.60	22.54	22.53	22.38	22.05
EDGE 12 (8PSK, 4 Uplink) – MCS5	21.31	21.25	21.17	20.88	21.08	20.84

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and 10dB attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and 10dB attenuator factor.

Offset = RF cable loss + attenuator factor.

Following table shows an offset computation example with cable loss 4.2 dB.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.22	32.14	32.12	25.94	25.92	25.89	22.70	22.73	22.75
Conducted Power (Watts)	1.67	1.64	1.63	0.39	0.39	0.39	0.19	0.19	0.19

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	30.00	30.05	29.92	25.67	25.66	25.44	23.04	23.28	23.13
Conducted Power (Watts)	1.00	1.01	0.98	0.37	0.37	0.35	0.20	0.21	0.21

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. For GSM/EGPRS operating modes:
 - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
 - b. Set EUT in maximum power output, and triggered the burst signal.
 - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

3.2.4 Test Setup




3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.08	0.09	0.08	0.09	0.09	0.09	2.72	2.92	2.28

3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link
---------------	----------	--------------------	----------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 29.DEC.2012 19:10:35

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)


Date: 29.DEC.2012 19:10:04



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 29.DEC.2012 19:09:16




Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Date: 29.DEC.2012 20:31:14

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 29.DEC.2012 20:30:43


Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 29.DEC.2012 20:30:01


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)




Date: 2.JAN.2013 14:10:17

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 2.JAN.2013 14:11:05

Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 2.JAN.2013 14:10:43

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meter from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-17.05	-48.12	0.00	-1.08	29.99	0.9977
836.40	-16.58	-48.28	0.00	-0.93	30.77	1.1940
848.80	-16.68	-48.35	0.00	-0.76	30.91	1.2331
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-19.05	-47.97	0.00	-1.08	27.84	0.6081
836.40	-23.68	-48.01	0.00	-0.93	23.40	0.2188
848.80	-25.62	-48.05	0.00	-0.76	21.67	0.1469

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.00	-48.12	0.00	-1.08	24.04	0.2535
836.40	-22.00	-48.28	0.00	-0.93	25.35	0.3428
848.80	-21.94	-48.35	0.00	-0.76	25.65	0.3673
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-33.23	-47.97	0.00	-1.08	13.66	0.0232
836.40	-31.77	-48.01	0.00	-0.93	15.31	0.0340
848.80	-30.99	-48.05	0.00	-0.76	16.30	0.0427

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.15	-48.12	0.00	-1.08	19.89	0.0975
836.40	-25.57	-48.28	0.00	-0.93	21.78	0.1507
846.60	-25.78	-48.35	0.00	-0.76	21.81	0.1517
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-36.57	-47.97	0.00	-1.08	10.32	0.0108
836.40	-35.51	-48.01	0.00	-0.93	11.57	0.0144
846.60	-35.15	-48.05	0.00	-0.76	12.14	0.0164

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-22.00	-51.88	0.00	1.96	31.84	1.5276
1880.00	-22.94	-52.99	0.00	2.00	32.05	1.6032
1909.80	-23.72	-54.28	0.00	1.98	32.54	1.7947
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-21.80	-52.13	0.00	1.96	32.29	1.6943
1880.00	-22.79	-53.17	0.00	2.00	32.38	1.7298
1909.80	-23.32	-54.13	0.00	1.98	32.79	1.9011

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.17	-51.88	0.00	1.96	28.67	0.7362
1880.00	-26.42	-52.99	0.00	2.00	28.57	0.7194
1909.80	-27.47	-54.28	0.00	1.98	28.79	0.7568
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.08	-52.13	0.00	1.96	29.01	0.7962
1880.00	-26.16	-53.17	0.00	2.00	29.01	0.7962
1909.80	-27.07	-54.13	0.00	1.98	29.04	0.8017



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-27.85	-51.88	0.00	1.96	25.99	0.3972
1880.00	-29.00	-52.99	0.00	2.00	25.99	0.3972
1907.60	-29.76	-54.28	0.00	1.98	26.50	0.4467
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-27.67	-52.13	0.00	1.96	26.42	0.4385
1880.00	-28.84	-53.17	0.00	2.00	26.33	0.4295
1907.60	-29.22	-54.13	0.00	1.98	26.89	0.4887

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (KHz)	246.00	246.00	246.00	248.00	250.00	250.00
26dB BW (KHz)	320.00	318.00	308.00	318.00	308.00	312.00


PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (KHz)	246.00	250.00	242.00	248.00	248.00	246.00
26dB BW (KHz)	308.00	310.00	316.00	316.00	318.00	318.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.20	4.18	4.18
26dB BW (MHz)	4.68	4.68	4.68


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.16	4.20
26dB BW (MHz)	4.68	4.68	4.72

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth

Band :	GSM 850	Test Mode :	GSM Link
---------------	---------	--------------------	----------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 29.DEC.2012 19:30:49

26dB Bandwidth Plot on Channel 128 (824.2 MHz)


Date: 29.DEC.2012 19:32:06




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 29.DEC.2012 19:29:06

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 29.DEC.2012 19:34:05

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 29.DEC.2012 19:27:51


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 29.DEC.2012 19:35:08


Band :	GSM 850	Test Mode :	EDGE 8 Link
--------	---------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 29.DEC.2012 20:59:23


26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 29.DEC.2012 20:52:57

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 29.DEC.2012 21:00:38

26dB Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 29.DEC.2012 20:52:04

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 29.DEC.2012 21:01:37


26dB Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 29.DEC.2012 20:50:46




Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 29.DEC.2012 18:58:17

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 29.DEC.2012 19:06:27

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 29.DEC.2012 18:56:41

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 29.DEC.2012 19:07:29

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 29.DEC.2012 18:55:43

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 29.DEC.2012 19:08:14




Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 29.DEC.2012 20:24:23


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 29.DEC.2012 20:07:44


99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)


Date: 29.DEC.2012 20:22:06

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 29.DEC.2012 20:06:26

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 29.DEC.2012 20:20:28

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 29.DEC.2012 20:08:57


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
---------------	--------------	--------------------	-------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 2.JAN.2013 14:42:27

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 2.JAN.2013 14:38:43

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 2.JAN.2013 14:43:28

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)


Date: 2.JAN.2013 14:38:01

99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 2.JAN.2013 14:41:34


26dB Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 2.JAN.2013 14:39:59




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date : 2.JAN.2013 13:59:08


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date : 2.JAN.2013 13:57:39

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 2.JAN.2013 14:01:04

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)


Date: 2.JAN.2013 13:55:42

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)


Date : 2.JAN.2013 14:00:18

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)


Date : 2.JAN.2013 13:56:29

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.28dB	Maximum 26dB Bandwidth :	0.320MHz
Band Edge :	-15.95dBm	Measurement Value :	-16.23dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 29.DEC.2012 19:16:01

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-16.23\text{dBm} + 0.28\text{dB} = -15.95\text{dBm}$


Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.28dB	Maximum 26dB Bandwidth :	0.320MHz
Band Edge :	-16.40dBm	Measurement Value :	-16.68dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 29.DEC.2012 19:14:54

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-17.87dBm	Measurement Value :	-18.12dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)


Date: 29.DEC.2012 20:57:12

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-15.61dBm	Measurement Value :	-15.86dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 29.DEC.2012 20:56:34

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-20.06dBm	Measurement Value :	-20.29dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 29.DEC.2012 19:00:07

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-19.16dBm	Measurement Value :	-19.39dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 29.DEC.2012 19:01:10

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-20.09dBm	Measurement Value :	-20.34dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 29.DEC.2012 20:15:17

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-19.37dBm	Measurement Value :	-19.62dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 29.DEC.2012 20:16:44

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-30.52dBm	Measurement Value :	-27.22dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)


Date: 2.JAN.2013 14:49:03

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.30dB	Maximum 26dB Bandwidth :	4.68MHz
Band Edge :	-29.86dBm	Measurement Value :	-26.56dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)


Date: 2.JAN.2013 14:49:39

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.72MHz
Band Edge :	-29.14dBm	Measurement Value :	-25.88dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)


Date: 2.JAN.2013 14:08:27

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.72MHz
Band Edge :	-26.04dBm	Measurement Value :	-22.78dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)


Date: 2.JAN.2013 14:08:00

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$


$$= -13\text{dBm}.$$

3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 29.DEC.2012 19:50:32

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 29.DEC.2012 19:39:20

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 29.DEC.2012 19:40:29

Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 29.DEC.2012 19:41:10


Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 29.DEC.2012 19:52:34


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 29.DEC.2012 19:54:37


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date : 29.DEC.2012 19:55:19


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date : 29.DEC.2012 19:56:08


Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 29.DEC.2012 19:48:16

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 29.DEC.2012 19:49:13


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 29.DEC.2012 19:44:26

Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 29.DEC.2012 19:45:56

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 29.DEC.2012 19:46:45


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 29.DEC.2012 19:58:57

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 29.DEC.2012 20:00:16


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 29.DEC.2012 20:01:44

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 29.DEC.2012 20:02:39

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 29.DEC.2012 20:04:03


Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 2.JAN.2013 14:53:04

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 2.JAN.2013 14:21:32

Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 2.JAN.2013 14:22:23


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 2.JAN.2013 14:23:03




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 2.JAN.2013 14:13:57


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 2.JAN.2013 14:13:09


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 2.JAN.2013 14:16:46

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 2.JAN.2013 14:17:38

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 2.JAN.2013 14:18:18

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13\text{dBm}.$$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.7.6 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	22~23°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 2D1808
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.61	-13	-39.61	-50.78	-53.26	0.57	3.37	H	Pass
2510	-54.86	-13	-41.86	-57.11	-57.09	0.78	5.16	H	Pass
3344	-61.96	-13	-48.96	-63.90	-65.60	0.87	6.66	H	Pass
4182	-62.11	-13	-49.11	-64.85	-66.70	0.97	7.71	H	Pass
5018	-53.02	-13	-40.02	-59.22	-58.69	1.09	8.91	H	Pass

Band :	GSM850	Temperature :	22~23°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 : HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 2D1808

Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-53.53	-13	-40.53	-53.56	-54.18	0.57	3.37	V	Pass
2510	-55.86	-13	-42.86	-58.97	-58.09	0.78	5.16	V	Pass
3344	-62.50	-13	-49.50	-64.48	-66.14	0.87	6.66	V	Pass
4182	-60.23	-13	-47.23	-64.07	-64.82	0.97	7.71	V	Pass
5018	-55.09	-13	-42.09	-60.03	-60.76	1.09	8.91	V	Pass


Band :	GSM850	Temperature :	22~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D1808
Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-65.22	-13	-52.22	-61.00	-65.87	0.57	3.37	H	Pass
2509	-64.46	-13	-51.46	-66.71	-66.69	0.78	5.16	H	Pass
3344	-63.49	-13	-50.49	-65.43	-67.13	0.87	6.66	H	Pass
4182	-62.85	-13	-49.85	-65.59	-67.44	0.97	7.71	H	Pass


Band :	GSM850	Temperature :	22~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D1808
Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-63.01	-13	-50.01	-58.66	-63.66	0.57	3.37	V	Pass
2509	-63.31	-13	-50.31	-66.42	-65.54	0.78	5.16	V	Pass
3344	-62.93	-13	-49.93	-64.91	-66.57	0.87	6.66	V	Pass
4182	-61.47	-13	-48.47	-65.31	-66.06	0.97	7.71	V	Pass

Band :	GSM1900	Temperature :	22~23°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 2D1808

Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-58.08	-13	-45.08	-59.05	-64.46	0.78	7.16	H	Pass
5640	-47.63	-13	-34.63	-55.74	-56.17	1.04	9.58	H	Pass
7520	-58.80	-13	-45.80	-63.93	-68.91	1.35	11.46	H	Pass
9399	-55.82	-13	-42.82	-59.08	-66.88	1.75	12.81	H	Pass
11283	-50.78	-13	-37.78	-62.27	-61.87	2	13.09	H	Pass

Band :	GSM1900	Temperature :	22~23°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 2D1808
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.17	-13	-43.17	-57.54	-62.55	0.78	7.16	V	Pass
5640	-54.05	-13	-41.05	-57.27	-62.59	1.04	9.58	V	Pass
7520	-57.80	-13	-44.80	-62.29	-67.91	1.35	11.46	V	Pass
9399	-60.30	-13	-47.30	-61.52	-71.36	1.75	12.81	V	Pass
11280	-51.69	-13	-38.69	-62.93	-62.78	2	13.09	V	Pass




Band :	GSM1900	Temperature :	22~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D1808
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-63.27	-13	-50.27	-64.24	-69.65	0.78	7.16	H	Pass
5640	-57.87	-13	-44.87	-62.05	-66.41	1.04	9.58	H	Pass
7520	-57.76	-13	-44.76	-62.89	-67.87	1.35	11.46	H	Pass


Band :	GSM1900	Temperature :	22~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D1808
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-60.58	-13	-47.58	-61.95	-66.96	0.78	7.16	V	Pass
5640	-57.00	-13	-44.00	-60.22	-65.54	1.04	9.58	V	Pass
7520	-61.11	-13	-48.11	-65.6	-71.22	1.35	11.46	V	Pass


Band :	WCDMA Band V	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 2D1808
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1670	-66.24	-13	-53.24	-62.02	-66.89	0.57	3.37	H	Pass
2508	-62.91	-13	-49.91	-65.16	-65.14	0.78	5.16	H	Pass
3344	-63.63	-13	-50.63	-65.57	-67.27	0.87	6.66	H	Pass

Band :	WCDMA Band V	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition : FCC PART22 24 : HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D1808
Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-61.51	-13	-48.51	-57.16	-62.16	0.57	3.37	V	Pass
2514	-59.33	-13	-46.33	-62.44	-61.56	0.78	5.16	V	Pass
3670	-56.54	-13	-43.54	-58.52	-60.18	0.87	6.66	V	Pass




Band :	WCDMA Band II	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 2D1808
 Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-63.36	-13	-50.36	-64.33	-69.74	0.78	7.16	H	Pass
5640	-60.50	-13	-47.50	-64.68	-69.04	1.04	9.58	H	Pass
7520	-59.55	-13	-46.55	-64.68	-69.66	1.35	11.46	H	Pass

Band :	WCDMA Band II	Temperature :	22~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 2D1808

Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3762	-61.29	-13	-48.29	-62.66	-67.67	0.78	7.16	V	Pass
5640	-61.49	-13	-48.49	-64.71	-70.03	1.04	9.58	V	Pass
7520	-59.99	-13	-46.99	-64.48	-70.10	1.35	11.46	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	15	0.02	19	0.02	PASS
-20	12	0.01	16	0.02	
-10	8	0.01	17	0.02	
0	9	0.01	18	0.02	
10	10	0.01	19	0.02	
20	8	0.01	17	0.02	
30	15	0.02	18	0.02	
40	17	0.02	19	0.02	
50	16	0.02	20	0.02	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	40	0.02	38	0.02	PASS
-20	42	0.02	34	0.02	
-10	30	0.02	41	0.02	
0	29	0.02	40	0.02	
10	31	0.02	41	0.02	
20	32	0.02	41	0.02	
30	43	0.02	45	0.02	
40	47	0.02	46	0.02	
50	49	0.03	48	0.03	

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-7	-0.01	PASS
-20	3	0.00	
-10	-4	0.00	
0	-3	0.00	
10	3	0.00	
20	-5	-0.01	
30	3	0.00	
40	-4	0.00	
50	3	0.00	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	10	0.01	PASS
-20	-7	0.00	
-10	8	0.00	
0	-7	0.00	
10	8	0.00	
20	8	0.00	
30	-9	0.00	
40	8	0.00	
50	-7	0.00	

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	8	0.01	2.5	PASS
		BEP	-12	-0.01		
		4.2	11	0.01		
	EDGE 8	3.8	14	0.02		
		BEP	-16	-0.02		
		4.2	13	0.02		
GSM 1900 CH661	GSM	3.8	23	0.01		
		BEP	26	0.01		
		4.2	35	0.02		
	EDGE 8	3.8	26	0.01		
		BEP	29	0.02		
		4.2	37	0.02		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	-3	0.00		
		BEP	3	0.00		
		4.2	3	0.00		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	6	0.00		
		BEP	8	0.00		
		4.2	8	0.00		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.5 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Dec. 29, 2012~Jan. 02, 2013	Dec. 28, 2013	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 29, 2012	Dec. 29, 2012~Jan. 02, 2013	Dec. 28, 2013	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 22, 2012	Dec. 29, 2012~Jan. 02, 2013	Aug. 21, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 29, 2012	Dec. 29, 2012~Jan. 02, 2013	Dec. 28, 2013	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Jan. 03, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	Jun. 01, 2012	Jan. 03, 2013	May 31, 2013	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Jan. 03, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 07, 2012	Jan. 03, 2013	Jan. 06, 2013	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	Jun. 01, 2012	Jan. 03, 2013	May 31, 2013	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Jan. 03, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Jan. 03, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9KHz ~ 30MHz	Jul. 03, 2012	Jan. 03, 2013	Jul. 02, 2014	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Dec. 29, 2012	Jan. 03, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 19, 2012	Jan. 03, 2013	Sep. 18, 2013	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
--	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------



Appendix A. Photographs of EUT

Please refer to Sporton report number EP2D1808 as below.