

FCC SAR Test Report

APPLICANT : CT Asia
EQUIPMENT : GSM & WCDMA Mobile Phone
BRAND NAME : BLU
MODEL NAME : Quattro 4.5
FCC ID : YHLBLUQUATTRO45
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003
FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was completely tested on Dec. 14, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : YHLBLUQUATTRO45

Page Number : 1 of 42

Report Issued Date : Dec. 17, 2012

Report Version : Rev. 01

Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
2.1 Testing Laboratory.....	5
2.2 Applicant	5
2.3 Manufacturer	5
2.4 Application Details.....	5
3. General Information	6
3.1 Description of Equipment Under Test (EUT)	6
3.2 Product Photos	8
3.3 Applied Standard.....	8
3.4 Device Category and SAR Limits	8
3.5 Test Conditions.....	8
4. Specific Absorption Rate (SAR).....	9
4.1 Introduction	9
4.2 SAR Definition.....	9
5. SAR Measurement System.....	10
5.1 E-Field Probe	11
5.2 Data Acquisition Electronics (DAE)	12
5.3 Robot	12
5.4 Measurement Server.....	12
5.5 Phantom.....	13
5.6 Device Holder	13
5.7 Data Storage and Evaluation	14
5.8 Test Equipment List.....	16
6. Tissue Simulating Liquids.....	17
7. SAR Measurement Evaluation	18
7.1 Purpose of System Performance check	18
7.2 System Setup.....	18
7.3 Verification Results.....	19
8. EUT Testing Position	20
8.1 Define two imaginary lines on the handset.....	20
8.2 Cheek Position	21
8.3 Tilted Position.....	21
8.4 Body Worn Position.....	22
9. Measurement Procedures	23
9.1 Spatial Peak SAR Evaluation.....	23
9.2 Area & Zoom Scan Procedures.....	23
9.3 Volume Scan Procedures.....	24
9.4 SAR Averaged Methods	24
9.5 Power Drift Monitoring.....	24
10. SAR Test Configurations.....	25
10.1 Exposure Positions Consideration	25
10.2 Conducted RF Output Power (Unit: dBm).....	27
11. SAR Test Results	31
11.1 Test Records for Head SAR Test.....	31
11.2 Test Records for Hotspot SAR Test	32
11.3 Test Records for Body-worn SAR Test	34
11.4 Simultaneous Multi-band Transmission Analysis.....	36
12. Uncertainty Assessment	40
13. References	42
Appendix A. Plots of System Performance Check	
Appendix B. Plots of SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Product Photos	
Appendix E. Test Setup Photos	



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA2N2701	Rev. 01	Initial issue of report	Dec. 17, 2012

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **CT Asia; DUT: GSM & WCDMA Mobile Phone; Brand Name: BLU; Model Name: Quattro 4.5** are as follows.

<Standalone SAR>

Band	Position	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)
GSM850	Head	0.728	0.804
GSM1900	Head	0.394	0.465
WCDMA Band V	Head	0.384	0.415
WCDMA Band IV	Head	0.497	0.559
WCDMA Band II	Head	0.398	0.433
WLAN 2.4G	Head	0.127	0.135
GSM850	Hotspot (1 cm Gap)	0.939	1.071
GSM1900	Hotspot (1 cm Gap)	0.925	1.079
WCDMA Band V	Hotspot (1 cm Gap)	0.650	0.703
WCDMA Band IV	Hotspot (1 cm Gap)	1.210	1.409
WCDMA Band II	Hotspot (1 cm Gap)	1.080	1.176
WLAN 2.4G	Hotspot (1 cm Gap)	0.088	0.094
GSM850	Body-worn (1 cm Gap)	0.939	1.071
GSM1900	Body-worn (1 cm Gap)	0.925	1.079
WCDMA Band V	Body-worn (1 cm Gap)	0.650	0.703
WCDMA Band IV	Body-worn (1 cm Gap)	0.923	1.038
WCDMA Band II	Body-worn (1 cm Gap)	1.010	1.100
WLAN 2.4G	Body-worn (1 cm Gap)	0.088	0.094

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

2. Administration Data

2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958

2.2 Applicant

Company Name	CT Asia
Address	Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

2.3 Manufacturer

Company Name	Beijing Tianyu Communication Equipment Co., Ltd.
Address	NO.55 Jiachang 2 road, OPTO-Mechatronics Industrial Park, Tongzhou district, Beijing 101111

2.4 Application Details

Date of Start during the Test	Dec. 11, 2012
Date of End during the Test	Dec. 14, 2012

3. General Information

3.1 Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT	GSM & WCDMA Mobile Phone
Brand Name	BLU
Model Name	Quattro 4.5
FCC ID	YHLBLUQUATTRO45
IMEI Code	864839010044366
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WLAN2.4G: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz WCDMA Band IV: 2112.4MHz ~ 2152.6 MHz WLAN2.4G: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Maximum Average Output Power to Antenna	GSM850: 32.94 dBm GSM1900: 29.86 dBm WCDMA Band V: 23.66 dBm WCDMA Band II: 23.63 dBm WCDMA Band IV: 23.79 dBm 802.11b: 14.72 dBm 802.11g: 12.98 dBm 802.11n-HT20 (2.4GHz) : 12.97 dBm Bluetooth: 7.12 dBm
Antenna Type	WWAN: Fixed Internal Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna
HW Version	P2.0
SW Version	BLU-D450-V05-GENERIC
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) 802.11b: DSSS (BPSK / QPSK / CCK) 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth 2.1 BDR (1Mbps) : GFSK Bluetooth 2.1 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK
Dual Transfer Mode (DTM) Category	Class A – EUT can support Packet Switched and Circuit Switched Network simultaneously.
EUT Stage	Production Unit
Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	

Per KDB 941225 D04 requirement, the required test configuration for this device is as below:

1. This EUT is class A device



2. This EUT supports (E)GPRS multi-slot class 33 (max. uplink : 4, max. downlink : 4, total timeslots : 6)
3. This EUT supports DTM multi-slot class 11 (max. uplink : 3 for 1 CS & 2 PS, max. downlink : 4, total timeslots : 5)
4. The measured maximum conducted power can be referred to section 12.1 of this report
5. For DTM multi-slot class 11 link mode, the device was linked with system emulator (Agilent E5515C) and transmit maximum power on maximum number of Tx slots (one CS timeslot and two PS timeslots per frame).



3.2 Product Photos

Please refer to Appendix D.

3.3 Applied Standard

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 447498 D01 v04
- FCC KDB 648474 D01 v01r05
- FCC KDB 941225 D01 v02
- FCC KDB 941225 D02 v02
- FCC KDB 941225 D03 v01
- FCC KDB 941225 D04 v01
- FCC KDB 941225 D06 v01
- FCC KDB 248227 D01 v01r02

3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

3.5 Test Conditions

3.5.1 Ambient Condition

Ambient Temperature	20 to 24 °C
Humidity	< 60 %

3.5.2 Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests.

For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.

The maximum rated power of WWAN and WLAN is listed in "Tune-Up Procedure" exhibit; The scaling factor is calculated according to the difference between measured output power and maximum tolerance power on this device.

4. Specific Absorption Rate (SAR)

4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

Page Number : 10 of 42
Report Issued Date : Dec. 17, 2012
Report Version : Rev. 01

5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

5.1.1 E-Field Probe Specification

<EX3DV4 Probe>


Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Fig 5.2 Photo of EX3DV4

5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.3 Photo of DAE

5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig 5.4 Photo of DASY5

5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Fig 5.5 Photo of Server for DASY5

5.5 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
Measurement Areas	Left Hand, Right Hand, Flat Phantom



Fig 5.6 Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

5.6 Device Holder

<Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.7 Device Holder

5.7 Data Storage and Evaluation

5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lossy media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

Probe parameters :	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters :	- Frequency	f
	- Crest factor	cf
Media parameters :	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i, (i = x, y, z)
 U_i = input signal of channel i, (i = x, y, z)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated :

$$\text{E-field Probes : } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field Probes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with V_i = compensated signal of channel i, (i = x, y, z)
 Norm_i = sensor sensitivity of channel i, (i = x, y, z), $\mu\text{V}/(\text{V/m})^2$ for E-field Probes
 ConvF = sensitivity enhancement in solution
 a_{ij} = sensor sensitivity factors for H-field probes
 f = carrier frequency [GHz]
 E_i = electric field strength of channel i in V/m
 H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm^3

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 18, 2011	Nov. 16, 2013
SPEAG	1750MHz System Validation Kit	D1750V2	1069	Jul. 13, 2012	Jul. 12, 2013
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2011	Nov. 16, 2013
SPEAG	2450MHz System Validation Kit	D2450V2	736	Jul. 25, 2011	Jul. 24, 2013
SPEAG	Data Acquisition Electronics	DAE3	360	Nov. 15, 2012	Nov. 14, 2013
SPEAG	Dosimetric E-Field Probe	EX3DV4	3857	Jun. 20, 2012	Jun. 19, 2013
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1477	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1479	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201074235	Nov. 29, 2012	Nov. 28, 2013
Agilent	Wireless Communication Test Set	E5515C	MY48367160	Oct. 25, 2012	Oct. 24, 2013
R&S	Universal Radio Communication Tester	CMU200	116456	Sep. 19, 2012	Sep. 18, 2013
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	Apr. 13, 2012	Apr. 12, 2013
R&S	Signal Generator	SMR40	100455	Dec. 30, 2011	Dec. 29, 2012
Agilent	Power Meter	E4416A	MY45101555	Aug. 22, 2012	Aug. 21, 2013
Agilent	Power Sensor	E9327A	MY44421198	Aug. 22, 2012	Aug. 21, 2013
R&S	Spectrum Analyzer	FSP30	101399	Jun. 01, 2012	May 31, 2013

Table 5.1 Test Equipment List

Note:

1. The calibration certificate of DASY can be referred to appendix C of this report.
2. Referring to KDB 450824 D02, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole D835V2, SN: 4d091, D1900V2, SN: 5d118, D2450V2, SN: 736 can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.



Fig 6.1 Photo of Liquid Height for Head SAR



Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7

Table 6.1 Recipes of Tissue Simulating Liquid

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

The following table shows the measuring results for simulating liquid.

Freq. (MHz)	Liquid Type	Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	21.5	0.905	42.233	0.90	41.5	0.56	1.77	±5	Dec. 11, 2012
1750	Head	21.6	1.38	41.322	1.37	40.1	0.73	3.05	±5	Dec. 14, 2012
1900	Head	21.1	1.426	38.855	1.40	40.0	1.86	-2.86	±5	Dec. 11, 2012
2450	Head	21.2	1.861	39.575	1.80	39.2	3.39	0.96	±5	Dec. 12, 2012
835	Body	21.3	0.983	54.864	0.97	55.2	1.34	-0.61	±5	Dec. 11, 2012
1750	Body	21.5	1.512	55.585	1.49	53.4	1.48	4.09	±5	Dec. 13, 2012
1900	Body	21.4	1.555	53.699	1.52	53.3	2.30	0.75	±5	Dec. 12, 2012
2450	Body	21.2	2.002	53.464	1.95	52.7	2.67	1.45	±5	Dec. 12, 2012

Table 6.2 Measuring Results for Simulating Liquid

7. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

7.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

7.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 7.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 24 dBm (250 mW) before dipole is connected.



Fig 7.2 Photo of Dipole Setup

7.3 Verification Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Table 7.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Frequency (MHz)	Liquid Type	Targeted SAR _{1g} (W/kg)	Measured SAR _{1g} (W/kg)	Normalized SAR _{1g} (W/kg)	Deviation (%)
Dec. 11, 2012	835	Head	9.40	2.33	9.32	-0.85
Dec. 14, 2012	1750	Head	36.4	8.78	35.12	-3.52
Dec. 11, 2012	1900	Head	40.3	10	40.00	-0.74
Dec. 12, 2012	2450	Head	54.8	13.8	55.20	0.73
Dec. 11, 2012	835	Body	9.42	2.28	9.12	-3.18
Dec. 13, 2012	1750	Body	37.1	8.97	35.88	-3.29
Dec. 12, 2012	1900	Body	41.8	10.1	40.40	-3.35
Dec. 12, 2012	2450	Body	52.3	13.4	53.60	2.49

Table 7.1 Target and Measurement SAR after Normalized

8. EUT Testing Position

This EUT was tested in ten different positions. They are right cheek, right tilted, left cheek, left tilted, Front of the EUT with phantom 1 cm gap, Back of the EUT with phantom 1 cm gap, Top Side of the EUT with phantom 1 cm gap, Bottom Side of the EUT with phantom 1 cm gap, Right Side of the EUT with phantom 1 cm gap, and Left Side of the EUT with phantom 1 cm gap, as illustrated below:

8.1 Define two imaginary lines on the handset

- The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig 9.1 Illustration for Handset Vertical and Horizontal Reference Lines

8.2 Cheek Position

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).




Fig 9.2 Illustration for Cheek Position

8.3 Tilted Position

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).




Fig 9.3 Illustration for Tilted Position

8.4 Body Worn Position

- (a) To position the device parallel to the phantom surface.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1 cm.




Fig 9.4 Illustration for Body Worn Position

<EUT Setup Photos>

Please refer to Appendix E for the test setup photos.

9. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% EUTy factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Appendix E demonstrates.
- (e) Set scan area, grid size and other setting on the DASY software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

9.3 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remains in the same test position for all measurements and all volume scans use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scans are completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculate the multiband SAR.

9.4 SAR Averaged Methods

In DASy, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.


Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

9.5 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

10. SAR Test Configurations

10.1 Exposure Positions Consideration



Antennas	Wireless Interface
WWAN Antenna (Tx / Rx)	GSM850/1900 WCDMA Band II/IV/V
WLAN & Bluetooth Antenna (Tx / Rx)	WLAN 2.4GHz Bluetooth

Sides for SAR tests; Hotspot mode Test distance: 10 mm						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	YES	YES	NO	YES	YES	YES
WLAN & Bluetooth	YES	YES	YES	NO	YES	NO

Note:

1. Head/Body-worn/Hotspot mode SAR assessments are required.
2. Referring to KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
3. For WWAN antenna, SAR measurement at Top side is not required since the distance between WWAN transmitting antenna and surface or edge $> 25\text{mm}$.
4. For WLAN & Bluetooth antenna, SAR measurements Bottom / Left sides are not required since the distance between WLAN & Bluetooth transmitting antenna and surface or edge $> 25\text{mm}$.

10.2 Conducted RF Output Power (Unit: dBm)
<GSM/GPRS/EDGE/DTM>

Burst Average Power						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1 Tx slot)	32.88	32.94	32.89	29.86	29.80	29.81
GPRS (GMSK, 1 Tx slot) – CS1	32.87	32.93	32.88	29.85	29.79	29.80
GPRS (GMSK, 2 Tx slots) – CS1	29.80	29.86	29.81	29.84	29.78	29.79
GPRS (GMSK, 3 Tx slots) – CS1	29.64	29.66	29.65	29.08	29.04	29.05
GPRS (GMSK, 4 Tx slots) – CS1	28.40	28.45	28.43	27.85	27.79	27.83
EDGE (GMSK, 1 Tx slot) – MCS1	32.86	32.91	32.86	29.85	29.79	29.80
EDGE (GMSK, 2 Tx slots) – MCS1	29.78	29.85	29.78	29.84	29.78	29.79
EDGE (GMSK, 3 Tx slots) – MCS1	29.63	29.65	29.64	29.06	28.99	29.01
EDGE (GMSK, 4 Tx slots) – MCS1	28.25	28.29	28.26	27.83	27.78	27.79
EDGE (8PSK, 1 Tx slot) – MCS5	27.08	27.13	27.09	25.86	25.83	25.87
EDGE (8PSK, 2 Tx slots) – MCS5	27.06	27.11	27.07	25.84	25.79	25.86
EDGE (8PSK, 3 Tx slots) – MCS5	26.24	26.28	26.24	25.01	24.97	25.01
EDGE (8PSK, 4 Tx slots) – MCS5	25.05	25.10	25.06	23.76	23.74	23.77
DTM 5	GSM (GMSK, 1 Tx slot)	29.53	29.58	29.52	29.60	29.55
	GPRS (GMSK, 1 Tx slot) – CS1	29.52	29.57	29.51	29.59	29.54
DTM 9	GSM (GMSK, 1 Tx slot)	29.52	29.57	29.51	29.59	29.54
	GPRS (GMSK, 1 Tx slot) – CS1	29.51	29.56	29.50	29.58	29.53
DTM 11	GSM (GMSK, 1 Tx slot)	29.51	29.57	29.50	28.78	28.75
	GPRS (GMSK, 2 Tx slots) – CS1	29.50	29.56	29.49	28.77	28.74
DTM 5	GSM (GMSK, 1 Tx slot)	29.52	29.57	29.51	29.59	29.54
	EDGE (8PSK, 1 Tx slot) – MCS5	29.51	29.56	29.50	29.58	29.53
DTM 9	GSM (GMSK, 1 Tx slot)	29.50	29.56	29.50	29.59	29.54
	EDGE (8PSK, 1 Tx slot) – MCS5	29.49	29.55	29.49	29.58	29.53
DTM 11	GSM (GMSK, 1 Tx slot)	29.49	29.55	29.49	28.77	28.74
	EDGE (8PSK, 2 Tx slots) – MCS5	29.48	29.54	29.48	28.76	28.73

Source-Based Time-Averaged Power						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1 Tx slot)	23.88	23.94	23.89	20.86	20.80	20.81
GPRS (GMSK, 1 Tx slot) – CS1	23.87	23.93	23.88	20.85	20.79	20.80
GPRS (GMSK, 2 Tx slots) – CS1	23.80	23.86	23.81	23.84	23.78	23.79
GPRS (GMSK, 3 Tx slots) – CS1	25.38	25.40	25.39	24.82	24.78	24.79
GPRS (GMSK, 4 Tx slots) – CS1	25.40	25.45	25.43	24.85	24.79	24.83
EDGE (GMSK, 1 Tx slot) – MCS1	23.86	23.91	23.86	20.85	20.79	20.80
EDGE (GMSK, 2 Tx slots) – MCS1	23.78	23.85	23.78	23.84	23.78	23.79
EDGE (GMSK, 3 Tx slots) – MCS1	25.37	25.39	25.38	24.80	24.73	24.75
EDGE (GMSK, 4 Tx slots) – MCS1	25.25	25.29	25.26	24.83	24.78	24.79
EDGE (8PSK, 1 Tx slot) – MCS5	18.08	18.13	18.09	16.86	16.83	16.87
EDGE (8PSK, 2 Tx slots) – MCS5	21.06	21.11	21.07	19.84	19.79	19.86
EDGE (8PSK, 3 Tx slots) – MCS5	21.98	22.02	21.98	20.75	20.71	20.75
EDGE (8PSK, 4 Tx slots) – MCS5	22.05	22.10	22.06	20.76	20.74	20.77
DTM 5	GSM (GMSK, 1 Tx slot)	23.50	23.55	23.49	23.57	23.51
	GPRS (GMSK, 1 Tx slot) – CS1					
DTM 9	GSM (GMSK, 1 Tx slot)	23.49	23.54	23.48	23.56	23.51
	GPRS (GMSK, 1 Tx slot) – CS1					
DTM 11	GSM (GMSK, 1 Tx slot)	25.24	25.30	25.23	24.51	24.45
	GPRS (GMSK, 2 Tx slots) – CS1					
DTM 5	GSM (GMSK, 1 Tx slot)	23.49	23.54	23.48	23.56	23.51
	EDGE (8PSK, 1 Tx slot) – MCS5					
DTM 9	GSM (GMSK, 1 Tx slot)	23.47	23.53	23.47	23.56	23.51
	EDGE (8PSK, 1 Tx slot) – MCS5					
DTM 11	GSM (GMSK, 1 Tx slot)	25.22	25.28	25.22	24.50	24.44
	EDGE (8PSK, 2 Tx slots) – MCS5					

Remark: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time averaged power = Maximum burst averaged power (1 Tx slot) - 9 dB

Source based time averaged power = Maximum burst averaged power (2 Tx slots) - 6 dB

Source based time averaged power = Maximum burst averaged power (3 Tx slots) - 4.26 dB

Source based time averaged power = Maximum burst averaged power (4 Tx slots) - 3 dB

Note:

1. For Head SAR testing, GSM and DTM should be evaluated, therefore the EUT was set in DTM 11 for GSM850 and set in DTM 11 for GSM1900 due to its highest source-based time-average power.
2. For Body SAR testing, GSM, GPRS, EDGE and DTM should be evaluated, therefore the EUT was set in GPRS (4 Tx slots) for GSM850 and GSM1900 due to its highest source-based time-average power.
3. Per KDB 447498, the maximum output power channel is used for SAR testing and for further SAR test reduction.
4. EDGE tests with MCS1 setting, GMSK modulation. Burst average power with MCS5 setting 8 PSK modulation, is provided voluntarily for reference.

<WCDMA>

Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency (MHz)	826.4	836.4	846.6	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6
AMR	23.64	23.57	23.59	23.60	23.55	23.51	23.77	23.70	23.61
RMC 12.2K	23.66	23.58	23.61	23.63	23.57	23.53	23.79	23.73	23.64
HSDPA Subtest-1	23.43	23.38	23.37	23.13	23.00	22.92	23.35	23.21	23.11
HSDPA Subtest-2	22.45	22.38	22.37	22.16	22.02	21.95	22.40	22.25	22.13
HSDPA Subtest-3	22.20	22.12	22.12	21.94	21.78	21.73	22.15	22.02	21.92
HSDPA Subtest-4	21.96	21.89	21.87	21.70	21.53	21.49	21.90	21.77	21.66
HSUPA Subtest-1	22.38	22.32	22.31	21.76	21.59	21.61	22.35	22.24	22.20
HSUPA Subtest-2	20.39	20.32	20.33	19.72	19.58	19.60	20.39	20.24	20.25
HSUPA Subtest-3	21.15	21.09	21.06	20.52	20.36	20.38	21.13	21.00	20.90
HSUPA Subtest-4	20.64	20.59	20.57	19.95	19.79	19.92	20.60	20.53	20.43
HSUPA Subtest-5	21.57	21.51	21.52	20.95	20.83	20.87	21.57	21.47	21.40

MPR (dB)										
3GPP MPR	Subtest	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
0	HSDPA Subtest-1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
0	HSDPA Subtest-2	0.98	1.00	1.00	0.97	0.98	0.97	0.95	0.96	0.98
≤ 0.5	HSDPA Subtest-3	1.23	1.26	1.25	1.19	1.22	1.19	1.20	1.19	1.19
≤ 0.5	HSDPA Subtest-4	1.47	1.49	1.50	1.43	1.47	1.43	1.45	1.44	1.45
0	HSUPA Subtest-1	-0.81	-0.81	-0.79	-0.81	-0.76	-0.74	-0.78	-0.77	-0.80
≤ 2	HSUPA Subtest-2	1.18	1.19	1.19	1.23	1.25	1.27	1.18	1.23	1.15
≤ 1	HSUPA Subtest-3	0.42	0.42	0.46	0.43	0.47	0.49	0.44	0.47	0.50
≤ 2	HSUPA Subtest-4	0.93	0.92	0.95	1.00	1.04	0.95	0.97	0.94	0.97
0	HSUPA Subtest-5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Note:

- For Head SAR, per KDB 941225 D01, RMC 12.2kbps setting is used to evaluate SAR. If AMR 12.2kbps power is < 1/4 dB higher than RMC, SAR tests with AMR 12.2kbps can be excluded.
- For Body SAR, per KDB 941225 D01, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA subset-1 and HSUPA subset-5 output power is < 1/4 dB higher than RMC, and SAR with RMC 12.2kbps setting is ≤ 1.2W/kg, HSDPA and HSUPA SAR evaluation can be excluded.
- EUT is designed to follow the MPR of 3GPP Table 5.2B.1 specification. In production units, MPR result deviation from 3GPP is expected; the implementation and expected deviation is detailed in tune-up procedure exhibit.

<WLAN 2.4GHz>

Mode	Channel	Frequency (MHz)	Average power (dBm)			
			Data Rate (bps)			
			1M	2M	5.5M	11M
802.11b	CH 01	2412	13.73	13.62	13.86	13.75
	CH 06	2437	13.87	14.01	14.24	14.16
	CH 11	2462	14.72	14.50	14.68	14.64

Mode	Channel	Frequency (MHz)	Average power (dBm)							
			Data Rate (bps)							
			6M	9M	12M	18M	24M	36M	48M	54M
802.11g	CH 01	2412	12.30	12.19	12.32	12.15	12.21	12.16	12.27	12.23
	CH 06	2437	12.56	12.58	12.49	12.61	12.67	12.49	12.57	12.61
	CH 11	2462	12.98	12.89	12.88	12.97	12.91	12.93	12.96	12.93

Mode	Channel	Frequency (MHz)	Average power (dBm)							
			Data Rate (bps)							
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n HT20	CH 01	2412	12.05	12.13	12.12	12.08	12.06	12.10	11.93	12.02
	CH 06	2437	12.31	12.42	12.49	12.53	12.41	12.33	12.28	12.31
	CH 11	2462	12.97	12.92	12.87	12.84	12.85	12.74	12.61	12.65

Note:

1. Per KDB 248227, choose the highest output power channel to test SAR and determine further SAR exclusion
2. Per KDB 248227, 11g and 11n output power is less than 1/4 dB higher than 11b mode, thus the SAR can be excluded.
3. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4 dB higher than those measured at the lowest data rate.

<Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power (dBm)								
			Data Rate								
			DH1	DH3	DH5	2DH1	2DH3	2DH5	3DH1	3DH3	3DH5
Bluetooth	CH 00	2402	7.12	6.86	6.74	4.98	4.30	4.69	4.86	4.38	4.72
	CH 39	2441	4.86	4.50	4.49	2.73	2.33	2.25	2.77	2.54	4.82
	CH 78	2480	3.81	3.32	3.50	1.78	1.41	1.47	1.69	1.37	1.46

11. SAR Test Results

11.1 Test Records for Head SAR Test

<GSM>

Plot No.	Band	Mode	Test Position	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
1	GSM850	DTM 11	Right Cheek	189	29.57	30	1.104	0.728	0.804	0.03
2	GSM850	DTM 11	Right Tilted	189	29.57	30	1.104	0.446	0.492	-0.10
3	GSM850	DTM 11	Left Cheek	189	29.57	30	1.104	0.671	0.741	0.08
4	GSM850	DTM 11	Left Tilted	189	29.57	30	1.104	0.460	0.508	0.14
5	GSM1900	DTM 11	Right Cheek	512	28.78	29.5	1.180	0.394	0.465	0.03
6	GSM1900	DTM 11	Right Tilted	512	28.78	29.5	1.180	0.068	0.080	-0.04
7	GSM1900	DTM 11	Left Cheek	512	28.78	29.5	1.180	0.358	0.423	0.02
8	GSM1900	DTM 11	Left Tilted	512	28.78	29.5	1.180	0.115	0.136	0.04

Note: Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WCDMA>

Plot No.	Band	Mode	Test Position	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
9	WCDMA Band V	RMC12.2K	Right Cheek	4132	23.66	24	1.081	0.384	0.415	0.03
10	WCDMA Band V	RMC12.2K	Right Tilted	4132	23.66	24	1.081	0.250	0.270	-0.03
11	WCDMA Band V	RMC12.2K	Left Cheek	4132	23.66	24	1.081	0.357	0.386	0.05
12	WCDMA Band V	RMC12.2K	Left Tilted	4132	23.66	24	1.081	0.236	0.255	0.07
62	WCDMA Band IV	RMC12.2K	Right Cheek	1312	23.79	24.3	1.125	0.497	0.559	-0.11
63	WCDMA Band IV	RMC12.2K	Right Tilted	1312	23.79	24.3	1.125	0.099	0.111	-0.03
64	WCDMA Band IV	RMC12.2K	Left Cheek	1312	23.79	24.3	1.125	0.388	0.436	0.17
65	WCDMA Band IV	RMC12.2K	Left Tilted	1312	23.79	24.3	1.125	0.138	0.155	0.15
13	WCDMA Band II	RMC12.2K	Right Cheek	9262	23.63	24	1.089	0.375	0.408	0.07
14	WCDMA Band II	RMC12.2K	Right Tilted	9262	23.63	24	1.089	0.060	0.065	0.06
15	WCDMA Band II	RMC12.2K	Left Cheek	9262	23.63	24	1.089	0.398	0.433	0.05
16	WCDMA Band II	RMC12.2K	Left Tilted	9262	23.63	24	1.089	0.099	0.108	0.06

Note: Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
17	WLAN2.4G	802.11b	Right Cheek	11	14.72	15	1.067	0.088	0.094	-0.037
18	WLAN2.4G	802.11b	Right Tilted	11	14.72	15	1.067	0.072	0.077	0.05
19	WLAN2.4G	802.11b	Left Cheek	11	14.72	15	1.067	0.127	0.135	0.01
20	WLAN2.4G	802.11b	Left Tilted	11	14.72	15	1.067	0.100	0.107	-0.09

Note: Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

11.2 Test Records for Hotspot SAR Test

<GSM>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
21	GSM850	GPRS (4 Tx slots)	Front	1	189	28.45	29	1.135	0.644	0.731	0.04
22	GSM850	GPRS (4 Tx slots)	Back	1	189	28.45	29	1.135	0.905	1.027	-0.02
23	GSM850	GPRS (4 Tx slots)	Left Side	1	189	28.45	29	1.135	0.541	0.614	0.034
24	GSM850	GPRS (4 Tx slots)	Right Side	1	189	28.45	29	1.135	0.701	0.796	-0.0013
25	GSM850	GPRS (4 Tx slots)	Bottom Side	1	189	28.45	29	1.135	0.204	0.232	0.09
26	GSM850	GPRS (4 Tx slots)	Back	1	128	28.40	29	1.148	0.845	0.970	0.03
27	GSM850	GPRS (4 Tx slots)	Back	1	251	28.43	29	1.140	0.939	1.071	0.14
29	GSM1900	GPRS (4 Tx slots)	Front	1	512	27.85	28.5	1.161	0.583	0.677	0.08
30	GSM1900	GPRS (4 Tx slots)	Back	1	512	27.85	28.5	1.161	0.876	1.017	-0.02
31	GSM1900	GPRS (4 Tx slots)	Left Side	1	512	27.85	28.5	1.161	0.249	0.289	0.03
32	GSM1900	GPRS (4 Tx slots)	Right Side	1	512	27.85	28.5	1.161	0.175	0.203	0.16
33	GSM1900	GPRS (4 Tx slots)	Bottom Side	1	512	27.85	28.5	1.161	0.913	1.060	-0.14
34	GSM1900	GPRS (4 Tx slots)	Back	1	661	27.79	28.5	1.178	0.911	1.073	0.0081
35	GSM1900	GPRS (4 Tx slots)	Back	1	810	27.83	28.5	1.167	0.925	1.079	-0.02
36	GSM1900	GPRS (4 Tx slots)	Bottom Side	1	661	27.79	28.5	1.178	0.898	1.057	-0.06
37	GSM1900	GPRS (4 Tx slots)	Bottom Side	1	810	27.83	28.5	1.167	0.899	1.049	-0.06

Note:

1. Per KDB 941225 D06, for EUT dimension $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
2. As in (1), SAR for Front/Back/Bottom Side/Left Side/Right Side is necessary.
3. Per KDB 447498 if the highest output channel SAR for each exposure position $\leq 0.8 \text{ W/kg}$ other channels SAR tests are not necessary.

<WCDMA>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
39	WCDMA Band V	RMC12.2K	Front	1	4132	23.66	24	1.081	0.468	0.506	-0.04
40	WCDMA Band V	RMC12.2K	Back	1	4132	23.66	24	1.081	0.650	0.703	0.07
41	WCDMA Band V	RMC12.2K	Left Side	1	4132	23.66	24	1.081	0.406	0.439	-0.0051
42	WCDMA Band V	RMC12.2K	Right Side	1	4132	23.66	24	1.081	0.510	0.552	0.01
43	WCDMA Band V	RMC12.2K	Bottom Side	1	4132	23.66	24	1.081	0.135	0.146	0.12
66	WCDMA Band IV	RMC12.2K	Front	1	1312	23.79	24.3	1.125	0.818	0.920	0.03
67	WCDMA Band IV	RMC12.2K	Back	1	1312	23.79	24.3	1.125	0.923	1.038	0.02
68	WCDMA Band IV	RMC12.2K	Left Side	1	1312	23.79	24.3	1.125	0.291	0.327	0.02
69	WCDMA Band IV	RMC12.2K	Right Side	1	1312	23.79	24.3	1.125	0.198	0.223	-0.01
70	WCDMA Band IV	RMC12.2K	Bottom Side	1	1312	23.79	24.3	1.125	1.200	1.350	-0.07
71	WCDMA Band IV	RMC12.2K	Front	1	1413	23.73	24.3	1.140	0.743	0.847	-0.02
72	WCDMA Band IV	RMC12.2K	Front	1	1513	23.64	24.3	1.164	0.750	0.873	0.02
73	WCDMA Band IV	RMC12.2K	Back	1	1413	23.73	24.3	1.140	0.872	0.994	0.08
74	WCDMA Band IV	RMC12.2K	Back	1	1513	23.64	24.3	1.164	0.886	1.031	-0.08
78	WCDMA Band IV	RMC12.2K	Bottom Side	1	1413	23.73	24.3	1.140	1.170	1.334	-0.12
79	WCDMA Band IV	RMC12.2K	Bottom Side	1	1513	23.64	24.3	1.164	1.210	1.409	-0.13
45	WCDMA Band II	RMC12.2K	Front	1	9262	23.63	24	1.089	0.686	0.747	0.02
46	WCDMA Band II	RMC12.2K	Back	1	9262	23.63	24	1.089	0.941	1.025	0.03
47	WCDMA Band II	RMC12.2K	Left Side	1	9262	23.63	24	1.089	0.261	0.284	0.14
48	WCDMA Band II	RMC12.2K	Right Side	1	9262	23.63	24	1.089	0.213	0.232	0.08
49	WCDMA Band II	RMC12.2K	Bottom Side	1	9262	23.63	24	1.089	1.080	1.176	-0.12
50	WCDMA Band II	RMC12.2K	Back	1	9400	23.57	24	1.104	0.884	0.976	-0.04
51	WCDMA Band II	RMC12.2K	Back	1	9583	23.53	24	1.114	0.944	1.052	-0.07
52	WCDMA Band II	RMC12.2K	Bottom Side	1	9400	23.57	24	1.104	0.986	1.089	-0.08
53	WCDMA Band II	RMC12.2K	Bottom Side	1	9583	23.53	24	1.114	1.030	1.148	-0.05

Note:

- Per KDB 941225 D06, for EUT dimension $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
- As in (1), SAR for Front/Back/Bottom Side/Left Side/Right Side is necessary.
- Per KDB 447498, if the highest output channel SAR for each exposure position $\leq 0.8 \text{ W/kg}$ other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
57	WLAN2.4G	802.11b	Front	1	11	14.72	15	1.067	0.032	0.034	-0.02
58	WLAN2.4G	802.11b	Back	1	11	14.72	15	1.067	0.088	0.094	0.07
59	WLAN2.4G	802.11b	Right Side	1	11	14.72	15	1.067	0.037	0.039	0.03
60	WLAN2.4G	802.11b	Top Side	1	11	14.72	15	1.067	0.034	0.036	0.06

Note:

- Per KDB 941225 D06, for EUT dimension $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
- As in (1), SAR for Front/Back/Top Side/Right Side is necessary.
- Per KDB 248227, if the highest output channel SAR for each exposure position $\leq 0.8 \text{ W/kg}$ other channels SAR tests are not necessary.

11.3 Test Records for Body-worn SAR Test

<GSM>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Headset	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
21	GSM850	GPRS (4 Tx slots)	Front	1	189	-	28.45	29	1.135	0.644	0.731	0.04
22	GSM850	GPRS (4 Tx slots)	Back	1	189	-	28.45	29	1.135	0.905	1.027	-0.02
26	GSM850	GPRS (4 Tx slots)	Back	1	128	-	28.40	29	1.148	0.845	0.970	0.03
27	GSM850	GPRS (4 Tx slots)	Back	1	251	-	28.43	29	1.140	0.939	1.071	0.14
28	GSM850	GSM	Back	1	251	w/headset	32.89	33.5	1.151	0.593	0.682	-0.03
29	GSM1900	GPRS (4 Tx slots)	Front	1	512	-	27.85	28.5	1.161	0.583	0.677	0.08
30	GSM1900	GPRS (4 Tx slots)	Back	1	512	-	27.85	28.5	1.161	0.876	1.017	-0.02
34	GSM1900	GPRS (4 Tx slots)	Back	1	661	-	27.79	28.5	1.178	0.911	1.073	0.0081
35	GSM1900	GPRS (4 Tx slots)	Back	1	810	-	27.83	28.5	1.167	0.925	1.079	-0.02
38	GSM1900	GSM	Back	1	810	w/headset	29.81	30.5	1.172	0.398	0.467	0.03

Note:

- Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
- "w/headset" in the headset column means the earphone is plugged during SAR testing.

<WCDMA>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Headset	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
39	WCDMA Band V	RMC12.2K	Front	1	4132	-	23.66	24	1.081	0.468	0.506	-0.04
40	WCDMA Band V	RMC12.2K	Back	1	4132	-	23.66	24	1.081	0.650	0.703	0.07
44	WCDMA Band V	RMC12.2K	Back	1	4132	w/headset	23.66	24	1.081	0.541	0.585	0.04
66	WCDMA Band IV	RMC12.2K	Front	1	1312	-	23.79	24.3	1.125	0.818	0.920	0.03
67	WCDMA Band IV	RMC12.2K	Back	1	1312	-	23.79	24.3	1.125	0.923	1.038	0.02
71	WCDMA Band IV	RMC12.2K	Front	1	1413	-	23.73	24.3	1.140	0.743	0.847	-0.02
72	WCDMA Band IV	RMC12.2K	Front	1	1513	-	23.64	24.3	1.164	0.750	0.873	0.02
73	WCDMA Band IV	RMC12.2K	Back	1	1413	-	23.73	24.3	1.140	0.872	0.994	0.08
74	WCDMA Band IV	RMC12.2K	Back	1	1513	-	23.64	24.3	1.164	0.886	1.031	-0.08
75	WCDMA Band IV	RMC12.2K	Back	1	1312	w/headset	23.79	24.3	1.125	0.899	1.011	0.02
76	WCDMA Band IV	RMC12.2K	Back	1	1413	w/headset	23.73	24.3	1.140	0.850	0.969	-0.03
77	WCDMA Band IV	RMC12.2K	Back	1	1513	w/headset	23.64	24.3	1.164	0.904	1.052	0.07
45	WCDMA Band II	RMC12.2K	Front	1	9262	-	23.63	24	1.089	0.686	0.747	0.02
46	WCDMA Band II	RMC12.2K	Back	1	9262	-	23.63	24	1.089	0.941	1.025	0.03
50	WCDMA Band II	RMC12.2K	Back	1	9400	-	23.57	24	1.104	0.884	0.976	-0.04
51	WCDMA Band II	RMC12.2K	Back	1	9583	-	23.53	24	1.114	0.944	1.052	-0.07
54	WCDMA Band II	RMC12.2K	Back	1	9583	w/headset	23.53	24	1.114	0.966	1.076	-0.09
55	WCDMA Band II	RMC12.2K	Back	1	9262	w/headset	23.63	24	1.089	1.010	1.100	-0.07
56	WCDMA Band II	RMC12.2K	Back	1	9400	w/headset	23.57	24	1.104	0.930	1.027	-0.11

Note:

- Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
- "w/headset" in the headset column means the earphone is plugged during SAR testing.

**<WLAN>**

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Headset	Output Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	SAR _{1g} (W/kg)	Scaled SAR _{1g} (W/kg)	Power Drift (dB)
57	WLAN2.4G	802.11b	Front	1	11	-	14.72	15	1.067	0.032	0.034	-0.02
58	WLAN2.4G	802.11b	Back	1	11	-	14.72	15	1.067	0.088	0.094	0.07
61	WLAN2.4G	802.11b	Back	1	11	w/headset	14.72	15	1.067	0.059	0.063	0.11

Note:

1. Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
2. "w/headset" in the headset column means the earphone is plugged during SAR testing.

11.4 Simultaneous Multi-band Transmission Analysis

No.	Applicable Simultaneous Transmission Combination
1	GSM / WCDMA + Bluetooth
2	GSM / WCDMA + WLAN 2.4G

Note:

1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. GSM and WCDMA share the same antenna, and cannot transmit simultaneously.
3. Per KDB 648474 D01, Bluetooth output power $\leq 2 \cdot P_{Ref}$ and the distance to WWAN transmitting antenna $\geq 5\text{cm}$, therefore, stand-alone SAR is not required; the simultaneous transmission SAR for WWAN and Bluetooth was not required, because Bluetooth standalone SAR is not required and the maximum WWAN scaled SAR (1.409 W/kg), so the SAR summation is less than 1.6 W/kg..
4. Per KDB 648474 D01, the simultaneous transmission SAR for WWAN and WLAN was not required, because the SAR scalar summation (Head: 0.90 W/kg; Body: 1.41 W/kg) is less than 1.6 W/kg.

<Head SAR>

Position	WWAN			WLAN		Max. SAR Sum	Scaled WWAN (W/kg)	Scaled WLAN (W/kg)	Scaled WWAN + Scaled WLAN
	WWAN Band	Plot No	Max. WWAN SAR (W/kg)	Plot No	Max. WLAN SAR (W/kg)				
Right Cheek	GSM850	#01	0.728	#17	0.088	0.82	0.804	0.094	0.90
	GSM1900	#05	0.394	#17	0.088	0.48	0.465	0.094	0.56
	WCDMA Band V	#09	0.384	#17	0.088	0.47	0.415	0.094	0.51
	WCDMA Band II	#13	0.375	#17	0.088	0.46	0.408	0.094	0.50
	WCDMA Band IV	#62	0.497	#17	0.088	0.59	0.559	0.094	0.65
Right Tilted	GSM850	#02	0.446	#18	0.072	0.52	0.492	0.077	0.57
	GSM1900	#06	0.068	#18	0.072	0.14	0.080	0.077	0.16
	WCDMA Band V	#10	0.250	#18	0.072	0.32	0.270	0.077	0.35
	WCDMA Band II	#14	0.060	#18	0.072	0.13	0.065	0.077	0.14
	WCDMA Band IV	#63	0.099	#18	0.072	0.17	0.111	0.077	0.19
Left Cheek	GSM850	#03	0.671	#19	0.127	0.80	0.741	0.135	0.88
	GSM1900	#07	0.358	#19	0.127	0.49	0.423	0.135	0.56
	WCDMA Band V	#11	0.357	#19	0.127	0.48	0.386	0.135	0.52
	WCDMA Band II	#15	0.398	#19	0.127	0.53	0.433	0.135	0.57
	WCDMA Band IV	#64	0.388	#19	0.127	0.52	0.436	0.135	0.57
Left Tilted	GSM850	#04	0.460	#20	0.100	0.56	0.508	0.107	0.62
	GSM1900	#08	0.115	#20	0.100	0.22	0.136	0.107	0.24
	WCDMA Band V	#12	0.236	#20	0.100	0.34	0.255	0.107	0.36
	WCDMA Band II	#16	0.099	#20	0.100	0.20	0.108	0.107	0.22
	WCDMA Band IV	#65	0.138	#20	0.100	0.24	0.155	0.107	0.26

Note:

1. The maximum SAR summation is calculated based on the same configuration and test position.
2. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements
3. If 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.
4. If 1g-SAR scalar summation > 1.6W/kg, SPLSR calculation is necessary.

<Hotspot SAR>

Position	WWAN			WLAN		Max. SAR Sum	Scaled WWAN (W/kg)	Scaled WLAN (W/kg)	Scaled WWAN + Scaled WLAN
	WWAN Band	Plot No	Max. WWAN SAR (W/kg)	Plot No	Max. WLAN SAR (W/kg)				
Front	GSM850	#21	0.644	#57	0.032	0.68	0.731	0.034	0.77
	GSM1900	#29	0.583	#57	0.032	0.62	0.677	0.034	0.71
	WCDMA Band V	#39	0.468	#57	0.032	0.50	0.506	0.034	0.54
	WCDMA Band II	#45	0.686	#57	0.032	0.72	0.747	0.034	0.78
	WCDMA Band IV	#66	0.818	#57	0.032	0.85	0.920	0.034	0.95
Back	GSM850	#27	0.939	#58	0.088	1.03	1.071	0.094	1.17
	GSM1900	#35	0.925	#58	0.088	1.01	1.079	0.094	1.17
	WCDMA Band V	#40	0.650	#58	0.088	0.74	0.703	0.094	0.80
	WCDMA Band II	#51	0.944	#58	0.088	1.03	1.052	0.094	1.15
	WCDMA Band IV	#67	0.923	#58	0.088	1.01	1.038	0.094	1.13
Left Side	GSM850	#23	0.541			0.54	0.614		0.61
	GSM1900	#31	0.249			0.25	0.289		0.29
	WCDMA Band V	#41	0.406			0.41	0.439		0.44
	WCDMA Band II	#47	0.261			0.26	0.284		0.28
	WCDMA Band IV	#68	0.291			0.29	0.327		0.33
Right Side	GSM850	#24	0.701	#59	0.037	0.74	0.796	0.039	0.84
	GSM1900	#32	0.175	#59	0.037	0.21	0.203	0.039	0.24
	WCDMA Band V	#42	0.510	#59	0.037	0.55	0.552	0.039	0.59
	WCDMA Band II	#48	0.213	#59	0.037	0.25	0.232	0.039	0.27
	WCDMA Band IV	#69	0.198	#59	0.037	0.24	0.223	0.039	0.26
Top Side	GSM850			#60	0.034	0.03		0.036	0.04
	GSM1900			#60	0.034	0.03		0.036	0.04
	WCDMA Band V			#60	0.034	0.03		0.036	0.04
	WCDMA Band II			#60	0.034	0.03		0.036	0.04
	WCDMA Band IV			#60	0.034	0.03		0.036	0.04
Bottom Side	GSM850	#25	0.204			0.20	0.232		0.23
	GSM1900	#33	0.913			0.91	1.060		1.06
	WCDMA Band V	#43	0.135			0.14	0.146		0.15
	WCDMA Band II	#49	1.080			1.08	1.176		1.18
	WCDMA Band IV	#79	1.210			1.21	1.409		1.41

Note:

1. The maximum SAR summation is calculated based on the same configuration and test position.
2. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements
3. If 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.
4. If 1g-SAR scalar summation > 1.6W/kg, SPLSR calculation is necessary.

<Body-worn SAR>

Position	WWAN			WLAN		Max. SAR Sum	Scaled WWAN (W/kg)	Scaled WLAN (W/kg)	Scaled WWAN + Scaled WLAN
	WWAN Band	Plot No	Max. WWAN SAR (W/kg)	Plot No	Max. WLAN SAR (W/kg)				
Front	GSM850	#21	0.644	#57	0.032	0.68	0.731	0.034	0.77
	GSM1900	#29	0.583	#57	0.032	0.62	0.677	0.034	0.71
	WCDMA Band V	#39	0.468	#57	0.032	0.50	0.506	0.034	0.54
	WCDMA Band II	#45	0.686	#57	0.032	0.72	0.747	0.034	0.78
	WCDMA Band IV	#66	0.818	#57	0.032	0.85	0.920	0.034	0.95
Back	GSM850	#27	0.939	#58	0.088	1.03	1.071	0.094	1.17
	GSM1900	#35	0.925	#58	0.088	1.01	1.079	0.094	1.17
	WCDMA Band V	#40	0.65	#58	0.088	0.74	0.703	0.094	0.80
	WCDMA Band II	#51	0.944	#58	0.088	1.03	1.052	0.094	1.15
	WCDMA Band IV	#67	0.923	#58	0.088	1.01	1.038	0.094	1.13
Back (w/headset)	GSM850	#28	0.593	#61	0.059	0.65	0.682	0.063	0.75
	GSM1900	#38	0.398	#61	0.059	0.46	0.467	0.063	0.53
	WCDMA Band V	#44	0.541	#61	0.059	0.60	0.585	0.063	0.65
	WCDMA Band II	#55	1.010	#61	0.059	1.07	1.100	0.063	1.16
	WCDMA Band IV	#77	0.904	#61	0.059	0.96	1.052	0.063	1.12

Note:

1. The maximum SAR summation is calculated based on the same configuration and test position.
2. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements
3. If 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.
4. If 1g-SAR scalar summation > 1.6W/kg, SPLSR calculation is necessary.

Test Engineer : Fulu Hu

12. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 12.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	$1/k^{(b)}$	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Table 12.1 Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty	Probability	Divisor	Ci	Ci	Standard	Standard
	Value	Distribution		(1g)	(10g)	Uncertainty	Uncertainty
	(±%)					(1g)	(10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 12.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz

13. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [7] FCC KDB 447498 D01 v04, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", November 2009
- [8] FCC KDB 648474 D01 v01r05, "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", September 2008
- [9] FCC KDB 941225 D01 v02, "SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA", October 2007
- [10] FCC KDB 941225 D02 v02 "3GPP R6 HSPA and R7 HSPA+ SAR Guidance", December 2009.
- [11] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008
- [12] FCC KDB 941225 D04 v01, "Evaluating SAR for GSM/(E)GPRS Dual Transfer Mode", January 27 2010
- [13] FCC KDB 941225 D06 v01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", April 2011
- [14] FCC KDB 388624 D02, "Permit But Ask List", December 2011.



Appendix A. Plots of System Performance Check

The plots are shown as follows.

System Check_Head_835MHz_121211

DUT: D835V2 - SN:4d091

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL_835_121211 Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.905 \text{ mho/m}$; $\epsilon_r = 42.233$;

$\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (61x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 2.513 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 53.299 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 3.375 W/kg

SAR(1 g) = 2.33 mW/g ; SAR(10 g) = 1.53 mW/g

Maximum value of SAR (measured) = 2.518 mW/g



0 dB = 2.520mW/g

System Check_Head_1750MHz_121214

DUT: D1750V2 - SN:1069

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL_1750_121214 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r =$

41.322; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.14, 8.14, 8.14); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 9.879 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 84.650 V/m; Power Drift = 0.00031 dB

Peak SAR (extrapolated) = 16.446 W/kg

SAR(1 g) = 8.78 mW/g; SAR(10 g) = 4.61 mW/g

Maximum value of SAR (measured) = 9.800 mW/g



0 dB = 9.800mW/g

System Check_Head_1900MHz_121211

DUT: D1900V2 - SN:5d118

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL_1900_121211 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.426$ mho/m; $\epsilon_r =$

38.855 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (91x91x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 11.371 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.533 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 18.985 W/kg

SAR(1 g) = 10 mW/g; SAR(10 g) = 5.14 mW/g

Maximum value of SAR (measured) = 11.289 mW/g



0 dB = 11.290mW/g

System Check_Head_2450MHz_121212

DUT: D2450V2 - SN:736

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL_2450_121212 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.861$ mho/m; $\epsilon_r =$

39.575; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.87, 6.87, 6.87); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 22.239 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 92.584 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 29.488 W/kg

SAR(1 g) = 13.8 mW/g; SAR(10 g) = 6.23 mW/g

Maximum value of SAR (measured) = 21.585 mW/g



0 dB = 21.590mW/g

System Check_Body_835MHz_121211

DUT: D835V2 - SN:4d091

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.983 \text{ mho/m}$; $\epsilon_r = 54.864$;

$\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.3 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (61x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 2.466 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 50.474 V/m ; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.280 W/kg

SAR(1 g) = 2.28 mW/g ; SAR(10 g) = 1.51 mW/g

Maximum value of SAR (measured) = 2.470 mW/g



0 dB = 2.470mW/g

System Check_Body_1750MHz_121213

DUT: D1750V2 - SN:1069

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

55.585; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 10.226 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 82.490 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 16.027 W/kg

SAR(1 g) = 8.97 mW/g; SAR(10 g) = 4.76 mW/g

Maximum value of SAR (measured) = 10.115 mW/g



0 dB = 10.120mW/g

System Check_Body_1900MHz_121212

DUT: D1900V2 - SN:5d118

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.555$ mho/m; $\epsilon_r =$

53.699; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (91x91x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 11.685 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 86.970 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 18.334 W/kg

SAR(1 g) = 10.1 mW/g; SAR(10 g) = 5.19 mW/g

Maximum value of SAR (measured) = 11.492 mW/g



0 dB = 11.490mW/g

System Check_Body_2450MHz_121212

DUT: D2450V2 - SN:736

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 2.002 \text{ mho/m}$; $\epsilon_r =$

53.464; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Pin=250mW/Area Scan (71x71x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (interpolated) = 21.254 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 87.408 V/m ; Power Drift = 0.022 dB

Peak SAR (extrapolated) = 29.087 W/kg

SAR(1 g) = 13.4 mW/g ; SAR(10 g) = 6.05 mW/g

Maximum value of SAR (measured) = 20.980 mW/g



0 dB = 20.980mW/g



Appendix B. Plots of SAR Measurement

The plots are shown as follows.

#01 GSM850_DTM 11_Right Cheek_Ch189

DUT: 2N2701



Communication System: GPRS/EDGE (3 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:3
Medium: HSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.906 \text{ mho/m}$; $\epsilon_r = 42.213$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.803 mW/g

Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 8.179 V/m ; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.889 W/kg
SAR(1 g) = 0.728 mW/g ; SAR(10 g) = 0.553 mW/g
Maximum value of SAR (measured) = 0.819 mW/g



0 dB = 0.820mW/g

#01 GSM850_DTM 11_Right Cheek_Ch189_2D

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:3
Medium: HSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.906 \text{ mho/m}$; $\epsilon_r = 42.213$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.803 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.179 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.889 W/kg

SAR(1 g) = 0.728 mW/g ; SAR(10 g) = 0.553 mW/g

Maximum value of SAR (measured) = 0.819 mW/g



#02 GSM850_DTM 11_Right Tilted_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:3
Medium: HSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.906 \text{ mho/m}$; $\epsilon_r = 42.213$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.507 mW/g



Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.092 V/m ; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.547 W/kg

SAR(1 g) = 0.446 mW/g ; SAR(10 g) = 0.345 mW/g

Maximum value of SAR (measured) = 0.501 mW/g



0 dB = 0.500mW/g

#03 GSM850_DTM 11_Left Cheek_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:3
Medium: HSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.906 \text{ mho/m}$; $\epsilon_r = 42.213$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.751 mW/g

Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.013 V/m ; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.816 W/kg

SAR(1 g) = 0.671 mW/g ; SAR(10 g) = 0.515 mW/g

Maximum value of SAR (measured) = 0.764 mW/g



0 dB = 0.760mW/g

#04 GSM850_DTM 11_Left Tilted_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:3
Medium: HSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.906 \text{ mho/m}$; $\epsilon_r = 42.213$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.511 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.315 V/m ; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.560 W/kg

SAR(1 g) = 0.460 mW/g ; SAR(10 g) = 0.356 mW/g

Maximum value of SAR (measured) = 0.514 mW/g



0 dB = 0.510mW/g

#05 GSM1900_DTM 11_Right Cheek_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:3
Medium: HSL_1900_121211 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.374 \text{ mho/m}$; $\epsilon_r = 39.102$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.1 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.512 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.359 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.607 W/kg

SAR(1 g) = 0.394 mW/g ; SAR(10 g) = 0.236 mW/g

Maximum value of SAR (measured) = 0.513 mW/g



0 dB = 0.510mW/g

#05 GSM1900_DTM 11_Right Cheek_Ch512_2D

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:3
Medium: HSL_1900_121211 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.374 \text{ mho/m}$; $\epsilon_r = 39.102$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.1 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.512 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.359 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.607 W/kg

SAR(1 g) = 0.394 mW/g ; SAR(10 g) = 0.236 mW/g

Maximum value of SAR (measured) = 0.513 mW/g



#06 GSM1900_DTM 11_Right Tilted_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:3
Medium: HSL_1900_121211 Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.374$ mho/m; $\epsilon_r = 39.102$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.095 mW/g

Ch512/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.432 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.116 W/kg

SAR(1 g) = 0.068 mW/g; SAR(10 g) = 0.039 mW/g

Maximum value of SAR (measured) = 0.087 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.432 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.101 W/kg

SAR(1 g) = 0.063 mW/g; SAR(10 g) = 0.040 mW/g

Maximum value of SAR (measured) = 0.084 mW/g



#07 GSM1900_DTM 11_Left Cheek_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:3
Medium: HSL_1900_121211 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.374 \text{ mho/m}$; $\epsilon_r = 39.102$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.1 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.481 mW/g

Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.683 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.565 W/kg

SAR(1 g) = 0.358 mW/g ; SAR(10 g) = 0.215 mW/g

Maximum value of SAR (measured) = 0.469 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.683 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.359 W/kg

SAR(1 g) = 0.238 mW/g ; SAR(10 g) = 0.158 mW/g

Maximum value of SAR (measured) = 0.309 mW/g



0 dB = 0.310mW/g

#08 GSM1900_DTM 11_Left Tilted_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (3 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:3
Medium: HSL_1900_121211 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.374 \text{ mho/m}$; $\epsilon_r = 39.102$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.1 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.163 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.949 V/m ; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.186 W/kg

SAR(1 g) = 0.115 mW/g ; SAR(10 g) = 0.071 mW/g

Maximum value of SAR (measured) = 0.152 mW/g



0 dB = 0.150mW/g

#09 WCDMA Band V_RMC12.2K_Right Cheek_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.897$ mho/m; $\epsilon_r =$

42.363; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.436 mW/g



Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.102 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.471 W/kg

SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.293 mW/g

Maximum value of SAR (measured) = 0.431 mW/g



0 dB = 0.430mW/g

#09 WCDMA Band V_RMC12.2K_Right Cheek_Ch4132_2D

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.897$ mho/m; $\epsilon_r =$

42.363 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.436 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.102 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.471 W/kg

SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.293 mW/g

Maximum value of SAR (measured) = 0.431 mW/g



#10 WCDMA Band V_RMC12.2K_Right Tilted_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.897$ mho/m; $\epsilon_r =$

42.363; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.289 mW/g



Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.592 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.303 W/kg

SAR(1 g) = 0.250 mW/g; SAR(10 g) = 0.193 mW/g

Maximum value of SAR (measured) = 0.279 mW/g



0 dB = 0.280mW/g

#11 WCDMA Band V_RMC12.2K_Left Cheek_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.897$ mho/m; $\epsilon_r =$

42.363; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.405 mW/g



Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.466 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.427 W/kg

SAR(1 g) = 0.357 mW/g; SAR(10 g) = 0.276 mW/g

Maximum value of SAR (measured) = 0.398 mW/g



0 dB = 0.400mW/g

#12 WCDMA Band V_RMC12.2K_Left Tilted_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: HSL_835_121211 Medium parameters used: $f = 826.4 \text{ MHz}$; $\sigma = 0.897 \text{ mho/m}$; $\epsilon_r =$

42.363 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.74, 8.74, 8.74); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.271 mW/g



Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.415 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.286 W/kg

SAR(1 g) = 0.236 mW/g ; SAR(10 g) = 0.183 mW/g

Maximum value of SAR (measured) = 0.263 mW/g



0 dB = 0.260mW/g

#62 WCDMA Band IV_RMC12.2K_Right Cheek_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: HSL_1750_121214 Medium parameters used: $f = 1712.4$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r =$

41.517; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.14, 8.14, 8.14); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.644 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.491 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.732 W/kg

SAR(1 g) = 0.497 mW/g; SAR(10 g) = 0.313 mW/g

Maximum value of SAR (measured) = 0.628 mW/g



0 dB = 0.630mW/g

#62 WCDMA Band IV_RMC12.2K_Right Cheek_Ch1312_2D

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: HSL_1750_121214 Medium parameters used: $f = 1712.4$ MHz; $\sigma = 1.34$ mho/m; $\epsilon_r =$

41.517; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.14, 8.14, 8.14); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.644 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.491 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.732 W/kg

SAR(1 g) = 0.497 mW/g; SAR(10 g) = 0.313 mW/g

Maximum value of SAR (measured) = 0.628 mW/g



#63 WCDMA Band IV_RMC12.2K_Right Tilted_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: HSL_1750_121214 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.34 \text{ mho/m}$; $\epsilon_r =$

41.517 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.6 \text{ }^\circ\text{C}$; Liquid Temperature : $21.6 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.14, 8.14, 8.14); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.131 mW/g

Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.848 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.154 W/kg

SAR(1 g) = 0.099 mW/g ; SAR(10 g) = 0.058 mW/g

Maximum value of SAR (measured) = 0.125 mW/g



Ch1312/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.848 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.119 W/kg

SAR(1 g) = 0.085 mW/g ; SAR(10 g) = 0.057 mW/g

Maximum value of SAR (measured) = 0.103 mW/g



0 dB = 0.100mW/g

#64 WCDMA Band IV_RMC12.2K_Left Cheek_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: HSL_1750_121214 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.34 \text{ mho/m}$; $\epsilon_r =$

41.517 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.6 \text{ }^\circ\text{C}$; Liquid Temperature : $21.6 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.14, 8.14, 8.14); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.508 mW/g

Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.532 V/m ; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.587 W/kg

SAR(1 g) = 0.388 mW/g ; SAR(10 g) = 0.245 mW/g

Maximum value of SAR (measured) = 0.489 mW/g



Ch1312/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.532 V/m ; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.451 W/kg

SAR(1 g) = 0.308 mW/g ; SAR(10 g) = 0.211 mW/g

Maximum value of SAR (measured) = 0.373 mW/g



0 dB = 0.370mW/g

#65 WCDMA Band IV_RMC12.2K_Left Tilted_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: HSL_1750_121214 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.34 \text{ mho/m}$; $\epsilon_r =$

41.517 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.6 \text{ }^\circ\text{C}$; Liquid Temperature : $21.6 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.14, 8.14, 8.14); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.187 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.927 V/m ; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.211 W/kg

SAR(1 g) = 0.138 mW/g ; SAR(10 g) = 0.085 mW/g

Maximum value of SAR (measured) = 0.174 mW/g



0 dB = 0.170mW/g

#13 WCDMA Band II_RMC12.2K_Right Cheek_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HSL_1900_121211 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.376$ mho/m; $\epsilon_r =$

39.094; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.484 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.839 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.578 W/kg

SAR(1 g) = 0.375 mW/g; SAR(10 g) = 0.224 mW/g

Maximum value of SAR (measured) = 0.489 mW/g



#14 WCDMA Band II_RMC12.2K_Right Tilted_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HSL_1900_121211 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.376$ mho/m; $\epsilon_r =$

39.094; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.078 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.859 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.060 mW/g; SAR(10 g) = 0.034 mW/g

Maximum value of SAR (measured) = 0.084 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.859 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.090 W/kg

SAR(1 g) = 0.050 mW/g; SAR(10 g) = 0.031 mW/g

Maximum value of SAR (measured) = 0.074 mW/g



0 dB = 0.070mW/g

#15 WCDMA Band II_RMC12.2K_Left Cheek_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HSL_1900_121211 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.376$ mho/m; $\epsilon_r =$

39.094; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.521 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.422 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.622 W/kg

SAR(1 g) = 0.398 mW/g; SAR(10 g) = 0.238 mW/g

Maximum value of SAR (measured) = 0.514 mW/g



0 dB = 0.510mW/g

#15 WCDMA Band II_RMC12.2K_Left Cheek_Ch9262_2D

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HSL_1900_121211 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.376$ mho/m; $\epsilon_r =$

39.094; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.521 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.422 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.622 W/kg

SAR(1 g) = 0.398 mW/g; SAR(10 g) = 0.238 mW/g

Maximum value of SAR (measured) = 0.514 mW/g



#16 WCDMA Band II_RMC12.2K_Left Tilted_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: HSL_1900_121211 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.376$ mho/m; $\epsilon_r =$

39.094; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.84, 7.84, 7.84); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.135 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.745 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.156 W/kg

SAR(1 g) = 0.099 mW/g; SAR(10 g) = 0.060 mW/g

Maximum value of SAR (measured) = 0.130 mW/g



Ch9262/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.745 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.102 W/kg

SAR(1 g) = 0.071 mW/g; SAR(10 g) = 0.047 mW/g

Maximum value of SAR (measured) = 0.087 mW/g



0 dB = 0.090mW/g

#17 802.11b_1M_Right Cheek_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450_121212 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.874$ mho/m; $\epsilon_r = 39.532$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.87, 6.87, 6.87); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.147 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.631 V/m; Power Drift = -0.037 dB

Peak SAR (extrapolated) = 0.199 W/kg

SAR(1 g) = 0.088 mW/g; SAR(10 g) = 0.042 mW/g

Maximum value of SAR (measured) = 0.135 mW/g



Ch11/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.631 V/m; Power Drift = -0.037 dB

Peak SAR (extrapolated) = 0.146 W/kg

SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.041 mW/g

Maximum value of SAR (measured) = 0.112 mW/g



0 dB = 0.110mW/g

#18 802.11b_1M_Right Tilted_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450_121212 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.874$ mho/m; $\epsilon_r = 39.532$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.87, 6.87, 6.87); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.104 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.443 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.161 W/kg

SAR(1 g) = 0.072 mW/g; SAR(10 g) = 0.034 mW/g

Maximum value of SAR (measured) = 0.113 mW/g



Ch11/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.443 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.121 W/kg

SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.034 mW/g

Maximum value of SAR (measured) = 0.092 mW/g



0 dB = 0.090mW/g

#19 802.11b_1M_Left Cheek_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450_121212 Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 1.874 \text{ mho/m}$; $\epsilon_r =$

39.532 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.3 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.87, 6.87, 6.87); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (interpolated) = 0.226 mW/g



Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.513 V/m ; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.283 W/kg

SAR(1 g) = 0.127 mW/g ; SAR(10 g) = 0.069 mW/g

Maximum value of SAR (measured) = 0.186 mW/g



0 dB = 0.190mW/g

#19 802.11b_1M_Left Cheek_Ch11_2D

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450_121212 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.874$ mho/m; $\epsilon_r =$

39.532 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.87, 6.87, 6.87); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (interpolated) = 0.226 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.513 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.283 W/kg

SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.069 mW/g

Maximum value of SAR (measured) = 0.186 mW/g



#20 802.11b_1M_Left Tilted_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450_121212 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.874$ mho/m; $\epsilon_r =$

39.532; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.87, 6.87, 6.87); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.142 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.059 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.194 W/kg

SAR(1 g) = 0.100 mW/g; SAR(10 g) = 0.051 mW/g

Maximum value of SAR (measured) = 0.142 mW/g



0 dB = 0.140mW/g

#21 GSM850_GPRS (4 Tx slots)_Front 1cm_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.984 \text{ mho/m}$; $\epsilon_r = 54.848$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.3 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.737 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.810 V/m ; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.799 W/kg

SAR(1 g) = 0.644 mW/g ; SAR(10 g) = 0.497 mW/g

Maximum value of SAR (measured) = 0.732 mW/g



0 dB = 0.730mW/g

#22 GSM850_GPRS (4 Tx slots)_Back 1cm_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.984$ mho/m; $\epsilon_r = 54.848$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C


DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.124 mW/g

Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.896 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 1.142 W/kg
SAR(1 g) = 0.905 mW/g; SAR(10 g) = 0.692 mW/g
Maximum value of SAR (measured) = 1.031 mW/g

Ch189/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.896 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.889 W/kg
SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.326 mW/g
Maximum value of SAR (measured) = 0.793 mW/g



#23 GSM850_GPRS (4 Tx slots)_Left Side 1cm_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.984 \text{ mho/m}$; $\epsilon_r = 54.848$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.3 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (31x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.648 mW/g



Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.110 V/m ; Power Drift = 0.034 dB

Peak SAR (extrapolated) = 0.765 W/kg

SAR(1 g) = 0.541 mW/g ; SAR(10 g) = 0.373 mW/g

Maximum value of SAR (measured) = 0.665 mW/g



0 dB = 0.670mW/g

#24 GSM850_GPRS (4 Tx slots)_Right Side 1cm_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.984 \text{ mho/m}$; $\epsilon_r = 54.848$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.3 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (31x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.854 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 27.518 V/m ; Power Drift = -0.0013 dB

Peak SAR (extrapolated) = 0.981 W/kg

SAR(1 g) = 0.701 mW/g ; SAR(10 g) = 0.486 mW/g

Maximum value of SAR (measured) = 0.858 mW/g



#25 GSM850_GPRS (4 Tx slots)_Bottom Side 1cm_Ch189

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 836.4 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.984 \text{ mho/m}$; $\epsilon_r = 54.848$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.3 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch189/Area Scan (31x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.291 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.392 V/m ; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.398 W/kg

SAR(1 g) = 0.204 mW/g ; SAR(10 g) = 0.109 mW/g

Maximum value of SAR (measured) = 0.300 mW/g



#26 GSM850_GPRS (4 Tx slots)_Back 1cm_Ch128

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 824.2 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.972$ mho/m; $\epsilon_r = 54.965$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch128/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.974 mW/g

Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.825 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.063 W/kg

SAR(1 g) = 0.845 mW/g; SAR(10 g) = 0.647 mW/g

Maximum value of SAR (measured) = 0.968 mW/g


Ch128/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.825 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.813 W/kg

SAR(1 g) = 0.497 mW/g; SAR(10 g) = 0.313 mW/g

Maximum value of SAR (measured) = 0.727 mW/g



#27 GSM850_GPRS (4 Tx slots)_Back 1cm_Ch251

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 848.8 MHz; Duty Cycle: 1:2
Medium: MSL_835_121211 Medium parameters used: $f = 849$ MHz; $\sigma = 0.997$ mho/m; $\epsilon_r = 54.717$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C


DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch251/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.090 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 31.327 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 1.187 W/kg
SAR(1 g) = 0.939 mW/g; SAR(10 g) = 0.718 mW/g
Maximum value of SAR (measured) = 1.076 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 31.327 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.922 W/kg
SAR(1 g) = 0.513 mW/g; SAR(10 g) = 0.327 mW/g
Maximum value of SAR (measured) = 0.799 mW/g



#27 GSM850_GPRS (4 Tx slots)_Back 1cm_Ch251_2D

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 848.8 MHz; Duty Cycle: 1:2

Medium: MSL_835_121211 Medium parameters used: $f = 849$ MHz; $\sigma = 0.997$ mho/m; $\epsilon_r = 54.717$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch251/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.090 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.327 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.187 W/kg

SAR(1 g) = 0.939 mW/g; SAR(10 g) = 0.718 mW/g

Maximum value of SAR (measured) = 1.076 mW/g


Ch251/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.327 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.922 W/kg

SAR(1 g) = 0.513 mW/g; SAR(10 g) = 0.327 mW/g

Maximum value of SAR (measured) = 0.799 mW/g



#28 GSM850_GSM_Back 1cm_Ch251_Headset

DUT: 2N2701

Communication System: General GSM; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: MSL_835_121211 Medium parameters used: $f = 849$ MHz; $\sigma = 0.997$ mho/m; $\epsilon_r = 54.717$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch251/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.703 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.042 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.776 W/kg

SAR(1 g) = 0.593 mW/g; SAR(10 g) = 0.436 mW/g

Maximum value of SAR (measured) = 0.692 mW/g


Ch251/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.042 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.767 W/kg

SAR(1 g) = 0.421 mW/g; SAR(10 g) = 0.250 mW/g

Maximum value of SAR (measured) = 0.608 mW/g



0 dB = 0.610mW/g

#29 GSM1900_GPRS (4 Tx slots)_Front 1cm_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.497 \text{ mho/m}$; $\epsilon_r = 53.903$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.833 mW/g

Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.562 V/m ; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.948 W/kg

SAR(1 g) = 0.583 mW/g ; SAR(10 g) = 0.345 mW/g

Maximum value of SAR (measured) = 0.782 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.562 V/m ; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.907 W/kg

SAR(1 g) = 0.537 mW/g ; SAR(10 g) = 0.324 mW/g

Maximum value of SAR (measured) = 0.719 mW/g



#30 GSM1900_GPRS (4 Tx slots)_Back 1cm_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.497 \text{ mho/m}$; $\epsilon_r = 53.903$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.091 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.492 V/m ; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.516 W/kg

SAR(1 g) = 0.876 mW/g ; SAR(10 g) = 0.501 mW/g

Maximum value of SAR (measured) = 1.191 mW/g



#31 GSM1900_GPRS (4 Tx slots)_Left Side 1cm_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.497 \text{ mho/m}$; $\epsilon_r = 53.903$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (31x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.311 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.985 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.416 W/kg

SAR(1 g) = 0.249 mW/g ; SAR(10 g) = 0.140 mW/g

Maximum value of SAR (measured) = 0.339 mW/g



0 dB = 0.340mW/g

#32 GSM1900_GPRS (4 Tx slots)_Right Side 1cm_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.497 \text{ mho/m}$; $\epsilon_r = 53.903$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (31x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.223 mW/g

Ch512/Zoom Scan (5x5x7)/Cube 1: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.909 V/m ; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.282 W/kg

SAR(1 g) = 0.175 mW/g ; SAR(10 g) = 0.104 mW/g

Maximum value of SAR (measured) = 0.234 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.909 V/m ; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.273 W/kg

SAR(1 g) = 0.167 mW/g ; SAR(10 g) = 0.096 mW/g

Maximum value of SAR (measured) = 0.225 mW/g



0 dB = 0.220mW/g

#33 GSM1900_GPRS (4 Tx slots)_Bottom Side 1cm_Ch512

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1850.2 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1850.2 \text{ MHz}$; $\sigma = 1.497 \text{ mho/m}$; $\epsilon_r = 53.903$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch512/Area Scan (31x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.190 mW/g


Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.278 V/m ; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.615 W/kg

SAR(1 g) = 0.913 mW/g ; SAR(10 g) = 0.472 mW/g

Maximum value of SAR (measured) = 1.312 mW/g



0 dB = 1.310mW/g

#34 GSM1900_GPRS (4 Tx slots)_Back 1cm_Ch661

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1880 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.533 \text{ mho/m}$; $\epsilon_r = 53.837$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch661/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.143 mW/g


Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.924 V/m ; Power Drift = 0.0081 dB

Peak SAR (extrapolated) = 1.576 W/kg

SAR(1 g) = 0.911 mW/g ; SAR(10 g) = 0.509 mW/g

Maximum value of SAR (measured) = 1.184 mW/g



0 dB = 1.180mW/g

#35 GSM1900_GPRS (4 Tx slots)_Back 1cm_Ch810

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1909.8 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.563$ mho/m; $\epsilon_r = 53.587$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch810/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.204 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.338 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.629 W/kg

SAR(1 g) = 0.925 mW/g; SAR(10 g) = 0.509 mW/g

Maximum value of SAR (measured) = 1.230 mW/g



#35 GSM1900_GPRS (4 Tx slots)_Back 1cm_Ch810_2D

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1909.8 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.563$ mho/m; $\epsilon_r = 53.587$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch810/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.204 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.338 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.629 W/kg

SAR(1 g) = 0.925 mW/g; SAR(10 g) = 0.509 mW/g

Maximum value of SAR (measured) = 1.230 mW/g



#36 GSM1900_GPRS (4 Tx slots)_Bottom Side 1cm_Ch661

DUT: 2N2701


Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1880 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.533 \text{ mho/m}$; $\epsilon_r = 53.837$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4°C ; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch661/Area Scan (31x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 1.176 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 24.528 V/m ; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 1.584 W/kg
SAR(1 g) = 0.898 mW/g ; SAR(10 g) = 0.465 mW/g
Maximum value of SAR (measured) = 1.289 mW/g



0 dB = 1.290mW/g

#37 GSM1900_GPRS (4 Tx slots)_Bottom Side 1cm_Ch810

DUT: 2N2701

Communication System: GPRS/EDGE (4 Tx slots); Frequency: 1909.8 MHz; Duty Cycle: 1:2
Medium: MSL_1900_121212 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.563$ mho/m; $\epsilon_r = 53.587$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch810/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.222 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.420 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.422 W/kg

SAR(1 g) = 0.899 mW/g; SAR(10 g) = 0.449 mW/g

Maximum value of SAR (measured) = 1.314 mW/g



#38 GSM1900_GSM_Back 1cm_Ch810_Headset

DUT: 2N2701

Communication System: General GSM; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: MSL_1900_121212 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.563$ mho/m; $\epsilon_r =$

53.587; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch810/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.510 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.463 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.699 W/kg

SAR(1 g) = 0.398 mW/g; SAR(10 g) = 0.219 mW/g

Maximum value of SAR (measured) = 0.528 mW/g



#39 WCDMA Band V_RMC12.2K_Front 1cm_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.533 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.159 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.580 W/kg

SAR(1 g) = 0.468 mW/g; SAR(10 g) = 0.361 mW/g

Maximum value of SAR (measured) = 0.532 mW/g



0 dB = 0.530mW/g

#40 WCDMA Band V_RMC12.2K_Back 1cm_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.758 mW/g

Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.022 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.813 W/kg

SAR(1 g) = 0.650 mW/g; SAR(10 g) = 0.497 mW/g

Maximum value of SAR (measured) = 0.744 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.022 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.611 W/kg

SAR(1 g) = 0.371 mW/g; SAR(10 g) = 0.233 mW/g

Maximum value of SAR (measured) = 0.548 mW/g



0 dB = 0.550mW/g

#40 WCDMA Band V_RMC12.2K_Back 1cm_Ch4132_2D

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.758 mW/g

Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.022 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.813 W/kg

SAR(1 g) = 0.650 mW/g; SAR(10 g) = 0.497 mW/g

Maximum value of SAR (measured) = 0.744 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.022 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.611 W/kg

SAR(1 g) = 0.371 mW/g; SAR(10 g) = 0.233 mW/g

Maximum value of SAR (measured) = 0.548 mW/g



#41 WCDMA Band V_RMC12.2K_Left Side 1cm_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (31x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.491 mW/g



Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.093 V/m; Power Drift = -0.0051 dB

Peak SAR (extrapolated) = 0.568 W/kg

SAR(1 g) = 0.406 mW/g; SAR(10 g) = 0.282 mW/g

Maximum value of SAR (measured) = 0.496 mW/g



0 dB = 0.500mW/g

#42 WCDMA Band V_RMC12.2K_Right Side 1cm_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (31x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.623 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.695 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.717 W/kg

SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.354 mW/g

Maximum value of SAR (measured) = 0.626 mW/g



0 dB = 0.630mW/g

#43 WCDMA Band V_RMC12.2K_Bottom Side 1cm_Ch4132

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.193 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.521 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.271 W/kg

SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.072 mW/g

Maximum value of SAR (measured) = 0.195 mW/g



#44 WCDMA Band V_RMC12.2K_Back 1cm_Ch4132_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: MSL_835_121211 Medium parameters used: $f = 826.4$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r =$

54.944; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(8.98, 8.98, 8.98); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch4132/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.627 mW/g

Ch4132/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.723 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.697 W/kg

SAR(1 g) = 0.541 mW/g; SAR(10 g) = 0.405 mW/g

Maximum value of SAR (measured) = 0.625 mW/g


Ch4132/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.723 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.672 W/kg

SAR(1 g) = 0.382 mW/g; SAR(10 g) = 0.241 mW/g

Maximum value of SAR (measured) = 0.535 mW/g



0 dB = 0.530mW/g

#66 WCDMA Band IV_RMC12.2K_Front 1cm_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.471 \text{ mho/m}$; $\epsilon_r = 55.65$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 23.4°C ; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.117 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.074 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.280 W/kg

SAR(1 g) = 0.818 mW/g ; SAR(10 g) = 0.488 mW/g

Maximum value of SAR (measured) = 1.055 mW/g



0 dB = 1.060mW/g

#67 WCDMA Band IV_RMC12.2K_Back 1cm_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.471 \text{ mho/m}$; $\epsilon_r =$

55.65 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.125 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.029 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.455 W/kg

SAR(1 g) = 0.923 mW/g ; SAR(10 g) = 0.584 mW/g

Maximum value of SAR (measured) = 1.211 mW/g



#68 WCDMA Band IV_RMC12.2K_Left Side 1cm_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.471 \text{ mho/m}$; $\epsilon_r =$

55.65 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.5 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (31x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.384 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.374 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.461 W/kg

SAR(1 g) = 0.291 mW/g ; SAR(10 g) = 0.172 mW/g

Maximum value of SAR (measured) = 0.386 mW/g



#69 WCDMA Band IV_RMC12.2K_Right Side 1cm_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1
Medium: MSL_1750_121213 Medium parameters used: $f = 1712.4$ MHz; $\sigma = 1.471$ mho/m; $\epsilon_r = 55.65$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C



DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (31x111x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.254 mW/g

Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.275 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.307 W/kg
SAR(1 g) = 0.198 mW/g; SAR(10 g) = 0.121 mW/g
Maximum value of SAR (measured) = 0.257 mW/g

Ch1312/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.275 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.263 W/kg
SAR(1 g) = 0.173 mW/g; SAR(10 g) = 0.109 mW/g
Maximum value of SAR (measured) = 0.221 mW/g



0 dB = 0.220mW/g

#70 WCDMA Band IV_RMC12.2K_Bottom Side 1cm_Ch1312

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.471 \text{ mho/m}$; $\epsilon_r = 55.65$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 23.4°C ; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (31x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.470 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 30.428 V/m ; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.055 W/kg

SAR(1 g) = 1.2 mW/g ; SAR(10 g) = 0.632 mW/g

Maximum value of SAR (measured) = 1.705 mW/g



0 dB = 1.710mW/g

#71 WCDMA Band IV_RMC12.2K_Front 1cm_Ch1413

DUT: 2N2701

Communication System: UMTS; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.612; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1413/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.026 mW/g


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.840 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.168 W/kg

SAR(1 g) = 0.743 mW/g; SAR(10 g) = 0.444 mW/g

Maximum value of SAR (measured) = 0.954 mW/g



#72 WCDMA Band IV_RMC12.2K_Front 1cm_Ch1513

DUT: 2N2701

Communication System: UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.515$ mho/m; $\epsilon_r =$

55.581; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.049 mW/g


Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.997 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.185 W/kg

SAR(1 g) = 0.750 mW/g; SAR(10 g) = 0.452 mW/g

Maximum value of SAR (measured) = 0.968 mW/g



#73 WCDMA Band IV_RMC12.2K_Back 1cm_Ch1413

DUT: 2N2701

Communication System: UMTS; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.612; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1413/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.166 mW/g


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.028 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.383 W/kg

SAR(1 g) = 0.872 mW/g; SAR(10 g) = 0.546 mW/g

Maximum value of SAR (measured) = 1.148 mW/g



0 dB = 1.150mW/g

#74 WCDMA Band IV_RMC12.2K_Back 1cm_Ch1513

DUT: 2N2701

Communication System: UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.515$ mho/m; $\epsilon_r =$

55.581; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.198 mW/g



Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.108 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.422 W/kg

SAR(1 g) = 0.886 mW/g; SAR(10 g) = 0.553 mW/g

Maximum value of SAR (measured) = 1.174 mW/g



0 dB = 1.170mW/g

#78 WCDMA Band IV_RMC12.2K_Bottom Side 1cm_Ch1413

DUT: 2N2701

Communication System: UMTS; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.612; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1413/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.419 mW/g


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.876 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 2.011 W/kg

SAR(1 g) = 1.17 mW/g; SAR(10 g) = 0.620 mW/g

Maximum value of SAR (measured) = 1.647 mW/g



#79 WCDMA Band IV_RMC12.2K_Bottom Side 1cm_Ch1513

DUT: 2N2701

Communication System: UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.515$ mho/m; $\epsilon_r =$

55.581; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.490 mW/g


Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.185 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 2.087 W/kg

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.640 mW/g

Maximum value of SAR (measured) = 1.726 mW/g



0 dB = 1.730mW/g

#79 WCDMA Band IV_RMC12.2K_Bottom Side 1cm_Ch1513_2D

DUT: 2N2701

Communication System: UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.515$ mho/m; $\epsilon_r =$

55.581; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.490 mW/g


Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.185 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 2.087 W/kg

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.640 mW/g

Maximum value of SAR (measured) = 1.726 mW/g



#75 WCDMA Band IV_RMC12.2K_Back 1cm_Ch1312_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1712.4 \text{ MHz}$; $\sigma = 1.471 \text{ mho/m}$; $\epsilon_r = 55.65$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 23.4°C ; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1312/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.182 mW/g


Ch1312/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.404 V/m ; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.414 W/kg

SAR(1 g) = 0.899 mW/g ; SAR(10 g) = 0.575 mW/g

Maximum value of SAR (measured) = 1.180 mW/g



0 dB = 1.180mW/g

#76 WCDMA Band IV_RMC12.2K_Back 1cm_Ch1413_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1733$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.612; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1413/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.126 mW/g


Ch1413/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.374 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.359 W/kg

SAR(1 g) = 0.850 mW/g; SAR(10 g) = 0.531 mW/g

Maximum value of SAR (measured) = 1.124 mW/g



#77 WCDMA Band IV_RMC12.2K_Back 1cm_Ch1513_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 1752.6 MHz; Duty Cycle: 1:1

Medium: MSL_1750_121213 Medium parameters used: $f = 1753$ MHz; $\sigma = 1.515$ mho/m; $\epsilon_r =$

55.581; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.68, 7.68, 7.68); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch1513/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.183 mW/g


Ch1513/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.565 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.450 W/kg

SAR(1 g) = 0.904 mW/g; SAR(10 g) = 0.562 mW/g

Maximum value of SAR (measured) = 1.200 mW/g



#45 WCDMA Band II_RMC12.2K_Front 1cm_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r =$

53.894; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.967 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.576 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.125 W/kg

SAR(1 g) = 0.686 mW/g; SAR(10 g) = 0.409 mW/g

Maximum value of SAR (measured) = 0.923 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.576 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.003 W/kg

SAR(1 g) = 0.591 mW/g; SAR(10 g) = 0.363 mW/g

Maximum value of SAR (measured) = 0.820 mW/g



0 dB = 0.820mW/g

#46 WCDMA Band II_RMC12.2K_Back 1cm_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4 \text{ MHz}$; $\sigma = 1.5 \text{ mho/m}$; $\epsilon_r =$

53.894 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.249 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.381 V/m ; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.609 W/kg

SAR(1 g) = 0.941 mW/g ; SAR(10 g) = 0.534 mW/g

Maximum value of SAR (measured) = 1.248 mW/g



#47 WCDMA Band II_RMC12.2K_Left Side 1cm_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4 \text{ MHz}$; $\sigma = 1.5 \text{ mho/m}$; $\epsilon_r =$

53.894 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (31x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.344 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.901 V/m ; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.438 W/kg

SAR(1 g) = 0.261 mW/g ; SAR(10 g) = 0.149 mW/g

Maximum value of SAR (measured) = 0.354 mW/g



#48 WCDMA Band II_RMC12.2K_Right Side 1cm_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r =$

53.894; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (31x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.284 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.458 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.347 W/kg

SAR(1 g) = 0.213 mW/g; SAR(10 g) = 0.127 mW/g

Maximum value of SAR (measured) = 0.286 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.458 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.337 W/kg

SAR(1 g) = 0.208 mW/g; SAR(10 g) = 0.121 mW/g

Maximum value of SAR (measured) = 0.277 mW/g



#49 WCDMA Band II_RMC12.2K_Bottom Side 1cm_Ch9262

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4 \text{ MHz}$; $\sigma = 1.5 \text{ mho/m}$; $\epsilon_r =$

53.894 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (31x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.404 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 28.152 V/m ; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.943 W/kg

SAR(1 g) = 1.08 mW/g ; SAR(10 g) = 0.558 mW/g

Maximum value of SAR (measured) = 1.579 mW/g



0 dB = 1.580mW/g

#49 WCDMA Band II_RMC12.2K_Bottom Side 1cm_Ch9262_2D

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4 \text{ MHz}$; $\sigma = 1.5 \text{ mho/m}$; $\epsilon_r =$

53.894 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (31x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.404 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 28.152 V/m ; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.943 W/kg

SAR(1 g) = 1.08 mW/g ; SAR(10 g) = 0.558 mW/g

Maximum value of SAR (measured) = 1.579 mW/g



#50 WCDMA Band II_RMC12.2K_Back 1cm_Ch9400

DUT: 2N2701

Communication System: UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.533$ mho/m; $\epsilon_r =$

53.837; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9400/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.154 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.214 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.528 W/kg

SAR(1 g) = 0.884 mW/g; SAR(10 g) = 0.495 mW/g

Maximum value of SAR (measured) = 1.158 mW/g



#51 WCDMA Band II_RMC12.2K_Back 1cm_Ch9538

DUT: 2N2701

Communication System: UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.561$ mho/m; $\epsilon_r =$

53.585; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9538/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.193 mW/g


Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.667 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.656 W/kg

SAR(1 g) = 0.944 mW/g; SAR(10 g) = 0.527 mW/g

Maximum value of SAR (measured) = 1.281 mW/g



0 dB = 1.280mW/g

#52 WCDMA Band II_RMC12.2K_Bottom Side 1cm_Ch9400

DUT: 2N2701

Communication System: UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.533$ mho/m; $\epsilon_r =$

53.837; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9400/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.276 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.296 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.768 W/kg

SAR(1 g) = 0.986 mW/g; SAR(10 g) = 0.505 mW/g

Maximum value of SAR (measured) = 1.431 mW/g



0 dB = 1.430mW/g

#53 WCDMA Band II_RMC12.2K_Bottom Side 1cm_Ch9538

DUT: 2N2701

Communication System: UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.561$ mho/m; $\epsilon_r =$

53.585; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9538/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.375 mW/g


Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.666 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.852 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.529 mW/g

Maximum value of SAR (measured) = 1.496 mW/g



#54 WCDMA Band II_RMC12.2K_Back 1cm_Ch9538_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1908$ MHz; $\sigma = 1.561$ mho/m; $\epsilon_r =$

53.585; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9538/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.217 mW/g


Ch9538/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.321 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.685 W/kg

SAR(1 g) = 0.966 mW/g; SAR(10 g) = 0.538 mW/g

Maximum value of SAR (measured) = 1.293 mW/g



0 dB = 1.290mW/g

#55 WCDMA Band II_RMC12.2K_Back 1cm_Ch9262_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1852.4 \text{ MHz}$; $\sigma = 1.5 \text{ mho/m}$; $\epsilon_r =$

53.894 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.4 \text{ }^\circ\text{C}$; Liquid Temperature : $21.4 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9262/Area Scan (71x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.307 mW/g


Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.230 V/m ; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.748 W/kg

SAR(1 g) = 1.01 mW/g ; SAR(10 g) = 0.580 mW/g

Maximum value of SAR (measured) = 1.382 mW/g



#56 WCDMA Band II_RMC12.2K_Back 1cm_Ch9400_Headset

DUT: 2N2701

Communication System: UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_121212 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.533$ mho/m; $\epsilon_r =$

53.837; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.35, 7.35, 7.35); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch9400/Area Scan (71x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.185 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.236 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.620 W/kg

SAR(1 g) = 0.930 mW/g; SAR(10 g) = 0.527 mW/g

Maximum value of SAR (measured) = 1.277 mW/g



0 dB = 1.280mW/g

#57 802.11b_1M_Front 1cm_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.050 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.811 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.064 W/kg

SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.018 mW/g

Maximum value of SAR (measured) = 0.046 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.811 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.056 W/kg

SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.014 mW/g

Maximum value of SAR (measured) = 0.042 mW/g



0 dB = 0.040mW/g

#58 802.11b_1M_Back 1cm_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.027 \text{ mho/m}$; $\epsilon_r =$

53.408 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (interpolated) = 0.120 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.950 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.182 W/kg

SAR(1 g) = 0.088 mW/g ; SAR(10 g) = 0.043 mW/g

Maximum value of SAR (measured) = 0.132 mW/g



0 dB = 0.130mW/g

#58 802.11b_1M_Back 1cm_Ch11_2D

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.027 \text{ mho/m}$; $\epsilon_r =$

53.408 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (interpolated) = 0.120 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.950 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.182 W/kg

SAR(1 g) = 0.088 mW/g ; SAR(10 g) = 0.043 mW/g

Maximum value of SAR (measured) = 0.132 mW/g



#59 802.11b_1M_Right Side 1cm_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (31x131x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.051 mW/g

Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.174 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.082 W/kg

SAR(1 g) = 0.037 mW/g; SAR(10 g) = 0.017 mW/g

Maximum value of SAR (measured) = 0.059 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.174 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.060 W/kg

SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.016 mW/g

Maximum value of SAR (measured) = 0.042 mW/g



#60 802.11b_1M_Top Side 1cm_Ch11

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.027 \text{ mho/m}$; $\epsilon_r =$

53.408 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (31x81x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (interpolated) = 0.054 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.152 V/m ; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.067 W/kg

SAR(1 g) = 0.034 mW/g ; SAR(10 g) = 0.018 mW/g

Maximum value of SAR (measured) = 0.051 mW/g



#61 802.11b_1M_Back_1cm Ch11_Headset

DUT: 2N2701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_121212 Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.027 \text{ mho/m}$; $\epsilon_r =$

53.408 ; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $21.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(6.94, 6.94, 6.94); Calibrated: 2012-6-20
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn360; Calibrated: 2012-11-15
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (81x131x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (interpolated) = 0.085 mW/g


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.695 V/m ; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.125 W/kg

SAR(1 g) = 0.059 mW/g ; SAR(10 g) = 0.025 mW/g

Maximum value of SAR (measured) = 0.090 mW/g



0 dB = 0.090mW/g