

**Test Plot 1#: GSM 850\_Head Left Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.355 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.229 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.412 W/kg

**SAR(1 g) = 0.328 W/kg; SAR(10 g) = 0.253 W/kg**

Maximum value of SAR (measured) = 0.342 W/kg



**Test Plot 2#: GSM 850\_Head Left Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.125 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.17 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.148 W/kg

**SAR(1 g) = 0.118 W/kg; SAR(10 g) = 0.094 W/kg**

Maximum value of SAR (measured) = 0.123 W/kg



0 dB = 0.123 W/kg = -9.10 dBW/kg

**Test Plot 3#: GSM 850\_Head Right Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.279 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.258 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.328 W/kg

**SAR(1 g) = 0.266 W/kg; SAR(10 g) = 0.207 W/kg**

Maximum value of SAR (measured) = 0.279 W/kg



0 dB = 0.279 W/kg = -5.54 dBW/kg

**Test Plot 4#: GSM 850\_Head Right Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.135 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.13 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.169 W/kg

**SAR(1 g) = 0.133 W/kg; SAR(10 g) = 0.103 W/kg**

Maximum value of SAR (measured) = 0.141 W/kg



**Test Plot 5#: GSM 850\_Body Worn Back\_Low Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 824.2 MHz; Duty Cycle: 1:8  
Medium parameters used: 824.2 MHz;  $\sigma = 0.968$  S/m;  $\epsilon_r = 53.264$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.975 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.69 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 0.815 W/kg; SAR(10 g) = 0.440 W/kg**

Maximum value of SAR (measured) = 0.935 W/kg



**Test Plot 6#: GSM 850\_Body Worn Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.09 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.11 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.74 W/kg

**SAR(1 g) = 0.899 W/kg; SAR(10 g) = 0.480 W/kg**

Maximum value of SAR (measured) = 1.04 W/kg



**Test Plot 7#: GSM 850\_Body Worn Back\_High Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 848.8 MHz; Duty Cycle: 1:8  
Medium parameters used: 848.8 MHz;  $\sigma = 1.005$  S/m;  $\epsilon_r = 53.059$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.16 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.45 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 2.01 W/kg

**SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.563 W/kg**

Maximum value of SAR (measured) = 1.17 W/kg



**Test Plot 8#: GSM 850\_Body Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 836.6 MHz; Duty Cycle: 1:2  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.662 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.89 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.832 W/kg

**SAR(1 g) = 0.628 W/kg; SAR(10 g) = 0.477 W/kg**

Maximum value of SAR (measured) = 0.663 W/kg





**Test Plot 9#: GSM 850\_Body Left\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 836.6 MHz; Duty Cycle: 1:2  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.357 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.12 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.478 W/kg

**SAR(1 g) = 0.336 W/kg; SAR(10 g) = 0.234 W/kg**

Maximum value of SAR (measured) = 0.361 W/kg



**Test Plot 10#: GSM 850\_Body Right\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 836.6 MHz; Duty Cycle: 1:2  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.356 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.45 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.460 W/kg

**SAR(1 g) = 0.329 W/kg; SAR(10 g) = 0.228 W/kg**

Maximum value of SAR (measured) = 0.354 W/kg



**Test Plot 11#: GSM 850\_Body Bottom\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 836.6 MHz; Duty Cycle: 1:2  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.125 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.29 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.216 W/kg

**SAR(1 g) = 0.121 W/kg; SAR(10 g) = 0.071 W/kg**

Maximum value of SAR (measured) = 0.132 W/kg



**Test Plot 12#: GSM 1900\_Head Left Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1880 MHz; Duty Cycle: 1:8  
Medium parameters used: 1880 MHz;  $\sigma = 1.406$  S/m;  $\epsilon_r = 39.213$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.302 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.063 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.441 W/kg

**SAR(1 g) = 0.274 W/kg; SAR(10 g) = 0.167 W/kg**

Maximum value of SAR (measured) = 0.300 W/kg



**Test Plot 13#: GSM 1900\_Head Left Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1880 MHz; Duty Cycle: 1:8  
Medium parameters used: 1880 MHz;  $\sigma = 1.406$  S/m;  $\epsilon_r = 39.213$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0911 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.405 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.118 W/kg

**SAR(1 g) = 0.076 W/kg; SAR(10 g) = 0.047 W/kg**

Maximum value of SAR (measured) = 0.0825 W/kg



**Test Plot 14#: GSM 1900\_Head Right Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1880 MHz; Duty Cycle: 1:8  
Medium parameters used: 1880 MHz;  $\sigma = 1.406$  S/m;  $\epsilon_r = 39.213$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.300 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.666 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.470 W/kg

**SAR(1 g) = 0.290 W/kg; SAR(10 g) = 0.175 W/kg**

Maximum value of SAR (measured) = 0.311 W/kg



**Test Plot 15#: GSM 1900\_Head Right Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1880 MHz; Duty Cycle: 1:8  
Medium parameters used: 1880 MHz;  $\sigma = 1.406$  S/m;  $\epsilon_r = 39.213$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.139 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.558 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.197 W/kg

**SAR(1 g) = 0.117 W/kg; SAR(10 g) = 0.070 W/kg**

Maximum value of SAR (measured) = 0.127 W/kg



**Test Plot 16#: GSM 1900\_Body Worn Back\_Low Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1850.2 MHz; Duty Cycle: 1:8  
Medium parameters used: 1850.2 MHz;  $\sigma = 1.524$  S/m;  $\epsilon_r = 51.558$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.28 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.66 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 2.00 W/kg

**SAR(1 g) = 0.978 W/kg; SAR(10 g) = 0.497 W/kg**

Maximum value of SAR (measured) = 1.13 W/kg






**Test Plot 17#: GSM 1900\_Body Worn Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1880 MHz; Duty Cycle: 1:8  
Medium parameters used: 1880 MHz;  $\sigma = 1.562 \text{ S/m}$ ;  $\epsilon_r = 51.432$ ;  $\rho = 1000 \text{ kg/m}^3$  ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $1.32 \text{ W/kg}$ **Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $12.08 \text{ V/m}$ ; Power Drift =  $-0.06 \text{ dB}$ Peak SAR (extrapolated) =  $2.07 \text{ W/kg}$ **SAR(1 g) =  $0.990 \text{ W/kg}$ ; SAR(10 g) =  $0.500 \text{ W/kg}$** Maximum value of SAR (measured) =  $1.14 \text{ W/kg}$ 

**Test Plot 18#: GSM 1900\_Body Worn Back\_High Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GSM; Frequency: 1909.8 MHz; Duty Cycle: 1:8  
Medium parameters used: 1909.8 MHz;  $\sigma = 1.583$  S/m;  $\epsilon_r = 51.35$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.27 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.46 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.93 W/kg

**SAR(1 g) = 0.922 W/kg; SAR(10 g) = 0.471 W/kg**

Maximum value of SAR (measured) = 1.06 W/kg



**Test Plot 19#: GSM 1900\_Body Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 1880 MHz; Duty Cycle: 1:2  
Medium parameters used: 1880 MHz;  $\sigma = 1.562$  S/m;  $\epsilon_r = 51.432$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.766 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.08 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.16 W/kg

**SAR(1 g) = 0.633 W/kg; SAR(10 g) = 0.349 W/kg**

Maximum value of SAR (measured) = 0.708 W/kg



**Test Plot 20#: GSM 1900\_Body Left\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 1880 MHz; Duty Cycle: 1:2  
Medium parameters used: 1880 MHz;  $\sigma = 1.562$  S/m;  $\epsilon_r = 51.432$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.167 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.417 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.247 W/kg

**SAR(1 g) = 0.153 W/kg; SAR(10 g) = 0.092 W/kg**

Maximum value of SAR (measured) = 0.169 W/kg



**Test Plot 21#: GSM 1900\_Body Right\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 1880 MHz; Duty Cycle: 1:2  
Medium parameters used: 1880 MHz;  $\sigma = 1.562$  S/m;  $\epsilon_r = 51.432$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.230 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.811 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.336 W/kg

**SAR(1 g) = 0.203 W/kg; SAR(10 g) = 0.117 W/kg**

Maximum value of SAR (measured) = 0.225 W/kg



**Test Plot 22#: GSM 1900\_Body Bottom\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic GPRS-4 slot; Frequency: 1880 MHz; Duty Cycle: 1:2  
Medium parameters used: 1880 MHz;  $\sigma = 1.562$  S/m;  $\epsilon_r = 51.432$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.752 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.06 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.12 W/kg

**SAR(1 g) = 0.669 W/kg; SAR(10 g) = 0.356 W/kg**

Maximum value of SAR (measured) = 0.758 W/kg



**Test Plot 23#: WCDMA Band 2\_Head Left Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: W; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: 1880 MHz;  $\sigma = 1.406 \text{ S/m}$ ;  $\epsilon_r = 39.213$ ;  $\rho = 1000 \text{ kg/m}^3$  ;

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.591 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.518 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.927 W/kg

**SAR(1 g) = 0.553 W/kg; SAR(10 g) = 0.321 W/kg**

Maximum value of SAR (measured) = 0.613 W/kg



**Test Plot 24#: WCDMA Band 2\_Head Left Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: W; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: 1880 MHz;  $\sigma = 1.406$  S/m;  $\epsilon_r = 39.213$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.179 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.52 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.231 W/kg

**SAR(1 g) = 0.140 W/kg; SAR(10 g) = 0.084 W/kg**

Maximum value of SAR (measured) = 0.154 W/kg





**Test Plot 25#: WCDMA Band 2\_Head Right Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**


Communication System: W; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: 1880 MHz;  $\sigma = 1.406 \text{ S/m}$ ;  $\epsilon_r = 39.213$ ;  $\rho = 1000 \text{ kg/m}^3$  ;

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.481 \text{ W/kg}$ **Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $6.543 \text{ V/m}$ ; Power Drift =  $0.09 \text{ dB}$ Peak SAR (extrapolated) =  $0.771 \text{ W/kg}$ **SAR(1 g) =  $0.466 \text{ W/kg}$ ; SAR(10 g) =  $0.279 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.509 \text{ W/kg}$ 

**Test Plot 26#: WCDMA Band 2\_Head Right Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: W; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: 1880 MHz;  $\sigma = 1.406$  S/m;  $\epsilon_r = 39.213$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.18, 8.18, 8.18); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.251 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.37 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.354 W/kg

**SAR(1 g) = 0.218 W/kg; SAR(10 g) = 0.127 W/kg**

Maximum value of SAR (measured) = 0.238 W/kg



**Test Plot 27#: WCDMA Band 2\_Body Worn Back\_Low Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used: 1852.4 MHz;  $\sigma = 1.522$  S/m;  $\epsilon_r = 51.545$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.28 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.21 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.00 W/kg

**SAR(1 g) = 0.998 W/kg; SAR(10 g) = 0.517 W/kg**

Maximum value of SAR (measured) = 1.14 W/kg



**Test Plot 28#: WCDMA Band 2\_Body Worn Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used: 1880 MHz;  $\sigma = 1.562$  S/m;  $\epsilon_r = 51.432$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.34 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.99 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.12 W/kg

**SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.532 W/kg**

Maximum value of SAR (measured) = 1.24 W/kg



**Test Plot 29#: WCDMA Band 2\_Body Worn Back\_High Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1907.6 MHz;  $\sigma = 1.581$  S/m;  $\epsilon_r = 51.36$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.39 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.30 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.14 W/kg

**SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.543 W/kg**

Maximum value of SAR (measured) = 1.21 W/kg




**Test Plot 30#: WCDMA Band 2\_Body Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used: 1880 MHz;  $\sigma = 1.562 \text{ S/m}$ ;  $\epsilon_r = 51.432$ ;  $\rho = 1000 \text{ kg/m}^3$ ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.866 \text{ W/kg}$ **Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $13.48 \text{ V/m}$ ; Power Drift =  $-0.02 \text{ dB}$ Peak SAR (extrapolated) =  $1.36 \text{ W/kg}$ **SAR(1 g) =  $0.736 \text{ W/kg}$ ; SAR(10 g) =  $0.403 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.830 \text{ W/kg}$ 

**Test Plot 31#: WCDMA Band 2\_Body Left\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used: 1880 MHz;  $\sigma = 1.562$  S/m;  $\epsilon_r = 51.432$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.397 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.70 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.565 W/kg

**SAR(1 g) = 0.341 W/kg; SAR(10 g) = 0.194 W/kg**

Maximum value of SAR (measured) = 0.374 W/kg




**Test Plot 32#: WCDMA Band 2\_Body Right\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used: 1880 MHz;  $\sigma = 1.562 \text{ S/m}$ ;  $\epsilon_r = 51.432$ ;  $\rho = 1000 \text{ kg/m}^3$ ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) =  $0.219 \text{ W/kg}$ **Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ Reference Value =  $10.13 \text{ V/m}$ ; Power Drift =  $0.06 \text{ dB}$ Peak SAR (extrapolated) =  $0.317 \text{ W/kg}$ **SAR(1 g) =  $0.197 \text{ W/kg}$ ; SAR(10 g) =  $0.119 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.215 \text{ W/kg}$ 



**Test Plot 33#: WCDMA Band 2\_Body Bottom\_Low Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1  
Medium parameters used: 1852.4 MHz;  $\sigma = 1.522$  S/m;  $\epsilon_r = 51.545$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.941 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.38 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.37 W/kg

**SAR(1 g) = 0.822 W/kg; SAR(10 g) = 0.438 W/kg**

Maximum value of SAR (measured) = 0.936 W/kg



**Test Plot 34#: WCDMA Band 2\_Body Bottom\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used: 1880 MHz;  $\sigma = 1.562 \text{ S/m}$ ;  $\epsilon_r = 51.432$ ;  $\rho = 1000 \text{ kg/m}^3$ ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.02 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.67 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.50 W/kg

**SAR(1 g) = 0.894 W/kg; SAR(10 g) = 0.475 W/kg**

Maximum value of SAR (measured) = 1.02 W/kg



**Test Plot 35#: WCDMA Band 2\_Body Bottom\_High Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1907.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1907.6 MHz;  $\sigma = 1.581$  S/m;  $\epsilon_r = 51.36$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(7.98, 7.98, 7.98); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.08 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.59 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 0.927 W/kg; SAR(10 g) = 0.488 W/kg**

Maximum value of SAR (measured) = 1.05 W/kg



**Test Plot 36#: WCDMA Band 4\_Head Left Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.365$  S/m;  $\epsilon_r = 41.258$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.47, 8.47, 8.47); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.492 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.012 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.742 W/kg

**SAR(1 g) = 0.468 W/kg; SAR(10 g) = 0.298 W/kg**

Maximum value of SAR (measured) = 0.509 W/kg



**Test Plot 37#: WCDMA Band 4\_Head Left Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.365$  S/m;  $\epsilon_r = 41.258$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.47, 8.47, 8.47); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.135 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.578 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.180 W/kg

**SAR(1 g) = 0.124 W/kg; SAR(10 g) = 0.081 W/kg**

Maximum value of SAR (measured) = 0.133 W/kg



**Test Plot 38#: WCDMA Band 4\_Head Right Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.365$  S/m;  $\epsilon_r = 41.258$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.47, 8.47, 8.47); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.493 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.185 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.723 W/kg

**SAR(1 g) = 0.476 W/kg; SAR(10 g) = 0.313 W/kg**

Maximum value of SAR (measured) = 0.507 W/kg



**Test Plot 39#: WCDMA Band 4\_Head Right Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.365$  S/m;  $\epsilon_r = 41.258$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.47, 8.47, 8.47); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.164 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.20 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.218 W/kg

**SAR(1 g) = 0.142 W/kg; SAR(10 g) = 0.094 W/kg**

Maximum value of SAR (measured) = 0.153 W/kg



**Test Plot 40#: WCDMA Band 4\_Body Worn Back\_Low Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1712.4 MHz; Duty Cycle: 1:1  
Medium parameters used: 1712.4 MHz;  $\sigma = 1.496$  S/m;  $\epsilon_r = 52.18$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.26 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.58 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.94 W/kg

**SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.623 W/kg**

Maximum value of SAR (measured) = 1.21 W/kg





**Test Plot 41#: WCDMA Band 4\_Body Worn Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.516$  S/m;  $\epsilon_r = 52.109$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.33 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.67 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 2.17 W/kg

**SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.635 W/kg**

Maximum value of SAR (measured) = 1.30 W/kg



**Test Plot 42#: WCDMA Band 4\_Body Worn Back\_High Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1752.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1752.6 MHz;  $\sigma = 1.545$  S/m;  $\epsilon_r = 51.957$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.43 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.79 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.42 W/kg

**SAR(1 g) = 1.26 W/kg; SAR(10 g) = 0.690 W/kg**

Maximum value of SAR (measured) = 1.41 W/kg



**Test Plot 43#: WCDMA Band 4\_Body Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.516$  S/m;  $\epsilon_r = 52.109$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.779 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.21 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.18 W/kg

**SAR(1 g) = 0.691 W/kg; SAR(10 g) = 0.428 W/kg**

Maximum value of SAR (measured) = 0.750 W/kg



**Test Plot 44#: WCDMA Band 4\_Body Left\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.516$  S/m;  $\epsilon_r = 52.109$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.155 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.181 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.234 W/kg

**SAR(1 g) = 0.147 W/kg; SAR(10 g) = 0.092 W/kg**

Maximum value of SAR (measured) = 0.159 W/kg



**Test Plot 45#: WCDMA Band 4\_Body Right\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.516$  S/m;  $\epsilon_r = 52.109$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.504 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.32 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.690 W/kg

**SAR(1 g) = 0.422 W/kg; SAR(10 g) = 0.244 W/kg**

Maximum value of SAR (measured) = 0.463 W/kg



**Test Plot 46#: WCDMA Band 4\_Body Bottom\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 1732.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 1732.6 MHz;  $\sigma = 1.516$  S/m;  $\epsilon_r = 52.109$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.688 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.12 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.00 W/kg

**SAR(1 g) = 0.621 W/kg; SAR(10 g) = 0.339 W/kg**

Maximum value of SAR (measured) = 0.699 W/kg



**Test Plot 47#: WCDMA Band 5\_Head Left Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.452 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.690 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.531 W/kg

**SAR(1 g) = 0.422 W/kg; SAR(10 g) = 0.323 W/kg**

Maximum value of SAR (measured) = 0.445 W/kg



**Test Plot 48#: WCDMA Band 5\_Head Left Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.245 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.49 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.289 W/kg

**SAR(1 g) = 0.234 W/kg; SAR(10 g) = 0.183 W/kg**

Maximum value of SAR (measured) = 0.244 W/kg





**Test Plot 49#: WCDMA Band 5\_Head Right Cheek\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.359 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.909 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.426 W/kg

**SAR(1 g) = 0.338 W/kg; SAR(10 g) = 0.260 W/kg**

Maximum value of SAR (measured) = 0.357 W/kg



**Test Plot 50#: WCDMA Band 5\_Head Right Tilt\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 0.893$  S/m;  $\epsilon_r = 41.902$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.84, 9.84, 9.84); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: SAM1; Type: QD000P40CC; Serial: TP:1412
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.250 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.67 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.302 W/kg

**SAR(1 g) = 0.243 W/kg; SAR(10 g) = 0.187 W/kg**

Maximum value of SAR (measured) = 0.253 W/kg



**Test Plot 51#: WCDMA Band 5\_Body Worn Back\_Low Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1  
Medium parameters used: 826.4 MHz;  $\sigma = 0.99$  S/m;  $\epsilon_r = 53.21$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.948 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.58 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.42 W/kg

**SAR(1 g) = 0.758 W/kg; SAR(10 g) = 0.431 W/kg**

Maximum value of SAR (measured) = 0.840 W/kg



**Test Plot 52#: WCDMA Band 5\_Body Worn Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.09 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.83 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.62 W/kg

**SAR(1 g) = 0.868 W/kg; SAR(10 g) = 0.488 W/kg**

Maximum value of SAR (measured) = 0.962 W/kg



**Test Plot 53#: WCDMA Band 5\_Body Worn Back\_High Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 846.6 MHz;  $\sigma = 0.992$  S/m;  $\epsilon_r = 53.098$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.14 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.63 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.73 W/kg

**SAR(1 g) = 0.912 W/kg; SAR(10 g) = 0.506 W/kg**

Maximum value of SAR (measured) = 1.01 W/kg



**Test Plot 54#: WCDMA Band 5\_Body Back\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.545 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.83 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.674 W/kg

**SAR(1 g) = 0.520 W/kg; SAR(10 g) = 0.388 W/kg**

Maximum value of SAR (measured) = 0.546 W/kg



**Test Plot 55#: WCDMA Band 5\_Body Left\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.218 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.33 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.284 W/kg

**SAR(1 g) = 0.205 W/kg; SAR(10 g) = 0.144 W/kg**

Maximum value of SAR (measured) = 0.218 W/kg



**Test Plot 56#: WCDMA Band 5\_Body Right\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (111x41x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.245 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.10 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.320 W/kg

**SAR(1 g) = 0.230 W/kg; SAR(10 g) = 0.161 W/kg**

Maximum value of SAR (measured) = 0.246 W/kg





**Test Plot 57#: WCDMA Band 5\_Body Bottom\_Middle Channel****DUT: Mobile phone; Type: NEO X2; Serial: 16101000721**

Communication System: Generic WCDMA; Frequency: 836.6 MHz; Duty Cycle: 1:1  
Medium parameters used: 836.6 MHz;  $\sigma = 1.008$  S/m;  $\epsilon_r = 53.194$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(9.89, 9.89, 9.89); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.0924 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.291 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.135 W/kg

**SAR(1 g) = 0.086 W/kg; SAR(10 g) = 0.057 W/kg**

Maximum value of SAR (measured) = 0.0923 W/kg

