




RF TEST REPORT



Report No.: 16071332-FCC-R1

Supersede Report No.: N/A

Applicant	BLU Products, Inc.	
Product Name	Mobile Phone	
Model No.	GRAND X	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; FCC Part 27:2015; ANSI/TIA-603-D: 2010	
Test Date	December 07 to 20, 2016	
Issue Date	December 21, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16071332-FCC-R1
Page	3 of 98

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	10
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	11
6.1 RF EXPOSURE (SAR).....	11
6.2 RF OUTPUT POWER	12
6.3 PEAK-AVERAGE RATIO.....	25
6.4 OCCUPIED BANDWIDTH.....	30
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	45
6.6 SPURIOUS RADIATED EMISSIONS	61
6.7 BAND EDGE.....	68
6.8 FREQUENCY STABILITY	82
ANNEX A. TEST INSTRUMENT.....	87
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	89
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	94
ANNEX C.II. EUT OPERATING CONKITIONS	96
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	97
ANNEX E. DECLARATION OF SIMILARITY	98

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071332-FCC-R1	NONE	Original	December 21, 2016

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	GRAND X
Serial Model:	N/A
Date EUT received:	December 06, 2016
Test Date(s):	December 07 to 20, 2016
Equipment Category :	PCE
Antenna Gain:	GSM850: -1.0dBi PCS1900:-0.6dBi UMTS-FDD Band V: -0.6dBi UMTS-FDD Band IV: -1.0dBi UMTS-FDD Band II: -1.0dBi WIFI: -1.0dBi Bluetooth/BLE: -1.0dBi GPS: -1.0dBi
Antenna Type:	GSM/PCS/UMTS-FDD :PIFA antenna WIFI/BT/BLE/GPS : Metallic Antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
 UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
 UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
 RX : 2112.4 ~ 2152.6 MHz
 RF Operating Frequency (ies): UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
 RX: 1932.4 ~ 1987.6 MHz
 WIFI: 802.11b/g/n(20M): 2412-2462 MHz
 WIFI: 802.11n(40M): 2422-2452 MHz
 Bluetooth& BLE: 2402-2480 MHz
 GPS: 1575.42 MHz

 GSM Voice:GSM850: 32.40dBm
 PCS1900: 30.12dBm
 GPRS:GSM850: 32.37 dBm
 PCS1900: 30.10dBm
 EGPRS(MCS1):GSM850: 32.35dBm
 PCS1900: 29.93 dBm
 EGPRS(MCS5):GSM850: 27.35 dBm
 PCS1900: 26.90 dBm
 Maximum Conducted
 AV Power to Antenna: RMC:UMTS-FDD Band V: 22.36 dBm
 UMTS-FDD Band II: 22.48 dBm
 UMTS-FDD Band IV: 22.69 dBm
 HSDPA:UMTS-FDD Band V: 21.39 dBm
 UMTS-FDD Band II: 21.39 dBm
 UMTS-FDD Band IV: 21.69 dBm
 HSUPA:UMTS-FDD Band V: 21.42 dBm
 UMTS-FDD Band II: 21.38 dBm
 UMTS-FDD Band IV: 21.60 dBm

	GSM Voice:GSM850: 29.25 dBm / ERP
	PCS1900: 29.52 dBm / EIRP
	GPRS:GSM850: 29.22 dBm / ERP
	PCS1900: 29.50 dBm / EIRP
	EGPRS(MCS5):GSM850: 24.20 dBm / ERP
	PCS1900: 26.30 dBm / EIRP
ERP/EIRP:	RMC:UMTS-FDD Band V: 19.61dBm / ERP
	UMTS-FDD Band II: 21.48 dBm / EIRP
	UMTS-FDD Band IV: 21.69 dBm / EIRP
	HSUPA:UMTS-FDD Band V: 18.64 dBm / ERP
	UMTS-FDD Band II: 20.39 dBm / EIRP
	UMTS-FDD Band IV: 20.69 dBm / EIRP
	HSDPA:UMTS-FDD Band V: 18.66dBm / ERP
	UMTS-FDD Band II: 20.39 dBm / EIRP
	UMTS-FDD Band IV: 20.60 dBm / EIRP
	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band IV: 202CH
	UMTS-FDD Band II: 277CH
Number of Channels:	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
	GPS:1CH
Port:	USB Port, Earphone Port
	Adapter:
	Model: US-ZC-1005
	Input: AC100-240V~50/60Hz,0.4A
Input Power:	Output: DC 5.0V,1.0A
	Battery:
	Model:C806239220L
	Spec: 3.8V,2200mAh,8.36Wh

Test Report	16071332-FCC-R1
Page	9 of 98

Trade Name : BLU

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: YHLBLUGRANDX

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 16071332-FCC-H.

6.2 RF Output Power

Temperature	24°C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	December 19, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>
§27.50 (c)	c)	EIRP: 30dBm	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Base Station EUT</p>
------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Report	16071332-FCC-R1
Page	13 of 98

	<p>frequency was investigated.</p> <ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.38	32.36	32.40	32±1	30.12	29.77	29.46	30±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.36	32.35	32.37	32±1	30.10	30.05	29.99	30±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.58	31.59	31.57	31±1	29.4	29.26	29.11	28±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	28.73	28.77	28.74	28±1	26.53	26.47	26.39	26±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	32.33	32.34	32.35	32±1	29.93	29.86	29.82	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.59	31.57	31.58	31±1	29.36	29.24	29.12	29±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	28.74	28.71	28.72	28±1	26.54	26.48	26.41	26±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	27.34	27.33	27.35	27±1	26.90	26.86	26.79	26±1
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	26.60	26.57	26.56	26±1	26.36	26.21	26.08	26±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	23.69	23.7	23.72	23±1	23.55	23.46	23.74	23±1

Test Report	16071332-FCC-R1
Page	15 of 98

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	22.36	22±1
	4175	835	22.35	22±1
	4233	846.6	22.25	22±1
HSDPA Subtest1	4132	826.4	21.36	21.3±1
	4175	835	21.39	21.3±1
	4233	846.6	21.35	21.3±1
HSDPA Subtest2	4132	826.4	21.33	21.3±1
	4175	835	21.33	21.3±1
	4233	846.6	21.32	21.3±1
HSDPA Subtest3	4132	826.4	21.36	21.3±1
	4175	835	21.39	21.3±1
	4233	846.6	21.35	21.3±1
HSDPA Subtest4	4132	826.4	21.37	21.3±1
	4175	835	21.34	21.3±1
	4233	846.6	21.33	21.3±1
HSUPA Subtest1	4132	826.4	21.31	21.3±1
	4175	835	21.36	21.3±1
	4233	846.6	21.39	21.3±1
HSUPA Subtest2	4132	826.4	21.41	21.3±1
	4175	835	21.42	21.3±1
	4233	846.6	21.36	21.3±1
HSUPA Subtest3	4132	826.4	21.36	21.3±1
	4175	835	21.33	21.3±1
	4233	846.6	21.39	21.3±1
HSUPA Subtest4	4132	826.4	21.35	21.3±1
	4175	835	21.36	21.3±1
	4233	846.6	21.33	21.3±1
HSUPA Subtest5	4132	826.4	21.41	21.3±1
	4175	835	21.33	21.3±1
	4233	846.6	21.37	21.3±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.48	22±1
	9400	1880	22.30	22±1
	9538	1907.6	22.37	22±1
HSDPA Subtest1	9262	1852.4	21.36	21.3±1
	9400	1880	21.35	21.3±1
	9538	1907.6	21.39	21.3±1
HSDPA Subtest2	9262	1852.4	21.32	21.3±1
	9400	1880	21.36	21.3±1
	9538	1907.6	21.39	21.3±1
HSDPA Subtest3	9262	1852.4	21.35	21.3±1
	9400	1880	21.39	21.3±1
	9538	1907.6	21.35	21.3±1
HSDPA Subtest4	9262	1852.4	21.34	21.3±1
	9400	1880	21.33	21.3±1
	9538	1907.6	21.31	21.3±1
HSUPA Subtest1	9262	1852.4	21.36	21.3±1
	9400	1880	21.36	21.3±1
	9538	1907.6	21.36	21.3±1
HSUPA Subtest2	9262	1852.4	21.33	21.3±1
	9400	1880	21.32	21.3±1
	9538	1907.6	21.38	21.3±1
HSUPA Subtest3	9262	1852.4	21.36	21.3±1
	9400	1880	21.34	21.3±1
	9538	1907.6	21.36	21.3±1
HSUPA Subtest4	9262	1852.4	21.39	21.3±1
	9400	1880	21.37	21.3±1
	9538	1907.6	21.32	21.3±1
HSUPA Subtest5	9262	1852.4	21.33	21.3±1
	9400	1880	21.37	21.3±1
	9538	1907.6	21.35	21.3±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	22.69	22±1
	1413	1732.6	22.34	22±1
	1512	1752.4	22.51	22±1
HSDPA Subtest1	1313	1712.6	21.53	21.3±1
	1413	1732.6	21.54	21.3±1
	1512	1752.4	21.36	21.3±1
HSDPA Subtest2	1313	1712.6	21.69	21.3±1
	1413	1732.6	21.21	21.3±1
	1512	1752.4	21.39	21.3±1
HSDPA Subtest3	1313	1712.6	21.35	21.3±1
	1413	1732.6	21.42	21.3±1
	1512	1752.4	21.46	21.3±1
HSDPA Subtest4	1313	1712.6	21.54	21.3±1
	1413	1732.6	21.53	21.3±1
	1512	1752.4	21.34	21.3±1
HSUPA Subtest1	1313	1712.6	21.37	21.3±1
	1413	1732.6	21.39	21.3±1
	1512	1752.4	21.33	21.3±1
HSUPA Subtest2	1313	1712.6	21.38	21.3±1
	1413	1732.6	21.35	21.3±1
	1512	1752.4	21.33	21.3±1
HSUPA Subtest3	1313	1712.6	21.36	21.3±1
	1413	1732.6	21.34	21.3±1
	1512	1752.4	21.33	21.3±1
HSUPA Subtest4	1313	1712.6	21.39	21.3±1
	1413	1732.6	21.37	21.3±1
	1512	1752.4	21.38	21.3±1
HSUPA Subtest5	1313	1712.6	21.36	21.3±1
	1413	1732.6	21.60	21.3±1
	1512	1752.4	21.52	21.3±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	22.96	V	6.8	0.53	29.23	38.45
824.2	21.69	H	6.8	0.53	27.96	38.45
836.6	22.94	V	6.8	0.53	29.21	38.45
836.6	21.67	H	6.8	0.53	27.94	38.45
848.8	22.88	V	6.9	0.53	29.25	38.45
848.8	21.67	H	6.9	0.53	28.04	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.49	V	7.88	0.85	29.52	33
1850.2	21.28	H	7.88	0.85	28.31	33
1880	22.14	V	7.88	0.85	29.17	33
1880	21.02	H	7.88	0.85	28.05	33
1909.8	21.85	V	7.86	0.85	28.86	33
1909.8	20.63	H	7.86	0.85	27.64	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	22.95	V	6.8	0.53	29.22	38.45
824.2	21.92	H	6.8	0.53	28.19	38.45
836.6	22.93	V	6.8	0.53	29.20	38.45
836.6	21.86	H	6.8	0.53	28.13	38.45
848.8	22.84	V	6.9	0.53	29.21	38.45
848.8	21.79	H	6.9	0.53	28.16	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.47	V	7.88	0.85	29.50	33
1850.2	21.34	H	7.88	0.85	28.37	33
1880	22.42	V	7.88	0.85	29.45	33
1880	21.28	H	7.88	0.85	28.31	33
1909.8	22.38	V	7.86	0.85	29.39	33
1909.8	21.21	H	7.86	0.85	28.22	33

EGPRS (MCS5):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	17.93	V	6.8	0.53	24.20	38.45
824.2	16.84	H	6.8	0.53	23.11	38.45
836.6	17.91	V	6.8	0.53	24.18	38.45
836.6	16.8	H	6.8	0.53	23.07	38.45
848.8	17.82	V	6.9	0.53	24.19	38.45
848.8	16.72	H	6.9	0.53	23.09	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	19.23	V	7.88	0.85	26.26	33
1850.2	18.13	H	7.88	0.85	25.16	33
1880	19.27	V	7.88	0.85	26.30	33
1880	18.01	H	7.88	0.85	25.04	33
1909.8	19.18	V	7.86	0.85	26.19	33
1909.8	18.07	H	7.86	0.85	25.08	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.34	V	6.8	0.53	19.61	38.45
826.4	12.19	H	6.8	0.53	18.46	38.45
835	13.33	V	6.8	0.53	19.60	38.45
835	12.06	H	6.8	0.53	18.33	38.45
846.6	13.13	V	6.9	0.53	19.50	38.45
846.6	12.04	H	6.9	0.53	18.41	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.45	V	7.88	0.85	21.48	33
1852.4	13.32	H	7.88	0.85	20.35	33
1880	14.27	V	7.88	0.85	21.30	33
1880	13.15	H	7.88	0.85	20.18	33
1907.6	14.36	V	7.86	0.85	21.37	33
1907.6	13.25	H	7.86	0.85	20.26	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	14.75	V	7.76	0.82	21.69	30
1712.4	13.64	H	7.76	0.82	20.58	30
1740	14.4	V	7.76	0.82	21.34	30
1740	13.48	H	7.76	0.82	20.42	30
1752.6	14.59	V	7.74	0.82	21.51	30
1752.6	13.54	H	7.74	0.82	20.46	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.35	V	6.8	0.53	18.62	38.45
826.4	11.22	H	6.8	0.53	17.49	38.45
835	12.37	V	6.8	0.53	18.64	38.45
835	11.17	H	6.8	0.53	17.44	38.45
846.6	12.23	V	6.9	0.53	18.60	38.45
846.6	11.14	H	6.9	0.53	17.51	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.33	V	7.88	0.85	20.36	33
1852.4	12.19	H	7.88	0.85	19.22	33
1880	13.32	V	7.88	0.85	20.35	33
1880	12.15	H	7.88	0.85	19.18	33
1907.6	13.38	V	7.86	0.85	20.39	33
1907.6	12.3	H	7.86	0.85	19.31	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	13.75	V	7.76	0.82	20.69	30
1712.4	12.41	H	7.76	0.82	19.35	30
1740	13.6	V	7.76	0.82	20.54	30
1740	12.33	H	7.76	0.82	19.27	30
1752.6	13.54	V	7.74	0.82	20.46	30
1752.6	17.23	H	7.74	0.82	19.31	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.39	V	6.8	0.53	18.66	38.45
826.4	11.22	H	6.8	0.53	17.49	38.45
835	12.4	V	6.8	0.53	18.67	38.45
835	11.26	H	6.8	0.53	17.53	38.45
846.6	12.27	V	6.9	0.53	18.64	38.45
846.6	11.05	H	6.9	0.53	17.42	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.36	V	7.88	0.85	20.39	33
1852.4	12.08	H	7.88	0.85	19.11	33
1880	13.34	V	7.88	0.85	20.37	33
1880	11.99	H	7.88	0.85	19.02	33
1907.6	13.35	V	7.86	0.85	20.36	33
1907.6	12.17	H	7.86	0.85	19.18	33

EIRP for UMTS-FDD Band IV (Part 27H)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	13.45	V	7.76	0.82	20.39	30
1712.4	12.19	H	7.76	0.82	19.13	30
1740	13.66	V	7.76	0.82	20.60	30
1740	12.43	H	7.76	0.82	19.37	30
1752.6	13.6	V	7.74	0.82	20.52	30
1752.6	12.41	H	7.74	0.82	19.33	30

6.3 Peak-Average Ratio

Temperature	24°C
Relative Humidity	52%
Atmospheric Pressure	1019mbar
Test date :	December 19, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	<input checked="" type="checkbox"/>

Test Setup	 <p>The diagram illustrates the test setup. On the left is a green box labeled 'Base Station'. A cable connects its output to the input of a green box labeled 'Spectrum Analyzer'. Another cable connects the output of the Spectrum Analyzer to a blue box labeled 'EUT' (Equipment Under Test).</p>
------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Procedure	<p>According with KDB 971168 v02r02</p> <p>5.7.2 Alternate procedure for PAPR</p> <p>5.1.2 Peak power measurements with a peak power meter</p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p>5.2.3 Average power measurement with average power meter</p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output</p>
----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Report	16071332-FCC-R1
Page	26 of 98

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	32.36	30.12	2.24
1880	31.49	29.77	1.72
1909.8	31.27	29.46	1.81

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	32.6	30.1	2.50
1880	32.16	30.05	2.11
1909.8	31.21	29.99	1.22

EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	28.36	26.86	1.50
1880	28.29	26.9	1.39
1909.8	28.41	26.79	1.62

RMC : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	26.07	22.48	3.59
1880	25.76	22.3	3.46
1907.6	25.32	22.37	2.95

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	26.32	22.69	3.63
1740	25.66	22.34	3.32
1752.6	26.06	22.51	3.55

HSUPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.41	21.36	3.05
1880	24.26	21.36	2.9
1907.6	24.39	21.36	3.03

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	34.36	21.37	12.99
1740	24.32	21.39	2.93
1752.6	24.31	21.33	2.98

HSDPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.42	21.36	3.06
1880	24.41	21.35	3.06
1907.6	24.45	21.39	3.06

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	25.36	21.53	3.83
1740	24.29	21.54	2.75
1752.6	24.46	21.36	3.10

6.4 Occupied Bandwidth

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup	<p>Base Station Spectrum Analyzer EUT</p>		
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	244.9521	321.101
190	836.6	244.2062	320.688
251	848.8	248.9482	319.087

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.2963	320.136
661	1880.0	244.9704	320.818
810	1909.8	245.7402	320.574

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.8757	319.583
190	836.6	243.9963	322.695
251	848.8	243.9761	320.512

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.3004	319.454
661	1880.0	244.1782	319.163
810	1909.8	247.6744	320.421

EGPRS (MCS 5):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	245.3513	322.234
190	836.6	246.5125	320.580
251	848.8	247.3617	321.024

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	242.9436	320.101
661	1880.0	245.2340	320.091
810	1909.8	245.7457	320.149

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1586	4.713
4175	835.0	4.1529	4.703
4233	846.6	4.1576	4.720

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1528	4.701
9400	1880.0	4.1524	4.706
9538	1907.6	4.1607	4.696

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1645	4.705
1413	1733	4.1559	4.715
1512	1752	4.1523	4.706

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.1610	4.696
4175	835.0	4.1577	4.721
4233	846.6	4.1455	4.721

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1598	4.714
9400	1880.0	4.1608	4.724
9538	1907.6	4.1581	4.720

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1564	4.703
1413	1733	4.1601	4.727
1512	1752	4.1517	4.702

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1645	4.711
4175	835.0	4.1630	4.707
4233	846.6	4.1528	4.718

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1628	4.700
9400	1880.0	4.1576	4.717
9538	1907.6	4.1574	4.708

UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.1653	4.737
1413	1733	4.1628	4.725
1512	1752	4.1584	4.694

Test Plots


GMS Voice:





GPRS:




EGPRS:




RMC:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.6 MHz




Band II BW - Low CH 1853MHz




Band II BW - Mid CH 1880MHz


Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

HSUPA:






Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz





Band IV BW - High CH 1752MHz



HSDPA:



Band V BW - Low CH 826.6 MHz




Band V BW - High CH 846.4 MHz




Band II BW - Mid CH 1880MHz


Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz



Band IV BW - High CH 1752MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup	<p style="text-align: center;">Base Station Spectrum Analyzer EUT</p>		
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:

Cellular Band (Part 22H) result




PCS Band (Part24E) result




GPRS:

Cellular Band (Part 22H) result




PCS Band (Part24E) result




EGPRS (MCS 5):

Cellular Band (Part 22H) result




PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSUPA:


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2

UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSDPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)



UMTS-FDD Band IV (Part 27)




6.6 Spurious Radiated Emissions

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--------------------------------------------------------------------------------------

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Test Report	16071332-FCC-R1
Page	62 of 98

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-44.36	V	7.95	0.78	-37.19	-13	-24.19
1648.4	-45.11	H	7.95	0.78	-37.94	-13	-24.94
323.6	-52.18	V	6.4	0.26	-46.04	-13	-33.04
611.8	-52.62	H	6.8	0.37	-46.19	-13	-33.19

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.58	V	7.95	0.78	-36.41	-13	-23.41
1673.2	-44.96	H	7.95	0.78	-37.79	-13	-24.79
323.9	-52.33	V	6.4	0.26	-46.19	-13	-33.19
311.2	-52.71	H	6.8	0.37	-46.28	-13	-33.28

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.42	V	7.95	0.78	-36.25	-13	-23.25
1697.6	-45.03	H	7.95	0.78	-37.86	-13	-24.86
323.4	-52.81	V	6.4	0.26	-46.67	-13	-33.67
311.5	-52.94	H	6.8	0.37	-46.51	-13	-33.51

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-49.12	V	10.25	2.73	-41.6	-13	-28.6
3700.4	-49.63	H	10.25	2.73	-42.11	-13	-29.11
322.9	-54.27	V	6.4	0.26	-48.13	-13	-35.13
310.8	-54.33	H	6.8	0.37	-47.9	-13	-34.9

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.99	V	10.25	2.73	-41.47	-13	-28.47
3760	-49.57	H	10.25	2.73	-42.05	-13	-29.05
322.7	-53.85	V	6.4	0.26	-47.71	-13	-34.71
310.5	-53.97	H	6.8	0.37	-47.54	-13	-34.54

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-49.06	V	10.36	2.73	-41.43	-13	-28.43
3819.6	-49.31	H	10.36	2.73	-41.68	-13	-28.68
322.3	-53.94	V	6.4	0.26	-47.8	-13	-34.8
310.1	-54.12	H	6.8	0.37	-47.69	-13	-34.69

Note:

1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-47.15	V	7.95	0.78	-39.98	-13	-26.98
1652.8	-46.22	H	7.95	0.78	-39.05	-13	-26.05
324.4	-53.28	V	6.4	0.26	-47.14	-13	-34.14
312.6	-53.46	H	6.8	0.37	-47.03	-13	-34.03

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-47.03	V	7.95	0.78	-39.86	-13	-26.86
1670	-46.34	H	7.95	0.78	-39.17	-13	-26.17
324.1	-52.91	V	6.4	0.26	-46.77	-13	-33.77
312.8	-53.26	H	6.8	0.37	-46.83	-13	-33.83

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-47.29	V	7.95	0.78	-40.12	-13	-27.12
1693.2	-47.77	H	7.95	0.78	-40.6	-13	-27.6
324.5	-53.02	V	6.4	0.26	-46.88	-13	-33.88
312.3	-53.68	H	6.8	0.37	-47.25	-13	-34.25

Note:

1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-49.91	V	10.25	2.73	-42.39	-13	-29.39
3704.8	-50.06	H	10.25	2.73	-42.54	-13	-29.54
325.7	-53.68	V	6.4	0.26	-47.54	-13	-34.54
313.9	-53.52	H	6.8	0.37	-47.09	-13	-34.09

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-49.88	V	10.25	2.73	-42.36	-13	-29.36
3760	-49.97	H	10.25	2.73	-42.45	-13	-29.45
325.4	-53.85	V	6.4	0.26	-47.71	-13	-34.71
313.3	-53.74	H	6.8	0.37	-47.31	-13	-34.31

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-49.78	V	10.36	2.73	-42.15	-13	-29.15
3815.2	-49.93	H	10.36	2.73	-42.3	-13	-29.3
325.5	-53.88	V	6.4	0.26	-47.74	-13	-34.74
313.1	-53.72	H	6.8	0.37	-47.29	-13	-34.29

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.15	V	10.07	2.52	-38.6	-13	-25.6
3424.8	-48.59	H	10.07	2.52	-41.04	-13	-28.04
325.7	-57.33	V	6.4	0.26	-51.19	-13	-38.19
739.4	-53.24	H	7.1	0.42	-46.56	-13	-33.56

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-46.32	V	10.09	2.52	-38.75	-13	-25.75
3480	-48.49	H	10.09	2.52	-40.92	-13	-27.92
325.3	-57.12	V	6.4	0.26	-50.98	-13	-37.98
739.1	-53.43	H	7.1	0.42	-46.75	-13	-33.75

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-46.08	V	10.09	2.52	-38.51	-13	-25.51
3505.2	-46.94	H	10.09	2.52	-39.37	-13	-26.37
325.2	-57.62	V	6.4	0.26	-51.48	-13	-38.48
739.5	-52.91	H	7.1	0.42	-46.23	-13	-33.23

Note:

1, The testing has been conformed to $10 \times 1752.6 \text{ MHz} = 17,526 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

6.7 Band Edge

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup	 <p>The diagram illustrates the test setup. A Base Station (green box) and a Spectrum Analyzer (green box) are connected to a power divider (black box). The power divider is then connected to the EUT (blue box). The Base Station and Spectrum Analyzer are both connected to the power divider, which then splits the signal to the EUT.</p>		
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9800	-16.76	-13
849.0200	-14.88	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.01	-13
1910.0200	-15.65	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-14.39	-13
849.0225	-16.32	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.91	-13
1910.0025	-16.11	-13

EGPRS (MCS5):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-16.41	-13
849.0050	-15.53	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.40	-13
1910.0025	-15.37	-13

RCM:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.125	-24.49	-13
849.750	-27.77	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.700	-26.51	-13
1910.325	-30.61	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.025	-25.84	-13
1755.250	-28.83	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.175	-25.23	-13
850.100	-26.96	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.700	-26.33	-13
1910.850	-31.48	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.025	-26.59	-13
1755.300	-27.83	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.775	-25.96	-13
849.750	-27.90	-13

UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1848.825	-26.38	-13
1910.325	-31.53	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.800	-26.15	-13
1756.050	-27.60	-13


GSM Voice:

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.21/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.19/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.20/3)=4.5+0.3=4.8dB




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.20/3)=4.5+0.3=4.8dB


GPRS:

Test Plots




EGPRS (MCS5):

Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.13/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.20/30)=4.0+2.0=6.0 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.01/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(46.96/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.05/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.0) + 10log
(47.06/30)=4.5+2.0=6.5 dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.96/30)=4.0+1.9=5.9dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.21/30)=4.0+2.0=6.0 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.14/30)=4.5+2.0=6.5 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.20/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.03/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.02/30)=4.5+2.0=6.5 dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.11/30)=4.0+2.0=6.0 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.18/30)=4.0+2.0=6.0 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.00/30)=4.5+1.9=6.4 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.08/30)=4.5+2.0=6.5 dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.37/30)=4.5+2.0=6.5 dB




UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log
(46.94/30)=4.5+1.9=6.4 dB

6.8 Frequency Stability

Temperature	23°C
Relative Humidity	56%
Atmospheric Pressure	1014mbar
Test date :	December 14, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 <p>The diagram illustrates the test setup. On the left, a green rectangular box represents the 'Base Station'. A horizontal line connects a small circle on the right side of the Base Station to another small circle on the left side of a blue rectangular box. This blue box is enclosed within a dashed-line rectangle labeled 'Thermal Chamber' at the bottom.</p>																																		

Test Report	16071332-FCC-R1
Page	83 of 98

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0227	2.5
0		15	0.0179	2.5
10		16	0.0191	2.5
20		17	0.0203	2.5
30		15	0.0179	2.5
40		15	0.0179	2.5
50		14	0.0167	2.5
55		17	0.0203	2.5
25	4.2	19	0.0227	2.5
	3.5	15	0.0179	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	14	0.0074	2.5
0		19	0.0101	2.5
10		15	0.0080	2.5
20		13	0.0069	2.5
30		14	0.0074	2.5
40		17	0.0090	2.5
50		15	0.0080	2.5
55		18	0.0096	2.5
25	4.2	15	0.0080	2.5
	3.5	15	0.0080	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0228	2.5
0		20	0.0240	2.5
10		16	0.0192	2.5
20		20	0.0240	2.5
30		14	0.0168	2.5
40		17	0.0204	2.5
50		16	0.0192	2.5
55		13	0.0156	2.5
25	4.2	17	0.0204	2.5
	3.5	15	0.0180	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0080	2.5
0		16	0.0085	2.5
10		14	0.0074	2.5
20		19	0.0101	2.5
30		15	0.0080	2.5
40		12	0.0064	2.5
50		16	0.0085	2.5
55		14	0.0074	2.5
25	4.2	17	0.0090	2.5
	3.5	13	0.0069	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1733$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0180	2.5
0		16	0.0192	2.5
10		19	0.0228	2.5
20		14	0.0168	2.5
30		13	0.0156	2.5
40		125	0.1497	2.5
50		20	0.0240	2.5
55		14	0.0168	2.5
25	4.2	17	0.0204	2.5
	3.5	16	0.0192	2.5

Annex A. TEST INSTRUMENT


Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>


Test Report	16071332-FCC-R1
Page	88 of 98

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo





EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View


Annex B.ii. Photograph: EUT Internal Photo




Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View



Mainboard without Shielding - Front View




Mainboard with Shielding – Rear View




Mainboard without Shielding - Rear View



LCD – Front View



LCD – Rear View




GSM/PCS/UMTS-FDD Antenna View




WIFI/BT/BLE/GPS – Metallic Antenna View

Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
BLU Products, Inc.	Adapter	US-ZC-1005	D0523

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	D0523

Test Report	16071332-FCC-R1
Page	96 of 98

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	16071332-FCC-R1
Page	97 of 98

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report	16071332-FCC-R1
Page	98 of 98

Annex E. DECLARATION OF SIMILARITY

N/A