

# FCC RF Test Report


APPLICANT : CT Asia  
EQUIPMENT : Tablet PC  
BRAND NAME : BLU  
MODEL NAME : Touch Book 7.0 3G  
FCC ID : YHLBLUTB703G  
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)  
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Apr. 15, 2014 and testing was completed on May 04, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.

## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification subjective to this standard.....	6
1.5 Modification of EUT .....	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	7
1.7 Testing Location .....	8
1.8 Applicable Standards .....	8
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System .....	11
2.3 Support Unit used in test configuration .....	11
2.4 Measurement Results Explanation Example .....	11
<b>3 TEST RESULT.....</b>	<b>12</b>
3.1 Conducted Output Power Measurement.....	12
3.2 Peak-to-Average Ratio .....	14
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	20
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	24
3.5 Band Edge Measurement.....	38
3.6 Conducted Spurious Emission Measurement.....	47
3.7 Field Strength of Spurious Radiation Measurement .....	58
3.8 Frequency Stability Measurement.....	68
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>73</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>74</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	

## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG441502	Rev. 01	Initial issue of report	May 13, 2014

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< $43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< $43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< $43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 26.33 dB at 2510.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

# 1 General Description

## 1.1 Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

## 1.2 Manufacturer

Nanjing Wanlida Technology Co., Ltd.

NanjingWanlida Industrial Zone, Zhang Zhou

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	BLU
Model Name	Touch Book 7.0 3G
FCC ID	YHLBLUTB703G
EUT supports Radios application	GSM/GPRS/WCDMA/HSPA/HSPA+(Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	V2.0
SW Version	BLU_P-200L_V01_GENERIC_04-04-2014-1200
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 28.19 dBm GSM1900 : 26.47 dBm WCDMA Band V : 17.21 dBm WCDMA Band II : 16.72 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Downlink Only)

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.23	0.02 ppm	246KGXW
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.02	0.01 ppm	4M18F9W
Part 24	GSM1900 GSM	GMSK	0.21	0.01 ppm	246KGXW
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.03	0.01 ppm	4M17F9W

## 1.7 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.		
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-3320-2398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Registration No.</b>
	TH01-SZ	03CH01-SZ	831040

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.		
<b>Test Site Location</b>	No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		
	OTA01-SZ		

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission (Z plane for 22H, Y plane for 24E).

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

**Note:** The maximum power levels are chosen to test as the worst case configuration as follows:

GSM mode for GMSK modulation,

RMC 12.2Kbps mode for WCDMA band V,


RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

**Conducted Power Measurement Results:**

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	28.11	28.16	28.19	26.30	26.27	26.47
GPRS class 8	28.08	28.15	28.16	26.28	26.26	26.44
GPRS class 10	25.16	25.25	25.27	23.68	23.66	23.88
GPRS class 11	24.69	24.78	24.80	22.47	22.43	22.61
GPRS class 12	23.10	23.21	23.24	21.27	21.24	21.46

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
AMR 12.2K	17.13	17.16	17.18	16.45	16.65	16.70
RMC 12.2K	17.15	17.17	17.21	16.49	16.67	16.72
HSDPA Subtest-1	16.25	16.17	16.25	15.41	15.69	15.57
HSDPA Subtest-2	16.24	16.19	16.24	15.41	15.70	15.57
HSDPA Subtest-3	15.78	15.71	15.77	14.94	15.24	15.10
HSDPA Subtest-4	15.76	15.68	15.77	14.97	15.22	15.06
HSUPA Subtest-1	13.76	13.81	13.90	13.21	13.40	13.56
HSUPA Subtest-2	12.75	12.79	12.88	12.26	12.33	12.39
HSUPA Subtest-3	13.77	13.86	13.92	13.39	13.43	13.57
HSUPA Subtest-4	13.31	13.27	13.35	12.79	12.83	12.94
HSUPA Subtest-5	13.57	13.85	13.78	13.35	13.36	13.51

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Earphone	Lenovo	SH100	FCC DoC	Unshielded, 1.2 m	N/A
3.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 7.0 dB and a 10dB attenuator.

$$\begin{aligned}
 \text{Offset (dB)} &= \text{RF cable loss (dB)} + \text{attenuator factor (dB)} \\
 &= 7.0 + 10 = 17.0 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### 3.1.4 Test Setup



**3.1.5 Test Result of Conducted Output Power**

Cellular Band						
Modes	GSM850 (GSM)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	28.11	28.16	28.19	17.15	17.17	17.21
Conducted Power (Watts)	0.65	0.65	0.66	0.05	0.05	0.05

PCS Band						
Modes	GSM1900 (GSM)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	26.30	26.27	26.47	16.49	16.67	16.72
Conducted Power (Watts)	0.43	0.42	0.44	0.04	0.05	0.05

**Note:** Maximum burst average power for GSM, and maximum average power for WCDMA.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. For GSM/GPRS operating modes:
  - a. Set EUT in maximum power output.
  - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
  - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
  - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
3. For UMTS operating modes:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

### 3.2.4 Test Setup





### 3.2.5 Test Result of Peak-to-Average Ratio

PCS Band						
Modes	GSM1900 (GSM)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.28	0.28	0.28	3.36	3.36	3.30

### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio


<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	GSM Link (GMSK)
---------------	----------	--------------------	-----------------

**Peak-to-Average Ratio on Channel 512 (1850.2 MHz)**

**Peak-to-Average Ratio on Channel 661 (1880.0 MHz)**







Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



<b>Band :</b>	WCDMA Band II	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)**

**Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)**


## Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
2. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$   
 $P_s$  (dBm) : Input power to substitution antenna.  
 $G_s$  (dBi or dBd) : Substitution antenna Gain.  
 $E_t = R_t + AF$   
 $E_s = R_s + AF$   
 $AF$  (dB/m) : Receive antenna factor  
 $R_t$  : The highest received signal in spectrum analyzer for EUT.  
 $R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup



**3.3.5 Test Result of ERP**

<b>GSM850 (GSM) Radiated Power ERP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.07	-48.12	0.00	-1.08	21.97	0.16
836.40	-24.44	-48.28	0.00	-0.93	22.91	0.20
848.80	-24.04	-48.35	0.00	-0.76	23.55	0.23
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.14	-47.97	0.00	-1.08	21.75	0.15
836.40	-24.48	-48.01	0.00	-0.93	22.60	0.18
848.80	-24.30	-48.05	0.00	-0.76	22.99	0.20

<b>WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-35.76	-48.12	0.00	-1.08	11.28	0.01
836.40	-34.80	-48.28	0.00	-0.93	12.55	0.02
846.60	-36.24	-48.35	0.00	-0.76	11.35	0.01
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-35.91	-47.97	0.00	-1.08	10.98	0.01
836.40	-34.87	-48.01	0.00	-0.93	12.21	0.02
846.60	-36.47	-48.05	0.00	-0.76	10.82	0.01

**3.3.6 Test Result of EIRP**

<b>GSM1900 (GSM) Radiated Power EIRP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-31.64	-51.88	0.00	1.96	22.20	0.17
1880.00	-33.09	-52.99	0.00	2.00	21.90	0.15
1909.80	-33.83	-54.28	0.00	1.98	22.43	0.17
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.91	-52.13	0.00	1.96	23.18	0.21
1880.00	-32.54	-53.17	0.00	2.00	22.63	0.18
1909.80	-33.20	-54.13	0.00	1.98	22.91	0.20

<b>WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-40.62	-51.88	0.00	1.96	13.22	0.02
1880.00	-41.46	-52.99	0.00	2.00	13.53	0.02
1907.60	-42.73	-54.28	0.00	1.98	13.53	0.02
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-40.00	-52.13	0.00	1.96	14.09	0.03
1880.00	-41.08	-53.17	0.00	2.00	14.09	0.03
1907.60	-42.01	-54.13	0.00	1.98	14.10	0.03



### 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3\*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3\*RBW, peak detector, trace maximum hold.

#### 3.4.4 Test Setup





**3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth**

Cellular Band			
Modes	GSM850 (GSM)		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
99% OBW (kHz)	246.02	246.02	243.13
26dB BW (kHz)	316.90	315.50	315.50

PCS Band			
Modes	GSM1900 (GSM)		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
99% OBW (kHz)	246.02	246.02	246.02
26dB BW (kHz)	308.20	311.10	309.70


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.15	4.18	4.15
26dB BW (MHz)	4.69	4.67	4.67

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.17	4.15	4.17
26dB BW (MHz)	4.69	4.69	4.69


### 3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth

<b>Band :</b>	GSM 850	<b>Test Mode :</b>	GSM Link (GMSK)
---------------	---------	--------------------	-----------------

**99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)**




**26dB Bandwidth Plot on Channel 128 (824.2 MHz)**






99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




26dB Bandwidth Plot on Channel 189 (836.4 MHz)






99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)




26dB Bandwidth Plot on Channel 251 (848.8 MHz)






Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




26dB Bandwidth Plot on Channel 512 (1850.2 MHz)






99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 6.APR.2014 12:21:41


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



### 99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)





### 26dB Bandwidth Plot on Channel 810 (1909.8 MHz)






<b>Band :</b>	WCDMA Band V	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	--------------	--------------------	--------------------------


**99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)**

**26dB Bandwidth Plot on Channel 4132 (826.4 MHz)**





## 99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




## 26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)




26dB Bandwidth Plot on Channel 4233 (846.6 MHz)






Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

### 99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)




### 26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




**99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)**

**26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)**


99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)





### 3.5 Band Edge Measurement

#### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.5.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)
 
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


#### 3.5.4 Test Setup



### 3.5.5 Test Result (Plots) of Conducted Band Edge


<b>Band :</b>	GSM850	<b>Test Mode :</b>	GSM Link (GMSK)
<b>Correction Factor :</b>	0.24dB	<b>Maximum 26dB Bandwidth :</b>	0.317MHz
<b>Band Edge :</b>	-19.54dBm	<b>Measurement Value :</b>	-19.78dBm

**Lower Band Edge Plot on Channel 128 (824.2 MHz)**



1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


<b>Band :</b>	GSM850	<b>Test Mode :</b>	GSM Link (GMSK)
<b>Correction Factor :</b>	0.24dB	<b>Maximum 26dB Bandwidth :</b>	0.317MHz
<b>Band Edge :</b>	-19.10dBm	<b>Measurement Value :</b>	-19.34dBm

**Higher Band Edge Plot on Channel 251 (848.8 MHz)**


1.  $\text{Correction Factor(dB)} = 10\log(1\% \text{ Emission BW/RBW})$
2.  $\text{Band Edge} = \text{Measurement Value} + \text{Correction Factor(dB)}$




<b>Band :</b>	GSM1900	<b>Test Mode :</b>	GSM Link (GMSK)
<b>Correction Factor :</b>	0.16dB	<b>Maximum 26dB Bandwidth :</b>	0.311MHz
<b>Band Edge :</b>	-21.57dBm	<b>Measurement Value :</b>	-21.73dBm

**Lower Band Edge Plot on Channel 512 (1850.2 MHz)**



1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

<b>Band :</b>	GSM1900	<b>Test Mode :</b>	GSM Link (GMSK)
<b>Correction Factor :</b>	0.16dB	<b>Maximum 26dB Bandwidth :</b>	0.311MHz
<b>Band Edge :</b>	-21.96dBm	<b>Measurement Value :</b>	-22.12dBm

**Higher Band Edge Plot on Channel 810 (1909.8 MHz)**



1.  $\text{Correction Factor(dB)} = 10\log(1\% \text{ Emission BW/RBW})$
2.  $\text{Band Edge} = \text{Measurement Value} + \text{Correction Factor(dB)}$

<b>Band :</b>	WCDMA Band V	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
<b>Correction Factor :</b>	-3.29dB	<b>Maximum 26dB Bandwidth :</b>	4.690MHz
<b>Band Edge :</b>	-33.67dBm	<b>Measurement Value :</b>	-30.38dBm


**Lower Band Edge Plot on Channel 4132 (826.4 MHz)**


1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


<b>Band :</b>	WCDMA Band V	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
<b>Correction Factor :</b>	-3.29dB	<b>Maximum 26dB Bandwidth :</b>	4.690MHz
<b>Band Edge :</b>	-34.02dBm	<b>Measurement Value :</b>	-30.73dBm

**Higher Band Edge Plot on Channel 4233 (846.6 MHz)**


1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	WCDMA Band II	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
<b>Correction Factor :</b>	-3.29dB	<b>Maximum 26dB Bandwidth :</b>	4.690MHz
<b>Band Edge :</b>	-35.26dBm	<b>Measurement Value :</b>	-31.97dBm

**Higher Band Edge Plot on Channel 9538 (1907.6 MHz)**


1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

## 3.6 Conducted Spurious Emission Measurement

### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.6.4 Test Setup







### 3.6.5 Test Result (Plots) of Conducted Spurious Emission

<b>Band :</b>	GSM850	<b>Channel :</b>	CH189
<b>Test Mode :</b>	GSM Link (GMSK)	<b>Frequency :</b>	836.4 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**




**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**








## Conducted Spurious Emission Plot between 3GHz ~ 7GHz





## Conducted Spurious Emission Plot between 7GHz ~ 9GHz




<b>Band :</b>	GSM1900	<b>Channel :</b>	CH661
<b>Test Mode :</b>	GSM Link (GMSK)	<b>Frequency :</b>	1880.0 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**

**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**




**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**

**Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz**






Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz





<b>Band :</b>	WCDMA Band V	<b>Channel :</b>	CH4182
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Frequency :</b>	836.4 MHz



**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**

**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**


**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**

**Conducted Spurious Emission Plot between 7GHz ~ 9GHz**





<b>Band :</b>	WCDMA Band II	<b>Channel :</b>	CH9400
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Frequency :</b>	1880.0 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**

**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**


**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**

**Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz**




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



### 3.7 Field Strength of Spurious Radiation Measurement

#### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13\text{dBm}.$$

### 3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



**3.7.5 Test Result of Field Strength of Spurious Radiated**

<b>Band :</b>	GSM850	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	GSM Link (GMSK)	<b>Relative Humidity :</b>	48~52%
<b>Test Engineer :</b>	Kaer Huang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)441502

Plane : Z

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-50.55	-13	-37.55	-65.14	-53.52	0.88	6.00	H	Pass
2510	-39.33	-13	-26.33	-63.62	-41.94	1.08	5.84	H	Pass
3346	-56.39	-13	-43.39	-66.99	-60.76	1.14	7.66	H	Pass

<b>Band :</b>	GSM850	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	GSM Link (GMSK)	<b>Relative Humidity :</b>	48~52%
<b>Test Engineer :</b>	Kaer Huang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)441502

Plane : Z

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-50.14	-13	-37.14	-62.68	-53.11	0.88	6.00	V	Pass
2510	-40.08	-13	-27.08	-62.33	-42.69	1.08	5.84	V	Pass
3346	-54.91	-13	-41.91	-66.74	-59.28	1.14	7.66	V	Pass



Band :	GSM1900	Temperature :	23~25°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%
Test Engineer :	Kaer Huang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
Project : (FG)441502

Plane : Y

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.60	-13	-42.60	-67.75	-62.34	1.28	8.02	H	Pass
5640	-50.74	-13	-37.74	-68.73	-59.16	1.58	10.00	H	Pass
7520	-45.95	-13	-32.95	-67.89	-56.27	1.78	12.10	H	Pass



Band :	GSM1900	Temperature :	23~25°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	48~52%
Test Engineer :	Kaer Huang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
Project : (FG)441502

Plane : Y

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-53.28	-13	-40.28	-68.31	-60.02	1.28	8.02	V	Pass
5640	-51.49	-13	-38.49	-68.57	-59.91	1.58	10	V	Pass
7520	-45.86	-13	-32.86	-68.11	-56.18	1.78	12.1	V	Pass

<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	48~52%
<b>Test Engineer :</b>	Kaer Huang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
 Project : (FG)441502

Plane : Z

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-50.45	-13	-37.45	-65.06	-53.42	0.88	6.00	H	Pass
2510	-42.52	-13	-29.52	-66.27	-45.13	1.08	5.84	H	Pass
3346	-55.90	-13	-42.90	-66.50	-60.27	1.14	7.66	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	48~52%
<b>Test Engineer :</b>	Kaer Huang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
 Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
 Project : (FG)441502

Plane : Z

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-53.77	-13	-40.77	-65.21	-56.74	0.88	6.00	V	Pass
2510	-44.63	-13	-31.63	-66.02	-47.24	1.08	5.84	V	Pass
3346	-55.28	-13	-42.28	-67.11	-59.65	1.14	7.66	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	23~25°C
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Relative Humidity :</b>	48~52%
<b>Test Engineer :</b>	Kaer Huang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-SZ  
Condition : -13DBM HF\_EIRP\_H\_130101 HORIZONTAL  
Project : (FG)441502

Plane : Y

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.68	-13	-42.68	-67.83	-62.42	1.28	8.02	H	Pass
5640	-50.89	-13	-37.89	-68.88	-59.31	1.58	10.00	H	Pass
7520	-46.36	-13	-33.36	-68.30	-56.68	1.78	12.10	H	Pass



Band :	WCDMA Band II	Temperature :	23~25°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	48~52%
Test Engineer :	Kaer Huang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-SZ  
Condition : -13DBM HF\_EIRP\_V\_130101 VERTICAL  
Project : (FG)441502

Plane : Y

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-52.62	-13	-39.62	-67.65	-59.36	1.28	8.02	V	Pass
5640	-51.88	-13	-38.88	-68.96	-60.30	1.58	10	V	Pass
7520	-45.68	-13	-32.68	-67.93	-56.00	1.78	12.1	V	Pass

### 3.8 Frequency Stability Measurement

#### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


#### 3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the system simulator.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup



**3.8.6 Test Result of Temperature Variation**

<b>Band :</b>	GSM 850	<b>Channel :</b>	189
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-16	-0.02	PASS
-20	-14	-0.02	
-10	-16	-0.02	
0	-14	-0.02	
10	-17	-0.02	
20	-13	-0.02	
30	-15	-0.02	
40	-16	-0.02	
50	-18	-0.02	

<b>Band :</b>	GSM 1900	<b>Channel :</b>	661
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-23	-0.01	PASS
-20	-20	-0.01	
-10	-22	-0.01	
0	-21	-0.01	
10	-19	-0.01	
20	-23	-0.01	
30	-22	-0.01	
40	-24	-0.01	
50	-26	-0.01	

<b>Band :</b>	WCDMA Band V	<b>Channel :</b>	4182
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	5	+0.01	PASS
-20	4	+0.01	
-10	5	+0.01	
0	4	+0.01	
10	5	+0.01	
20	5	+0.01	
30	5	+0.01	
40	4	+0.01	
50	6	+0.01	

<b>Band :</b>	WCDMA Band II	<b>Channel :</b>	9400
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	13	+0.01	PASS
-20	12	+0.01	
-10	14	+0.01	
0	12	+0.01	
10	13	+0.01	
20	11	+0.01	
30	13	+0.01	
40	14	+0.01	
50	16	+0.01	

**3.8.7 Test Result of Voltage Variation**

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.7	-13	-0.02	2.5	PASS
		BEP	-16	-0.02		
		4.2	-14	-0.02		
GSM 1900 CH661	GSM	3.7	-23	-0.01		
		BEP	-21	-0.01		
		4.2	-25	-0.01		
WCDMA Band V CH4182	RMC 12.2Kbps	3.7	5	+0.01		
		BEP	5	+0.01		
		4.2	4	+0.00		
WCDMA Band II CH9400	RMC 12.2Kbps	3.7	11	+0.01		
		BEP	13	+0.01		
		4.2	12	+0.01		

**Note:**

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.4 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Jun. 17, 2013	May 04, 2014	Jun. 16, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	-40℃~150℃	Feb. 21, 2014	May 04, 2014	Feb. 20, 2015	Conducted (TH01-SZ)
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	May 04, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Signal Analyzer	R&S	FSV40	101078	10Hz~40GHz	Jun. 17, 2013	May 04, 2014	Jun. 16, 2014	Radiation (03CH01-SZ)
Bilog Antenna	TESEQ	CBL 6112D	23188	30MHz~2GHz	Oct. 26, 2013	May 04, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 26, 2013	May 04, 2014	Oct. 25, 2014	Radiation (03CH01-SZ)
Double Ridged Horn Antenna	COM-POWER	AH-840	101073	18GHz~40GHz	Jan. 27, 2014	May 04, 2014	Jan. 26, 2015	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz	Feb. 21, 2014	May 04, 2014	Feb. 20, 2015	Radiation (03CH01-SZ)
Amplifier	Agilent	83017A	MY39501302	3Hz~26.5GHz	Mar. 03, 2014	May 04, 2014	Mar. 02, 2015	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0~360 degree	NCR	May 04, 2014	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m~4 m	NCR	May 04, 2014	NCR	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Sep. 03, 2013	May 04, 2014~ May 06, 2014	Sep. 02, 2014	ERP/EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MHz	N/A	May 04, 2014~ May 06, 2014	N/A	ERP/EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	May 04, 2014~ May 06, 2014	N/A	ERP/EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	May 04, 2014~ May 06, 2014	N/A	ERP/EIRP (OTA01-SZ)

## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	3.90
--	------