Test Plot 1#: GSM 850_Head Left Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; ε_r = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.312 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.950 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.192 W/kg
SAR(1 g) = 0.109 W/kg; SAR(10 g) = 0.086 W/kg
Maximum value of SAR (measured) = 0.149 W/kg

0 dB = 0.149 W/kg = -8.27 dBW/kg

Test Plot 2#: GSM 850_Head Left Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; ε_r = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.206 W/kg

Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.471 V/m; Power Drift = -0.19 dB
Peak SAR (extrapolated) = 0.421 W/kg
SAR(1 g) = 0.086 W/kg; SAR(10 g) = 0.038 W/kg
Maximum value of SAR (measured) = 0.425 W/kg

0 dB = 0.425 W/kg = -3.72 dBW/kg

Test Plot 3#: GSM 850_Head Right Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; ε_r = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.153 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.245 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.314 W/kg
SAR(1 g) = 0.134 W/kg; SAR(10 g) = 0.094 W/kg
Maximum value of SAR (measured) = 0.272 W/kg

0 dB = 0.272 W/kg = -5.65 dBW/kg

Test Plot 4#: GSM 850_Head Right Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; $ε_r$ = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0902 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.544 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.419 W/kg
SAR(1 g) = 0.067 W/kg; SAR(10 g) = 0.054 W/kg
Maximum value of SAR (measured) = 0.419 W/kg

0 dB = 0.419 W/kg = -3.78 dBW/kg

Test Plot 5#: GSM 850_Body Worn Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 836.6 MHz;Duty Cycle: 1:8
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; ε_r = 57.206; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.198 W/kg

Zoom Scan (8x12x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.24 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.220 W/kg
SAR(1 g) = 0.142 W/kg; SAR(10 g) = 0.118 W/kg
Maximum value of SAR (measured) = 0.181 W/kg

0 dB = 0.181 W/kg = -7.42 dBW/kg

Test Plot 6#: GSM 850_Body Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 836.6 MHz;Duty Cycle: 1:2
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; $ε_r$ = 57.206; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.292 W/kg

Zoom Scan (7x9x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.20 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 0.324 W/kg
SAR(1 g) = 0.167 W/kg; SAR(10 g) = 0.114 W/kg
Maximum value of SAR (measured) = 0.252 W/kg

0 dB = 0.252 W/kg = -5.99 dBW/kg

Test Plot 7#: GSM 850_Body Right_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 836.6 MHz;Duty Cycle: 1:2
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; ε$_r$ = 57.206; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0813 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.448 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.0890 W/kg
SAR(1 g) = 0.064 W/kg; SAR(10 g) = 0.048 W/kg
Maximum value of SAR (measured) = 0.0801 W/kg

0 dB = 0.0801 W/kg = -10.96 dBW/kg

Test Plot 8#: GSM 850_Body Bottom_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 836.6 MHz;Duty Cycle: 1:2
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; ε_r = 57.206; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.130 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.324 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.166 W/kg
SAR(1 g) = 0.082 W/kg; SAR(10 g) = 0.053 W/kg
Maximum value of SAR (measured) = 0.123 W/kg

0 dB = 0.123 W/kg = -9.10 dBW/kg

Test Plot 9#: GSM 1900_Head Left Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.206 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.711 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.248 W/kg
SAR(1 g) = 0.160 W/kg; SAR(10 g) = 0.104 W/kg
Maximum value of SAR (measured) = 0.209 W/kg

0 dB = 0.209 W/kg = -6.80 dBW/kg

Test Plot 10#: GSM 1900_Head Left Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.121 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.088 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 0.145 W/kg
SAR(1 g) = 0.089 W/kg; SAR(10 g) = 0.058 W/kg
Maximum value of SAR (measured) = 0.119 W/kg

0 dB = 0.119 W/kg = -9.24 dBW/kg

Test Plot 11#: GSM 1900_Head Right Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.287 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.545 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.327 W/kg
SAR(1 g) = 0.198 W/kg; SAR(10 g) = 0.124 W/kg
Maximum value of SAR (measured) = 0.276 W/kg

0 dB = 0.276 W/kg = -5.59 dBW/kg

Test Plot 12#: GSM 1900_Head Right Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.111 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.333 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.120 W/kg
SAR(1 g) = 0.079 W/kg; SAR(10 g) = 0.054 W/kg
Maximum value of SAR (measured) = 0.103 W/kg

0 dB = 0.103 W/kg = -9.87 dBW/kg

Test Plot 13#: GSM 1900_Body Worn Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GSM; Frequency: 1880 MHz;Duty Cycle: 1:8
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; $ε_r$ = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.902 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.13 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.09 W/kg
SAR(1 g) = 0.541 W/kg; SAR(10 g) = 0.298 W/kg
Maximum value of SAR (measured) = 0.838 W/kg

0 dB = 0.838 W/kg = -0.77 dBW/kg

Test Plot 14#: GSM 1900_Body Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 1880 MHz;Duty Cycle: 1:2
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.24 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.20 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 1.48 W/kg
SAR(1 g) = 0.742 W/kg; SAR(10 g) = 0.408 W/kg
Maximum value of SAR (measured) = 1.12 W/kg

0 dB = 1.12 W/kg = 0.49 dBW/kg

Test Plot 15#: GSM 1900_Body Right_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 1880 MHz;Duty Cycle: 1:2
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.487$ S/m; $\varepsilon_r = 54.196$; $\rho = 1000$ kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.469 W/kg

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.869 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.551 W/kg
SAR(1 g) = 0.304 W/kg; SAR(10 g) = 0.180 W/kg
Maximum value of SAR (measured) = 0.455 W/kg

0 dB = 0.455 W/kg = -3.42 dBW/kg

Test Plot 16#: GSM 1900_Body Bottom_Low

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 1850.2 MHz;Duty Cycle: 1:2
Medium parameters used: f = 1850.2 MHz; σ = 1.462 S/m; $ε_r$ = 54.605; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.84 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.27 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 2.22 W/kg
SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.558 W/kg
Maximum value of SAR (measured) = 1.79 W/kg

0 dB = 1.79 W/kg = 2.53 dBW/kg

Test Plot 17#: GSM 1900_Body Bottom_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 1880 MHz;Duty Cycle: 1:2
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.61 W/kg

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.42 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 2.03 W/kg
SAR(1 g) = 0.993 W/kg; SAR(10 g) = 0.504 W/kg
Maximum value of SAR (measured) = 1.62 W/kg

0 dB = 1.62 W/kg = 2.10 dBW/kg

Test Plot 18#: GSM 1900_Body Bottom_High

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic GPRS-4 slots; Frequency: 1909.8 MHz;Duty Cycle: 1:2
Medium parameters used: f = 1909.8 MHz; σ = 1.525 S/m; ε_r = 54.052; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.54 W/kg

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.73 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.89 W/kg
SAR(1 g) = 0.961 W/kg; SAR(10 g) = 0.503 W/kg
Maximum value of SAR (measured) = 1.50 W/kg

0 dB = 1.50 W/kg = 1.76 dBW/kg

Test Plot 19#: WCDMA Band 2_Head Left Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.366 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.054 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.424 W/kg
SAR(1 g) = 0.262 W/kg; SAR(10 g) = 0.170 W/kg
Maximum value of SAR (measured) = 0.359 W/kg

0 dB = 0.359 W/kg = -4.45 dBW/kg

Test Plot 20#: WCDMA Band 2_Head Left Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.188 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.579 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.209 W/kg
SAR(1 g) = 0.128 W/kg; SAR(10 g) = 0.082 W/kg
Maximum value of SAR (measured) = 0.177 W/kg

0 dB = 0.177 W/kg = -7.52 dBW/kg

Test Plot 21#: WCDMA Band 2_Head Right Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.477 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.423 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.530 W/kg
SAR(1 g) = 0.333 W/kg; SAR(10 g) = 0.211 W/kg
Maximum value of SAR (measured) = 0.456 W/kg

0 dB = 0.456 W/kg = -3.41 dBW/kg

Test Plot 22#: WCDMA Band 2_Head Right Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.216 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.970 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 0.224 W/kg
SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.092 W/kg
Maximum value of SAR (measured) = 0.196 W/kg

0 dB = 0.196 W/kg = -7.08 dBW/kg

Test Plot 23#: WCDMA Band 2_Body Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.26 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.89 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.47 W/kg
SAR(1 g) = 0.732 W/kg; SAR(10 g) = 0.412 W/kg
Maximum value of SAR (measured) = 1.16 W/kg

0 dB = 1.16 W/kg = 0.64 dBW/kg

Test Plot 24#: WCDMA Band 2_Body Right_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.596 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.26 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.707 W/kg
SAR(1 g) = 0.384 W/kg; SAR(10 g) = 0.225 W/kg
Maximum value of SAR (measured) = 0.575 W/kg

0 dB = 0.575 W/kg = -2.40 dBW/kg

Test Plot 25#: WCDMA Band 2_Body Bottom_Low

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1852.4 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1852.4 MHz; σ = 1.467 S/m; ε_r = 54.597; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.39 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.32 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.64 W/kg
SAR(1 g) = 0.863 W/kg; SAR(10 g) = 0.452 W/kg
Maximum value of SAR (measured) = 1.36 W/kg

0 dB = 1.36 W/kg = 1.34 dBW/kg

Test Plot 26#: WCDMA Band 2_Body Bottom_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.46 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.41 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 1.73 W/kg
SAR(1 g) = 0.855 W/kg; SAR(10 g) = 0.433 W/kg
Maximum value of SAR (measured) = 1.39 W/kg

0 dB = 1.39 W/kg = 1.43 dBW/kg

Test Plot 27#: WCDMA Band 2_Body Bottom_High

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1907.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1907.6 MHz; σ = 1.518 S/m; ε_r = 54.08; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.83 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 27.89 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 2.16 W/kg
SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.564 W/kg
Maximum value of SAR (measured) = 1.77 W/kg

0 dB = 1.77 W/kg = 2.48 dBW/kg

Test Plot 28#: WCDMA Band 4_Head Left Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.346 S/m; ε_r = 41.153; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.380 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.85 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 0.547 W/kg
SAR(1 g) = 0.192 W/kg; SAR(10 g) = 0.121 W/kg
Maximum value of SAR (measured) = 0.311 W/kg

0 dB = 0.311 W/kg = -5.07 dBW/kg

Test Plot 29#: WCDMA Band 4_Head Left Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.346 S/m; $ε_r$ = 41.153; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.100 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.382 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 0.214 W/kg
SAR(1 g) = 0.094 W/kg; SAR(10 g) = 0.058 W/kg
Maximum value of SAR (measured) = 0.214 W/kg

0 dB = 0.214 W/kg = -6.70 dBW/kg

Test Plot 30#: WCDMA Band 4_Head Right Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.346 S/m; ε_r = 41.153; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.217 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.739 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.264 W/kg
SAR(1 g) = 0.168 W/kg; SAR(10 g) = 0.114 W/kg
Maximum value of SAR (measured) = 0.227 W/kg

0 dB = 0.227 W/kg = -6.44 dBW/kg

Test Plot 31#: WCDMA Band 4_Head Right Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.346 S/m; ε_r = 41.153; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.106 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.914 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.106 W/kg
SAR(1 g) = 0.085 W/kg; SAR(10 g) = 0.069 W/kg
Maximum value of SAR (measured) = 0.100 W/kg

0 dB = 0.100 W/kg = -10.00 dBW/kg

Test Plot 32#: WCDMA Band 4_Body Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.526 S/m; ε_r = 52.785; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.852 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.52 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.972 W/kg
SAR(1 g) = 0.530 W/kg; SAR(10 g) = 0.324 W/kg
Maximum value of SAR (measured) = 0.784 W/kg

0 dB = 0.784 W/kg = -1.06 dBW/kg

Test Plot 33#: WCDMA Band 4_Body Right_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.526 S/m; ε_r = 52.785; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.405 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.242 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.463 W/kg
SAR(1 g) = 0.272 W/kg; SAR(10 g) = 0.170 W/kg
Maximum value of SAR (measured) = 0.390 W/kg

0 dB = 0.390 W/kg = -4.09 dBW/kg

Test Plot 34#: WCDMA Band 4_Body Bottom_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.6 MHz; σ = 1.526 S/m; ε_r = 52.785; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.16 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 23.19 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 1.36 W/kg
SAR(1 g) = 0.735 W/kg; SAR(10 g) = 0.400 W/kg
Maximum value of SAR (measured) = 1.12 W/kg

0 dB = 1.12 W/kg = 0.49 dBW/kg

Test Plot 35#: WCDMA Band 5_Head Left Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; ε_r = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.856 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.778 V/m; Power Drift = 0.19 dB
Peak SAR (extrapolated) = 0.275 W/kg
SAR(1 g) = 0.197 W/kg; SAR(10 g) = 0.133 W/kg
Maximum value of SAR (measured) = 0.244 W/kg

0 dB = 0.244 W/kg = -6.13 dBW/kg

Test Plot 36#: WCDMA Band 5_Head Left Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; $ε_r$ = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0481 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.308 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.0510 W/kg
SAR(1 g) = 0.042 W/kg; SAR(10 g) = 0.035 W/kg
Maximum value of SAR (measured) = 0.0468 W/kg

0 dB = 0.0468 W/kg = -13.30 dBW/kg

Test Plot 37#: WCDMA Band 5_Head Right Cheek_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; ε_r = 42.315; ρ = 1000 kg/m³ ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.102 W/kg

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.962 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.524 W/kg
SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.104 W/kg
Maximum value of SAR (measured) = 0.524 W/kg

0 dB = 0.524 W/kg = -2.81 dBW/kg

Test Plot 38#: WCDMA Band 5_Head Right Tilt_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.88 S/m; $ε_r$ = 42.315; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0335 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.862 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.0473 W/kg
SAR(1 g) = 0.032 W/kg; SAR(10 g) = 0.025 W/kg
Maximum value of SAR (measured) = 0.0394 W/kg

0 dB = 0.0394 W/kg = -14.05 dBW/kg

Test Plot 39#: WCDMA Band 5_Body Back_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; ε_r = 57.206; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.170 W/kg

Zoom Scan (7x9x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.362 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.167 W/kg
SAR(1 g) = 0.104 W/kg; SAR(10 g) = 0.079 W/kg
Maximum value of SAR (measured) = 0.129 W/kg

0 dB = 0.129 W/kg = -8.89 dBW/kg

Test Plot 40#: WCDMA Band 5_Body Right_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; ε_r = 57.206; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0651 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.664 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.0690 W/kg
SAR(1 g) = 0.051 W/kg; SAR(10 g) = 0.039 W/kg
Maximum value of SAR (measured) = 0.0633 W/kg

0 dB = 0.0633 W/kg = -11.99 dBW/kg

Test Plot 41#: WCDMA Band 5_Body Bottom_Middle

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System:WCDMA; Frequency: 836.6 MHz;Duty Cycle: 1:1
Medium parameters used: f = 836.6 MHz; σ = 0.957 S/m; $ε_r$ = 57.206; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0916 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.942 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.130 W/kg
SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.040 W/kg
Maximum value of SAR (measured) = 0.0962 W/kg

0 dB = 0.0962 W/kg = -10.17 dBW/kg

Test Plot 42#: LTE Band 2_Head Left Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.279 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.178 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.340 W/kg
SAR(1 g) = 0.210 W/kg; SAR(10 g) = 0.134 W/kg
Maximum value of SAR (measured) = 0.287 W/kg

0 dB = 0.287 W/kg = -5.42 dBW/kg

Test Plot 43#: LTE Band 2_Head Left Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.218 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.809 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.270 W/kg
SAR(1 g) = 0.167 W/kg; SAR(10 g) = 0.106 W/kg
Maximum value of SAR (measured) = 0.222 W/kg

0 dB = 0.222 W/kg = -6.54 dBW/kg

Test Plot 44#: LTE Band 2_Head Left Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.198 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.04 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.216 W/kg
SAR(1 g) = 0.132 W/kg; SAR(10 g) = 0.084 W/kg
Maximum value of SAR (measured) = 0.185 W/kg

0 dB = 0.185 W/kg = -7.33 dBW/kg

Test Plot 45#: LTE Band 2_Head Left Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m³ ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.154 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.934 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.169 W/kg
SAR(1 g) = 0.104 W/kg; SAR(10 g) = 0.067 W/kg
Maximum value of SAR (measured) = 0.145 W/kg

0 dB = 0.145 W/kg = -8.39 dBW/kg

Test Plot 46#: LTE Band 2_Head Right Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; $ε_r$ = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.444 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.075 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.539 W/kg
SAR(1 g) = 0.317 W/kg; SAR(10 g) = 0.195 W/kg
Maximum value of SAR (measured) = 0.436 W/kg

0 dB = 0.436 W/kg = -3.61 dBW/kg

Test Plot 47#: LTE Band 2_Head Right Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.340 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.489 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.410 W/kg
SAR(1 g) = 0.243 W/kg; SAR(10 g) = 0.150 W/kg
Maximum value of SAR (measured) = 0.333 W/kg

0 dB = 0.333 W/kg = -4.78 dBW/kg

Test Plot 48#: LTE Band 2_Head Right Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.242 W/kg

**Zoom Scan (6x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.378 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 0.189 W/kg
SAR(1 g) = 0.122 W/kg; SAR(10 g) = 0.080 W/kg
Maximum value of SAR (measured) = 0.160 W/kg

0 dB = 0.160 W/kg = -7.96 dBW/kg

Test Plot 49#: LTE Band 2_Head Right Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.365 S/m; ε_r = 40.424; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.9, 7.9, 7.9); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.167 W/kg

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.013 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.169 W/kg
SAR(1 g) = 0.108 W/kg; SAR(10 g) = 0.071 W/kg
Maximum value of SAR (measured) = 0.144 W/kg

0 dB = 0.144 W/kg = -8.42 dBW/kg

Test Plot 50#: LTE Band 2_Body Back_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.958 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.00 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.19 W/kg
SAR(1 g) = 0.581 W/kg; SAR(10 g) = 0.316 W/kg
Maximum value of SAR (measured) = 0.916 W/kg

0 dB = 0.916 W/kg = -0.38 dBW/kg

Test Plot 51#: LTE Band 2_Body Back_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; $ε_r$ = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.848 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.33 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.04 W/kg
SAR(1 g) = 0.510 W/kg; SAR(10 g) = 0.279 W/kg
Maximum value of SAR (measured) = 0.797 W/kg

0 dB = 0.797 W/kg = -0.99 dBW/kg

Test Plot 52#: LTE Band 2_Body Right_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.388 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.089 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.453 W/kg
SAR(1 g) = 0.248 W/kg; SAR(10 g) = 0.146 W/kg
Maximum value of SAR (measured) = 0.374 W/kg

0 dB = 0.374 W/kg = -4.27 dBW/kg

Test Plot 53#: LTE Band 2_Body Right_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; $ε_r$ = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.338 W/kg

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.533 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.396 W/kg
SAR(1 g) = 0.220 W/kg; SAR(10 g) = 0.130 W/kg
Maximum value of SAR (measured) = 0.327 W/kg

0 dB = 0.327 W/kg = -4.85 dBW/kg

Test Plot 54#: LTE Band 2_Body Bottom_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.18 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.65 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 1.44 W/kg
SAR(1 g) = 0.722 W/kg; SAR(10 g) = 0.365 W/kg
Maximum value of SAR (measured) = 1.17 W/kg

0 dB = 1.17 W/kg = 0.68 dBW/kg

Test Plot 55#: LTE Band 2_Body Bottom_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1880 MHz; σ = 1.487 S/m; ε_r = 54.196; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.79, 7.79, 7.79); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.03 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.01 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.24 W/kg
SAR(1 g) = 0.624 W/kg; SAR(10 g) = 0.316 W/kg
Maximum value of SAR (measured) = 1.01 W/kg

0 dB = 1.01 W/kg = 0.04 dBW/kg

Test Plot 56#: LTE Band 4_Head Left Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; ε$_r$ = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.294 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.161 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.330 W/kg
SAR(1 g) = 0.235 W/kg; SAR(10 g) = 0.183 W/kg
Maximum value of SAR (measured) = 0.288 W/kg

0 dB = 0.288 W/kg = -5.41 dBW/kg

Test Plot 57#: LTE Band 4_Head Left Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; $ε_r$ = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.230 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.567 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.497 W/kg
SAR(1 g) = 0.215 W/kg; SAR(10 g) = 0.138 W/kg
Maximum value of SAR (measured) = 0.371 W/kg

0 dB = 0.371 W/kg = -4.31 dBW/kg

Test Plot 58#: LTE Band 4_Head Left Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; $ε_r$ = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.148 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.618 V/m; Power Drift = 0.19 dB
Peak SAR (extrapolated) = 0.139 W/kg
SAR(1 g) = 0.110 W/kg; SAR(10 g) = 0.089 W/kg
Maximum value of SAR (measured) = 0.132 W/kg

0 dB = 0.132 W/kg = -8.79 dBW/kg

Test Plot 59#: LTE Band 4_Head Left Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; ε_r = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.156 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.750 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.131 W/kg
SAR(1 g) = 0.099 W/kg; SAR(10 g) = 0.081 W/kg
Maximum value of SAR (measured) = 0.115 W/kg

0 dB = 0.115 W/kg = -9.39 dBW/kg

Test Plot 60#: LTE Band 4_Head Right Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; ε_r = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.206 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.235 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.243 W/kg
SAR(1 g) = 0.174 W/kg; SAR(10 g) = 0.127 W/kg
Maximum value of SAR (measured) = 0.215 W/kg

0 dB = 0.215 W/kg = -6.68 dBW/kg

Test Plot 61#: LTE Band 4_Head Right Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; $ε_r$ = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.178 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.307 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 0.199 W/kg
SAR(1 g) = 0.141 W/kg; SAR(10 g) = 0.105 W/kg
Maximum value of SAR (measured) = 0.177 W/kg

0 dB = 0.177 W/kg = -7.52 dBW/kg

Test Plot 62#: LTE Band 4_Head Right Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; ε_r = 41.25; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.114 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.394 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.111 W/kg
SAR(1 g) = 0.090 W/kg; SAR(10 g) = 0.073 W/kg
Maximum value of SAR (measured) = 0.104 W/kg

0 dB = 0.104 W/kg = -9.83 dBW/kg

Test Plot 63#: LTE Band 4_Head Right Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.345 S/m; ε_r = 41.25; ρ = 1000 kg/m³ ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.22, 8.22, 8.22); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.109 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.847 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.112 W/kg
SAR(1 g) = 0.085 W/kg; SAR(10 g) = 0.069 W/kg
Maximum value of SAR (measured) = 0.100 W/kg

0 dB = 0.100 W/kg = -10.00 dBW/kg

Test Plot 64#: LTE Band 4_Body Back_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.527 S/m; $ε_r$ = 52.825; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.792 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.987 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.961 W/kg
SAR(1 g) = 0.518 W/kg; SAR(10 g) = 0.314 W/kg
Maximum value of SAR (measured) = 0.768 W/kg

0 dB = 0.768 W/kg = -1.15 dBW/kg

Test Plot 65#: LTE Band 4_Body Back_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.527 S/m; ε_r = 52.825; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.682 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.262 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.813 W/kg
SAR(1 g) = 0.439 W/kg; SAR(10 g) = 0.266 W/kg
Maximum value of SAR (measured) = 0.649 W/kg

0 dB = 0.649 W/kg = -1.88 dBW/kg

Test Plot 66#: LTE Band 4_Body Right_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.527 S/m; ε_r = 52.825; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.307 W/kg

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.050 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 0.345 W/kg
SAR(1 g) = 0.207 W/kg; SAR(10 g) = 0.131 W/kg
Maximum value of SAR (measured) = 0.292 W/kg

0 dB = 0.292 W/kg = -5.35 dBW/kg

Test Plot 67#: LTE Band 4_Body Right_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.527 S/m; ε_r = 52.825; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.263 W/kg

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.658 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.295 W/kg
SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.114 W/kg
Maximum value of SAR (measured) = 0.250 W/kg

0 dB = 0.250 W/kg = -6.02 dBW/kg

Test Plot 68#: LTE Band 4_Body Bottom_Low_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1720 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1720 MHz; σ = 1.514 S/m; ε_r = 52.829; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.20 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.96 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.39 W/kg
SAR(1 g) = 0.748 W/kg; SAR(10 g) = 0.406 W/kg
Maximum value of SAR (measured) = 1.15 W/kg

0 dB = 1.15 W/kg = 0.61 dBW/kg

Test Plot 69#: LTE Band 4_Body Bottom_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.527 S/m; ε$_r$ = 52.825; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.43 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.64 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 1.61 W/kg
SAR(1 g) = 0.887 W/kg; SAR(10 g) = 0.485 W/kg
Maximum value of SAR (measured) = 1.35 W/kg

0 dB = 1.35 W/kg = 1.30 dBW/kg

Test Plot 70#: LTE Band 4_Body Bottom_High_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1745 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1745 MHz; σ = 1.534 S/m; ε_r = 52.717; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.07 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.48 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 1.25 W/kg
SAR(1 g) = 0.667 W/kg; SAR(10 g) = 0.359 W/kg
Maximum value of SAR (measured) = 1.03 W/kg

0 dB = 1.03 W/kg = 0.13 dBW/kg

Test Plot 71#: LTE Band 4_Body Bottom_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1732.5 MHz; σ = 1.527 S/m; ε_r = 52.825; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.05 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.41 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.25 W/kg
SAR(1 g) = 0.675 W/kg; SAR(10 g) = 0.368 W/kg
Maximum value of SAR (measured) = 1.04 W/kg

0 dB = 1.04 W/kg = 0.17 dBW/kg

Test Plot 72#: LTE Band 7_Head Left Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.279 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.532 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.310 W/kg
SAR(1 g) = 0.179 W/kg; SAR(10 g) = 0.109 W/kg
Maximum value of SAR (measured) = 0.252 W/kg

0 dB = 0.252 W/kg = -5.99 dBW/kg

Test Plot 73#: LTE Band 7_Head Left Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε$_r$ = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.238 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.957 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.289 W/kg
SAR(1 g) = 0.162 W/kg; SAR(10 g) = 0.102 W/kg
Maximum value of SAR (measured) = 0.224 W/kg

0 dB = 0.224 W/kg = -6.50 dBW/kg

Test Plot 74#: LTE Band 7_Head Left Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.140 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.777 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.166 W/kg
SAR(1 g) = 0.091 W/kg; SAR(10 g) = 0.052 W/kg
Maximum value of SAR (measured) = 0.131 W/kg

0 dB = 0.131 W/kg = -8.83 dBW/kg

Test Plot 75#: LTE Band 7_Head Left Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.101 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.086 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.123 W/kg
SAR(1 g) = 0.067 W/kg; SAR(10 g) = 0.040 W/kg
Maximum value of SAR (measured) = 0.0951 W/kg

0 dB = 0.0951 W/kg = -10.22 dBW/kg

Test Plot 76#: LTE Band 7_Head Right Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.160 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.436 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 0.176 W/kg
SAR(1 g) = 0.123 W/kg; SAR(10 g) = 0.096 W/kg
Maximum value of SAR (measured) = 0.162 W/kg

0 dB = 0.162 W/kg = -7.90 dBW/kg

Test Plot 77#: LTE Band 7_Head Right Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m³ ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.331 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.738 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.149 W/kg
SAR(1 g) = 0.109 W/kg; SAR(10 g) = 0.087 W/kg
Maximum value of SAR (measured) = 0.129 W/kg

0 dB = 0.129 W/kg = -8.89 dBW/kg

Test Plot 78#: LTE Band 7_Head Right Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.159 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.155 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.0960 W/kg
SAR(1 g) = 0.076 W/kg; SAR(10 g) = 0.070 W/kg
Maximum value of SAR (measured) = 0.0875 W/kg

0 dB = 0.0875 W/kg = -10.58 dBW/kg

Test Plot 79#: LTE Band 7_Head Right Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 1.895 S/m; ε_r = 39.016; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.34, 7.34, 7.34); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0856 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.054 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 0.100 W/kg
SAR(1 g) = 0.057 W/kg; SAR(10 g) = 0.035 W/kg
Maximum value of SAR (measured) = 0.0814 W/kg

0 dB = 0.0814 W/kg = -10.89 dBW/kg

Test Plot 80#: LTE Band 7_Body Back_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 2.109 S/m; ε_r = 52.726; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.816 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.199 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 1.17 W/kg
SAR(1 g) = 0.467 W/kg; SAR(10 g) = 0.202 W/kg
Maximum value of SAR (measured) = 0.852 W/kg

0 dB = 0.852 W/kg = -0.70 dBW/kg

Test Plot 81#: LTE Band 7_Body Back_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 2.109 S/m; ε_r = 52.726; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.658 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.972 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.939 W/kg
SAR(1 g) = 0.381 W/kg; SAR(10 g) = 0.169 W/kg
Maximum value of SAR (measured) = 0.684 W/kg

0 dB = 0.684 W/kg = -1.65 dBW/kg

Test Plot 82#: LTE Band 7_Body Right_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 2.109 S/m; ε_r = 52.726; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x141x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.125 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.227 V/m; Power Drift = -0.20 dB
Peak SAR (extrapolated) = 0.152 W/kg
SAR(1 g) = 0.082 W/kg; SAR(10 g) = 0.055 W/kg
Maximum value of SAR (measured) = 0.119 W/kg

0 dB = 0.119 W/kg = -9.24 dBW/kg

Test Plot 83#: LTE Band 7_Body Right_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 2.109 S/m; ε_r = 52.726; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.110 W/kg

Zoom Scan (6x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.022 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.134 W/kg
SAR(1 g) = 0.071 W/kg; SAR(10 g) = 0.049 W/kg
Maximum value of SAR (measured) = 0.104 W/kg

0 dB = 0.104 W/kg = -9.83 dBW/kg

Test Plot 84#: LTE Band 7_Body Bottom_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 2.109 S/m; ε_r = 52.726; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.16 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.38 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 1.45 W/kg
SAR(1 g) = 0.591 W/kg; SAR(10 g) = 0.249 W/kg
Maximum value of SAR (measured) = 1.07 W/kg

0 dB = 1.07 W/kg = 0.29 dBW/kg

Test Plot 85#: LTE Band 7_Body Bottom_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2535 MHz; σ = 2.109 S/m; ε_r = 52.726; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(7.4, 7.4, 7.4); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.918 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.49 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 1.17 W/kg
SAR(1 g) = 0.479 W/kg; SAR(10 g) = 0.205 W/kg
Maximum value of SAR (measured) = 0.855 W/kg

0 dB = 0.855 W/kg = -0.68 dBW/kg

Test Plot 86#: LTE Band 12&17_Head Left Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; ε_r = 43.006; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.124 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.271 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.137 W/kg
SAR(1 g) = 0.110 W/kg; SAR(10 g) = 0.092 W/kg
Maximum value of SAR (measured) = 0.127 W/kg

0 dB = 0.127 W/kg = -8.96 dBW/kg

Test Plot 87#: LTE Band 12&17_Head Left Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; $ε_r$ = 43.006; ρ = 1000 kg/m³ ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.103 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.022 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 0.109 W/kg
SAR(1 g) = 0.090 W/kg; SAR(10 g) = 0.076 W/kg
Maximum value of SAR (measured) = 0.102 W/kg

0 dB = 0.102 W/kg = -9.91 dBW/kg

Test Plot 88#: LTE Band 12&17_Head Left Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; ε_r = 43.006; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.154 W/kg

Zoom Scan (6x9x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.405 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 0.0650 W/kg
SAR(1 g) = 0.057 W/kg; SAR(10 g) = 0.050 W/kg
Maximum value of SAR (measured) = 0.0647 W/kg

0 dB = 0.0647 W/kg = -11.89 dBW/kg

Test Plot 89#: LTE Band 12&17_Head Left Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; $ε_r$ = 43.006; ρ = 1000 kg/m^3 ;
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.343 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.431 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 0.0550 W/kg
SAR(1 g) = 0.030 W/kg; SAR(10 g) = 0.026 W/kg
Maximum value of SAR (measured) = 0.0552 W/kg

0 dB = 0.0552 W/kg = -12.58 dBW/kg

Test Plot 90#: LTE Band 12&17_Head Right Cheek_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; $ε_r$ = 43.006; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0998 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.980 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.175 W/kg
SAR(1 g) = 0.080 W/kg; SAR(10 g) = 0.062 W/kg
Maximum value of SAR (measured) = 0.0986 W/kg

0 dB = 0.0986 W/kg = -10.06 dBW/kg

Test Plot 91#: LTE Band 12&17_Head Right Cheek_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; $ε_r$ = 43.006; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0816 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.927 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.425 W/kg
SAR(1 g) = 0.071 W/kg; SAR(10 g) = 0.060 W/kg
Maximum value of SAR (measured) = 0.425 W/kg

0 dB = 0.425 W/kg = -3.72 dBW/kg

Test Plot 92#: LTE Band 12&17_Head Right Tilt_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; ε_r = 43.006; ρ = 1000 kg/m^3 ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0649 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 5.528 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.0690 W/kg
SAR(1 g) = 0.059 W/kg; SAR(10 g) = 0.043 W/kg
Maximum value of SAR (measured) = 0.0643 W/kg

0 dB = 0.0643 W/kg = -11.92 dBW/kg

Test Plot 93#: LTE Band 12&17_Head Right Tilt_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.881 S/m; $ε_r$ = 43.006; ρ = 1000 kg/m³ ;
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.98, 9.98, 9.98); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0530 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.360 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 0.0602 W/kg
SAR(1 g) = 0.038 W/kg; SAR(10 g) = 0.029 W/kg
Maximum value of SAR (measured) = 0.0573 W/kg

0 dB = 0.0573 W/kg = -12.42 dBW/kg

Test Plot 94#: LTE Band 12&17_Body Back_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.956 S/m; ε_r = 55.129; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.156 W/kg

Zoom Scan (7x9x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.018 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.352 W/kg
SAR(1 g) = 0.094 W/kg; SAR(10 g) = 0.073 W/kg
Maximum value of SAR (measured) = 0.133 W/kg

0 dB = 0.133 W/kg = -8.76 dBW/kg

Test Plot 95#: LTE Band 12&17_Body Back_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.956 S/m; ε$_r$ = 55.129; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.131 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.799 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 0.242 W/kg
SAR(1 g) = 0.055 W/kg; SAR(10 g) = 0.038 W/kg
Maximum value of SAR (measured) = 0.113 W/kg

0 dB = 0.113 W/kg = -9.47 dBW/kg

Test Plot 96#: LTE Band 12&17_Body Right_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.956 S/m; ε_r = 55.129; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0620 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.284 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.0710 W/kg
SAR(1 g) = 0.050 W/kg; SAR(10 g) = 0.037 W/kg
Maximum value of SAR (measured) = 0.0631 W/kg

0 dB = 0.0631 W/kg = -12.00 dBW/kg

Test Plot 97#: LTE Band 12&17_Body Right_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.956 S/m; ε_r = 55.129; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0501 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.674 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.0560 W/kg
SAR(1 g) = 0.040 W/kg; SAR(10 g) = 0.030 W/kg
Maximum value of SAR (measured) = 0.0499 W/kg

0 dB = 0.0499 W/kg = -13.02 dBW/kg

Test Plot 98#: LTE Band 12&17_Body Bottom_Middle_1RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.956 S/m; ε_r = 55.129; ρ = 1000 kg/m³ ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0303 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.882 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 0.0750 W/kg
SAR(1 g) = 0.031 W/kg; SAR(10 g) = 0.019 W/kg
Maximum value of SAR (measured) = 0.0463 W/kg

0 dB = 0.0463 W/kg = -13.34 dBW/kg

Test Plot 99#: LTE Band 12&17_Body Bottom_Middle_50%RB

DUT: Mobile phone; Type: STUDIO MEGA LTE; Serial: 18052800321

Communication System: Generic FDD-LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used: f = 707.5 MHz; σ = 0.956 S/m; ε_r = 55.129; ρ = 1000 kg/m^3 ;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7441; ConvF(9.95, 9.95, 9.95); Calibrated: 2017/11/2;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459;Calibrated: 2017/9/15
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Area Scan (51x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0439 W/kg

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.998 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.0570 W/kg
SAR(1 g) = 0.025 W/kg; SAR(10 g) = 0.017 W/kg
Maximum value of SAR (measured) = 0.0407 W/kg

0 dB = 0.0407 W/kg = -13.90 dBW/kg