

# FCC RF Test Report

APPLICANT : CT Asia  
EQUIPMENT : WCDMA/GSM smartphone  
BRAND NAME : Blu  
MODEL NAME : Elite3.8  
FCC ID : YHLBLUELITE  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on May 02, 2012 and completely tested on Jun. 13, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



---

Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**

## TABLE OF CONTENTS

REVISION HISTORY .....	3
SUMMARY OF TEST RESULT .....	4
1 GENERAL DESCRIPTION .....	5
1.1 Applicant .....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test .....	5
1.4 Testing Site .....	6
1.5 Applied Standards .....	6
1.6 Ancillary Equipment List .....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....	7
2.1 RF Output Power .....	7
2.2 Test Mode .....	8
2.3 Connection Diagram of Test System .....	9
2.4 RF Utility .....	9
3 TEST RESULT .....	10
3.1 Number of Channel Measurement .....	10
3.2 20dB and 99% Bandwidth Measurement .....	12
3.3 Hopping Channel Separation Measurement .....	19
3.4 Dwell Time Measurement .....	22
3.5 Peak Output Power Measurement .....	24
3.6 Band Edges Measurement .....	27
3.7 Spurious Emission Measurement .....	38
3.8 AC Conducted Emission Measurement .....	42
3.9 Radiated Emission Measurement .....	46
3.10 Antenna Requirements .....	55
4 LIST OF MEASURING EQUIPMENT .....	56
5 UNCERTAINTY OF EVALUATION .....	57
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	

## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR250202A	Rev. 01	Initial issue of report	Jun. 14, 2012

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.8	15.207	Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 11.39 dB at 0.380 MHz
3.9	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.37 dB at 30.000 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

CT Asia

RMA2011, 20/F, GOLDEN CENTRAL TOWER, NO.3037# JINTIAN ROAD, FUTIAN DISTRICT

## 1.2 Manufacturer

Beijing Tianyu Communication Equipment Co., Ltd.

NO.55 Jiachang 2 road, OPTO-Mechatronics Industrial Park, Tongzhou district, Beijing 101111

## 1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	WCDMA/GSM smartphone
Brand Name	Blu
Model Name	Elite3.8
FCC ID	YHLBLUELITE
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 9.69 dBm (0.00932 W) Bluetooth EDR (2Mbps) : 9.37 dBm (0.00865 W) Bluetooth EDR (3Mbps) : 9.74 dBm (0.00942 W)
Antenna Type	PIFA Antenna with gain 0.80 dBi
HW Version	P3.1
SW Version	TBW591227_834F_V2029
Type of Modulation	Bluetooth 2.1 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK Bluetooth 3.0 EDR (1Mbps) : GFSK, $\pi/4$ -DQPSK, 8-DPSK
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.			
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC/IC Registration No.</b>
	TH01-KS	CO01-KS	03CH01-KS	149928/4086E-1

## 1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8
- ♦ IC RSS-Gen Issue 3

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	Router	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
5.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
6.	Notebook	Dell	VOSTRO1450	PPD-AR5B195	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Band	Bluetooth RF Output Power		
Channel	00	39	78
Frequency	2402	2441	2480
Peak Power	9.09	9.74	9.58

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
3. The EUT is programmed to transmit signals continuously for all testing.

## 2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 KHz to 30 MHz), radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.


The following tables are showing the test modes as the worst cases (Zplane) and recorded in this report.

Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	N/A	N/A	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		
Remark:			
1. For radiated TCs, the data rate was set in 3Mbps due to the highest RF output power; only the data of these modes was reported.			




## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 RF Utility

For Bluetooth function, the RF utility, “\* #8924 #” was installed in EUT which was programmed in order to make the EUT into the engineering modes to contact with Bluetooth base station for continuous transmitting and receiving signals.

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Span = the frequency band of operation;  $RBW \geq 1\%$  of the span;  $VBW \geq RBW$ ; Sweep = auto;  
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.


##### 3.1.4 Test Setup




### 3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 7~9	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

**Number of Hopping Channel Plot on Channel 00 - 78**



Date: 25.MAY.2012 20:10:12



Date: 25.MAY.2012 20:16:57

## 3.2 20dB Bandwidth Measurement

### 3.2.1 Limit of 20dB Bandwidth

N/A


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

### 3.2.4 Test Setup




### 3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.904
39	2441	0.908
78	2480	0.904

**20 dB Bandwidth Plot on Channel 00**




Date: 25.MAY.2012 19:37:00

### 20 dB Bandwidth Plot on Channel 39



Date: 25.MAY.2012 19:38:27

### 20 dB Bandwidth Plot on Channel 78




Date: 25.MAY.2012 19:40:45




Test Mode :	Mode 4, 5, 6	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.350
39	2441	1.350
78	2480	1.362

**20 dB Bandwidth Plot on Channel 00**


Date: 25.MAY.2012 19:42:58

### 20 dB Bandwidth Plot on Channel 39



Date: 25.MAY.2012 19:43:28

### 20 dB Bandwidth Plot on Channel 78




Date: 25.MAY.2012 19:43:51



<b>Test Mode :</b>	Mode 7, 8, 9	<b>Temperature :</b>	23~24℃
<b>Test Engineer :</b>	Lizy Li	<b>Relative Humidity :</b>	47~48%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.338
39	2441	1.338
78	2480	1.338

**20 dB Bandwidth Plot on Channel 00**


Date: 25.MAY.2012 19:44:42




20 dB Bandwidth Plot on Channel 39



Date: 25.MAY.2012 19:46:23

20 dB Bandwidth Plot on Channel 78



Date: 25.MAY.2012 19:47:05

### 3.3 Hopping Channel Separation Measurement

#### 3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  $RBW \geq 1\%$  of the span;  
VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

#### 3.3.4 Test Setup




### 3.3.5 Test Result of Hopping Channel Separation


Test Mode :	Mode 7, 8, 9	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8920	Pass
39	2441	1.002	0.8920	Pass
78	2480	1.008	0.8920	Pass


**Channel Separation Plot on Channel 00 - 01**



Date: 25.MAY.2012 19:32:30

**Channel Separation Plot on Channel 39 - 40**


Date: 25.MAY.2012 19:33:35

**Channel Separation Plot on Channel 77 - 78**


Date: 25.MAY.2012 19:34:17

### 3.4 Dwell Time Measurement

#### 3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

#### 3.4.4 Test Setup



#### 3.4.5 Test Result of Dwell Time


<b>Test Mode :</b>	Mode 8	<b>Temperature :</b>	23~24℃
<b>Test Engineer :</b>	Lizy Li	<b>Relative Humidity :</b>	47~48%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
3DH5	3.60	2962.00	0.34	0.4	Pass

**Remark:**

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. T: Package Transfer Time(us)

**3DH5 Dwell Time (One Pulse) Plot on Channel 39**


Date: 25.MAY.2012 19:23:24

**3DH5 Dwell Time (Count Pulses) Plot on Channel 39**


Date: 25.MAY.2012 19:36:37

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, and 3Mbps are 0.125 watts.


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

#### 3.5.4 Test Setup






### 3.5.5 Test Result of Peak Output Power


Test Mode :	Mode 7, 8, 9	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	9.09	20.97	Pass
39	2441	9.74	20.97	Pass
78	2480	9.58	20.97	Pass


**Peak Output Power Plot on Channel 00**



Date: 25.MAY.2012 19:09:51

**Peak Output Power Plot on Channel 39**


Date: 25.MAY.2012 19:11:07

**Peak Output Power Plot on Channel 78**


Date: 25.MAY.2012 19:12:23

## 3.6 Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300KHz, Video bandwidth (VBW)  $\geq$  RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

### 3.6.4 Test Setup

#### <Radiated Band Edges>



#### <Conducted Band Edges>



**3.6.5 Test Result of Radiated Band Edges**

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	40~41%
		<b>Test Engineer :</b>	Jack Li

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2370.8	49.66	-24.34	74	47.42	32.83	3.42	34.01	131	360	Peak
2370.8	36.14	-17.86	54	33.9	32.83	3.42	34.01	131	360	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2312.85	49.71	-24.29	74	47.62	32.73	3.22	33.86	198	360	Peak
2312.85	35.61	-18.39	54	33.52	32.73	3.22	33.86	198	360	Average



Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
		Test Engineer :	Jack Li

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.68	43.46	-30.54	74	40.97	33.01	3.68	34.2	110	0	Peak
2483.68	27.7	-26.3	54	25.21	33.01	3.68	34.2	110	0	Average

## Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	85.57	57.87	27.7	54	-26.3	Pass
Hopping Mode	85.57	58.63	26.94	54	-27.06	Pass

Note : Average result = Maximum field strength – Delta result


ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.78	43.86	-30.14	74	41.37	33.01	3.68	34.2	100	220	Peak
2483.78	28.21	-25.79	54	25.72	33.01	3.68	34.2	100	220	Average

## Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	85.16	58.23	26.93	54	-27.07	Pass
Hopping Mode	85.16	56.95	28.21	54	-25.79	Pass

Note : Average result = Maximum field strength – Delta result

Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
Test Engineer :	Jack Li	Polarization :	Horizontal



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL


Mode : mode 3

: 3DH5

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	103.51	29.51	74.00	101.02	33.01	3.68	34.20	112	0	Peak
2 X	2480.00	85.57	31.57	54.00	83.08	33.01	3.68	34.20	112	0	Average

\* Maximum field strength of the fundamental emission

Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
Test Engineer :	Jack Li	Polarization :	Horizontal



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL

Mode : mode 3


: 3DH5

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 X	2480.00	101.33	27.33	74.00	98.84	33.01	3.68	34.20	115	5 Peak
2	2483.68	43.46	-30.54	74.00	40.97	33.01	3.68	34.20	110	0 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 57.87 dB , single carrier Mode



Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
Test Engineer :	Jack Li	Polarization :	Horizontal



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL


Mode : mode 3

: 3DH5

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level Factor	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 X	2480.00	100.88	26.88	74.00	98.39	33.01	3.68	34.20	114	360 Peak
2	2483.66	42.25	-31.75	74.00	39.76	33.01	3.68	34.20	114	358 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 58.63 dB , Hopping Mode

Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
Test Engineer :	Jack Li	Polarization :	Vertical



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL


Mode : mode 3

: 3DH5

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	103.09	29.09	74.00	100.60	33.01	3.68	34.20	101	215	Peak
2 X	2480.00	85.16	31.16	54.00	82.67	33.01	3.68	34.20	101	215	Average

\* Maximum field strength of the fundamental emission

Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
Test Engineer :	Jack Li	Polarization :	Vertical



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL


Mode : mode 3

: 3DH5

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 X	2480.00	100.53	26.53	74.00	98.04	33.01	3.68	34.20	100	212 Peak
2	2484.14	42.30	-31.70	74.00	39.81	33.01	3.68	34.20	102	360 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 58.23 dB , single carrier Mode

Test Mode :	Mode 3	Temperature :	21~22°C
Test Channel :	78	Relative Humidity :	40~41%
Test Engineer :	Jack Li	Polarization :	Vertical



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL

Mode : mode 3  
: 3DH5


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	100.81	26.81	74.00	98.32	3.68	34.20	101	216	Peak
2	2483.78	43.86	-30.14	74.00	41.37	3.68	34.20	100	220	Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 56.95 dB , Hopping Mode

### 3.6.6 Test Result of Conducted Band Edges


<b>Test Mode :</b>	Mode 7 and 9	<b>Temperature :</b>	23~24℃
<b>Test Channel :</b>	00 and 78	<b>Relative Humidity :</b>	47~48%
		<b>Test Engineer :</b>	Lizy Li

**Low Band Edge Plot on Channel 00**



Date: 25.MAY.2012 19:51:48

**High Band Edge Plot on Channel 78**



Date: 25.MAY.2012 19:52:50

### 3.7 Spurious Emission Measurement

#### 3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


#### 3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 KHz, Video bandwidth (VBW)  $\geq$  RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 KHz RBW.


#### 3.7.4 Test Setup



### 3.7.5 Test Result


Test Mode :	Mode 7	Temperature :	23~24℃
Test Channel :	00	Relative Humidity :	47~48%
		Test Engineer :	Lizy Li

#### Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 25.MAY.2012 19:59:10


#### Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 25.MAY.2012 19:59:22



Test Mode :	Mode 8	Temperature :	23~24℃
Test Channel :	39	Relative Humidity :	47~48%
		Test Engineer :	Lizy Li

**Conducted Spurious Emission Plot between 30MHz ~ 3 GHz**


Date: 25.MAY.2012 20:00:14

**Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz**


Date: 25.MAY.2012 20:00:26



<b>Test Mode :</b>	Mode 9	<b>Temperature :</b>	23~24℃
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	47~48%
		<b>Test Engineer :</b>	Lizy Li

**Conducted Spurious Emission Plot between 30MHz ~ 3 GHz**


Date: 25.MAY.2012 20:01:18

**Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz**


Date: 25.MAY.2012 20:01:30

### 3.8 AC Conducted Emission Measurement

#### 3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.8.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 KHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.8.4 Test Setup



### 3.8.5 Test Result of AC Conducted Emission

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	19~20℃
<b>Test Engineer :</b>	Tom Wang	<b>Relative Humidity :</b>	39~40%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		
<b>Remark :</b>	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS  
Condition: FCC PART15C LISN-100807 LINE

mode : Mode 1  
IMEI : 356379010094173

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.19	31.08	-23.03	54.11	21.00	-0.07	10.15	Average
2	0.19	39.48	-24.63	64.11	29.40	-0.07	10.15	QP
3	0.22	27.08	-25.71	52.79	17.00	-0.07	10.15	Average
4	0.22	36.38	-26.41	62.79	26.30	-0.07	10.15	QP
5	0.38	42.41	-15.89	58.30	32.30	-0.08	10.19	QP
6	0.38	36.91	-11.39	48.30	26.80	-0.08	10.19	Average
7	0.43	28.92	-18.41	47.33	18.80	-0.08	10.20	Average
8	0.43	34.42	-22.91	57.33	24.30	-0.08	10.20	QP
9	0.62	27.04	-18.96	46.00	16.91	-0.09	10.22	Average
10	0.62	32.34	-23.66	56.00	22.21	-0.09	10.22	QP
11	2.31	26.43	-19.57	46.00	16.20	-0.11	10.34	Average
12	2.31	31.93	-24.07	56.00	21.70	-0.11	10.34	QP

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	19~20°C
<b>Test Engineer :</b>	Tom Wang	<b>Relative Humidity :</b>	39~40%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		
<b>Remark :</b>	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS  
Condition: FCC PART15C LISN-100807 NEUTRAL

mode : Mode 1  
IMEI : 356379010094173

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.38	41.91	-16.48	58.39	31.80	-0.08	10.19	QP
2	0.38	35.61	-12.78	48.39	25.50	-0.08	10.19	Average
3	0.68	31.05	-14.95	46.00	20.90	-0.08	10.23	Average
4	0.68	35.15	-20.85	56.00	25.00	-0.08	10.23	QP
5	1.18	34.58	-21.42	56.00	24.39	-0.09	10.28	QP
6	1.18	31.38	-14.62	46.00	21.19	-0.09	10.28	Average
7	1.25	31.79	-14.21	46.00	21.60	-0.09	10.28	Average
8	1.25	35.49	-20.51	56.00	25.30	-0.09	10.28	QP
9	2.10	30.62	-15.38	46.00	20.40	-0.11	10.33	Average
10	2.10	35.02	-20.98	56.00	24.80	-0.11	10.33	QP
11	2.42	30.14	-15.86	46.00	19.90	-0.11	10.35	Average
12	2.42	33.44	-22.56	56.00	23.20	-0.11	10.35	QP

### 3.9 Radiated Emission Measurement

#### 3.9.1 Limit of Radiated Emission

In any 100 KHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.9.3 Test Procedures


- The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
- Use the following spectrum analyzer settings:
  - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for  $f \geq 1$  GHz, 100 KHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
  - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.  
Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.
- Measured average value for the peak value is greater than 54 dBuV/m

### 3.9.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.9.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



**3.9.6 Test Result of Radiated Emission (30 MHz ~ 10<sup>th</sup> Harmonic)**

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	40~41%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2402 MHz is fundamental signals which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
35.82	33.49	-6.51	40	48.69	14.65	0.23	30.08	156	247	Peak
90.14	34.63	-8.87	43.5	55.33	8.9	0.39	29.99	-	-	Peak
129.91	32.1	-11.4	43.5	49.92	11.7	0.47	29.99	-	-	Peak
171.62	33.59	-9.91	43.5	53.86	9.08	0.55	29.9	-	-	Peak
282.2	30.05	-15.95	46	46.59	12.7	0.71	29.95	-	-	Peak
670.2	27.08	-18.92	46	36.61	19.05	1.1	29.68	-	-	Peak
2370.8	49.66	-24.34	74	47.42	32.83	3.42	34.01	131	360	Peak
2370.8	36.14	-17.86	54	33.9	32.83	3.42	34.01	131	360	Average
2402	107.73	-	-	105.45	32.86	3.47	34.05	131	360	Peak
2402	87.64	-	-	85.36	32.86	3.47	34.05	131	360	Average
2498.86	49.11	-24.89	74	46.57	33.05	3.72	34.23	131	360	Peak
2498.86	36.02	-17.98	54	33.48	33.05	3.72	34.23	131	360	Average
4804	53.59	-20.41	74	45.72	35.17	4.97	32.27	135	360	Peak
4804	47.78	-6.22	54	39.91	35.17	4.97	32.27	135	360	Average

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	40~41%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2402 MHz is fundamental signals which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
61.04	32.41	-7.59	40	56.95	5.28	0.31	30.13	-	-	Peak
94.02	34.99	-8.51	43.5	54.91	9.66	0.4	29.98	-	-	Peak
126.03	36.92	-6.58	43.5	54.7	11.74	0.46	29.98	120	360	Peak
257.95	33.49	-12.51	46	50.55	12.12	0.68	29.86	-	-	Peak
719.67	29.21	-16.79	46	38.2	19.52	1.15	29.66	-	-	Peak
989.33	29.26	-24.74	54	36.33	21.04	1.41	29.52	-	-	Peak
2312.85	49.71	-24.29	74	47.62	32.73	3.22	33.86	198	360	Peak
2312.85	35.61	-18.39	54	33.52	32.73	3.22	33.86	198	360	Average
2402	101.07	-	-	98.79	32.86	3.47	34.05	198	360	Peak
2402	80.37	-	-	78.09	32.86	3.47	34.05	198	360	Average
2494.68	49.05	-24.95	74	46.51	33.05	3.72	34.23	198	360	Peak
2494.68	35.61	-18.39	54	33.07	33.05	3.72	34.23	198	360	Average
4804	52	-22	74	44.13	35.17	4.97	32.27	156	248	Peak
4804	40.32	-13.68	54	32.45	35.17	4.97	32.27	156	248	Average

<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	40~41%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2441 MHz is fundamental signals which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30	35.63	-4.37	40	47.45	18	0.26	30.08	120	11	Peak
89.17	34.74	-8.76	43.5	55.73	8.61	0.39	29.99	-	-	Peak
130.88	32.74	-10.76	43.5	50.63	11.63	0.47	29.99	-	-	Peak
171.62	32.71	-10.79	43.5	52.98	9.08	0.55	29.9	-	-	Peak
670.2	26.26	-19.74	46	35.79	19.05	1.1	29.68	-	-	Peak
838.01	27.47	-18.53	46	35.47	20.38	1.27	29.65	-	-	Peak
2331.47	49.23	-24.77	74	47.1	32.76	3.27	33.9	130	360	Peak
2331.47	35.53	-18.47	54	33.4	32.76	3.27	33.9	130	360	Average
2441	106.8	-	-	104.4	32.95	3.6	34.15	130	360	Peak
2441	87.58	-	-	85.18	32.95	3.6	34.15	130	360	Average
2492.97	49.03	-24.97	74	46.49	33.05	3.72	34.23	130	360	Peak
2492.97	35.49	-18.51	54	32.95	33.05	3.72	34.23	130	360	Average
4874	52.63	-21.37	74	44.74	35.18	4.98	32.27	125	48	Peak
4874	38.32	-15.68	54	30.43	35.18	4.98	32.27	125	48	Average

<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	40~41%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2441 MHz is fundamental signals which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
31.94	32.74	-7.26	40	46.04	16.55	0.24	30.09	-	-	Peak
97.9	35.92	-7.58	43.5	55.33	10.15	0.41	29.97	-	-	Peak
127	36.36	-7.14	43.5	54.15	11.73	0.46	29.98	153	286	Peak
257.95	30.66	-15.34	46	47.72	12.12	0.68	29.86	-	-	Peak
580.96	27.79	-18.21	46	37.81	18.57	1.05	29.64	-	-	Peak
719.67	29.63	-16.37	46	38.62	19.52	1.15	29.66	-	-	Peak
2345.72	48.9	-25.1	74	46.73	32.78	3.33	33.94	193	360	Peak
2345.72	35.45	-18.55	54	33.28	32.78	3.33	33.94	193	360	Average
2441	99.78	-	-	97.38	32.95	3.6	34.15	193	360	Peak
2441	79.75	-	-	77.35	32.95	3.6	34.15	193	360	Average
2494.3	49.14	-24.86	74	46.6	33.05	3.72	34.23	193	360	Peak
2494.3	35.66	-18.34	54	33.12	33.05	3.72	34.23	193	360	Average
4874	52.82	-21.18	74	44.93	35.18	4.98	32.27	148	89	Peak
4874	39.12	-14.88	54	31.23	35.18	4.98	32.27	148	89	Average

<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	40~41%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2480 MHz is fundamental signals which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30	34.4	-5.6	40	46.22	18	0.26	30.08	115	263	Peak
89.17	35.13	-8.37	43.5	56.12	8.61	0.39	29.99	-	-	Peak
129.91	33.56	-9.94	43.5	51.38	11.7	0.47	29.99	-	-	Peak
171.62	32.36	-11.14	43.5	52.63	9.08	0.55	29.9	-	-	Peak
666.32	26.42	-19.58	46	35.98	19.01	1.1	29.67	-	-	Peak
900.09	26.89	-19.11	46	34.62	20.45	1.3	29.48	-	-	Peak
2316	48.03	-25.97	74	45.94	32.73	3.22	33.86	134	360	Peak
2316	35.86	-18.14	54	33.77	32.73	3.22	33.86	134	360	Average
2480	103.51	-	-	101.02	33.01	3.68	34.2	112	0	Peak
2480	85.57	-	-	83.08	33.01	3.68	34.2	112	0	Average
2483.68	43.46	-30.54	74	40.97	33.01	3.68	34.2	110	0	Peak
2483.68	27.7	-26.3	54	25.21	33.01	3.68	34.2	110	0	Average
4960	53.03	-20.97	74	45.09	35.2	5	32.26	153	360	Peak
4960	41.73	-12.27	54	33.79	35.2	5	32.26	153	360	Average

<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	21~22°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	40~41%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2480 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
31.94	33.62	-6.38	40	46.92	16.55	0.24	30.09	125	248	Peak
94.02	34.69	-8.81	43.5	54.61	9.66	0.4	29.98	-	-	Peak
131.85	35.4	-8.1	43.5	53.37	11.55	0.47	29.99	-	-	Peak
257.95	31.33	-14.67	46	48.39	12.12	0.68	29.86	-	-	Peak
721.61	28.72	-17.28	46	37.67	19.55	1.15	29.65	-	-	Peak
992.24	29.27	-24.73	54	36.32	21.06	1.41	29.52	-	-	Peak
2314	48.87	-25.13	74	46.78	32.73	3.22	33.86	151	150	Peak
2314	35.67	-18.33	54	33.58	32.73	3.22	33.86	151	150	Average
2480	103.09	-	-	100.6	33.01	3.68	34.2	101	215	Peak
2480	85.16	-	-	82.67	33.01	3.68	34.2	101	215	Average
2483.78	43.86	-30.14	74	41.37	33.01	3.68	34.2	100	220	Peak
2483.78	28.21	-25.79	54	25.72	33.01	3.68	34.2	100	220	Average
4960	52.64	-21.36	74	44.7	35.2	5	32.26	100	360	Peak
4960	39.7	-14.3	54	31.76	35.2	5	32.26	100	360	Average

### 3.10 Antenna Requirements

#### 3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### 3.10.2 Antenna Connected Construction

Non-standard connector used.

#### 3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	May 25, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 30, 2011	May 25, 2012	Dec. 29, 2012	Conducted (TH01-KS)
DC Power supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 23, 2011	May 25, 2012	Aug. 22, 2012	Conducted (TH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	May 25, 2012	Aug. 17, 2012	Conducted (TH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 01, 2012	May 25, 2012	May 31, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 30, 2011	May 25, 2012	Dec. 29, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Dec. 30, 2011	May 25, 2012	Dec. 29, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	N/A	Nov. 16, 2011	May 25, 2012	Nov. 15, 2012	Conduction (CO01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Dec. 30, 2011	May 25, 2012	Dec. 29, 2012	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Jun. 13, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Jun. 13, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Jun. 13, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00	9 kHz~30 MHz	Jul. 28, 2011	Jun. 13, 2012	Jul. 27, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Jun. 13, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 30, 2011	Jun. 13, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Jun. 13, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 07, 2011	Jun. 13, 2012	Nov. 06, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Oct. 11, 2011	Jun. 13, 2012	Oct.10, 2012	Radiation (03CH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	Jun. 13, 2012	Aug. 17, 2012	Radiation (03CH01-KS)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 KHz ~ 30 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.13</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.26</b>		

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.27</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.54</b>		

**Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)**

Contribution	Uncertainty of $X_i$		$u(X_i)$	$C_i$	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	$\pm 0.10$	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	$\pm 1.70$	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	$\pm 0.50$	Normal (k=2)	0.25	1	0.25
Receiver Correction	$\pm 2.00$	Rectangular	1.15	1	1.15
Antenna Factor Directional	$\pm 1.50$	Rectangular	0.87	1	0.87
Site Imperfection	$\pm 2.80$	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>2.36</b>				
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>4.72</b>				



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP250202 as below.