



# FCC RF Test Report

**APPLICANT** : BLU Products, Inc.  
**EQUIPMENT** : Mobile phone  
**BRAND NAME** : BLU  
**MODEL NAME** : DIVA FLIP  
**FCC ID** : YHLBLUDIVAFLIP  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 12, 2016 and testing was completed on Feb. 23, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.


The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

---

Prepared by: Andy Yeh / Manager

---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,  
Nanshan District, Shenzhen, Guangdong, P. R. China**



## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>6</b>
1.1	Applicant.....	6
1.2	Manufacturer .....	6
1.3	Product Feature of Equipment Under Test .....	6
1.4	Product Specification of Equipment Under Test .....	7
1.5	Modification of EUT .....	7
1.6	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	8
1.7	Testing Location .....	8
1.8	Applicable Standards .....	9
<b>2</b>	<b>TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
2.1	Test Mode.....	10
2.2	Connection Diagram of Test System .....	11
2.3	Support Unit used in test configuration .....	11
2.4	Measurement Results Explanation Example .....	12
<b>3</b>	<b>CONDUCTED TEST RESULT .....</b>	<b>13</b>
3.1	Measuring Instruments.....	13
3.2	Test Setup .....	13
3.3	Test Result of Conducted Test.....	13
3.4	Conducted Output Power .....	14
3.5	Peak-to-Average Ratio .....	15
3.6	99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	16
3.7	Conducted Band Edge .....	17
3.8	Conducted Spurious Emission .....	18
3.9	Frequency Stability .....	19
<b>4</b>	<b>RADIATED TEST ITEMS .....</b>	<b>20</b>
4.1	Measuring Instruments.....	20
4.2	Test Setup .....	20
4.3	Test Result of Radiated Test.....	20
4.4	Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	21
4.5	Field Strength of Spurious Radiation Measurement .....	23
<b>5</b>	<b>LIST OF MEASURING EQUIPMENT .....</b>	<b>24</b>
<b>6</b>	<b>UNCERTAINTY OF EVALUATION .....</b>	<b>25</b>
<b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>		
<b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>		
<b>APPENDIX C. TEST SETUP PHOTOGRAPHS</b>		



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG611204	Rev. 01	Initial issue of report	Mar. 17, 2016

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.4	§2.1046	RSS-132 (5.4) RSS-133 (6.4)	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	RSS-132 (5.4) RSS-133 (6.4)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	RSS-GEN(6.6) RSS-132(3.1) RSS-133(3.1)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	RSS-GEN(6.11) RSS-132 (5.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-
	§2.1055 §24.235	RSS-GEN(6.11) RSS-133 (6.3)		Within Authorized Band		



Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
4.4	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 2.02 dB at 5640.000 MHz



# 1 General Description

## 1.1 Applicant

**BLU Products, Inc.**

10814 NW 33rd St # 100 Doral, FL 33172

## 1.2 Manufacturer

**BLU Products, Inc.**

10814 NW 33rd St # 100 Doral, FL 33172

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	DIVA FLIP
FCC ID	YHLBLUDIVAFLIP
EUT supports Radios application	GSM/Bluetooth v3.0+EDR
IMEI Code	Conducted: 351771053541794/351771053541802 Radiation: 351771053541711/351771053541729 ERP/EIRP: 351771053541711/351771053541729
HW Version	S2415-MB-V1.2
SW Version	BLU_T390_V08_GENERIC_ANATEL_160129_1415
EUT Stage	Production Unit

### Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose dual SIM1 card to perform all tests.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	<b>GSM:</b> 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz
<b>Rx Frequency</b>	<b>GSM:</b> 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz
<b>Maximum Output Power to Antenna</b>	<b>GSM:</b> 850: 32.17 dBm 1900: 28.82 dBm
<b>Antenna Type</b>	IFA Antenna
<b>Type of Modulation</b>	GSM: GMSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.0855	0.0693 ppm	243KGXW
Part 24	GSM1900 GSM	GMSK	0.4084	0.0420 ppm	242KGXW

## 1.7 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-SZ	

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.	
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC/IC Registration No.</b>
	03CH03-KS	306251/4086E

**Note:** The test site complies with ANSI C63.4 2014 requirement.





## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.


Radiated emissions were investigated from 30 MHz to 10th harmonic.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m



## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$

### 3 Conducted Test Result

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



## **3.4 Conducted Output Power**

### **3.4.1 Description of the Conducted Output Power**

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

### **3.4.2 Test Procedures**

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



## **3.5 Peak-to-Average Ratio**

### **3.5.1 Description of the PAR Measurement**

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### **3.5.2 Test Procedures**

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.  
Record the maximum PAPR level associated with a probability of 0.1%.

### 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.  
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### 3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.  
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.8 Conducted Spurious Emission

#### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

#### 3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
=  $P(W) - [43 + 10\log(P)]$  (dB)  
=  $[30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
= -13dBm.

### 3.9 Frequency Stability

#### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.

## 4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

### 4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

### 4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor,  $EIRP = LVL + \text{Correction factor}$  and  $ERP = EIRP - 2.15$ . Take the record of the output power at substitution antenna.



	GSM
SPAN	500kHz
RBW	10kHz
VBW	30kHz
Detector	RMS
Trace	Average
Average Type	Power
Sweep Count	100

## 4.5 Field Strength of Spurious Radiation Measurement

### 4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 05,2015	Jan. 20, 2016	May 04, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangro	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2015	Jan. 20, 2016	Aug. 06, 2016	Conducted (TH01-SZ)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Jun. 05, 2015	Feb. 23, 2016	Jun. 04, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25MHz~2GHz	Jan. 16, 2016	Feb. 23, 2016	Jan. 15, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Feb. 23, 2016	Jun. 24, 2016	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 03, 2015	Feb. 23, 2016	Mar. 02, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz~3000MHz	Aug. 10, 2015	Feb. 23, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-001 01800-30-10	1889560	1GHz~18GHz	Aug. 10, 2015	Feb. 23, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Feb. 23, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Aug. 27, 2015	Feb. 23, 2016	Aug. 26, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 23, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 23, 2016	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 23, 2016	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required





## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5 dB
---	--------

## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	31.80	32.00	32.17	28.82	28.62	28.34


### Peak-to-Average Ratio

Mode	GSM		Limit: 13dB
Mod.	GSM850	GSM1900	Result
Lowest CH	0.17	0.12	PASS
Middle CH	0.12	0.12	
Highest CH	0.12	0.12	




## GSM850 (GSM)

## Lowest Channel




## GSM1900 (GSM)


## Lowest Channel




## Middle Channel




## Middle Channel



## Highest Channel



## Highest Channel




**26dB Bandwidth**

Mode	GSM	
Mod.	GSM850	GSM1900
Lowest CH	0.312	0.315
Middle CH	0.310	0.317
Highest CH	0.312	0.311




## GSM850 (GSM)

## Lowest Channel



## GSM1900 (GSM)


## Lowest Channel



## Middle Channel




## Middle Channel



## Highest Channel



## Highest Channel



**Occupied Bandwidth**


Mode	GSM	
Mod.	GSM850	GSM1900
Lowest CH	0.243	0.242
Middle CH	0.242	0.242
Highest CH	0.243	0.242





## GSM850 (GSM)

## Lowest Channel




## GSM1900 (GSM)


## Lowest Channel




## Middle Channel




## Middle Channel



## Highest Channel





## Highest Channel





## Conducted Band Edge








## Conducted Spurious Emission


### GSM850 (GSM)

#### Lowest Channel




### GSM1900 (GSM)


#### Lowest Channel




### Middle Channel




### Middle Channel



### Highest Channel



### Highest Channel



**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0681	PASS
40	Normal Voltage	0.0036	
30	Normal Voltage	0.0622	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0036	
-10	Normal Voltage	0.0670	
-20	Normal Voltage	0.0693	
-30	Normal Voltage	0.0108	
20	Maximum Voltage	0.0012	
20	Normal Voltage	0.0036	
20	Battery End Point	0.0012	

Test Conditions	Middle Channel	GSM1900 (GSM)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0415	PASS
40	Normal Voltage	0.0404	
30	Normal Voltage	0.0394	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0362	
-10	Normal Voltage	0.0383	
-20	Normal Voltage	0.0394	
-30	Normal Voltage	0.0420	
20	Maximum Voltage	0.0016	
20	Normal Voltage	0.0005	
20	Battery End Point	0.0011	

**Note:**

1. Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.4V. ; Maximum Voltage =4.2V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small

## Appendix B. Test Results of Radiated Test

### ERP/EIRP

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	GSM850 GSM	16.85	0.0484	5.68	0.0037
Middle		18.52	0.0711	6.21	0.0042
Highest		19.32	0.0855	7.46	0.0056
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GSM	25.73	0.3744	26.11	0.4084
Middle		25.06	0.3209	25.45	0.3507
Highest		25.32	0.3405	25.34	0.3416
Limit	EIRP < 2W	Result		PASS	



## Radiated Spurious Emission

GSM850 (GSM)									
Channel	Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-44.41	-13	-31.41	-54.98	-51.09	0.57	9.40	H
	2472.6	-36.05	-13	-23.05	-52.72	-43.76	0.74	10.60	H
	3296.8	-35.97	-13	-22.97	-55.22	-45.57	0.85	12.60	H
	4121	-23.28	-13	-10.28	-45.58	-32.84	0.89	12.60	H
	4945.2	-37.79	-13	-24.79	-59.79	-47.40	0.94	12.70	H
	5769.4	-40.65	-13	-27.65	-62.24	-50.39	1.11	13.00	H
	6593.6	-43.42	-13	-30.42	-66.61	-51.75	1.22	11.70	H
	7417.8	-50.14	-13	-37.14	-74.60	-57.60	1.69	11.30	H
	8242	-36.31	-13	-23.31	-62.98	-43.83	1.63	11.30	H
	1648.4	-37.79	-13	-24.79	-48.67	-44.47	0.57	9.40	V
	2472.6	-34.74	-13	-21.74	-51.59	-42.45	0.74	10.60	V
	3296.8	-36.66	-13	-23.66	-55.86	-46.26	0.85	12.60	V
	4121	-19.80	-13	-6.80	-42.19	-29.36	0.89	12.60	V
	4945.2	-30.09	-13	-17.09	-53.35	-39.70	0.94	12.70	V
	5769.4	-36.56	-13	-23.56	-59.20	-46.30	1.11	13.00	V
	6593.6	-39.16	-13	-26.16	-62.55	-47.49	1.22	11.70	V
	7417.8	-44.79	-13	-31.79	-68.97	-52.25	1.69	11.30	V
	8242	-32.74	-13	-19.74	-60.11	-40.26	1.63	11.30	V
Middle	1672	-39.63	-13	-26.63	-50.96	-46.31	0.57	9.40	H
	2510	-33.79	-13	-20.79	-50.77	-41.50	0.74	10.60	H
	3346	-36.93	-13	-23.93	-55.99	-46.53	0.85	12.60	H
	4182	-24.97	-13	-11.97	-47.25	-34.53	0.89	12.60	H
	5018	-38.69	-13	-25.69	-60.44	-48.30	0.94	12.70	H
	5854	-43.16	-13	-30.16	-65.01	-52.90	1.11	13.00	H
	6691	-44.19	-13	-31.19	-67.38	-52.52	1.22	11.70	H
	7528	-47.32	-13	-34.32	-71.78	-54.78	1.69	11.30	H
	8364	-40.01	-13	-27.01	-66.68	-47.53	1.63	11.30	H
	1672	-40.51	-13	-27.51	-51.14	-47.19	0.57	9.40	V
	2510	-31.87	-13	-18.87	-49.25	-39.58	0.74	10.60	V
	3346	-36.46	-13	-23.46	-55.72	-46.06	0.85	12.60	V
	4182	-20.82	-13	-7.82	-43.08	-30.38	0.89	12.60	V
	5018	-32.80	-13	-19.80	-55.80	-42.41	0.94	12.70	V
	5854	-37.61	-13	-24.61	-60.15	-47.35	1.11	13.00	V
	6691	-35.75	-13	-22.75	-59.74	-44.08	1.22	11.70	V
	7528	-44.77	-13	-31.77	-68.95	-52.23	1.69	11.30	V
	8364	-36.94	-13	-23.94	-63.37	-44.46	1.63	11.30	V



Highest	1697.6	-44.26	-13	-31.26	-54.88	-50.94	0.57	9.40	H
	2546.4	-37.19	-13	-24.19	-53.75	-44.90	0.74	10.60	H
	3395.2	-35.02	-13	-22.02	-54.45	-44.62	0.85	12.60	H
	4244	-25.38	-13	-12.38	-47.63	-34.94	0.89	12.60	H
	5092.8	-40.03	-13	-27.03	-61.23	-49.64	0.94	12.70	H
	5941.6	-43.64	-13	-30.64	-65.49	-53.38	1.11	13.00	H
	6790.4	-44.18	-13	-31.18	-67.37	-52.51	1.22	11.70	H
	7639.2	-49.14	-13	-36.14	-73.60	-56.60	1.69	11.30	H
	8488	-44.06	-13	-31.06	-70.73	-51.58	1.63	11.30	H
	1697.6	-45.69	-13	-32.69	-55.56	-52.37	0.57	9.40	V
	2546.4	-27.26	-13	-14.26	-44.78	-34.97	0.74	10.60	V
	3395.2	-37.25	-13	-24.25	-56.30	-46.85	0.85	12.60	V
	4244	-20.63	-13	-7.63	-42.92	-30.19	0.89	12.60	V
	5092.8	-34.15	-13	-21.15	-56.85	-43.76	0.94	12.70	V
	5941.6	-38.15	-13	-25.15	-60.68	-47.89	1.11	13.00	V
	6790.4	-39.69	-13	-26.69	-63.08	-48.02	1.22	11.70	V
	7639.2	-45.29	-13	-32.29	-69.47	-52.75	1.69	11.30	V
	8488	-41.78	-13	-28.78	-68.21	-49.30	1.63	11.30	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GSM)									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-31.26	-13	-18.26	-54.56	-42.99	0.87	12.60	H
	5550.6	-22.74	-13	-9.74	-48.97	-34.77	1.07	13.10	H
	7400.8	-37.17	-13	-24.17	-63.32	-46.78	1.69	11.30	H
	9252	-38.52	-13	-25.52	-68.74	-48.59	1.83	11.90	H
	3700.4	-29.44	-13	-16.44	-53.35	-41.17	0.87	12.60	V
	5550.6	-20.73	-13	-7.73	-47.49	-32.76	1.07	13.10	V
	7400.8	-37.02	-13	-24.02	-63.04	-46.45	1.87	11.30	V
	9252	-43.98	-13	-30.98	-73.26	-54.05	1.83	11.90	V
Middle	3760	-26.15	-13	-13.15	-50.01	-37.88	0.87	12.60	H
	5640	-15.02	-13	-2.02	-41.48	-27.05	1.07	13.10	H
	7520	-37.77	-13	-24.77	-63.70	-47.38	1.69	11.30	H
	9400	-42.57	-13	-29.57	-72.79	-52.64	1.83	11.90	H
	3760	-27.09	-13	-14.09	-51.22	-38.82	0.87	12.60	V
	5640	-19.81	-13	-6.81	-46.59	-31.84	1.07	13.10	V
	7520	-35.41	-13	-22.41	-61.79	-44.84	1.87	11.30	V
	9400	-44.31	-13	-31.31	-73.59	-54.38	1.83	11.90	V
Highest	3819.6	-23.68	-13	-10.68	-47.57	-35.41	0.87	12.60	H
	5729.4	-16.64	-13	-3.64	-43.07	-28.67	1.07	13.10	H
	7639.2	-45.53	-13	-32.53	-70.66	-55.14	1.69	11.30	H
	9548	-36.88	-13	-23.88	-67.10	-46.95	1.83	11.90	H
	3819.6	-22.54	-13	-9.54	-46.99	-34.27	0.87	12.60	V
	5729.4	-20.44	-13	-7.44	-47.21	-32.47	1.07	13.10	V
	7639.2	-46.41	-13	-33.41	-71.32	-55.84	1.87	11.30	V
	9548	-45.81	-13	-32.81	-75.09	-55.88	1.83	11.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.