


FCC Test Report


APPLICANT : CT Asia
EQUIPMENT : Mobile phone
BRAND NAME : BLU
MODEL NAME : Studio 5.5 S
MARKETING NAME : Studio 5.5 S
FCC ID : YHLBLUSTUDIO55S
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Dec. 18, 2013 and testing was completed on Jan. 02, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Louis Wu / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Feature of Equipment Under Test.....	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	7
1.6. Test Site	7
1.7. Applied Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1. Test Mode	8
2.2. Connection Diagram of Test System	10
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup	12
3. TEST RESULT	13
3.1. Test of AC Conducted Emission Measurement	13
3.2. Test of Radiated Emission Measurement	21
4. LIST OF MEASURING EQUIPMENT	25
5. UNCERTAINTY OF EVALUATION	26
APPENDIX A. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC3D1804	Rev. 01	Initial issue of report	Jan. 13, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.69 dB at 3.400 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 2.79 dB at 193.930 MHz for Quasi-Peak

1. General Description

1.1. Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2. Manufacturer

TINNO MOBILE

4/F., H-3 Building, OCT Eastern Industrial Park. NO.1 Xiangshan East Road, Nan Shan District, Shenzhen, P.R. CHINA

1.3. Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	Studio 5.5 S
Marketing Name	Studio 5.5 S
FCC ID	YHLBLUSTUDIO55S
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	V1.1
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900 : 1850.2 MHz ~ 1909.8MHz WCDMA Band V : 826.4 MHz ~ 846.6 MHz WCDMA Band II : 1852.4 MHz ~ 1907.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850 : 869.2 MHz ~ 893.8 MHz GSM1900 : 1930.2 MHz ~ 1989.8 MHz WCDMA Band V : 871.4 MHz ~ 891.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Downlink Only) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth v4.0 LE : GFSK Bluetooth v3.0 + EDR : GFSK, $\pi/4$ -DQPSK, 8-DPSK GPS : BPSK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Site

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.		FCC Registration No.
	CO01-SZ	03CH01-SZ	831040

1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	Note 1
2.	Data application transferred mode (EUT connected with notebook)	☒	☒	☒

Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Note 1: Testing for this mode is not required or not the worst case.


Remark: For signal above 1GHz, the worst case was test item 2.

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera + SIM1<Fig. 1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM1<Fig. 1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1<Fig. 2>
Radiated Emissions < 1GHz	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera + SIM1<Fig. 1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM1<Fig. 1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1<Fig. 2>
Radiated Emissions ≥ 1GHz	2	Mode 1: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1<Fig. 2>
Remark: <ol style="list-style-type: none"> The worst case of AC is mode 2, and the USB Link mode of AC is mode 3, the test data of these modes are reported. The worst case of RE < 1G is mode 3; only the test data of this mode is reported. Link with Notebook means data application transferred mode between EUT and Notebook. 		

2.2. Connection Diagram of Test System



<Fig. 1>



<Fig. 2>

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-link	DIR-815	KA2IR815A1	N/A	Unshielded, 1.8m
4.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
5.	Bluetooth Earphone	Nokia	BH-108	FCC DoC	N/A	N/A
6.	Notebook	DELL	Vostro2420	FCC DoC	N/A	AC I/P: Unshielded, 1.2m DC O/P: Shielded, 1.8 m
7.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
8.	Monitor	DELL	IN1940MWb	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m
9.	SD Card	SanDisk	4G Class 4	FCC DoC	N/A	N/A
10.	iPod nano 8GB	Apple	MC690 ZP/A	FCC DoC	Shielded, 1.2 m	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Execute the program, "Winthrax" under WIN7 installed in notebook for files transfer with EUT via USB cable / iPod.
2. Turn on GPS function to make the EUT receive continuous signals from GPS station.
3. Execute "Video Player" to play MPEG4 files.
4. Turn on camera to capture images.
5. Execute "H Pattern" to show H Pattern via VGA Cable on the Monitor.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.1.4 Test Setup




3.1.5 Test Result of AC Conducted Emission






Test Mode :	Mode 2	Temperature :	21~22℃
Test Engineer :	Henry Chen	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM1		



Site : C001-SZ
Condition: FCC 15B_QP LISN_L_20130328 LINE
Project : (FC)3D1804
Mode : Mode 2


	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
26	1.84	41.71	-14.29	56.00	31.30	0.23	10.18	QP
27	1.93	31.21	-14.79	46.00	20.80	0.23	10.18	Average
28	1.93	41.11	-14.89	56.00	30.70	0.23	10.18	QP
29	2.10	32.22	-13.78	46.00	21.80	0.23	10.19	Average
30	2.10	42.42	-13.58	56.00	32.00	0.23	10.19	QP
31	2.45	33.74	-12.26	46.00	23.29	0.25	10.20	Average
32	2.45	43.84	-12.16	56.00	33.39	0.25	10.20	QP
33	2.64	34.45	-11.55	46.00	24.00	0.25	10.20	Average
34	2.64	44.15	-11.85	56.00	33.70	0.25	10.20	QP
35	2.76	35.26	-10.74	46.00	24.80	0.26	10.20	Average
36	2.76	45.16	-10.84	56.00	34.70	0.26	10.20	QP
37	3.06	36.27	-9.73	46.00	25.79	0.27	10.21	Average
38	3.06	46.47	-9.53	56.00	35.99	0.27	10.21	QP
39 *	3.36	36.79	-9.21	46.00	26.30	0.28	10.21	Average
40	3.36	46.69	-9.31	56.00	36.20	0.28	10.21	QP
41	3.66	36.30	-9.70	46.00	25.80	0.28	10.22	Average
42	3.66	46.50	-9.50	56.00	36.00	0.28	10.22	QP
43	3.84	35.51	-10.49	46.00	25.00	0.29	10.22	Average
44	3.84	45.21	-10.79	56.00	34.70	0.29	10.22	QP
45	4.16	33.52	-12.48	46.00	23.01	0.29	10.22	Average
46	4.16	43.22	-12.78	56.00	32.71	0.29	10.22	QP
47	4.38	31.73	-14.27	46.00	21.20	0.30	10.23	Average
48	4.38	42.13	-13.87	56.00	31.60	0.30	10.23	QP
49	4.72	29.84	-16.16	46.00	19.30	0.31	10.23	Average
50	4.72	40.54	-15.46	56.00	30.00	0.31	10.23	QP
51	4.98	28.75	-17.25	46.00	18.20	0.31	10.24	Average
52	4.98	39.55	-16.45	56.00	29.00	0.31	10.24	QP

Test Mode :	Mode 2	Temperature :	21~22℃
Test Engineer :	Henry Chen	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM1		




Site : CO01-SZ
Condition: FCC 15B_QP LISN_N_20130328 NEUTRAL
Project : (FC)3D1804
Mode : Mode 2

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.38	40.02	-8.32	48.34	29.80	0.04	10.18	Average
2	0.38	47.22	-11.12	58.34	37.00	0.04	10.18	QP
3	0.40	38.41	-9.36	47.77	28.20	0.04	10.17	Average
4	0.40	46.21	-11.56	57.77	36.00	0.04	10.17	QP
5	0.50	35.70	-10.35	46.05	25.50	0.04	10.16	Average
6	0.50	44.20	-11.85	56.05	34.00	0.04	10.16	QP
7	0.53	36.79	-9.21	46.00	26.60	0.04	10.15	Average
8	0.53	47.49	-8.51	56.00	37.30	0.04	10.15	QP
9	0.61	38.79	-7.21	46.00	28.60	0.04	10.15	Average
10	0.61	47.29	-8.71	56.00	37.10	0.04	10.15	QP
11	0.64	36.19	-9.81	46.00	26.00	0.04	10.15	Average
12	0.64	46.19	-9.81	56.00	36.00	0.04	10.15	QP
13	0.77	32.29	-13.71	46.00	22.10	0.04	10.15	Average
14	0.77	41.39	-14.61	56.00	31.20	0.04	10.15	QP
15	0.83	30.89	-15.11	46.00	20.70	0.04	10.15	Average
16	0.83	41.49	-14.51	56.00	31.30	0.04	10.15	QP
17	1.02	33.79	-12.21	46.00	23.60	0.04	10.15	Average
18	1.02	42.99	-13.01	56.00	32.80	0.04	10.15	QP
19	1.09	34.20	-11.80	46.00	24.00	0.04	10.16	Average
20	1.09	43.90	-12.10	56.00	33.70	0.04	10.16	QP
21	1.31	33.41	-12.59	46.00	23.19	0.05	10.17	Average
22	1.31	43.21	-12.79	56.00	32.99	0.05	10.17	QP
23	1.53	34.73	-11.27	46.00	24.51	0.05	10.17	Average
24	1.53	44.83	-11.17	56.00	34.61	0.05	10.17	QP
25	1.66	35.93	-10.07	46.00	25.70	0.05	10.18	Average
26	1.66	45.23	-10.77	56.00	35.00	0.05	10.18	QP
27	1.78	36.24	-9.76	46.00	26.00	0.06	10.18	Average
28	1.78	46.04	-9.96	56.00	35.80	0.06	10.18	QP
29	1.86	35.84	-10.16	46.00	25.60	0.06	10.18	Average




Test Mode :	Mode 3	Temperature :	21~22℃
Test Engineer :	Henry Chen	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		



Site : C001-SZ
 Condition: FCC 15B_QP LISN_L_20130328 LINE
 Project : (FC)3D1804
 Mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.15	26.22	-29.78	56.00	15.80	0.06	10.36	Average
2	0.15	44.02	-21.98	66.00	33.60	0.06	10.36	QP
3	0.19	34.57	-19.41	53.98	24.20	0.07	10.30	Average
4 *	0.19	48.77	-15.21	63.98	38.40	0.07	10.30	QP
5	0.27	34.51	-16.47	50.98	24.20	0.09	10.22	Average
6	0.27	44.11	-16.87	60.98	33.80	0.09	10.22	QP
7	0.34	29.30	-19.97	49.27	19.00	0.11	10.19	Average
8	0.34	39.90	-19.37	59.27	29.60	0.11	10.19	QP
9	0.38	23.70	-24.60	48.30	13.40	0.12	10.18	Average
10	0.38	36.50	-21.80	58.30	26.20	0.12	10.18	QP
11	4.29	17.93	-28.07	46.00	7.40	0.30	10.23	Average
12	4.29	31.53	-24.47	56.00	21.00	0.30	10.23	QP

Test Mode :	Mode 3	Temperature :	21~22℃
Test Engineer :	Henry Chen	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		



Site : CO01-SZ
 Condition: FCC 15B_QP LISN_N_20130328 NEUTRAL
 Project : (FC)3D1804
 Mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	34.39	-21.17	55.56	24.00	0.04	10.35	Average
2	0.16	49.39	-16.17	65.56	39.00	0.04	10.35	QP
3	0.21	31.33	-21.99	53.32	21.00	0.04	10.29	Average
4	0.21	44.73	-18.59	63.32	34.40	0.04	10.29	QP
5	0.27	25.36	-25.71	51.07	15.10	0.04	10.22	Average
6	0.27	39.46	-21.61	61.07	29.20	0.04	10.22	QP
7	0.35	22.73	-26.32	49.05	12.50	0.04	10.19	Average
8	0.35	35.83	-23.22	59.05	25.60	0.04	10.19	QP
9	0.40	29.41	-18.40	47.81	19.20	0.04	10.17	Average
10	0.40	38.31	-19.50	57.81	28.10	0.04	10.17	QP
11 *	0.47	31.20	-15.38	46.58	21.00	0.04	10.16	Average
12	0.47	35.20	-21.38	56.58	25.00	0.04	10.16	QP

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission


Test Mode :	Mode 3	Temperature :	24~26°C
Test Engineer :	Robin Luo	Relative Humidity :	49~50%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		



Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF_ANT_121103 HORIZONTAL
 Project : (FC)3D1804
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 Q	193.93	40.71	-2.79	43.50	59.96	9.43	1.67	30.35	100	235 QP
2 P	239.52	41.59	-4.41	46.00	58.24	11.73	1.82	30.20	---	---
3 !	330.70	40.85	-5.15	46.00	53.97	14.68	2.10	29.90	100	321 QP
4	480.08	39.81	-6.19	46.00	49.53	17.20	2.48	29.40	---	---
5	684.75	39.25	-6.75	46.00	46.29	19.12	2.93	29.09	---	---
6	960.23	36.67	-17.33	54.00	40.16	21.80	3.43	28.72	---	---

Test Mode :	Mode 3	Temperature :	24~26°C
Test Engineer :	Robin Luo	Relative Humidity :	49~50%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		



Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF_ANT_121103 VERTICAL
 Project : (FC)3D1804
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	193.93	39.51	-3.99	43.50	58.76	9.43	1.67	30.35	---	---	Peak
2	240.49	38.96	-7.04	46.00	55.44	11.90	1.82	30.20	---	---	Peak
3 P	480.08	42.13	-3.87	46.00	51.85	17.20	2.48	29.40	100	0	Peak
4 !	688.63	40.16	-5.84	46.00	47.05	19.24	2.95	29.08	---	---	Peak
5 !	719.67	41.99	-4.01	46.00	48.04	20.00	2.99	29.04	---	---	Peak
6	960.23	36.30	-17.70	54.00	39.79	21.80	3.43	28.72	---	---	Peak

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC LISN	ETS-LINDGREN	3816/2SH	00103912	0.1MHz~108MHz	Feb. 28, 2011	Dec. 25, 2013~ Jan. 02, 2014	Feb. 27, 2014	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	ETS-LINDGREN	3816/2SH	00103892	0.1MHz~108MHz	Feb. 28, 2011	Dec. 25, 2013~ Jan. 02, 2014	Feb. 27, 2014	Conduction (CO01-SZ)
ESCIO TEST Receiver	R&S	1142.8007.0 3	100724	9kHz~3GHz	Mar. 08, 2011	Dec. 25, 2013~ Jan. 02, 2014	Mar. 07, 2014	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000 891N/A	N/A	Nov. 20, 2013	Dec. 25, 2013~ Jan. 02, 2014	Nov. 19, 2014	Conduction (CO01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260 185	20Hz~26.5GHz	Apr. 04, 2013	Dec. 31, 2013	Apr. 03, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 26, 2013	Dec. 31, 2013	Oct. 25, 2014	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Dec. 26, 2013	Dec. 31, 2013	Dec. 25, 2014	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz GAIN 30db	Mar. 28, 2013	Dec. 31, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	Dec. 31, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0 ~ 360 degree	N/A	Dec. 31, 2013	N/A	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m - 4 m	N/A	Dec. 31, 2013	N/A	Radiation (03CH01-SZ)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.90
--	------