

FCC RF Test Report

APPLICANT : CT Asia
EQUIPMENT : GSM & WCDMA Mobile Phone
BRAND NAME : BLU
MODEL NAME : Quattro 5.7 HD
FCC ID : YHLBLUQT57HD
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 25, 2012 and completely tested on Jan. 29, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test	6
1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.6 Testing Site	7
1.7 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration and system.....	10
2.4 Measurement Results Explanation Example	10
3 TEST RESULT	11
3.1 Conducted Output Power Measurement.....	11
3.2 Peak-to-Average Ratio	13
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	23
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	29
3.5 Band Edge Measurement.....	53
3.6 Conducted Spurious Emission Measurement	68
3.7 Field Strength of Spurious Radiation Measurement	87
3.8 Frequency Stability Measurement.....	104
4 LIST OF MEASURING EQUIPMENT	110
5 UNCERTAINTY OF EVALUATION	111
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG2D2505	Rev. 01	Initial issue of report	Feb. 22, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d) §27.50(d)(5)	RSS-133 (6.4)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§27.50(d)(4)	RSS-139 (6.4) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a) §27.53(h)	N/A	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(h)	RSS-132 (5.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 19.59 dB at 10395.600 MHz
3.8	§2.1055 §22.355 §24.235 §27.54	RSS-132 (5.3) RSS-133 (6.3) RSS-139 (6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

CT Asia

Unit 01, 15/F, Seaview Centre, 139-141 Hoi bun road, Kwun Tong, Kowloon, Hongkong

1.2 Manufacturer

Beijing Tianyu Communication Equipment Co. Ltd.

NO.55 Jiachang 2 road, OPTO-Mechatronics Industrial Park, Tongzhou district, Beijing 101111

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	GSM & WCDMA Mobile Phone
Brand Name	BLU
Model Name	Quattro 5.7 HD
FCC ID	YHLBLUQT57HD
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/WLAN 11bgn/Bluetooth
HW Version	P3.0
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.74 dBm GSM1900 : 29.87 dBm WCDMA Band V : 23.80 dBm WCDMA Band IV : 24.04 dBm WCDMA Band II : 24.17 dBm
Antenna Type	Fixed Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.5834	0.02 ppm	246KGXW
Part 22	GSM850 EDGE 8	8PSK	0.1567	0.02 ppm	244KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0861	0.01 ppm	4M10F9W
Part 24	GSM1900 GSM	GMSK	0.7656	0.01 ppm	246KGXW
Part 24	GSM1900 EDGE 8	8PSK	0.3097	0.01 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.2844	0.01 ppm	4M10F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.2328	0.01 ppm	4M08F9W

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-KS	03CH01-KS	149928/4086E-1

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note:


The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, RMC 12.2Kbps mode for WCDMA band IV, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM (GMSK, 1 Tx slot)	32.74	32.72	32.70	29.87	29.72	29.66
GPRS (GMSK, 1 Tx slot) – CS1	32.71	32.70	32.69	29.85	29.70	29.64
GPRS (GMSK, 2 Tx slots) – CS1	32.69	32.68	32.68	29.82	29.69	29.63
GPRS (GMSK, 3 Tx slots) – CS1	31.93	31.92	31.91	29.10	28.95	28.88
GPRS (GMSK, 4 Tx slots) – CS1	30.78	30.77	30.76	27.90	27.76	27.71
EDGE (8PSK, 1 Tx slot) – MCS5	27.15	27.11	27.10	25.98	25.87	25.85
EDGE (8PSK, 2 Tx slots) – MCS5	27.13	27.09	27.07	25.96	25.85	25.82
EDGE (8PSK, 3 Tx slots) – MCS5	26.33	26.31	26.26	25.14	25.04	25.01
EDGE (8PSK, 4 Tx slots) – MCS5	25.15	25.12	25.08	23.92	23.81	23.78
GSM (GMSK, 1 Tx slot)	32.72	32.70	32.69	29.74	29.58	29.52
GPRS (GMSK, 1 Tx slot) – CS1	32.73	32.71	32.70	29.75	29.60	29.54
GSM (GMSK, 1 Tx slot)	32.71	32.69	32.68	29.73	29.58	29.51
GPRS (GMSK, 1 Tx slot) – CS1	32.72	32.70	32.69	29.74	29.59	29.53
GSM (GMSK, 1 Tx slot)	31.95	31.94	31.93	28.98	28.84	28.78
GPRS (GMSK, 2 Tx slots) – CS1	31.96	31.95	31.94	28.99	28.85	28.78
GSM (GMSK, 1 Tx slot)	27.03	27.03	27.02	25.81	25.66	25.65
EDGE (8PSK, 1 Tx slot) – MCS5	27.05	27.04	27.03	25.82	25.68	25.66
GSM (GMSK, 1 Tx slot)	27.07	27.05	27.04	25.80	25.63	25.60
EDGE (8PSK, 1 Tx slot) – MCS5	27.08	27.07	27.05	25.80	25.64	25.61
GSM (GMSK, 1 Tx slot)	26.21	26.20	26.18	24.97	24.83	24.80
EDGE (8PSK, 2 Tx slots) – MCS5	26.22	26.20	26.17	24.98	24.85	24.80

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Tx Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2k	23.78	23.76	23.75	24.15	24.01	23.80	24.01	23.96	24.02
RMC 12.2k	23.80	23.79	23.77	24.17	24.02	23.82	24.03	23.97	24.04
HSDPA Subtest-1	23.61	23.60	23.58	23.89	23.74	23.65	23.83	23.78	23.85
HSDPA Subtest-2	23.43	23.46	23.43	23.68	23.74	23.47	23.65	23.59	23.67
HSDPA Subtest-3	23.25	23.27	23.20	23.49	23.55	23.30	23.47	23.34	23.48
HSDPA Subtest-4	21.96	21.94	21.94	22.11	22.38	22.20	22.19	22.07	22.21
HSUPA Subtest-1	22.52	22.58	22.56	23.12	22.83	22.82	22.92	22.84	22.93
HSUPA Subtest-2	21.35	21.39	21.37	21.82	21.56	21.54	21.66	21.57	21.69
HSUPA Subtest-3	21.33	21.37	21.35	21.81	21.54	21.52	21.62	21.55	21.66
HSUPA Subtest-4	20.82	20.88	20.83	21.48	21.08	21.05	21.16	21.08	21.17
HSUPA Subtest-5	22.30	22.32	22.35	23.01	22.89	22.76	22.72	22.69	22.74

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and 10dB attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and 10dB attenuator factor.

Offset = RF cable loss + attenuator factor.

Following table shows an offset computation example with cable loss 4.2 dB.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Compare each band and different modulation combination to show the worst data rate.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.74	32.72	32.70	27.15	27.11	27.10	23.80	23.79	23.77
Conducted Power (Watts)	1.88	1.87	1.86	0.52	0.51	0.51	0.24	0.24	0.24

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.87	29.72	29.66	25.98	25.87	25.85	24.17	24.02	23.82
Conducted Power (Watts)	0.97	0.94	0.92	0.40	0.39	0.38	0.26	0.25	0.24

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	24.03	23.97	24.04
Conducted Power (Watts)	0.25	0.25	0.25

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. For GSM/EGPRS operating modes:
 - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
 - b. Set EUT in maximum power output, and triggered the burst signal.
 - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.05	0.04	0.04	0.04	0.04	0.05	2.36	2.28	2.28

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	2.68	2.68	2.76

3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 1900	Test Mode :	GSM Link
---------------	-----------------	--------------------	-----------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 12.JAN.2013 06:33:10


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 12.JAN.2013 06:32:42



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 12.JAN.2013 06:33:37




Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 12.JAN.2013 07:14:31


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 12.JAN.2013 07:14:04




Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 12.JAN.2013 07:13:39

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 13.JAN.2013 17:15:24

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)


Date: 13.JAN.2013 17:14:09



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)




Date: 13.JAN.2013 17:13:04




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)




Date: 13.JAN.2013 17:48:53

Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)



Date: 13.JAN.2013 17:49:55

Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)



Date: 13.JAN.2013 17:50:43

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-19.59	-48.12	0.00	-1.08	27.45	0.5559
836.40	-19.69	-48.28	0.00	-0.93	27.66	0.5834
848.80	-20.02	-48.35	0.00	-0.76	27.57	0.5715
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-27.87	-47.97	0.00	-1.08	19.02	0.0798
836.40	-27.49	-48.01	0.00	-0.93	19.59	0.0910
848.80	-27.17	-48.05	0.00	-0.76	20.12	0.1028

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.20	-48.12	0.00	-1.08	21.84	0.1528
836.40	-25.40	-48.28	0.00	-0.93	21.95	0.1567
848.80	-25.68	-48.35	0.00	-0.76	21.91	0.1552
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-33.43	-47.97	0.00	-1.08	13.46	0.0222
836.40	-33.37	-48.01	0.00	-0.93	13.71	0.0235
848.80	-33.19	-48.05	0.00	-0.76	14.10	0.0257

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.69	-48.12	0.00	-1.08	19.35	0.0861
836.40	-28.08	-48.28	0.00	-0.93	19.27	0.0845
846.60	-28.40	-48.35	0.00	-0.76	19.19	0.0830
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-35.76	-47.97	0.00	-1.08	11.13	0.0130
836.40	-35.77	-48.01	0.00	-0.93	11.31	0.0135
846.60	-35.79	-48.05	0.00	-0.76	11.50	0.0141

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.70	-51.88	0.00	1.96	27.14	0.5176
1880.00	-27.62	-52.99	0.00	2.00	27.37	0.5458
1909.80	-28.33	-54.28	0.00	1.98	27.93	0.6209
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.25	-52.13	0.00	1.96	28.84	0.7656
1880.00	-27.20	-53.17	0.00	2.00	27.97	0.6266
1909.80	-28.60	-54.13	0.00	1.98	27.51	0.5636

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.67	-51.88	0.00	1.96	23.17	0.2075
1880.00	-31.46	-52.99	0.00	2.00	23.53	0.2254
1909.80	-32.21	-54.28	0.00	1.98	24.05	0.2541
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.18	-52.13	0.00	1.96	24.91	0.3097
1880.00	-31.19	-53.17	0.00	2.00	23.98	0.2500
1909.80	-32.26	-54.13	0.00	1.98	23.85	0.2427

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-30.96	-51.88	0.00	1.96	22.88	0.1941
1880.00	-32.35	-52.99	0.00	2.00	22.64	0.1837
1907.60	-33.22	-54.28	0.00	1.98	23.04	0.2014
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.55	-52.13	0.00	1.96	24.54	0.2844
1880.00	-31.53	-53.17	0.00	2.00	23.64	0.2312
1907.60	-33.15	-54.13	0.00	1.98	22.96	0.1977

WCDMA Band IV (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-32.00	-51.88	0.00	1.96	21.84	0.1528
1732.60	-33.30	-52.99	0.00	2.00	21.69	0.1476
1752.60	-33.42	-54.28	0.00	1.98	22.84	0.1923
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-32.02	-52.13	0.00	1.96	22.07	0.1611
1732.60	-32.90	-53.17	0.00	2.00	22.27	0.1687
1752.60	-32.44	-54.13	0.00	1.98	23.67	0.2328

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

3.4.4 Test Setup



3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (KHz)	246.00	246.00	244.00	242.00	242.00	244.00
26dB BW (KHz)	314.00	318.00	314.00	312.00	314.00	312.00

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (KHz)	246.00	246.00	244.00	246.00	246.00	246.00
26dB BW (KHz)	304.00	304.00	306.00	316.00	304.00	314.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.10	4.10	4.10
26dB BW (MHz)	4.70	4.70	4.68

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880.0	1907.6
99% OBW (MHz)	4.08	4.08	4.10
26dB BW (MHz)	4.68	4.72	4.68


AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.08	4.06	4.08
26dB BW (MHz)	4.66	4.66	4.66

3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GSM Link
---------------	---------	--------------------	----------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 12.JAN.2013 06:12:21

26dB Bandwidth Plot on Channel 128 (824.2 MHz)


Date: 12.JAN.2013 06:08:07


99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 12.JAN.2013 06:13:27

26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 12.JAN.2013 06:07:22

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 12.JAN.2013 06:11:01

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 12.JAN.2013 06:09:25


Band :	GSM 850	Test Mode :	EDGE 8 Link
---------------	----------------	--------------------	--------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 12.JAN.2013 07:27:20

26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 12.JAN.2013 07:25:17

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 12.JAN.2013 07:28:39

26dB Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 12.JAN.2013 07:23:45

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 12.JAN.2013 07:30:00


26dB Bandwidth Plot on Channel 251 (848.8 MHz)


Date: 12.JAN.2013 07:22:45




Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 12.JAN.2013 06:39:54

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 12.JAN.2013 06:37:46

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 12.JAN.2013 06:41:20


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 12.JAN.2013 06:36:45


99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 12.JAN.2013 06:43:07


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 12.JAN.2013 06:35:52


Band :	GSM 1900	Test Mode :	EDGE 8 Link
---------------	-----------------	--------------------	--------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 12.JAN.2013 07:09:42

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)


Date: 12.JAN.2013 07:10:59


99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)


Date: 12.JAN.2013 07:08:37

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 12.JAN.2013 07:11:57

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 12.JAN.2013 07:07:03

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 12.JAN.2013 07:12:57




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
--------	--------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 13.JAN.2013 15:50:46


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)




Date: 13.JAN.2013 15:06:10

99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 13.JAN.2013 15:44:25

26dB Bandwidth Plot on Channel 4182 (836.4 MHz)


Date: 13.JAN.2013 15:07:54


99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 13.JAN.2013 15:43:10


26dB Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 13.JAN.2013 15:08:59

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------


99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)


Date: 13.JAN.2013 17:03:26

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 13.JAN.2013 14:55:55

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 13.JAN.2013 17:07:40

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 13.JAN.2013 14:59:10

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 13.JAN.2013 17:09:02

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)




Date: 13.JAN.2013 15:00:24




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)




Date: 13.JAN.2013 17:42:36

26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)




Date: 13.JAN.2013 14:47:37

99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 13.JAN.2013 17:41:22


26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 13.JAN.2013 14:46:09




99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 13.JAN.2013 17:36:50

26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 13.JAN.2013 14:51:34

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-16.82dBm	Measurement Value :	-17.07dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 12.JAN.2013 06:23:23

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-17.07\text{dBm} + 0.25\text{dB} = -16.82\text{dBm}$


Band :	GSM850	Test Mode :	GSM Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-17.05dBm	Measurement Value :	-17.30dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 12.JAN.2013 06:24:04

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-16.96dBm	Measurement Value :	-17.16dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)


Date: 12.JAN.2013 07:38:06

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE 8 Link
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-15.03dBm	Measurement Value :	-15.23dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 12.JAN.2013 07:37:09

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.09dB	Maximum 26dB Bandwidth :	0.306MHz
Band Edge :	-18.72dBm	Measurement Value :	-18.81dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 12.JAN.2013 06:51:48

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link
Correction Factor :	0.09dB	Maximum 26dB Bandwidth :	0.306MHz
Band Edge :	-18.17dBm	Measurement Value :	-18.26dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 12.JAN.2013 06:50:51

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-20.57dBm	Measurement Value :	-20.80dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 12.JAN.2013 06:54:52

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-19.30dBm	Measurement Value :	-19.53dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 12.JAN.2013 06:56:02

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.700MHz
Band Edge :	-23.89dBm	Measurement Value :	-20.61dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)


Date: 13.JAN.2013 15:20:07

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.700MHz
Band Edge :	-23.30dBm	Measurement Value :	-20.02dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)


Date: 13.JAN.2013 15:22:27

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.720MHz
Band Edge :	-24.36dBm	Measurement Value :	-21.10dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)


Date: 13.JAN.2013 16:31:20

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.720MHz
Band Edge :	-24.65dBm	Measurement Value :	-21.39dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)


Date: 13.JAN.2013 18:44:03

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.32dB	Maximum 26dB Bandwidth :	4.660MHz
Band Edge :	-25.73dBm	Measurement Value :	-22.41dBm

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)


Date: 13.JAN.2013 17:24:38

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.32dB	Maximum 26dB Bandwidth :	4.660MHz
Band Edge :	-26.16dBm	Measurement Value :	-22.84dBm

Higher Band Edge Plot on Channel 1513 (1752.6 MHz)


Date: 13.JAN.2013 17:32:05

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 12.JAN.2013 06:28:11

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 13.JAN.2013 19:15:57

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2013 19:15:06

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.JAN.2013 19:14:19




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 12.JAN.2013 07:19:13

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 13.JAN.2013 19:11:30

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 13.JAN.2013 19:12:28

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.JAN.2013 19:13:08

Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 12.JAN.2013 06:30:32

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 12.JAN.2013 06:31:25

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2013 18:58:44


Conducted Spurious Emission Plot between 7GHz ~ 13.6G



Date: 13.JAN.2013 18:59:47




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.JAN.2013 19:00:24

Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 12.JAN.2013 07:16:04

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 12.JAN.2013 07:16:45

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 13.JAN.2013 18:56:37

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz




Date: 13.JAN.2013 19:02:48


Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz


Date: 13.JAN.2013 19:01:41

Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 13.JAN.2013 18:48:15

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 13.JAN.2013 19:17:16

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 13.JAN.2013 19:18:09

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 13.JAN.2013 19:18:49


Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 13.JAN.2013 18:46:52

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 13.JAN.2013 18:49:23

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2013 18:52:59

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 13.JAN.2013 19:04:19



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.JAN.2013 19:05:38




Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link	Frequency :	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 13.JAN.2013 18:45:50


Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 13.JAN.2013 18:50:03

Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 13.JAN.2013 18:51:59

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 13.JAN.2013 19:07:48

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz


Date: 13.JAN.2013 19:06:56

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13\text{dBm}.$$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.7.6 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-46.66	-13	-33.66	-62.34	-49.63	0.88	6.00	H	Pass
2510	-45.95	-13	-32.95	-68.77	-48.56	1.08	5.84	H	Pass
3345	-57.70	-13	-44.70	-68.30	-62.07	1.14	7.66	H	Pass
4182	-54.57	-13	-41.57	-69.33	-59.84	1.37	8.79	H	Pass
5018	-51.37	-13	-38.37	-69.66	-57.51	1.51	9.80	H	Pass
5854	-51.86	-13	-38.86	-70.08	-58.39	1.62	10.30	H	Pass


Band :	GSM850	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 2D2505
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-47.45	-13	-34.45	-60.31	-50.42	0.88	6.00	V	Pass
2510	-52.74	-13	-39.74	-72.64	-55.35	1.08	5.84	V	Pass
3345	-57.26	-13	-44.26	-69.09	-61.63	1.14	7.66	V	Pass
4182	-55.32	-13	-42.32	-70.54	-60.59	1.37	8.79	V	Pass
5018	-52.62	-13	-39.62	-70.07	-58.76	1.51	9.80	V	Pass
5854	-52.80	-13	-39.80	-70.70	-59.33	1.62	10.30	V	Pass


Band :	GSM850	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-44.53	-13	-31.53	-60.52	-47.50	0.88	6.00	H	Pass
2510	-40.52	-13	-27.52	-64.75	-43.13	1.08	5.84	H	Pass
3345	-58.32	-13	-45.32	-68.92	-62.69	1.14	7.66	H	Pass
4182	-55.82	-13	-42.82	-70.58	-61.09	1.37	8.79	H	Pass
5018	-52.21	-13	-39.21	-70.50	-58.35	1.51	9.80	H	Pass
5854	-52.90	-13	-39.90	-71.12	-59.43	1.62	10.30	H	Pass

Band :	GSM850	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 2D2505

Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.61	-13	-35.61	-61.49	-51.58	0.88	6.00	V	Pass
2510	-34.25	-13	-21.25	-57.11	-36.86	1.08	5.84	V	Pass
3345	-56.94	-13	-43.94	-68.77	-61.31	1.14	7.66	V	Pass
4182	-54.46	-13	-41.46	-69.68	-59.73	1.37	8.79	V	Pass
5018	-52.81	-13	-39.81	-70.26	-58.95	1.51	9.80	V	Pass
5854	-52.39	-13	-39.39	-70.29	-58.92	1.62	10.30	V	Pass

Band :	GSM1900	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-57.85	-13	-44.85	-70.00	-64.59	1.28	8.02	H	Pass
5640	-51.28	-13	-38.28	-69.27	-59.70	1.58	10.00	H	Pass
7520	-49.34	-13	-36.34	-71.28	-59.66	1.78	12.10	H	Pass
9400	-50.57	-13	-37.57	-72.69	-61.35	2.22	13.00	H	Pass
11280	-44.35	-13	-31.35	-72.84	-55.20	2.16	13.01	H	Pass
13160	-41.77	-13	-28.77	-72.35	-52.83	2.64	13.70	H	Pass



Band :	GSM1900	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-53.18	-13	-40.18	-68.21	-59.92	1.28	8.02	V	Pass
5640	-53.31	-13	-40.31	-70.39	-61.73	1.58	10.00	V	Pass
7520	-48.75	-13	-35.75	-71.00	-59.07	1.78	12.10	V	Pass
9400	-47.86	-13	-34.86	-71.48	-58.64	2.22	13.00	V	Pass
11280	-43.27	-13	-30.27	-71.86	-54.12	2.16	13.01	V	Pass
13160	-41.53	-13	-28.53	-72.18	-52.59	2.64	13.70	V	Pass




Band :	GSM1900	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-58.41	-13	-45.41	-70.56	-65.15	1.28	8.02	H	Pass
5640	-51.52	-13	-38.52	-69.51	-59.94	1.58	10.00	H	Pass
7520	-48.12	-13	-35.12	-70.06	-58.44	1.78	12.10	H	Pass
9400	-49.51	-13	-36.51	-71.63	-60.29	2.22	13.00	H	Pass
11280	-43.21	-13	-30.21	-71.70	-54.06	2.16	13.01	H	Pass
13160	-42.16	-13	-29.16	-72.74	-53.22	2.64	13.70	H	Pass

Band :	GSM1900	Temperature :	21~22°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.53	-13	-42.53	-70.56	-62.27	1.28	8.02	V	Pass
5640	-52.36	-13	-39.36	-69.44	-60.78	1.58	10.00	V	Pass
7520	-49.01	-13	-36.01	-71.26	-59.33	1.78	12.10	V	Pass
9400	-47.70	-13	-34.70	-71.32	-58.48	2.22	13.00	V	Pass
11280	-42.30	-13	-29.30	-70.89	-53.15	2.16	13.01	V	Pass
13160	-39.11	-13	-26.11	-69.76	-50.17	2.64	13.70	V	Pass




Band :	WCDMA Band V	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 2D2505
 Plane : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-50.09	-13	-37.09	-64.77	-53.06	0.88	6.00	H	Pass
2510	-53.44	-13	-40.44	-75.00	-56.05	1.08	5.84	H	Pass
3345	-57.90	-13	-44.90	-68.50	-62.27	1.14	7.66	H	Pass
4182	-54.90	-13	-41.90	-69.66	-60.17	1.37	8.79	H	Pass
5018	-52.16	-13	-39.16	-70.45	-58.30	1.51	9.80	H	Pass
5854	-52.18	-13	-39.18	-70.40	-58.71	1.62	10.30	H	Pass

Band :	WCDMA Band V	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D2505
Plane : H


Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-61.17	-13	-48.17	-71.80	-64.14	0.88	6.00	V	Pass
2510	-57.07	-13	-44.07	-76.97	-59.68	1.08	5.84	V	Pass
3345	-57.45	-13	-44.45	-69.28	-61.82	1.14	7.66	V	Pass
4182	-54.85	-13	-41.85	-70.07	-60.12	1.37	8.79	V	Pass
5018	-53.81	-13	-40.81	-71.26	-59.95	1.51	9.80	V	Pass
5854	-53.36	-13	-40.36	-71.26	-59.89	1.62	10.30	V	Pass



FCC RF Test Report

Report No. : FG2D2505


Band :	WCDMA Band II	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-58.45	-13	-45.45	-70.60	-65.19	1.28	8.02	H	Pass
5640	-51.95	-13	-38.95	-69.94	-60.37	1.58	10.00	H	Pass
7520	-48.75	-13	-35.75	-70.69	-59.07	1.78	12.10	H	Pass
9400	-49.50	-13	-36.50	-71.62	-60.28	2.22	13.00	H	Pass
11280	-43.37	-13	-30.37	-71.86	-54.22	2.16	13.01	H	Pass
13160	-41.24	-13	-28.24	-71.82	-52.30	2.64	13.70	H	Pass


Band :	WCDMA Band II	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.48	-13	-43.48	-71.51	-63.22	1.28	8.02	V	Pass
5640	-52.97	-13	-39.97	-70.05	-61.39	1.58	10.00	V	Pass
7520	-49.81	-13	-36.81	-72.06	-60.13	1.78	12.10	V	Pass
9400	-48.35	-13	-35.35	-71.97	-59.13	2.22	13.00	V	Pass
11280	-43.14	-13	-30.14	-71.73	-53.99	2.16	13.01	V	Pass
13160	-41.42	-13	-28.42	-72.07	-52.48	2.64	13.70	V	Pass


Band :	WCDMA Band IV	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465.2	-55.19	-13	-42.19	-66.27	-61.58	1.15	7.54	H	Pass
5197.8	-51.16	-13	-38.16	-70.12	-59.45	1.51	9.80	H	Pass
6930.4	-48.71	-13	-35.71	-72.33	-58.47	1.75	11.51	H	Pass
8663	-45.72	-13	-32.72	-71.98	-56.61	1.97	12.86	H	Pass
10395.6	-42.60	-13	-29.60	-72.54	-53.39	2.11	12.90	H	Pass
12128.2	-39.23	-13	-26.23	-72.91	-50.09	2.24	13.10	H	Pass

Band :	WCDMA Band IV	Temperature :	21~22°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Steven Hao	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 2D2505
Plane : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3465.2	-52.43	-13	-39.43	-65.29	-58.82	1.15	7.54	V	Pass
5197.8	-49.28	-13	-36.28	-68.68	-57.57	1.51	9.80	V	Pass
6930.4	-47.34	-13	-34.34	-70.67	-57.10	1.75	11.51	V	Pass
8663	-46.75	-13	-33.75	-72.65	-57.64	1.97	12.86	V	Pass
10395.6	-32.59	-13	-19.59	-71.33	-43.38	2.11	12.90	V	Pass
12128.2	-39.10	-13	-26.10	-71.44	-49.96	2.24	13.10	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	16	0.02	15	0.02	PASS
-20	15	0.02	16	0.02	
-10	14	0.02	19	0.02	
0	13	0.02	16	0.02	
10	-14	-0.02	15	0.02	
20	15	0.02	14	0.02	
30	-17	-0.02	13	0.02	
40	-15	-0.02	13	0.02	
50	-13	-0.02	14	0.02	
55	16	0.02	16	0.02	

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	17	0.01	17	0.01	PASS
-20	16	0.01	16	0.01	
-10	15	0.01	20	0.01	
0	14	0.01	-19	-0.01	
10	13	0.01	18	0.01	
20	-15	-0.01	-21	-0.01	
30	-16	-0.01	18	0.01	
40	-15	-0.01	17	0.01	
50	-16	-0.01	17	0.01	
55	-17	-0.01	19	0.01	

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	4	0.00	PASS
-20	-5	-0.01	
-10	-4	0.00	
0	-3	0.00	
10	-3	0.00	
20	3	0.00	
30	-5	-0.01	
40	-4	0.00	
50	-3	0.00	
55	-3	0.00	

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-13	-0.01	PASS
-20	-12	-0.01	
-10	-11	-0.01	
0	-11	-0.01	
10	-12	-0.01	
20	-10	-0.01	
30	-14	-0.01	
40	-11	-0.01	
50	-10	-0.01	
55	-11	-0.01	

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

Band :	WCDMA Band IV	Channel :	1413
Limit (ppm) :	2.5	Frequency :	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	10	0.01	PASS
-20	-9	-0.01	
-10	8	0.00	
0	7	0.00	
10	-9	-0.01	
20	-7	0.00	
30	9	0.01	
40	7	0.00	
50	7	0.00	
55	10	0.01	

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.7	12	0.01	2.5	PASS
		BEP	9	0.01		
		4.2	12	0.01		
	EDGE 8	3.7	13	0.02		
		BEP	15	0.02		
		4.2	14	0.02		
GSM 1900 CH661	GSM	3.7	-17	-0.01		
		BEP	13	0.01		
		4.2	14	0.01		
	EDGE 8	3.7	16	0.01		
		BEP	18	0.01		
		4.2	17	0.01		
WCDMA Band V CH4182	RMC 12.2Kbps	3.7	-4	0.00		
		BEP	-3	0.00		
		4.2	-5	-0.01		
WCDMA Band II CH1413	RMC 12.2Kbps	3.7	-12	-0.01		
		BEP	-13	-0.01		
		4.2	-11	-0.01		
WCDMA Band IV CH9400	RMC 12.2Kbps	3.7	9	0.01		
		BEP	-8	0.00		
		4.2	-8	0.00		

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Jan. 12, 2013~ Jan. 29, 2013	Dec. 28, 2013	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 29, 2012	Jan. 12, 2013~ Jan. 29, 2013	Dec. 28, 2013	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 22, 2012	Jan. 12, 2013~ Jan. 29, 2013	Aug. 21, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 29, 2012	Jan. 12, 2013~ Jan. 29, 2013	Dec. 28, 2013	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Jan. 29, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	Jun. 01, 2012	Jan. 29, 2013	May 31, 2013	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Jan. 29, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Jan. 29, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	Jun. 01, 2012	Jan. 29, 2013	May 31, 2013	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Jan. 29, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Jan. 29, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9KHz ~ 30MHz	Jul. 03, 2012	Jan. 29, 2013	Jul. 02, 2014	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Dec. 29, 2012	Jan. 29, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 19, 2012	Jan. 29, 2013	Sep. 18, 2013	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54
-----------------------------------------------------------------------------	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72
--------------------------------------------------------------------------------	------



Appendix A. Photographs of EUT

Please refer to Sporton report number EP2D2505 as below.