

# FCC Test Report

APPLICANT : BLU Products, Inc.  
EQUIPMENT : Mobile phone  
BRAND NAME : BLU  
MODEL NAME : DIVA FLIP  
FCC ID : YHLBLUDIVAFLIP  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification

The product was received on Jan. 12, 2016 and testing was completed on Mar. 03, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



---

Prepared by: James Huang / Manager



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China**



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Product Feature of Equipment Under Test .....	5
1.4. Product Specification of Equipment Under Test .....	5
1.5. Modification of EUT .....	6
1.6. Test Location .....	6
1.7. Applicable Standards .....	6
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>7</b>
2.1. Test Mode .....	7
2.2. Connection Diagram of Test System .....	9
2.3. Support Unit used in test configuration and system.....	10
2.4. EUT Operation Test Setup .....	11
<b>3. TEST RESULT .....</b>	<b>12</b>
3.1. Test of AC Conducted Emission Measurement .....	12
3.2. Test of Radiated Emission Measurement .....	18
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>25</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>26</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC611204	Rev. 01	Initial issue of report	Mar. 17, 2016



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.107	ICES003 Section 6.1	AC Conducted Emission	< 15.107 limits < ICES003 6.1 limits	PASS	Under limit 7.56 dB at 0.170 MHz
3.2	15.109	ICES003 Section 6.2	Radiated Emission	< 15.109 limits < ICES003 6.2 limits	PASS	Under limit 3.37 dB at 600.300 MHz for Quasi-Peak



## 1. General Description

### 1.1. Applicant

BLU Products, Inc.  
10814 NW 33rd St # 100 Doral, FL 33172

### 1.2. Manufacturer

BLU Products, Inc.  
10814 NW 33rd St # 100 Doral, FL 33172

### 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	DIVA FLIP
FCC ID	YHLBLUDIVAFLIP
EUT supports Radios application	GSM/Bluetooth v3.0+EDR
IMEI Code	Conduction: 351771053541752/351771053541760 Radiation: 351771053541711/351771053541729
HW Version	S2415-MB-V1.2
SW Version	BLU_T390_V08_GENERIC_ANATEL_160129_1415
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Antenna Type	WWAN : IFA Antenna Bluetooth : Monopole Antenna
Type of Modulation	GSM: GMSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK

## 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6. Test Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO01-KS	03CH03-KS	306251/4086E

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	☒
2.	Data application transferred mode (EUT with notebook)	☒	☒	☒


**Abbreviations:**

- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz


Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: GSM1900 Idle + Bluetooth Idle + Adapter + Earphone + Camera + SIM1<Fig.1> Mode 2: GSM850 Idle + Bluetooth Idle + Adapter + Earphone + MP3 + SIM2<Fig.1> Mode 3: GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1<Fig.2>
Radiated Emissions < 1GHz	1/2	Mode 1: GSM1900 Idle + Bluetooth Idle + Adapter + Earphone + Camera + SIM1<Fig.1> Mode 2: GSM850 Idle + Bluetooth Idle + Adapter + Earphone + MP3 + SIM2<Fig.1> Mode 3: GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1<Fig.2>
Radiated Emissions ≥ 1GHz	1/2	Mode 1: GSM1900 Idle + Bluetooth Idle + Adapter + Earphone + Camera + SIM1<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1<Fig.2>
<b>Remark:</b> <ol style="list-style-type: none"> <li>The worst case of AC is mode 2; and the USB Link mode of AC is mode 3, only the test data of this mode are reported.</li> <li>The worst case of RE&lt; 1G is mode 1; and the USB Link mode of AC is mode 3, only the test data of this mode are reported.</li> <li>Data Link with notebook means data application transferred mode between EUT and notebook.</li> </ol>		



## 2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
4.	Bluetooth Earphone	Samsung	HS3000	A3LHS3000	N/A	N/A
5.	Earphone	Apple	MC690ZP/A	N/A	Unshielded, 1.6 m	N/A
6.	iPod	Apple	MC525 ZP/A	FCC DoC	Shielded, 1.0 m	N/A
7.	SD Card	SanDisk	4G class 4	FCC DoC	N/A	N/A



## **2.4. EUT Operation Test Setup**

The EUT was in GSM idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Execute "Music Player" to play MP3 file.
3. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test Setup



### 3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	21~23℃
Test Engineer :	Jacky Yang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Idle + Adapter + Earphone + MP3 + SIM2		




Condition: FCC 15B\_QP LISN\_L\_20160112 LINE  
 Project : (FC) 611204  
 Mode : Mode 2  
 IMEI : 351771053541752/351771053541760

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV		dB	dBuV	dB	dB	
1	0.15	42.89	-13.02	55.91	32.10	0.43	10.36	Average
2	0.15	57.29	-8.62	65.91	46.50	0.43	10.36	QP
3	0.17	40.90	-14.26	55.16	30.10	0.46	10.34	Average
4 *	0.17	57.60	-7.56	65.16	46.80	0.46	10.34	QP
5	0.18	37.51	-16.77	54.28	26.71	0.49	10.31	Average
6	0.18	55.61	-8.67	64.28	44.81	0.49	10.31	QP
7	0.20	37.11	-16.38	53.49	26.30	0.52	10.29	Average
8	0.20	55.71	-7.78	63.49	44.90	0.52	10.29	QP
9	0.22	34.50	-18.24	52.74	23.70	0.53	10.27	Average
10	0.22	50.20	-12.54	62.74	39.40	0.53	10.27	QP
11	0.25	30.19	-21.59	51.78	19.40	0.55	10.24	Average
12	0.25	45.99	-15.79	61.78	35.20	0.55	10.24	QP
13	0.28	29.68	-21.17	50.85	18.90	0.56	10.22	Average
14	0.28	44.98	-15.87	60.85	34.20	0.56	10.22	QP
15	0.45	31.06	-15.87	46.93	20.30	0.60	10.16	Average
16	0.45	42.96	-13.97	56.93	32.20	0.60	10.16	QP



Test Mode :	Mode 2	Temperature :	21~23°C
Test Engineer :	Jacky Yang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Idle + Adapter + Earphone + MP3 + SIM2		



Condition: FCC 15B\_QP LISN\_N\_20160112 NEUTRAL

Project : (FC)611204


Mode : Mode 2

IMEI : 351771053541752/351771053541760

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	40.81	-15.10	55.91	30.00	0.45	10.36	Average
2	0.15	53.11	-12.80	65.91	42.30	0.45	10.36	QP
3	0.18	36.61	-18.07	54.68	25.81	0.48	10.32	Average
4	0.18	52.11	-12.57	64.68	41.31	0.48	10.32	QP
5	0.20	36.80	-16.96	53.76	25.99	0.51	10.30	Average
6 *	0.20	55.60	-8.16	63.76	44.79	0.51	10.30	QP
7	0.22	32.80	-19.86	52.66	22.00	0.53	10.27	Average
8	0.22	50.10	-12.56	62.66	39.30	0.53	10.27	QP
9	0.28	28.79	-22.11	50.90	17.99	0.58	10.22	Average
10	0.28	44.89	-16.01	60.90	34.09	0.58	10.22	QP
11	0.44	33.54	-13.44	46.98	22.80	0.58	10.16	Average
12	0.44	46.14	-10.84	56.98	35.40	0.58	10.16	QP



Test Mode :	Mode 3	Temperature :	21~23℃
Test Engineer :	Jacky Yang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1		




Condition: FCC 15B\_QP LISN\_L\_20150304 LINE  
Project : (FC)611204  
Mode : Mode 3  
IMEI : 351771053541752/351771053541760

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV		dB	dBuV	dB	dB	
1	0.24	22.30	-29.92	52.22	11.51	0.54	10.25	Average
2	0.24	37.20	-25.02	62.22	26.41	0.54	10.25	QP
3	0.26	23.98	-27.36	51.34	13.20	0.55	10.23	Average
4	0.26	38.08	-23.26	61.34	27.30	0.55	10.23	QP
5	0.37	21.63	-26.93	48.56	10.90	0.55	10.18	Average
6	0.37	35.53	-23.03	58.56	24.80	0.55	10.18	QP
7	0.45	22.47	-24.33	46.80	11.70	0.61	10.16	Average
8	0.45	35.97	-20.83	56.80	25.20	0.61	10.16	QP
9	0.59	23.46	-22.54	46.00	12.70	0.61	10.15	Average
10 *	0.59	35.66	-20.34	56.00	24.90	0.61	10.15	QP
11	0.70	20.79	-25.21	46.00	10.10	0.54	10.15	Average
12	0.70	34.29	-21.71	56.00	23.60	0.54	10.15	QP





Test Mode :	Mode 3	Temperature :	21~23°C
Test Engineer :	Jacky Yang	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1		



Condition: FCC 15B\_QP LISN\_N\_20150304 NEUTRAL  
Project : (FC)611204  
Mode : Mode 3  
IMEI : 351771053541752/351771053541760

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.23	23.10	-29.38	52.48	12.30	0.54	10.26	Average
2	0.23	42.00	-20.48	62.48	31.20	0.54	10.26	QP
3	0.26	25.40	-25.89	51.29	14.60	0.57	10.23	Average
4	0.26	44.30	-16.99	61.29	33.50	0.57	10.23	QP
5	0.35	23.96	-25.09	49.05	13.20	0.57	10.19	Average
6	0.35	37.26	-21.79	59.05	26.50	0.57	10.19	QP
7	0.40	25.42	-22.35	47.77	14.70	0.55	10.17	Average
8	0.40	37.92	-19.85	57.77	27.20	0.55	10.17	QP
9	0.58	23.94	-22.06	46.00	13.21	0.58	10.15	Average
10 *	0.58	40.44	-15.56	56.00	29.71	0.58	10.15	QP
11	0.66	25.81	-20.19	46.00	15.10	0.56	10.15	Average
12	0.66	38.31	-17.69	56.00	27.60	0.56	10.15	QP

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





## 3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Jeff Yao	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	GSM1900 Idle + Bluetooth Idle + Adapter + Earphone + Camera + SIM1		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-KS  
 Condition : FCC CLASS-B 3m LF\_ANT(23188)\_151017 HORIZONTAL  
 Project : (FC) 611204  
 Mode : Mode 1  
 IMEI : 351771053541711/351771053541729  
 Plane : Y

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	143.94	30.87	-12.63	43.50	41.64	13.58	1.20	25.55	---	Peak
2	167.97	30.69	-12.81	43.50	42.98	11.93	1.20	25.42	---	Peak
3	288.12	31.83	-14.17	46.00	41.62	13.70	1.57	25.06	---	Peak
4	384.00	36.59	-9.41	46.00	45.05	15.20	2.03	25.69	---	Peak
5	456.10	37.91	-8.09	46.00	44.27	17.63	2.12	26.11	100	0 Peak
6	503.70	37.80	-8.20	46.00	42.56	19.41	2.17	26.34	---	Peak
7	1960.00	49.03			71.34	31.74	4.59	58.64	---	Peak
8	2138.00	40.78	-33.22	74.00	62.32	32.34	4.80	58.68	---	Peak
9	4708.00	42.78	-31.22	74.00	60.35	34.32	7.36	59.25	---	Peak
10	6926.00	39.97	-34.03	74.00	52.22	36.13	9.26	57.64	---	Peak
11	7828.00	42.60	-31.40	74.00	54.00	36.43	10.71	58.54	---	Peak
12	10392.00	43.76	-30.24	74.00	52.13	38.41	12.23	59.01	100	0 Peak
13	11262.00	43.52	-30.48	74.00	51.60	39.01	12.58	59.67	---	Peak



Test Mode :	Mode 1	Temperature :	23~25°C
Test Engineer :	Jeff Yao	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Vertical
Function Type :	GSM1900 Idle + Bluetooth Idle + Adapter + Earphone + Camera + SIM1		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-KS  
 Condition : FCC CLASS-B 3m LF\_ANT(23188)\_151017 VERTICAL  
 Project : (FC) 611204  
 Mode : Mode 1  
 IMEI : 351771053541711/351771053541729  
 Plane : Y

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.27	32.25	-7.75	40.00	31.97	25.60	0.75	26.07	---	---	Peak
2	143.94	32.23	-11.27	43.50	43.00	13.58	1.20	25.55	---	---	Peak
3	192.00	31.93	-11.57	43.50	44.16	11.56	1.50	25.29	---	---	Peak
4	600.30	42.63	-3.37	46.00	46.85	19.70	2.52	26.44	145	80	QP
5	647.90	41.46	-4.54	46.00	45.32	19.99	2.56	26.41	100	20	QP
6	696.20	41.20	-4.80	46.00	44.64	20.28	2.65	26.37	147	80	QP
7	1960.00	48.97	---	---	71.28	31.74	4.59	58.64	---	---	Peak
8	2186.00	41.28	-32.72	74.00	62.71	32.39	4.85	58.67	---	---	Peak
9	4982.00	43.43	-30.57	74.00	59.53	34.49	7.59	58.18	---	---	Peak
10	5084.00	40.45	-33.55	74.00	55.82	34.60	7.66	57.63	---	---	Peak
11	8538.00	43.17	-30.83	74.00	53.31	36.24	11.04	57.42	---	---	Peak
12	10338.00	43.20	-30.80	74.00	51.61	38.37	12.21	58.99	---	---	Peak
13	11726.00	43.46	-30.54	74.00	51.50	39.33	12.61	59.98	100	0	Peak



Test Mode :	Mode 3	Temperature :	23~25°C
Test Engineer :	Jeff Yao	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-KS  
Condition : FCC CLASS-B 3m LF\_ANT(23188)\_151017 HORIZONTAL  
Project : (FC) 611204  
Mode : Mode 3  
IMEI : 351771053541711/351771053541729  
Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	43.50	28.42	-11.58	40.00	39.83	13.83	0.75	25.99	---	---	Peak
2	192.00	36.70	-6.80	43.50	48.93	11.56	1.50	25.29	100	0	Peak
3	227.91	38.96	-7.04	46.00	50.56	12.05	1.54	25.19	---	---	Peak
4	300.00	32.25	-13.75	46.00	41.48	14.10	1.71	25.04	---	---	Peak
5	498.10	32.16	-13.84	46.00	37.00	19.32	2.17	26.33	---	---	Peak
6	696.90	30.59	-15.41	46.00	34.03	20.28	2.65	26.37	---	---	Peak
7	1960.00	49.03			71.34	31.74	4.59	58.64	---	---	Peak
8	2614.00	41.26	-32.74	74.00	61.98	32.79	5.36	58.87	---	---	Peak
9	4708.00	44.78	-29.22	74.00	62.35	34.32	7.36	59.25	100	0	Peak
10	6926.00	42.97	-31.03	74.00	55.22	36.13	9.26	57.64	---	---	Peak
11	7828.00	43.60	-30.40	74.00	55.00	36.43	10.71	58.54	---	---	Peak
12	10392.00	44.76	-29.24	74.00	53.13	38.41	12.23	59.01	---	---	Peak
13	11262.00	44.52	-29.48	74.00	52.60	39.01	12.58	59.67	---	---	Peak



Test Mode :	Mode 3	Temperature :	23~25°C
Test Engineer :	Jeff Yao	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Vertical
Function Type :	GSM1900 Idle + Bluetooth Idle + USB Cable (Data Link with Notebook) + Earphone + SD Card + SIM1		
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH03-KS  
 Condition : FCC CLASS-B 3m LF\_ANT(23188)\_151017 VERTICAL  
 Project : (FC) 611204  
 Mode : Mode 3  
 IMEI : 351771053541711/351771053541729  
 Plane : Y

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	43.23	27.86	-12.14	40.00	39.27	13.83	0.75	25.99	---	Peak
2	167.97	35.75	-7.75	43.50	48.04	11.93	1.20	25.42	100	0 Peak
3	264.09	31.71	-14.29	46.00	42.39	12.87	1.57	25.12	---	Peak
4	499.50	32.52	-13.48	46.00	37.32	19.36	2.17	26.33	---	Peak
5	699.70	31.15	-14.85	46.00	34.58	20.29	2.65	26.37	---	Peak
6	796.30	30.75	-15.25	46.00	31.64	22.41	2.88	26.18	---	Peak
7	1960.00	49.97			72.28	31.74	4.59	58.64	---	Peak
8	2474.00	41.02	-32.98	74.00	61.95	32.68	5.16	58.77	---	Peak
9	4982.00	44.43	-29.57	74.00	60.53	34.49	7.59	58.18	---	Peak
10	5084.00	44.45	-29.55	74.00	59.82	34.60	7.66	57.63	---	Peak
11	8538.00	44.17	-29.83	74.00	54.31	36.24	11.04	57.42	---	Peak
12	10338.00	45.20	-28.80	74.00	53.61	38.37	12.21	58.99	100	0 Peak
13	11726.00	44.46	-29.54	74.00	52.50	39.33	12.61	59.98	---	Peak





## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2015	Jan. 13, 2016~ Mar. 03, 2016	May 03, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Jan. 13, 2016~ Mar. 03, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Jan. 13, 2016~ Mar. 03, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Jan. 13, 2016~ Mar. 03, 2016	Oct. 23, 2016	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Sep. 10, 2015	Mar. 01, 2016	Sep. 09, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Jun. 05, 2015	Mar. 01, 2016	Jun. 04, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25MHz~2GHz	Jan. 16, 2016	Mar. 01, 2016	Jan. 15, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Mar. 01, 2016	Jun. 24, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz~3000 MHz	Aug.10, 2015	Mar. 01, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Mar. 01, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 01, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 01, 2016	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 01, 2016	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.3dB
--	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	4.5dB
--	-------