



# FCC RF Test Report

**APPLICANT** : BLU Products, Inc.  
**EQUIPMENT** : Mobile phone  
**BRAND NAME** : BLU  
**MODEL NAME** : LIFE ONE X3  
**FCC ID** : YHLBLULIFEONEX3  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DSS) Spread Spectrum Transmitter

The product was received on Sep. 04, 2017 and testing was completed on Sep. 07, 2017. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



---

Approved by: Eric Shih / Manager

***Sporton International (Shenzhen) Inc.***

***1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City  
Guangdong Province 518055 China***



## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Applicant .....	5
1.2	Manufacturer .....	5
1.3	Product Feature of Equipment Under Test .....	5
1.4	Product Specification of Equipment Under Test .....	6
1.5	Modification of EUT .....	6
1.6	Testing Location .....	6
1.7	Applicable Standards .....	7
<b>2</b>	<b>TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1	Descriptions of Test Mode .....	8
2.2	Test Mode .....	9
2.3	Connection Diagram of Test System .....	10
2.4	Support Unit used in test configuration and system .....	11
2.5	EUT Operation Test Setup .....	11
2.6	Measurement Results Explanation Example .....	12
<b>3</b>	<b>TEST RESULT .....</b>	<b>13</b>
3.1	Number of Channel Measurement .....	13
3.2	Hopping Channel Separation Measurement .....	15
3.3	Dwell Time Measurement .....	22
3.4	20dB Bandwidth Measurement .....	25
3.5	Peak Output Power Measurement .....	32
3.6	Conducted Band Edges Measurement .....	34
3.7	Conducted Spurious Emission Measurement .....	41
3.8	Radiated Band Edges and Spurious Emission Measurement .....	51
3.9	AC Conducted Emission Measurement .....	57
3.10	Antenna Requirements .....	61
<b>4</b>	<b>LIST OF MEASURING EQUIPMENT .....</b>	<b>62</b>
<b>5</b>	<b>UNCERTAINTY OF EVALUATION .....</b>	<b>63</b>
<b>APPENDIX A. RADIATED SPURIOUS EMISSION</b>		
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>		



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR790406A	Rev. 01	Initial issue of report	Sep. 30, 2017

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.83 dB at 30.970 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.22 dB at 2.100 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**BLU Products, Inc.**

10814 NW 33rd St # 100 Doral, FL 33172

## 1.2 Manufacturer

**BLU Products, Inc.**

10814 NW 33rd St # 100 Doral, FL 33172

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	BLU
Model Name	LIFE ONE X3
FCC ID	YHLBLULIFEONEX3
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+/LTE WLAN2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0+EDR/ Bluetooth v4.0LE
IMEI Code	Conducted: 351372098270638/351372098270646 Conduction: 351372098270497/351372098270505 Radiation: 351372098270596/351372098270604
HW Version	V1.0
SW Version	BLU_LifeOneX3_V7.0.01.00_GENERIC_30-08-2017_21:20
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	79
<b>Carrier Frequency of Each Channel</b>	2402+n*1 MHz; n=0~78
<b>Maximum Output Power to Antenna</b>	Bluetooth BR(1Mbps) : 7.08 dBm (0.0051 W) Bluetooth EDR (2Mbps) : 6.35 dBm (0.0043 W) Bluetooth EDR (3Mbps) : 6.60 dBm (0.0046 W)
<b>Antenna Type / Gain</b>	PIFA Antenna with gain -0.35 dBi
<b>Type of Modulation</b>	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi$ /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019

<b>Test Site</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CO01-SZ	251365

<b>Test Site</b>	Sporton International (Shenzhen) Inc.		
<b>Test Site Location</b>	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Test Firm Registration No.</b>
	03CH01-SZ		577730

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	5.72 dBm	4.88 dBm	5.21 dBm
Ch39	2441MHz	<b>7.08 dBm</b>	6.35 dBm	6.60 dBm
Ch78	2480MHz	6.43 dBm	5.69 dBm	5.95 dBm

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
  2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Z plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.




## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi$ /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + SIM 1		
Remark:  For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.			

## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8m
3.	WLAN AP	Linksys	WRT310W	FCC DoC	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	E450	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	SAMSUNG	E0-MG900	FCC DoC	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24 ~ 26°C
<b>Test Engineer :</b>	Sam Zheng	<b>Relative Humidity :</b>	50 ~ 53%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 5.SEP.2017 12:44:11



Date: 5.SEP.2017 12:50:20

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24 ~ 26℃
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6240	Pass
39	2441	1.008	0.6267	Pass
78	2480	1.002	0.5680	Pass

**Channel Separation Plot on Channel 00 - 01**




Date: 5.SEP.2017 12:14:51






### Channel Separation Plot on Channel 39 - 40



Date: 5.SEP.2017 12:15:31

### Channel Separation Plot on Channel 77 - 78




Date: 5.SEP.2017 15:24:57



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8440	Pass
39	2441	1.008	0.8480	Pass
78	2480	1.002	0.8280	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 5.SEP.2017 12:16:48




### Channel Separation Plot on Channel 39 - 40



Date: 5.SEP.2017 15:28:40

### Channel Separation Plot on Channel 77 - 78




Date: 5.SEP.2017 15:51:55



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8360	Pass
39	2441	1.002	0.8320	Pass
78	2480	1.002	0.8360	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 5.SEP.2017 12:19:17




### Channel Separation Plot on Channel 39 - 40



Date: 5.SEP.2017 12:20:01

### Channel Separation Plot on Channel 77 - 78



Date: 5.SEP.2017 12:20:41

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



### 3.3.5 Test Result of Dwell Time

<b>Test Mode :</b>	3DH5	<b>Temperature :</b>	24 ~ 26℃
<b>Test Engineer :</b>	Sam Zheng	<b>Relative Humidity :</b>	50 ~ 53%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.8841	0.31	0.4	Pass
AFH	20	53.33	2.8841	0.15	0.4	Pass

**Remark:** 0.15

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot





### 3.4 20dB Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Measure and record the results in the test report.

#### 3.4.4 Test Setup




### 3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24 ~ 26℃
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.936
39	2441	0.940
78	2480	0.852


**20 dB Bandwidth Plot on Channel 00**



Date: 5.SEP.2017 12:23:19




### 20 dB Bandwidth Plot on Channel 39



Date: 5.SEP.2017 12:24:26

### 20 dB Bandwidth Plot on Channel 78




Date: 5.SEP.2017 15:17:21



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.272
78	2480	1.242

**20 dB Bandwidth Plot on Channel 00**

Date: 5.SEP.2017 12:25:27




### 20 dB Bandwidth Plot on Channel 39



Date: 5.SEP.2017 12:25:58

### 20 dB Bandwidth Plot on Channel 78




Date: 5.SEP.2017 12:26:46



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.254
39	2441	1.248
78	2480	1.254

**20 dB Bandwidth Plot on Channel 00**

Date: 5.SEP.2017 12:27:20




### 20 dB Bandwidth Plot on Channel 39



Date: 5.SEP.2017 12:28:45

### 20 dB Bandwidth Plot on Channel 78



Date: 5.SEP.2017 12:29:50

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

#### 3.5.4 Test Setup





### 3.5.5 Test Result of Peak Output Power

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	24 ~ 26℃
<b>Test Engineer :</b>	Sam Zheng	<b>Relative Humidity :</b>	50 ~ 53%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	5.72	20.97	Pass
39	2441	7.08	20.97	Pass
78	2480	6.43	20.97	Pass

<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	24 ~ 26℃
<b>Test Engineer :</b>	Sam Zheng	<b>Relative Humidity :</b>	50 ~ 53%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	4.88	20.97	Pass
39	2441	6.35	20.97	Pass
78	2480	5.69	20.97	Pass

<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24 ~ 26℃
<b>Test Engineer :</b>	Sam Zheng	<b>Relative Humidity :</b>	50 ~ 53%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	5.21	20.97	Pass
39	2441	6.60	20.97	Pass
78	2480	5.95	20.97	Pass

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






## 3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	00 and 78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

Low Band Edge Plot on Channel 00



Date: 5.SEP.2017 12:50:43


High Band Edge Plot on Channel 78




Date: 5.SEP.2017 13:00:09



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	00 and 78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**Low Band Edge Plot on Channel 00**


Date: 5.SEP.2017 13:03:23

**High Band Edge Plot on Channel 78**

Date: 5.SEP.2017 14:49:13


<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	24 ~ 26℃
<b>Test Channel :</b>	00 and 78	<b>Relative Humidity :</b>	50 ~ 53%
		<b>Test Engineer :</b>	Sam Zheng

### Low Band Edge Plot on Channel 00



Date: 5.SEP.2017 14:56:57


### High Band Edge Plot on Channel 78




Date: 5.SEP.2017 15:10:30

### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%

**1Mbps Hopping Mode Low Band Edge Plot**



Date: 5.SEP.2017 12:56:55

**1Mbps Hopping Mode High Band Edge Plot**



Date: 5.SEP.2017 13:02:59



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%

**2Mbps Hopping Mode Low Band Edge Plot**


Date: 5.SEP.2017 14:42:47

**2Mbps Hopping Mode High Band Edge Plot**


Date: 5.SEP.2017 14:56:34



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Engineer :	Sam Zheng	Relative Humidity :	50 ~ 53%

**3Mbps Hopping Mode Low Band Edge Plot**

Date: 5.SEP.2017 15:06:05

**3Mbps Hopping Mode High Band Edge Plot**

Date: 5.SEP.2017 15:16:10



## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure


1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup




**3.7.5 Test Result of Conducted Spurious Emission**

Test Mode :	1Mbps	Temperature :	24 ~ 26℃
Test Channel :	00	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 12:57:19

**1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 12:57:40



Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	39	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 12:58:09

**1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 12:58:31



Test Mode :	1Mbps	Temperature :	24 ~ 26°C
Test Channel :	78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 12:59:16

**1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 12:59:38



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	00	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 15:40:34

**2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 15:40:55



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	39	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 15:37:18

**2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 15:37:40



Test Mode :	2Mbps	Temperature :	24 ~ 26°C
Test Channel :	78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 15:35:39

**2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 15:36:01



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	00	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**

Date: 5.SEP.2017 15:44:42


**3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**

Date: 5.SEP.2017 15:45:03






Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	39	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 5.SEP.2017 15:08:08

**3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 5.SEP.2017 15:08:29



Test Mode :	3Mbps	Temperature :	24 ~ 26°C
Test Channel :	78	Relative Humidity :	50 ~ 53%
		Test Engineer :	Sam Zheng

**3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

Date: 5.SEP.2017 15:45:31

**3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**

Date: 5.SEP.2017 15:45:52

### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.82dB) derived from  $20\log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

### 3.8.6 Duty cycle correction factor for average measurement

#### DH5 on time (One Pulse) Plot on Channel 39



#### DH5 on time (Count Pulses) Plot on Channel 39



#### Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.87 / 100 = 5.74 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.82 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.87 \text{ ms} \times 20 \text{ channels} = 57.4 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.4\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.87 \text{ ms} \times 2 = 5.74 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.74 \text{ ms}/100\text{ms}) = -24.82 \text{ dB}$$

**3.8.7 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix A.

**3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix A.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.9.4 Test Setup





## 3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24 ~25°C
Test Engineer :	Peng Wang	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + SIM 1		




Site : CO01-SZ  
Condition: FCC 15C\_QP LISN\_20170301\_L LINE

Mode : Mode 1  
IMEI : 351372098270497/351372098270505

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	1.36	30.14	-15.86	46.00	19.90	0.09	10.15	Average
2	1.36	40.84	-15.16	56.00	30.60	0.09	10.15	QP
3	1.58	30.35	-15.65	46.00	20.09	0.10	10.16	Average
4	1.58	41.65	-14.35	56.00	31.39	0.10	10.16	QP
5	1.91	31.37	-14.63	46.00	21.10	0.11	10.16	Average
6	1.91	42.97	-13.03	56.00	32.70	0.11	10.16	QP
7	2.10	31.68	-14.32	46.00	21.39	0.12	10.17	Average
8 *	2.10	43.78	-12.22	56.00	33.49	0.12	10.17	QP
9	2.57	28.74	-17.26	46.00	18.41	0.14	10.19	Average
10	2.57	40.63	-15.37	56.00	30.30	0.14	10.19	QP
11	3.55	30.00	-16.00	46.00	19.60	0.17	10.23	Average
12	3.55	40.70	-15.30	56.00	30.30	0.17	10.23	QP
13	13.34	36.09	-13.91	50.00	25.29	0.47	10.33	Average
14	13.34	46.39	-13.61	60.00	35.59	0.47	10.33	QP
15	14.99	35.02	-14.98	50.00	24.20	0.51	10.31	Average
16	14.99	45.62	-14.38	60.00	34.80	0.51	10.31	QP



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	24 ~25℃
<b>Test Engineer :</b>	Peng Wang	<b>Relative Humidity :</b>	50~55%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + SIM 1		



Site : CO01-SZ  
Condition: FCC 15C\_QP LISN\_20170301\_N NEUTRAL

Mode : Mode 1  
IMEI : 351372098270497/351372098270505

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.89	24.30	-21.70	46.00	14.11	0.04	10.15	Average
2	0.89	33.20	-22.80	56.00	23.01	0.04	10.15	QP
3	1.18	23.10	-22.90	46.00	12.90	0.05	10.15	Average
4	1.18	33.50	-22.50	56.00	23.30	0.05	10.15	QP
5	1.65	24.61	-21.39	46.00	14.40	0.05	10.16	Average
6	1.65	34.91	-21.09	56.00	24.70	0.05	10.16	QP
7	2.50	23.03	-22.97	46.00	12.80	0.04	10.19	Average
8	2.50	33.63	-22.37	56.00	23.40	0.04	10.19	QP
9	13.48	31.01	-18.99	50.00	20.40	0.28	10.33	Average
10	13.48	43.21	-16.79	60.00	32.60	0.28	10.33	QP
11	15.23	30.17	-19.83	50.00	19.50	0.34	10.33	Average
12 *	15.23	43.27	-16.73	60.00	32.60	0.34	10.33	QP



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 06, 2017	Sep. 05, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20, 2017	Sep. 05, 2017	Apr. 19, 2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	Sep. 05, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	Sep. 05, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	Sep. 07, 2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	Sep. 07, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	Sep. 07, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 19, 2017	Sep. 07, 2017	Jul. 18, 2018	Conduction (CO01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 20, 2017	Sep. 07, 2017	Apr. 19, 2018	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Sep. 07, 2017	May 13, 2018	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Apr. 25, 2017	Sep. 07, 2017	Apr. 24, 2018	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 12, 2017	Sep. 07, 2017	Jan. 11, 2018	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Jun. 16, 2017	Sep. 07, 2017	Jun. 15, 2018	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 20, 2017	Sep. 07, 2017	Apr. 19, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1707137	1GHz~18GHz	Oct. 11, 2016	Sep. 07, 2017	Oct. 10, 2017	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5GHz	Oct. 11, 2016	Sep. 07, 2017	Oct. 10, 2017	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Sep. 07, 2017	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Sep. 07, 2017	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Sep. 07, 2017	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.5dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
---	-------

### Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2dB
---	-------

### Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
---	-------



## Appendix A. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
BT CH00 2402MHz		2389.905	40.78	-33.22	74	39.95	27.23	6.81	33.21	104	326	P	H
		2389.905	15.96	-38.04	54	-	-	-	-	104	326	A	H
	*	2402	95.16	-	-	94.33	27.23	6.81	33.21	104	326	P	H
	*	2402	70.34	-	-	-	-	-	-	104	326	A	H
		2379.3	41	-33	74	40.31	27.19	6.73	33.23	268	256	P	V
		2379.3	16.18	-37.82	54	-	-	-	-	268	256	A	V
	*	2402	97.43	-	-	96.6	27.23	6.81	33.21	268	256	P	V
	*	2402	72.61	-	-	-	-	-	-	268	256	A	V
BT CH 39 2441MHz		2378.04	40.91	-33.09	74	40.22	27.19	6.73	33.23	116	323	P	H
		2378.04	16.09	-37.91	54	-	-	-	-	116	323	A	H
	*	2441	95.9	-	-	94.82	27.37	6.86	33.15	116	323	P	H
	*	2441	71.08	-	-	-	-	-	-	116	323	A	H
		2489.29	40.76	-33.24	74	39.45	27.5	6.91	33.1	116	323	P	H
		2489.29	15.94	-38.06	54	-	-	-	-	116	323	A	H
		2342.48	40.43	-33.57	74	39.94	27.1	6.65	33.26	137	246	P	V
		2342.48	15.61	-38.39	54	-	-	-	-	137	246	A	V
	*	2441	98.17	-	-	97.09	27.37	6.86	33.15	137	246	P	V
	*	2441	73.35	-	-	-	-	-	-	137	246	A	V
		2498.25	40.98	-33.02	74	39.67	27.5	6.91	33.1	137	246	P	V
		2498.25	16.16	-37.84	54	-	-	-	-	137	246	A	V





<b>BT CH 78 2480MHz</b>	*	2480	94.9	-	-	93.65	27.46	6.91	33.12	100	320	P	H
	*	2480	70.08	-	-	-	-	-	-	100	320	A	H
		2484.44	40.77	-33.23	74	39.52	27.46	6.91	33.12	100	320	P	H
		2484.44	15.95	-38.05	54	-	-	-	-	100	320	A	H
	*	2480	97.23	-	-	95.98	27.46	6.91	33.12	284	256	P	V
	*	2480	72.41	-	-	-	-	-	-	284	256	A	V
		2485	41.56	-32.44	74	40.31	27.46	6.91	33.12	284	256	P	V
		2485	16.74	-37.26	54	-	-	-	-	284	256	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 15C 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH 00 2402MHz		4804	49.56	-24.44	74	62.02	33.29	10.89	56.64	151	219	P	H
		4804	24.77	-29.23	54	-	-	-	-	151	219	A	H
		4804	48.24	-25.76	74	60.7	33.29	10.89	56.64	151	219	P	V
		4804	23.45	-30.55	54	-	-	-	-	151	219	A	V
BT CH 39 2441MHz		4882	47.65	-26.35	74	60.28	33.33	10.95	56.91	150	258	P	H
		4882	22.86	-31.14	54	-	-	-	-	150	258	A	H
		7323	48.35	-25.65	74	57.54	35.38	13.29	57.86	152	309	P	H
		7323	23.56	-30.44	54	-	-	-	-	152	309	A	H
		4882	46.53	-27.47	74	59.16	33.33	10.95	56.91	150	258	P	V
		4882	21.74	-32.26	54	-	-	-	-	150	258	A	V
		7323	48.12	-25.88	74	57.31	35.38	13.29	57.86	152	309	P	V
		7323	23.33	-30.67	54	-	-	-	-	152	309	A	V
BT CH 78 2480MHz		4960	44.64	-29.36	74	58	31.87	11.02	56.25	118	289	P	H
		4960	19.82	-34.18	54	-	-	-	-	118	289	A	H
		7440	48.61	-25.39	74	57.42	35.91	13.06	57.78	158	273	P	H
		7440	23.79	-30.21	54	-	-	-	-	158	273	A	H
		4960	45.34	-28.66	74	58.7	31.87	11.02	56.25	118	289	P	V
		4960	20.52	-33.48	54	-	-	-	-	118	289	A	V
		7440	48.67	-25.33	74	57.48	35.91	13.06	57.78	158	273	P	V
		7440	23.85	-30.15	54	-	-	-	-	158	273	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 15C Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz BT CH 00 _LF		30.97	26.34	-13.66	40	31.49	26.3	0.25	31.7	-	-	P	H
		96.93	27.59	-15.91	43.5	39.86	18.52	0.81	31.6	-	-	P	H
		252.13	21.78	-24.22	46	33.48	17.54	1.87	31.11	-	-	P	H
		443.22	27.74	-18.26	46	32.07	24.42	2.55	31.3	-	-	P	H
		692.51	30.29	-15.71	46	31.92	26.62	3.25	31.5	-	-	P	H
		953.44	33.43	-12.57	46	31.24	29.73	3.96	31.5	100	150	P	H
		30.97	30.17	-9.83	40	35.32	26.3	0.25	31.7	100	255	P	V
		93.05	24.86	-18.64	43.5	37.84	17.84	0.78	31.6	-	-	P	V
		192.96	26.11	-17.39	43.5	39.39	16.37	1.57	31.22	-	-	P	V
		458.74	26.7	-19.3	46	31.17	24.26	2.59	31.32	-	-	P	V
		638.19	33.22	-12.78	46	36.14	25.46	3.12	31.5	-	-	P	V
		938.89	33.4	-12.6	46	31.57	29.42	3.91	31.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.