

Dates of Tests: Dec 27~31, 2010  
Test Report S/N: LR500111012M  
Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.

**YI7IHD2E100T0W**

APPLICANT

**eZEX Corporation**

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	Color In-home Display
Manufacturer	:	eZEX Corporation
Brand name	:	General Electric (GE)
Model name	:	IHD2E100T0WW
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C-63.4-2003
Frequency Range	:	2405MHz ~ 2480MHz
Max. Output Power	:	Max 20.04dBm – Conducted
Data of issue	:	January 5, 2011

This test report is issued under the authority of:

The test was supervised by:



Kyung-Taek LEE, Technical Manager

Hyun-Chae You, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION'S	3
2. INFORMATION'S ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 TECHNICAL CHARACTERISTICS TEST	6
3.2.1 6dB BANDWIDTH	6
3.2.2 PEAK OUTPUT POWER	9
3.2.3 POWER SPECTRAL DENSITY	12
3.2.4 BAND – EDGE & SPURIOUS	15
3.2.5 FIELD STRENGTH OF HARMONICS	21
3.2.6 AC CONDUCTED EMISSIONS	25
 <b>APPENDIX</b>	
APPENDIX TEST EQUIPMENT USED FOR TESTS	30

## 1. General information's

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2011-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-09-01	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2012-05-14	IC filing

## 2. Information's about test item

### 2-1 Applicant & Manufacturer

Company name : eZEX Corporation  
 Address : Rm 508, Ssangyong IT Twin-tower 2, 442-5, Sangdaewon-dong, Jungwon-gu,  
 Seongnam-si, Gyeonggi-do, South Korea  
 Tel / Fax : TEL No : +82-31 - 608 - 4700 / FAX No : +82-31-608 - 4701

### 2-2 Equipment Under Test (EUT)

Trade name : Color In-home Display  
 FCC ID : YI7IHD2E100T0W  
 Brand name : General Electric (GE)  
 Model name : IHD2E100T0WW  
 Serial number : Identical prototype  
 Date of receipt : December 24, 2010  
 EUT condition : Pre-production, not damaged  
 Antenna type : Chip antenna with Max. 4.37dBi gain  
 Frequency Range : 2405MHz ~ 2480MHz (DSSS)  
 RF output power : Max 20.04dBm - Conducted  
 Number of channels : 16  
 Type of Modulation : O-QPSK  
 Channel spacing : 5MHz  
 Power Source : 5Vdc by adapter  
 Power Source for Adapter : DC 5V, 0.7A (M/N : GELVPS-1)

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2405	2445	2480

### 2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
PC	HP Compaq dx7400 Microtower	CNG8330J9R	HP
MONITOR	HPL1710	CNC816QH92	HP
KEYBOARD	SK-8115	68A-04Q6	DELL
MOUSE	MO56UOA	LNB33130022	DELL
PRINTER	STYLUS C65	FXSY002205	EPSON

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8dBm @ 3kHz		C
15.247(d)	Band Edge & Spurious	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

#### → Antenna Requirement

This unit complies with the requirement of §15.203.

The antenna is connected to inside of EUT. And type is Chip antenna.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

## 3.2 Technical Characteristics Test

### 3.2.1 6 dB Bandwidth

#### Procedure:

The bandwidth at 6dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 30 MHz

VBW = 100 kHz (VBW  $\geq$  RBW)

Sweep = auto

Trace = max hold

Detector function = peak

#### Measurement Data:

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	1.662	Complies
2445	1.599	Complies
2480	1.570	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

6 dB Bandwidth > 500kHz


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


## Low Channel



## Mid Channel



High Channel





### 3.2.2 Peak Output Power Measurement

#### Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1MHz

Span = auto

VBW = 1MHz (VBW  $\geq$  RBW)

Sweep = auto

Detector function = peak

#### Measurement Data:


Frequency (MHz)	Test Results		
	dBm	mW	Result
2405	20.04	100.93	Complies
2445	19.59	90.99	Complies
2480	1.19	1.32	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

Peak output power	< 1W
-------------------	------


## Low Channel



## Mid Channel



### High Channel



### 3.2.3 Power Spectral Density

#### Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz

Span = 300 kHz

VBW = 10 kHz

Sweep = 100 sec

Detector function = peak

Trace = max hold

#### Measurement Data:

Frequency (MHz)	Test Results	
	dBm	Result
2405	3.16	Complies
2445	2.37	Complies
2480	-16.23	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:


Power Spectral Density	< 8dBm @ 3kHz BW
------------------------	------------------

#### Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

## Power Density Measurement


### Low Channel



### Mid Channel



High Channel



### 3.2.4 Band - edge & Spurious

#### Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 50 MHz

Detector function = peak

Trace = max hold

Sweep = auto

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK:

RBW = VBW = 1MHz, Sweep=Auto

Average:

RBW = 1MHz, VBW=10Hz, Sweep=Auto

Measurement Distance:

3m

Polarization:



Horizontal / Vertical

#### Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

## Band-edge





**Band-edges in the restricted band 2310-2390 MHz measurement**


Frequency	Reading		Pol.	Correction			Limits		Result		Margin	
	[dBuV/m]			Factor			[dBuV/m]		[dBuV/m]		[dB]	
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
2390	52.9	64.5	V	26.0	36.0	8.2	54.0	74.0	51.1	62.7	2.9	11.3

**Band-edges in the restricted band 2483.5-2500 MHz measurement**


Frequency	Reading		Pol.	Correction			Limits		Result		Margin	
	[dBuV/m]			Factor			[dBuV/m]		[dBuV/m]		[dB]	
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
2483.5	54.1	65.3	V	26.0	36.0	8.2	54.0	74.0	52.3	63.5	1.7	10.5

**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.**


Low channel  
Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.



Mid channel  
Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.



**High channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.**



### 3.2.5 Field Strength of Harmonics

#### Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions. In case of the air temperature of the test site is out of the range is 10 to 40°C before the testing proceeds the warm-up time of EUT maintain adequately

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30MHz ~ 1 GHz)

VBW  $\geq$  RBW

= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic )

Span = 100 MHz

Detector function = peak

Trace = max hold

Sweep = auto

#### Measurement Data: Complies

- See next pages for actual measured data.
- The warm-up time of the EUT is 20min.

#### Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data:**

Frequency	Reading		Pol.	Correction			Limits		Result		Margin	
	[dBuV/m]			Factor			[dBuV/m]		[dBuV/m]		[dB]	
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
4810.0	46.2	58.3	V	31.4	34.6	8.7	54.0	74.0	51.7	63.8	2.3	10.3
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency	Reading		Pol.	Correction			Limits		Result		Margin	
	[dBuV/m]			Factor			[dBuV/m]		[dBuV/m]		[dB]	
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
4890.0	45.8	57.6	V	31.4	34.6	8.7	54.0	74.0	51.3	63.1	2.8	11.0
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
Frequency	Reading		Pol.	Correction			Limits		Result		Margin	
	[dBuV/m]			Factor			[dBuV/m]		[dBuV/m]		[dB]	
[MHz]	AV / Peak			Antenna	Amp. Gain	Cable	AV / Peak		AV / Peak		AV / Peak	
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-


No other emissions were detected at a level greater than 20dB below limit.

Radiated Emissions – Firmware update mode



243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: IHD2E100T0WW TEST MODE: Firmware Update mode  
Temp Humi : 6 / 32 Tested by: PARK.H.W



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1 141.56	37.00	-12.09	24.91	43.50	18.59	224	330	HORIZONTAL
2 144.00	48.50	-11.92	36.58	43.50	6.92	225	321	HORIZONTAL
3 240.00	54.00	-10.67	43.33	46.00	2.67	141	110	HORIZONTAL
4 295.78	35.40	-8.65	26.75	46.00	19.25	114	0	HORIZONTAL
5 534.00	36.50	-4.33	32.17	46.00	13.83	127	62	HORIZONTAL
6 720.00	45.50	-0.64	44.86	46.00	1.14	144	73	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

**Radiated Emissions – Zigbee mode**

243 Jubug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT/Model No.: IHD2E100T0WW

TEST MODE: Zigbee mode


Temp Humi : 6 / 32

Tested by: PARK.H.W

Data: 50

Level (dBuV/m)

Date: 2010-12-28



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1 46.53	41.60	-13.56	28.04	40.00	11.96	100	209	VERTICAL
2 144.01	48.30	-11.92	36.38	43.50	7.12	210	324	HORIZONTAL
3 172.22	43.40	-11.70	31.70	43.50	11.80	240	163	HORIZONTAL
4 412.02	41.80	-6.54	35.26	46.00	10.74	112	267	VERTICAL
5 430.26	38.50	-6.26	32.24	46.00	13.76	122	54	VERTICAL
6 460.12	36.20	-5.82	30.38	46.00	15.62	120	215	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



### 3.2.6 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 20dB below limit.

#### Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50


\* Decreases with the logarithm of the frequency

**AC Conducted Emissions – Firmware update – Line**

243 Jibug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT / Model No. :	IHD2E100T0WW	Phase :	LINE
Test Mode :	Firmware Update mode	Test Power :	120 / 60
Temp./Humi. :	18 / 37	Test Engineer :	PARK.H.W

Data: 44 File: C:\Conducted Data\2010\LTA\_Conduction\_1012-2.EMI (127) Date: 12-27-2010




Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.180	35.56	31.96	9.65	45.21	41.61	64.49	54.49	19.28	12.88
0.215	29.26	25.86	9.65	38.91	35.51	63.01	53.01	24.10	17.50
0.248	34.65	35.85	9.66	44.31	45.51	61.82	51.82	17.51	6.31
0.283	26.56	21.66	9.65	36.21	31.31	60.73	50.73	24.52	19.42
0.321	25.96	21.66	9.65	35.61	31.31	59.68	49.68	24.07	18.37
0.389	24.15	20.35	9.67	33.82	30.02	58.09	48.09	24.27	18.07

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

**AC Conducted Emissions – Firmware update – Neutral**

243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-3236008,9  
Fax: +82-31-3236010

EUT / Model No. :	IHD2E100T0WW	Phase :	NEUTRAL
Test Mode :	Firmware Update mode	Test Power :	120 / 60
Temp./Humi. :	18 / 37	Test Engineer :	PARK.H.W



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.176	36.36	33.16	9.66	46.02	42.82	64.67	54.67	18.66	11.86
0.211	29.06	26.66	9.66	38.72	36.32	63.17	53.17	24.45	16.85
0.250	38.65	37.55	9.66	48.31	47.21	61.76	51.76	13.45	4.55
0.321	27.26	22.86	9.66	36.92	32.52	59.68	49.68	22.76	17.16
0.393	26.55	24.35	9.66	36.21	34.01	58.00	48.00	21.79	13.99
0.462	22.85	19.15	9.66	32.51	28.81	56.66	46.66	24.15	17.85


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

**AC Conducted Emissions – Zigbee – Line**

243 Jibug-ni, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel :+82-31-3236008,9  
Fax:+82-31-3236010

EUT / Model No. : IHD2E100T0WW	Phase : LINE
Test Mode : Zigbee mode	Test Power : 120 / 60
Temp./Humi. : 18 / 37	Test Engineer : PARK.H.W

Data: 48 File: C:\Conducted Data\2010\LTA\_Conduction\_1012-2.EMI (127) Date: 12-27-2010



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.329	38.56	31.66	9.66	48.21	41.31	59.48	49.48	11.26	8.16
0.590	31.15	23.35	9.72	40.87	33.07	56.00	46.00	15.13	12.93
0.614	30.96	23.46	9.73	40.69	33.19	56.00	46.00	15.31	12.81
0.640	30.76	23.36	9.74	40.50	33.10	56.00	46.00	15.50	12.90
0.662	29.16	21.26	9.75	38.91	31.01	56.00	46.00	17.09	14.99
0.895	28.96	21.26	9.78	38.74	31.04	56.00	46.00	17.26	14.96


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

**AC Conducted Emissions – Zigbee – Neutral**

243 Jubug-ri, yangji-Myeon, Youngin-si,  
Gyeonggi-do 449-822 Korea  
Tel +82-31-3236008,9  
Fax: +82-31-3236010

EUT / Model No. : IHD2E100T0WW	Phase : NEUTRAL
Test Mode : Zigbee mode	Test Power : 120 / 60
Temp./Humi. : 18 / 37	Test Engineer : PARK.H.W

Data: 50 Level (dBuV) File: C:\Conducted Data\2010\LTA\_Conduction\_1012-2.EMI (127) Date: 12-27-2010



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.332	35.56	27.56	9.66	45.22	37.22	59.40	49.40	14.18	12.18
0.384	29.25	20.15	9.66	38.91	29.81	58.19	48.19	19.28	18.38
0.412	29.05	21.25	9.66	38.71	30.91	57.61	47.61	18.90	16.70
0.591	26.65	17.85	9.71	36.37	27.57	56.00	46.00	19.63	18.43
0.616	26.86	19.76	9.73	36.58	29.48	56.00	46.00	19.42	16.52
0.641	26.46	18.56	9.74	36.20	28.30	56.00	46.00	19.80	17.70

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

**APPENDIX**

**TEST EQUIPMENT USED FOR TESTS**

	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	1 year	2010-02-01
2	Spectrum Analyzer	8563E	3425A02505	HP	1 year	2010-03-29
3	Spectrum Analyzer	8594E	3710A04074	HP	2 year	2009-10-12
4	Signal Generator	8648C	3623A02597	HP	1 year	2010-03-30
5	Signal Generator	83711B	US34490456	HP	1 year	2010-03-30
6	Attenuator (3dB)	8491A	37822	HP	1 year	2010-10-08
7	Attenuator (10dB)	8491A	63196	HP	1 year	2010-10-08
8	EMI Test Receiver	ESCI7	100722	R&S	1 year	2010-10-08
9	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	2 year	2010-11-25
10	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	2 year	2010-11-25
11	RF Amplifier	8447D	2949A02670	HP	2 year	2009-10-12
12	RF Amplifier	8449B	3008A02126	HP	1 year	2010-03-29
13	Test Receiver	ESHS10	828404/009	R&S	1 year	2010-03-29
14	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	2 year	2009-04-02
15	Log Periodic Antenna	VULP 9118	9118 A 401	SCHWARZBECK	2 year	2009-04-13
16	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	2 year	2009-04-13
17	Horn Antenna	3115	00055005	ETS LINDGREN	2 year	2009-03-16
18	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	2 year	2010-12-24
19	Dipole Antenna	VHA9103	2116	SCHWARZBECK	2 year	2010-11-25
20	Dipole Antenna	VHA9103	2117	SCHWARZBECK	2 year	2010-11-25
21	Dipole Antenna	VHA9105	2261	SCHWARZBECK	2 year	2010-11-25
22	Dipole Antenna	VHA9105	2262	SCHWARZBECK	2 year	2010-11-25
23	Hygro-Thermograph	THB-36	0041557-01	ISUZU	1 year	2010-04-12
24	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
25	Power Divider	11636A	6243	HP	1 year	2010-10-08
26	DC Power Supply	6622A	3448A03079	HP	1 year	2010-10-08
27	Frequency Counter	5342A	2826A12411	HP	1 year	2010-03-30
28	Power Meter	EPM-441A	GB32481702	HP	1 year	2010-03-29
29	Power Sensor	8481A	US41030291	HP	1 year	2010-10-08
30	Audio Analyzer	8903B	3729A18901	HP	1 year	2010-10-08
31	Modulation Analyzer	8901B	3749A05878	HP	1 year	2010-10-08
32	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2010-10-08
33	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	2 year	2009-03-02
34	Stop Watch	HS-3	601Q09R	CASIO	2 year	2010-03-31
35	LISN	ENV216	100408	R&S	1 year	2010-10-08
36	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	2 year	2010-05-13
37	Attenuator (30dB)	8498A	3318A10929	HP	1 year	2011-01-05