



**CENTRE OF TESTING SERVICE  
INTERNATIONAL**

**OPERATE ACCORDING TO ISO/IEC 17025**

# **FCC ID TEST REPORT**

**TEST REPORT NUMBER : CGZ3150626-00733-EF**



**CENTRE OF TESTING SERVICE CO., LTD.**

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China



<b>TEST REPORT For FCC ID 47 CFR PART 15 OCT, 2014</b>	
<b>Report Reference No.</b> .....	CGZ3150626-00733-EF
<b>Date of issue</b> .....	16 July 2015
<b>Testing Laboratory Name</b> ..... <b>CENTRE OF TESTING SERVICE CO., LTD.</b>	
<b>Address</b> .....	A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China
<b>Testing location/ procedure</b> .....	Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>
<b>Applicant's name</b> ..... SHENZHEN JIAYIYANG ELECTRONICS CO., LTD.	
<b>Address</b> .....	5/F, B Building, Fuali Industrial Zone, District 28, Baoan, Shenzhen Guangdong, China. P.C: 518101
<b>Test specification</b> .....	
<b>Standard</b> .....	<b>47 CFR PART 15 OCT, 2014</b>
<b>Test Report Form No.</b> ..... CTSEMC-1.0	
<b>TRF Originator</b> .....	CENTRE OF TESTING SERVICE CO., LTD
<b>Master TRF</b> .....	Dated 2009-01
<b>CENTRE OF TESTING SERVICE CO., LTD. All rights reserved.</b> This publication may be reproduced in whole or in part for non-commercial purposes as long as the CENTRE OF TESTING SERVICE CO., LTD is acknowledged as copyright owner and source of the material. CENTRE OF TESTING SERVICE CO., LTD takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
<b>Test item description</b> ..... Remote Pet Training System with Flashing LED Display	
<b>Trade Mark</b> .....	/
<b>Manufacturer</b> .....	SHENZHEN JIAYIYANG ELECTRONICS CO., LTD.
<b>Model/Type reference</b> .....	IS-PET617RA
<b>Ratings</b> .....	Battery 3.7V
<b>Operating Frequency</b> .....	915.0 MHz
<b>Result</b> .....	<b>Positive</b>

**Compiled by:**

Kate zhang / File  
administrators**Supervised by:**

Duke yang / Technique principal

**Approved by:**

Vincent yao / Manager

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

**CENTRE OF TESTING SERVICE CO., LTD.**

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



## FCC ID -- T E S T R E P O R T

**Test Report No. : CGZ3150626-00733-EF**
16 July 2015  
Date of issue

Type / Model.....	IS-PET617RA
EUT.....	Remote Pet Training System with Flashing LED Display
<b>Applicant</b> .....	SHENZHEN JIAYIYANG ELECTRONICS CO., LTD.
Address.....	5/F, B Building, Fuali Industrial Zone, District 28, Baoan, Shenzhen Guangdong, China. P.C: 518101
Telephone.....	+86-0755-33931980
Fax.....	+86-0755-33931982
Contact.....	/
<b>Manufacturer</b> .....	SHENZHEN JIAYIYANG ELECTRONICS CO., LTD.
Address.....	5/F, B Building, Fuali Industrial Zone, District 28, Baoan, Shenzhen Guangdong, China. P.C: 518101
Telephone.....	+86-0755-33931980
Fax.....	+86-0755-33931982
Contact.....	/
<b>Factory</b> .....	SHENZHEN JIAYIYANG ELECTRONICS CO., LTD.
Address.....	5/F, B Building, Fuali Industrial Zone, District 28, Baoan, Shenzhen Guangdong, China. P.C: 518101
Telephone.....	+86-0755-33931980
Fax.....	+86-0755-33931982
Contact.....	/

**Test Result** according to the standards on page 1:

**PASSED**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
<b>1.TEST STANDARDS.....</b>	<b>4</b>
<b>2.SUMMARY.....</b>	<b>4</b>
2.1 GENERAL REMARKS.....	4
2.2 FINAL ASSESSMENT .....	4
<b>3.EQUIPMENT UNDER TEST .....</b>	<b>4</b>
3.1 POWER SUPPLY SYSTEM UTILISED .....	4
3.2 SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT) .....	4
3.3 EUT OPERATION MODE.....	4
3.4 EUT CONFIGURATION .....	5
<b>4.TEST ENVIRONMENT .....</b>	<b>6</b>
4.1 ADDRESS OF THE TEST LABORATORY .....	6
4.2 TEST FACILITY .....	6
4.3 ENVIRONMENTAL CONDITIONS.....	6
4.4 DEFINITIONS OF SYMBOLS USED IN THIS TEST REPORT.....	6
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	6
4.6 MEASUREMENT UNCERTAINTY .....	7
<b>5.SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>7</b>
5.1.DESRIPTION OF STANDARDS AND RESULTS.....	7
<b>6.TEST CONDITIONS AND RESULTS .....</b>	<b>8</b>
6.1 POWER LINE CONDUCTED EMISSION TEST .....	8
<b>7.TRANSMITTER OUPUT POWER AND SPURIOUS EMISSION (ELECTRIC FIELD) .....</b>	<b>10</b>
7.1.TEST EQUIPMENT .....	10
7.2.BLOCK DIAGRAM OF TEST SETUP .....	10
7.3. TRANSMITTER OUTPUT POWER AND SPURIOUS EMISSIONS LIMIT : .....	11
7.4.TEST PROCEDURE.....	12
7.5.RADIATED EMISSION TEST RESULTS .....	12
<b>8.BAND EDGE COMPLIANCE TEST .....</b>	<b>18</b>
8.1. TEST EQUIPMENT .....	18
8.2. TEST INFORMATION .....	18
8.3. TEST PROCEDURE .....	18
8.4. TEST RESULTS.....	18
<b>9.DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>21</b>

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

### CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

## 1 . TEST STANDARDS

The tests were performed according to following standards:

- 47 CFR PART 15 OCT, 2014
- ANSI C63.4-2009

## 2 . SUMMARY

### 2.1 GENERAL REMARKS

Date of receipt of test sample	26 June 2015
Testing commenced on	26 June~15 July 2015
Testing concluded on	16 July 2015

### 2.2 FINAL ASSESSMENT

The FCC requirements pertaining to the technical standards and tested operation modes are

- - fulfilled.
- ☐ - **not** fulfilled.

The equipment under test

- - fulfils the FCC requirements cited on page 1.
- ☐ - **does not** fulfil the FCC requirements cited on page 1.

## 3 . EQUIPMENT UNDER TEST

### 3.1 Power supply system utilised

Power supply voltage : ■ **Battery 3.7V**

### 3.2 Short description of the Equipment under Test (EUT)

Number of tested samples: **1**  
Serial number: Prototype

### 3.3 EUT operation mode

The equipment under test was operated during the measurement under the following conditions:

- ☐ TX- Y position
- ☐ TX- Zposition
- TX- X position

TX-X position: TX-X Position

Note: TX -X position of EUT is the worst case, so only these test results be recorded in the test report.



### 3.4 EUT configuration

#### 3.4.1. Description of configuration (EUT)

Description	:	Remote Pet Training System with Flashing LED Display
Model Number	:	IS-PET617RA
Operation frequency	:	915.0 MHz
Radio Technology	:	FSK
Modulation Technology	:	FSKmodulation
Antenna	:	External antenna

#### 3.4.2. Tested Supporting System Details

N/A

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

#### **CENTRE OF TESTING SERVICE CO., LTD.**

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

## 4 . TEST ENVIRONMENT

### 4.1 Address of the test laboratory

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

### 4.2 Test facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L3394

CENTRE OF TESTING SERVICE CO., LTD has been assessed and proved to be in compliance with CNAS-CL01: 2006 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### IC-Registration No.: 8374A

The 3m Alternate Test Site of CENTRE OF TESTING SERVICE CO., LTD has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 8374A on May 22, 2014.

#### FCC-Registration No.: 971995

CENTRE OF TESTING SERVICE CO., LTD, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration No.791995, July 13,2012.

### 4.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 ° C
Humidity:	25~75 %
Atmospheric pressure:	86~106 kPa

### 4.4 Definitions of symbols used in this test report

- - The black square indicates that the listed condition, standard or equipment is applicable for this report.
- - The empty square indicates that the listed condition, standard or equipment is **not** applicable for this report.

### 4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the CTS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

#### 4.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	$\pm 1.22\text{dB}$	(1)
Power disturbance	30MHz~300MHz	$\pm 1.38\text{dB}$	(1)
Radiation emission (3m)	30MHz~300MHz	$\pm 3.14\text{dB}$	(1)
	300MHz~1000MHz	$\pm 3.18\text{dB}$	(1)
	1GHz~18GHz	$\pm 3.54\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 5 . SUMMARY OF STANDARDS AND RESULTS

### 5.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Conducted Emission Test	FCC Part 15 : 15.207 ANSI C63.4-2009	N/A
Transmitter Output power and Spurious Emissions	FCC Part 15 C: 15.249 FCC Part 15 C: 15.209 ANSI C63.4-2009	PASSED
Band Edge Compliance Test	FCC Part 15 C: 15.249 ANSI C63.4-2009	PASSED
N/A is an abbreviation for Not Applicable.		

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

#### CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



## 6 . TEST CONDITIONS AND RESULTS

### 6.1 Power Line Conducted Emission Test

For test instruments and accessories used see section 6.1.5

#### 6.1.1 Description of the test location


Test location : Shielding Room

#### 6.1.2 Description of the test set-up

##### 6.1.2.1 Operating Condition

The EUT is engraving during the test, and the results of the maximum emanation are recorded

##### 6.1.2.2 Block Diagram of Test Setup



#### 6.1.3 Limits of disturbance (Class B)

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note: (1) The tighter limit shall apply at the edge between two frequency bands.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

#### CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

#### 6.1.4. Block Diagram of Test Setup

##### 6.1.4.1 Block Diagram of connection between EUT and simulators



(**EUT:** Remote Pet Training System with Flashing LED Display)

#### 6.1.5. Conducted disturbance Test Equipment

Conducted Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESHS10	842884/012	2014/11
2	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/025	2014/11
3	Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100301	2014/11
4	EMI Test Software	ROHDE & SCHWARZ	ESK1	N/A	2014/11

#### 6.1.6 Test result

The requirements are	<b>Fulfilled</b>
Band width	9kHz
Frequency range	0.15kHz - 30 MHz
Min. limit margin	>N/A at 0.15MHz - 30 MHz

**Remarks:** The EUT power supply by battery, Not applicable.

## 7 . TRANSMITTER OUPUT POWER AND SPURIOUS EMISSION (Electric field)

### 7.1.Test Equipment

Radiated disturbance (electric field)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2014/11
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2015/03
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2015/03
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2015/03
5	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2015/03
6	Loop Antenna	A.R.A	PLA-1030/B	1030	2014/11

### 7.2.Block Diagram of Test Setup


#### 6.2.1 Block Diagram of connection between EUT and simulators

TX


EUT

(**EUT:** Remote Pet Training System with Flashing LED Display)

### 7.2.2 Anechoic Chamber Setup Diagram



### 7.3. Transmitter Output power and Spurious Emissions Limit :

#### Standard: FCC Part 15:249.

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

Frequency (Hz)	Field Strength (μV/m at meter)	Measurement Distance (meter)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

- Remark:
- (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

#### CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

#### 7.4. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2009 on radiated emission Test.

The frequency range from 30MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 120kHz RBW below 1GHz and a Peak and Average detector with 1MHz RBW above 1GHz,

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 300kHz VBW below 1GHz and a Peak detector with 1MHz VBW above 1GHz, A average detector with 10Hz VBW above 1GHz

Pretest x, y, z position of EUT, final, select the worst case x position test and record the test results in the report.

The test modes (TX Mode) is tested in Anechoic Chamber and all the scanning waveforms are reported on section 7.5

#### 7.5. Radiated Emission Test Results

**PASSED.**

The frequency range from 9KHz~30MHz, 30MHz to 230MHz, 230MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.



Test Mode:	TX –X Position Mode	Result:	<input checked="" type="checkbox"/> - passed
Frequency range:	9KHz~30MHz		<input type="checkbox"/> - not passed

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
Remark:Other frequency no specific emission form the EUT (Margin > 6dB form the applicable Limit)							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.


**CENTRE OF TESTING SERVICE CO., LTD.**  
A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China  
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406  
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



Test Model:	TX -X	Result:	<input checked="" type="checkbox"/> - passed
Test point:	Horizontal		<input type="checkbox"/> - not passed
Frequency range:	30MHz~18GHz		

EUT	Remote Pet Training System with Flashing LED Display
Operating Condition	Battery 3.7V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Operator	Duke




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	31.8900	-16.28	34.84	18.56	40.00	-21.44	QP
2	130.4400	-16.14	30.04	13.90	43.50	-29.60	QP
3	165.8100	-15.98	29.74	13.76	43.50	-29.74	QP
4	209.8200	-10.23	28.67	18.44	43.50	-25.06	QP
5	253.5600	-11.23	29.34	18.11	46.00	-27.89	QP
6	299.4600	-1.56	28.81	27.25	46.00	-18.75	QP

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

**CENTRE OF TESTING SERVICE CO., LTD.**  
A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China  
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406  
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	915.0.0000	-1.11	90.46	92.45	114.00	-21.55	Peak
2	915.0.0000	-1.11	87.65	89.25	94.00	-4.75	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	443.5000	-8.73	33.01	24.28	46.00	-21.72	QP
2	559.0000	-5.66	34.07	28.41	46.00	-17.59	QP
3	627.6000	-4.27	32.95	28.68	46.00	-17.32	QP
4	724.8999	-2.66	34.74	32.08	46.00	-13.92	QP
5	851.6000	-0.34	35.89	35.55	46.00	-10.45	QP
6	947.5000	0.31	36.06	36.37	46.00	-9.63	QP

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1830.000	-10.35	54.66	44.31	74.00	-29.69	peak
2	1830.000	-10.35	41.97	31.62	54.00	-22.38	AVG
3	2746.000	-4.93	52.49	47.56	74.00	-26.44	peak
4	2746.000	-4.93	39.61	34.68	54.00	-19.32	AVG

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

**CENTRE OF TESTING SERVICE CO., LTD.**

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471


E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service





Test Model:	TX -X	Result:	<input checked="" type="checkbox"/> - passed
Test point:	Vertical		<input type="checkbox"/> - not passed
Frequency range:	30MHz~18GHz		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	37.0200	-16.95	36.20	19.25	40.00	-20.75	QP
2	63.4799	-20.06	38.01	17.95	40.00	-22.05	QP
3	106.4099	-17.63	33.50	15.87	43.50	-27.63	QP
4	213.8700	-10.47	29.50	19.03	43.50	-24.47	QP
5	231.9600	-11.63	31.81	20.18	46.00	-25.82	QP
6	281.9100	-6.53	34.68	28.15	46.00	-17.85	QP

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

**CENTRE OF TESTING SERVICE CO., LTD.**  
A101, No.65, Zhuji Highway,Tianhe District, Guangzhou, China  
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406  
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	915.0.0000	-1.11	93.56	89.35	114.00	-24.65	Peak
2	915.0.0000	-1.11	90.36	86.54	94.00	-7.46	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	365.1000	-11.10	42.85	31.75	46.00	-14.25	QP
2	428.8000	-9.33	37.68	28.35	46.00	-17.65	QP
3	552.7000	-5.67	33.80	28.13	46.00	-17.87	QP
4	685.0000	-3.57	35.43	31.86	46.00	-14.14	QP
5	883.1000	-1.28	40.75	39.47	46.00	-6.53	QP
6	947.5000	0.31	42.84	43.15	46.00	-2.85	QP

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1830.000	-10.35	63.31	52.96	74.00	-21.04	peak
2	1830.000	-10.35	49.31	38.96	54.00	-15.04	AVG
3	2746.000	-4.93	54.52	49.59	74.00	-24.41	peak
4	2746.000	-4.93	41.80	36.87	54.00	-17.13	AVG

Note:Level=Reading+Factor.    Margin=Level-Limit.

Remark: Others frequency test result margin all >6dB of the limit.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

## 8 . BAND EDGE COMPLIANCE TEST

### 8.1. Test Equipment

Band Edge Compliance test					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	10868	2014/11
2	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2015/03
3	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2015/03
4	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2015/03

### 8.2. Test Information

EUT	Remote Pet Training System with Flashing LED Display
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Operator	Duke

### 8.3. Test procedure

- 1、 The EUT operates at TX mode. The transmitter channel are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2、 Max hold the trace of the setp 1,and the EUT operates at Normal test mode to verify the largest spurious emissions power.

### 8.4. Test Results



#### PASSED.

The EUT operates at TX test mode. The transmitter channel are tested to verify the band edge emissions.

Test Mode	Channel Marked Frequency	Test Result Highest Emission (dBuv/m)			
		Horizontal		Vertical	
		Peak	Limit	Peak	Limit
TX	614MHz	31.81	46	31.78	46
	960MHz	31.90	54	32.07	54
Remark: Other Spurious Emissions mini margin all >6 dB of Limit.					



Band Edges (Low)





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

**CENTRE OF TESTING SERVICE CO., LTD.**  
A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China  
Tel: +86-20-85543113 (32 lines)      Fax: +86-20-38780406  
Complaint line: +86-20-85533471      E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



## Band Edges (High)



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

**CENTRE OF TESTING SERVICE CO., LTD.**

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



## 9 . DEVIATION TO TEST SPECIFICATIONS

The following identical model(s):

**IS-PET617RB**

Belong to the tested device:

Product description: **Remote Pet Training System with Flashing LED Display**

Model name: **IS-PET617RA**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

### **CENTRE OF TESTING SERVICE CO., LTD.**

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service