



## SAR exemption evaluation

**Applicant** Phicomm(Shanghai)Co.,Ltd  
**FCC ID** YJY2018W301  
**Product** PHICOMM W3 Fitness Band  
**Brand** PHICOMM  
**Model** PHICOMM W3  
**Report No.** R1806A0280-S1  
**Issue Date** July 13, 2018

*Approved by: Jiangpeng Lan*

*Reviewed by: Kai Xu*

**TA Technology (Shanghai) Co., Ltd.**

*No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## Conducted Power

Network Standards	Channel	Frequency (MHz)	Output Power (dBm)			Conclusion
			DH5	2DH5	3DH5	
Bluetooth	0	2402	5.63	5.00	5.14	PASS
	39	2441	5.14	4.39	4.64	PASS
	78	2480	5.24	4.53	4.74	PASS

Network Standards	Carrier frequency (MHz)	Output Power (dBm)	Conclusion
Bluetooth (Low Energy)	2402	-1.55	PASS
	2440	-2.15	PASS
	2480	-1.98	PASS

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Bluetooth	Distance (mm)	MAX Power (dBm)	Frequency (MHz)	Ratio	Evaluation
Head	5	5.63	2480	1.15	No
Body-worn	5	5.63	2480	1.15	No