

# FCC Test Report

Product Name	Bluetooth Module
Model No.	319-BT82600
FCC ID.	YKH319-BT82600

Applicant	NUMA Electronics Inc.
Address	7F-8, No. 5, Sec. 3, New Taipei Blvd., Xinzhuang Dist., New Taipei City 242, Taiwan(R.O.C.)

Date of Receipt	Aug. 31, 2017
Issued Date	Sep. 15, 2017
Report No.	1780554R-RFUSP01V00-A
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

# Test Report

Issued Date: Sep. 15, 2017

Report No.: 1780554R-RFUSP01V00-A



Product Name	Bluetooth Module
Applicant	NUMA Electronics Inc.
Address	7F-8, No. 5, Sec. 3, New Taipei Blvd., Xinzhuang Dist., New Taipei City 242, Taiwan(R.O.C.)
Manufacturer	NUMA Electronics Inc.
Model No.	319-BT82600
FCC ID.	YKH319-BT82600
EUT Rated Voltage	DC 3.3V
EUT Test Voltage	AC 120V/60Hz
Trade Name	NUMA
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2016 ANSI C63.4: 2014, ANSI C63.10: 2013
Test Result	Complied

Documented By :



( Adm. Assistant / Peggy Tu )

Tested By :



( Assistant Engineer / Jason Chang )

Approved By :



( Director / Vincent Lin )

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. EUT Description.....	5
1.2. Operational Description.....	7
1.3. Tested System Details.....	8
1.4. Configuration of Tested System .....	8
1.5. EUT Exercise Software .....	8
1.6. Test Facility .....	9
1.7. List of Test Equipment.....	10
<b>2. CONDUCTED EMISSION .....</b>	<b>11</b>
2.1. Test Setup .....	11
2.2. Limits.....	12
2.3. Test Procedure .....	12
2.4. Uncertainty .....	12
2.5. Test Result of Conducted Emission.....	13
<b>3. PEAK POWER OUTPUT .....</b>	<b>15</b>
3.1. Test Setup .....	15
3.2. Limit .....	15
3.3. Test Procedure .....	15
3.4. Uncertainty .....	15
3.5. Test Result of Peak Power Output.....	16
<b>4. RADIATED EMISSION .....</b>	<b>18</b>
4.1. Test Setup .....	18
4.2. Limits.....	19
4.3. Test Procedure .....	20
4.4. Uncertainty .....	20
4.5. Test Result of Radiated Emission.....	21
<b>5. RF ANTENNA CONDUCTED TEST.....</b>	<b>29</b>
5.1. Test Setup .....	29
5.2. Limits.....	29
5.3. Test Procedure .....	29
5.4. Uncertainty .....	29
5.5. Test Result of RF Antenna Conducted Test.....	30
<b>6. BAND EDGE .....</b>	<b>32</b>
6.1. Test Setup .....	32
6.2. Limit .....	32
6.3. Test Procedure .....	33
6.4. Uncertainty .....	33
6.5. Test Result of Band Edge .....	34
<b>7. CHANNEL NUMBER.....</b>	<b>46</b>
7.1. Test Setup .....	46
7.2. Limit .....	46

7.3.	Test Procedure .....	46
7.4.	Uncertainty .....	46
7.5.	Test Result of Channel Number.....	47
<b>8.</b>	<b>CHANNEL SEPARATION.....</b>	<b>49</b>
8.1.	Test Setup .....	49
8.2.	Limit .....	49
8.3.	Test Procedure .....	49
8.4.	Uncertainty .....	49
8.5.	Test Result of Channel Separation.....	50
<b>9.</b>	<b>DWELL TIME .....</b>	<b>54</b>
9.1.	Test Setup .....	54
9.2.	Limit .....	54
9.3.	Test Procedure .....	54
9.4.	Uncertainty .....	54
9.5.	Test Result of Dwell Time .....	55
<b>10.</b>	<b>OCCUPIED BANDWIDTH .....</b>	<b>59</b>
10.1.	Test Setup .....	59
10.2.	Limits.....	59
10.3.	Test Procedure .....	59
10.4.	Uncertainty .....	59
10.5.	Test Result of Occupied Bandwidth .....	60
<b>11.</b>	<b>EMI REDUCTION METHOD DURING COMPLIANCE TESTING .....</b>	<b>64</b>
Attachment 1: EUT Test Photographs		
Attachment 2: EUT Detailed Photographs		

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Bluetooth Module
Trade Name	NUMA
Model No.	319-BT82600
FCC ID.	YKH319-BT82600
Frequency Range	2402-2480MHz
Channel Number	79
Type of Modulation	FHSS: GFSK(1Mbps) / $\pi$ /4DQPSK(2Mbps) / 8DPSK(3Mbps)
Antenna Type	PCB Antenna
Channel Control	Auto
Antenna Gain	Refer to the table “Antenna List”

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	FEASYCOM	N/A	PCB Antenna	3.03 dBi for 2.4 GHz

Note: 1. The antenna of EUT conforms to FCC 15.203.

## Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 00:	2402 MHz	Channel 20:	2422 MHz	Channel 40:	2442 MHz	Channel 60:	2462 MHz
Channel 01:	2403 MHz	Channel 21:	2423 MHz	Channel 41:	2443 MHz	Channel 61:	2463 MHz
Channel 02:	2404 MHz	Channel 22:	2424 MHz	Channel 42:	2444 MHz	Channel 62:	2464 MHz
Channel 03:	2405 MHz	Channel 23:	2425 MHz	Channel 43:	2445 MHz	Channel 63:	2465 MHz
Channel 04:	2406 MHz	Channel 24:	2426 MHz	Channel 44:	2446 MHz	Channel 64:	2466 MHz
Channel 05:	2407 MHz	Channel 25:	2427 MHz	Channel 45:	2447 MHz	Channel 65:	2467 MHz
Channel 06:	2408 MHz	Channel 26:	2428 MHz	Channel 46:	2448 MHz	Channel 66:	2468 MHz
Channel 07:	2409 MHz	Channel 27:	2429 MHz	Channel 47:	2449 MHz	Channel 67:	2469 MHz
Channel 08:	2410 MHz	Channel 28:	2430 MHz	Channel 48:	2450 MHz	Channel 68:	2470 MHz
Channel 09:	2411 MHz	Channel 29:	2431 MHz	Channel 49:	2451 MHz	Channel 69:	2471 MHz
Channel 10:	2412 MHz	Channel 30:	2432 MHz	Channel 50:	2452 MHz	Channel 70:	2472 MHz
Channel 11:	2413 MHz	Channel 31:	2433 MHz	Channel 51:	2453 MHz	Channel 71:	2473 MHz
Channel 12:	2414 MHz	Channel 32:	2434 MHz	Channel 52:	2454 MHz	Channel 72:	2474 MHz
Channel 13:	2415 MHz	Channel 33:	2435 MHz	Channel 53:	2455 MHz	Channel 73:	2475 MHz
Channel 14:	2416 MHz	Channel 34:	2436 MHz	Channel 54:	2456 MHz	Channel 74:	2476 MHz
Channel 15:	2417 MHz	Channel 35:	2437 MHz	Channel 55:	2457 MHz	Channel 75:	2477 MHz
Channel 16:	2418 MHz	Channel 36:	2438 MHz	Channel 56:	2458 MHz	Channel 76:	2478 MHz
Channel 17:	2419 MHz	Channel 37:	2439 MHz	Channel 57:	2459 MHz	Channel 77:	2479 MHz
Channel 18:	2420 MHz	Channel 38:	2440 MHz	Channel 58:	2460 MHz	Channel 78:	2480 MHz
Channel 19:	2421 MHz	Channel 39:	2441 MHz	Channel 59:	2461 MHz		

## Note:

1. The EUT is a Bluetooth Module with a built-in Bluetooth V3.0, V2.1+EDR transceiver, this report for Bluetooth V3.0, V2.1+EDR.
2. These tests were conducted on a sample for the purpose of demonstrating compliance of Bluetooth transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test
4. Bluetooth operation was evaluated at both 1Mb/s and 3Mb/s data rates. 2Mb/s data rate was found, through pre-testing, to produce emissions similar to those for 3Mb/s.

Test Mode	Mode 1: Transmit - 1Mbps (GFSK)
	Mode 2: Transmit - 3Mbps (8DPSK)


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Notebook PC	DELL	Latitude 5580	2HRD7H2	Non-Shielded, 0.8m
2 Fixture	FTDI	TTL-232R-PCB	N/A	N/A

Signal Cable Type	Signal cable Description
A USB Cable	Non-Shielded, 1.7m
B Fixture Cable	Non-Shielded, 0.09m

### 1.4. Configuration of Tested System



### 1.5. EUT Exercise Software

1. Setup the EUT as shown in Section 1.4.
2. Execute software "RTLBTAPP" on the Notebook PC.
3. Configure the test mode, the test channel, and the data rate.
4. Press "OK" to start the continuous Transmit.
5. Verify that the EUT works properly.

## 1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	30-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from DEKRA Testing and Certification Co., Ltd. Web Site:

<http://www.dekra.com.tw/english/about/certificates.aspx?bval=5>

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site: [http://www.dekra.com.tw/index\\_en.aspx](http://www.dekra.com.tw/index_en.aspx)

Site Description:   Accredited by TAF  
                          Accredited Number: 3023

Site Name:           DEKRA Testing and Certification Co., Ltd  
Site Address:       No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451,  
                          Taiwan, R.O.C.  
                          TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789  
                          E-Mail : [info.tw@dekra.com](mailto:info.tw@dekra.com)

FCC Accreditation Number: TW3023



## 1.7. List of Test Equipment

### For Conducted measurements /CB3/SR8

	Equipment	Manufacturer	Model No.	Serial No.	Cali. Data	Due. Data
	Temperature Chamber	WIT GROUP	TH-1S-B	EQ-201-00146	2016/11/28	2017/11/27
X	Spectrum Analyzer	Agilent	N9010A	MY48030495	2017/7/22	2018/7/21
X	Power Meter	Anritsu	ML2495A	6K00003357	2017/6/23	2018/6/22
X	Pulse power sensor	Anritsu	MA2411B	0846193	2017/6/23	2018/6/22
X	EMI Test Receiver	R&S	ESCS 30	100369	2016/10/13	2017/10/12
X	LISN	R&S	ESH3-Z5	836679/017	2017/1/7	2018/1/6
X	LISN	R&S	ENV216	100097	2017/1/7	2018/1/6
X	Coaxial Cable	QTK(Arnist)	RG 400	LC018-RG	2017/6/25	2018/6/24

### For Radiated measurements /Site3/CB8


	Equipment	Manufacturer	Model No.	Serial No.	Cali. Data	Due. Data
X	Spectrum Analyzer	R&S	FSP40	100170	2017/1/5	2018/1/4
X	Loop Antenna	Teseq	HLA6121	37133	2017/3/18	2018/3/17
X	Bi-Log Antenna	Schaffner Chase	CBL6112B	2707	2017/6/11	2018/6/10
X	Horn Antenna	ETS-Lindgren	3117	00135205	2017/4/6	2018/4/5
X	Horn Antenna	Schwarzbeck	BBHA9170	9170430	2017/1/11	2018/1/10
X	Pre-Amplifier	QTK	AP/0100A	CHM/0901069	2017/6/23	2018/6/22
X	Pre-Amplifier	EMCI	EMC012630SE	980210	2017/1/26	2018/1/24
X	Pre-Amplifier	NARDA WE	DBL-1840N506	013	2016/9/30	2017/9/29
X	Filter	MicroTRON	BRM50701	019	2016/11/2	2017/11/1
	Filter	Microwave Circuits	N0257881	36681	2016/12/7	2017/12/6
X	EMI Test Receiver	R&S	ESR26	101385	2016/9/29	2017/9/28
X	Coaxial Cable	QTK(Arnist)	SUCOFLEX 106	L1606-015C	2017/6/23	2018/6/22
X	EMI Test Receiver	R&S	ESCS 30	838251/001	2017/7/21	2018/7/20
X	Coaxial Cable	QTK(Arnist)	RG 214	LC003-RG	2017/6/16	2018/6/15
X	Coaxial signal switch	Anritsu	MP59B	6201415889	2017/6/16	2018/6/15

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.
3. Test Software version :QuiTek EMI 2.0 V2.1.113.

## 2. Conducted Emission

### 2.1. Test Setup



## 2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBμV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

## 2.3. Test Procedure

The EUT and Peripherals are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

## 2.4. Uncertainty

± 2.26 dB

## 2.5. Test Result of Conducted Emission

Product : Bluetooth Module  
 Test Item : Conducted Emission Test  
 Power Line : Line 1  
 Test date : 2017/09/06  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2441MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V	Margin dB	Limit dB $\mu$ V
<b>LINE 1</b>					
<b>Quasi-Peak</b>					
0.173	9.760	29.860	39.620	-25.723	65.343
0.216	9.773	24.780	34.553	-29.561	64.114
0.517	9.742	24.360	34.102	-21.898	56.000
2.834	9.794	26.960	36.754	-19.246	56.000
9.502	9.956	21.460	31.416	-28.584	60.000
18.224	10.066	16.600	26.666	-33.334	60.000
<b>Average</b>					
0.173	9.760	15.880	25.640	-29.703	55.343
0.216	9.773	15.410	25.183	-28.931	54.114
0.517	9.742	18.600	28.342	-17.658	46.000
2.834	9.794	21.430	31.224	-14.776	46.000
9.502	9.956	14.970	24.926	-25.074	50.000
18.224	10.066	9.510	19.576	-30.424	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : Bluetooth Module  
 Test Item : Conducted Emission Test  
 Power Line : Line 2  
 Test date : 2017/09/06  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2441MHz)


Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB $\mu$ V	dB $\mu$ V	dB	dB $\mu$ V
<b>LINE 2</b>					
<b>Quasi-Peak</b>					
0.162	9.704	31.700	41.403	-24.254	65.657
0.240	9.755	20.680	30.435	-32.994	63.429
0.494	9.783	23.480	33.262	-22.909	56.171
2.943	9.887	24.560	34.447	-21.553	56.000
9.478	10.016	17.580	27.596	-32.404	60.000
18.599	10.219	16.320	26.539	-33.461	60.000
<b>Average</b>					
0.162	9.704	21.230	30.933	-24.724	55.657
0.240	9.755	8.260	18.015	-35.414	53.429
0.494	9.783	17.280	27.062	-19.109	46.171
2.943	9.887	19.330	29.217	-16.783	46.000
9.478	10.016	9.570	19.586	-30.414	50.000
18.599	10.219	11.780	21.999	-28.001	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

### 3. Peak Power Output

#### 3.1. Test Setup



#### 3.2. Limit

The maximum peak power shall be less 1Watt.

#### 3.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

#### 3.4. Uncertainty

$\pm 1.19$  dB

### 3.5. Test Result of Peak Power Output

Product : Bluetooth Module  
Test Item : Peak Power Output  
Test Site : No.3 OATS  
Test date : 2017/09/04  
Test Mode : Mode 1: Transmit - 1Mbps (GFSK)

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	3.83	1 Watt= 30 dBm	Pass
Channel 39	2441.00	5.76	1 Watt= 30 dBm	Pass
Channel 78	2480.00	3.25	1 Watt= 30 dBm	Pass

Product : Bluetooth Module  
Test Item : Peak Power Output  
Test Site : No.3 OATS  
Test date : 2017/09/04  
Test Mode : Mode 2: Transmit - 3Mbps (8DPSK)


Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	5.45	1 Watt= 30 dBm	Pass
Channel 39	2441.00	7.04	1 Watt= 30 dBm	Pass
Channel 78	2480.00	4.54	1 Watt= 30 dBm	Pass




#### 4. Radiated Emission

##### 4.1. Test Setup


Under 30MHz



Below 1GHz



Above 1GHz



## 4.2. Limits

### ➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

- Remarks:
1. RF Voltage (dB $\mu$ V) = 20 log RF Voltage (uV)
  2. In the Above Table, the tighter limit applies at the band edges.
  3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

### 4.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

### 4.4. Uncertainty

± 4.08 dB above 1GHz

± 4.22 dB below 1GHz

#### 4.5. Test Result of Radiated Emission

Product : Bluetooth Module  
 Test Item : Harmonic Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/11  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(2402MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4804.000	2.511	37.514	40.024	-33.976	74.000
7206.000	9.511	35.641	45.152	-28.848	74.000
9608.000	10.394	36.872	47.266	-26.734	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4804.000	2.923	38.621	41.543	-32.457	74.000
7206.000	9.988	35.479	45.468	-28.532	74.000
9608.000	10.847	36.320	47.167	-26.833	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Bluetooth Module  
 Test Item : Harmonic Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/11  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(2441MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4882.000	2.025	37.409	39.434	-34.566	74.000
7323.000	9.762	35.522	45.283	-28.717	74.000
9764.000	9.682	35.310	44.991	-29.009	74.000
<b>Average</b>					
<b>Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4882.000	2.488	38.839	41.327	-32.673	74.000
7323.000	10.375	35.714	46.088	-27.912	74.000
9764.000	10.315	34.385	44.700	-29.300	74.000
<b>Average</b>					
<b>Detector:</b>					
--					

## Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Bluetooth Module  
 Test Item : Harmonic Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/11  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(2480MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4960.000	2.582	38.520	41.102	-32.898	74.000
7440.000	10.555	35.340	45.895	-28.105	74.000
9920.000	10.206	35.238	45.444	-28.556	74.000
<b>Average</b>					
<b>Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4960.000	3.398	39.113	42.512	-31.488	74.000
7440.000	11.214	35.017	46.231	-27.769	74.000
9920.000	11.245	35.520	46.765	-27.235	74.000
<b>Average</b>					
<b>Detector:</b>					
--					

## Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Bluetooth Module  
 Test Item : Harmonic Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/11  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK)(2402MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level	dB	dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4804.000	2.511	38.547	41.057	-32.943	74.000
7206.000	9.511	35.999	45.510	-28.490	74.000
9608.000	10.394	36.393	46.787	-27.213	74.000
<b>Average</b>					
<b>Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4804.000	2.923	38.235	41.157	-32.843	74.000
7206.000	9.988	35.814	45.803	-28.197	74.000
9608.000	10.847	37.222	48.069	-25.931	74.000
<b>Average</b>					
<b>Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Bluetooth Module  
 Test Item : Harmonic Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/11  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2441MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4882.000	2.025	38.296	40.321	-33.679	74.000
7323.000	9.762	35.917	45.678	-28.322	74.000
9764.000	9.682	35.007	44.688	-29.312	74.000
<b>Average</b>					
<b>Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4882.000	2.488	38.346	40.834	-33.166	74.000
7323.000	10.375	35.530	45.904	-28.096	74.000
9764.000	10.315	35.259	45.574	-28.426	74.000
<b>Average</b>					
<b>Detector:</b>					
--					

## Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product : Bluetooth Module  
 Test Item : Harmonic Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/11  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2480MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4960.000	2.582	38.400	40.982	-33.018	74.000
7440.000	10.555	35.936	46.491	-27.509	74.000
9920.000	10.206	35.284	45.490	-28.510	74.000
<b>Average</b>					
<b>Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4960.000	3.398	38.987	42.386	-31.614	74.000
7440.000	11.214	35.482	46.696	-27.304	74.000
9920.000	11.245	34.185	45.430	-28.570	74.000
<b>Average</b>					
<b>Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Bluetooth Module  
 Test Item : General Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/12  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2441MHz)

Frequency	Correct	Reading	Measurement	Margin	Limit
MHz	Factor	Level	Level		
	dB	dB $\mu$ V	dB $\mu$ V/m	dB	dB $\mu$ V/m
<b>Horizontal</b>					
48.430	-11.893	45.645	33.752	-6.248	40.000
150.280	-7.870	46.608	38.738	-4.762	43.500
257.950	-5.432	43.748	38.316	-7.684	46.000
349.130	-1.309	42.701	41.392	-4.608	46.000
529.550	3.068	36.763	39.831	-6.169	46.000
836.070	6.013	27.381	33.394	-12.606	46.000
<b>Vertical</b>					
153.190	-5.284	38.578	33.294	-10.206	43.500
344.280	-0.584	35.171	34.587	-11.413	46.000
456.800	-3.328	31.747	28.419	-17.581	46.000
545.070	1.305	25.287	26.592	-19.408	46.000
796.300	2.639	25.163	27.802	-18.198	46.000
930.160	3.830	25.600	29.430	-16.570	46.000

## Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Bluetooth Module  
 Test Item : General Radiated Emission  
 Test Site : No.3 OATS  
 Test date : 2017/09/12  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2441MHz)


Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
49.400	-11.553	42.784	31.231	-8.769	40.000
147.370	-7.781	46.637	38.856	-4.644	43.500
345.250	-1.492	41.925	40.434	-5.566	46.000
459.710	3.729	28.917	32.646	-13.354	46.000
576.110	3.127	29.603	32.730	-13.270	46.000
882.630	6.700	23.678	30.378	-15.622	46.000
<b>Vertical</b>					
154.160	-5.272	37.713	32.441	-11.059	43.500
263.770	-4.993	31.358	26.365	-19.635	46.000
343.310	-0.765	33.719	32.954	-13.046	46.000
456.800	-3.328	31.851	28.523	-17.477	46.000
681.840	1.622	27.704	29.326	-16.674	46.000
828.310	2.544	24.470	27.014	-18.986	46.000

## Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

## 5. RF Antenna Conducted Test

### 5.1. Test Setup



### 5.2. Limits

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 5.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.


### 5.4. Uncertainty

$\pm 1.20\text{dB}$


### 5.5. Test Result of RF Antenna Conducted Test

Product : Bluetooth Module  
Test Item : RF Antenna Conducted Test  
Test Site : No.3 OATS  
Test date : 2017/09/04  
Test Mode : Mode 1: Transmit - 1Mbps (GFSK)


**Figure Channel 00:**



**Figure Channel 39:**






**Figure Channel 78:**



Note: The above test pattern is synthesized by multiple of the frequency range.

Product : Bluetooth Module  
Test Item : RF Antenna Conducted Test  
Test Site : No.3 OATS  
Test date : 2017/09/04  
Test Mode : Mode 2: Transmit - 3Mbps (8DPSK)

**Figure Channel 00:****Figure Channel 39:****Figure Channel 78:**


Note: The above test pattern is synthesized by multiple of the frequency range.

## 6. Band Edge


### 6.1. Test Setup

#### RF Radiated Measurement:

Above 1GHz



#### RF Conducted Measurement



### 6.2. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### **6.3. Test Procedure**

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz, respectively.

### **6.4. Uncertainty**

± 4.08 dB above 1GHz

± 4.22 dB below 1GHz



## 6.5. Test Result of Band Edge

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2402MHz)

### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
00 (Peak)	2362.200	6.351	49.443	55.794	74.00	54.00	Pass
00 (Peak)	2390.000	6.474	44.670	51.145	74.00	54.00	Pass
00 (Peak)	2400.000	6.528	50.921	57.449	--	--	--
00 (Peak)	2401.900	6.540	86.799	93.339	--	--	--
00 (Average)	2362.000	6.350	40.579	46.929	74.00	54.00	Pass
00 (Average)	2390.000	6.474	34.324	40.799	74.00	54.00	Pass
00 (Average)	2400.000	6.528	41.186	47.714	--	--	--
00 (Average)	2402.000	6.540	86.319	92.859	--	--	--

Figure Channel 00:

Horizontal (Peak)





Figure Channel 00:

Horizontal (Average)





Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2402MHz)

**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
00 (Peak)	2362.000	5.996	47.876	53.872	74.00	54.00	Pass
00 (Peak)	2390.000	5.880	47.008	52.889	74.00	54.00	Pass
00 (Peak)	2400.000	5.879	47.719	53.598	--	--	--
00 (Peak)	2402.000	5.884	78.528	84.412	--	--	--
00 (Average)	2362.100	5.995	35.327	41.322	74.00	54.00	Pass
00 (Average)	2390.000	5.880	34.436	40.317	74.00	54.00	Pass
00 (Average)	2400.000	5.879	36.992	42.871	--	--	--
00 (Average)	2402.000	5.884	77.980	83.864	--	--	--



**Figure Channel 00:****VERTICAL (Peak)****Figure Channel 00:****VERTICAL (Average)****Note:**

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2480MHz)

**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
78 (Peak)	2479.900	7.085	92.685	99.769	--	--	Pass
78 (Peak)	2483.500	7.110	46.338	53.448	74.00	54.00	Pass
78 (Peak)	2519.900	7.125	50.193	57.318	74.00	54.00	Pass
78 (Average)	2480.000	7.085	92.264	99.349	--	--	Pass
78 (Average)	2483.500	7.110	34.397	41.507	74.00	54.00	Pass
78 (Average)	2520.000	7.125	42.494	49.619	74.00	54.00	Pass



**Figure Channel 78: Horizontal (Peak)****Figure Channel 78: Horizontal (Average)****Note:**

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (2480MHz)

**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Average Limit (dB $\mu$ V/m)	Result
78 (Peak)	2479.800	6.341	83.711	90.051	--	--	Pass
78 (Peak)	2483.500	6.363	46.601	52.964	74.00	54.00	Pass
78 (Peak)	2520.100	6.465	47.954	54.419	74.00	54.00	Pass
78 (Average)	2480.000	6.342	83.221	89.562	--	--	Pass
78 (Average)	2483.500	6.363	33.720	40.083	74.00	54.00	Pass
78 (Average)	2520.000	6.465	36.003	42.468	74.00	54.00	Pass



**Figure Channel 78: VERTICAL (Peak)****Figure Channel 78: VERTICAL (Average)****Note:**

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2402MHz)

**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
00 (Peak)	2362.200	6.351	49.232	55.583	74.00	54.00	Pass
00 (Peak)	2390.000	6.474	45.924	52.399	74.00	54.00	Pass
00 (Peak)	2400.000	6.528	59.115	65.643	--	--	--
00 (Peak)	2402.000	6.540	87.885	94.425	--	--	--
00 (Average)	2362.000	6.350	39.171	45.521	74.00	54.00	Pass
00 (Average)	2390.000	6.474	34.288	40.763	74.00	54.00	Pass
00 (Average)	2400.000	6.528	47.772	54.300	--	--	--
00 (Average)	2402.000	6.540	84.210	90.750	--	--	--



**Figure Channel 00:****Horizontal (Peak)****Figure Channel 00:****Horizontal (Average)****Note:**

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2402MHz)

**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Average Limit (dB $\mu$ V/m)	Result
00 (Peak)	2389.100	5.884	47.460	53.344	74.00	54.00	Pass
00 (Peak)	2390.000	5.880	46.144	52.025	74.00	54.00	Pass
00 (Peak)	2400.000	5.879	51.333	57.212	--	--	--
00 (Peak)	2402.000	5.884	78.890	84.774	--	--	--
00 (Average)	2361.900	5.996	34.675	40.671	74.00	54.00	Pass
00 (Average)	2390.000	5.880	34.370	40.251	74.00	54.00	Pass
00 (Average)	2400.000	5.879	40.858	46.737	--	--	--
00 (Average)	2402.000	5.884	75.209	81.093	--	--	--

**Figure Channel 00:****VERTICAL (Peak)****Figure Channel 00:****VERTICAL (Average)**



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " \* ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2480MHz)

**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Average Limit (dB $\mu$ V/m)	Result
78 (Peak)	2480.000	7.085	93.306	100.391	--	--	Pass
78 (Peak)	2483.500	7.110	46.201	53.311	74.00	54.00	Pass
78 (Peak)	2520.200	7.123	49.697	56.821	74.00	54.00	Pass
78 (Average)	2480.000	7.085	89.871	96.956	--	--	Pass
78 (Average)	2483.500	7.110	34.387	41.497	74.00	54.00	Pass
78 (Average)	2519.800	7.126	40.791	47.917	74.00	54.00	Pass

**Figure Channel 00:****Horizontal (Peak)****Figure Channel 00:****Horizontal (Average)**



Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. " \* ", means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.

Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test date : 2017/09/06  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2480MHz)

**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Average Limit (dB $\mu$ V/m)	Result
78 (Peak)	2479.900	6.341	84.806	91.147	--	--	Pass
78 (Peak)	2483.500	6.363	45.719	52.082	74.00	54.00	Pass
78 (Peak)	2520.400	6.465	47.882	54.347	--	--	Pass
78 (Average)	2480.000	6.342	81.334	87.675	--	--	Pass
78 (Average)	2483.500	6.363	33.737	40.100	74.00	54.00	Pass
78 (Average)	2519.700	6.465	35.305	41.771	74.00	54.00	Pass

**Figure Channel 78: VERTICAL (Peak)****Figure Channel 78: VERTICAL (Average)****Note:**

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. “ \* ”, means this data is the worst emission level.
5. Measurement Level = Reading Level + Correction Factor.
6. The average measurement was not performed when the peak measured data is under the limit of average detection.



Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(Hopping off)

Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

Figure Channel 00:





Figure Channel 78:



Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (Hopping off)

Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

Figure Channel 00:





Figure Channel 78:



Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)(Hopping on)

Measurement Level	Result
$\Delta$ (dB)	
> 20	PASS

Figure Channel 00 Hopping:





Figure Channel 78 Hopping:



Product : Bluetooth Module  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (Hopping on)

Measurement Level $\Delta$ (dB)	Result
> 20	PASS

Figure Channel 00 Hopping:






Figure Channel 78 Hopping:



## 7. Channel Number

### 7.1. Test Setup



### 7.2. Limit

Frequency hopping systems operating in the 2400-2483.5 MHz bands shall use at least 75 hopping frequencies.

### 7.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

### 7.4. Uncertainty


N/A

## 7.5. Test Result of Channel Number


Product : Bluetooth Module  
 Test Item : Channel Number  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)

Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>75	Pass


2402-2421MHz




2422-2441MHz



2442-2461MHz



2462-2480MHz







Product : Bluetooth Module  
 Test Item : Channel Number  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK)

Frequency Range (MHz)	Measurement (Hopping Channel)	Required Limit (Hopping Channel)	Result
2402 ~ 2480	79	>75	Pass


2402-2421MHz




2422-2441MHz



2442-2461MHz




2462-2480MHz



## 8. Channel Separation

### 8.1. Test Setup



### 8.2. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

### 8.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

### 8.4. Uncertainty

$\pm 283\text{Hz}$




### 8.5. Test Result of Channel Separation

Product : Bluetooth Module  
 Test Item : Channel Separation  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Limit (kHz)	Limit of (2/3)*20dB Bandwidth (kHz)	Result
00	2402	1000	>25 kHz	696.0	Pass
39	2441	1000	>25 kHz	702.0	Pass
78	2480	1000	>25 kHz	698.0	Pass

NOTE: The 20dB Bandwidth is refer to section 10.


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




Product : Bluetooth Module  
 Test Item : Channel Separation  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK)


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Limit (kHz)	Limit of (2/3)*20dB Bandwidth (kHz)	Result
00	2402	1000	>25 kHz	872.0	Pass
39	2441	1000	>25 kHz	894.0	Pass
78	2480	1000	>25 kHz	892.0	Pass

NOTE: The 20dB Bandwidth is refer to section 10.


### Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)



## 9. Dwell Time

### 9.1. Test Setup



### 9.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 9.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

### 9.4. Uncertainty

$\pm 25\text{msec}$

## 9.5. Test Result of Dwell Time


Product : Bluetooth Module  
 Test Item : Dwell Time  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK) (Channel 00,39,78 –DH5)

Frequency (MHz)	Time slot length (ms)	Hopping of Number	Sweep time (ms)	Duty cycle	Dwell Time (Sec)	Limit (Sec)	Result
2402	2.867	16	50	0.92	0.367	0.4	Pass
2441	2.867	16	50	0.92	0.367	0.4	Pass
2480	2.847	16	50	0.91	0.364	0.4	Pass


Duty cycle = ((Time slot length(ms)\*Hopping of Number) / Sweep time (ms)

Dwell time = (Duty cycle /79) \* (79\*0.4)


CH 00 Time Interval between hops




CH 00 Transmission Time



CH39 Time Interval between hops




CH39 Transmission Time



## CH 78 Time Interval between hops

## CH 78 Transmission Time



Note:

The dwell times of the packet type of DH1, DH3, and DH5 are tested. Only the worst case is shown on the report.


Product : Bluetooth Module  
 Test Item : Dwell Time  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (Channel 00,39,78 –DH5)

Frequency (MHz)	Time slot length (ms)	Hopping of Number	Sweep time (ms)	Duty cycle	Dwell Time (Sec)	Limit (Sec)	Result
2402	2.887	16	50	0.92	0.370	0.4	Pass
2441	2.877	16	50	0.92	0.368	0.4	Pass
2480	2.887	16	50	0.92	0.370	0.4	Pass


Duty cycle = ((Time slot length(ms)\*Hopping of Number) / Sweep time (ms))

Dwell time = (Duty cycle / 79) \* (79\*0.4)


CH 00 Time Interval between hops




CH 00 Transmission Time



CH39 Time Interval between hops




CH39 Transmission Time





CH 78 Time Interval between hops

CH 78 Transmission Time




Note:

The dwell times of the packet type of DH1, DH3, and DH5 are tested. Only the worst case is shown on the report.

## 10. Occupied Bandwidth

### 10.1. Test Setup



### 10.2. Limits

N/A

### 10.3. Test Procedure

The EUT was setup to ANSI C63.4, 2014; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

### 10.4. Uncertainty

$\pm 283\text{Hz}$

### 10.5. Test Result of Occupied Bandwidth

Product : Bluetooth Module  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit - 1Mbps (GFSK)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	1044	--	NA
39	2441	1053	--	NA
78	2480	1047	--	NA

**Figure Channel 00:**




Figure Channel 39:





Figure Channel 78:



Product : Bluetooth Module  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit - 3Mbps (8DPSK) (2402MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	1308	--	NA
39	2441	1341	--	NA
78	2480	1338	--	NA

Figure Channel 00:




Figure Channel 39:





Figure Channel 78:



## **11. EMI Reduction Method During Compliance Testing**

No modification was made during testing.

## Attachment 1: EUT Test Photographs



## Attachment 2: EUT Detailed Photographs