

Test Report

T-0249-3677-01 JP

Type / Model Name: AW-GH321

FCC ID: YM6-AWGH321

Product Description: WLAN module

Applicant: MSC Freiburg GmbH

EMC -- TEST REPORT

Test Report No. :	T-0249-3677-01 JP	2011-07-18 Date of issue
--------------------------	--------------------------	-----------------------------

Type / Model Name : AW-GH321

FCC ID: YM6-AWGH321

Product Description : WLAN module

Applicant : MSC Freiburg GmbH

Address : August-Wessels-Str. 17

86156 Augsburg

Germany

Manufacturer : MSC Freiburg GmbH

Address : Munzinger Str. 3

79111 Freiburg

Germany

Test Result according to the standards listed in clause 1 test standards:	POSITIVE
--	-----------------



DAT-P-121/02-01
KBA-P 00057-01

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

File No. **T-0249-3677-01 JP**

Contents

1	<u>TEST STANDARDS</u>	4
2	<u>OVERVIEW TEST RESULT</u>	5
3	<u>SUMMARY</u>	6
4	<u>EQUIPMENT UNDER TEST</u>	7
4.1	PHOTO DOCUMENTATION OF THE EUT	7
4.2	POWER SUPPLY SYSTEM	10
4.3	SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)	10
5	<u>TEST ENVIRONMENT</u>	11
5.1	ADDRESS OF THE TEST LABORATORY	11
5.2	ENVIRONMENTAL CONDITIONS	11
5.3	STATEMENT OF THE MEASUREMENT UNCERTAINTY	11
5.4	MEASUREMENT PROTOCOL FOR FCC, VCCI AND AUSTEL	12
6	<u>TEST CONDITIONS AND RESULTS</u>	14
6.1	CONDUCTED DISTURBANCE	14
6.2	RADIATED DISTURBANCE IN THE FREQUENCY RANGE 9kHz – 30MHz	27
6.3	RADIATED DISTURBANCE IN THE FREQUENCY RANGE 30MHz – 1000MHz	34
6.4	RADIATED DISTURBANCE IN THE FREQUENCY RANGE 1GHz – 25GHz	53
6.5	RESTRICTED BANDEDGES	71
6.6	6dB BANDWIDTH	84
6.7	MAXIMUM CONDUCTED OUTPUT POWER	89
6.8	POWER SPECTRAL DENSITY	94
6.9	CONDUCTED SPURIOUS EMISSIONS 30 MHz – 25GHz	99
7	<u>USED TEST EQUIPMENT AND ACCESSORIES</u>	106

File No. **T-0249-3677-01 JP**

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Part 15 Subpart A : 2009	Code of Regulations Part 15 (Radio Frequency Devices), Subpart A (General) of the Federal Communication Commission (FCC)
FCC Part 15 Subpart C : 2009	Code of Regulations Part 15 (Radio Frequency Devices), Subpart C (Intentional Radiators) of the Federal Communication Commission (FCC) Applied Paragraphs: §15.207, §15.209, §15.247
ANSI C63.4-2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz – 40 GHz

File No. **T-0249-3677-01 JP**

2 OVERVIEW TEST RESULT

Performed test(s)	Result		
	Passed	Failed	Not performed
Conducted disturbance	X		
Radiated disturbance in the frequency range 9kHz – 30MHz	X		
Radiated disturbance in the frequency range 30MHz – 1000MHz	X		
Radiated disturbance in the frequency range 1GHz – 25GHz	X		
Restricted Bandedges	X		
6dB Bandwidth	X		
Maximum Conducted Output Power	X		
Power spectral density	X		
Conducted spurious emissions in the frequency range 30MHz – 25GHz	X		

File No. **T-0249-3677-01 JP**

3 SUMMARY

GENERAL REMARKS:

The EUT has a TX mode and a RX mode but RX is without TX beacons not possible therefore the measurements were performed in TX mode only. The frequency range was scanned from 9 kHz to 25GHz.

FINAL ASSESSMENT:

The equipment under test **fulfills** the EMC requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 2010-08-10

Testing concluded on : 2010-08-20

Checked by:

Tested by:


Frank Scharnowski
Quality Manager

Jürgen Pessinger


File No. **T-0249-3677-01 JP**

4 EQUIPMENT UNDER TEST


4.1 Photo documentation of the EuT




File No. **T-0249-3677-01 JP**




Antenna:



File No. **T-0249-3677-01 JP**



Periphery:



File No. **T-0249-3677-01 JP**

4.2 Power supply system

Power supply voltage: 3,3V DC

4.3 Short description of the Equipment under Test (EuT)

Number of tested samples: 1
Serial number: none

Dimensions: L: 53mm W: 30mm H: 4mm

Radio equipment characteristics

Frequency band(s): 2400 – 2483,5 MHz
Operating frequency: 2412 – 2462 MHz
Channel spacing: 5MHz
Number of RF-channels: 11
Comments: None

EuT operation mode:

The equipment under test was operated during the measurement under the following conditions:

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

Transmission mode IEEE 802.11b (Datatransfer rate 11Mbps) and IEEE 802.11g (Datatransfer rate 54Mbps) were tested in following channels:

- CH01 2412MHz
- CH06 2437MHz
- CH11 2462MHz

EuT configuration:

The following interface cables and peripheral devices were connected during the measurements:

Interface cables:

Interface cable	Length [m]	Type	Line		Line termination
			shielded	unshielded	
Antenna cable	0,3	1-wires	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Antenna

Peripheral devices:

Kind of equipment		Model and/or Manufacturer
Antenna		WE-MCA, Würth Elektronik
Motherboard		LY4003582_AGC_DV4-Main, MSC Freiburg

File No. **T-0249-3677-01 JP**

5 TEST ENVIRONMENT

5.1 Address of the test laboratory

**emitel AG
Ohmstrasse 1
94342 STRASSKIRCHEN
DEUTSCHLAND**

Laboratory registration numbers:

DAR Registration number:	DAT-P-121/02-01
DAR Registration number:	KBA-P 00057-01
SNCH Registration number:	SNCH 001/2005 ext 01
FCC Registration number:	765810
IC Registration number:	IC 5066A-1
VCCI Registration number:	T-215; C-3049; R-2765

5.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

All atmospheric pressure values refer to our Laboratory altitude of 324m.

5.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 /11.2003 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer does have the sole responsibility for the continued compliance of the device.

File No. **T-0249-3677-01 JP**

5.4 Measurement Protocol for FCC, VCCI and AUSTEL

5.4.1 GENERAL INFORMATION

5.4.1.1 Test Methodology

Conducted and radiated disturbance testing is performed according to the procedures in International Special Committee on Radio Interference (CISPR) Publication 22 (1997+A1:2000+A2:2002), European Standard EN 55022 (1998+A1:2000+A2:2003) and Australian Standard AS 3548 (which are based on CISPR 22).

The Japanese standard, "Voluntary Control Council for Interference (VCCI) by Data Processing Equipment and Electronic Office Machines, Technical Requirements" is technically equivalent to CISPR 22 (1997+A1:2000+A2:2002). For official compliance, a conformance report must be sent to and accepted by the VCCI.

In compliance with FCC Docket 92-152, "Harmonization of Rules for Digital Devices Incorporate International Standards", testing for FCC compliance may be done following the ANSI C63.4-2003 procedures and using the CISPR 22 Limits.

5.4.1.2 Measurement Error

The data and results referenced in this document are true and accurate. The reader is cautioned that there is some measurement variability due to the tolerances of the test equipment that can contribute to a nominal product measurement uncertainty. The measurement uncertainty was calculated for all measurements listed in this test report according to NIS 81/5.1994 "The treatment of uncertainty in EMC measurements" and is documented in the emitel AG quality system according to DIN EN ISO/IEC 17025. Furthermore, component differences and manufacturing process variability of production units similar to that tested may result in additional product uncertainty. If necessary, refer to the test lab for the actual measurement uncertainty for specific tests. The manufacturer has the sole responsibility of continued compliance of the device.

5.4.1.3 Justification

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left unterminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum disturbances from the unit.

5.4.2 CONDUCTED DISTURBANCE

The final level, expressed in dB μ V, is arrived at by taking the reading directly from the EMI receiver. This level is compared directly to the CISPR limit, which is equivalent to the Australian AS 3548 limit.

To convert between dB μ V and μ V, the following conversions apply:

$$\text{dB}\mu\text{V} = 20(\log \mu\text{V})$$

$$\mu\text{V} = \text{Inverse log}(\text{dB}\mu\text{V}/20)$$

File No. **T-0249-3677-01 JP**

5.4.3 RADIATED DISTURBANCE

The final level, expressed in dB μ V/m, is arrived at by taking the reading from the EMI receiver (Level dB μ V) and adding the antenna correction factor and cable loss factor (Factor dB) to it. This is done automatically in the EMI receiver, where the correction factor are stored. This result then has the CISPR limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets in section 5.2. The CISPR 22 limit is equivalent to the Australian AS 3548 limit.

Example:	CISPR B	Delta						
Frequency	Level	+	Factor	=	Final	-	Limit	=
(MHz)	(dB μ V)		(dB)		(dB μ V/m)		(dB μ V/m)	
								CISPR B
								(dB)
37.19	10.2	+	12.0	=	22.2	-	40.0	=
								-17.8

5.4.4 DETAILS OF TEST PROCEDURES

5.4.4.1 General Standard Information

The test methods used comply with CISPR Publication 22 (1997+A1:2000+A2:2002), EN 55022 (1998+A1:2000+A2:2003) and AS 3548 (1992) - "Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment" and with ANSI C63.4-2003 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

5.4.4.2 Conducted disturbance

Conducted disturbance on the 50 Hz and/or 60 Hz power interface of the EUT are measured in the frequency range of 150 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi peak detection, and a Line Impedance Stabilization Network (LISN), with 50 Ω /50 μ H (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 centimetres above the floor and is positioned 40 centimetres from the vertical ground plane (wall) of the screen room. If the minimum passing margin appears to be less than 20 dB with a peak mode measurement, the emissions are remeasured using a tuned receiver with quasi peak and average detection and recorded on the data sheets.

5.4.4.3 Radiated disturbance

Radiated disturbance from the EUT are measured in the frequency range of 30 to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi peak detection and measurements above 1000 MHz are made with a 1 MHz/6 dB bandwidth and average detection. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Interface cables that are closer than 40 centimetres to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimetres from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna was positioned 3, 10 or 30 meters horizontally from the EUT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarizations and the EUT are rotated 360 degrees.

File No. **T-0249-3677-01 JP**

6 TEST CONDITIONS AND RESULTS


6.1 Conducted disturbance

For test instruments and accessories used see section 7 Part A 4.

6.1.1 Description of the test location

Test location: Shielded Room SK5

6.1.2 Photo documentation of the test set-up



6.1.3 Test specification

Environmental conditions: Temperature: 24 ° C Humidity: 50 % Atmospheric pressure: 97 kPa

Frequency range: 0.15 MHz - 30 MHz

The test was carried out in the following operation mode(s):

- continous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.1.4 Test result

The requirements are **FULFILLED**.


Remarks: The measurement was made at AC input port of AC/DC power supply.

Used AC/DC power supply: PeakTech 6000A, emitel ID: 01-05/50-05-005

File No. **T-0249-3677-01 JP**

6.1.5 Test protocol

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase L1
Remark:	none




Minimum margin to limit: -12,4 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV]		Limit [dBμV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	43,6	12,3	0,0	43,6	12,3	56,0	46,0	-12,4	-33,7

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase N
Remark:	none




Minimum margin to limit: -12,6 dB

Frequency [MHz]	Reading [dBµV] QP	Reading [dBµV] AV	Correction [dB]	Values [dBµV] QP	Values [dBµV] AV	Limit [dBµV] QP	Limit [dBµV] AV	Margin [dB] QP	Margin [dB] AV
1,190	43,4	14,1	0,0	43,4	14,1	56,0	46,0	-12,6	-31,9

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase L1
Remark:	none




Minimum margin to limit: -12,6 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV]		Limit [dBμV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	43,4	10,2	0,0	43,4	10,2	56,0	46,0	-12,6	-35,8

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase N
Remark:	none




Minimum margin to limit: -12,5 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV]		Limit [dBµV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	43,5	13,4	0,0	43,5	13,4	56,0	46,0	-12,5	-32,6

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase L1
Remark:	none




Minimum margin to limit: -12,7 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV]		Limit [dBμV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	43,3	12,1	0,0	43,3	12,1	56,0	46,0	-12,7	-33,9

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase N
Remark:	none




Minimum margin to limit: -12,5 dB

Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV]	Limit [dBµV]	Margin [dB]
	QP		QP	QP	QP
	AV		AV	AV	AV
1,190	43,5	0,0	43,5	56,0	-12,5
	13,3		13,3	46,0	-32,7

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase L1
Remark:	none




Minimum margin to limit: -12,4 dB

Frequency [MHz]	Reading [dBµV] QP	Reading [dBµV] AV	Correction [dB]	Values [dBµV] QP	Values [dBµV] AV	Limit [dBµV] QP	Limit [dBµV] AV	Margin [dB] QP	Margin [dB] AV
1,190	43,6	15,9	0,0	43,6	15,9	56,0	46,0	-12,4	-30,1

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 54Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase L1
Remark:	none




Minimum margin to limit: -12,5 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV]		Limit [dBμV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	43,5	15,7	0,0	43,5	15,7	56,0	46,0	-12,5	-30,3

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 54Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase N
Remark:	none




Minimum margin to limit: -13,0 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV]		Limit [dBµV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	43,0	14,4	0,0	43,0	14,4	56,0	46,0	-13,0	-31,6

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase L1
Remark:	none




Minimum margin to limit: -14,4 dB

Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV]	Limit [dBµV]	Margin [dB]
	QP	AV	QP	AV	QP
1,190	41,6	12,3	41,6	12,3	56,0
					46,0
					-14,4
					-33,7

File No. T-0249-3677-01 JP

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC Part 15.207
Test:	Conducted Emission Test
Detector:	QP / AV
Result:	Limit kept
Applied to:	Phase N
Remark:	none



Minimum margin to limit: -13,3 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV]		Limit [dBµV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
1,190	42,7	12,8	0,0	42,7	12,8	56,0	46,0	-13,3	-33,2

File No. T-0249-3677-01 JP

6.2 Radiated disturbance in the frequency range 9kHz – 30MHz


For test instruments and accessories used see section 7 Part SER 1.

6.2.1 Description of the test location

Test location: Shielded Room SK5

Test distance: 2 metres

6.2.2 Photo documentation of the test set-up



6.2.3 Test specification

Environmental conditions: Temperature: 24 °C Humidity: 50 % Atmospheric pressure: 97 kPa

Frequency range: 0.009 MHz - 30 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.2.4 Test result


The requirements are **FULFILLED**.

Remarks: The prescan shows that the Peak value is below the Average / QuasiPeak limit, therefore
no final measurement was made.

File No. **T-0249-3677-01 JP**


6.2.5 Test protocol

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC Part 15.209
Test:	Radiated Emission Test
Detector:	No QuasiPeak / Average measurement was made because the Peak values are below the AV / QP Limit
Result:	Limit kept
Remark:	none




File No. **T-0249-3677-01 JP**

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC Part 15.209
Test:	Radiated Emission Test
Detector:	No QuasiPeak / Average measurement was made because the Peak values are below the AV / QP Limit
Result:	Limit kept
Remark:	none




File No. **T-0249-3677-01 JP**

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC Part 15.209
Test:	Radiated Emission Test
Detector:	No QuasiPeak / Average measurement was made because the Peak values are below the AV / QP Limit
Result:	Limit kept
Remark:	none




File No. **T-0249-3677-01 JP**

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC Part 15.209
Test:	Radiated Emission Test
Detector:	No QuasiPeak / Average measurement was made because the Peak values are below the AV / QP Limit
Result:	Limit kept
Remark:	none




File No. **T-0249-3677-01 JP**

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC Part 15.209
Test:	Radiated Emission Test
Detector:	No QuasiPeak / Average measurement was made because the Peak values are below the AV / QP Limit
Result:	Limit kept
Remark:	none



File No. **T-0249-3677-01 JP**

Date of test:	2010-08-18
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC Part 15.209
Test:	Radiated Emission Test
Detector:	No QuasiPeak / Average measurement was made because the Peak values are below the AV / QP Limit
Result:	Limit kept
Remark:	none



File No. **T-0249-3677-01 JP**

6.3 Radiated disturbance in the frequency range 30MHz – 1000MHz


For test instruments and accessories used see section 7 Part SER 2.

6.3.1 Description of the test location

Test location: OATS 1

Test distance: 3 metres

6.3.2 Photo documentation of the test set-up



6.3.3 Test specification

Environmental conditions: Temperature: 24 ° C Humidity: 50 % Atmospheric pressure: 98 kPa

Frequency range: 30 MHz - 1000 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.3.4 Test result


The requirements are **FULFILLED**.

Remarks: none

File No. **T-0249-3677-01 JP**

6.3.5 Test protocol

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -1,3 dB

Frequency [MHz]	Reading [dBμV] QP	Correction [dB]	Values [dBμV/m] QP	Limit [dBμV/m] QP	Margin [dB] QP
125,000	8,8	11,6	20,4	43,5	-23,1
197,997	22,8	13,3	36,1	43,5	-7,5
329,999	24,6	17,4	42,0	46,0	-4,0
375,000	18,5	18,4	36,9	46,0	-9,1
396,000	24,2	18,9	43,1	46,0	-3,0
461,997	24,2	20,2	44,4	46,0	-1,6
527,997	22,8	21,7	44,5	46,0	-1,5
593,998	13,8	22,9	36,7	46,0	-9,3
625,000	17,7	23,6	41,3	46,0	-4,7
660,000	17,9	23,8	41,7	46,0	-4,3
726,000	17,3	24,9	42,2	46,0	-3,8
783,751	15,5	25,6	41,1	46,0	-4,9
791,998	19,1	25,7	44,8	46,0	-1,3
875,000	14,5	26,6	41,1	46,0	-4,9
924,000	16,3	27,1	43,4	46,0	-2,6
990,000	6,9	27,9	34,8	54,0	-19,2

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Vertical
Remark:	none




Minimum margin to limit: -6,7 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
66,000	8,0	11,7	19,7	40,0	-20,3
330,000	15,7	17,4	33,1	46,0	-12,9
462,000	12,3	20,2	32,5	46,0	-13,5
924,000	12,2	27,1	39,3	46,0	-6,7
990,000	10,4	27,9	38,3	54,0	-15,7

File No. T-0249-3677-01 JP

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -1,4 dB

Frequency [MHz]	Reading [dBμV] QP	Correction [dB]	Values [dBμV/m] QP	Limit [dBμV/m] QP	Margin [dB] QP
125,000	8,9	11,6	20,5	43,5	-23,0
197,997	23,7	13,3	37,0	43,5	-6,6
329,999	23,9	17,4	41,3	46,0	-4,7
375,000	18,7	18,4	37,1	46,0	-8,9
396,000	24,2	18,9	43,1	46,0	-3,0
461,997	24,4	20,2	44,6	46,0	-1,4
527,997	21,9	21,7	43,6	46,0	-2,4
593,998	12,8	22,9	35,7	46,0	-10,3
625,000	17,8	23,6	41,4	46,0	-4,6
660,000	18,4	23,8	42,2	46,0	-3,8
726,000	16,3	24,9	41,2	46,0	-4,8
783,751	14,3	25,6	39,9	46,0	-6,1
791,998	18,7	25,7	44,4	46,0	-1,7
875,000	13,9	26,6	40,5	46,0	-5,5
924,000	16,3	27,1	43,4	46,0	-2,6
990,000	7,2	27,9	35,1	54,0	-18,9

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Vertical
Remark:	none




Minimum margin to limit: -7,0 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
66,000	8,3	11,7	20,0	40,0	-20,0
330,000	15,7	17,4	33,1	46,0	-12,9
462,000	12,1	20,2	32,3	46,0	-13,7
924,000	11,9	27,1	39,0	46,0	-7,0
990,000	10,3	27,9	38,2	54,0	-15,8

File No. T-0249-3677-01 JP

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -1,6 dB

Frequency [MHz]	Reading [dBμV] QP	Correction [dB]	Values [dBμV/m] QP	Limit [dBμV/m] QP	Margin [dB] QP
125,000	8,8	11,6	20,4	43,5	-23,1
197,997	24,2	13,3	37,5	43,5	-6,1
329,999	23,9	17,4	41,3	46,0	-4,7
375,000	17,9	18,4	36,3	46,0	-9,7
396,000	23,7	18,9	42,6	46,0	-3,5
461,997	24,2	20,2	44,4	46,0	-1,6
527,997	22,3	21,7	44,0	46,0	-2,0
593,998	12,7	22,9	35,6	46,0	-10,4
625,000	17,9	23,6	41,5	46,0	-4,5
660,000	18,0	23,8	41,8	46,0	-4,2
726,000	16,9	24,9	41,8	46,0	-4,2
783,751	12,7	25,6	38,3	46,0	-7,7
791,998	18,6	25,7	44,3	46,0	-1,8
875,000	14,7	26,6	41,3	46,0	-4,7
924,000	13,4	27,1	40,5	46,0	-5,5
990,000	8,9	27,9	36,8	54,0	-17,2

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Vertical
Remark:	none




Minimum margin to limit: -7,2 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
66,000	8,7	11,7	20,4	40,0	-19,6
330,000	14,9	17,4	32,3	46,0	-13,7
462,000	13,2	20,2	33,4	46,0	-12,6
924,000	11,7	27,1	38,8	46,0	-7,2
990,000	10,2	27,9	38,1	54,0	-15,9

File No. T-0249-3677-01 JP

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -1,0 dB

Frequency [MHz]	Reading [dBμV] QP	Correction [dB]	Values [dBμV/m] QP	Limit [dBμV/m] QP	Margin [dB] QP
66,000	9,7	11,7	21,4	40,0	-18,6
198,000	24,9	13,3	38,2	43,5	-5,4
330,000	23,3	17,4	40,7	46,0	-5,3
395,999	22,8	18,9	41,7	46,0	-4,4
462,000	24,7	20,2	44,9	46,0	-1,1
528,000	20,4	21,7	42,1	46,0	-3,9
625,000	19,9	23,6	43,5	46,0	-2,5
726,000	16,0	24,9	40,9	46,0	-5,1
792,000	19,4	25,7	45,1	46,0	-1,0
875,000	13,5	26,6	40,1	46,0	-5,9
924,000	16,0	27,1	43,1	46,0	-2,9

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Vertical
Remark:	none




Minimum margin to limit: -6,7 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
66,000	11,9	11,7	23,6	40,0	-16,4
198,000	13,0	13,3	26,3	43,5	-17,3
330,400	14,3	17,4	31,7	46,0	-14,3
462,000	19,1	20,2	39,3	46,0	-6,7
990,000	15,4	27,9	43,3	54,0	-10,7

File No. T-0249-3677-01 JP

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -1,2 dB

Frequency [MHz]	Reading [dBμV] QP	Correction [dB]	Values [dBμV/m] QP	Limit [dBμV/m] QP	Margin [dB] QP
66,000	9,7	11,7	21,4	40,0	-18,6
198,000	25,8	13,3	39,1	43,5	-4,5
330,000	23,5	17,4	40,9	46,0	-5,1
395,999	23,1	18,9	42,0	46,0	-4,1
462,000	24,4	20,2	44,6	46,0	-1,4
528,000	21,3	21,7	43,0	46,0	-3,0
625,000	19,4	23,6	43,0	46,0	-3,0
726,000	15,1	24,9	40,0	46,0	-6,0
792,000	19,2	25,7	44,9	46,0	-1,2
875,000	14,3	26,6	40,9	46,0	-5,1
924,000	16,0	27,1	43,1	46,0	-2,9

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Vertical
Remark:	none




Minimum margin to limit: -6,5 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
66,000	13,1	11,7	24,8	40,0	-15,2
198,000	12,9	13,3	26,2	43,5	-17,4
330,400	14,7	17,4	32,1	46,0	-13,9
462,000	19,3	20,2	39,5	46,0	-6,5
990,000	14,9	27,9	42,8	54,0	-11,2

File No. T-0249-3677-01 JP

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -0,7 dB

Frequency [MHz]	Reading [dBμV] QP	Correction [dB]	Values [dBμV/m] QP	Limit [dBμV/m] QP	Margin [dB] QP
66,000	9,9	11,7	21,6	40,0	-18,4
198,000	25,0	13,3	38,3	43,5	-5,3
330,000	23,9	17,4	41,3	46,0	-4,7
395,999	24,2	18,9	43,1	46,0	-3,0
462,000	25,1	20,2	45,3	46,0	-0,7
528,000	20,7	21,7	42,4	46,0	-3,6
625,000	19,5	23,6	43,1	46,0	-2,9
726,000	15,9	24,9	40,8	46,0	-5,2
792,000	18,7	25,7	44,4	46,0	-1,7
875,000	14,2	26,6	40,8	46,0	-5,2
924,000	16,3	27,1	43,4	46,0	-2,6

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-20
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	QP
Result:	Limit kept
Applied to:	Vertical
Remark:	none



Minimum margin to limit: -6,9 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
66,000	12,2	11,7	23,9	40,0	-16,1
198,000	13,8	13,3	27,1	43,5	-16,5
330,400	15,2	17,4	32,6	46,0	-13,4
462,000	18,9	20,2	39,1	46,0	-6,9
990,000	15,8	27,9	43,7	54,0	-10,3

File No. T-0249-3677-01 JP

6.4 Radiated disturbance in the frequency range 1GHz – 25GHz


For test instruments and accessories used see section 7 Part SER 3.

6.4.1 Description of the test location

Test location: Anechoic Chamber A4

Test distance: 3 metres

6.4.2 Photo documentation of the test set-up



6.4.3 Test specification

Environmental conditions: Temperature: 25 ° C Humidity: 48 % Atmospheric pressure: 97 kPa

Frequency range: 1000 MHz - 25000 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.4.4 Test result


The requirements are **FULFILLED**.

Remarks: none

File No. **T-0249-3677-01 JP**

6.4.5 Test protocol

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Horizontal
Remark:	none



Minimum margin to limit: -11,3 dB


Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3300,000	46,9	34,8	-3,1	43,8	31,7	74,0	54,0	-30,1	-22,3
3630,000	47,1	35,0	-2,4	44,7	32,6	74,0	54,0	-29,3	-21,4
4800,000	45,2	--	-0,3	44,9	--	74,0	54,0	-29,1	--
5220,000	47,4	33,5	0,9	48,3	34,4	74,0	54,0	-25,7	-19,6
6030,000	46,0	--	1,4	47,4	--	74,0	54,0	-26,6	--
7230,000	52,1	38,3	4,3	56,4	42,6	74,0	54,0	-17,6	-11,3
9780,000	45,5	33,5	6,4	51,9	39,8	74,0	54,0	-22,0	-14,1
11970,000	45,3	32,7	8,6	53,9	41,3	74,0	54,0	-20,1	-12,7
14550,000	41,8	--	9,9	51,7	--	74,0	54,0	-22,3	--

File No. T-0249-3677-01 JP

Minimum margin to limit: -6,1 dB									
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3120,000	49,4	35,7	-3,3	46,1	32,4	74,0	54,0	-27,9	-21,6
3300,000	52,8	36,9	-3,1	49,7	33,8	74,0	54,0	-24,3	-20,1
3780,000	48,4	35,6	-1,4	47,0	34,2	74,0	54,0	-27,0	-19,8
4290,000	48,8	34,5	-1,8	47,0	32,8	74,0	54,0	-27,0	-21,2
4620,000	49,7	35,2	-0,9	48,8	34,3	74,0	54,0	-25,2	-19,7
5280,000	47,6	34,9	0,8	48,4	35,7	74,0	54,0	-25,6	-18,3
7236,000	57,9	43,6	4,3	62,3	47,9	74,0	54,0	-11,7	-6,1
9480,000	44,7	--	6,3	51,0	--	74,0	54,0	-23,0	--
12120,000	44,2	--	8,1	52,3	--	74,0	54,0	-21,7	--

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




Minimum margin to limit: -12,4 dB

Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	Pk	AV	Pk	AV	Pk
3210,000	46,7	35,0	43,5	31,9	74,0
3630,000	47,9	35,2	45,5	32,8	74,0
4860,000	48,9	35,2	48,8	35,1	74,0
5940,000	45,7	--	47,0	--	74,0
7320,000	50,1	35,8	54,6	40,4	74,0
8730,000	45,0	32,9	50,8	38,6	74,0
9780,000	44,8	33,4	51,2	39,8	74,0
11670,000	44,7	32,7	53,6	41,6	74,0
12270,000	44,6	32,9	52,6	40,8	74,0

File No. T-0249-3677-01 JP

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -8,1 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3120,000	50,3	35,8	-3,3	47,0	32,5	74,0	54,0	-27,0	-21,5
3300,000	53,5	37,1	-3,1	50,4	34,0	74,0	54,0	-23,5	-20,0
3630,000	51,2	35,9	-2,4	48,8	33,5	74,0	54,0	-25,1	-20,5
4860,000	51,4	35,6	-0,1	51,2	35,4	74,0	54,0	-22,7	-18,5
5280,000	47,9	35,0	0,8	48,7	35,8	74,0	54,0	-25,3	-18,2
7320,000	56,7	41,3	4,6	61,2	45,9	74,0	54,0	-12,7	-8,1
9750,000	44,9	34,7	6,4	51,3	41,0	74,0	54,0	-22,7	-12,9
11130,000	44,8	32,1	8,2	53,0	40,3	74,0	54,0	-21,0	-13,7
12060,000	45,0	32,5	8,2	53,3	40,8	74,0	54,0	-20,7	-13,2

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




Minimum margin to limit: -11,9 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3120,000	46,5	--	-3,3	43,2	--	74,0	54,0	-30,7	--
3300,000	47,4	35,0	-3,1	44,3	31,9	74,0	54,0	-29,7	-22,1
3960,000	46,3	--	-1,5	44,8	--	74,0	54,0	-29,2	--
4920,000	51,3	35,4	0,0	51,2	35,4	74,0	54,0	-22,7	-18,6
5550,000	45,8	33,6	1,3	47,0	34,9	74,0	54,0	-27,0	-19,1
7380,000	54,0	37,5	4,6	58,6	42,1	74,0	54,0	-15,4	-11,9
9840,000	46,5	33,4	6,5	53,0	39,9	74,0	54,0	-21,0	-14,1
12360,000	44,6	33,1	8,0	52,5	41,0	74,0	54,0	-21,5	-13,0

File No. T-0249-3677-01 JP

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -4,4 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3120,000	50,2	35,9	-3,3	46,9	32,6	74,0	54,0	-27,0	-21,4
3300,000	53,2	36,9	-3,1	50,1	33,8	74,0	54,0	-23,8	-20,1
4110,000	49,2	35,1	-1,8	47,4	33,3	74,0	54,0	-26,6	-20,7
4920,000	52,9	36,0	0,0	52,9	36,0	74,0	54,0	-21,1	-18,0
5280,000	48,3	34,9	0,8	49,1	35,7	74,0	54,0	-24,8	-18,3
7386,000	60,0	45,0	4,6	64,6	49,5	74,0	54,0	-9,4	-4,4
9840,000	48,9	34,1	6,5	55,3	40,5	74,0	54,0	-18,6	-13,4
10950,000	45,3	32,9	8,1	53,4	41,0	74,0	54,0	-20,5	-13,0
12270,000	45,7	--	8,0	53,7	--	74,0	54,0	-20,3	--
17190,000	50,6	--	13,6	64,2	--	74,0	54,0	-9,8	--

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




Minimum margin to limit: -11,4 dB

Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	Pk	AV	Pk	AV	Pk
3300,000	46,9	34,8	43,8	31,7	74,0
3630,000	47,1	35,0	44,7	32,6	74,0
6030,000	46,0	--	47,4	--	74,0
7230,000	52,1	38,3	56,4	42,6	74,0
9780,000	45,5	33,5	51,9	39,8	74,0
10140,000	45,6	--	52,6	--	74,0
11970,000	45,4	32,6	53,9	41,1	74,0
14550,000	50,2	--	60,2	--	74,0

File No. T-0249-3677-01 JP

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -6,1 dB									
Frequency [MHz]	Reading [dB μ V]		Correction [dB]	Values [dB μ V/m]		Limit [dB μ V/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3300,000	52,8	36,9	-3,1	49,7	33,8	74,0	54,0	-24,3	-20,1
3780,000	48,4	35,6	-1,4	47,0	34,2	74,0	54,0	-27,0	-19,8
4620,000	49,6	35,1	-0,9	48,8	34,3	74,0	54,0	-25,2	-19,7
5280,000	47,6	34,9	0,8	48,4	35,7	74,0	54,0	-25,6	-18,3
7230,000	57,9	43,6	4,3	62,2	47,9	74,0	54,0	-11,7	-6,1
8460,000	45,2	--	5,5	50,6	--	74,0	54,0	-23,3	--
9570,000	44,9	--	6,3	51,1	--	74,0	54,0	-22,8	--
10410,000	44,7	33,0	7,6	52,3	40,6	74,0	54,0	-21,7	-13,4
11430,000	44,6	32,5	8,8	53,5	41,3	74,0	54,0	-20,5	-12,7
12030,000	43,9	32,5	8,4	52,2	40,9	74,0	54,0	-21,8	-13,1
14340,000	49,8	--	10,4	60,2	--	74,0	54,0	-13,8	--

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




Minimum margin to limit: -13,1 dB

Frequency [MHz]	Reading [dBµV] Pk	Reading [dBµV] AV	Correction [dB]	Values [dBµV/m] Pk	Values [dBµV/m] AV	Limit [dBµV/m] Pk	Limit [dBµV/m] AV	Margin [dB] Pk	Margin [dB] AV
3630,000	47,6	34,9	-2,4	45,2	32,5	74,0	54,0	-28,8	-21,4
4860,000	45,0	34,5	-0,1	44,9	34,3	74,0	54,0	-29,1	-19,6
5580,000	45,7	33,7	1,3	47,0	35,0	74,0	54,0	-27,0	-19,0
6930,000	46,3	34,2	3,2	49,4	37,4	74,0	54,0	-24,6	-16,6
7290,000	46,8	34,8	4,5	51,3	39,3	74,0	54,0	-22,6	-14,7
9800,000	45,2	--	6,4	51,7	--	74,0	54,0	-22,3	--
12150,000	44,6	--	8,1	52,7	--	74,0	54,0	-21,3	--
14640,000	51,3	--	9,5	60,8	--	74,0	54,0	-13,1	--

File No. T-0249-3677-01 JP

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	none




File No. **T-0249-3677-01 JP**

Minimum margin to limit: -9,9 dB									
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3300,000	53,8	37,2	-3,1	50,7	34,1	74,0	54,0	-23,3	-19,9
4110,000	49,8	34,9	-1,8	48,0	33,1	74,0	54,0	-25,9	-20,9
4620,000	48,7	35,2	-0,9	47,9	34,3	74,0	54,0	-26,1	-19,7
5610,000	47,1	34,1	1,3	48,3	35,4	74,0	54,0	-25,6	-18,6
7320,000	58,2	39,5	4,6	62,8	44,1	74,0	54,0	-11,2	-9,9
9800,000	45,7	--	6,4	52,1	--	74,0	54,0	-21,8	--
12090,000	44,7	--	8,1	52,9	--	74,0	54,0	-21,1	--
14580,000	51,0	--	9,7	60,7	--	74,0	54,0	-13,2	--

File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Horizontal
Remark:	none




Minimum margin to limit: -12,9 dB

Frequency [MHz]	Reading [dBµV] Pk	Reading [dBµV] AV	Correction [dB]	Values [dBµV/m] Pk	Values [dBµV/m] AV	Limit [dBµV/m] Pk	Limit [dBµV/m] AV	Margin [dB] Pk	Margin [dB] AV
3300,000	47,7	34,7	-3,1	44,5	31,6	74,0	54,0	-29,4	-22,4
3630,000	47,5	34,9	-2,4	45,1	32,5	74,0	54,0	-28,9	-21,5
4920,000	46,6	35,0	0,0	46,5	34,9	74,0	54,0	-27,4	-19,0
6000,000	46,6	--	1,4	47,9	--	74,0	54,0	-26,0	--
7380,000	47,3	35,8	4,6	51,9	40,4	74,0	54,0	-22,1	-13,6
8670,000	45,2	33,0	5,7	50,9	38,7	74,0	54,0	-23,1	-15,2
9840,000	45,3	33,5	6,5	51,8	39,9	74,0	54,0	-22,2	-14,0
12210,000	44,9	33,0	8,0	52,9	41,0	74,0	54,0	-21,0	-12,9

File No. T-0249-3677-01 JP

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC 15.209
Test:	Radiated Emission Test (Distance 3m)
Detector:	Pk / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	none



Minimum margin to limit: -8,4 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	Pk	AV		Pk	AV	Pk	AV	Pk	AV
3300,000	52,9	37,0	-3,1	49,8	33,9	74,0	54,0	-24,2	-20,1
3960,000	48,1	34,9	-1,5	46,6	33,3	74,0	54,0	-27,4	-20,6
4620,000	49,7	35,1	-0,9	48,9	34,2	74,0	54,0	-25,1	-19,8
5280,000	48,1	34,9	0,8	48,9	35,7	74,0	54,0	-25,1	-18,3
7380,000	53,8	41,0	4,6	58,4	45,6	74,0	54,0	-15,6	-8,4
10110,000	45,1	--	6,9	52,0	--	74,0	54,0	-22,0	--
11460,000	45,3	32,7	8,8	54,1	41,4	74,0	54,0	-19,9	-12,5
12360,000	44,6	--	8,0	52,5	--	74,0	54,0	-21,4	--

File No. T-0249-3677-01 JP

6.5 Restricted Bandedges


For test instruments and accessories used see section 7 Part **SER 3**.

6.5.1 Description of the test location

Test location: AREA A4

Test distance: conducted

6.5.2 Photo documentation of the test set-up



6.5.3 Test specification

Environmental conditions: Temperature: 25 ° C Humidity: 48 % Atmospheric pressure: 97 kPa

Frequency range: 2310 MHz - 2500 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.5.4 Test result



The requirements are **FULFILLED**.

Remarks: The measurement was performed in vertical polarization, pretests showed the highest emission
at the band edges occur in vertical polarization.

File No. **T-0249-3677-01 JP**



6.5.5 Test protocol

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	Low bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH1 (11Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	High bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	Low bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH6 (11Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	High bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	Low bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11b CH11 (11Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	High bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	Low bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH1 (54Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	High bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	Low bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH6 (54Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	High bandedge





File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	Low bandedge



File No. **T-0249-3677-01 JP**

Date of test:	2010-08-17
Operator:	Jürgen Pessinger
Mode:	TX mode, 802.11g CH11 (54Mbps)
Standard:	FCC 15.209
Test:	bandedge
Detector:	PK / AV
Result:	Limit kept
Applied to:	Vertical
Remark:	High bandedge



File No. **T-0249-3677-01 JP**

6.6 6dB Bandwidth


For test instruments and accessories used see section 7 Part CPC 3.

6.6.1 Description of the test location

Test location: AREA A4

Test distance: conducted

6.6.2 Photo documentation of the test set-up



6.6.3 Test specification

Environmental conditions: Temperature: 25 ° C Humidity: 60 % Atmospheric pressure: 97 kPa

Frequency range: 2400 MHz – 2483,5 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.6.4 Test result

The requirements are **FULFILLED**.

Remarks: The measurement was made with antenna cable defined by the manufacturer.


File No. **T-0249-3677-01 JP**

6.6.5 Test protocol

IEEE 802.11b

CH	frequency [MHz]	6dB Bandwidth [MHz]	minimum Limit [MHz]	Result
1	2412	10,24	0,5	Limit kept
6	2437	8,72	0,5	Limit kept
11	2462	9,2	0,5	Limit kept


IEEE 802.11b (11Mbps) CH1



Date: 12.AUG.2010 14:47:49


File No. T-0249-3677-01 JP

IEEE 802.11b (11Mbps) CH6



Date: 12.AUG.2010 14:44:33

IEEE 802.11b (11Mbps) CH11




Date: 12.AUG.2010 14:28:07

File No. T-0249-3677-01 JP

IEEE 802.11g

CH	frequency [MHz]	6dB Bandwidth [MHz]	minimum Limit [MHz]	Result
1	2412	15,36	0,5	Limit kept
6	2437	15,28	0,5	Limit kept
11	2462	15,44	0,5	Limit kept


IEEE 802.11g (54Mbps) CH1



Date: 12.AUG.2010 14:50:29


File No. **T-0249-3677-01 JP**

IEEE 802.11g (54Mbps) CH6



Date: 12.AUG.2010 14:40:54

IEEE 802.11g (54Mbps) CH11



Date: 12.AUG.2010 14:36:22

File No. T-0249-3677-01 JP

6.7 Maximum Conducted Output Power


For test instruments and accessories used see section 7 Part CPC 3.

6.7.1 Description of the test location

Test location: AREA A4

Test distance: conducted

6.7.2 Photo documentation of the test set-up



6.7.3 Test specification

Environmental conditions: Temperature: 25 ° C Humidity: 60 % Atmospheric pressure: 97 kPa

Frequency range: 2400 MHz – 2483,5 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.7.4 Test result

The requirements are **FULFILLED**.

Remarks: The measurement was made with antenna cable defined by the manufacturer.

File No. **T-0249-3677-01 JP**

6.7.5 Test protocol


IEEE 802.11b (11Mbps)

CH	frequency [MHz]	conducted output power [dBm]	Limit [dBm]	Result
1	2412	21,2	30	Limit kept
6	2437	21,7	30	Limit kept
11	2462	21,1	30	Limit kept

IEEE 802.11b (11Mbps) CH1




1 PK
VIEW




File No. T-0249-3677-01 JP

IEEE 802.11b (11Mbps) CH6



IEEE 802.11b (11Mbps) CH11




File No. T-0249-3677-01 JP

IEEE 802.11g (54Mbps)

CH	frequency [MHz]	conducted output power [dBm]	Limit [dBm]	Result
1	2412	19,4	30	Limit kept
6	2437	18,7	30	Limit kept
11	2462	17,9	30	Limit kept

IEEE 802.11g (54Mbps) CH1




File No. **T-0249-3677-01 JP**

IEEE 802.11g (54Mbps) CH6



IEEE 802.11g (54Mbps) CH11



File No. T-0249-3677-01 JP

6.8 Power Spectral Density


For test instruments and accessories used see section 7 Part CPC 3.

6.8.1 Description of the test location

Test location: AREA A4

Test distance: conducted

6.8.2 Photo documentation of the test set-up



6.8.3 Test specification

Environmental conditions: Temperature: 25 ° C Humidity: 60 % Atmospheric pressure: 97 kPa

Frequency range: 2400 MHz – 2483,5 MHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.8.4 Test result

The requirements are **FULFILLED**.

Remarks: The measurement was made with antenna cable defined by the manufacturer.

File No. **T-0249-3677-01 JP**


6.8.5 Test protocol

IEEE 802.11b (11Mbps)

CH	frequency [MHz]	reading [dBm/Hz]	correction to 3kHz [dB]	Power Spectral Density [dBm]	Limit [dBm]	Result
1	2412	-45,4	35	-10,4	8	Limit kept
6	2437	-46,1	35	-11,1	8	Limit kept
11	2462	-46,7	35	-11,7	8	Limit kept


Correction of 35 dB: $10\log(3000\text{Hz}/\text{Hz})$

IEEE 802.11b (11Mbps) CH1




File No. T-0249-3677-01 JP

IEEE 802.11b (11Mbps) CH6



IEEE 802.11b (11Mbps) CH11




File No. T-0249-3677-01 JP

IEEE 802.11g (54Mbps)

CH	frequency [MHz]	reading [dBm/Hz]	correction to 3kHz [dB]	Power Spectral Density [dBm]	Limit [dBm]	Result
1	2412	-45,9	35	-10,9	8	Limit kept
6	2437	-46,7	35	-11,7	8	Limit kept
11	2462	-47,7	35	-12,7	8	Limit kept


Correction of 35 dB: $10\log(3000\text{Hz/Hz})$

IEEE 802.11g (54Mbps) CH1




File No. **T-0249-3677-01 JP**

IEEE 802.11g (54Mbps) CH6



IEEE 802.11g (54Mbps) CH11



File No. T-0249-3677-01 JP

6.9 Conducted spurious emissions 30 MHz – 25GHz


For test instruments and accessories used see section 7 Part SEC 1-3.

6.9.1 Description of the test location

Test location: AREA A4

Test distance: conducted

6.9.2 Photo documentation of the test set-up



6.9.3 Test specification

Environmental conditions: Temperature: 25 ° C Humidity: 60 % Atmospheric pressure: 97 kPa

Frequency range: 30 MHz – 25 GHz

The test was carried out in the following operation mode(s):

- continuous transmit mode (duty cycle = 99%), maximum RF power adjusted

6.9.4 Test result





The requirements are **FULFILLED**.

Remarks: The measurement was made with antenna cable defined by the manufacturer.

File No. **T-0249-3677-01 JP**





6.9.5 Test protocol

IEEE 802.11b CH01







File No. **T-0249-3677-01 JP**

IEEE 802.11b CH06







File No. **T-0249-3677-01 JP**

IEEE 802.11b CH11







File No. **T-0249-3677-01 JP**

IEEE 802.11g CH01







File No. **T-0249-3677-01 JP**

IEEE 802.11g CH06



File No. **T-0249-3677-01 JP**

IEEE 802.11g CH11



File No. **T-0249-3677-01 JP**

7 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used, in addition to the test accessories, are calibrated and verified regularly.

Test ID	Model Type	Equipment No.	Next Calib.	Last Calib.	Next Verif.	Last Verif.
A 4	ESH 3	01-02/03-01-005	02/12/2011	02/12/2010		
	ESH 2 - Z 5	01-02/20-01-001	26/01/2014	26/01/2011	12/04/2011	12/04/2010
	ESH 3 - Z 2	01-02/50-02-020	02/12/2011	18/02/2010		
	BNC-3000-N	01-02/50-07-008				
	N-5000-N	01-02/50-07-009				
	Tile Version 3.4K20	01-02/68-09-001				
CPC 3	FSP 30	02-02/11-05-001	04/05/2011	04/05/2010		
SEC 1-3	Tile Version 3.4K20	01-02/68-09-001				
	FSP 30	02-02/11-05-001	04/05/2011	04/05/2010		
SER 1	ESH 3	01-02/03-01-005	02/12/2011	02/12/2010		
	FMZB 1516	01-02/24-01-018			16/02/2012	16/02/2011
	BNC-3000-N	01-02/50-07-008				
	N-5000-N	01-02/50-07-009				
	Tile Version 3.4K20	01-02/68-09-001				
SER 2	ESVP	01-02/03-01-002	04/02/2012	04/02/2011		
	HM 5012	01-02/11-01-001				
	VULB 9163	01-02/24-01-006	24/10/2011	24/10/2008		
	N-40000-N	01-02/50-05-043				
	N-30000-N	01-02/50-05-044				
	Tile Version 3.4K20	01-02/68-09-001				
SER 3	emitel ESW V31	01-02/68-09-002				
	AMF-40-005-180-24-10P	01-02/17-02-009			02/12/2011	02/12/2010
	3117	02-02/24-05-009	10/02/2011	10/02/2010		
	HCC	01-02/50-01-021				
	FA210A0020000000	01-02/50-06-065				
	FA210A0050000000	01-02/50-10-005				
	Tile Version 3.4K20	01-02/68-09-001				
	emitel ESW V31	01-02/68-09-002				
	RST 070	01-05/60-02-003				
	FSP 30	02-02/11-05-001	04/05/2011	04/05/2010		
	R1 _ 18 - 30 GHz	02-02/30-09-002			17/02/2011	17/02/2010

File No. **T-0249-3677-01 JP**