





# EMCE Engineering

1726 Ringwood Avenue, San Jose, CA 95131 USA

Tel. +1(510)490-4307 / Fax +1(510)490-3441

<http://www.universalcompliance.com>

## RF EXPOSURE EVALUATION REPORT

<b>Applicant Name:</b> Stem Innovation, LLC dBa Iconoscope, LLC 21 G Street, Salt Lake City, UT 84102 USA		<b>Date of Issue :</b> 11/27/2017 <b>Test Site/Location:</b> EMCE ENGINEERING 1726 Ringwood Avenue, San Jose, CA 95131 USA <b>Report No.:</b> 4325-4 <b>EMCE FRN:</b> 0007198120	
<b>FCC ID :</b> <b>IC :</b>	<b>YM780-9500</b> <b>9637A-809500</b>		
<b>Application Type</b>	Certification		
<b>Model:</b>	80-9500		
<b>Additional Model(s):</b>	N/A		
<b>EUT Type:</b>	IP Camera		
<b>Frequency Range:</b>	2402 MHz – 2480 MHz(BT) 2412 MHz – 2462 MHz (802.11b/g/n) 5180 MHz – 5240 MHz(UNII-1) / 5260 MHz – 5320 MHz(UNII-2A) / 5500 MHz – 5720 MHz(UNII-2C) / 5745 MHz – 5825 MHz(UNII-3)		
<b>FCC Classification</b>	Spread Spectrum Transmitter (DSS) Digital Transmission System(DTS) Unlicensed National Information Infrastructure (NII)		
<b>FCC Rule Part(s)</b> <b>ISED Rule Part(s)</b>	Part 15.247 and 407 RSS-247 Issue 2(Feb. 2017) / RSS-GEN Issue 4 (Nov. 2014)		
The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this Equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. <b>EMCE Engineering</b> Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)			
 Report prepared by : Amy Jones Administrative Assistant, <b>EMCE Engineering</b>		 Approved by : Bob Cole <b>President</b> <b>EMCE Engineering</b>	
This report only responds to the tested sample and may not be reproduced except in full, without prior written approval of EMCE Engineering.			

FCC PT.15.247 & 407 TEST REPORT	RF Exposaura Evaluation Report		FCC ID : YM780-9500
Test Report No. 4325-4	Date of Issue: 11/27/2017	EUT : IP Camera	IC : 9637A-809500

## Version

TEST REPORT NO.	DATE	DESCRIPTION
4325-4	11/27/17	- First Approval Report

## Table of Contents

1. GENERAL INFORMATION .....	4
2. EUT DESCRIPTION .....	4
3. SUMMARY OF TEST RESULTS .....	5

FCC PT.15.247 & 407 TEST REPORT	RF Exposure Evaluation Report		FCC ID : YM780-9500
Test Report No. 4325-4	Date of Issue: 11/27/2017	EUT : IP Camera	Test Report No. 4325-4

## 1. GENERAL INFORMATION

<b>Applicant</b>	Stem Innovation, LLC dBa Iconoscope, LLC
<b>Applicant Address</b>	21 G Street, Salt Lake City, UT 84102 USA
<b>FCC ID</b>	YM780-9500
<b>EUT Type</b>	IP Camera
<b>Model name(s)</b>	80-9500
<b>Additional Model name(s):</b>	N/A
<b>Date(s) of Tests:</b>	07/10/2017 – 10/05/2017
<b>Place of Tests:</b>	EMCE ENGINEERING 1726 Ringwood Avenue, San Jose, CA 95131 USA

## 2. EUT DESCRIPTION

<b>EUT Type</b>	IP Camera
<b>Model Name</b>	80-9500
<b>Additional Model Name(s)</b>	N/A
<b>Power Supply</b>	DC 5.0 vdc
<b>Battery type</b>	Li-ion Battery(Standard)
<b>Frequency Range(TX/RX)</b>	2402 MHz – 2480 MHz(BT) 2412 MHz – 2462 MHz (802.11b/g/n(20 MHz)) 5180 - 5240 MHz (UNII-1 Band - 20 / 40 MHz), 5260 - 5320 MHz (UNII-2A Band - 20 / 40 MHz), 5500 - 5720 MHz (UNII-2C Band - 20 / 40 MHz), 5745 - 5825 MHz (UNII-3 Band - 20 / 40 MHz)
<b>Max. RF Output Power</b>	BT (6.11dBm) 4.08 mW Wi-Fi 802.11b (15.61 dBm) 36.39 mW Wi-Fi 802.11g (15.71 dBm) 37.23 mW Wi-Fi 802.11n (10.03 dBm) 10.06 mW UNII-1 802.11n-20 MHz BW (5.62 dBm), UNII-1 802.11n-40 MHz BW (7.32 dBm) UNII-2A 802.11n-20 MHz BW (8.32 dBm), UNII-2A 802.11n-40 MHz BW (6.77 dBm), UNII-2C 802.11n-20 MHz BW (10.49 dBm), UNII-2C 802.11n-40 MHz BW (6.53 dBm), UNII-3 802.11n-20 MHz BW (10.89 dBm), UNII-3 802.11n-40 MHz BW (6.37 dBm)
<b>Antenna Specification</b>	Manufacturer: MOLEX Antenna type: 2.4 / 5 GHz Balance Flex Antenna 1461530100 Peak Gain : 3.2 dBi (2.4 GHz Band), 4.75 dBi (5.8 GHz Band)

FCC PT.15.247 & 407 TEST REPORT	RF Exposure Evaluation Report		FCC ID : YM780-9500
Test Report No. 4325-4	Date of Issue: 11/27/2017	EUT : IP Camera	Test Report No. 4325-4

## 3. SUMMARY OF TEST RESULTS

### 3-1. Maximum Permissible Exposure

#### A. FCC Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (s) mW/cm <sup>2</sup>	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S minutes
0.3-3.0	614	1.63	100*	6
3.0-30	1842/f	4.89/f	900/f*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

#### B. FCC Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (s) mW/cm <sup>2</sup>	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S minutes
0.3-3.0	614	1.63	100*	6
3.0-30	1842/f	4.89/f	900/f*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: F = frequency in MHz; plane wave equivalent power density

### C. ISED Limits (per IC RSS102)

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> <sup>0.5</sup>	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ <i>f</i> <sup>0.25</sup>	0.1540/ <i>f</i> <sup>0.25</sup>	8.944/ <i>f</i> <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> <sup>0.3417</sup>	0.008335 <i>f</i> <sup>0.3417</sup>	0.02619 <i>f</i> <sup>0.6834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> <sup>1.2</sup>
150000-300000	0.158 <i>f</i> <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> <i>f</i>	616000/ <i>f</i> <sup>1.2</sup>

Note: *f* is frequency in MHz.  
 \* Based on nerve stimulation (NS).  
 \*\* Based on specific absorption rate (SAR).

## 3.2 MPE Calculation Method

The MPE was calculated at 31 cm to show compliance with the power density limit.

The following formula was used to calculate the power density.

(According to the FCC OET Bulletin 65 (Edition 97-01))

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density (in appropriate units, e.g., mW/cm<sup>2</sup>)

P = Power input to antenna (in appropriate units, e.g., mW)

G = Power Gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

FCC PT.15.247 & 407 TEST REPORT	RF Exposure Evaluation Report		FCC ID : YM780-9500
Test Report No. 4325-4	Date of Issue: 11/27/2017	EUT : IP Camera	Test Report No. 4325-4

### 3.3 Results

#### Bluetooth

Max Peak Output Power at antenna input terminal	6.11	dBm
Max Peak Output Power at antenna input terminal	4.08	mW
Prediction Distance	20	cm
Prediction Frequency	2440	MHz
Antenna Gain	3.2	dBi
Antenna Gain	2.089	Numeric
Power Density at Prediction Frequency (S)	0.00169	mW/cm <sup>2</sup>
MPE Limit for Uncontrolled Exposure at Prediction Frequency	1	mW/cm <sup>2</sup>

#### 2.4GHz Band

Max Peak Output Power at antenna input terminal	15.71	dBm
Max Peak Output Power at antenna input terminal	37.23	mW
Prediction Distance	20	cm
Prediction Frequency	2437	MHz
Antenna Gain	3.2	dBi
Antenna Gain	2.089	Numeric
Power Density at Prediction Frequency (S)	0.01547	mW/cm <sup>2</sup>
MPE Limit for Uncontrolled Exposure at Prediction Frequency	1	mW/cm <sup>2</sup>

#### 5GHz Band

Max Peak Output Power at antenna input terminal	10.89	dBm
Max Peak Output Power at antenna input terminal	12.27	mW
Prediction Distance	20	cm
Prediction Frequency	5745	MHz
Antenna Gain	4.75	dBi
Antenna Gain	2.985	Numeric
Power Density at Prediction Frequency (S)	0.00729	mW/cm <sup>2</sup>
MPE Limit for Uncontrolled Exposure at Prediction Frequency	1	mW/cm <sup>2</sup>

### Simultaneous Transmission Operations

$$=(0.01547/1)+(0.00169/1)+(0.00729) = 0.02445 < 1$$