1. RF Exposure Evaluation

1.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric field	Magnetic field	Power	Averaging			
range	strength	strength	density	time			
(MHz)	(V/m)	(A/m)	(mW/cm ²)	(minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f ²)	6			
30–300	61.4	0.163	1.0	6			
300–1500			f/300	6			
1500-100,000			5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f ²)	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500-100,000			1.0	30			

f = frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2 . If we know the maximum gain of the antenna and the total

power input to the antenna, through the calculation, we will know the distance r where the MPE

limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle

and highest channel individually.

1.3. Test Result of RF Exposure Evaluation

Mode	Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm ²)	Result
GFSK	Lowest	2.046445	0.000645252	1.0	PASS
	Middle	2.312065	0.000729003	1.0	PASS
	Highest	1.625549	0.000512542	1.0	PASS
Pi/4QPSK	Lowest	1.633052	0.000514907	1.0	PASS
	Middle	1.828100	0.000576407	1.0	PASS
	Highest	1.213389	0.000382586	1.0	PASS
8DPSK	Lowest	1.671091	0.000526901	1.0	PASS
	Middle	1.883649	0.000593922	1.0	PASS
	Highest	1.273503	0.000401540	1.0	PASS

Remark: antenna gain=2dBi