# Compliance Certification Services Inc. Report No: KS110411B01-SF

# IIII. 802.11 G RESULTS

<b>TYPE</b>	<u>PARAMETERS</u>
TYPE  Phone	Measurement 1: Right Head with Cheek device position on Low Channel in 802.11g mode Measurement 3: Right Head with Cheek device position on Middle Channel in 802.11g mode Measurement 3: Right Head with Cheek device position on High Channel in 802.11g mode Measurement 4: Right Head with Tilt device position on Low Channel in 802.11g mode Measurement 5: Right Head with Tilt device position on Middle Channel in 802.11g mode Measurement 6: Right Head with Tilt device position on High Channel in 802.11g mode Measurement 7: Left Head with Cheek device position on Low Channel in 802.11g mode Measurement 8: Left Head with Cheek device position on Middle Channel in 802.11g mode Measurement 9: Left Head with Cheek device position on High Channel in 802.11g mode Measurement 10: Left Head with Tilt device position on Low Channel in 802.11g mode Measurement 11: Left Head with Tilt device position on Middle Channel in 802.11g mode Measurement 12: Left Head with Tilt device position on High Channel in 802.11g mode Measurement 13: FrontSide toward phantom 15mm on Low Channel in 802.11g mode Measurement 14: FrontSide toward phantom 15mm on Middle Channel in 802.11g mode Measurement 15: FrontSide toward phantom 15mm on High Channel in 802.11g mode
	Measurement 16: BackSide toward phantom 15mm on Low Channel in 802.11g mode  Measurement 17: BackSide toward phantom 15mm on Middle Channel in 802.11g mode  Measurement 18: BackSide toward phantom 15mm on High Channel in 802.11g mode



**MEASUREMENT 1** 

Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm


## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Right head
Device Position	Cheek
Band	802.11g
Channels	Low
Signal	wireless

#### **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz,	Calibrated: N/A
	SN:375052-AA1)	
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2412.0000
Relative permitivity (real part)	40.415741
Relative permitivity (imaginary part)	13.348512
Conductivity (S/m)	1.814101
Variation (%)	-1.110000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C
ConvF:	51.18,53.87,70.48






**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.045851
SAR 1g (W/Kg)	0.104750

SAR, Z Axis Scan (X = -13, Y = -3)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

#### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Right head
Device Position	Cheek
Band	802.11g
Channels	Middle
Signal	wireless


# **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2437.000000
Relative permitivity (real part)	40.426168
Relative permitivity (imaginary part)	13.348910
Conductivity (S/m)	1.865411
Variation (%)	-0.300000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.068410
SAR 1g (W/Kg)	0.079851

SAR, Z Axis Scan (X = -13, Y = -3)





**MEASUREMENT 3** 

Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm


## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Right head
Device Position	Cheek
Band	802.11g
Channels	High
Signal	wireless

## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz,	Calibrated: N/A
	SN:375052-AA1)	
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2462.000000
Relative permitivity (real part)	40.421402
Relative permitivity (imaginary part)	13.244152
Conductivity (S/m)	1.854787
Variation (%)	-0.100000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C
ConvF:	51.18,53.87,70.48






**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.068745
SAR 1g (W/Kg)	0.126877

SAR, Z Axis Scan (X = -13, Y = -3)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

## A. Experimental conditions.

Phantom File	zinf15.txt, Adaptative 2 max	
Phantom	Right head	
Device Position	Tilt	
Band	802.11g	
Channels	Low	
Signal	wireless	


# **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz,	Calibrated: N/A
	SN:375052-AA1)	
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2412.000000
Relative permitivity (real part)	40.423616
Relative permitivity (imaginary part)	13.294711
Conductivity (S/m)	1.857114
Variation (%)	-1.400000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C



Report No: KS110411B01-SF




# VOLUME SAR

**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.068778
SAR 1g (W/Kg)	0.115878

SAR, Z Axis Scan (X = -9, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

#### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max	
Phantom	Right head	
Device Position	Tilt	
Band	802.11g	
Channels	Middle	
Signal	wireless	


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2437.000000
Relative permitivity (real part)	40.421410
Relative permitivity (imaginary part)	13.339811
Conductivity (S/m)	1.854144
Variation (%)	-0.400000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.078541
SAR 1g (W/Kg)	0.127894

SAR, Z Axis Scan (X = -9, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Right head
Device Position	Tilt
Band	802.11g
Channels	High
Signal	wireless


# **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2462.000000
Relative permitivity (real part)	40.415410
Relative permitivity (imaginary part)	13.348744
Conductivity (S/m)	1.847550
Variation (%)	-1.500000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.075692
SAR 1g (W/Kg)	0.148721

SAR, Z Axis Scan (X = -9, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

#### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Left head
Device Position	Cheek
Band	802.11g
Channels	Low
Signal	wireless


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2412.000000
Relative permitivity (real part)	40.411885
Relative permitivity (imaginary part)	13.360125
Conductivity (S/m)	1.858704
Variation (%)	0.300000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








Maximum location: X=-13.00, Y=-3.00

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.089874
SAR 1g (W/Kg)	0.134785

SAR, Z Axis Scan (X = -25, Y = -11)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Left head
Device Position	Cheek
Band	802.11g
Channels	Middle
Signal	wireless


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2437.000000
Relative permitivity (real part)	40.423651
Relative permitivity (imaginary part)	13.35741
Conductivity (S/m)	1.851741
Variation (%)	1.350000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.098714
SAR 1g (W/Kg)	0.178414

SAR, Z Axis Scan (X = -25, Y = -11)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Left head
Device Position	Cheek
Band	802.11g
Channels	High
Signal	wireless


# **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2462.000000
Relative permitivity (real part)	40.354108
Relative permitivity (imaginary part)	13.35710
Conductivity (S/m)	1.856720
Variation (%)	0.490000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.074120
SAR 1g (W/Kg)	0.098742

SAR, Z Axis Scan (X = -25, Y = -11)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Left head
Device Position	Tilt
Band	802.11g
Channels	Low
Signal	wireless


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2412.000000
Relative permitivity (real part)	40.411584
Relative permitivity (imaginary part)	13.360591
Conductivity (S/m)	1.858466
Variation (%)	-0.600000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.112540
SAR 1g (W/Kg)	0.168740

SAR, Z Axis Scan (X = -22, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

#### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Left head
Device Position	Tilt
Band	802.11g
Channels	Middle
Signal	wireless


# **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2437.000000
Relative permitivity (real part)	40.432015
Relative permitivity (imaginary part)	13.291614
Conductivity (S/m)	1.848710
Variation (%)	-1.100000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.125743
SAR 1g (W/Kg)	0.223598

SAR, Z Axis Scan (X = -22, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

## A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Left head
Device Position	Tilt
Band	802.11g
Channels	High
Signal	wireless


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2462.000000
Relative permitivity (real part)	40.430141
Relative permitivity (imaginary part)	13.374121
Conductivity (S/m)	1.854970
Variation (%)	-1.110000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.155746
SAR 1g (W/Kg)	0.234785

SAR, Z Axis Scan (X = -22, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max	
Phantom	Body	
Device Position	FrontSide toward phantom	
Band	802.11g	
Channels	Low	
Signal	wireless	


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2412.000000
Relative permitivity (real part)	51.518744
Relative permitivity (imaginary part)	13.36810
Conductivity (S/m)	1.959874
Variation (%)	-0.140000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.048712
SAR 1g (W/Kg)	0.068741

SAR, Z Axis Scan (X = 0, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max	
Phantom	Body	
Device Position	FrontSide toward phantom	
Band	802.11g	
Channels	Middle	
Signal	wireless	


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2437.000000
Relative permitivity (real part)	51.521000
Relative permitivity (imaginary part)	13.357011
Conductivity (S/m)	1.959871
Variation (%)	-0.600000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.054712
SAR 1g (W/Kg)	0.058987

SAR, Z Axis Scan (X = 0, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

#### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max	
Phantom	Body	
Device Position	FrontSide toward phantom	
Band	802.11g	
Channels	High	
Signal	wireless	


### **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2462.000000
Relative permitivity (real part)	51.536640
Relative permitivity (imaginary part)	13.380026
Conductivity (S/m)	1.959641
Variation (%)	-0.400000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.064751
SAR 1g (W/Kg)	0.098727

SAR, Z Axis Scan (X = 0, Y = -6)





**MEASUREMENT 16** 

Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm


### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Body
Device Position	BackSide toward phantom
Band	802.11g
Channels	Low
Signal	wireless

### **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz,	Calibrated: N/A
	SN:375052-AA1)	
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2412.000000
Relative permitivity (real part)	51.526981
Relative permitivity (imaginary part)	13.357411
Conductivity (S/m)	1.957404
Variation (%)	-0.110000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C
ConvF:	50.35,52.98,69.78






**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.042354
SAR 1g (W/Kg)	0.078970

SAR, Z Axis Scan (X = 0, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max	
Phantom	Body	
Device Position	BackSide toward phantom	
Band	802.11g	
Channels	Middle	
Signal	wireless	


## **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2437.000000
Relative permitivity (real part)	51.512500
Relative permitivity (imaginary part)	13.358011
Conductivity (S/m)	1.954720
Variation (%)	-0.600000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C








**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.077461
SAR 1g (W/Kg)	0.106845

SAR, Z Axis Scan (X = 0, Y = -6)



Report No: KS110411B01-SF

Date of measurement: 04/14/2011

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm

Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm

#### A. Experimental conditions.


Phantom File	zinf15.txt, Adaptative 2 max
Phantom	Body
Device Position	BackSide toward phantom
Band	802.11g
Channels	High
Signal	wireless


### **B.** Instrumentations.

PC	HP (Pentium(R) V3.06GHz, SN:375052-AA1)	Calibrated: N/A
Wireless Communication	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Test Set		
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2012
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C, SN:MY43321570)	Calibration Due: 03/24/2012
Amplifier	Mini-Circuits (ZHL-42, SN:110405)	Calibration Due: 07/29/2011
Power Meter	Agilent (E4416A, SN:QB41292714)	Calibration Due: 03/24/2012
Probe	Antennessa (SN:SN_1109_EP_100)	Calibration Due: 05/04/2011
DIPOLE 2450	Antennessa (DIPJ37,SN 48/05)	Calibration Due: 10/09/2011
Phantom	Antennessa (SN:SN41_05_SAM29)	Calibrated: N/A
Liquid	Antennessa	Calibrated: N/A
Measurement SW	OPEN SAR V2.1	Calibrated: N/A

Frequency (MHz)	2462.000000
Relative permitivity (real part)	51.549840
Relative permitivity (imaginary part)	13.389326
Conductivity (S/m)	1.958413
Variation (%)	-0.400000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C







**Maximum location: X=-13.00, Y=-3.00** 

Report No: KS110411B01-SF

SAR 10g (W/Kg)	0.057513
SAR 1g (W/Kg)	0.087811

SAR, Z Axis Scan (X = 0, Y = -6)

