

TEST REPORT



Applicant:	Disruptive Ltd.
Address:	Windsor House, Turnpike Road, High Wycombe, Bucks, HP12 3NR, UK

Manufacturer or Supplier	Disruptive Ltd.
Address	Windsor House, Turnpike Road, High Wycombe, Bucks, HP12 3NR, UK
Product:	Xorb Wireless
Brand Name:	Gear4
Model:	PG766US
Additional Model & Model Difference:	See section 3.1
Date of tests:	Oct. 23 ~ Oct. 31, 2012

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C (Section 15.249)**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Kent Liu Project Engineer / EMC Department	Approved by Sam Tung Manager / EMC Department
	 Date: Nov. 01, 2012

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS	3
2 MEASUREMENT UNCERTAINTY	3
3 GENERAL INFORMATION	3
3.1 GENERAL DESCRIPTION OF EUT	3
3.2 DESCRIPTION OF TEST MODES	3
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	3
3.4 DESCRIPTION OF SUPPORT UNITS	3
4. TEST TYPES AND RESULTS	3
4.1 CONDUCTED EMISSION MEASUREMENT	3
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	3
4.1.2 TEST INSTRUMENTS	3
4.1.3 TEST PROCEDURES.....	3
4.1.4 DEVIATION FROM TEST STANDARD.....	3
4.1.5 TEST SETUP	3
4.1.6 EUT OPERATING CONDITIONS	3
4.1.7 TEST RESULTS.....	3
4.2 RADIATED EMISSION MEASUREMENT	3
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	3
4.2.2 TEST INSTRUMENTS	3
4.2.3 TEST PROCEDURES.....	3
4.2.4 DEVIATION FROM TEST STANDARD.....	3
4.2.5 TEST SETUP.....	3
4.2.6 EUT OPERATING CONDITIONS	3
4.2.7 TEST RESULTS.....	3
4.3 20dB BANDWIDTH MEASUREMENT.....	3
4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT	3
4.3.2 TEST INSTRUMENTS	3
4.3.3 TEST PROCEDURE	3
4.3.4 DEVIATION FROM TEST STANDARD.....	3
4.3.5 TEST SETUP	3
4.3.6 EUT OPERATING CONDITIONS	3
4.3.7 TEST RESULTS.....	3
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	3
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	3

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF121022N042	Original release	Nov. 1, 2012

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.249)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
§15.203	Antenna Requirement	PASS	Compliant
§15.207 (a)	Conducted Emission	PASS	Compliant
§15.205	Restricted Band of Operation	PASS	Compliant
§15.209 §15.249(a)	Radiated Emission	PASS	Compliant
§15.215(c)	20dB Bandwidth Test	PASS	Compliant

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44dB
Radiated emissions	30MHz ~ 200MHz	3.19dB
	200MHz ~1000MHz	3.21dB
	1GHz ~ 18GHz	2.26dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Xorb
MODEL NO.	PG766US
ADDITIONAL MODEL	PG766EUK
FCC ID	YNKPG766V2
NOMINAL VOLTAGE	DC 15V/2A From Adapter Input AC 230V/50Hz
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, $\pi/4$ DPSK
OPERATING FREQUENCY	2402-2480MHz
ANTENNA TYPE	Integral PCB Antenna; 0dBi gain
I/O PORTS	Aux in port, Line out port, USB port
DATA CABLE SUPPLIED	Audio cable: Unshielded, Detachable, 1.4m

NOTE:

1. The EUT was powered by the following adapters:

ADAPTER	
BRAND:	N/A
MODEL:	SHF1500200U1BA
INPUT:	AC 100-240V 50/60HZ, 0.8A
OUTPUT:	DC 15V/2A
DC LINE:	Unshielded, Undetachable, 1.5m

- 2 Additional model PG766EUK is identical with the test model PG766US except the model number for marketing purpose.
- 3 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 4 For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- 5 When EUT is connected to the AUX in port. BT will be not functioning.

3.2 DESCRIPTION OF TEST MODES

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE	PACKET TYPE
Low, Middle, High	FHSS	GFSK	1M/	DH1/3/5
Low, Middle, High	FHSS	$\pi/4$ DPSK	2M	DH1/3/5
Low, Middle, High	FHSS	8DPSK	3M	DH1/3/5

CHANNEL NUMBER	TESTED CHANNEL	TESTED FREQUENCY
0	Low	2402 MHz
39	Mid.	2441 MHz
78	High	2480 MHz

After estimating all the combination of every test mode, the result shown as below is the worst case

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE	PACKET TYPE
Low, Middle, High	FHSS	GFSK	1M	DH5

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.249)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Verification). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

◆ FOR CONDUCTED EMISSION MEASUREMENT

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A				

NO.	DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
EMI Test Receiver Rohde&Schwarz	ESU 26	100005	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ENV216	101173	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ESH2-Z5	100071	May 15,12	May 14,13
Test software	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA
2. The test was performed in Dongguan Shielded Room 553.

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.1577	10.63	38.38	28.85	49.01	39.48	65.58	55.58	-16.58	-16.11
2	0.186	10.52	35.67	27.82	46.19	38.34	64.21	54.21	-18.03	-15.88
3	0.21406	10.45	33.86	26.15	44.31	36.6	63.05	53.05	-18.74	-16.45
4	0.5704	10.23	28.9	20.26	39.13	30.49	56	46	-16.87	-15.51
5	11.038	10.03	24.63	17.68	34.66	27.71	60	50	-25.34	-22.29
6	20.458	10.31	22.48	17.14	32.79	27.45	60	50	-27.21	-22.55


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	10.73	37.31	26.45	48.04	37.18	65.78	55.78	-17.74	-18.6
2	0.182	10.5	32.73	21.2	43.23	31.7	64.39	54.39	-21.16	-22.69
3	0.24614	10.38	26.79	17.79	37.17	28.17	61.89	51.89	-24.72	-23.72
4	0.574	10.29	24.24	15.9	34.53	26.19	56	46	-21.47	-19.81
5	10.434	9.94	26.05	18.49	35.99	28.43	60	50	-24.01	-21.57
6	20.738	10.24	22.46	17.14	32.7	27.38	60	50	-27.3	-22.62

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

**4.2.2 TEST INSTRUMENTS**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer ROHDE & SCHWARZ	E4446A	MY46180622	May 02, 12	May 01, 13
Test Receiver ROHDE & SCHWARZ	ESVD	847398/003	May 15,12	May 14,13
Bilog Antenna TESEQ	CBL 6111D	27089	July 16,12	July 15,13
Horn Antenna EMCO	3117	00062558	Nov.07,11	Nov.07,12
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar 24,12	Mar 23,13
RF Cable IMRO	IMRO-400	10m Cable 1#10m	May 16,12	May 15,13
RF Cable IMRO	IMRO-400	10m Cable 2#3m	May 16,12	May 15,13
Signal Amplifier SONOMA	310N	186955	Mar. 14,12	Mar. 13,13
Signal Amplifier HP	8449B	3008A00409	May 31,12	May 30,13
RF Cable DRAKA	M06/25-RG102	10m Cable 2#	May 16,12	May 15,13
Test software ADT	ADT_Radiated_V7. 6.15	N/A	N/A	N/A

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.
 2. The test was performed in Dongguan Chamber 10m.
 3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA: GFSK DH5

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	65.57	27.0 QP	40.0	-13.0	1.00 H	79	19.84	7.14
2	109.22	25.6 QP	43.5	-18.0	1.00 H	166	13.52	12.03
3	170.65	39.2 QP	43.5	-4.3	1.00 H	156	28.21	10.97
4	238.55	37.0 QP	46.0	-9.0	1.00 H	350	24.30	12.74
5	264.42	34.0 QP	46.0	-12.0	1.00 H	247	18.96	15.08
6	296.75	33.0 QP	46.0	-13.0	1.00 H	0	18.00	14.99
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.40	35.0 QP	40.0	-5.1	1.00 V	116	24.50	10.45
2	63.95	34.6 QP	40.0	-5.4	1.00 V	199	27.31	7.31
3	105.98	32.7 QP	43.5	-10.8	1.00 V	230	20.86	11.86
4	156.10	38.0 QP	43.5	-5.6	1.00 V	54	26.08	11.87
5	178.73	38.5 QP	43.5	-5.0	1.00 V	27	27.99	10.50
6	233.70	33.5 QP	46.0	-12.5	1.00 V	159	21.28	12.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



ABOVE 1GHz DATA: GFSK DH5

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	66.2 PK	74.0	-7.8	1.00 H	198	29.70	36.50
2	2400.00	36.1 AV	54.0	-17.9	1.00 H	198	-0.40	36.50
3	*2402.00	101.8 PK	114.0	-12.2	1.00 H	126	65.28	36.52
4	*2402.00	71.7 AV	94.0	-22.3	1.00 H	126	35.18	36.52
5	4804.00	60.4 PK	74.0	-13.6	1.28 H	175	11.15	49.25
6	4804.00	30.3 AV	54.0	-23.7	1.28 H	175	-18.95	49.25
7	7206.00	60.3 PK	74.0	-13.7	1.15 H	172	13.78	46.52
8	7206.00	30.2 AV	54.0	-23.8	1.15 H	172	-16.32	46.52
9	9608.00	59.3 PK	74.0	-14.7	1.25 H	156	14.40	44.90
10	9608.00	29.2 AV	54.0	-24.8	1.25 H	156	-15.70	44.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	57.4 PK	74.0	-16.6	1.05 V	305	20.90	36.50
2	2400.00	27.3 AV	54.0	-26.7	1.05 V	305	-9.20	36.50
3	*2402.00	99.4 PK	114.0	-14.6	1.07 V	95	62.88	36.52
4	*2402.00	69.3 AV	94.0	-24.7	1.07 V	95	32.78	36.52
5	4804.00	61.7 PK	74.0	-12.3	1.06 V	230	12.45	49.25
6	4804.00	31.6 AV	54.0	-22.4	1.06 V	230	-17.65	49.25
7	7206.00	60.5 PK	74.0	-13.5	1.03 V	345	13.98	46.52
8	7206.00	30.4 AV	54.0	-23.6	1.03 V	345	-16.12	46.52
9	9608.00	59.5 PK	74.0	-14.5	1.23 V	36	14.60	44.90
10	9608.00	29.4 AV	54.0	-24.6	1.23 V	36	-15.50	44.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	99.3 PK	114.0	-14.7	1.00 H	0	62.43	36.87
2	*2441.00	69.2 AV	94.0	-24.8	1.00 H	0	32.33	36.87
3	4882.00	61.2 PK	74.0	-12.8	1.00 H	345	11.97	49.23
4	4882.00	31.1 AV	54.0	-22.9	1.00 H	345	-18.13	49.23
5	7323.00	59.7 PK	74.0	-14.3	1.00 H	21	13.09	46.61
6	7323.00	29.6 AV	54.0	-24.4	1.00 H	21	-17.01	46.61
7	9764.00	58.6 PK	74.0	-15.4	1.00 H	266	13.79	44.81
8	9764.00	28.5 AV	54.0	-25.5	1.00 H	266	-16.31	44.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	99.0 PK	114.0	-15.0	1.28 V	185	62.13	36.87
2	*2441.00	68.9 AV	94.0	-25.1	1.28 V	185	32.03	36.87
3	4882.00	60.8 PK	74.0	-13.2	1.28 V	278	11.57	49.23
4	4882.00	30.7 AV	54.0	-23.3	1.28 V	278	-18.53	49.23
5	7323.00	59.8 PK	74.0	-14.2	1.25 V	36	13.19	46.61
6	7323.00	29.7 AV	54.0	-24.3	1.25 V	36	-16.91	46.61
7	9764.00	58.4 PK	74.0	-15.6	1.00 V	75	13.59	44.81
8	9764.00	28.3 AV	54.0	-25.7	1.00 V	75	-16.51	44.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.0 PK	114.0	-13.0	1.18 H	40	63.79	37.21
2	*2480.00	70.9 AV	94.0	-23.1	1.18 H	40	33.69	37.21
3	2483.50	58.0 PK	74.0	-16.0	1.15 H	42	20.76	37.24
4	2483.50	27.9 AV	54.0	-26.1	1.15 H	43	-9.34	37.24
5	4960.00	61.0 PK	74.0	-13.0	1.18 H	332	11.79	49.21
6	4960.00	30.9 AV	54.0	-23.1	1.18 H	332	-18.31	49.21
7	7740.00	59.1 PK	74.0	-14.9	1.15 H	118	11.34	47.76
8	7740.00	29.0 AV	54.0	-25.0	1.15 H	118	-18.76	47.76
9	9920.00	57.8 PK	74.0	-16.2	1.18 H	245	13.09	44.71
10	9920.00	27.7 AV	54.0	-26.3	1.18 H	245	-17.01	44.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	94.4 PK	114.0	-19.6	1.28 V	283	57.19	37.21
2	*2480.00	64.3 AV	94.0	-29.7	1.28 V	283	27.09	37.21
3	2483.50	58.9 PK	74.0	-15.1	1.18 V	271	21.66	37.24
4	2483.50	28.8 AV	54.0	-25.2	1.18 V	271	-8.44	37.24
5	4960.00	60.9 PK	74.0	-13.1	1.25 V	305	11.69	49.21
6	4960.00	30.8 AV	54.0	-23.2	1.25 V	305	-18.41	49.21
7	7440.00	59.3 PK	74.0	-14.7	1.26 V	256	12.60	46.70
8	7440.00	29.2 AV	54.0	-24.8	1.26 V	256	-17.50	46.70
9	9920.00	58.3 PK	74.0	-15.7	1.20 V	296	13.59	44.71
10	9920.00	28.2 AV	54.0	-25.8	1.20 V	296	-16.51	44.71

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.



BT_8DPSK DH5

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 00	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	72.2 PK	74.0	-1.8	1.00 H	33	35.70	36.50
2	2400.00	42.1 AV	54.0	-11.9	1.00 H	33	5.60	36.50
3	*2402.00	100.8 PK	114.0	-13.2	1.00 H	33	64.28	36.52
4	*2402.00	70.7 AV	94.0	-23.3	1.00 H	33	34.18	36.52
5	4804.00	60.2 PK	74.0	-13.8	1.00 H	26	10.95	49.25
6	4804.00	30.1 AV	54.0	-23.9	1.00 H	26	-19.15	49.25
7	7206.00	59.6 PK	74.0	-14.4	1.03 H	298	13.08	46.52
8	7206.00	29.5 AV	54.0	-24.5	1.03 H	298	-17.02	46.52
9	9608.00	57.6 PK	74.0	-16.4	1.05 H	155	12.70	44.90
10	9608.00	27.5 AV	54.0	-26.5	1.05 H	155	-17.40	44.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	69.1 PK	74.0	-4.9	1.29 V	276	32.60	36.50
2	2400.00	39.0 AV	54.0	-15.0	1.29 V	276	2.50	36.50
3	*2402.00	97.8 PK	114.0	-16.2	1.39 V	320	61.28	36.52
4	*2402.00	67.7 AV	94.0	-26.3	1.39 V	320	31.18	36.52
5	4804.00	60.3 PK	74.0	-13.7	1.35 V	142	11.05	49.25
6	4804.00	30.2 AV	54.0	-23.8	1.35 V	142	-19.05	49.25
7	7206.00	57.8 PK	74.0	-16.2	1.39 V	245	11.28	46.52
8	7206.00	27.7 AV	54.0	-26.3	1.39 V	245	-18.82	46.52
9	9608.00	56.6 PK	74.0	-17.4	1.25 V	206	11.70	44.90
10	9608.00	26.5 AV	54.0	-27.5	1.25 V	206	-18.40	44.90

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	98.8 PK	114.0	-15.2	1.06 H	360	61.93	36.87
2	*2441.00	68.7 AV	94.0	-25.3	1.06 H	360	31.83	36.87
3	4882.00	57.6 PK	74.0	-16.4	1.10 H	240	8.37	49.23
4	4882.00	27.5 AV	54.0	-26.5	1.10 H	240	-21.73	49.23
5	7323.00	58.2 PK	74.0	-15.8	1.12 H	214	11.59	46.61
6	7323.00	28.1 AV	54.0	-25.9	1.12 H	214	-18.51	46.61
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	96.8 PK	114.0	-17.2	1.02 V	320	59.93	36.87
2	*2441.00	66.7 AV	94.0	-27.3	1.02 V	320	29.83	36.87
3	4882.00	59.4 PK	74.0	-14.6	1.04 V	250	10.17	49.23
4	4882.00	29.3 AV	54.0	-24.7	1.04 V	250	-19.93	49.23
5	7323.00	57.4 PK	74.0	-16.6	1.00 V	230	10.79	46.61
6	7323.00	27.3 AV	54.0	-26.7	1.00 V	230	-19.31	46.61

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	96.4 PK	114.0	-17.6	1.00 H	0	59.19	37.21
2	*2480.00	66.3 AV	94.0	-27.7	1.00 H	0	29.09	37.21
3	2483.50	50.9 PK	74.0	-23.1	1.05 H	136	13.66	37.24
4	2483.50	20.8 AV	54.0	-33.2	1.05 H	136	-16.44	37.24
5	4960.00	59.3 PK	74.0	-14.7	1.00 H	223	10.09	49.21
6	4960.00	29.2 AV	54.0	-24.8	1.00 H	223	-20.01	49.21
7	7440.00	57.6 PK	74.0	-16.4	1.00 H	30	10.90	46.70
8	7440.00	27.5 AV	54.0	-26.5	1.00 H	30	-19.20	46.70
9	9920.00	57.3 PK	74.0	-16.7	1.03 H	116	12.59	44.71
10	9920.00	27.2 AV	54.0	-26.8	1.03 H	116	-17.51	44.71
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	94.0 PK	114.0	-20.0	1.10 V	300	56.79	37.21
2	*2480.00	63.9 AV	94.0	-30.1	1.10 V	300	26.69	37.21
3	2483.50	48.6 PK	74.0	-25.4	1.05 V	15	11.36	37.24
4	2483.50	18.5 AV	54.0	-35.5	1.05 V	15	-18.74	37.24
5	4960.00	59.6 PK	74.0	-14.4	1.25 V	246	10.39	49.21
6	4960.00	29.5 AV	54.0	-24.5	1.25 V	246	-19.71	49.21
7	7440.00	57.6 PK	74.0	-16.4	1.15 V	138	10.90	46.70
8	7440.00	27.5 AV	54.0	-26.5	1.15 V	138	-19.20	46.70
9	9920.00	57.4 PK	74.0	-16.6	1.26 V	183	12.69	44.71
10	9920.00	27.3 AV	54.0	-26.7	1.26 V	183	-17.41	44.71

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB.
7. Average value = peak reading + $20\log(\text{duty cycle})$.

4.3 20dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer ROHDE & SCHWARZ	E4446A	MY46180622	May 02, 12	May 01, 13
Horn Antenna EMCO	3117	00062558	Oct.18,12	Oct.17,13
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar 24,12	Mar 23,13
RF Cable IMRO	IMRO-400	10m Cable 2#3m	May 16,12	May 15,13
Signal Amplifier EMCI	EMC 012645	980077	Nov 07,11	Nov 07,12
RF Cable DRAKA	M06/25-RG102	10m Cable 2#	May 16,12	May 15,13
Test software ADT	ADT_Radiated_V7.6.15	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

2. The test was performed in Dongguan Chamber 10m.

4.3.3 TEST PROCEDURE


The EUT was placed on a turn table which was 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on a antenna tower. At the frequency band of 30MHz to 1GHz, The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 to 4 m for horizontal and vertical polarizations.

The spectrum analyzer was receiving the maximum emission level. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

GFSK DH5

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2402	0.932
Middle	2441	0.929
High	2480	0.927

Test Data: Low channel







BUREAU
VERITAS

Test Report No.: RF121022N042

Test Data: Middle channel




Test Data: High channel




8DPSK DH5

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2402	1.26
Middle	2441	1.26
Hight	2480	1.25


Test Data: Low channel



Test Data: Middle channel



Test Data: High channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---