

PRODUCT LABELS

DEVICE LABEL

The product device label can be found on the underside of the Main housing.









Any Alternative Parts MUST be approved by Customer. -50mm 4x R3.0mm-

NOTES:

- 1. Hazardous Substances Specification (HSS) MCV of hazardous substances in homogeneous material meet: PE-HSS-1001
- 2. Color:
 - Film color: Black Pantone 6C
- Print text color: White 3. Thickness: 0.07 +/-0.01mm
- Temperature rating of -20degC to +85degC.
 Label will be applied to a painted magnesium alloy surface.
- 6. Label adhesive required to sustain IPx5 water fall to applied label.
- 7. For on line printing, all text shown in red shall be unique to each label printed (text color will be white). WE-TCFXXXXX :WiFi SSID number

15digit : IMEI of internal Afterburner module 15digit : IMEI of internal TOBY-L210 module

TCFxxxxx: Serial number of device

code128 Barcode: Serial number in barcode format

8. Barcode artwork only for reference, add barcode to each label, reference dimension of barcode 3mm x ~19mm



Scale*	Roughness	Tolerance unless otherwise stated		Original Sheet Size*		
2:1		+/- 0.2mm			~ 4	
oc mm	Material Fass	on® 2 Mil W	BEAM P/N:			
Projection 3rd. Angle	_	ester TC/S33	LBLSPP0149			
VΨ	Treatment Finish				Date	
Approved 1	Date Title C	Title Cioffi Device Label			01-Aug-2017	
2			Sheet	1 Of 1 Sheets		
3	Drawn:	GI	Date: 08 Mar 2017	Checked:		
BEAM Beam Communications P/L 8 Anzed Court, Mulgrave Victoria 3170 AUSTRALIA						

JST BE CERTIFIED ROHS - EU Directive 2002/95/EC nogenous weight percentage must be less than: Lead-c0.1%, Hex. Chromium-c0.1%, ruy-c0.1%, Polybro.Biphenyis-c0.1%, Polybro.Biphenyis-c0.1%, Cadmium-c0.01%.



PART 15 LABEL

The Part 15 label can be found on the backside of the Radome.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause interference; and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device







Any Alternative Parts MUST be approved by Customer.



JST BE CERTIFIED RoHS - EU Directive 2002/95/EC rogenous weight percentage must be less than: Lead-ol. 1%, Hex.Chromium-ol. 1%, cury-ol. 1%, Polybro Biphenyis-ol. 1%, Polybro DiphenyiEthers-ol. 1%, Cadmium-ol. 0.1%.



1:1 scale

NOTES:


- 1. Hazardous Substances Specification (HSS) MCV of hazardous substances in homogeneous material meet: PE-HSS-1001
- 2. Color:
 - Film color: Pantone Black 6C

- Print text color: Pantone 428C

 3. Thickness: 0.07 +/-0.01mm

 4. Temperature rating of -20degC to +85degC.

 5. Label will be applied to a painted magnesium alloy surface.
- 6. Label adhesive required to sustain IPx5 water fall to applied label.



4x R3.0mm

Scale*	Roughness		otherwise stated	Original Sheet Size* A4			
	+/-0.2mm Material Fasson® 2 Mil White Polyester TC/S333 (Spec# 72825)			BEAM P/N: LBLSPP0154			
1 •	Treatment				Date		
Approved 1	Date Title	FCC Part15 Label			19-Jul-2017		
2			Sheet '	1 Of 1 Sheets			
3	Drawn:	GI	Date: 29 Mar 2017	Checked:			
BEAM Beam Communications P/L 8 Anzed Court, Mulgrave Victoria 3170 AUSTRALIA							