

FCC PART 22H, 24E

## MEASUREMENT AND TEST REPORT

For

**ITALCOM GROUP**

6303 Blue Lagoon Dr. Suite 400, Miami, Florida 33126, USA

**FCC ID: YPVITALCOMIQUQ**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Mobile Phone
<b>Test Engineer:</b> <u>Jimmy Xiao</u> <i>Jimmy Xiao</i>	
<b>Report Number:</b> <u>RSZ11010702-22H&amp;24E</u>	
<b>Report Date:</b> <u>2011-01-21</u>	
<b>Reviewed By:</b> <u>EMC Engineer</u> <i>Merry Zhao</i>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
JUSTIFICATION .....	6
EQUIPMENT MODIFICATIONS .....	6
CONFIGURATION OF TEST SETUP .....	6
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>FCC §1.1307 &amp; §2.1093 - RF EXPOSURE INFORMATION .....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
TEST RESULT .....	8
<b>FCC §2.1047 - MODULATION CHARACTERISTIC .....</b>	<b>9</b>
<b>FCC §2.1046, §22.913 (A) &amp; §24.232 (C) - RF OUTPUT POWER.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
TEST PROCEDURE .....	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST DATA .....	11
<b>FCC §2.1049, §22.917, §22.905 &amp; §24.238 - OCCUPIED BANDWIDTH .....</b>	<b>13</b>
APPLICABLE STANDARDS.....	13
TEST PROCEDURE .....	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST DATA .....	13
<b>FCC §2.1051, §22.917(A) &amp; §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....</b>	<b>17</b>
APPLICABLE STANDARDS.....	17
TEST PROCEDURE .....	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA .....	17
<b>FCC §2.1053, §22.917 &amp; §24.238 - SPURIOUS RADIATED EMISSIONS .....</b>	<b>21</b>
APPLICABLE STANDARDS.....	21
TEST PROCEDURE .....	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA .....	22
<b>FCC §22.917(A) &amp; §24.238(A) - BAND EDGES.....</b>	<b>24</b>
APPLICABLE STANDARDS.....	24
TEST PROCEDURE .....	24
TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA .....	24
<b>FCC §2.1055, §22.355 &amp; §24.235 - FREQUENCY STABILITY.....</b>	<b>28</b>

APPLICABLE STANDARD .....28

TEST PROCEDURE .....28

TEST EQUIPMENT LIST AND DETAILS.....29

TEST DATA .....29

---

## GENERAL INFORMATION

---

### Product Description for Equipment Under Test (EUT)

The *ITALCOM GROUP*'s product, model number: *iQ (FCC ID: YPVITALCOMIQUQ)* or the "EUT" as referred to in this report is a *Mobile Phone*, which measures approximately: 11.3 cm (L) x 6.3 cm (W) x 1.3 cm (H), rated input voltage: DC 3.7V battery.

#### Frequency Range:

Cellular Band: 824-849MHz (Tx) , 869-894MHz (Rx)  
PCS Band: 1850-1910 MHz (Tx), 1930-1990 MHz (Rx)  
Bluetooth: 2400-2483.5 MHz (Tx/Rx)

Modulation Mode: GMSK (GSM/PCS); GFSK (Bluetooth).

#### Transmitter Output Power:

Cellular Band: 33 dBm, PCS Band: 30 dBm  
Bluetooth: -6~4 dBm

*\* All measurement and test data in this report was gathered from production sample serial number: 1010083 (Assigned by BACL, Shenzhen). The EUT was received on 2010-11-29.*

### Objective

This type approval report is prepared on behalf of *ITALCOM GROUP* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 Bluetooth and FCC Part 15 B submission with FCC ID: YPVITALCOMIQUQ.

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services  
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Justification


The EUT was configured for testing according to TIA/EIA-603-C.

The final qualification test was performed with the EUT operating at normal mode.


### Equipment Modifications

No modifications were made to the EUT.

### Configuration of Test Setup



### Block Diagram of Test Setup



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance *
§2.1046; §22.913 (a); §24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	N/A
§2.1049; §22.905 §22.917; §24.238	99% & -26 dB Occupied Bandwidth	Compliance
§2.1051, §22.917 (a); §24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§2.1053 §22.917 (a); §24.238 (a)	Field Strength of Spurious Radiation	Compliance
§22.917 (a); §24.238 (a)	Out of band emission, Band Edge	Compliance
§2.1055 §22.355; §24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

\* SAR report released by BACL, Report Number: RSZ11010702-SAR

---

**FCC §1.1307 & §2.1093 - RF EXPOSURE INFORMATION**

---

**Applicable Standard**

FCC §1.1307 and §2.1093.

**Test Result****Compliance**

The EUT is a portable device, thus requires SAR evaluation; please refer to BACL SAR  
Report: RSZ11010702-SAR



---

**FCC §2.1047 - MODULATION CHARACTERISTIC**

---

According to FCC §2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

## FCC §2.1046, §22.913 (a) & §24.232 (c) - RF OUTPUT POWER

### Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

### Test Procedure

*Conducted method:*

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



*Radiated method:*

TIA 603-C section 2.2.17

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2010-05-05	2011-05-04
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-03-11	2011-03-11
HP	Amplifier	2VA-213+	T-E27H	2010-03-08	2011-03-07
HP	Signal Generator	HP8657A	2849U00982	2010-10-28	2011-10-27
HP	Amplifier	HP8447D	2944A09795	2010-08-02	2011-08-01
HP	Synthesized Sweeper	8341B	2624A00116	2010-11-07	2011-11-06
Com Power	Dipole Antenna	AD-100	041000	2010-09-25	2011-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2010-05-17	2011-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.0kPa

*The testing was performed by Jimmy Xiao on 2011-01-14.*

**Conducted Power:****Cellular Band (Part 22H)**

Mode	Channel No.	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
GSM	128	824.2	31.58	38.45
	190	836.6	31.61	38.45
	251	848.8	31.59	38.45

Mode	Channel No.	Frequency (MHz)	Output Power (dBm)		Limit (dBm)
			1 uplink slot	2 uplink slot	
GPRS	128	824.2	31.56	31.52	38.45
	190	836.6	31.60	31.54	38.45
	251	848.8	31.55	31.52	38.45

**PCS Band (Part 24E)**

Mode	Channel No.	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	28.60	33
	661	1880.0	28.46	33
	810	1909.8	28.47	33

Mode	Channel No.	Frequency (MHz)	Output Power (dBm)		Limit (dBm)
			1 uplink slot	2 uplink slot	
GPRS	512	1850.2	28.62	28.61	33
	661	1880.0	28.47	28.46	33
	810	1909.8	28.49	28.45	33

**ERP & EIRP:****ERP for Cellular Band (Part 22H)**

Indicated		Table Angle Degree	Test Antenna		Substituted			Antenna Gain Correction (dBd)	Cable Loss (dB)	Absolute Level (dBm)	Part 22H Limit (dBm)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)				
Middle Channel											
836.6	86.32	180	1.5	H	836.6	25.5	H	0	0.68	24.82	38.45
836.6	94.32	210	2.1	V	836.6	30.4	V	0	0.68	29.72	38.45

**EIRP for PCS Band (Part 24E)**

Indicated		Table Angle Degree	Test Antenna		Substituted			Antenna Gain Correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Part 24E Limit (dBm)
Frequency (MHz)	S.A. Reading (dBμV/m)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)				
Low Channel											
1850.2	94.93	330	1.8	H	1850.2	20.7	H	6.2	1.10	25.80	33
1850.2	95.35	158	2.1	V	1850.2	22.6	V	6.2	1.10	27.70	33

Note: All above data were tested with no amplifier.

## FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH


### Applicable Standards

FCC §2.1049, §22.917, §22.905 and §24.238.

### Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 30 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2010-11-24	2011-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

*The testing was performed by Jimmy Xiao on 2011-01-15.*

**GMSK:**

## Cellular Band (Part 22H)

Channel No.	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
190	836.6	250.0	336.0


## PCS Band (Part 24E)

Channel No.	Frequency (MHz)	99% Bandwidth (kHz)	26 dB Bandwidth (kHz)
661	1880.0	250.0	336.0

Please refer to the following plots.


## Cellular Band (Part 22H)

## 99% Occupied Bandwidth



Date: 15.JAN.2011 11:29:44


## 26 dB Occupied Bandwidth



Date: 15.JAN.2011 11:28:38


## PCS Band (Part 24E)

## 99% Occupied Bandwidth



Date: 15.JAN.2011 11:23:37

## 26 dB Occupied Bandwidth



Date: 15.JAN.2011 11:21:24



## FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


### Applicable Standards

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

### Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

*The testing was performed by Jimmy Xiao on 2011-01-15.*

Please refer to the following plots.


## Cellular Band (Part 22H)

## 30 – 1000 MHz - Middle Channel




Date: 15.JAN.2011 11:45:06

## 1 – 3 GHz - Middle Channel




Date: 16.JAN.2011 17:23:56

## 3 – 10 GHz - Middle Channel




## PCS Band (Part24E)

## 30 – 1000 MHz - Middle Channel




Date: 15.JAN.2011 11:50:35

## 1 - 3 GHz - Middle Channel



Date: 16.JAN.2011 17:26:48

## 3 - 20 GHz - Middle Channel



## FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

### Applicable Standards

FCC §2.1053, §22.917 and §24.238.

### Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB =  $10 \lg (\text{TXpwr in Watts}/0.001)$  – the absolute level

Spurious attenuation limit in dB =  $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2010-05-05	2011-05-04
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-03-11	2011-03-11
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07
HP	Amplifier	2VA-213+	T-E27H	2010-03-08	2011-03-07
HP	Signal Generator	HP8657A	2849U00982	2010-10-28	2011-10-27
HP	Amplifier	HP8447D	2944A09795	2010-08-02	2011-08-01
HP	Synthesized Sweeper	8341B	2624A00116	2010-11-07	2011-11-06
COM POWER	Dipole Antenna	AD-100	041000	2010-09-25	2011-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2010-05-17	2011-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.0kPa

The testing was performed by Jimmy Xiao on 2011-01-15.

Test mode: Transmitting

**Cellular Band (Part 22H)**

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel, Below 1 GHz											
812.36	43.69	180	1.5	H	812.36	-53.6	0	0.67	-54.27	-13	41.27
889.35	39.65	335	1.4	H	889.35	-55.1	0	0.69	-55.79	-13	42.79
752.65	38.47	210	1.8	V	752.65	-57.3	0	0.64	-57.94	-13	44.94
483.65	36.54	250	1.9	V	483.65	-58.4	0	0.49	-58.89	-13	45.89

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBuV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel, Above 1 GHz											
1673.0	52.86	180	1.5	H	1673.0	-48.1	6.2	0.94	-42.84	-13	29.84
1673.0	50.31	160	2.1	V	1673.0	-49.3	6.2	0.94	-44.04	-13	31.04
2495.9	46.11	180	2.3	V	2495.9	-51.7	7.3	1.19	-45.59	-13	32.59
2495.9	45.66	0	2.5	H	2495.9	-52.3	7.3	1.19	-46.19	-13	33.19
3346.4	37.61	320	1.8	V	3346.4	-56.4	6.7	1.39	-51.09	-13	38.09
3346.4	36.86	360	1.4	H	3346.4	-57.1	6.7	1.39	-51.79	-13	38.79

## PCS Band (Part 24E)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBd)	Cable Loss (dB)			
Middle Channel, Below 1 GHz											
687.39	41.23	130	2.1	H	687.39	-53.6	0	0.60	-54.2	-13	41.20
425.36	39.65	180	1.8	V	425.36	-57.1	0	0.45	-57.55	-13	44.55
245.65	37.45	250	1.4	V	245.65	-59.3	0	0.30	-59.60	-13	46.60
812.54	35.62	210	1.0	H	812.54	-60.2	0	0.67	-60.87	-13	47.87

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel, Above 1 GHz											
7520	41.72	310	1.4	H	7520	-41.3	7.6	2.10	-35.09	-13	22.09
7520	43.31	270	2.6	V	7520	-41.4	7.6	2.10	-35.19	-13	22.19
3760	51.08	300	1.7	V	3760	-42.8	6.9	1.47	-36.84	-13	23.84
3760	50.85	250	1.5	H	3760	-43.4	6.9	1.47	-37.44	-13	24.44
5640	44.64	180	2.1	H	5640	-49.1	8.3	1.76	-41.99	-13	28.99
5640	42.98	150	2.3	V	5640	-51.6	8.3	1.76	-44.49	-13	31.49

## FCC §22.917(a) & §24.238(a) - BAND EDGES

### Applicable Standards


According to FCC § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to FCC §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

### Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2010-11-24	2011-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

*The testing was performed by Jimmy Xiao on 2011-01-15.*



Please refer to the following tables and plots.


Cellular Band (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.976	-15.76	-13
849.004	-14.94	-13

PCS Band (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1850.000	-18.33	-13
1910.020	-16.58	-13

## Cellular Band, Lowest Channel




Date: 15.JAN.2011 10:51:05

## Cellular Band, Highest Channel




Date: 15.JAN.2011 10:54:38

## PCS Band, Lowest Channel



Date: 15.JAN.2011 10:59:52

## PCS Band, Highest Channel



Date: 15.JAN.2011 11:03:11

## FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

### Applicable Standard

FCC §2.1055 (a), §2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

### Test Procedure

**Frequency Stability vs. Temperature:** The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

**Frequency Stability vs. Voltage:** An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2010-06-04	2011-06-03
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2010-06-11	2011-06-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Data

### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

*The testing was performed by Jimmy Xiao on 2011-01-16.*

### Cellular Band (Part 22H)

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-20	3.7 V	-16	-0.0191	2.5
-10		-15	-0.0179	2.5
0		-13	-0.0155	2.5
10		-11	-0.0131	2.5
20		-13	-0.0155	2.5
25		-14	-0.0167	2.5
35		-12	-0.0143	2.5
45		-10	-0.0120	2.5
55		-9	-0.0108	2.5
25	V max.= 4.2 V	-14	-0.0167	2.5
	V min.= 3.5 V	-16	-0.0191	2.5

## PCS Band (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Result
-20	3.7 V	-36	-0.0191	pass
-10		-38	-0.0202	pass
0		-45	-0.0239	pass
10		-41	-0.0218	pass
20		-40	-0.0213	pass
25		-42	-0.0223	pass
35		-46	-0.0245	pass
45		-45	-0.0239	pass
55		-45	-0.0239	pass
25	V max.= 4.2 V	-37	-0.0197	pass
	V min.= 3.5 V	-39	-0.0207	pass

\*\*\*\*\* END OF REPORT \*\*\*\*\*