



FCC PART 15.247 TEST REPORT

For

ITALCOM GROUP

1728 Coral Way, Coral Gables, Miami, Florida 33145, USA

FCC ID: YPVITALCOMFLYMINI

Report Type: Product Type: Original Report Mobile Phone Am lin **Test Engineer:** Ares Liu **Report Number:** RSZ140304015-00A **Report Date:** 2014-03-19 Ivan Cao fram Car **Reviewed By:** RF Leader Bay Area Compliance Laboratories Corp. (Dongguan) **Test Laboratory:** No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

| GENERAL INFORMATION | 4 |
|--|----|
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | |
| Objective | |
| RELATED SUBMITTAL(S)/GRANT(S) | |
| TEST METHODOLOGY | |
| SYSTEM TEST CONFIGURATION | |
| DESCRIPTION OF TEST CONFIGURATION | |
| EUT Exercise Software | |
| EQUIPMENT MODIFICATIONS | |
| SUPPORT EQUIPMENT LIST AND DETAILS | |
| EXTERNAL I/O CABLE | |
| BLOCK DIAGRAM OF TEST SETUP | |
| SUMMARY OF TEST RESULTS | |
| FCC §15.247 (i) & §2.1093 – RF EXPOSURE | |
| APPLICABLE STANDARD | |
| FCC §15.203 - ANTENNA REQUIREMENT | |
| APPLICABLE STANDARD | 10 |
| ANTENNA CONNECTOR CONSTRUCTION | |
| FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS | |
| APPLICABLE STANDARD | |
| MEASUREMENT UNCERTAINTY | |
| EUT SETUPEMI TEST RECEIVER SETUP | |
| TEST PROCEDURE | |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | |
| TEST EQUIPMENT LIST AND DETAILS. | |
| TEST RESULTS SUMMARY | |
| TEST DATA | |
| FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS | |
| Applicable Standard | |
| EUT SETUP | |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | |
| Test Procedure | |
| TEST EQUIPMENT LIST AND DETAILS. | |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | |
| TEST RESULTS SUMMARY | |
| TEST DATA | |
| FCC §15.247(a) (1) - CHANNEL SEPARATION TEST | |
| APPLICABLE STANDARDTEST EQUIPMENT LIST AND DETAILS | |
| TEST PROCEDURE Test Procedure | |
| TEST DATA | 27 |
| FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING | 33 |

| APPLICABLE STANDARD | 33 |
|---|----|
| TEST PROCEDURE | 33 |
| TEST EQUIPMENT LIST AND DETAILS | |
| TEST DATA | |
| FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST | 39 |
| APPLICABLE STANDARD | |
| TEST PROCEDURE | |
| | |
| TEST EQUIPMENT LIST AND DETAILS | |
| TEST DATA | 39 |
| FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME) | 43 |
| APPLICABLE STANDARD | 43 |
| Test Procedure | |
| TEST EQUIPMENT LIST AND DETAILS | |
| Test Data | |
| FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT | 59 |
| APPLICABLE STANDARD | |
| TEST PROCEDURE | |
| TEST EQUIPMENT LIST AND DETAILS. | |
| Test Data | |
| ECC 915 247(J) DAND EDCES TESTING | (5 |
| FCC §15.247(d) - BAND EDGES TESTING | |
| APPLICABLE STANDARD | |
| TEST PROCEDURE | |
| TEST EQUIPMENT LIST AND DETAILS | |
| Trox DATA | 65 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *ITALCOM GROUP*'s product, model number: *FLY MINI (FCC ID: YPVITALCOMFLYMINI)* (the "EUT") in this report was a *Mobile Phone*, which was measured approximately: 11.8 cm (L) x 6.3 cm (W) x 1.0 cm (H), rated input voltage: DC 3.7 V from lithium battery or DC 4.2V charging from adapter.

Report No.: RSZ140304015-00A

Adapter information:

Input: AC 100-250V, 50-60Hz Output: DC 4.2V ± 0.5V, 500mA

Objective

This report is prepared on behalf of *ITALCOM GROUP* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: YPVITALCOMFLYMINI FCC Part 15C DTS submissions with FCC ID: YPVITALCOMFLYMINI FCC Part 22H & 24E PCE submissions with FCC ID: YPVITALCOMFLYMINI

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

FCC Part 15.247 Page 4 of 68

^{*} All measurement and test data in this report was gathered from production sample serial number: 140304015 (Assigned by BACL.Dongguan). The EUT was received on 2014-03-07.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: RSZ140304015-00A

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at http://ts.nist.gov/standards/scopes/5000690.htm

FCC Part 15.247 Page 5 of 68

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer. The engineering mode was controlled by the Bluetooth Tester.

Report No.: RSZ140304015-00A

EUT Exercise Software

No software was used.

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


| Manufacturer | Description | Model | Serial Number |
|--------------|------------------|----------|---------------|
| TESCOM | Bluetooth Tester | TC-3000C | 3000C000314 |

External I/O Cable

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | То |
|-------------------|-------------------|--------------|------------|-----------|----------|
| USB Cable | yes | No | 1.0 | EUT | Adapter |
| Earphone Cable | No | No | 0.8 | EUT | Earphone |

FCC Part 15.247 Page 6 of 68

Block Diagram of Test Setup



FCC Part 15.247 Page 7 of 68

SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|---------------------------------------|----------------------------------|------------|
| §15.247 (i), §1.1307 (b) (1)& §2.1093 | RF Exposure | Compliace |
| §15.203 | Antenna Requirement | Compliance |
| §15.207 (a) | Conducted Emissions | Compliace |
| \$15.205, \$15.209, \$15.247(d) | Radiated Emissions | Compliance |
| §15.247 (a)(1) | 20 dB Bandwidth | Compliance |
| §15.247(a)(1) | Channel Separation Test | Compliance |
| §15.247(a)(1)(iii) | Time of Occupancy (Dwell Time) | Compliance |
| §15.247(a)(1)(iii) | Quantity of hopping channel Test | Compliance |
| §15.247(b)(1) | Peak Output Power Measurement | Compliance |
| §15.247(d) | Band Edges | Compliance |

Report No.: RSZ140304015-00A

FCC Part 15.247 Page 8 of 68

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RSZ140304015-00A

The SAR data please refer to the SAR report, report No.: RSZ140304015-20.

FCC Part 15.247 Page 9 of 68

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RSZ140304015-00A

Antenna Connector Construction

The EUT has one internal antenna arrangement for bluetooth, the antenna gain is 2.4 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC Part 15.247 Page 10 of 68

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RSZ140304015-00A

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\text{cispr}}$$

| Measurement | $U_{ m cispr}$ |
|---|----------------|
| Conducted disturbance at mains port using AMN (150 kHz to 30 MHz) | 3.4 dB |

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 11 of 68

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

Report No.: RSZ140304015-00A

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 V_C : corrected voltage amplitude V_R : reading voltage amplitude A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 12 of 68

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|----------|------------------|---------------------|-------------------------|
| R&S | EMI Test Receiver | ESCS 30 | 830245/006 | 2013-11-20 | 2014-11-19 |
| R&S | Two-line V-network | ENV216 | 3560.6550.12 | 2014-01-22 | 2015-01-21 |
| R&S | L.I.S.N | ESH3-Z5 | 100113 | N/A | N/A |
| BACL | Test Software | BACL-EMC | V1.0-2010 | N/A | N/A |

Report No.: RSZ140304015-00A

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

10.59 dB at 0.830 MHz in the Neutral conducted mode

Test Data

Environmental Conditions

| Temperature: | 22.7 °C |
|--------------------|-----------|
| Relative Humidity: | 40 % |
| ATM Pressure: | 101.6 kPa |


The testing was performed by Ares Liu on 2014-03-14.

FCC Part 15.247 Page 13 of 68

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Charging&Transmitting


AC 120 V, 60 Hz, Line:



| Frequency (MHz) | Cord. Reading (dBµV) | Correction Factor (dB) | Limit (dBµV) | Margin (dB) | Detector (PK/AV/QP) |
|--------------------|----------------------------|------------------------------|-----------------|----------------|------------------------|
| 0.490 | 38.15 | 9.96 | 56.17 | 18.02 | QP |
| 0.490 | 32.96 | 9.96 | 46.17 | 13.21 | AV |
| 1.220 | 33.66 | 9.72 | 56.00 | 22.34 | QP |
| 1.220 | 24.13 | 9.72 | 46.00 | 21.87 | AV |
| 1.650 | 37.92 | 9.72 | 56.00 | 18.08 | QP |
| 1.650 | 22.91 | 9.72 | 46.00 | 23.09 | AV |
| 1.770 | 39.89 | 9.72 | 56.00 | 16.11 | QP |
| 1.770 | 29.38 | 9.72 | 46.00 | 16.62 | AV |
| 1.940 | 39.97 | 9.72 | 56.00 | 16.03 | QP |
| 1.940 | 24.37 | 9.72 | 46.00 | 21.63 | AV |
| 27.120 | 38.53 | 9.98 | 60.00 | 21.47 | QP |
| 27.120 | 32.11 | 9.98 | 50.00 | 17.89 | AV |

FCC Part 15.247 Page 14 of 68

AC 120 V, 60 Hz, Neutral:



| Frequency (MHz) | Cord. Reading (dBµV) | Correction Factor (dB) | Limit (dBµV) | Margin (dB) | Detector (PK/AV/QP) |
|--------------------|----------------------------|------------------------------|-----------------|----------------|------------------------|
| 0.470 | 38.33 | 10.03 | 56.51 | 18.18 | QP |
| 0.470 | 33.54 | 10.03 | 46.51 | 12.97 | AV |
| 0.780 | 38.32 | 9.82 | 56.00 | 17.68 | QP |
| 0.780 | 34.62 | 9.82 | 46.00 | 11.38 | AV |
| 0.830 | 38.85 | 9.82 | 56.00 | 17.15 | QP |
| 0.830 | 35.41 | 9.82 | 46.00 | 10.59 | AV |
| 1.480 | 37.52 | 9.77 | 56.00 | 18.48 | QP |
| 1.480 | 29.14 | 9.77 | 46.00 | 16.86 | AV |
| 1.770 | 37.38 | 9.74 | 56.00 | 18.62 | QP |
| 1.770 | 26.70 | 9.74 | 46.00 | 19.30 | AV |
| 27.120 | 40.45 | 10.02 | 60.00 | 19.55 | QP |
| 27.120 | 34.35 | 10.02 | 50.00 | 15.65 | AV |

FCC Part 15.247 Page 15 of 68

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RSZ140304015-00A

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 1 – Values of $U_{\rm cispr}$

| Measurement | | | | |
|--|--------|--|--|--|
| Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz) | 6.3 dB | | | |
| Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz) | 5.2 dB | | | |
| Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz) | 5.5 dB | | | |


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 16 of 68

Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|------------------|---------|-----------|---------|----------|
| 30MHz – 1000 MHz | 120 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1MHz | 3 MHz | / | PK |
| Above I GHZ | 1MHz | 10 Hz | / | Ave. |

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 17 of 68

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------------------|-------------------|---------------------|--------------------|---------------------|-------------------------|
| R&S | EMI Test Receiver | ESCI | 100224 | 2013-05-06 | 2014-05-05 |
| Sunol Sciences | Antenna | JB3 | A060611-1 | 2011-09-06 | 2014-09-05 |
| HP | Amplifier | 8447E | 2434A02181 | 2013-09-06 | 2014-09-05 |
| R&S | Spectrum Analyzer | FSEM | DE31388 | 2013-05-07 | 2014-05-06 |
| ETS-Lindgren | Horn Antenna | 3115 | 000 527 35 | 2012-09-06 | 2015-09-05 |
| Mini-Circuit | Amplifier | ZVA-213-S+ | 054201245 | 2014-02-19 | 2015-02-18 |
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |
| Ducommun Technolagies | horn antenna | ARH-4223-02 | 1007726-01 1304 | 2013-06-16 | 2014-06-15 |
| Quinstar | Amplifier | QLW- 18405536-JO | 15964001001 | 2013-09-06 | 2014-09-05 |

Report No.: RSZ140304015-00A

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit - Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

6.53 dB at **2390 MHz** in the **Horizontal** polarization of EDR Mode ($\pi/4$ -DQPSK)

Test Data

Environmental Conditions

| Temperature: | 19.4 °C |
|--------------------|-----------|
| Relative Humidity: | 67 % |
| ATM Pressure: | 100.0 kPa |

The testing was performed by Ares Liu on 2014-03-12.

Mode: Transmitting

FCC Part 15.247 Page 18 of 68

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Report No.: RSZ140304015-00A

BDR Mode (GFSK):

| Frequency | de (GFSK): Re | eceiver | Rx A | ntenna | Cable | Amplifier | Corrected | FCC 1 | 15.247 |
|-----------|------------------|------------------------|----------------|----------------------|--------------|--------------|--------------------|----------------|-------------|
| (MHz) | Reading (dBµV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB/m) | loss (dB) | Gain (dB) | Amplitude (dBμV/m) | Limit (dBµV/m) | Margin (dB) |
| | | | I | ow Channe | el: 2402(N | ИHz) | | | |
| 2402 | 65.39 | PK | Н | 25.65 | 4.42 | 0.00 | 95.46 | N/A | N/A |
| 2402 | 28.63 | AV | Н | 25.65 | 4.42 | 0.00 | 58.70 | N/A | N/A |
| 2402 | 57.12 | PK | V | 25.65 | 4.42 | 0.00 | 87.19 | N/A | N/A |
| 2402 | 22.41 | AV | V | 25.65 | 4.42 | 0.00 | 52.48 | N/A | N/A |
| 2390 | 28.52 | PK | Н | 25.61 | 4.39 | 0.00 | 58.52 | 74.00 | 15.48 |
| 2390 | 15.41 | AV | Н | 25.61 | 4.39 | 0.00 | 45.41 | 54.00 | 8.59 |
| 4804 | 57.24 | PK | Н | 30.59 | 5.98 | 27.41 | 66.40 | 74.00 | 7.60 |
| 4804 | 25.31 | AV | Н | 30.59 | 5.98 | 27.41 | 34.47 | 54.00 | 19.53 |
| 7206 | 45.63 | PK | Н | 34.09 | 7.45 | 25.91 | 61.26 | 74.00 | 12.74 |
| 7206 | 21.1 | AV | Н | 34.09 | 7.45 | 25.91 | 36.73 | 54.00 | 17.27 |
| 9608 | 35.47 | PK | Н | 35.96 | 8.80 | 27.55 | 52.68 | 74.00 | 21.32 |
| 9608 | 20.14 | AV | Н | 35.96 | 8.80 | 27.55 | 37.35 | 54.00 | 16.65 |
| 2654 | 32.22 | PK | Н | 26.30 | 4.83 | 27.46 | 35.89 | 74.00 | 38.11 |
| 2654 | 18.46 | AV | Н | 26.30 | 4.83 | 27.46 | 22.13 | 54.00 | 31.87 |
| 182 | 27.6 | QP | Н | 11.37 | 1.56 | 21.45 | 19.08 | 43.50 | 24.42 |
| 2441 | 64.47 | PK | H | iddle Chant 25.75 | 4.40 | 0.00 | 94.62 | N/A | N/A |
| 2441 | 27.63 | AV | Н | 25.75 | 4.40 | 0.00 | 57.78 | N/A N/A | N/A N/A |
| 2441 | 56.14 | PK | V | 25.75 | 4.40 | 0.00 | 86.29 | N/A N/A | N/A N/A |
| 2441 | 21.1 | AV | V | 25.75 | 4.40 | 0.00 | 51.25 | N/A | N/A |
| 4882 | 56.24 | PK | H | 30.79 | 6.08 | 27.42 | 65.69 | 74.00 | 8.31 |
| 4882 | 23.17 | AV | Н | 30.79 | 6.08 | 27.42 | 32.62 | 54.00 | 21.38 |
| 7323 | 42.58 | PK | Н | 34.38 | 7.51 | 25.88 | 58.59 | 74.00 | 15.41 |
| 7323 | 21.15 | AV | Н | 34.38 | 7.51 | 25.88 | 37.16 | 54.00 | 16.84 |
| 9764 | 36.57 | PK | Н | 36.33 | 8.83 | 27.20 | 54.53 | 74.00 | 19.47 |
| 9764 | 21.49 | AV | Н | 36.33 | 8.83 | 27.20 | 39.45 | 54.00 | 14.55 |
| 2654 | 33.21 | PK | Н | 26.30 | 4.83 | 27.46 | 36.88 | 74.00 | 37.12 |
| 2654 | 18.2 | AV | Н | 26.30 | 4.83 | 27.46 | 21.87 | 54.00 | 32.13 |
| 1852 | 30.56 | PK | Н | 24.30 | 3.76 | 27.52 | 31.10 | 74.00 | 42.90 |
| 1852 | 17.54 | AV | Н | 24.30 | 3.76 | 27.52 | 18.08 | 54.00 | 35.92 |
| 182 | 26.8 | QP | Н | 11.37 | 1.56 | 21.45 | 18.28 | 43.50 | 25.22 |
| | | | | Iigh Channe | | | | | |
| 2480 | 65.12 | PK | Н | 25.85 | 4.48 | 0.00 | 95.45 | N/A | N/A |
| 2480 | 28.05 | AV | Н | 25.85 | 4.48 | 0.00 | 58.38 | N/A | N/A |
| 2480 | 56.94 | PK | V | 25.85 | 4.48 | 0.00 | 87.27 | N/A | N/A |
| 2480 | 22.06 | AV | V | 25.85 | 4.48 | 0.00 | 52.39 | N/A | N/A |
| 2483.5 | 33.26 | PK | Н | 25.86 | 4.49 | 0.00 | 63.61 | 74.00 | 10.39 |
| 2483.5 | 14.5 | AV | Н | 25.86 | 4.49 | 0.00 | 44.85 | 54.00 | 9.15 |
| 4960 | 54.17 | PK | Н | 31.00 | 5.90 | 27.43 | 63.64 | 74.00 | 10.36 |
| 4960 | 22.04 | AV | Н | 31.00 | 5.90 | 27.43 | 31.51 | 54.00 | 22.49 |
| 7440 | 39.87 | PK | Н | 34.66 | 7.58 | 25.97 | 56.14 | 74.00 | 17.86 |
| 7440 | 19.57 | AV | Н | 34.66 | 7.58 | 25.97 | 35.84 | 54.00 | 18.16 |
| 9920 | 35.48 | PK | Н | 36.71 | 8.87 | 26.66 | 54.40 | 74.00 | 19.60 |
| 9920 | 20.44 | AV | Н | 36.71 | 8.87 | 26.66 | 39.36 | 54.00 | 14.64 |
| 2654 | 30.56 | PK | Н | 26.30 | 4.83 | 27.46 | 34.23 | 74.00 | 39.77 |
| 2654 | 16.88 | AV | Н | 26.30 | 4.83 | 27.46 | 20.55 | 54.00 | 33.45 |
| 182 | 26.5 | QP | Н | 11.37 | 1.56 | 21.45 | 17.98 | 43.50 | 25.52 |

FCC Part 15.247 Page 19 of 68

Report No.: RSZ140304015-00A

EDR Mode ($\pi/4$ -DQPSK):

| Frequency | R | eceiver | Rx A | ntenna | Cable | Amplifier | Corrected | FCC 1 | 5.247 |
|-----------|----------------|------------------------|----------------|---------------|--------------|--------------|--------------------|----------------|-------------|
| (MHz) | Reading (dBµV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB/m) | loss (dB) | Gain (dB) | Amplitude (dBμV/m) | Limit (dBµV/m) | Margin (dB) |
| | | | I | ow Channe | el: 2402(N | ИHz) | | | |
| 2402 | 64.74 | PK | Н | 25.65 | 4.42 | 0.00 | 94.81 | N/A | N/A |
| 2402 | 26.11 | AV | Н | 25.65 | 4.42 | 0.00 | 56.18 | N/A | N/A |
| 2402 | 54.36 | PK | V | 25.65 | 4.42 | 0.00 | 84.43 | N/A | N/A |
| 2402 | 19.47 | AV | V | 25.65 | 4.42 | 0.00 | 49.54 | N/A | N/A |
| 2390 | 32.55 | PK | Н | 25.61 | 4.39 | 0.00 | 62.55 | 74.00 | 11.45 |
| 2390 | 17.47 | AV | Н | 25.61 | 4.39 | 0.00 | 47.47 | 54.00 | 6.53 |
| 4804 | 52.11 | PK | Н | 30.59 | 5.98 | 27.41 | 61.27 | 74.00 | 12.73 |
| 4804 | 25.63 | AV | Н | 30.59 | 5.98 | 27.41 | 34.79 | 54.00 | 19.21 |
| 7206 | 46.28 | PK | Н | 34.09 | 7.45 | 25.91 | 61.91 | 74.00 | 12.09 |
| 7206 | 21.14 | AV | Н | 34.09 | 7.45 | 25.91 | 36.77 | 54.00 | 17.23 |
| 9608 | 35.49 | PK | Н | 35.96 | 8.80 | 27.55 | 52.70 | 74.00 | 21.30 |
| 9608 | 18.65 | AV | Н | 35.96 | 8.80 | 27.55 | 35.86 | 54.00 | 18.14 |
| 2654 | 35.16 | PK | Н | 26.30 | 4.83 | 27.46 | 38.83 | 74.00 | 35.17 |
| 2654 | 20.11 | AV | Н | 26.30 | 4.83 | 27.46 | 23.78 | 54.00 | 30.22 |
| 185 | 26.7 | QP | Н | 11.37 | 1.63 | 21.45 | 18.25 | 43.50 | 25.25 |
| | | | M | iddle Chanr | nel: 2441(| (MHz) | | | |
| 2441 | 64.26 | PK | Н | 25.75 | 4.40 | 0.00 | 94.41 | N/A | N/A |
| 2441 | 26.53 | AV | Н | 25.75 | 4.40 | 0.00 | 56.68 | N/A | N/A |
| 2441 | 56.23 | PK | V | 25.75 | 4.40 | 0.00 | 86.38 | N/A | N/A |
| 2441 | 19.85 | AV | V | 25.75 | 4.40 | 0.00 | 50.00 | N/A | N/A |
| 4882 | 56.32 | PK | Н | 30.79 | 6.08 | 27.42 | 65.77 | 74.00 | 8.23 |
| 4882 | 25.14 | AV | Н | 30.79 | 6.08 | 27.42 | 34.59 | 54.00 | 19.41 |
| 7323 | 45.2 | PK | Н | 34.38 | 7.51 | 25.88 | 61.21 | 74.00 | 12.79 |
| 7323 | 19.87 | AV | Н | 34.38 | 7.51 | 25.88 | 35.88 | 54.00 | 18.12 |
| 9764 | 36.74 | PK | Н | 36.33 | 8.83 | 27.20 | 54.70 | 74.00 | 19.30 |
| 9764 | 21.07 | AV | Н | 36.33 | 8.83 | 27.20 | 39.03 | 54.00 | 14.97 |
| 2654 | 33.26 | PK | Н | 26.30 | 4.83 | 27.46 | 36.93 | 74.00 | 37.07 |
| 2654 | 18.23 | AV | Н | 26.30 | 4.83 | 27.46 | 21.90 | 54.00 | 32.10 |
| 1852 | 32.26 | PK | Н | 24.30 | 3.76 | 27.52 | 32.80 | 74.00 | 41.20 |
| 1852 | 17.05 | AV | Н | 24.30 | 3.76 | 27.52 | 17.59 | 54.00 | 36.41 |
| 185 | 26.9 | QP | Н | 11.37 | 1.63 | 21.45 | 18.45 | 43.50 | 25.05 |
| | | | | Iigh Channe | | | | | |
| 2480 | 63.86 | PK | Н | | 4.48 | | 94.19 | N/A | N/A |
| 2480 | 25.87 | AV | Н | 25.85 | 4.48 | 0.00 | 56.20 | N/A | N/A |
| 2480 | 55.23 | PK | V | 25.85 | 4.48 | 0.00 | 85.56 | N/A | N/A |
| 2480 | 18.69 | AV | V | 25.85 | 4.48 | 0.00 | 49.02 | N/A | N/A |
| 2483.5 | 34.21 | PK | Н | 25.86 | 4.49 | 0.00 | 64.56 | 74.00 | 9.44 |
| 2483.5 | 15.26 | AV | Н | 25.86 | 4.49 | 0.00 | 45.61 | 54.00 | 8.39 |
| 4960 | 52.34 | PK | Н | 31.00 | 5.90 | 27.43 | 61.81 | 74.00 | 12.19 |
| 4960 | 21.47 | AV | Н | 31.00 | 5.90 | 27.43 | 30.94 | 54.00 | 23.06 |
| 7440 | 43.36 | PK | Н | 34.66 | 7.58 | 25.97 | 59.63 | 74.00 | 14.37 |
| 7440 | 21.25 | AV | Н | 34.66 | 7.58 | 25.97 | 37.52 | 54.00 | 16.48 |
| 9920 | 37.28 | PK | Н | 36.71 | 8.87 | 26.66 | 56.20 | 74.00 | 17.80 |
| 9920 | 21.17 | AV | Н | 36.71 | 8.87 | 26.66 | 40.09 | 54.00 | 13.91 |
| 2654 | 33.63 | PK | Н | 26.30 | 4.83 | 27.46 | 37.30 | 74.00 | 36.70 |
| 2654 | 18.26 | AV | Н | 26.30 | 4.83 | 27.46 | 21.93 | 54.00 | 32.07 |
| 185 | 26.9 | QP | Н | 11.37 | 1.63 | 21.45 | 18.45 | 43.50 | 25.05 |

FCC Part 15.247 Page 20 of 68

Report No.: RSZ140304015-00A

EDR Mode (8-DPSK):


| Frequency | de (8-DPSK) R o | eceiver | Rx A | ntenna | Cable | Amplifier | Corrected | FCC 1 | 15.247 |
|-----------|---------------------------|------------------------|----------------|---------------|--------------|--------------|--------------------|----------------|-------------|
| (MHz) | Reading (dBµV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB/m) | loss (dB) | Gain (dB) | Amplitude (dBµV/m) | Limit (dBµV/m) | Margin (dB) |
| | | | Ι | low Channe | el: 2402(N | ИHz) | | | |
| 2402 | 63.52 | PK | Н | 25.65 | 4.42 | 0.00 | 93.59 | N/A | N/A |
| 2402 | 26.41 | AV | Н | 25.65 | 4.42 | 0.00 | 56.48 | N/A | N/A |
| 2402 | 56.44 | PK | V | 25.65 | 4.42 | 0.00 | 86.51 | N/A | N/A |
| 2402 | 20.37 | AV | V | 25.65 | 4.42 | 0.00 | 50.44 | N/A | N/A |
| 2390 | 32.36 | PK | Н | 25.61 | 4.39 | 0.00 | 62.36 | 74.00 | 11.64 |
| 2390 | 16.54 | AV | Н | 25.61 | 4.39 | 0.00 | 46.54 | 54.00 | 7.46 |
| 4804 | 56.47 | PK | Н | 30.59 | 5.98 | 27.41 | 65.63 | 74.00 | 8.37 |
| 4804 | 26.3 | AV | Н | 30.59 | 5.98 | 27.41 | 35.46 | 54.00 | 18.54 |
| 7206 | 45.13 | PK | Н | 34.09 | 7.45 | 25.91 | 60.76 | 74.00 | 13.24 |
| 7206 | 20.63 | AV | Н | 34.09 | 7.45 | 25.91 | 36.26 | 54.00 | 17.74 |
| 9608 | 36.54 | PK | Н | 35.96 | 8.80 | 27.55 | 53.75 | 74.00 | 20.25 |
| 9608 | 20.23 | AV | Н | 35.96 | 8.80 | 27.55 | 37.44 | 54.00 | 16.56 |
| 2654 | 33.41 | PK | Н | 26.30 | 4.83 | 27.46 | 37.08 | 74.00 | 36.92 |
| 2654 | 18.56 | AV | Н | 26.30 | 4.83 | 27.46 | 22.23 | 54.00 | 31.77 |
| 185 | 26.5 | QP | Н | 11.37 | 1.63 | 21.45 | 18.05 | 43.50 | 25.45 |
| | | | M | iddle Chanı | nel: 2441(| MHz) | | | |
| 2441 | 63.24 | PK | Н | 25.75 | 4.40 | 0.00 | 93.39 | N/A | N/A |
| 2441 | 26.37 | AV | Н | 25.75 | 4.40 | 0.00 | 56.52 | N/A | N/A |
| 2441 | 55.49 | PK | V | 25.75 | 4.40 | 0.00 | 85.64 | N/A | N/A |
| 2441 | 20.04 | AV | V | 25.75 | 4.40 | 0.00 | 50.19 | N/A | N/A |
| 4882 | 55.93 | PK | Н | 30.79 | 6.08 | 27.42 | 65.38 | 74.00 | 8.62 |
| 4882 | 25.12 | AV | Н | 30.79 | 6.08 | 27.42 | 34.57 | 54.00 | 19.43 |
| 7323 | 44.24 | PK | Н | 34.38 | 7.51 | 25.88 | 60.25 | 74.00 | 13.75 |
| 7323 | 21.06 | AV | Н | 34.38 | 7.51 | 25.88 | 37.07 | 54.00 | 16.93 |
| 9764 | 36.57 | PK | Н | 36.33 | 8.83 | 27.20 | 54.53 | 74.00 | 19.47 |
| 9764 | 21.14 | AV | Н | 36.33 | 8.83 | 27.20 | 39.10 | 54.00 | 14.90 |
| 2654 | 33.32 | PK | Н | 26.30 | 4.83 | 27.46 | 36.99 | 74.00 | 37.01 |
| 2654 | 19.04 | AV | Н | 26.30 | 4.83 | 27.46 | 22.71 | 54.00 | 31.29 |
| 1852 | 32.52 | PK | Н | 24.30 | 3.76 | 27.52 | 33.06 | 74.00 | 40.94 |
| 1852 | 18.17 | AV | Н | 24.30 | 3.76 | 27.52 | 18.71 | 54.00 | 35.29 |
| 185 | 26.7 | QP | Н | 11.37 | 1.63 | 21.45 | 18.25 | 43.50 | 25.25 |
| | | | | Iigh Chann | | | | | |
| 2480 | 63.54 | PK | Н | | 4.48 | 0.00 | 93.87 | N/A | N/A |
| 2480 | 26.11 | AV | Н | 25.85 | 4.48 | 0.00 | 56.44 | N/A | N/A |
| 2480 | 55.28 | PK | V | 25.85 | 4.48 | 0.00 | 85.61 | N/A | N/A |
| 2480 | 20.3 | AV | V | 25.85 | 4.48 | 0.00 | 50.63 | N/A | N/A |
| 2483.5 | 32.63 | PK | Н | 25.86 | 4.49 | 0.00 | 62.98 | 74.00 | 11.02 |
| 2483.5 | 14.52 | AV | Н | 25.86 | 4.49 | 0.00 | 44.87 | 54.00 | 9.13 |
| 4960 | 55.47 | PK | Н | 31.00 | 5.90 | 27.43 | 64.94 | 74.00 | 9.06 |
| 4960 | 24.3 | AV | Н | 31.00 | 5.90 | 27.43 | 33.77 | 54.00 | 20.23 |
| 7440 | 43.26 | PK | Н | 34.66 | 7.58 | 25.97 | 59.53 | 74.00 | 14.47 |
| 7440 | 20.54 | AV | Н | 34.66 | 7.58 | 25.97 | 36.81 | 54.00 | 17.19 |
| 9920 | 35.63 | PK | Н | 36.71 | 8.87 | 26.66 | 54.55 | 74.00 | 19.45 |
| 9920 | 20.3 | AV | Н | 36.71 | 8.87 | 26.66 | 39.22 | 54.00 | 14.78 |
| 2654 | 33.63 | PK | Н | 26.30 | 4.83 | 27.46 | 37.30 | 74.00 | 36.70 |
| 2654 | 18.5 | AV | Н | 26.30 | 4.83 | 27.46 | 22.17 | 54.00 | 31.83 |
| 185 | 26.9 | QP | Н | 11.37 | 1.63 | 21.45 | 18.45 | 43.50 | 25.05 |

FCC Part 15.247 Page 21 of 68

Conducted Spurious Emissions at Antenna Port


BDR Mode (GFSK):

Low Channel



Date: 12.MAR.2014 17:45:29


Middle Channel



Date: 12.MAR.2014 17:46:13

FCC Part 15.247 Page 22 of 68






Date: 12.MAR.2014 17:46:31

EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 12.MAR.2014 17:46:48

FCC Part 15.247 Page 23 of 68


#: 1 11 C1 1

Report No.: RSZ140304015-00A



Date: 12.MAR.2014 17:47:06

High Channel




Date: 12.MAR.2014 17:47:24

FCC Part 15.247 Page 24 of 68


EDR Mode (8-DPSK):





Date: 12.MAR.2014 17:47:41


Middle Channel



Date: 12.MAR.2014 17:47:59

FCC Part 15.247 Page 25 of 68





Date: 12.MAR.2014 17:48:16

FCC Part 15.247 Page 26 of 68

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ140304015-00A

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another truce
- 3. Measure the channel separation.

Test Data

Environmental Conditions

| Temperature: | 22.8 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.0 kPa |

^{*} The testing was performed by Ares Liu on 2014-03-12

Test Result: Compliance.

Please refer to following tables and plots


FCC Part 15.247 Page 27 of 68

Test Mode: Transmitting

| Mode | Channel | Frequency (MHz) | Channel Separation (MHz) | Limit (MHz) | Result |
|--------------------------|----------|--------------------|--------------------------------|----------------|--------|
| | Low | 2402 | 1.022 | 0.615 | Pass |
| | Adjacent | 2403 | 1.022 | 0.013 | 1 488 |
| BDR Mode | Middle | 2441 | 1.010 | 0.615 | Pass |
| (GFSK) | Adjacent | 2442 | 1.010 | 0.013 | Pass |
| | High | 2480 | 1.002 | 0.617 | Pass |
| | Adjacent | 2479 | 1.002 | 0.01/ | F 455 |
| | Low | 2402 | 1.010 | 0.847 | Pass |
| | Adjacent | 2403 | 1.010 | 0.847 | Pass |
| EDR Mode | Middle | 2441 | 1.001 | 0.871 | Pass |
| $(\pi/4\text{-DQPSK})$: | Adjacent | 2442 | 1.001 | | Pass |
| | High | 2480 | 1.002 | 0.050 | Pass |
| | Adjacent | 2479 | 1.002 | 0.859 | Pass |
| | Low | 2402 | 1.004 | 0.950 | D |
| | Adjacent | 2403 | 1.004 | 0.850 | Pass |
| EDR Mode | Middle | 2441 | 1.002 | 0.965 | Dogg |
| (8-DPSK): | Adjacent | 2442 | 1.002 | 0.865 | Pass |
| | High | 2480 | 1.000 | 0.866 | Pass |
| | Adjacent | 2479 | 1.000 | 0.800 | rass |

BDR Mode (GFSK):


Low Channel



Date: 12.MAR.2014 17:52:05

FCC Part 15.247 Page 28 of 68

Middle Channel



Date: 12.MAR.2014 17:52:23

High Channel




Date: 12.MAR.2014 17:52:42

FCC Part 15.247 Page 29 of 68


EDR Mode ($\pi/4$ -DQPSK):

Low Channel



Date: 12.MAR.2014 17:53:01


Middle Channel



Date: 12.MAR.2014 17:53:20

FCC Part 15.247 Page 30 of 68


High Channel



Date: 12.MAR.2014 17:53:38

EDR Mode (8-DPSK):


Low Channel



Date: 12.MAR.2014 17:53:57


FCC Part 15.247 Page 31 of 68





Date: 12.MAR.2014 17:54:15

High Channel



Date: 12.MAR.2014 17:54:34

FCC Part 15.247 Page 32 of 68

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ140304015-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 22.8 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.0 kPa |

^{*} The testing was performed by Ares Liu on 2014-03-12

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 33 of 68


Test Mode: Transmitting

| Mode | Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |
|-----------------------|---------|--------------------|--------------------------|
| DDD M. I | Low | 2402 | 0.923 |
| BDR Mode (GFSK) | Middle | 2441 | 0.923 |
| (GI SIL) | High | 2480 | 0.925 |
| EDD 14 1 | Low | 2402 | 1.271 |
| EDR Mode (π/4-DQPSK): | Middle | 2441 | 1.307 |
| (M+DQI SIK). | High | 2480 | 1.289 |
| EDD 14 1 | Low | 2402 | 1.275 |
| EDR Mode (8-DPSK): | Middle | 2441 | 1.297 |
| (6-DI 5K). | High | 2480 | 1.299 |

Please refer to the following plots.

BDR Mode (GFSK):


Low Channel



Date: 12.MAR.2014 17:39:28


FCC Part 15.247 Page 34 of 68

Middle Channel



Date: 12.MAR.2014 17:39:48

High Channel




Date: 12.MAR.2014 17:40:08

FCC Part 15.247 Page 35 of 68


EDR Mode (\pi/4-DQPSK):





Date: 12.MAR.2014 17:40:28


Middle Channel



Date: 12.MAR.2014 17:40:48

FCC Part 15.247 Page 36 of 68


High Channel



Date: 12.MAR.2014 17:41:08

EDR Mode (8-DPSK):


Low Channel



Date: 12.MAR.2014 17:41:28


FCC Part 15.247 Page 37 of 68

Middle Channel



Date: 12.MAR.2014 17:41:48

High Channel



Date: 12.MAR.2014 17:42:10

FCC Part 15.247 Page 38 of 68

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Report No.: RSZ140304015-00A

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 22.8 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.0 kPa |

^{*} The testing was performed by Ares Liu on 2014-03-12

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 39 of 68


Test Mode: Transmitting

BDR Mode (GFSK):

| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|--------------------------|------------------------------|-------|
| 2400-2483.5 | 79 | ≥15 |

Report No.: RSZ140304015-00A

Number of Hopping Channels




Date: 12.MAR.2014 18:50:40

FCC Part 15.247 Page 40 of 68

| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|--------------------------|------------------------------|-------|
| 2400-2483.5 | 79 | ≥15 |

Number of Hopping Channels




Date: 12.MAR.2014 18:56:12

FCC Part 15.247 Page 41 of 68

| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|--------------------------|------------------------------|-------|
| 2400-2483.5 | 79 | ≥15 |

Number of Hopping Channels



Date: 12.MAR.2014 19:01:38

FCC Part 15.247 Page 42 of 68

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ140304015-00A

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s Hop rate=1600/s

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 22.8 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.0 kPa |

^{*} The testing was performed by Ares Liu on 2014-03-12

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 43 of 68


Test Mode: Transmitting

BDR Mode (GFSK):

| Mode | Channel | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result | | |
|------|---|------------------------|----------------------|-----------|--------|--|--|
| | Low | 0.388 | 0.124 | 0.4 | Pass | | |
| DH1 | Middle | 0.388 | 0.124 | 0.4 | Pass | | |
| | High | 0.388 | 0.124 | 0.4 | Pass | | |
| | Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s | | | | | | |
| | Low | 1.668 | 0.267 | 0.4 | Pass | | |
| DH3 | Middle | 1.680 | 0.269 | 0.4 | Pass | | |
| Diis | High | 1.668 | 0.267 | 0.4 | Pass | | |
| | Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s | | | | | | |
| | Low | 2.918 | 0.311 | 0.4 | Pass | | |
| DH5 | Middle | 2.918 | 0.311 | 0.4 | Pass | | |
| | High | 2.918 | 0.311 | 0.4 | Pass | | |
| | Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s | | | | | | |

Report No.: RSZ140304015-00A


DH1: Low Channel



Date: 12.MAR.2014 19:51:13


FCC Part 15.247 Page 44 of 68





Date: 12.MAR.2014 19:51:21


DH1: High Channel



Date: 12.MAR.2014 19:51:30


FCC Part 15.247 Page 45 of 68

DH3: Low Channel



Date: 12.MAR.2014 19:52:55


DH3: Middle Channel



Date: 12.MAR.2014 19:52:10


FCC Part 15.247 Page 46 of 68

DH3: High Channel



Date: 12.MAR.2014 19:52:20


DH5: Low Channel



Date: 12.MAR.2014 19:53:39


FCC Part 15.247 Page 47 of 68

DH5: Middle Channel



Date: 12.MAR.2014 19:53:55

DH5: High Channel



Date: 12.MAR.2014 19:54:03


FCC Part 15.247 Page 48 of 68

EDR Mode (\pi/4-DQPSK):

| Mode | Channel | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result | |
|--------------|---|------------------------|----------------------|-----------|--------|--|
| | Low | 0.394 | 0.126 | 0.4 | Pass | |
| DH1 | Middle | 0.394 | 0.126 | 0.4 | Pass | |
| DIII | High | 0.394 | 0.126 | 0.4 | Pass | |
| | Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s | | | | | |
| | Low | 1.674 | 0.268 | 0.4 | Pass | |
| DH3 | Middle | 1.680 | 0.269 | 0.4 | Pass | |
| <i>D</i> 113 | High | 1.674 | 0.268 | 0.4 | Pass | |
| | Note: Dwell time=Pulse time (ms) × (1600/4/79) ×31.6 s | | | | | |
| | Low | 2.934 | 0.313 | 0.4 | Pass | |
| DH5 | Middle | 2.934 | 0.313 | 0.4 | Pass | |
| DIIS | High | 2.934 | 0.313 | 0.4 | Pass | |
| | Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s | | | | | |

Report No.: RSZ140304015-00A


DH1: Low Channel



Date: 12.MAR.2014 19:44:04


FCC Part 15.247 Page 49 of 68

DH1: Middle Channel



Date: 12.MAR.2014 19:43:54


DH1: High Channel



Date: 12.MAR.2014 19:43:47


FCC Part 15.247 Page 50 of 68

DH3: Low Channel



Date: 12.MAR.2014 19:45:01


DH3: Middle Channel



Date: 12.MAR.2014 19:57:03


FCC Part 15.247 Page 51 of 68

DH3: High Channel



Date: 12.MAR.2014 19:45:22


DH5: Low Channel



Date: 12.MAR.2014 19:46:17


FCC Part 15.247 Page 52 of 68

DH5: Middle Channel



Date: 12.MAR.2014 19:46:08

DH5: High Channel




Date: 12.MAR.2014 19:46:01

FCC Part 15.247 Page 53 of 68

EDR Mode (8-DPSK):

| Mode | Channel | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result | |
|---|---|------------------|----------------------|-----------|--------|--|
| | Low | 0.394 | 0.126 | 0.4 | Pass | |
| DH1 | Middle | 0.394 | 0.126 | 0.4 | Pass | |
| DIII | High | 0.394 | 0.126 | 0.4 | Pass | |
| | Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s | | | | | |
| | Low | 1.684 | 0.269 | 0.4 | Pass | |
| DH3 | Middle | 1.684 | 0.269 | 0.4 | Pass | |
| DHS | High | 1.680 | 0.269 | 0.4 | Pass | |
| Note: Dwell time=Pulse time (ms) \times (1600/4/79) | | | | | | |
| | Low | 2.930 | 0.313 | 0.4 | Pass | |
| DH5 | Middle | 2.914 | 0.311 | 0.4 | Pass | |
| DIIS | High | 2.914 | 0.311 | 0.4 | Pass | |
| | Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s | | | | | |


DH1: Low Channel



Date: 12.MAR.2014 19:02:55


FCC Part 15.247 Page 54 of 68

DH1: Middle Channel



Date: 12.MAR.2014 19:03:05


DH1: High Channel



Date: 12.MAR.2014 19:03:19


FCC Part 15.247 Page 55 of 68

DH3: Low Channel




Date: 12.MAR.2014 19:37:24


DH3: Middle Channel



Date: 12.MAR.2014 19:37:16


FCC Part 15.247 Page 56 of 68





Date: 12.MAR.2014 19:58:49


DH5: Low Channel



Date: 12.MAR.2014 20:00:27


FCC Part 15.247 Page 57 of 68

DH5: Middle Channel



Date: 12.MAR.2014 19:38:08

DH5: High Channel



Date: 12.MAR.2014 19:38:16

FCC Part 15.247 Page 58 of 68

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Report No.: RSZ140304015-00A

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 22.8 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.0 kPa |

^{*} The testing was performed by Ares Liu on 2014-03-12.

Test Result: Compliance.

FCC Part 15.247 Page 59 of 68


Test Mode: Transmitting

| Mode | Channel | Frequency (MHz) | Max Peak Output Power (dBm) | Limit (dBm) |
|-------------------------|---------|--------------------|-----------------------------------|----------------|
| BDR Mode (GFSK) | Low | 2402 | -0.40 | 30 |
| | Middle | 2441 | 0.86 | 30 |
| | High | 2480 | 1.44 | 30 |
| EDR Mode (π/4-DQPSK) | Low | 2402 | -0.48 | 30 |
| | Middle | 2441 | 0.75 | 30 |
| | High | 2480 | 1.33 | 30 |
| EDR Mode (8-DPSK) | Low | 2402 | -0.32 | 30 |
| | Middle | 2441 | 0.87 | 30 |
| | High | 2480 | 1.42 | 30 |

Note: The data above was tested in conducted mode.

BDR Mode (GFSK):


Output Power, Low



Date: 12.MAR.2014 17:37:58


FCC Part 15.247 Page 60 of 68

Output Power, Middle



Date: 12.MAR.2014 17:38:08

Output Power, High




Date: 12.MAR.2014 17:38:18

FCC Part 15.247 Page 61 of 68

EDR Mode (\pi/4-DQPSK):


Output Power, Low

Report No.: RSZ140304015-00A



Date: 12.MAR.2014 17:38:27


Output Power, Middle



Date: 12.MAR.2014 17:38:37

FCC Part 15.247 Page 62 of 68


Output Power, High



Date: 12.MAR.2014 17:38:47

EDR Mode (8-DPSK):


Output Power, Low



Date: 12.MAR.2014 17:38:56


FCC Part 15.247 Page 63 of 68

Output Power, Middle



Date: 12.MAR.2014 17:39:06

Output Power, High



Date: 12.MAR.2014 17:39:16

FCC Part 15.247 Page 64 of 68

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RSZ140304015-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to the test equipment, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|------------------|---------------------|-------------------------|
| R&S | Spectrum analyzer | FSP 38 | 100478 | 2013-06-16 | 2014-06-15 |

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| Temperature: | 22.8 °C |
|--------------------|-----------|
| Relative Humidity: | 61 % |
| ATM Pressure: | 100.0 kPa |


^{*} The testing was performed by Ares Liu on 2014-03-12.

FCC Part 15.247 Page 65 of 68

Test Result: Compliance


BDR Mode (GFSK):

Band Edge, Left Side



Date: 12.MAR.2014 17:48:33

Band Edge, Right Side




Date: 12.MAR.2014 17:48:50

FCC Part 15.247 Page 66 of 68

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side

Report No.: RSZ140304015-00A



Date: 12.MAR.2014 17:49:07

Band Edge, Right Side




Date: 12.MAR.2014 17:49:24

FCC Part 15.247 Page 67 of 68

EDR Mode (8-DPSK):


Band Edge, Left Side

Report No.: RSZ140304015-00A



Date: 12.MAR.2014 17:49:41

Band Edge, Right Side



Date: 12.MAR.2014 17:49:58

***** END OF REPORT *****

FCC Part 15.247 Page 68 of 68