

FCC PART 15B
MEASUREMENT AND TEST REPORT

For

Queclink Wireless Solutions Co.,Ltd.

Room 501, Building 9, No 99, TianZhou Road, shanghai, china

FCC ID: YQD-GD100

Report Type: Original Report	Product Type: GD100
Test Engineer: Allen Tian <i>Allen-tian</i>	
Report Number: RKS160421001-00A	
Report Date: 2016-05-03	
Reviewed By: EMC Manager Jesse huang <i>Jesse.Huang</i>	
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road,Kunshan Development Zone No.248,Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION (FCC §15.27)	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
SPECIAL ACCESSORIES.....	4
EQUIPMENT MODIFICATIONS	4
SUPPORT EQUIPMENT LIST AND DETAILS	4
EXTERNAL I/O CABLE.....	4
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §15.107 – AC LINE CONDUCTED EMISSIONS.....	7
APPLICABLE STANDARD	7
MEASUREMENT UNCERTAINTY	7
EUT SETUP	7
EMI TEST RECEIVER SETUP.....	8
TEST PROCEDURE	8
TEST EQUIPMENT LIST AND DETAILS.....	8
CORRECTED FACTOR & MARGIN CALCULATION	8
TEST RESULTS SUMMARY	9
TEST DATA	9
FCC §15.109 - RADIATED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
TEST EQUIPMENT LIST AND DETAILS.....	13
CORRECTION FACTOR & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Queclink Wireless Solutions Co.,Ltd.'s product, model number: GD100 or the "EUT" in this report was a GD100, which was measured approximately: 109 mm (L) × 61 mm (W) × 13(21) mm (H), rated with input voltage: DC 9V, the highest operating frequency is 26MHz when operating at USB disk mode.

**All measurement and test data in this report was gathered from production sample serial number: 160418006 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-04-18*

Objective

This report is prepared on behalf of Queclink Wireless Solutions Co.,Ltd in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15, Class B.

Related Submittal(s)/Grant(s)

FCC Part 22H&24E PCB submissions with FCC ID: YQD-GD100.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION (FCC §15.27)

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

No exercise software was used.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Notebook PC	D420	0002530
Ecosys	Printer	FS-1125MFP	0365
DELL	Mouse	MO-1008BU	M0914
DELL	Keyboard	KB-BL919EB	K0988

External I/O Cable

Cable Description	Length (m)	From/Port	To
Unshielded detachable AC Cable	1.8	Adapter	LISN 1
Unshielded detachable AC Cable	1.8	Printer	LISN 2
Unshielded detachable RJ45 Cable	1.2	Notebook PC	Printer

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC§15.107


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Kunshan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The EUT was connected to an AC 120V/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	831294/005	2015-11-04	2016-11-03
Rohde & Schwarz	LISN	ESH3-Z5	12005	2015-11-04	2016-11-03
Rohde & Schwarz	LISN	ESH3-Z5	12008	2015-06-23	2016-06-22
BACL	RF cable	KS-LAB-09	KS-LAB-09	2015-06-16	2016-12-15
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	--	--

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - (\text{QuasiPeak} \& \text{Average})$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107 Class B, the worst margin reading as below:

12.78 dB at 4.790000 MHz in the **Neutral** conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25°C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa


The testing was performed by Allen.tian on 2016-04-21

Test Mode: USB DISK

AC 120V/60 Hz, Line



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	45.79	---	65.73	19.94	9.000	L1	11.0
0.155000	---	17.86	55.73	37.87	9.000	L1	11.0
0.190000	47.42	---	64.04	16.62	9.000	L1	11.0
0.190000	---	33.22	54.04	20.82	9.000	L1	11.0
0.535000	38.19	---	56.00	17.81	9.000	L1	11.0
0.535000	---	26.20	46.00	19.80	9.000	L1	11.0
3.875000	---	21.03	46.00	24.97	9.000	L1	11.3
3.875000	30.31	---	56.00	25.69	9.000	L1	11.3
4.725000	---	32.50	46.00	13.50	9.000	L1	11.3
4.725000	38.63	---	56.00	17.37	9.000	L1	11.3
18.340000	---	24.07	50.00	25.93	9.000	L1	11.4
18.340000	28.51	---	60.00	31.49	9.000	L1	11.4

AC 120V/60 Hz, Neutral

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.175000	---	36.00	54.72	18.72	9.000	N	11.0
0.175000	50.35	---	64.72	14.37	9.000	N	11.0
0.235000	---	25.00	52.27	27.27	9.000	N	11.0
0.235000	40.42	---	62.27	21.85	9.000	N	11.0
0.290000	---	22.71	50.52	27.81	9.000	N	11.0
0.290000	34.41	---	60.52	26.11	9.000	N	11.0
0.525000	---	24.65	46.00	21.35	9.000	N	11.0
0.525000	37.80	---	56.00	18.20	9.000	N	11.0
2.925000	---	24.87	46.00	21.13	9.000	N	11.3
2.925000	34.18	---	56.00	21.82	9.000	N	11.3
4.790000	---	33.22	46.00	12.78	9.000	N	11.4
4.790000	38.09	---	56.00	17.91	9.000	N	11.4

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss
The corrected factor has been input into the transducer of the test software.
- 2) Margin = Limit – (QuasiPeak & Average)

FCC §15.109 - RADIATED EMISSIONS

Applicable Standard

FCC §15.109


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Kunshan) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

Frequency	Polarity	Measurement uncertainty
30 MHz~200 MHz	Horizontal	4.62 dB (k=2, 95% level of confidence)
	Vertical	4.54 dB (k=2, 95% level of confidence)
200 MHz~1 GHz	Horizontal	4.84 dB (k=2, 95% level of confidence)
	Vertical	5.91 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	Horizontal/Vertical	4.68 dB (k=2, 95% level of confidence)
Above 6 GHz	Horizontal/Vertical	4.92 dB (k=2, 95% level of confidence)

EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The EUT was connected to an AC 120V/60 Hz power source.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrunent	Amplifier	330	171377	2015-09-16	2016-09-15
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-05-20	2016-05-19
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2015-11-07	2016-11-06
ETS	Horn Antenna	3115	6229	2015-11-07	2016-11-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-04	2016-11-03
Mini	Pre-amplifier	ZVA-183-S+	857001418	2015-09-16	2016-09-15
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-06-16	2016-12-15
R&S	Auto test Software	EMC32	V 09.10.0	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Correction Factor & Margin Calculation

The Correction Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Correction Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - (\text{QuasiPeak} \& \text{Average})$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, with the worst margin reading of:

14.33 dB at 74.377500 MHz in the Vertical polarization mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25°C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Allen Tian on 2016-04-25

Operation Mode: USB DISK

30MHz ~ 1GHz, AC 120V/60 Hz



Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
34.850000	25.47	40.00	14.53	120.000	100.0	V	196.0	-7.7
46.975000	24.87	40.00	15.13	120.000	100.0	V	162.0	-14.7
74.377500	25.67	40.00	14.33	120.000	100.0	V	318.0	-17.1
296.507500	20.46	46.00	25.54	120.000	200.0	V	261.0	-10.5
354.586250	21.38	46.00	24.62	120.000	200.0	V	203.0	-9.3
675.050000	31.66	46.00	14.34	120.000	100.0	V	143.0	-3.2

2) Above 1 GHz:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dBV/m)	Limit (dB μ V/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1378.757515	35.87	---	73.90	38.03	1000.000	150.0	V	358.0	2.1
1378.757515	---	22.53	53.90	31.37	1000.000	150.0	V	358.0	2.1
1743.486974	37.56	---	73.90	36.34	1000.000	150.0	H	246.0	3.5
1743.486974	---	23.91	53.90	29.99	1000.000	150.0	H	246.0	3.5
2430.861723	38.84	---	73.90	35.06	1000.000	150.0	H	0.0	4.9
2430.861723	---	25.80	53.90	28.10	1000.000	150.0	H	0.0	4.9
3903.807615	---	30.09	53.90	23.81	1000.000	150.0	H	206.0	9.6
3903.807615	43.28	---	73.90	30.62	1000.000	150.0	H	206.0	9.6
5615.230461	---	33.58	53.90	20.32	1000.000	150.0	V	251.0	15.1
5615.230461	47.82	---	73.90	26.08	1000.000	150.0	V	251.0	15.1
6667.334669	53.04	---	73.90	20.86	1000.000	150.0	V	237.0	17.8
6667.334669	---	39.51	53.90	14.39	1000.000	150.0	V	237.0	17.8

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss – amplifier factor
- 2) Margin = Limit - (QuasiPeak & Average)

******* END OF REPORT *******