

RF Exposure Statement

Equipment Information

Type of equipment: Bluetooth Blood Pressure Monitor for Arm
Type / Model: HPL-308, IVT-BPM02
Applicant: Mytech Technology Co., Ltd.
5F, 6, Alley 2, Lane 222, Lien Cheng Rd., Chung Ho City, Taipei
Hsien Taiwan

The main function of HPL-308 (EUT) is to send 2.4GHz RF signals by GFSK, $\pi/4$ DPSK and 8DPSK modulations.

The model listed below is identical to model HPL-308 (EUT). Different brand serves as marketing strategy.

Trade Name	Model Number
IVT	IVT-BPM02
-	HPL-308

Standard Applicable


According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Measurement Result:

The Wireless Optical Mouse is a portable device with the max. peak output power 101.07 dBuV/m, or 6.31 dBm (4.2756 mW) much lower than the low threshold 60/f GHz mW (24.9792 mW).

Therefore, the SAR/MPE measurement is not necessary.

Date of issue: Aug. 30, 2010



Jacky Chen
Engineer

Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan