BillOfMaterials-serielle-reader.txt

Bi I	Of	Materials	for Serial reader.sch on Wed Ja	an 02 09: 12: 23 2008
		·	e Part Name Manufacturer	
			1000UF-35V-RUB Rubycon	
	1	1	YCON-YXF,	
	1		1000uF	
2	15	C3 C5-7	100NF_50VDC_10 Philips	100nF 50VDC X7R 1208
	1	C11-15	%_X7R_0805	
	1	C19 C24	1	
	1	C37	1	
	1	C40-42	1	
3	1	C16	100NF_50VDC_10 Philips	100nF 50VDC X7R 1208
	1	1	%_X7R_0805,	
	1		100nF	
1	1	C39	100PF_100VDC_5 yageo	100pF 100VDC NP0/C0G 0805
	1		%_NPO_0805,	
	1		100pF	
5	1	C38	100PF_100VDC_5 yageo	100pF 100VDC NP0/C0G 0805
	1		%_NPO_0805,	
	1		100pF, 2%, 5%	
6	1	C8	220UF_6V_20%_ EVX	220uF 63V 20% SMD D-case
	1	1	SMD_D-CASE,	
	1		220uF, 20%	
7	1	C9	10NF_100VDC_10 yageo	10nF 100VDC X7R 0805
	1	1	%_X7R_0805	
8	3	C25	10NF_100VDC_NP phycomp/yageo	10nF 100VDC NPO 1210 case
	1	C33-34	0_1210, 10nF,	
	1	1	2%, 5%	
9	1	J2	10P0L-MALE-ISP	
10	1	C18	10UF_35V_20%_S SI EMENS	10uF 35V 20% SMD D-case
	1		MD_D-CASE,	
	1	1	10uF, 20%	

11	1	C17	BillOfMateria 1NF-50VDC-NPO-	als-serielle-rea Murata	ader.txt 1nF 50VDC NPO 1%
			0805, 1nF, 1%	I	
12	2	C22 C35	1NF_100VDC_NP0	phycomp/yageo	1nF 100VDC NPO 0805 case
			_0805, 1nF, 2%,		I
	1		5%	I	
13	1	C36	2. 2UF_16VDC_10	murata	2.2uF 16VDC 5 % X7R 1206
			-20%_X7R_1206	I	
14	1	C43	2. 2UF_16VDC_10	murata	2. 2uF 16VDC 5 % X7R 1206
			-20%_X7R_1206,		
			2. 2uF, 10%	I	
15	1	C4	2. 2UF_35V_10%_	EPCOS	2.2uF 35V 10% SMD B-case
		1	SMD_B-CASE,	I	
		1	2. 2uF, 10%		
16	4	C26-29	220PF-50VDC-NP	Murata	220pF 50VDC NPO 1%
			0-0805, 220pF,	I	
			1%	I	
17	4	C1-2	22PF-50VDC-NP0	Murata	22pF 50VDC NPO 1%
		C20-21	-0805, 22pF, 1%	I	
18	1	C23	22PF_100VDC_5%	yageo	22pF 100VDC NPO/COG 0805
			_NP0_0805,	I	
			22pF, 1%	I	
19	1	U11	AD8527ARZ	ANALOG DEVICES	DUAL OPERATIONAL AMPLFIER 5V
		1			suppl y
20	1	U3	ADM202ARZ	Analog Devices	
21	1	U1	ATMEGA32-16AU	ATMEL	AVR RISC - 32Kbyte 16MHz
22	4	D12-15	BAT54S	Phi I i ps	series dual schottky diode
23	1	U8	CF45538NSRG4	TI	Tiris RF-module
24 . 100	1	J1	CON-SIP-8P	l	GENERIC 8 PIN SIP HEADER
	'	1		l	CENTERS
25	1	J4	DSUB-9POL-HUN-	l	DSUB-9 pole female 90
		1	90GRADER	l	degrees.
26	1	Y2	ESB17.1776F30M	l	ESB17.1776F30M55F
		1	55F, 17. 1776MHz	l	
		1	30pF, +/-50ppm	I	

27	1	Y1	BillOfMateria ESB8.0000F30M5	al s-seri el l e-rea 	ader. txt ESB8. 0000F30M55F
	1		5F, 8. 0000MHz	I	
	1		30pF, +/-50ppm	I	
28	1	U7	FDS8958A	Fai rchi I d	Complementary mosfets
			1	Semi conductor	
29	2	J18-19	FIDUCIAL-60MIL	I	
30	2	J14-15	JUMP-2POL	1	2 pol jumper block
31	4	J10-13	JUMP-3POL	1	3 pol jumper block
32	1	U2	LM2674M-5.0	nati onal	SIMPLE SWITCHER STEP-DOWN
	1		1	1	VOLTAGE REGULATOR
33	1	U14	LM317S	MOTOROLA	POSITIVE VOLTAGE REGULATOR;
	1		1	1	ADJUSTABLE
34	1	D3	LTST-C170CKT	Agi I ent	SMD 0805 size LED
35	1	D5	LTST-C170GKT	Agi I ent	SMD 0805 size LED
36	1	D2	LTST-C170YKT	Agi I ent	SMD 0805 size LED
37	8	L2-9	MLS1206-4S7-10	FERROXCUBE	SMD ferrit bead, Z=1k@50MHz
	1		2	1	
38	1	J16	MOLEX6410-2	Mol ex	Molex 6410 2 Pin center
			1	1	header
39 head	1	J3	MOLEX6410-3	Mol ex	Molex 6410 3Pin center
40	6	J5-9 J17	MTHOLE-130/300	I	
41	2	J20-21	MTHOLE_3MM-NON	I	
	1		PLATE	I	
42	2	R32-33	RES0805-100K-5	I PC SM-782	MILSPEC 0805 BODY FOR
	1		%, 100K	STD.	RESI STOR
43	2	R15 R43	RES0805-100R-5	IPC SM-782	MILSPEC 0805 BODY FOR
	1		%, 100R	STD.	RESI STOR
44	2	R30-31	RES0805-10K-1%	IPC SM-782	MILSPEC 0805 BODY FOR
	1		, 10K	STD.	RESI STOR
45	1	R42	RES0805-10R-5%	IPC SM-782	MILSPEC 0805 BODY FOR
	1		, 10R	STD.	RESI STOR
46	5	R2 R4 R28	B RES0805-1K-1%,	IPC SM-782	MILSPEC 0805 BODY FOR
		R34 R41	1K	STD.	RESI STOR

		1	BillOfMateri , 1K2	als-seri elle-re STD.	eader.txt RESISTOR
48	5	R16 R40	RES0805-1K8-5%	6 IPC SM-782	MILSPEC 0805 BODY FOR
		R45-47	, 1K8	STD.	RESI STOR
49	1	R29	RES0805-1M-5%,	IPC SM-782	MILSPEC 0805 BODY FOR
			1M	STD.	RESI STOR
50	2	R26-27	RES0805-220R-5	5 IPC SM-782	MILSPEC 0805 BODY FOR
			%, 220R	STD.	RESI STOR
51	2	R1 R35	RES0805-22K-5%	6 IPC SM-782	MILSPEC 0805 BODY FOR
			, 22K	STD.	RESI STOR
52	3	R3 R5 R44	1 RES0805-2K7-5%	6 IPC SM-782	MILSPEC 0805 BODY FOR
			, 2K7	STD.	RESI STOR
53	3	R12-14	RES0805-330R-5	5 IPC SM-782	MILSPEC 0805 BODY FOR
			%, 330R	STD.	RESI STOR
54	5	R22-25	RES1218-22R-5%	6 IPC SM-782	RES1218
		R50	, 22R	STD.	
 55 .6Amp	1	L1	SLF7045T-680MF	R TDK	TDK power inductor 68uH
. OAIIIL	'		60PF		
56	1	D4	SMBJC33A	Fai rchi I d	Transi ent vol tage supressors
			1	Semi conductor	
57	7	D1 D6-11	SS14	General	Surface mount Schottky
		1		Semi conductor	Barrier Rectifier 40V/1A