

FCC Test Report

FCC ID : YUW-301F

Equipment: Mobile Phone

Model No. : 301F

Brand Name : FUJITSU

Applicant : Fujitsu Mobile Communications Ltd.

Address : 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

Standard : 47 CFR FCC Part 15.247

Received Date : Sep. 13, 2013

Tested Date : Oct. 04 ~ Oct. 22, 2013

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Iac MRA

TAF

Testing Laboratory

Report No.: FR391306AE
Report Version: Rev. 01

Page: 1 of 39



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	8
1.4	The Equipment List	9
1.5	Test Standards	
1.6	Measurement Uncertainty	11
2	TEST CONFIGURATION	12
2.1	Testing Condition	12
2.2	The Worst Test Modes and Channel Details	
3	TRANSMITTER TEST RESULTS	13
3.1	Conducted Emissions	13
3.2	6dB and Occupied Bandwidth	18
3.3	RF Output Power	
3.4	Power Spectral Density	22
3.5	Unwanted Emissions into Restricted Frequency Bands	24
3.6	Unwanted Emissions into Non-Restricted Frequency Bands	36
4	TEST LABORATORY INFORMATION	39



Release Record

Report No.	Version	Description	Issued Date
FR391306AE	Rev. 01	Initial issue	Nov. 01, 2013

Report No.: FR391306AE Page: 3 of 39



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.494MHz 28.23 (Margin -17.87dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 75.59MHz 36.51 (Margin -3.49dB) - PK	Pass
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 0.32	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR391306AE Page: 4 of 39



1 General Description

1.1 Information

1.1.1 Product Details

Product Name	Mobile Phone
Brand Name	FUJITSU
Model Name	301F
IMEI Code	357613050018539, 357613050017572
H/W Version	V2.1.0
S/W Version	R25.1e

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz) Bluetooth (MHz) Channel Number Data Rate							
2400-2483.5 BT LE 2402-2480 0-39 [40] 1 Mbps							

1.1.3 Antenna Details

Ant. No.	Туре	Gain (dBi) Connector		Remark
1	λ/4 Monopole	-3		

1.1.4 EUT Operational Condition

Supply Voltage		□ DC	
Type of DC Source	☐ Internal DC supply		Battery

Report No.: FR391306AE Page: 5 of 39



1.1.5 Accessories

	Accessories						
No. Equipment Description							
		Brand Name: Fujitsu limited					
1	Battery	Model Name: CA54310-0053					
		Power Rating: O/P: 3.75Vdc, 2600mA					
	Cradle	Brand Name: SOFTBANK MOBILE Corp.					
2		Model Name: CA50601-1881					
		Power Rating: O/P: 12.0Vdc, 1.5A					
		Brand Name: SOFTBANK MOBILE Corp.					
		Model Name: TA08017-B330					
3	Adapter for cradle	I/P: 100-240Vac, 1000mA					
		O/P: 12.0Vdc, 3000mA DC 1.1m non-shielded cable with one core					
		AC 0.9m non-shielded cable without core					

1.1.6 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
37	2402.00	18	2442.00
0	2404.00	19	2444.00
1	2406.00	20	2446.00
2	2408.00	21	2448.00
3	2410.00	22	2450.00
4	2412.00	23	2452.00
5	2414.00	24	2454.00
6	2416.00	25	2456.00
7	2418.00	26	2458.00
8	2420.00	27	2460.00
9	2422.00	28	2462.00
10	2424.00	29	2464.00
38	2426.00	30	2466.00
11	2428.00	31	2468.00
12	2430.00	32	2470.00
13	2432.00	33	2472.00
14	2434.00	34	2474.00
15	2436.00	35	2476.00
16	2438.00	36	2478.00
17	2440.00	39	2480.00

Report No.: FR391306AE Page: 6 of 39



1.1.7 Test Tool and Power Setting

Test tool	QRCT, Ver 3.0.6.0				
Modulation Mode		Test Frequency (MHz)			
Wodulation Wode	2402	2440	2480		
GFSK/1Mbps	Default	Default	Default		

1.2 Local Support Equipment List


	Support Equipment List						
No.	No. Equipment Brand Model S/N FCC ID Signal cable / Length (r						
1	Adapter	NTT docomo	AC Adaptor 04			1m non-shielded with 2 cores	
2	Earphone	Apple	MD827FE/A			1.2m non-shielded w/o core	


Note: Item 1 was provided by client.

Report No.: FR391306AE Page: 7 of 39



1.3 Test Setup Chart





Report No.: FR391306AE Page: 8 of 39



1.4 The Equipment List

Test Item	Conducted Emission							
Test Site	Conduction room 1 / (CO01-WS)							
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Un							
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014			
LISN	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-667	Dec. 04, 2012	Dec. 03, 2013			
LISN (Support Unit)	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-666	Dec. 04, 2012	Dec. 03, 2013			
ISN	TESEQ	ISN T800	34406	Apr. 08, 2013	Apr. 07, 2014			
ISN	TESEQ	ISN T200A	30494	Apr. 09, 2013	Apr. 08, 2014			
ISN	TESEQ	ISN ST08	22589	Jan. 24, 2013	Jan. 23, 2014			
RF Current Probe	FCC	F-33-4	121630	Dec. 04, 2012	Dec. 03, 2013			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 25, 2012	Dec. 24, 2013			
ESH3-Z6 V-Network(+)	R&S	ESH3-Z6	100920	Nov. 21, 2012	Nov. 20, 2013			
ESH3-Z6 V-Network(-)	R&S	ESH3-Z6	100951	Jan. 30, 2013	Jan. 29, 2014			
Two-Line V-Network	R&S	ENV216	101579	Jan. 07, 2013	Jan. 06, 2014			
50 ohm terminal	NA	50	03	Apr. 22, 2013	Apr. 21, 2014			
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014			
, ,,	val of instruments listed a	above is one year.						

Test Item	RF Conducted	RF Conducted						
Test Site	(TH01-WS)	(TH01-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV 40	101063	Feb. 18, 2013	Feb. 17, 2014			
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 29, 2012	Nov. 28, 2013			
Power Meter	Anritsu	ML2495A	1241001	Oct. 08, 2013	Oct. 07, 2014			
Power Sensor	Anritsu	MA2411B	1207362	Oct. 08, 2013	Oct. 07, 2014			
Signal Generator R&S SMB100A 175727 Jan. 14, 2013 Jan. 13, 201								
Note: Calibration Inter	Note: Calibration Interval of instruments listed above is one year.							

Report No.: FR391306AE Page: 9 of 39



Test Item	Radiated Emission above 1GHz							
Test Site	966 chamber1 / (03CH01-WS)							
Instrument	Manufacturer	Manufacturer Model No. Serial No. Calibration Date Calibration Ur						
3m semi-anechoic chamber	CHAMPRO	SAC-03	03CH01-WS	Jan. 04, 2013	Jan. 03, 2014			
Spectrum Analyzer	R&S	FSV40	101498	Jan. 24, 2013	Jan. 23, 2014			
Receiver	R&S	ESR3	101658	Jan. 28, 2013	Jan. 27, 2014			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 11, 2013	Jan. 10, 2014			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 18, 2013	Feb. 17, 2014			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Jan. 14, 2013	Jan. 13, 2014			
Amplifier	Burgeon	BPA-530	100219	Nov. 28, 2012	Nov. 27, 2013			
Amplifier	Agilent	83017A	MY39501308	Dec. 18, 2012	Dec. 17, 2013			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 25, 2012	Dec. 24, 2013			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 25, 2012	Dec. 24, 2013			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 25, 2012	Dec. 24, 2013			
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-001	Dec. 25, 2012	Dec. 24, 2013			
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-002	Dec. 25, 2012	Dec. 24, 2013			
control	EM Electronics	EM1000	60612	N/A	N/A			

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014	
Amplifier	MITEQ	AMF-6F-260400	9121372	Apr. 19, 2013	Apr. 18, 2015	
Note: Calibration Interval of instruments listed above is two year.						

Report No.: FR391306AE Page: 10 of 39



1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r01

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty				
Parameters	Uncertainty			
Bandwidth	±35.286 Hz			
Conducted power	±0.536 dB			
Frequency error	±35.286 Hz			
Temperature	±0.3 °C			
Conducted emission	±2.946 dB			
AC conducted emission	±2.43 dB			
Radiated emission	±2.49 dB			

Report No.: FR391306AE Page: 11 of 39



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By	Tested Date
AC Conduction	CO01-WS	21°C / 55%	Skys Huang	Oct. 22, 2013
Radiated Emissions	03CH01-WS	23°C / 64%	Aska Huang Haru Yang	Oct. 04~ Oct. 11, 2013
RF Conducted	TH01-WS	24°C / 61%	Felix Sung	Oct. 09, 2013

FCC site registration No.: 657002IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data rate (Mbps)	Test Configuration
AC Power Line Conducted Emissions	BT LE	2402	1Mbps	1, 2
Radiated Emissions < 1GHz	BT LE	2402	1Mbps	1, 2
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	1
Fundamental Emission Output Power				
6dB bandwidth	BT LE	2402, 2440, 2480	1Mbps	1
Power spectral density				

NOTE:

- 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
- 2. The EUT had been tested by following test configurations for radiated emission below 1GHz.
 - 1) Configuration 1 : Adapter mode
 - 2) Configuration 2: Cradle mode
- 3. Adapter and cradle mode had been pretested for radiated emission above 1GHz and found that the adapter mode was the worst case and was selected for final test.

Report No.: FR391306AE Page: 12 of 39



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit					
Frequency Emission (MHz) Quasi-Peak Average					
0.15-0.5 66 - 56 * 56 - 46 *					
0.5-5	56	46			
5-30 60 50					
Note 1: * Decreases with the logarithm of the frequency.					

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR391306AE Page: 13 of 39




3.1.4 Test Result of Conducted Emissions



2: Over Limit (dBuV) = Limit Line (dBuV) – Level (dBuV).


Report No.: FR391306AE Page: 14 of 39






Report No.: FR391306AE Page: 15 of 39





Report No.: FR391306AE Page: 16 of 39





Report No.: FR391306AE Page: 17 of 39



3.2 6dB and Occupied Bandwidth


3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

3.2.3 Test Setup




Report No.: FR391306AE Page: 18 of 39



3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.674	1.05	500
BT LE	2440	0.670	1.05	500
BT LE	2480	0.670	1.05	500



Report No.: FR391306AE Page: 19 of 39



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Con	duct	ed po	ower shall not exceed 1Watt.
\boxtimes	Ante	enna	gain <= 6dBi, no any corresponding reduction is in output power limit.
	Ante	enna	gain > 6dBi
		The	n Fixed, point to point operations. e conducted output power from the intentional radiator shall be reduced by the amount in dB the directional gain of the antenna exceeds 6 dB
		Sys Ope	ed, point to point operations tems operations in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point erations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 that the directional gain of the antenna exceeds 6 dBi.
			tems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point rations ,no any corresponding reduction is in transmitter peak output power
3.3.	2	Test	t Procedures
\boxtimes	Max	kimur	m Peak Conducted Output Power
		Spe	ectrum analyzer
		1.	Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
		2.	Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
		3.	Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
	\boxtimes	Pov	ver meter
		1.	A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
\boxtimes	Max	kimur	m Conducted Output Power (For reference only)
		Spe	ectrum analyzer
		1.	Set RBW = 1MHz, VBW = 3MHz, Detector = RMS.
		2.	Set the sweep time to: $\geq 10 \text{ x}$ (number of measurement points in sweep) x (maximum data rate per stream).
		3.	Perform the measurement over a single sweep.
		4.	Use the spectrum analyzer's band power measurement function with band limits set equal to the EBW(26dBc) band edges.

Report No.: FR391306AE Page: 20 of 39

A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission

Report Version: Rev. 01

Now Power meter

burst for measuring output power.



3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)
BT LE	2402	1.08	0.32	30
BT LE	2440	1.07	0.31	30
BT LE	2480	1.00	-0.01	30

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	1.04	0.16	30
BT LE	2440	1.04	0.15	30
BT LE	2480	0.94	-0.25	30

Note: Average power is for reference only

Report No.: FR391306AE Page: 21 of 39



3.4 Power Spectral Density

3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - Set the RBW = 3kHz, VBW = 10kHz.
 - Detector = Peak, Sweep time = auto couple.
 - 3. Trace mode = max hold, allow trace to fully stabilize.
 - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - 1. Set the RBW = 10kHz, VBW = 30kHz.
 - 2. Detector = RMS, Sweep time = auto couple.
 - 3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
 - 4. Perform the measurement over a single sweep.
 - 5. Use the peak marker function to determine the maximum amplitude level.\

3.4.3 Test Setup




Report No.: FR391306AE Page: 22 of 39



3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-15.28	8
BT LE	2440	-15.78	8
BT LE	2480	-15.75	8



Report No.: FR391306AE Page: 23 of 39



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit									
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)						
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300						
0.490~1.705	24000/F(kHz)	33.8 - 23	30						
1.705~30.0	30	29	30						
30~88	100	40	3						
88~216	150	43.5	3						
216~960	200	46	3						
Above 960	500	54	3						

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR391306AE Page: 24 of 39




3.5.3 Test Setup



Report No.: FR391306AE Page: 25 of 39



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 26 of 39



Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1
l evel (dRu)	//m)		



	Freq.	Emission level dBuV/m		Ū	SA reading dBuV		Remark		Turn Table
	МПZ	ubuv/m	ubuv/m	uБ	abuv	ub		cm	deg
1	30.00	26.13	40.00	-13.87	43.86	-17.73	Peak		
2	133.79	25.68	43.50	-17.82	43.45	-17.77	Peak		
3	185.20	23.61	43.50	-19.89	42.35	-18.74	Peak		
4	202.66	29.72	43.50	-13.78	49.01	-19.29	Peak		
5	358.83	20.10	46.00	-25.90	34.78	-14.68	Peak		
6	689.60	33.91	46.00	-12.09	42.32	-8.41	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 27 of 39



Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m		Ū	SA reading dBuV		Remark	ANT High cm	Turn Table deg
1	37.76	28.31	40.00	-11.69	45.48	-17.17	Peak		
2	75.59	31.69	40.00	-8.31	52.36	-20.67	Peak		
3	92.08	32.53	43.50	-10.97	55.19	-22.66	Peak		
4	126.03	27.27	43.50	-16.23	45.80	-18.53	Peak		
5	168.71	29.19	43.50	-14.31	46.32	-17.13	Peak		
6	336.52	26.67	46.00	-19.33	41.93	-15.26	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 28 of 39



Polarization Vertical Test Configuration 2	CLASS-B
80 70 60 50 40 2 3 4 30	CLASS-B
80 70 60 50 40 2 3 4 30	CLASS-B
60 50 40 2 3 30 5 6	CLASS-B
50 40 2 30 5 6	CLASS-B
40 2 3 4 30 5 6	
30 2 4 6	
20	
10	
0 30 100. 200. 300. 400. 500. 600. 700. 800. 900 Frequency (MHz)	0. 1000
Freq. Emission Limit Margin SA Factor Remark AN level reading Hi	
level reading Hi MHz dBuV/m dBuV/m dB dBuV dB cm	
1 30.00 31.72 40.00 -8.28 49.45 -17.73 Peak	
2 52.31 33.77 40.00 -6.23 50.49 -16.72 Peak - 3 75.59 36.51 40.00 -3.49 57.18 -20.67 Peak -	

92.08 31.94 43.50 -11.56 54.60 -22.66

254.07 23.68 46.00 -22.32

359.80 27.03 46.00 -18.97

Peak

Peak

Peak

41.44 -17.76

41.68 -14.65

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Report No.: FR391306AE Page: 29 of 39

Report Version: Rev. 01

5



3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 30 of 39



Modulation			G	GFSK					Test Freq. (MHz)				2402		
Polarization			Ve	Vertical											
	127	Leve	l (dBuV/m)											
	120														
	100														
	80											Fi	CC CLAS	S.R	
	60	2											ASS-B (A		
	40		4	6											
	20		3												
	0	1000	4000	. 6	000. 80	00. 100				6000. 180	00. 200	00. 22	000.	25000	
			Frea	. Fm	nission	Limit		u ency (N .n S/		Factor	Rema	ırk	ANT	Turn	
			MHz		level BuV/m		_		ding	dB			High cm	Table deg	
	1		1594.	90	36.66	54.00	-17.34	42	.96	-6.30	Aver	age			
	2		1594.		54.34				.64	-6.30	Peak				
	3				28.73				.95	-3.22	Aver	_			
	4 5				47.04 32.90				. 26 . 62	-3.22 4.28	Peak Aver				
	,		4004.	00	32.50	54.00	-21.10	20	.02	4.20	Avei	age			

Peak

4.28

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

4804.00 45.12 74.00 -28.88 40.84


Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR391306AE Page: 31 of 39

Report Version: Rev. 01

6






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 32 of 39






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 33 of 39






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 34 of 39





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR391306AE Page: 35 of 39



3.6 Unwanted Emissions into Non-Restricted Frequency Bands

3.6.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

\boxtimes	The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band
	shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

The peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference Level Measurement

- 1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


3.6.3 Test Setup




Report No.: FR391306AE Page: 36 of 39



3.6.4 Unwanted Emissions into Non-Restricted Frequency Bands



Report No.: FR391306AE Page: 37 of 39



Report No.: FR391306AE Page: 38 of 39



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR391306AE Page: 39 of 39