



## 規格承認書

Specification for Approval

客 戶：

Customer

品 名：

A04 LTCC ANTENNA

Part name

料 號：


GPL52P245000-00

Part No.

客戶承認印 CUSTOMER APPROVED BY		
APPROVAL	CHIEF	SUPERVISOR
Approval No.		
Model		
Part No.		

CHIEF	SALES	R&D	DESIGN
Jeff	James	GWP	Hui
Date: 2009.11.13		Date: 2009.11.13	

驊 原 科 技 股 份 有 限 公 司  
**WIESON INTERNATIONAL CO., LTD.**

 <b>WIESON</b> INTERNATIONAL CO., LTD.		<b>SPECIFICATION LIST</b>		TYPE OF PRODUCT	
				<b>LTCC Antenna</b>	
ITEM		INDEX			PAGE
一. 概述 Introduction.....					3
二. 外型尺寸 Dimensions.....					3
三. 測試電路 Evaluation Board.....					3
四. 電氣特性 Electrical Characteristics.....					4
五. 回流焊溫度 Reflow Soldering Standard Condition.....					4
六. 環境測試 Environmental Test.....					5
七. 包裝 Packaging.....					6
八. 測試報告 Test Report.....					7~18
九. 環保報告 Green Report.....					19~23
				Approvals	
Rev	Date	Description	Edited by	Prepared	Hui
01	2009.11.13	NEW RELEASE	Hui	Checked	GWP
				Approved	Jeff
				Issued No	1.0
				Sheet	<b>2 OF 23</b>



# WIESON INTERNATIONAL CO., LTD.


TYPE OF PRODUCT	LTCC Antenna	PAGE : 3/23
-----------------	--------------	-------------

## 一. 概述 Introduction



"驊原"微波多層片狀陶瓷天線 GPL 系列產品用於無線區域網路、藍芽天線、手機多頻天線、GPS 等小體積貼版式設計。

"WIESON" microwave multi-layer chip ceramic antenna GPL series are designed to be used in WLAN, Bluetooth, multiple-band mobile phone antenna, GPS, etc and compact size SMD chip design.

## 二. 外型尺寸 Dimensions



## 三. 測試電路 Evaluation Board





# WIESON INTERNATIONAL CO., LTD.


TYPE OF PRODUCT	LTCC Antenna	PAGE : 4/23
-----------------	--------------	-------------

## 四. 電氣特性Electrical Characteristics

項目	Item	特性	Specification
中心頻率	Center Frequency	2450 ± 25 MHz	
頻寬	Bandwidth	>150MHz	
增益	Gain	1.5 dBi Typical	
電壓駐波比	VSWR	2.0 MAX.	
極化方式	Polarization	線性	Linear
方位角	Azimuth Beam width	全向性	Omni-directional
阻抗	Impedance	50 Ohm	

※本天線在應用 PCB 上通過設計匹配電路，將天線工作頻率調整到 2.45GHz 的中心頻率。

## 五. 回流焊溫度Reflow Soldering Standard Condition






# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 5/23
-----------------	--------------	-------------

## 六. 環境測試Environmental Test

測試項目 Item	測試條件 Requirement
振動 Vibration Resist	在振動頻率為 10~55Hz 振幅為 1.5mm 沿 X,Y,Z 方向各振動 2 小時
落摔 Drop Shock	在 100CM 高度處按 X,Y,Z 三個面分別自由落下在木質地板上共 3 次
焊接耐熱 Solder Heat Proof	能承受經 120~150°C 的溫度預熱 120 秒後，在 230°C+10°C 的焊錫浸 5±0.5 秒。
結合力 Tensile Strength of Terminal	在產品電極端上或表面上能承受 1 公斤拉力 10±1 秒。
耐彎曲 Bending Resist Test	 <p>將產品按圖焊在 1.6 ±0.2mm 的 PCB 中間，由箭頭方向施力：1mm/s，彎曲距離：1.5mm，保持 5 ±1 秒，產品金屬無脫落。</p>
耐濕熱 Moisture Proof	在溫度為 60±2°C，相對濕度 90~95% 的恆溫恆濕機器中放置 96 小時，在常溫中恢復 1~2 小時。
高溫 High Temperature Endurance	在溫度為 85±5°C 的恆溫箱中放置 24±2 小時，在常溫中恢復 1~2 小時。
低溫 Low Temperature Endurance	在溫度為 -40±5°C 的恆溫箱中放置 24±2 小時，在常溫中恢復 1~2 小時。
冷熱衝擊 Temperature Cycle Test	在 -25°C 中保持 30 分鐘，在 +85°C 中保持 30 分鐘，共循環 5 次後在常溫中恢復 1~2 小時。

## 基礎條件

項目	Item	條件 Requirement
溫度範圍	Temperature range	25 ± 5
相對濕度範圍	Relative Humidity range	55~75%RH
工作溫度	Operating Temperature range	-40 ~+85
儲存溫度	Storage Temperature range	-40 ~+85




# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 6/23
-----------------	--------------	-------------

## 七.包裝 Packaging

### 1. Plastic Tape




### Remarks for Package :

Reserve a length of 150~200mm for the trailer of the carrier and 250~300 mm for the leader of the carrier and further 250mm of cover tape at the leading part of the carrier.

### 2. Reel

( 3000 pcs/Reel )



<b>TYPE OF PRODUCT</b>	<b>LTCC Antenna</b>	<b>PAGE : 7/23</b>
------------------------	---------------------	--------------------

## 八. 測試報告 Test Report

### 1. S-PARAMETER

#### Summary :

This report to account for the measurement setup and result of LTCC Chip antenna.

- (1) The measurement setup includes reflection coefficient, pattern, and gain measurement.
- (2) The measured data for LTCC Chip antenna are presented and analysis.

#### I. Measurement Coefficient Measurement :


##### A. Reflection Coefficient Measurement :

(a) Instrument : Network Analyzer.

(b) Setup :

- (1) Calibrate the Network Analyzer by one port calibration using O.S.L. calibration kits.
- (2) Connect the antenna under test to the Network Analyzer.
- (3) Measure the S11(reflection coefficient) shown in Fig. 1.
- (4) Generally, the S11 is less than  $-10\text{dB}$  to ensure the 90% power into antenna and only less than 10% power back to system.

### NETWORK ANALYZER



**Fig. 1 LTCC antenna measured in Network Analyzer.**




# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 8/23
-----------------	--------------	-------------


## II. Test Value :

### A. VSWR

Sample \ Frequency	2.40GHz	2.45GHz	2.50GHz
1	1.4011	1.2627	1.3671
2	1.3578	1.1881	1.3185



SAMPLE-1



SAMPLE-2






# WIESON INTERNATIONAL CO., LTD.


TYPE OF PRODUCT	LTCC Antenna	PAGE : 9/23
-----------------	--------------	-------------

## B. RETURN LOSS

Frequency	2.40GHz	2.45GHz	2.50GHz
Sample 1	-15.659	-18.567	-16.305
Sample 2	-16.188	-21.179	-17.406



SAMPLE-1



SAMPLE-2




# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT


LTCC Antenna

PAGE : 10/23

## C. SMITH CHART



SAMPLE-1



SAMPLE-2


## 2. 2D PATTERN

### I. Measurement

(a) **Instruments** : anechoic chamber, network analyzer, standard gain antenna.

(b) **chamber description** :

- (1) The anechoic chamber is a far-field measurement system with size of 3.25M\*2.84M\*6.4M. The quiet zone region is 44cm\*44cm\*44cm at frequency range of 2.4GHz in the center of the rotator.



**Fig. 2 The interior components of the anechoic.**

- (2) Fig. 2. shows the interior components of the anechoic chamber. The antenna standard antenna as probe and antenna under test is 3M. The antenna under test is fixed on a step rotator. We can control the rotating angle for accurate or rough measurement.
- (3) While we measure the radiation patterns by rotating AUT with 360 degrees and repeat again by replacing the AUT with the standard gain antenna under test, we compare both data and using a formula to obtain the

$$G_{AUT} = G_{stand} + P_{AUT} - P_{stand}$$

$G_{AUT}$  : Gain of AUT


$G_{stand}$  : Gain of Standard Gain Antenna

$P_{AUT}$  : Measured Power of AUT


$P_{stand}$  : Measured Power of Standard Gain Antenna

<b>TYPE OF PRODUCT</b>	<b>LTCC Antenna</b>	<b>PAGE : 12/23</b>
------------------------	---------------------	---------------------

- (3) Gain of AUT. The standard gain antenna is a gain horn( SG-430 1.7GHz ~ 2.6GHz ).
- (4) The planes defined in the Fig. 4 which we want to measure are H(X-Y) , E1(X-Z) and E2(Y-Z) planes. The vertical or horizontal polarization's power is measured by rotating the antenna probe to 0 degree or to 90 degree shown in Fig. 3, respectively. While we combine both vertical and horizontal power, we obtain total power.
- (5) From the total power in three basic planes( H, and E ), we can analyze the performance of the antenna is good or not.



**Fig. 3. The definition of vertical and horizontal polarization.**



**Fig. 4. The plane definition : H-Plane , E1-Plane and E2-Plane.**



# WIESON INTERNATIONAL CO., LTD.


TYPE OF PRODUCT	LTCC Antenna	PAGE : 13/23
-----------------	--------------	--------------

## II. Test Value :

A. Sample-1  
(1) H-Plane

Frequency	2.40GHz	2.45GHz	2.50GHz
Gain (dBi)			
Peak	1.23878	1.76309	1.94786
Avg.	0.236	0.324	0.583

Far-field amplitude of A04 LTCC Chip Antenna H-Plane.nsi






# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 14/23
-----------------	--------------	--------------

(2) E1-Plane

Frequency	2.40GHz	2.45GHz	2.50GHz
Gain (dBi)			
Peak	1.02541	0.93877	1.31626
Avg.	-3.539	-3.537	-3.104

Far-field amplitude of A04 LTCC Chip Antenna E1-Plane.nsi






# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 15/23
-----------------	--------------	--------------

( 3 ) E2-Plane

Frequency	2.40GHz	2.45GHz	2.50GHz
Gain ( dBi )			
Peak	1.73482	1.77531	2.2492
Avg.	-2.653	-2.772	-2.345

Far-field amplitude of A04 LTCC Chip Antenna E2-Plane.nsi






# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 16/23
-----------------	--------------	--------------

B. Sample-2  
(1) H-Plane

Frequency	2.40GHz	2.45GHz	2.50GHz
Gain (dBi)			
Peak	1.18998	1.77512	2.01254
Avg.	-0.219	0.380	0.677

Far-field amplitude of A04 LTCC Chip Antenna H-Plane.nsi








# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 17/23
-----------------	--------------	--------------

(2) E1-Plane

Frequency	2.40GHz	2.45GHz	2.50GHz
Gain (dBi)			
Peak	1.10138	1.023	1.40474
Avg.	-3.465	-3.454	-3.013

Far-field amplitude of A04 LTCC Chip Antenna E1-Plane.nsi






# WIESON INTERNATIONAL CO., LTD.

TYPE OF PRODUCT	LTCC Antenna	PAGE : 18/23
-----------------	--------------	--------------

( 3 ) E2-Plane

Frequency	2.40GHz	2.45GHz	2.50GHz
Gain ( dBi )			
Peak	1.80321	1.87149	2.3496
Avg.	-2.612	-2.703	-2.275

Far-field amplitude of A04 LTCC Chip Antenna E2-Plane.nsi



## TEST REPORT

NUMBER: SZHH0038564301

APPLICANT: JIAXING JIALI ELECTRIC CO., LTD  
NO.1 ZHENGYUAN ROAD IN TANGHUI  
INDUSTRIAL GARDEN, JIAXING,  
ZHEJIANG PROVINCE

DATE: May 12, 2009

ATTN: ZHOU JIAN LI

### SAMPLE DESCRIPTION:

ONE (1) SUBMITTED SAMPLE SAID TO BE **GREY CERAMIC WITH SILVER COLOR METAL & LIGHT GREY TREATED LAYER (MULTI LAYER DIELECTRIC PRODUCT 多层介质产品)**.



\*\*\*\*\*

### TESTS CONDUCTED:

AS REQUESTED BY THE APPLICANT, FOR DETAILS REFER TO ATTACHED PAGE(S)

\*\*\*\*\*

AUTHORIZED BY:  
FOR INTERTEK TESTING SERVICES  
SHENZHEN LTD.

KARBON M.Y. WU  
GENERAL MANAGER

**TEST REPORT**

NUMBER: SZHH0038564301

## TESTS CONDUCTED

## RoHS CHEMICAL TEST

## (A) TEST RESULT SUMMARY:

TESTING ITEM	RESULT
CADMIUM (Cd) CONTENT (mg/kg)	ND (<2)
LEAD (Pb) CONTENT (mg/kg)	ND (<2)
MERCURY (Hg) CONTENT (mg/kg)	ND (<2)
CHROMIUM (VI) (Cr <sup>6+</sup> ) CONTENT (mg/kg)	ND (<1)
POLYBROMINATED BIPHENYLS (PBBs) (mg/kg)	
MONOBROMOBIPHENYL (MonoBB)	ND (<5)
DIBROMOBIPHENYL (DiBB)	ND (<5)
TRIBROMOBIPHENYL (TriBB)	ND (<5)
TETRABROMOBIPHENYL (TetraBB)	ND (<5)
PENTABROMOBIPHENYL (PentaBB)	ND (<5)
HEXABROMOBIPHENYL (HexaBB)	ND (<5)
HEPTABROMOBIPHENYL (HeptaBB)	ND (<5)
OCTABROMOBIPHENYL (OctaBB)	ND (<5)
NONABROMOBIPHENYL (NonaBB)	ND (<5)
DECABROMOBIPHENYL (DecaBB)	ND (<5)
POLYBROMINATED DIPHENYL ETHERS (PBDEs) (mg/kg)	
MONOBROMODIPHENYL ETHER (MonoBDE)	ND (<5)
DIBROMODIPHENYL ETHER (DiBDE)	ND (<5)
TRIBROMODIPHENYL ETHER (TriBDE)	ND (<5)
TETRABROMODIPHENYL ETHER (TetraBDE)	ND (<5)
PENTABROMODIPHENYL ETHER (PentaBDE)	ND (<5)
HEXABROMODIPHENYL ETHER (HexaBDE)	ND (<5)
HEPTABROMODIPHENYL ETHER (HeptaBDE)	ND (<5)
OCTABROMODIPHENYL ETHER (OctaBDE)	ND (<5)
NONABROMODIPHENYL ETHER (NonaBDE)	ND (<5)
DECABROMODIPHENYL ETHER (DecaBDE)	ND (<5)

CHEMIST: LV LINNA

mg/kg = MILLIGRAM PER KILOGRAM = ppm

&lt; = LESS THAN

ND = NOT DETECTED

\*\*\*\*\*

**TEST REPORT**

NUMBER: SZHH0038564301

## TESTS CONDUCTED

## (B) RoHS REQUIREMENT:

RESTRICTED SUBSTANCES	LIMITS
CADMIUM (Cd)	0.01% (100 ppm)
LEAD (Pb)	0.1% (1000 ppm)
MERCURY (Hg)	0.1% (1000 ppm)
CHROMIUM (VI) (Cr <sup>6+</sup> )	0.1% (1000 ppm)
POLYBROMINATED BIPHENYLS (PBBs)	0.1% (1000 ppm)
POLYBROMINATED DIPHENYL ETHERS (PBDEs)	0.1% (1000 ppm)

THE ABOVE LIMITS WERE QUOTED FROM 2002/95/EC AND AMENDMENT 2005/618/EC FOR HOMOGENEOUS MATERIAL.

## (C) TEST METHOD:

TESTING ITEM	TESTING METHOD	REPORTING LIMIT
CADMIUM (Cd) CONTENT	WITH REFERENCE TO IEC 62321 EDITION 1.0:2008, BY ACID DIGESTION AND DETERMINED BY ICP - OES	2 mg/kg
LEAD (Pb) CONTENT	WITH REFERENCE TO IEC 62321 EDITION 1.0:2008, BY ACID DIGESTION AND DETERMINED BY ICP - OES	2 mg/kg
MERCURY (Hg) CONTENT	WITH REFERENCE TO IEC 62321 EDITION 1.0:2008, BY ACID DIGESTION AND DETERMINED BY ICP - OES	2 mg/kg
CHROMIUM (VI) (Cr <sup>6+</sup> ) CONTENT	WITH REFERENCE TO IEC 62321 EDITION 1.0:2008, BY ALKALINE DIGESTION AND DETERMINED BY UV-VIS SPECTROPHOTOMETER	1 mg/kg
POLYBROMINATED BIPHENYLS (PBBs) & POLYBROMINATED DIPHENYL ETHERS (PBDEs)	WITH REFERENCE TO IEC 62321 EDITION 1.0:2008, BY SOLVENT EXTRACTION AND DETERMINED BY GC/MS AND FURTHER HPLC CONFIRMATION WHEN NECESSARY	5 mg/kg

DATE SAMPLE RECEIVED : MAY 08, 2009

TESTING PERIOD : MAY 08, 2009 TO MAY 11, 2009

\*\*\*\*\*


**TEST REPORT**

NUMBER: SZHH0038564301


TESTS CONDUCTED

(D) MEASUREMENT FLOWCHART:

1. TEST FOR Cd/Pb CONTENTS



2. TEST FOR Hg CONTENT




\*\*\*\*\*

**TEST REPORT**


NUMBER: SZHH0038564301

TESTS CONDUCTED

3. TEST FOR CHROMIUM (VI) ( $\text{Cr}^{6+}$ ) CONTENT (ALKALINE DIGESTION)



4. TEST FOR PBBs/PBDEs CONTENTS



\*\*\*\*\*  
END OF REPORT