

FCC TEST REPORT
for
Shenzhen Autone-Tronic Technology Co., Ltd.

In-dash multimedia
Model No.: AXVN 825

Prepared for : Shenzhen Autone-Tronic Technology Co., Ltd.
Address : Fl4, Building 21, Changxing Technology Park, Shayi Village,
Shajin Town, Baoan District, Shenzhen City , China

Prepared By : Anbotek Compliance Laboratory Limited
Address : 1/F, 1 /Building, SEC Industrial Park, No. 4 Qianhai Road,
Nanshan District, Shenzhen, 518054, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772

Report Number : 201204693F
Date of Test : Apr. 20~26, 2012
Date of Report : Apr. 27, 2012

TABLE OF CONTENTS

| Description | Page |
|--|-----------|
| Test Report | |
| 1. GENERAL INFORMATION | 4 |
| 1.1. Description of Device (EUT)..... | 4 |
| 1.2. Auxiliary Equipment Used during Test..... | 5 |
| 1.3. Description of Test Facility | 6 |
| 1.4. Measurement Uncertainty..... | 6 |
| 2. MEASURING DEVICE AND TEST EQUIPMENT..... | 7 |
| 3. TEST PROCEDURE | 8 |
| 4. RADIATION INTERFERENCE..... | 9 |
| 4.1. Requirements (15.249, 15.209): | 9 |
| 4.2 Test Procedure | 9 |
| 4.3 Test Results..... | 9 |
| 5. OCCUPIED BANDWIDTH..... | 13 |
| 5.1. Requirements (15.249): | 13 |
| 5.2. Test Procedure | 13 |
| 5.3. Test Configuration:..... | 13 |
| 5.4. Test Results..... | 13 |
| 6. PHOTOGRAPH..... | 16 |
| 6.1. Photo of Radiation Emission Test | 16 |
| APPENDIX I (ExternalPhotos) (2 Pages) | |
| APPENDIX II (InternalPhotos) (5 Pages) | |

TEST REPORT

Applicant : Shenzhen Autone-Tronic Technology Co., Ltd.
Manufacturer : Shenzhen Autone-Tronic Technology Co., Ltd.
EUT : In-dash multimedia
Model No. : AXVN 825
Serial No. : N/A
Rating : 14.4V~~---~~, 15A, 4*25W
Trade Mark : Axxera

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.207, 15.249 & 15.209

The device described above is tested by Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Anbotek Compliance Laboratory Limited

Date of Test :

Apr. 20~26, 2012

Andy chen

Prepared by :

(Tested Engineer / Andy Chen)

Jerry Du

Reviewer :

(Project Manager / Jerry Du)

Henry. Yang.

Approved & Authorized Signer :

(Manager / Henry Yang)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : In-dash multimedia

Model Number : AXVN 825

Test Power Supply : 14.4V $\overline{\text{---}}$, 15A, 4*25W

Frequency : 2402~2480MHz

Antenna
Specification : Printed Antenna:1.87dBi

Applicant : Shenzhen Autone-Tronic Technology Co., Ltd.
Address : F14, Building 21, Changxing Technology Park, Shayi Village, Shajin
Town, Baoan District, Shenzhen City , China

Manufacturer : Shenzhen Autone-Tronic Technology Co., Ltd.
Address : F14, Building 21, Changxing Technology Park, Shayi Village, Shajin
Town, Baoan District, Shenzhen City , China

Date of receiver : Apr. 20, 2012
Date of Test : Apr. 20~26, 2012

1.2.Auxiliary Equipment Used during Test

| | |
|------------|--|
| PC | : Manufacturer: DELL M/N: OPTIPLEX 380 S/N: 1J63X2X CE , FCC: DOC |
| MONITOR | : Manufacturer: DELL M/N: E170Sc S/N: CN-00V539-64180-055-0UPS CE , FCC: DOC |
| MOUSE | : Manufacturer: DELL M/N: M-UARDEL7 S/N: N/A CE , FCC: DOC Cable: 1m, unshielded |
| Printer | : Manufacturer:Brother M/N: MFC-3360C S/N: N/A CE, FCC:DOC |
| Power Line | : Non-Shielded, 1.5m |
| VGA Cable | : Non-Shielded, 1.5m |
| USB Cable | : Non-Shielded, 0.5m |

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503

Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 752021

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, August 20, 2010.

IC-Registration No.: 8058A-1

Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, August 30, 2010.

Test Location

All Emissions tests were performed at
Anbotek Compliance Laboratory Limited. at 1/F, 1 /Building, SEC Industrial Park,
No. 4 Qianhai Road, Nanshan District, Shenzhen, 518054, China

1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB

Conduction Uncertainty : Uc = 3.4dB

2. MEASURING DEVICE AND TEST EQUIPMENT

The following test equipments were used during test:

| Equipment | Manufacturer | Model # | Serial # | Data of Cal. | Due Data |
|--------------------------------------|----------------------|---------|------------|---------------|---------------|
| EMI Test Receiver | Rohde & Schwarz | ESCI | 100119 | May 03, 2011 | May 02, 2012 |
| EMI Test Receiver | Rohde & Schwarz | ESIB26 | 100249 | Sep.22, 2011 | Sep.21, 2012 |
| EMI Test Software | SHURPLE | ESK1 | N/A | N/A | N/A |
| Spectrum Analyzer | Agilent | E7405A | MY45114970 | Jun.21, 2011 | Jun.20, 2012 |
| Signal Generator | Rohde & Schwarz | SMR27 | 100124 | Jul.06, 2011 | Jul.05, 2012 |
| Signal Generator | Rohde & Schwarz | SML03 | 102319 | Aug.01, 2011 | Aug.01, 2012 |
| AC Power Source | Sepcial power system | YF650 | N/A | N/A | N/A |
| Absorbing Clamp | Rohde & Schwarz | MDS21 | 100218 | Apr.30, 2011 | Apr.29, 2012 |
| Power Meter | Rohde & Schwarz | NRVD | 101287 | Jul.19, 2011 | Jul.18, 2012 |
| Coaxial Cable | N/A | N/A | N/A | May.31, 2011 | May.30, 2012 |
| Coaxial Cable | N/A | N/A | N/A | May.31, 2011 | May.30, 2012 |
| Coaxial Cable | N/A | N/A | N/A | May.31, 2011 | May.30, 2012 |
| Universal radio Communication tester | Rohde & Schwarz | CMU200 | 101724 | Sep.08, 2011 | Sep.07, 2012 |
| Pulse Limiter | Rohde & Schwarz | ESH3-Z2 | N/A | N/A | N/A |
| BiConilog Antenna | ETS-LINDGREN | 3142C | 00042670 | May 03, 2011 | May 02, 2012 |
| BiConilog Antenna | ETS-LINDGREN | 3142C | 00042673 | May 03, 2011 | May 02, 2012 |
| Loop Antenna | ETS-LINGREN | 6502 | 00071730 | May 03, 2011 | May 02, 2012 |
| Double-ridged Waveguide horn | ETS-LINDGREN | 3117 | 00035926 | Dec.30, 2011 | Dec.29, 2012 |
| Double-ridged Waveguide horn | ETS-LINDGREN | 3117 | 00041545 | Dec.30, 2011 | Dec.29, 2012 |
| Pre-amplifier | CD | PAM0203 | 804203 | Jun.21, 2011 | Jun.20, 2012 |
| RF Switch | CD | RSU-M3 | 706543 | Jun.21, 2011 | Jun.20, 2012 |
| Thermo-/Hygrometer | N/A | TH01 | N/A | May 03, 2011 | May 02, 2012 |
| Shielding Room | Zhong Yu Electronic | N/A | N/A | N/A | N/A |
| 3m Anechoic Chamber | Zhong Yu Electronic | N/A | N/A | Jun .28, 2011 | Jun .27, 2012 |

3. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2009 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2009 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

4. Radiation Interference

4.1. Requirements (15.249, 15.209):

| FIELD STRENGTH of Fundamental: | FIELD STRENGTH of Harmonics | S15.209 | |
|-----------------------------------|--------------------------------|---------------|---------------|
| 902-928 MHZ | | 30 - 88 MHz | 40 dBuV/m @3M |
| 2.4-2.4835 GHz | | 88 - 216 MHz | 43.5 |
| 94 dBuV/m @3m | 54 dBuV/m @3m | 216 - 960 MHz | 46 |
| | | ABOVE 960 MHz | 54dBuV/m |

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

4.2 Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 5.3.

4.3 Test Results

PASS.

Please refer the following pages.

FCC ID: YZG-DNAED

Data:

| Horizontal CH Low(2402MHz) | | | | | | | | |
|-------------------------------|-------|--------|--------|-------|--------|--------|--------|--------|
| Frequency | Cable | Ant | Preamp | Read | Level | Limit | Over | Remark |
| MHz | Loss | Factor | Factor | Level | dBμV/m | dBμV/m | Limit | |
| | dB | dB/m | dB | dBμV | | | dB | |
| 239.98 | 1.58 | 13.50 | 38.90 | 57.45 | 33.65 | 46.00 | -12.35 | QP |
| 2402.00 | 2.17 | 31.21 | 35.30 | 86.65 | 84.73 | 114.0 | -29.27 | Peak |
| 2402.00 | 2.17 | 31.21 | 35.30 | 84.71 | 82.79 | 94.0 | -11.21 | AV |
| 4804.10 | 2.56 | 34.01 | 34.71 | 41.05 | 42.91 | 74.0 | -31.09 | Peak |
| 4804.10 | 2.56 | 34.01 | 34.71 | 38.25 | 40.11 | 54.0 | -13.89 | AV |
| 7207.97 | 2.98 | 36.16 | 35.15 | 38.33 | 42.32 | 74.0 | -31.68 | Peak |
| 7207.97 | 2.98 | 36.16 | 35.15 | 35.55 | 39.54 | 54.0 | -14.46 | AV |
| 9608.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 12010.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 14412.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 16814.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 19216.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 21618.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 24020.00 | --- | --- | --- | --- | --- | --- | --- | --- |

| CH Middle(2441MHz) | | | | | | | | |
|--------------------|-------|--------|--------|-------|--------|--------|--------|--------|
| Frequency | Cable | Ant | Preamp | Read | Level | Limit | Over | Remark |
| MHz | Loss | Factor | Factor | Level | dBμV/m | dBμV/m | Limit | |
| | dB | dB/m | dB | dBμV | | | dB | |
| 312.18 | 1.60 | 13.52 | 38.82 | 56.40 | 32.70 | 46.00 | -13.30 | QP |
| 2441.00 | 2.19 | 31.22 | 34.60 | 85.35 | 84.16 | 114.0 | -29.84 | Peak |
| 2441.00 | 2.19 | 31.22 | 34.60 | 83.55 | 82.36 | 94.0 | -11.64 | AV |
| 4882.08 | 2.57 | 35.00 | 34.58 | 39.62 | 42.61 | 74.0 | -31.39 | Peak |
| 4882.08 | 2.57 | 35.00 | 34.58 | 37.47 | 40.46 | 54.0 | -13.54 | AV |
| 7323.05 | 3.00 | 36.17 | 35.14 | 38.80 | 42.83 | 74.0 | -31.17 | Peak |
| 7323.05 | 3.00 | 36.17 | 35.14 | 36.08 | 40.11 | 54.0 | -13.89 | AV |
| 9764.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 12205.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 14646.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 17087.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 19528.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 21969.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 24410.00 | --- | --- | --- | --- | --- | --- | --- | --- |

FCC ID: YZG-DNAED

| CH High(2480MHz) | | | | | | | | |
|------------------|-------|--------|--------|-------|--------|--------|--------|--------|
| Frequency | Cable | Ant | Preamp | Read | Level | Limit | Over | Remark |
| MHz | Loss | Factor | Factor | Level | dBμV/m | dBμV/m | Limit | |
| | dB | dB/m | dB | dBμV | | | dB | |
| 312.18 | 1.60 | 13.52 | 38.82 | 54.21 | 30.51 | 46.00 | -15.49 | QP |
| 2480.00 | 2.20 | 31.65 | 36.00 | 92.78 | 90.63 | 114.0 | -23.37 | Peak |
| 2480.00 | 2.20 | 31.65 | 36.00 | 89.51 | 87.36 | 94.0 | -6.64 | AV |
| 4960.05 | 2.58 | 35.06 | 34.79 | 41.76 | 44.61 | 74.0 | -29.39 | Peak |
| 4960.05 | 2.58 | 35.06 | 34.79 | 39.28 | 42.13 | 54.0 | -11.87 | AV |
| 7439.97 | 3.02 | 36.19 | 34.90 | 39.53 | 43.84 | 74.0 | -30.16 | Peak |
| 7439.97 | 3.02 | 36.20 | 35.20 | 37.40 | 41.42 | 54.0 | -12.58 | AV |
| 9920.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 12400.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 14880.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 17360.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 19840.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 22320.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 24800.00 | --- | --- | --- | --- | --- | --- | --- | --- |

| Vertical CH Low(2402MHz) | | | | | | | | |
|-----------------------------|-------|--------|--------|-------|--------|--------|--------|--------|
| Frequency | Cable | Ant | Preamp | Read | Level | Limit | Over | Remark |
| MHz | Loss | Factor | Factor | Level | dBμV/m | dBμV/m | Limit | |
| | dB | dB/m | dB | dBμV | | | dB | |
| 30.42 | 1.43 | 12.13 | 38.45 | 53.50 | 28.61 | 40.00 | -11.39 | QP |
| 2402.00 | 2.17 | 31.21 | 35.30 | 84.23 | 82.31 | 114.0 | -31.69 | Peak |
| 2402.00 | 2.17 | 31.21 | 35.30 | 81.85 | 79.93 | 94.0 | -14.07 | AV |
| 4804.10 | 2.56 | 34.01 | 34.71 | 41.05 | 42.91 | 74.0 | -31.09 | Peak |
| 4804.10 | 2.56 | 34.01 | 34.71 | 38.60 | 40.46 | 54.0 | -13.54 | AV |
| 7207.93 | 2.98 | 36.16 | 35.15 | 37.46 | 41.45 | 74.0 | -32.55 | Peak |
| 7207.93 | 2.98 | 36.16 | 35.15 | 34.50 | 38.49 | 54.0 | -15.51 | AV |
| 9608.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 12010.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 14412.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 16814.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 19216.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 21618.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 24020.00 | --- | --- | --- | --- | --- | --- | --- | --- |

FCC ID: YZG-DNAED

| CH Middle(2441MHz) | | | | | | | | |
|--------------------|-------|--------|---------|-------|--------|--------|--------|--------|
| Frequency | Cable | Ant | Preampl | Read | Level | Limit | Over | Remark |
| MHz | Loss | Factor | Factor | Level | dBμV/m | dBμV/m | Limit | |
| | dB | dB/m | dB | dBμV | | | dB | |
| 143.82 | 1.50 | 13.40 | 38.89 | 53.90 | 29.91 | 43.50 | -13.59 | QP |
| 2441.01 | 2.19 | 31.22 | 34.60 | 82.35 | 81.16 | 114.0 | -32.84 | Peak |
| 2441.01 | 2.19 | 31.22 | 34.60 | 81.01 | 79.82 | 94.0 | -14.18 | AV |
| 4882.11 | 2.57 | 35.00 | 34.58 | 40.15 | 43.14 | 74.0 | -30.86 | Peak |
| 4882.11 | 2.57 | 35.00 | 34.58 | 37.86 | 40.85 | 54.0 | -13.15 | AV |
| 7323.05 | 3.00 | 36.17 | 35.14 | 38.70 | 42.73 | 74.0 | -31.27 | Peak |
| 7323.05 | 3.00 | 36.17 | 35.14 | 36.00 | 40.03 | 54.0 | -13.81 | AV |
| 9764.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 12205.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 14646.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 17087.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 19528.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 21969.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 24410.00 | --- | --- | --- | --- | --- | --- | --- | --- |

| CH High(2480MHz) | | | | | | | | |
|------------------|-------|--------|---------|-------|--------|--------|--------|--------|
| Frequency | Cable | Ant | Preampl | Read | Level | Limit | Over | Remark |
| MHz | Loss | Factor | Factor | Level | dBμV/m | dBμV/m | Limit | |
| | dB | dB/m | dB | dBμV | | | dB | |
| 408.80 | 1.62 | 13.54 | 38.45 | 51.16 | 27.87 | 46.00 | -18.13 | QP |
| 2480.00 | 2.20 | 31.65 | 36.00 | 83.52 | 81.37 | 114.0 | -32.63 | Peak |
| 2480.00 | 2.20 | 31.65 | 36.00 | 82.02 | 79.87 | 94.0 | -14.13 | AV |
| 4960.10 | 2.58 | 35.06 | 34.79 | 40.08 | 42.93 | 74.0 | -31.07 | Peak |
| 4960.10 | 2.58 | 35.06 | 34.79 | 38.10 | 40.95 | 54.0 | -13.05 | AV |
| 7439.97 | 3.02 | 36.19 | 34.90 | 38.58 | 42.89 | 74.0 | -31.11 | Peak |
| 7439.97 | 3.02 | 36.20 | 35.20 | 36.34 | 40.36 | 54.0 | -13.64 | AV |
| 9920.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 12400.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 14880.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 17360.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 19840.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 22320.00 | --- | --- | --- | --- | --- | --- | --- | --- |
| 24800.00 | --- | --- | --- | --- | --- | --- | --- | --- |

NOTE: “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

5. Occupied Bandwidth


5.1. Requirements (15.249):

The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

5.2. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

5.3. Test Configuration:




5.4. Test Results

Pass.

Please refer the following plot.


(Note: Marker 3 means the highest value in 2.39GHz~2.4GHz or 2.4835~2.5GHz)

FCC ID: YZG-DNAED



Bandedges-L


Date: 23.APR.2012 18:19:57



Bandedges-L-AV


Date: 23.APR.2012 18:22:28

FCC ID: YZG-DNAED



Bandedges-H

Date: 23.APR.2012 18:17:27



Bandedges-H-AV

Date: 23.APR.2012 18:25:46