

## FCC Test Report (WLAN)

**Report No.:** RF170703E05-1

**FCC ID:** YZKECW54100

**Test Model:** ECW5410-O

**Series Model:** ECW5410-L2, ECW5410-L

**Received Date:** July 04, 2017

**Test Date:** Aug. 08 to Sep. 08, 2017

**Issued Date:** Oct. 20, 2017

**Applicant:** Edgecore Networks Corporation.

**Address:** No.1, Creation Rd. III, Hsinchu Science Park, Hsinchu 30077, Taiwan,  
R.O.C

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location :** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record .....</b>	<b>4</b>
<b>1 Certificate of Conformity .....</b>	<b>5</b>
<b>2 Summary of Test Results .....</b>	<b>6</b>
2.1 Measurement Uncertainty .....	6
2.2 Modification Record .....	6
<b>3 General Information .....</b>	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Description of Test Modes .....	11
3.2.1 Test Mode Applicability and Tested Channel Detail .....	12
3.3 Duty Cycle of Test Signal .....	15
3.4 Description of Support Units .....	16
3.4.1 Configuration of System under Test .....	17
3.5 General Description of Applied Standard .....	19
<b>4 Test Types and Results .....</b>	<b>20</b>
4.1 Radiated Emission and Bandedge Measurement .....	20
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	20
4.1.2 Test Instruments .....	21
4.1.3 Test Procedure .....	23
4.1.4 Deviation from Test Standard .....	23
4.1.5 Test Setup .....	24
4.1.6 EUT Operating Condition .....	25
4.1.7 Test Results .....	26
4.2 Conducted Emission Measurement .....	46
4.2.1 Limits of Conducted Emission Measurement .....	46
4.2.2 Test Instruments .....	46
4.2.3 Test Procedure .....	47
4.2.4 Deviation from Test Standard .....	47
4.2.5 Test Setup .....	47
4.2.6 EUT Operating Condition .....	47
4.2.7 Test Results (Mode 1) .....	48
4.2.8 Test Results (Mode 2) .....	50
4.3 Transmit Power Measurement .....	52
4.3.1 Limits of Transmit Power Measurement .....	52
4.3.2 Test Setup .....	52
4.3.3 Test Instruments .....	52
4.3.4 Test Procedure .....	52
4.3.5 Deviation from Test Standard .....	52
4.3.6 EUT Operating Condition .....	52
4.3.7 Test Result .....	53
4.4 Occupied Bandwidth Measurement .....	57
4.4.1 Test Setup .....	57
4.4.2 Test Instruments .....	57
4.4.3 Test Procedure .....	57
4.4.4 Test Results .....	58
4.5 Peak Power Spectral Density Measurement .....	66
4.5.1 Limits of Peak Power Spectral Density Measurement .....	66
4.5.2 Test Setup .....	66
4.5.3 Test Instruments .....	66
4.5.4 Test Procedure .....	67
4.5.5 Deviation from Test Standard .....	67
4.5.6 EUT Operating Condition .....	67
4.5.7 Test Results .....	68
4.6 Frequency Stability Measurement .....	76

4.6.1 Limits of Frequency Stability Measurement .....	76
4.6.2 Test Setup .....	76
4.6.3 Test Instruments .....	76
4.6.4 Test Procedure .....	76
4.6.5 Deviation from Test Standard .....	76
4.6.6 EUT Operating Condition .....	76
4.6.7 Test Results .....	77
4.7 6dB Bandwidth Measurement .....	78
4.7.1 Limits of 6dB Bandwidth Measurement .....	78
4.7.2 Test Setup .....	78
4.7.3 Test Instruments .....	78
4.7.4 Test Procedure .....	78
4.7.5 Deviation from Test Standard .....	78
4.7.6 EUT Operating Condition .....	78
4.7.7 Test Results .....	79
<b>5 Pictures of Test Arrangements .....</b>	<b>81</b>
<b>Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band) .....</b>	<b>82</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>86</b>

### Release Control Record

Issue No.	Description	Date Issued
RF170703E05-1	Original release.	Oct. 20, 2017

## 1 Certificate of Conformity

**Product:** 802.11ac Wireless Access Point

**Brand:** Edgecore

**Test Model:** ECW5410-O

**Series Model:** ECW5410-L2, ECW5410-L

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** Edgecore Networks Corporation.

**Test Date:** Aug. 08 to Sep. 08, 2017

**Standard:** 47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Wendy Wu , **Date:** Oct. 20, 2017  
Wendy Wu / Specialist

**Approved by :** May Chen , **Date:** Oct. 20, 2017  
May Chen / Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
FCC Clause	Test Item	Result	Remarks
15.407(b)(6)	AC Power Conducted Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -4.17dB at 8.15625MHz.
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement*	Pass	Meet the requirement of limit. Minimum passing margin is -0.1dB at 5150.00MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	-	Reference only.
15.407(a)(1/2/3)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6dB bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is i-pex not a standard connector.

\*For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.30 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.16 dB
	6GHz ~ 18GHz	4.91 dB
	18GHz ~ 40GHz	5.30 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	802.11ac Wireless Access Point
Brand	Edgecore
Test Model	ECW5410-O
Series Model	ECW5410-L2, ECW5410-L
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	DC 12V from power adapter or DC 55V from POE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode only
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 600Mbps 802.11ac: up to 1733.3Mbps 802.11ac (80+80): up to 3466.7Mbps
Operating Frequency	<b>2.4GHz:</b> 2.412 ~ 2.462GHz <b>5GHz:</b> 5.18~ 5.24GHz, 5.745 ~ 5.825GHz
Number of Channel	<b>2.4GHz:</b> 802.11b, 802.11g, 802.11n (HT20): 11 802.11n (HT40): 7 <b>5GHz:</b> 802.11a, 802.11n (HT20), 802.11ac (VHT20): 9 802.11n (HT40), 802.11ac (VHT40): 4 802.11ac (VHT80): 2 802.11ac (VHT80+80): 1 set
Output Power	<b>2.4GHz:</b> <b>CDD Mode:</b> 721.798mW <b>Beamforming Mode:</b> 354.694mW <b>5GHz:</b> <b>CDD Mode:</b> <b>5.18 ~ 5.24GHz:</b> 528.397mW <b>5.745 ~ 5.825GHz:</b> 865.625mW <b>Beamforming Mode:</b> <b>5.18 ~ 5.24GHz:</b> 262.23mW <b>5.745 ~ 5.825GHz:</b> 271.036mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x 1
Data Cable Supplied	NA

Note:

1. Simultaneously transmission condition.

Condition	Technology		
1	WLAN 2.4GHz	WLAN 5GHz	Bluetooth

**Note:** The emission of the simultaneous operation has been evaluated and no non-compliance was found.

2. The EUT has below model names, which are identical to each other in all aspects except for the following information:

Brand	Model Name	Difference
Edgecore	ECW5410-O	1. Difference SW. 2. Open WRT code based. 3. -O => ONIE code. 4. For marketing purpose.
	ECW5410-L2	1. Difference SW. 2. Cloud code based 3. -L2 => cloud based code. 4. For marketing purpose.
	ECW5410-L	1. Difference SW. 2. Controller based code. 3. -L => controller based code. 4. For marketing purpose.

From the above models, model: **ECW5410-O** was selected as representative model for the test and its data was recorded in this report.

3. The EUT must be supplied with a power adapter or POE (only for test not for sale) as following table:

Adapter		
Brand	Model No.	Spec.
APD	WA-24Q12FU	Input: 100-240Vac, 50/60Hz, 0.7A Output: 12Vdc, 2.0A DC output cable (Unshielded, 1.8m)
POE(Only for test not for sale)		
Brand	Model No.	Spec.
Motorola	PD-7001G	Input: 100-240Vac, 50/60Hz, 0.67A Output: 55Vdc, 1.35A

Note: From above adapter and POE, the radiated emission worst case was found in **Adapter**. Therefore only the test data of the modes were recorded in this report individually.



4. The antennas provided to the EUT, please refer to the following table:

WLAN						
Antenna No.	Brand	Model No.	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
1	NA	NA	3.59	2.4~2.4835	Monopole	i-pex
			6.28	5.15~5.25		
			5.41	5.25~5.35		
			5.24	5.47~5.725		
			6.39	5.725~5.85		
2	NA	NA	3.74	2.4~2.4835	Monopole	i-pex
			3.9	5.15~5.25		
			3.48	5.25~5.35		
			4.16	5.47~5.725		
			4.41	5.725~5.85		
3	NA	NA	4.33	2.4~2.4835	Monopole	i-pex
			5.65	5.15~5.25		
			5.02	5.25~5.35		
			4.84	5.47~5.725		
			4.93	5.725~5.85		
4	NA	NA	4.09	2.4~2.4835	Monopole	i-pex
			6.09	5.15~5.25		
			5.37	5.25~5.35		
			5.29	5.47~5.725		
			6.62	5.725~5.85		
Bluetooth						
Antenna No.	Brand	Model No.	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
5	NA	NA	4.68	2.4~2.4835	Monopole	i-pex

5. The EUT incorporates a MIMO function:

2.4GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11b	1 ~ 11Mbps	4TX	4RX
802.11g	6 ~ 54Mbps	4TX	4RX
802.11n (HT20)	MCS 0~7	4TX	4RX
	MCS 8~15	4TX	4RX
	MCS 16~23	4TX	4RX
	MCS 24~31	4TX	4RX
802.11n (HT40)	MCS 0~7	4TX	4RX
	MCS 8~15	4TX	4RX
	MCS 16~23	4TX	4RX
	MCS 24~31	4TX	4RX
5GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11a	6 ~ 54Mbps	4TX	4RX
802.11n (HT20)	MCS 0~7	4TX	4RX
	MCS 8~15	4TX	4RX
	MCS 16~23	4TX	4RX
	MCS 24~31	4TX	4RX
802.11n (HT40)	MCS 0~7	4TX	4RX
	MCS 8~15	4TX	4RX
	MCS 16~23	4TX	4RX
	MCS 24~31	4TX	4RX
802.11ac (VHT20)	MCS 0~8, Nss=1	4TX	4RX
	MCS 0~8, Nss=2	4TX	4RX
	MCS 0~9, Nss=3	4TX	4RX
	MCS 0~8, Nss=4	4TX	4RX
802.11ac (VHT40)	MCS 0~9, Nss=1	4TX	4RX
	MCS 0~9, Nss=2	4TX	4RX
	MCS 0~9, Nss=3	4TX	4RX
	MCS 0~9, Nss=4	4TX	4RX
802.11ac (VHT80)	MCS 0~9, Nss=1	4TX	4RX
	MCS 0~9, Nss=2	4TX	4RX
	MCS 0~9, Nss=3	4TX	4RX
	MCS 0~9, Nss=4	4TX	4RX
802.11ac (VHT80+VHT80)	MCS 0~9, Nss=2	4TX	4RX
	MCS 0~9, Nss=4	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz) and 802.11ac mode for 20MHz (40MHz), therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

#### FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
42	5210MHz

#### FOR 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
155	5775MHz

#### For simultaneous transmission:

1 set is provided for 802.11ac (VHT80+80):

Channel	Frequency
42+155	5210MHz + 5775MHz

Note: The transmission is for noncontiguous transmission using two nonadjacent 80MHz channels.

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	√	√	Power from adapter
2	-	-	√	-	Power from POE

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

**NOTE:**

1. The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **Y-plane**.
2. "-" means no effect.

#### **Radiated Emission Test (Above 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6
802.11ac (VHT20)		36 to 48	36, 40, 48	OFDM	BPSK	6.5
802.11ac (VHT40)		38 to 46	38, 46	OFDM	BPSK	13.5
802.11ac (VHT80)		42	42	OFDM	BPSK	29.3
802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6
802.11ac (VHT20)		149 to 165	149, 157, 165	OFDM	BPSK	6.5
802.11ac (VHT40)		151 to 159	151, 159	OFDM	BPSK	13.5
802.11ac (VHT80)		155	155	OFDM	BPSK	29.3
802.11ac (VHT80+80)	5180-5240 5745-5825	42 to 155	42 + 155	OFDM	BPSK	58.5

#### **Radiated Emission Test (Below 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	5180-5240 5745-5825	36 to 48 149 to 165	146	OFDM	BPSK	6

### **Power Line Conducted Emission Test:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	5180-5240 5745-5825	36 to 48 149 to 165	146	OFDM	BPSK	6

### **Antenna Port Conducted Measurement:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

CDD Mode						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6
802.11ac (VHT20)		36 to 48	36, 40, 48	OFDM	BPSK	6.5
802.11ac (VHT40)		38 to 46	38, 46	OFDM	BPSK	13.5
802.11ac (VHT80)		42	42	OFDM	BPSK	29.3
802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6
802.11ac (VHT20)		149 to 165	149, 157, 165	OFDM	BPSK	6.5
802.11ac (VHT40)		151 to 159	151, 159	OFDM	BPSK	13.5
802.11ac (VHT80)		155	155	OFDM	BPSK	29.3
802.11ac (VHT80+80)	5180-5240 5745-5825	42 to 155	42 + 155	OFDM	BPSK	58.5
Beamforming Mode (output power only & occupied bandwidth)						
Mode	FREQ. Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11ac (VHT20)	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6.5
802.11ac (VHT40)		38 to 46	38, 46	OFDM	BPSK	13.5
802.11ac (VHT80)		42	42	OFDM	BPSK	29.3
802.11ac (VHT20)	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6.5
802.11ac (VHT40)		151 to 159	151, 159	OFDM	BPSK	13.5
802.11ac (VHT80)		155	155	OFDM	BPSK	29.3
802.11ac (VHT80+80)	5180-5240 5745-5825	42 to 155	42 + 155	OFDM	BPSK	58.5

**Test Condition:**

Applicable To	Environmental Conditions	Input Power	Tested By
RE $\geq$ 1G	23deg. C, 62%RH	120Vac, 60Hz	Jyunchun Lin
RE<1G	25deg. C, 64%RH	120Vac, 60Hz	Jyunchun Lin
PLC	25deg. C, 75%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Robert Cheng

### 3.3 Duty Cycle of Test Signal

If duty cycle of test signal is  $\geq 98\%$ , duty factor is not required.

If duty cycle of test signal is  $< 98\%$ , duty factor shall be considered.

**802.11a:** Duty cycle =  $2.06 \text{ ms} / 2.13 \text{ ms} = 0.967$ , Duty factor =  $10 * \log(1/0.967) = 0.15$


**802.11ac (VHT20):** Duty cycle =  $5.006 \text{ ms} / 5.074 \text{ ms} = 0.978$

**802.11ac (VHT40):** Duty cycle =  $2.482 \text{ ms} / 2.059 \text{ ms} = 0.968$ , Duty factor =  $10 * \log(1/0.968) = 0.14$


**802.11ac (VHT80):** Duty cycle =  $1.147 \text{ ms} / 1.215 \text{ ms} = 0.944$ , Duty factor =  $10 * \log(1/0.944) = 0.25$

**802.11ac (VHT80+80):** Duty cycle =  $1.147 / 1.215 = 0.944$ , Duty factor =  $10 * \log(1/0.944) = 0.25$


**802.11a**




**802.11ac (VHT20)**




**802.11ac (VHT40)**



**802.11ac (VHT80)**



**802.11ac (VHT80+80)**



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	POE	Motorola	PD-7001G	NA	NA	Provided by Lab
B.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
C.	Laptop	DELL	E5430	4YV4VY1	FCC DoC	Provided by Lab

Note:


1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ-45 Cable	1	3	No	0	Provided by Lab
2.	RJ-45 Cable	1	10	No	0	Provided by Lab
3.	RJ-45 Cable	1	10	No	0	Provided by Lab
4.	Console Cable	1	1.6	No	0	Provided by Lab
5.	DC Cable	1	1.8	No	0	Supplied by client




### 3.4.1 Configuration of System under Test

#### Mode 1:



**Mode 2:**



### 3.5 General Description of Applied Standard

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)**

**KDB 789033 D02 General UNII Test Procedure New Rules v01r04**

**KDB 662911 D01 Multiple Transmitter Output v02r01**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### NOTE:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To			Limit	
789033 D02 General UNII Test Procedure New Rules v01r03			Field Strength at 3m	
			PK:74 (dBµV/m)	AV:54 (dBµV/m)
Frequency Band	Applicable To		EIRP Limit	Equivalent Field Strength at 3m
5150~5250 MHz	15.407(b)(1)		PK:-27 (dBm/MHz)	PK:68.2(dBµV/m)
5250~5350 MHz	15.407(b)(2)			
5470~5725 MHz	15.407(b)(3)			
5725~5850 MHz	<input checked="" type="checkbox"/>	15.407(b)(4)(i)	PK:-27 (dBm/MHz) <sup>*1</sup> PK:10 (dBm/MHz) <sup>*2</sup> PK:15.6 (dBm/MHz) <sup>*3</sup> PK:27 (dBm/MHz) <sup>*4</sup>	PK: 68.2(dBµV/m) <sup>*1</sup> PK:105.2 (dBµV/m) <sup>*2</sup> PK: 110.8(dBµV/m) <sup>*3</sup> PK:122.2 (dBµV/m) <sup>*4</sup>
	<input type="checkbox"/>	15.407(b)(4)(ii)	Emission limits in section 15.247(d)	
<sup>*1</sup> beyond 75 MHz or more above of the band edge.			<sup>*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.	
<sup>*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.			<sup>*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	

#### Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 08, 2017	July 07, 2018
Pre-Amplifier <sup>(*)</sup> EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna <sup>(*)</sup> Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 17, 2017	Jan. 16, 2018
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Nov. 10, 2016	Nov. 09, 2017
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Dec. 13, 2016	Dec. 12, 2017
RF Cable	8D	966-4-1 966-4-2 966-4-3	Apr. 01, 2017	Mar. 31, 2018
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Oct. 05, 2016	Oct. 04, 2017
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Dec. 27, 2016	Dec. 26, 2017
Pre-Amplifier EMCI	EMC12630SE	980385	Feb. 02, 2017	Feb. 01, 2018
RF Cable	EMC104-SM-SM-1200 EMC104-SM-SM-2000 EMC104-SM-SM-5000	160923 150318 150321	Feb. 02, 2017 Mar. 29, 2017 Mar. 29, 2017	Feb. 01, 2018 Mar. 28, 2018 Mar. 28, 2018
Pre-Amplifier EMCI	EMC184045SE	980387	Feb. 02, 2017	Feb. 01, 2018
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Dec. 15, 2016	Dec. 14, 2017
RF Cable	SUCOFLEX 102	36432/2 36433/2	Jan. 15, 2017	Jan. 14, 2018
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208410	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP02	NA	NA
Spectrum Analyzer R&S	FSv40	100964	July 1, 2017	June 30, 2018
Power meter Anritsu	ML2495A	1014008	May 11, 2017	May 10, 2018
Power sensor Anritsu	MA2411B	0917122	May 11, 2017	May 10, 2018
AC Power Source Extech Electronics	6205	1440452	NA	NA
Temperature & Humidity Chamber Giant Force	GTH-150-40-SP-AR	MAA0812-008	Jan. 11, 2017	Jan. 10, 2018
Digital Multimeter FLUKE	87III	73680266	Nov. 10, 2016	Nov. 09, 2017

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. \*The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 4.
4. Loop antenna was used for all emissions below 30 MHz.
5. The FCC Designation Number is TW2022.
6. The CANADA Site Registration No. is 20331-2
7. Tested Date: Sep. 06 to 08, 2017

#### 4.1.3 Test Procedure

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup

##### For Radiated emission below 30MHz




##### For Radiated emission 30MHz to 1GHz





### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Condition

- Connected the EUT with the Laptop which is placed on remote site.
- Contorlling software (Wifi QDART-Connectivity1000036.exe) has been activated to set the EUT on specific status.

#### 4.1.7 Test Results

##### Above 1GHz Data:

##### 802.11a

<b>CHANNEL</b>	TX Channel 36	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.1 PK	74.0	-7.9	1.89 H	340	62.1	4.0
2	5150.00	53.6 AV	54.0	-0.4	1.89 H	340	49.6	4.0
3	*5180.00	120.6 PK			1.89 H	340	116.6	4.0
4	*5180.00	110.2 AV			1.89 H	340	106.2	4.0
5	#10360.00	54.7 PK	74.0	-19.3	1.00 H	15	41.1	13.6
6	#10360.00	42.0 AV	54.0	-12.0	1.00 H	15	28.4	13.6
7	15540.00	46.4 PK	74.0	-27.6	1.00 H	10	33.2	13.2
8	15540.00	34.1 AV	54.0	-19.9	1.00 H	10	20.9	13.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	62.7 PK	74.0	-11.3	1.50 V	29	58.7	4.0
2	5150.00	49.9 AV	54.0	-4.1	1.50 V	29	45.9	4.0
3	*5180.00	118.2 PK			1.50 V	29	114.2	4.0
4	*5180.00	109.2 AV			1.50 V	29	105.2	4.0
5	#10360.00	58.8 PK	74.0	-15.2	1.00 V	356	45.2	13.6
6	#10360.00	46.3 AV	54.0	-7.7	1.00 V	356	32.7	13.6
7	15540.00	46.8 PK	74.0	-27.2	2.20 V	29	33.6	13.2
8	15540.00	34.6 AV	54.0	-19.4	2.20 V	29	21.4	13.2

##### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 40	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.5 PK	74.0	-7.5	1.66 H	57	62.5	4.0
2	5150.00	53.6 AV	54.0	-0.4	1.66 H	57	49.6	4.0
3	*5200.00	121.0 PK			1.66 H	57	117.0	4.0
4	*5200.00	111.5 AV			1.66 H	57	107.5	4.0
5	5350.00	51.5 PK	74.0	-22.5	1.66 H	57	47.1	4.4
6	5350.00	39.8 AV	54.0	-14.2	1.66 H	57	35.4	4.4
7	#10400.00	54.7 PK	74.0	-19.3	1.04 H	22	41.1	13.6
8	#10400.00	42.2 AV	54.0	-11.8	1.04 H	22	28.6	13.6
9	15600.00	45.9 PK	74.0	-28.1	1.06 H	20	32.5	13.4
10	15600.00	33.8 AV	54.0	-20.2	1.06 H	20	20.4	13.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	58.9 PK	74.0	-15.1	1.63 V	359	54.9	4.0
2	5150.00	47.0 AV	54.0	-7.0	1.63 V	359	43.0	4.0
3	*5200.00	120.4 PK			1.63 V	359	116.4	4.0
4	*5200.00	111.3 AV			1.63 V	359	107.3	4.0
5	5350.00	50.6 PK	74.0	-23.4	1.63 V	359	46.2	4.4
6	5350.00	38.8 AV	54.0	-15.2	1.63 V	359	34.4	4.4
7	#10400.00	58.4 PK	74.0	-15.6	1.05 V	360	44.8	13.6
8	#10400.00	46.0 AV	54.0	-8.0	1.05 V	360	32.4	13.6
9	15600.00	46.8 PK	74.0	-27.2	2.14 V	15	33.4	13.4
10	15600.00	34.5 AV	54.0	-19.5	2.14 V	15	21.1	13.4

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 48	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	121.3 PK			1.47 H	61	117.1	4.2
2	*5240.00	117.7 AV			1.47 H	61	113.5	4.2
3	5350.00	50.3 PK	74.0	-23.7	1.47 H	61	45.9	4.4
4	5350.00	38.6 AV	54.0	-15.4	1.47 H	61	34.2	4.4
5	#10480.00	54.5 PK	74.0	-19.5	1.02 H	12	40.8	13.7
6	#10480.00	41.6 AV	54.0	-12.4	1.02 H	12	27.9	13.7
7	15720.00	46.7 PK	74.0	-27.3	1.09 H	2	32.7	14.0
8	15720.00	34.4 AV	54.0	-19.6	1.09 H	2	20.4	14.0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	120.6 PK			1.61 V	359	116.4	4.2
2	*5240.00	117.1 AV			1.61 V	359	112.9	4.2
3	5350.00	50.1 PK	74.0	-23.9	1.61 V	359	45.7	4.4
4	5350.00	38.5 AV	54.0	-15.5	1.61 V	359	34.1	4.4
5	#10480.00	59.0 PK	74.0	-15.0	1.08 V	358	45.3	13.7
6	#10480.00	46.2 AV	54.0	-7.8	1.08 V	358	32.5	13.7
7	15720.00	46.8 PK	74.0	-27.2	2.22 V	37	32.8	14.0
8	15720.00	34.7 AV	54.0	-19.3	2.22 V	37	20.7	14.0

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 149	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5644.77	58.1 PK	68.2	-10.1	1.99 H	19	53.3	4.8
2	*5745.00	123.8 PK			1.99 H	19	118.8	5.0
3	*5745.00	113.9 AV			1.99 H	19	108.9	5.0
4	#5995.36	57.9 PK	68.2	-10.3	1.99 H	19	52.3	5.6
5	11490.00	58.7 PK	74.0	-15.3	1.56 H	305	44.6	14.1
6	11490.00	46.9 AV	54.0	-7.1	1.56 H	305	32.8	14.1
7	#17235.00	53.7 PK	74.0	-20.3	1.78 H	244	35.4	18.3
8	#17235.00	41.7 AV	54.0	-12.3	1.78 H	244	23.4	18.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5650.62	59.1 PK	68.7	-9.6	2.79 V	360	54.4	4.7
2	*5745.00	122.4 PK			2.79 V	360	117.4	5.0
3	*5745.00	113.5 AV			2.79 V	360	108.5	5.0
4	#6020.75	58.7 PK	68.2	-9.5	2.79 V	360	53.0	5.7
5	11490.00	64.7 PK	74.0	-9.3	2.46 V	358	50.6	14.1
6	11490.00	53.6 AV	54.0	-0.4	2.46 V	358	39.5	14.1
7	#17235.00	54.3 PK	74.0	-19.7	2.18 V	31	36.0	18.3
8	#17235.00	41.6 AV	54.0	-12.4	2.18 V	31	23.3	18.3

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 157	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5627.23	57.6 PK	68.2	-10.6	2.01 H	18	52.9	4.7
2	*5785.00	123.7 PK			2.01 H	18	118.7	5.0
3	*5785.00	113.6 AV			2.01 H	18	108.6	5.0
4	#6000.43	58.3 PK	68.2	-9.9	2.01 H	18	52.7	5.6
5	11570.00	58.5 PK	74.0	-15.5	1.54 H	315	44.5	14.0
6	11570.00	46.9 AV	54.0	-7.1	1.54 H	315	32.9	14.0
7	#17355.00	53.4 PK	74.0	-20.6	1.75 H	243	34.5	18.9
8	#17355.00	41.4 AV	54.0	-12.6	1.75 H	243	22.5	18.9

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5646.05	58.4 PK	68.2	-9.8	2.62 V	360	53.6	4.8
2	*5785.00	122.1 PK			2.62 V	360	117.1	5.0
3	*5785.00	113.1 AV			2.62 V	360	108.1	5.0
4	#5965.34	57.6 PK	68.2	-10.6	2.62 V	360	52.1	5.5
5	11570.00	64.7 PK	74.0	-9.3	2.34 V	360	50.7	14.0
6	11570.00	53.5 AV	54.0	-0.5	2.34 V	360	39.5	14.0
7	#17355.00	53.8 PK	74.0	-20.2	2.17 V	38	34.9	18.9
8	#17355.00	41.5 AV	54.0	-12.5	2.17 V	38	22.6	18.9

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 165	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5572.08	57.6 PK	68.2	-10.6	1.98 H	27	53.0	4.6
2	*5825.00	123.7 PK			1.98 H	27	118.5	5.2
3	*5825.00	113.8 AV			1.98 H	27	108.6	5.2
4	#6012.15	58.2 PK	68.2	-10.0	1.98 H	27	52.5	5.7
5	11650.00	58.2 PK	74.0	-15.8	1.51 H	303	44.1	14.1
6	11650.00	46.5 AV	54.0	-7.5	1.51 H	303	32.4	14.1
7	#17475.00	53.4 PK	74.0	-20.6	1.73 H	251	33.7	19.7
8	#17475.00	41.6 AV	54.0	-12.4	1.73 H	251	21.9	19.7

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5557.54	57.5 PK	68.2	-10.7	2.75 V	360	52.9	4.6
2	*5825.00	122.2 PK			2.75 V	360	117.0	5.2
3	*5825.00	113.3 AV			2.75 V	360	108.1	5.2
4	#6014.12	58.6 PK	68.2	-9.6	2.75 V	360	52.9	5.7
5	11650.00	64.7 PK	74.0	-9.3	2.40 V	360	50.6	14.1
6	11650.00	53.7 AV	54.0	-0.3	2.40 V	360	39.6	14.1
7	#17475.00	54.2 PK	74.0	-19.8	2.16 V	39	34.5	19.7
8	#17475.00	41.9 AV	54.0	-12.1	2.16 V	39	22.2	19.7

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11ac (VHT20)

<b>CHANNEL</b>	TX Channel 36	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.1 PK	74.0	-7.9	1.55 H	61	62.1	4.0
2	5150.00	53.5 AV	54.0	-0.5	1.55 H	61	49.5	4.0
3	*5180.00	119.4 PK			1.55 H	60	115.4	4.0
4	*5180.00	109.2 AV			1.55 H	60	105.2	4.0
5	#10360.00	54.9 PK	74.0	-19.1	1.09 H	19	41.3	13.6
6	#10360.00	42.4 AV	54.0	-11.6	1.09 H	19	28.8	13.6
7	15540.00	46.4 PK	74.0	-27.6	1.07 H	20	33.2	13.2
8	15540.00	34.3 AV	54.0	-19.7	1.07 H	20	21.1	13.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	61.7 PK	74.0	-12.3	1.59 V	348	57.7	4.0
2	5150.00	49.6 AV	54.0	-4.4	1.59 V	348	45.6	4.0
3	*5180.00	119.1 PK			1.59 V	348	115.1	4.0
4	*5180.00	108.9 AV			1.59 V	348	104.9	4.0
5	#10360.00	58.5 PK	74.0	-15.5	1.00 V	360	44.9	13.6
6	#10360.00	46.3 AV	54.0	-7.7	1.00 V	360	32.7	13.6
7	15540.00	46.9 PK	74.0	-27.1	2.21 V	30	33.7	13.2
8	15540.00	34.4 AV	54.0	-19.6	2.21 V	30	21.2	13.2

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.



<b>CHANNEL</b>	TX Channel 40	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.4 PK	74.0	-7.6	1.48 H	66	62.4	4.0
2	5150.00	53.5 AV	54.0	-0.5	1.48 H	66	49.5	4.0
3	*5200.00	121.6 PK			1.48 H	66	117.6	4.0
4	*5200.00	110.7 AV			1.48 H	66	106.7	4.0
5	5350.00	50.1 PK	74.0	-23.9	1.48 H	66	45.7	4.4
6	5350.00	37.4 AV	54.0	-16.6	1.48 H	66	33.0	4.4
7	#10400.00	55.0 PK	74.0	-19.0	1.07 H	32	41.4	13.6
8	#10400.00	42.7 AV	54.0	-11.3	1.07 H	32	29.1	13.6
9	15600.00	46.3 PK	74.0	-27.7	1.11 H	18	32.9	13.4
10	15600.00	34.0 AV	54.0	-20.0	1.11 H	18	20.6	13.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	61.5 PK	74.0	-12.5	1.62 V	343	57.5	4.0
2	5150.00	49.5 AV	54.0	-4.5	1.62 V	343	45.5	4.0
3	*5200.00	120.8 PK			1.62 V	343	116.8	4.0
4	*5200.00	110.2 AV			1.62 V	343	106.2	4.0
5	5350.00	49.8 PK	74.0	-24.2	1.62 V	343	45.4	4.4
6	5350.00	37.2 AV	54.0	-16.8	1.62 V	343	32.8	4.4
7	#10400.00	58.1 PK	74.0	-15.9	1.09 V	360	44.5	13.6
8	#10400.00	45.9 AV	54.0	-8.1	1.09 V	360	32.3	13.6
9	15600.00	47.2 PK	74.0	-26.8	2.14 V	16	33.8	13.4
10	15600.00	34.9 AV	54.0	-19.1	2.14 V	16	21.5	13.4

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 48	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	121.5 PK			1.37 H	63	117.3	4.2
2	*5240.00	110.5 AV			1.37 H	63	106.3	4.2
3	5350.00	52.4 PK	74.0	-21.6	1.37 H	63	48.0	4.4
4	5350.00	38.2 AV	54.0	-15.8	1.37 H	63	33.8	4.4
5	#10480.00	55.0 PK	74.0	-19.0	1.08 H	11	41.3	13.7
6	#10480.00	42.5 AV	54.0	-11.5	1.08 H	11	28.8	13.7
7	15720.00	45.3 PK	74.0	-28.7	1.03 H	19	31.3	14.0
8	15720.00	33.4 AV	54.0	-20.6	1.03 H	19	19.4	14.0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	120.5 PK			1.62 V	336	116.3	4.2
2	*5240.00	110.0 AV			1.62 V	336	105.8	4.2
3	5350.00	51.5 PK	74.0	-22.5	1.62 V	336	47.1	4.4
4	5350.00	37.1 AV	54.0	-16.9	1.62 V	336	32.7	4.4
5	#10480.00	58.4 PK	74.0	-15.6	1.01 V	360	44.7	13.7
6	#10480.00	46.2 AV	54.0	-7.8	1.01 V	360	32.5	13.7
7	15720.00	47.0 PK	74.0	-27.0	2.08 V	30	33.0	14.0
8	15720.00	35.0 AV	54.0	-19.0	2.08 V	30	21.0	14.0

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 149	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5646.56	57.6 PK	68.2	-10.6	2.02 H	25	52.8	4.8
2	*5745.00	123.0 PK			2.02 H	25	118.0	5.0
3	*5745.00	112.6 AV			2.02 H	25	107.6	5.0
4	#5943.98	57.8 PK	68.2	-10.4	2.02 H	25	52.4	5.4
5	11490.00	58.6 PK	74.0	-15.4	1.45 H	351	44.5	14.1
6	11490.00	46.4 AV	54.0	-7.6	1.45 H	351	32.3	14.1
7	#17235.00	53.2 PK	74.0	-20.8	1.70 H	279	34.9	18.3
8	#17235.00	40.9 AV	54.0	-13.1	1.70 H	279	22.6	18.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5650.00	59.9 PK	68.2	-8.3	2.70 V	15	55.2	4.7
2	*5745.00	122.0 PK			2.70 V	15	117.0	5.0
3	*5745.00	119.8 AV			2.70 V	15	114.8	5.0
4	#6007.03	59.1 PK	68.2	-9.1	2.70 V	15	53.4	5.7
5	11490.00	65.4 PK	74.0	-8.6	2.15 V	360	51.3	14.1
6	11490.00	52.3 AV	54.0	-1.7	2.15 V	360	38.2	14.1
7	#17235.00	52.8 PK	74.0	-21.2	2.15 V	19	34.5	18.3
8	#17235.00	40.5 AV	54.0	-13.5	2.15 V	19	22.2	18.3

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 157	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5616.93	57.5 PK	68.2	-10.7	1.98 H	12	52.8	4.7
2	*5785.00	123.4 PK			1.98 H	12	118.4	5.0
3	*5785.00	113.0 AV			1.98 H	12	108.0	5.0
4	#5927.70	57.6 PK	68.2	-10.6	1.98 H	12	52.2	5.4
5	11570.00	58.1 PK	74.0	-15.9	1.46 H	355	44.1	14.0
6	11570.00	46.1 AV	54.0	-7.9	1.46 H	355	32.1	14.0
7	#17355.00	53.3 PK	74.0	-20.7	1.68 H	263	34.4	18.9
8	#17355.00	40.8 AV	54.0	-13.2	1.68 H	263	21.9	18.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5625.30	57.1 PK	68.2	-11.1	2.71 V	8	52.4	4.7
2	*5785.00	122.4 PK			2.71 V	8	117.4	5.0
3	*5785.00	112.1 AV			2.71 V	8	107.1	5.0
4	#6005.87	58.3 PK	68.2	-9.9	2.71 V	8	52.6	5.7
5	11570.00	65.6 PK	74.0	-8.4	2.15 V	360	51.6	14.0
6	11570.00	52.5 AV	54.0	-1.5	2.15 V	360	38.5	14.0
7	#17355.00	53.1 PK	74.0	-20.9	2.13 V	34	34.2	18.9
8	#17355.00	40.6 AV	54.0	-13.4	2.13 V	34	21.7	18.9

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 165	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5644.26	57.8 PK	68.2	-10.4	2.00 H	17	53.0	4.8
2	*5825.00	123.5 PK			2.00 H	17	118.3	5.2
3	*5825.00	113.1 AV			2.00 H	17	107.9	5.2
4	#5948.07	58.6 PK	68.2	-9.6	2.00 H	17	53.2	5.4
5	11650.00	58.1 PK	74.0	-15.9	1.45 H	360	44.0	14.1
6	11650.00	46.0 AV	54.0	-8.0	1.45 H	360	31.9	14.1
7	#17475.00	53.3 PK	74.0	-20.7	1.71 H	273	33.6	19.7
8	#17475.00	41.0 AV	54.0	-13.0	1.71 H	273	21.3	19.7

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5596.11	57.2 PK	68.2	-11.0	2.68 V	9	52.6	4.6
2	*5825.00	122.3 PK			2.68 V	9	117.1	5.2
3	*5825.00	112.1 AV			2.68 V	9	106.9	5.2
4	#5937.87	59.8 PK	68.2	-8.4	2.68 V	9	54.4	5.4
5	11650.00	65.6 PK	74.0	-8.4	2.14 V	360	51.5	14.1
6	11650.00	52.5 AV	54.0	-1.5	2.14 V	360	38.4	14.1
7	#17475.00	52.8 PK	74.0	-21.2	2.13 V	29	33.1	19.7
8	#17475.00	40.3 AV	54.0	-13.7	2.13 V	29	20.6	19.7

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

## 802.11ac (VHT40)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	67.2 PK	74.0	-6.8	1.41 H	65	63.2	4.0
2	5150.00	53.7 AV	54.0	-0.3	1.41 H	65	49.7	4.0
3	*5190.00	111.6 PK			1.41 H	65	107.6	4.0
4	*5190.00	103.1 AV			1.41 H	65	99.1	4.0
5	5350.00	50.3 PK	74.0	-23.7	1.41 H	65	45.9	4.4
6	5350.00	37.8 AV	54.0	-16.2	1.41 H	65	33.4	4.4
7	#10380.00	48.7 PK	74.0	-25.3	1.04 H	12	35.1	13.6
8	#10380.00	36.5 AV	54.0	-17.5	1.04 H	12	22.9	13.6
9	15570.00	46.4 PK	74.0	-27.6	1.10 H	19	33.1	13.3
10	15570.00	34.3 AV	54.0	-19.7	1.10 H	19	21.0	13.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	63.1 PK	74.0	-10.9	1.60 V	349	59.1	4.0
2	5150.00	49.1 AV	54.0	-4.9	1.60 V	349	45.1	4.0
3	*5190.00	111.0 PK			1.60 V	349	107.0	4.0
4	*5190.00	102.6 AV			1.60 V	349	98.6	4.0
5	5350.00	50.1 PK	74.0	-23.9	1.60 V	349	45.7	4.4
6	5350.00	37.6 AV	54.0	-16.4	1.60 V	349	33.2	4.4
7	#10380.00	52.5 PK	74.0	-21.5	1.04 V	355	38.9	13.6
8	#10380.00	40.3 AV	54.0	-13.7	1.04 V	355	26.7	13.6
9	15570.00	46.9 PK	74.0	-27.1	2.25 V	45	33.6	13.3
10	15570.00	34.7 AV	54.0	-19.3	2.25 V	45	21.4	13.3

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 46	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.4 PK	74.0	-7.6	1.45 H	69	62.4	4.0
2	5150.00	53.6 AV	54.0	-0.4	1.45 H	69	49.6	4.0
3	*5230.00	119.3 PK			1.45 H	69	115.1	4.2
4	*5230.00	109.1 AV			1.45 H	69	104.9	4.2
5	5350.00	53.9 PK	74.0	-20.1	1.45 H	69	49.5	4.4
6	5350.00	41.2 AV	54.0	-12.8	1.45 H	69	36.8	4.4
7	#10460.00	52.4 PK	74.0	-21.6	1.05 H	1	38.7	13.7
8	#10460.00	40.1 AV	54.0	-13.9	1.05 H	1	26.4	13.7
9	15690.00	46.4 PK	74.0	-27.6	1.05 H	10	32.4	14.0
10	15690.00	34.6 AV	54.0	-19.4	1.05 H	10	20.6	14.0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	62.2 PK	74.0	-11.8	1.59 V	342	58.2	4.0
2	5150.00	49.2 AV	54.0	-4.8	1.59 V	342	45.2	4.0
3	*5230.00	118.5 PK			1.59 V	342	114.3	4.2
4	*5230.00	108.2 AV			1.59 V	342	104.0	4.2
5	5350.00	50.5 PK	74.0	-23.5	1.59 V	342	46.1	4.4
6	5350.00	37.9 AV	54.0	-16.1	1.59 V	342	33.5	4.4
7	#10460.00	55.6 PK	74.0	-18.4	1.00 V	342	41.9	13.7
8	#10460.00	43.5 AV	54.0	-10.5	1.00 V	342	29.8	13.7
9	15690.00	46.7 PK	74.0	-27.3	2.21 V	18	32.7	14.0
10	15690.00	34.3 AV	54.0	-19.7	2.21 V	18	20.3	14.0

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 151	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5647.91	65.5 PK	68.2	-2.7	2.17 H	3	60.7	4.8
2	*5755.00	122.0 PK			2.17 H	3	117.0	5.0
3	*5755.00	111.6 AV			2.17 H	3	106.6	5.0
4	#5941.28	58.5 PK	68.2	-9.7	2.17 H	3	53.1	5.4
5	11510.00	57.0 PK	74.0	-17.0	1.49 H	354	43.0	14.0
6	11510.00	44.7 AV	54.0	-9.3	1.49 H	354	30.7	14.0
7	#17265.00	53.3 PK	74.0	-20.7	1.65 H	268	34.8	18.5
8	#17265.00	40.9 AV	54.0	-13.1	1.65 H	268	22.4	18.5
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5643.68	63.0 PK	68.2	-5.2	2.92 V	7	58.2	4.8
2	*5755.00	119.1 PK			2.92 V	7	114.1	5.0
3	*5755.00	109.0 AV			2.92 V	7	104.0	5.0
4	#5950.27	58.0 PK	68.2	-10.2	2.92 V	7	52.6	5.4
5	11510.00	62.9 PK	74.0	-11.1	2.11 V	360	48.9	14.0
6	11510.00	50.0 AV	54.0	-4.0	2.11 V	360	36.0	14.0
7	#17265.00	52.8 PK	74.0	-21.2	2.10 V	15	34.3	18.5
8	#17265.00	40.6 AV	54.0	-13.4	2.10 V	15	22.1	18.5

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



<b>CHANNEL</b>	TX Channel 159	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5649.74	65.5 PK	68.2	-2.7	2.16 H	4	60.7	4.8
2	*5795.00	121.7 PK			2.16 H	4	116.6	5.1
3	*5795.00	111.4 AV			2.16 H	4	106.3	5.1
4	#5926.41	67.3 PK	68.2	-0.9	2.16 H	4	61.9	5.4
5	11590.00	57.2 PK	74.0	-16.8	1.41 H	354	43.2	14.0
6	11590.00	44.8 AV	54.0	-9.2	1.41 H	354	30.8	14.0
7	#17385.00	53.0 PK	74.0	-21.0	1.71 H	288	33.9	19.1
8	#17385.00	40.9 AV	54.0	-13.1	1.71 H	288	21.8	19.1

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5644.60	58.7 PK	68.2	-9.5	2.87 V	6	53.9	4.8
2	*5795.00	118.9 PK			2.87 V	6	113.8	5.1
3	*5795.00	108.9 AV			2.87 V	6	103.8	5.1
4	#5936.52	60.7 PK	68.2	-7.5	2.87 V	6	55.3	5.4
5	11590.00	63.2 PK	74.0	-10.8	2.15 V	356	49.2	14.0
6	11590.00	50.3 AV	54.0	-3.7	2.15 V	356	36.3	14.0
7	#17385.00	52.4 PK	74.0	-21.6	2.19 V	11	33.3	19.1
8	#17385.00	40.2 AV	54.0	-13.8	2.19 V	11	21.1	19.1

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

## 802.11ac (VHT80)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	70.2 PK	74.0	-3.8	1.50 H	4	66.2	4.0
2	5150.00	53.9 AV	54.0	-0.1	1.50 H	4	49.9	4.0
3	*5210.00	109.3 PK			1.50 H	4	105.2	4.1
4	*5210.00	100.2 AV			1.50 H	4	96.1	4.1
5	5350.00	53.9 PK	74.0	-20.1	1.50 H	4	49.5	4.4
6	5350.00	42.0 AV	54.0	-12.0	1.50 H	4	37.6	4.4
7	#10420.00	48.8 PK	74.0	-25.2	1.08 H	10	35.2	13.6
8	#10420.00	36.3 AV	54.0	-17.7	1.08 H	10	22.7	13.6
9	15630.00	45.7 PK	74.0	-28.3	1.16 H	16	32.1	13.6
10	15630.00	33.9 AV	54.0	-20.1	1.16 H	16	20.3	13.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	69.8 PK	74.0	-4.2	1.27 V	23	65.8	4.0
2	5150.00	53.5 AV	54.0	-0.5	1.27 V	23	49.5	4.0
3	*5210.00	110.4 PK			1.27 V	23	106.3	4.1
4	*5210.00	101.0 AV			1.27 V	23	96.9	4.1
5	5350.00	54.3 PK	74.0	-19.7	1.27 V	23	49.9	4.4
6	5350.00	42.1 AV	54.0	-11.9	1.27 V	23	37.7	4.4
7	#10420.00	51.1 PK	74.0	-22.9	1.06 V	357	37.5	13.6
8	#10420.00	39.1 AV	54.0	-14.9	1.06 V	357	25.5	13.6
9	15630.00	47.1 PK	74.0	-26.9	2.24 V	49	33.5	13.6
10	15630.00	34.7 AV	54.0	-19.3	2.24 V	49	21.1	13.6

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>CHANNEL</b>	TX Channel 155	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5635.51	64.6 PK	68.2	-3.6	1.00 H	360	59.8	4.8
2	*5775.00	110.7 PK			2.04 H	360	105.7	5.0
3	*5775.00	102.2 AV			2.04 H	360	97.2	5.0
4	#5933.49	60.6 PK	68.2	-7.6	2.04 H	360	55.2	5.4
5	11550.00	52.8 PK	74.0	-21.2	1.00 H	2	38.8	14.0
6	11550.00	41.4 AV	54.0	-12.6	1.00 H	2	27.4	14.0
7	#17325.00	52.8 PK	74.0	-21.2	1.72 H	272	34.2	18.6
8	#17325.00	40.8 AV	54.0	-13.2	1.72 H	272	22.2	18.6

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5642.30	63.3 PK	68.2	-4.9	2.69 V	6	58.5	4.8
2	*5775.00	110.2 PK			2.69 V	6	105.2	5.0
3	*5775.00	102.0 AV			2.69 V	6	97.0	5.0
4	#5934.84	59.2 PK	68.2	-9.0	2.69 V	6	53.8	5.4
5	11550.00	57.4 PK	74.0	-16.6	2.13 V	360	43.4	14.0
6	11550.00	46.2 AV	54.0	-7.8	2.13 V	360	32.2	14.0
7	#17325.00	52.3 PK	74.0	-21.7	2.18 V	3	33.7	18.6
8	#17325.00	39.9 AV	54.0	-14.1	2.18 V	3	21.3	18.6

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11ac (VHT80+80)

CHANNEL	TX Channel 42+155	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	67.2 PK	74.0	-6.8	3.22 H	343	63.2	4.0
2	5150.00	53.9 AV	54.0	-0.1	3.22 H	343	49.9	4.0
3	*5210.00	108.0 PK			3.22 H	343	103.9	4.1
4	*5210.00	98.2 AV			3.22 H	343	94.1	4.1
5	#5648.12	66.7 PK	68.2	-1.5	3.91 H	346	61.9	4.8
6	*5775.00	110.2 PK			3.91 H	346	105.2	5.0
7	*5775.00	101.6 AV			3.91 H	346	96.6	5.0
8	#5989.45	55.8 PK	68.2	-12.4	3.91 H	346	50.2	5.6
9	#10420.00	45.7 PK	74.0	-28.3	1.45 H	214	32.1	13.6
10	#10420.00	33.9 AV	54.0	-20.1	1.45 H	214	20.3	13.6
11	11550.00	51.2 PK	74.0	-22.8	1.60 H	360	37.2	14.0
12	11550.00	38.5 AV	54.0	-15.5	1.60 H	360	24.5	14.0
13	15630.00	44.6 PK	74.0	-29.4	1.73 H	158	31.0	13.6
14	15630.00	33.4 AV	54.0	-20.6	1.73 H	158	19.8	13.6
15	#17325.00	50.2 PK	74.0	-23.8	1.55 H	158	31.6	18.6
16	#17325.00	38.3 AV	54.0	-15.7	1.55 H	158	19.7	18.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	67.0 PK	74.0	-7.0	1.60 V	5	63.0	4.0
2	5150.00	53.7 AV	54.0	-0.3	1.60 V	5	49.7	4.0
3	*5210.00	107.7 PK			1.60 V	5	103.6	4.1
4	*5210.00	98.0 AV			1.60 V	5	93.9	4.1
5	#5646.81	60.7 PK	68.2	-7.5	1.61 V	321	55.9	4.8
6	*5775.00	106.4 PK			1.61 V	321	101.4	5.0
7	*5775.00	97.4 AV			1.61 V	321	92.4	5.0
8	#5931.58	54.3 PK	68.2	-13.9	1.61 V	321	48.9	5.4
9	#10420.00	49.2 PK	74.0	-24.8	1.34 V	358	35.6	13.6
10	#10420.00	37.0 AV	54.0	-17.0	1.34 V	358	23.4	13.6
11	11550.00	51.4 PK	74.0	-22.6	1.51 V	352	37.4	14.0
12	11550.00	39.5 AV	54.0	-14.5	1.51 V	352	25.5	14.0
13	15630.00	45.3 PK	74.0	-28.7	1.54 V	275	31.7	13.6
14	15630.00	33.3 AV	54.0	-20.7	1.54 V	275	19.7	13.6
15	#17325.00	50.0 PK	74.0	-24.0	1.49 V	302	31.4	18.6
16	#17325.00	38.2 AV	54.0	-15.8	1.49 V	302	19.6	18.6

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# Below 1GHz Data:

## 802.11a

<b>CHANNEL</b>	TX Channel 149	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	250.00	39.1 QP	46.0	-6.9	1.00 H	116	48.6	-9.5
2	418.56	38.1 QP	46.0	-7.9	1.00 H	127	42.7	-4.6
3	500.01	37.1 QP	46.0	-8.9	1.50 H	245	39.9	-2.8
4	625.02	38.4 QP	46.0	-7.6	1.50 H	156	38.5	-0.1
5	750.03	36.6 QP	46.0	-9.4	1.00 H	174	34.4	2.2
6	875.02	40.5 QP	46.0	-5.5	1.50 H	226	36.9	3.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	78.91	35.7 QP	40.0	-4.3	1.00 V	21	48.3	-12.6
2	375.00	43.8 QP	46.0	-2.2	1.00 V	51	49.6	-5.8
3	432.62	40.7 QP	46.0	-5.3	1.50 V	180	44.7	-4.0
4	625.02	39.2 QP	46.0	-6.8	1.00 V	236	39.3	-0.1
5	875.02	41.1 QP	46.0	-4.9	1.00 V	163	37.5	3.6
6	1000.00	38.0 QP	54.0	-16.0	1.00 V	300	33.0	5.0

### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2016	Oct. 23, 2017
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 26, 2016	Oct. 25, 2017
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 03, 2017	June 02, 2018
50 ohms Terminator	N/A	EMC-02	Sep. 29, 2016	Sep. 28, 2017
RF Cable	5D-FB	COCCAB-001	Sep. 30, 2016	Sep. 29, 2017
10 dB PAD Mini-Circuits	HAT-10+	CONATT-004	June 18, 2017	June 17, 2018
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 1.
- 3 Tested Date: Aug. 08, 2017

#### 4.2.3 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note: 1.Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Condition

Same as 4.1.6.


#### 4.2.7 Test Results (Mode 1)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	-----------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.08	40.31	29.57	50.39	39.65	66.00	56.00	-15.61	-16.35
2	0.23594	10.08	33.54	25.80	43.62	35.88	62.24	52.24	-18.62	-16.36
3	0.35341	10.11	34.89	32.53	45.00	42.64	58.88	48.88	-13.88	-6.24
4	4.22266	10.39	20.94	12.39	31.33	22.78	56.00	46.00	-24.67	-23.22
5	8.01953	10.64	16.48	9.98	27.12	20.62	60.00	50.00	-32.88	-29.38
6	22.21094	11.61	24.86	19.10	36.47	30.71	60.00	50.00	-23.53	-19.29

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.






Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.07	39.68	28.89	49.75	38.96	66.00	56.00	-16.25	-17.04
2	0.18906	10.05	35.37	22.72	45.42	32.77	64.08	54.08	-18.66	-21.31
3	0.24375	10.06	31.46	21.71	41.52	31.77	61.97	51.97	-20.45	-20.20
4	0.34922	10.10	30.41	25.99	40.51	36.09	58.98	48.98	-18.47	-12.89
5	3.71094	10.26	18.32	10.26	28.58	20.52	56.00	46.00	-27.42	-25.48
6	23.12891	11.28	28.05	23.20	39.33	34.48	60.00	50.00	-20.67	-15.52

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




#### 4.2.8 Test Results (Mode 2)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.22331	10.07	32.07	15.52	42.14	25.59	62.69	52.69	-20.55	-27.10
2	0.34531	10.10	30.17	27.50	40.27	37.60	59.07	49.07	-18.80	-11.47
3	0.46250	10.11	30.10	27.61	40.21	37.72	56.65	46.65	-16.44	-8.93
4	8.16016	10.51	35.37	34.91	45.88	45.42	60.00	50.00	-14.12	-4.58
5	21.66797	11.30	34.99	32.75	46.29	44.05	60.00	50.00	-13.71	-5.95
6	28.76172	11.37	28.05	22.93	39.42	34.30	60.00	50.00	-20.58	-15.70

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.23081	10.04	34.38	31.84	44.42	41.88	62.42	52.42	-18.00	-10.54
2	0.45469	10.10	32.68	27.51	42.78	37.61	56.79	46.79	-14.01	-9.18
3	2.85938	10.20	33.30	18.64	43.50	28.84	56.00	46.00	-12.50	-17.16
4	<b>8.15625</b>	<b>10.45</b>	<b>35.66</b>	<b>35.38</b>	<b>46.11</b>	<b>45.83</b>	<b>60.00</b>	<b>50.00</b>	<b>-13.89</b>	<b>-4.17</b>
5	20.90234	11.00	35.68	33.50	46.68	44.50	60.00	50.00	-13.32	-5.50
6	28.76953	10.96	27.93	22.61	38.89	33.57	60.00	50.00	-21.11	-16.43

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



### 4.3 Transmit Power Measurement

#### 4.3.1 Limits of Transmit Power Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
	√	Indoor Access Point	1 Watt (30 dBm)
		Mobile and Portable client device	250mW (24 dBm)
U-NII-2A			250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C			250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3		√	1 Watt (30 dBm)

\*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;

Array Gain =  $5 \log(N_{ANT}/N_{SS})$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(N_{ANT}/N_{SS})$  dB.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

#### CDD Mode

#### 802.11a

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	17.89	17.72	18.01	18.06	247.888	23.94	29.72	Pass
40	5200	17.87	17.78	18.31	18.33	257.055	24.10	29.72	Pass
48	5240	18.19	18.06	18.43	18.41	268.896	24.30	29.72	Pass
149	5745	23.12	23.42	23.19	23.66	865.625	29.37	29.38	Pass
157	5785	23.40	23.49	23.00	23.42	861.445	29.35	29.38	Pass
165	5825	23.34	23.44	23.08	23.51	864.198	29.37	29.38	Pass

- Note:** 1. For UNII-1: The Max Antenna gain is 6.28dBi > 6dBi, so the power limit shall be reduced to  $30-(6.28-6) = 29.72\text{dBm}$ .  
2. For UNII-3: The Max Antenna gain is 6.62dBi > 6dBi, so the power limit shall be reduced to  $30-(6.62-6) = 29.38\text{dBm}$ .

#### 802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	17.54	17.56	18.23	18.26	247.285	23.93	29.72	Pass
40	5200	18.02	17.85	18.38	18.39	262.23	24.19	29.72	Pass
48	5240	17.80	17.88	18.36	18.61	262.792	24.20	29.72	Pass
149	5745	23.31	23.46	23.12	23.45	862.534	29.36	29.38	Pass
157	5785	23.29	23.16	22.97	23.02	818.918	29.13	29.38	Pass
165	5825	23.31	23.45	23.51	23.07	862.754	29.36	29.38	Pass

- Note:** 1. For UNII-1: The Max Antenna gain is 6.28dBi > 6dBi, so the power limit shall be reduced to  $30-(6.28-6) = 29.72\text{dBm}$ .  
2. For UNII-3: The Max Antenna gain is 6.62dBi > 6dBi, so the power limit shall be reduced to  $30-(6.62-6) = 29.38\text{dBm}$ .

### 802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	16.27	16.06	16.99	16.88	181.485	22.59	29.72	Pass
46	5230	20.61	20.89	21.48	21.76	528.397	27.23	29.72	Pass
151	5755	22.78	23.06	23.27	24.07	859.567	29.34	29.38	Pass
159	5795	22.93	23.14	22.94	23.68	832.534	29.20	29.38	Pass

- Note:** 1. For UNII-1: The Max Antenna gain is 6.28dBi > 6dBi, so the power limit shall be reduced to  $30-(6.28-6) = 29.72\text{dBm}$ .  
2. For UNII-3: The Max Antenna gain is 6.62dBi > 6dBi, so the power limit shall be reduced to  $30-(6.62-6) = 29.38\text{dBm}$ .

### 802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	15.43	15.07	16.32	17.06	160.722	22.06	29.72	Pass
155	5775	18.24	18.33	18.27	18.96	280.606	24.48	29.38	Pass

- Note:** 1. For UNII-1: The Max Antenna gain is 6.28dBi > 6dBi, so the power limit shall be reduced to  $30-(6.28-6) = 29.72\text{dBm}$ .  
2. For UNII-3: The Max Antenna gain is 6.62dBi > 6dBi, so the power limit shall be reduced to  $30-(6.62-6) = 29.38\text{dBm}$ .

### 802.11ac (VHT80+80)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42 +155	5210	19.26	19.66	-	-	176.803	22.47	29.72	Pass
	5775	-	-	18.89	19.40	164.542	22.16	29.38	Pass

- Note:** 1. For UNII-1: The Max Antenna gain is 6.28dBi > 6dBi, so the power limit shall be reduced to  $30-(6.28-6) = 29.72\text{dBm}$ .  
2. For UNII-3: The Max Antenna gain is 6.62dBi > 6dBi, so the power limit shall be reduced to  $30-(6.62-6) = 29.38\text{dBm}$ .

## Beamforming Mode

### 802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	17.54	17.56	18.23	18.26	247.285	23.93	24.45	Pass
40	5200	18.02	17.85	18.38	18.39	262.23	24.19	24.45	Pass
48	5240	17.30	17.28	17.88	18.11	233.249	23.68	24.45	Pass
149	5745	18.27	18.45	18.15	18.34	270.674	24.32	24.34	Pass
157	5785	18.27	18.15	17.99	18.02	258.794	24.13	24.34	Pass
165	5825	18.30	18.43	18.38	18.06	270.109	24.32	24.34	Pass

**Note:** 1. For UNII-1: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.55 - 6) = 24.45\text{dBm}$ .  
 2. For UNII-3: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.66 - 6) = 24.34\text{dBm}$ .

### 802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	16.25	15.26	16.97	16.98	175.406	22.44	24.45	Pass
46	5230	17.68	17.58	17.88	17.98	240.076	23.80	24.45	Pass
151	5755	17.96	18.09	18.25	18.88	271.036	24.33	24.34	Pass
159	5795	17.91	18.15	17.95	18.67	263.109	24.20	24.34	Pass

**Note:** 1. For UNII-1: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.55 - 6) = 24.45\text{dBm}$ .  
 2. For UNII-3: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.66 - 6) = 24.34\text{dBm}$ .

### 802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	14.46	14.21	14.88	14.87	115.739	20.63	24.45	Pass
155	5775	17.44	17.34	17.26	17.85	223.828	23.50	24.34	Pass

**Note:** 1. For UNII-1: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.55 - 6) = 24.45\text{dBm}$ .  
 2. For UNII-3: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.66 - 6) = 24.34\text{dBm}$ .

### 802.11ac (VHT80+80)


Chan.	Chan. Freq. (MHz)	Maximum Conducted Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42+155	5210	19.26	19.66	-	-	176.803	22.47	27.82	Pass
	5775	-	-	18.89	19.40	164.542	22.16	27.17	Pass

**Note:** 1. For UNII-1: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 8.18\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (8.18 - 6) = 27.82\text{dBm}$ .  
 2. For UNII-3: Directional gain =  $10 \log[(10^{G3/20} + 10^{G4/20})^2 / 2] = 8.83\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (8.83 - 6) = 27.17\text{dBm}$ .



## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Setup



### 4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to SAMPLE. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 4.4.4 Test Results

##### 802.11a

Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
36	5180	16.44	16.56	16.56	16.56
40	5200	16.56	16.56	16.56	16.56
48	5240	16.56	16.56	16.56	16.56
149	5745	20.64	18.48	18.96	24.60
157	5785	22.20	23.04	19.20	25.92
165	5825	23.76	22.20	17.40	25.80

##### 802.11ac (VHT20)

Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
36	5180	17.64	17.76	17.76	17.76
40	5200	17.76	17.76	17.64	17.76
48	5240	17.64	17.64	17.64	17.76
149	5745	19.56	18.60	18.60	24.48
157	5785	21.48	22.08	18.48	20.76
165	5825	22.44	21.12	18.24	25.92

##### 802.11ac (VHT40)

Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
38	5190	36.48	36.48	36.48	36.48
46	5230	36.24	36.48	36.48	36.72
151	5755	38.16	43.92	39.84	54.24
159	5795	42.48	52.80	40.08	43.68

##### 802.11ac (VHT80)


Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
42	5210	75.84	75.84	75.84	75.84
155	5775	76.32	75.84	76.32	76.32

##### 802.11ac (VHT80+80)


Channel	Channel Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
42+155	5210	75.84	76.32	-	-
	5775	-	-	76.32	75.84

### Spectrum Plot of Worst Value


#### 802.11a / Chain 3 : CH157




#### 802.11ac (VHT20) / Chain 3 : CH165




#### 802.11ac (VHT40) / Chain 3: CH151



#### 802.11ac (VHT80) / Chain 0 : CH155




#### 802.11ac (VHT80+80) / Chain 1: CH42




## Spectrum Plot for near by DFS band (DFS is required, if 99% OCP straddle into U-NII-2A band)


**802.11a / Chain 0 : CH48**




**802.11a / Chain 1 : CH48**




**802.11a / Chain 2 : CH48**




**802.11a / Chain 3 : CH48**




**802.11ac (VHT20) / Chain 0 : CH48**




**802.11ac (VHT20) / Chain 1 : CH48**



**802.11ac (VHT20) / Chain 2 : CH48**




**802.11ac (VHT20) / Chain 3 : CH48**




## Spectrum Plot for near by DFS band (DFS is required, if 99% OCP straddle into U-NII-2A band)


**802.11ac (VHT40) / Chain 0 : CH46**




**802.11ac (VHT40) / Chain 1 : CH46**




**802.11ac (VHT40) / Chain 2 : CH46**




**802.11ac (VHT40) / Chain 3 : CH46**




**802.11ac (VHT80) / Chain 0 : CH42**




**802.11ac (VHT80) / Chain 1 : CH42**




**802.11ac (VHT80) / Chain 2 : CH42**




**802.11ac (VHT80) / Chain 3 : CH42**






## Spectrum Plot for near by DFS band (DFS is required, if 99% OCP straddle into U-NII-2C band)


**802.11a / Chain 0 : CH149**




**802.11a / Chain 1 : CH149**




**802.11a / Chain 2 : CH149**




**802.11a / Chain 3 : CH149**




**802.11ac (VHT20) / Chain 0 : CH149**




**802.11ac (VHT20) / Chain 1 : CH149**



**802.11ac (VHT20) / Chain 2 : CH149**




**802.11ac (VHT20) / Chain 3 : CH149**




## Spectrum Plot for near by DFS band (DFS is required, if 99% OCP straddle into U-NII-2C band)


**802.11ac (VHT40) / Chain 0 : CH151**




**802.11ac (VHT40) / Chain 1 : CH151**




**802.11ac (VHT40) / Chain 2 : CH151**




**802.11ac (VHT40) / Chain 3 : CH151**




**802.11ac (VHT80) / Chain 0 : CH155**




**802.11ac (VHT80) / Chain 1 : CH155**




**802.11ac (VHT80) / Chain 2 : CH155**



**802.11ac (VHT80) / Chain 3 : CH155**







## 4.5 Peak Power Spectral Density Measurement

### 4.5.1 Limits of Peak Power Spectral Density Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
	√	Indoor Access Point	
		Mobile and Portable client device	11dBm/ MHz
U-NII-2A			11dBm/ MHz
U-NII-2C			11dBm/ MHz
U-NII-3	√		30dBm/ 500kHz

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.5.4 Test Procedure

##### **802.11ac (VHT20)**

###### **For U-NII-1:**

Using method SA-1

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW  $\geq$  3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value

###### **For U-NII-3:**

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 300 kHz, Set VBW  $\geq$  1 MHz, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(500 \text{ kHz}/300\text{kHz})$
5. Sweep time = auto, trigger set to "free run".
6. Trace average at least 100 traces in power averaging mode.
7. Record the max value

##### **802.11a, 802.11ac (VHT40), 802.11ac (VHT80)**

###### **For U-NII-1:**

Using method SA-2

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW  $\geq$  3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value and add  $10 \log (1/\text{duty cycle})$

###### **For U-NII-3:**

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 300 kHz, Set VBW  $\geq$  1 MHz, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $BWCF = 10\log(500 \text{ kHz}/300\text{kHz})$
5. Sweep time = auto, trigger set to "free run".
6. Trace average at least 100 traces in power averaging mode.
7. Record the max value and add  $10 \log (1/\text{duty cycle})$

#### 4.5.5 Deviation from Test Standard

No deviation.

#### 4.5.6 EUT Operating Condition

Same as Item 4.3.6.

#### 4.5.7 Test Results

##### For U-NII-1:

##### 802.11a

Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor (dBm)				Duty Factor (dB)	Total PSD With Duty Factor (dBm)	MAX. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
36	5180	4.85	4.85	4.70	4.32	0.15	10.85	11.45	Pass
40	5200	4.46	4.98	4.93	5.07	0.15	11.03	11.45	Pass
48	5240	5.21	4.84	4.79	4.96	0.15	11.12	11.45	Pass

- Note:** 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17 - (11.55 - 6) = 11.45\text{dBm}$ .
3. Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/MHz)				Total Power Density (dBm/MHz)	MAX. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3			
36	5180	4.83	4.57	5.40	4.77	10.92	11.45	Pass
40	5200	4.71	4.76	5.65	5.07	11.08	11.45	Pass
48	5240	4.82	5.16	5.74	5.19	11.26	11.45	Pass

- Note:** 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17 - (11.55 - 6) = 11.45\text{dBm}$ .

##### 802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor (dBm)				Duty Factor (dB)	Total PSD With Duty Factor (dBm)	MAX. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
38	5190	-0.55	-0.93	0.33	0.36	0.14	6.00	11.45	Pass
46	5230	3.94	4.28	4.98	5.34	0.14	10.83	11.45	Pass

- Note:** 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17 - (11.55 - 6) = 11.45\text{dBm}$ .
3. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor (dBm)				Duty Factor (dB)	Total PSD With Duty Factor (dBm)	MAX. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42	5210	-4.08	-4.51	-3.89	-2.21	0.25	2.69	11.45	Pass

- Note:**
1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
  2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.55\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(11.55-6) = 11.45\text{dBm}$ .
  3. Refer to section 3.3 for duty cycle spectrum plot.


### 802.11ac (VHT80+80)

Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor (dBm)				Duty Factor (dB)	Total Power Density (dBm/MHz)	MAX. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
42+ 155	5210	-0.72	-0.12	-	-	0.25	2.85	14.82	Pass
	5775	Test results refer to U_NII-3 data							


- Note:**
1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
  2. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 8.18\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(8.18-6) = 14.82\text{dBm}$ .
  3. Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value


**802.11a / Chain 0 : CH48**




**802.11ac (VHT20) / Chain 2 : CH48**




**802.11ac (VHT40) / Chain 3: CH46**



**802.11ac (VHT80) / Chain 3 : CH42**



**802.11ac (VHT80+80) / Chain 1: CH42**



### For U-NII-3:

#### 802.11a

TX chain	Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor		10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass /Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	149	5745	1.67	3.89	6.02	0.15	10.06	24.34	Pass
	157	5785	1.67	3.89	6.02	0.15	10.06	24.34	Pass
	165	5825	1.76	3.98	6.02	0.15	10.15	24.34	Pass
1	149	5745	1.87	4.09	6.02	0.15	10.26	24.34	Pass
	157	5785	1.91	4.13	6.02	0.15	10.30	24.34	Pass
	165	5825	2.00	4.22	6.02	0.15	10.39	24.34	Pass
2	149	5745	2.26	4.48	6.02	0.15	10.65	24.34	Pass
	157	5785	1.82	4.04	6.02	0.15	10.21	24.34	Pass
	165	5825	1.07	3.29	6.02	0.15	9.46	24.34	Pass
3	149	5745	2.21	4.43	6.02	0.15	10.60	24.34	Pass
	157	5785	2.12	4.34	6.02	0.15	10.51	24.34	Pass
	165	5825	1.77	3.99	6.02	0.15	10.16	24.34	Pass

Note: 1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.66 - 6) = 24.34\text{dBm}$ .

2. Refer to section 3.3 for duty cycle spectrum plot.

## 802.11ac (VHT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm/300kHz)	PSD (dBm/500kHz)	10 log (N=4) dB	Total PSD (dBm/500kHz)	Limit (dBm/500kHz)	Pass /Fail
0	149	5745	1.39	3.61	6.02	9.63	24.34	Pass
	157	5785	1.40	3.62	6.02	9.64	24.34	Pass
	165	5825	1.37	3.59	6.02	9.61	24.34	Pass
1	149	5745	1.72	3.94	6.02	9.96	24.34	Pass
	157	5785	1.89	4.11	6.02	10.13	24.34	Pass
	165	5825	1.50	3.72	6.02	9.74	24.34	Pass
2	149	5745	1.84	4.06	6.02	10.08	24.34	Pass
	157	5785	1.36	3.58	6.02	9.60	24.34	Pass
	165	5825	1.03	3.25	6.02	9.27	24.34	Pass
3	149	5745	2.03	4.25	6.02	10.27	24.34	Pass
	157	5785	1.33	3.55	6.02	9.57	24.34	Pass
	165	5825	1.91	4.13	6.02	10.15	24.34	Pass

Note: 1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.66 - 6) = 24.34\text{dBm}$ .



### 802.11ac (VHT40)

TX chain	Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor		10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass /Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	151	5755	-2.27	-0.05	6.02	0.14	6.11	24.34	Pass
	159	5795	-2.01	0.21	6.02	0.14	6.37	24.34	Pass
1	151	5755	-1.49	0.73	6.02	0.14	6.89	24.34	Pass
	159	5795	-1.60	0.62	6.02	0.14	6.78	24.34	Pass
2	151	5755	-1.83	0.39	6.02	0.14	6.55	24.34	Pass
	159	5795	-2.20	0.02	6.02	0.14	6.18	24.34	Pass
3	151	5755	-1.47	0.75	6.02	0.14	6.91	24.34	Pass
	159	5795	-2.20	0.02	6.02	0.14	6.18	24.34	Pass

Note: 1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30-(11.66-6) = 24.34\text{dBm}$ .

2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11ac (VHT80)

TX chain	Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor		10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass /Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	155	5775	-10.47	-8.25	6.02	0.25	-1.98	24.34	Pass
1	155	5775	-10.53	-8.31	6.02	0.25	-2.04	24.34	Pass
2	155	5775	-10.40	-8.18	6.02	0.25	-1.91	24.34	Pass
3	155	5775	-9.53	-7.31	6.02	0.25	-1.04	24.34	Pass

Note: 1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2 / 4] = 11.66\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30-(11.66-6) = 24.34\text{dBm}$ .

2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11ac (VHT80+80)


TX chain	Chan.	Chan. Freq. (MHz)	PSD W/O Duty Factor		10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass /Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	42	5210	Test results refer to U_NII-1 data						
1	42	5210	Test results refer to U_NII-1 data						
2	155	5775	-9.68	-7.46	3.01	0.25	-4.20	27.17	Pass
3	155	5775	-9.14	-6.92	3.01	0.25	-3.66	27.17	Pass

Note: 1. Directional gain =  $10 \log[(10^{G3/20} + 10^{G4/20})^2 / 2] = 8.83\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30-(8.83-6) = 27.17\text{dBm}$ .


2. Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value


**802.11a / Chain 2 : CH149**




**802.11ac (VHT20) / Chain 3 : CH149**




**802.11ac (VHT40) / Chain 3: CH151**



**802.11ac (VHT80) / Chain 3 : CH155**



**802.11ac (VHT80+80) / Chain 3: CH155**




## 4.6 Frequency Stability Measurement

### 4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

#### 4.6.7 Test Results

Frequency Stability Versus Temp.									
Operating Frequency: 5180 MHz									
TEMP. (°C)	Power Supply (Vac)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail
50	120	5180.0158	PASS	5180.0202	PASS	5180.0156	PASS	5180.0174	PASS
40	120	5179.9854	PASS	5179.988	PASS	5179.9846	PASS	5179.9862	PASS
30	120	5180.0154	PASS	5180.0151	PASS	5180.014	PASS	5180.0142	PASS
20	120	5179.9917	PASS	5179.9925	PASS	5179.9927	PASS	5179.9916	PASS
10	120	5180.0226	PASS	5180.025	PASS	5180.024	PASS	5180.0221	PASS
0	120	5180.0231	PASS	5180.0256	PASS	5180.0248	PASS	5180.0229	PASS
-10	120	5180.0191	PASS	5180.0188	PASS	5180.0145	PASS	5180.018	PASS
-20	120	5180.0087	PASS	5180.0041	PASS	5180.0085	PASS	5180.005	PASS
-30	120	5179.9838	PASS	5179.9874	PASS	5179.988	PASS	5179.9869	PASS


Frequency Stability Versus Voltage									
Operating Frequency: 5180 MHz									
TEMP. (°C)	Power Supply (Vac)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail
20	138	5179.9924	PASS	5179.9932	PASS	5179.9925	PASS	5179.9913	PASS
	120	5179.9917	PASS	5179.9925	PASS	5179.9927	PASS	5179.9916	PASS
	102	5179.9909	PASS	5179.9932	PASS	5179.9922	PASS	5179.9921	PASS

## 4.7 6dB Bandwidth Measurement

### 4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

### 4.7.2 Test Setup



### 4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.7.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.7.5 Deviation from Test Standard

No deviation.

### 4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.7.7 Test Results

##### 802.11a

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
149	5745	16.36	16.38	16.33	16.36	0.5	PASS
157	5785	16.38	16.35	16.37	16.37	0.5	PASS
165	5825	16.34	16.35	16.37	16.35	0.5	PASS

##### 802.11ac (VHT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
149	5745	17.65	17.36	17.62	17.63	0.5	PASS
157	5785	17.63	17.37	17.61	17.61	0.5	PASS
165	5825	17.61	17.59	17.23	17.24	0.5	PASS

##### 802.11ac (VHT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
151	5755	36.42	35.96	35.74	35.76	0.5	PASS
159	5795	35.82	35.83	35.86	35.80	0.5	PASS

##### 802.11ac (VHT80)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
155	5775	76.12	76.46	76.46	76.42	0.5	PASS

##### 802.11ac (VHT80+80)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
42+155	5210	-					
	5775	-	-	76.51	76.51	0.5	PASS

## Spectrum Plot of Worst Value


**802.11a\_Chain 2 / CH149**




**802.11ac (VHT20)\_Chain 2 / CH165**




**802.11ac (VHT40)\_Chain 2 / CH151**



**802.11ac (VHT80)\_Chain 0 / CH155**



**802.11ac (VHT80+80)\_Chain 2 / CH155**





## 5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

## Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)


802.11a

CH 149 5745 MHz

Horizontal




Vertical




CH 157 5785 MHz

Horizontal




Vertical




CH 165 5825 MHz

Horizontal




Vertical




## 802.11ac (VHT20)

### CH 149 5745 MHz

#### Horizontal




#### Vertical




### CH 157 5785 MHz

#### Horizontal




#### Vertical




### CH 165 5825 MHz

#### Horizontal




#### Vertical




# 802.11ac (VHT40)

CH 151 5755 MHz

Horizontal




Vertical




CH 159 5795 MHz

Horizontal




Vertical




## 802.11ac (VHT80)

CH 155 5775 MHz

Horizontal




Vertical




## 802.11ac (VHT80+80)

CH 42+155 5210+5775 MHz

Horizontal



Vertical



## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---