



FCC PART 15.247 TEST REPORT

For

Grandstream Networks, Inc.

126 Brookline Ave, 3rd Floor Boston, MA 02215, USA

FCC ID: YZZGXV3275V3

Report Type: Product Type:

Original Report IP Multimedia Phone

Report Number: RSZ170927003-00B

Report Date: 2018-01-08

Candy Li

Reviewed By: RF Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

Candy, Li

Shenzhen, Guangdong, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
Measurement Uncertainty Test Facility	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT EXERCISE SOFTWARE	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL I/O CABLE	
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
APPLICABLE STANDARD	
Result	
FCC §15.203 – ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
Test Procedure	
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST RESULTS SUMMARY	
Test Data	
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	27
APPLICABLE STANDARD	27
TEST PROCEDURE	
Test Data	27

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH	34
APPLICABLE STANDARD	34
TEST PROCEDURE	
Test Data	34
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	40
APPLICABLE STANDARD	40
TEST PROCEDURE	
Test Data	
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	43
APPLICABLE STANDARD	43
TEST PROCEDURE	
Test Data	
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	59
APPLICABLE STANDARD	
TEST PROCEDURE	
Test Data	
FCC §15.247(d) - BAND EDGES TESTING	61
APPLICABLE STANDARD	61
TEST PROCEDURE	
TEST DATA	61

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Grandstream Networks, Inc.* 's product, model number: GXV3275 (FCC ID: YZZGXV3275V3) in this report was an *IP Multimedia Phone*, which was measured approximately: 25.2 cm (L) \times 21.1 cm (W) \times 8.4 cm (H), rated with input voltage: DC 12V from adapter or DC 48 V powered by POE supply.

Report No.: RSZ170927003-00B

Adapter 1 Information:

Model: F18W8-120150SPAUY Input: AC 100-240V, 50/60Hz, 0.6A

Output: DC 12V, 1.5 A

Adapter 2 Information: Model: H18US1200150A

Input: AC 100-240V, 50/60Hz, 0.8A

Output: DC 12V, 1.5 A

Objective

This test report is prepared on behalf of *Grandstream Networks, Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS and Part 15B JBP submissions with FCC ID: YZZGXV3275V3.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 67

^{*}All measurement and test data in this report was gathered from production sample serial number: 1702164 (Assigned by BACL, shenzhen). The EUT supplied by the applicant was received on 2017-09-27.

Measurement Uncertainty

Parameter	uncertainty
Occupied Channel Bandwidth	±5%
RF Output Power with Power meter	±0.5dB
RF conducted test with spectrum	±1.5dB
AC Power Lines Conducted Emissions	±1.95dB
All emissions, radiated	±4.88dB
Temperature	±3°C
Humidity	±6%
Supply voltages	±0.4%

Report No.: RSZ170927003-00B

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS (Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP (Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15.247 Page 5 of 67

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

Software "RF test tool" was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A	N/A	N/A	N/A

Report No.: RSZ170927003-00B


External I/O Cable

Cable Description	Length (m)	From Port	То
Un-Shielding Un-detachable DC Cable	2.5	EUT	Adapter

FCC Part 15.247 Page 6 of 67

Block Diagram of Test Setup

For conducted emission: (Adapter)



FCC Part 15.247 Page 7 of 67

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1307 (b) (1) & §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
\$15.205, \$15.209 & \$15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

Report No.: RSZ170927003-00B

FCC Part 15.247 Page 8 of 67

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date		
Conducted Emissions Test							
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04		
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2016-12-07	2017-12-07		
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-05-21	2017-11-19		
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR		
N/A	Conducted Emission Cable	N/A	UF A210B-1- 0720-504504	2017-05-12	2017-11-12		
	Radia	ated Emission T	`est				
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28		
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24		
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21		
HP	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19		
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2014-12-17	2017-12-16		
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07		
Ducommun technologies	RF Cable	UFA210A-1- 4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19		
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19		
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19		
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22		
Ducommun Technologies	Horn Antenna	ARH-4223- 02	1007726-04	2014-12-29	2017-12-28		
Ducommun Technologies	Pre-amplifier	ALN- 22093530-01	991373-01	2017-08-03	2018-08-03		
	RF	Conducted Tes	t				
Agilent	P-Series Power Meter	N1912A	MY5000448	2016-12-05	2017-12-05		
Agilent	Wideband Power Sensor	N1921A	MY54210016	2016-12-05	2017-12-05		
WEINSCHEL	3 dB Attenuator	N/A	N/A	2017-05-21	2017-11-19		
WEINSCHEL	3 dB Attenuator	N/A	N/A	2017-11-19	2018-05-21		
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2016-12-05	2017-12-05		
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03 -101746-zn	2017-08-17	2018-08-17		
Ducommun technologies	RF Cable	RG-214	3	2017-05-22	2017-11-22		

Report No.: RSZ170927003-00B

FCC Part 15.247 Page 9 of 67

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Report No.: RSZ170927003-00B

Limits for General Population/Uncontrolled Exposure					
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)	
0.3-1.34	614	1.63	*(100)	30	
1.34-30	824/f	2.19/f	$*(180/f^2)$	30	
30-300	27.5	0.073	0.2	30	
300-1500	/	/	f/1500	30	
1500-100,000	/	/	1.0	30	

f = frequency in MHz

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency	Antenna Gain		Conducted Power		Evaluation	Power	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	Distance (cm)	Density (mW/cm ²)	(mW/cm^2)
2402-2480	2	1.58	8.0	6.31	20	0.002	1

Note: The conducted power is the tune-up power of the Max Conducted Output Power

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

FCC Part 15.247 Page 10 of 67

^{* =} Plane-wave equivalent power density

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RSZ170927003-00B

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 11 of 67

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Report No.: RSZ170927003-00B

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.247 Page 12 of 67

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RSZ170927003-00B

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Simon Wang on 2017-10-09.

EUT operation mode: Transmitting

FCC Part 15.247 Page 13 of 67

Powered by Adapter 1

AC 120V/60 Hz, Line




Report No.: RSZ170927003-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.150000	43.5	20.2	66.0	22.5	QP
0.286500	43.5	20.2	60.6	17.1	QP
0.289500	43.1	20.2	60.5	17.4	QP
1.010850	32.4	20.1	56.0	23.6	QP
1.050250	35.3	20.1	56.0	20.7	QP
1.125110	36.6	20.1	56.0	19.4	QP
0.150000	33.8	20.2	56.0	22.2	Ave.
0.286500	36.7	20.2	50.6	13.9	Ave.
0.289500	37.8	20.2	50.5	12.7	Ave.
1.010850	26.4	20.1	46.0	19.6	Ave.
1.050250	28.5	20.1	46.0	17.5	Ave.
1.125110	30.3	20.1	46.0	15.7	Ave.

FCC Part 15.247 Page 14 of 67

AC 120V/60 Hz, Neutral




Report No.: RSZ170927003-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.297470	39.1	20.2	60.3	21.2	QP
0.340930	38.4	20.2	59.2	20.8	QP
0.888710	31.7	20.1	56.0	24.3	QP
0.943930	35.3	20.1	56.0	20.7	QP
1.086050	36.9	20.1	56.0	19.1	QP
1.204150	38.3	20.1	56.0	17.7	QP
0.297470	29.1	20.2	50.3	21.2	Ave.
0.340930	27.0	20.2	49.2	22.2	Ave.
0.888710	23.9	20.1	46.0	22.1	Ave.
0.943930	28.2	20.1	46.0	17.8	Ave.
1.086050	29.7	20.1	46.0	16.3	Ave.
1.204150	29.2	20.1	46.0	16.8	Ave.

FCC Part 15.247 Page 15 of 67

Powered by Adapter 2

AC 120V/60 Hz, Line




Report No.: RSZ170927003-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.380270	44.4	20.2	58.3	13.9	QP
0.419610	44.5	20.2	57.5	13.0	QP
0.439370	45.1	20.2	57.1	12.0	QP
0.691650	39.0	20.0	56.0	17.0	QP
0.971630	40.4	20.1	56.0	15.6	QP
1.160330	39.5	20.1	56.0	16.5	QP
0.380270	33.6	20.2	48.3	14.7	Ave.
0.419610	36.2	20.2	47.5	11.3	Ave.
0.439370	36.0	20.2	47.1	11.1	Ave.
0.691650	31.5	20.0	46.0	14.5	Ave.
0.971630	33.0	20.1	46.0	13.0	Ave.
1.160330	33.9	20.1	46.0	12.1	Ave.

FCC Part 15.247 Page 16 of 67

AC 120V/60 Hz, Neutral




Report No.: RSZ170927003-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.407850	45.4	20.2	57.7	12.3	QP
0.459010	44.6	20.2	56.7	12.1	QP
0.829550	41.8	20.0	56.0	14.2	QP
0.967330	44.8	20.1	56.0	11.2	QP
1.046250	42.1	20.1	56.0	13.9	QP
1.152690	42.5	20.1	56.0	13.5	QP
0.407850	38.1	20.2	47.7	9.6	Ave.
0.459010	35.5	20.2	46.7	11.2	Ave.
0.829550	32.1	20.0	46.0	13.9	Ave.
0.967330	36.1	20.1	46.0	9.9	Ave.
1.046250	36.0	20.1	46.0	10.0	Ave.
1.152690	36.1	20.1	46.0	9.9	Ave.

FCC Part 15.247 Page 17 of 67

Powered by POE

AC 120V/60 Hz, Line




Report No.: RSZ170927003-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.154000	52.4	20.2	65.8	13.4	QP
0.181500	46.4	20.2	64.4	18.0	QP
0.352690	40.8	20.2	58.9	18.1	QP
0.435550	35.3	20.2	57.1	21.8	QP
0.439490	34.2	20.2	57.1	22.9	QP
0.987210	41.8	20.1	56.0	14.2	QP
0.154000	36.7	20.2	55.8	19.1	Ave.
0.181500	20.0	20.2	54.4	34.4	Ave.
0.352690	28.8	20.2	48.9	20.1	Ave.
0.435550	22.4	20.2	47.1	24.7	Ave.
0.439490	21.7	20.2	47.1	25.4	Ave.
0.987210	33.6	20.1	46.0	12.4	Ave.

FCC Part 15.247 Page 18 of 67

AC 120V/60 Hz, Neutral



Report No.: RSZ170927003-00B

Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.205000	48.2	20.2	63.4	15.2	QP
0.205500	48.9	20.2	63.4	14.5	QP
0.352690	41.4	20.2	58.9	17.5	QP
0.411850	40.0	20.2	57.6	17.6	QP
0.948010	41.1	20.1	56.0	14.9	QP
1.022790	40.2	20.1	56.0	15.8	QP
0.205000	37.1	20.2	53.4	16.3	Ave.
0.205500	37.0	20.2	53.4	16.4	Ave.
0.352690	29.6	20.2	48.9	19.3	Ave.
0.411850	29.0	20.2	47.6	18.6	Ave.
0.948010	33.4	20.1	46.0	12.6	Ave.
1.022790	33.8	20.1	46.0	12.2	Ave.

Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
 3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 19 of 67

Report No.: RSZ170927003-00B

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

FCC Part 15.247 Page 20 of 67

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	Frequency Range RBW		IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	PK

Report No.: RSZ170927003-00B

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 21 of 67

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \le L_{\rm lim} + U_{\rm cispr}$$

Report No.: RSZ170927003-00B

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2017-10-12. EUT operation mode: Transmitting

30 MHz~1 GHz: (BDR Mode, Low channel)



FCC Part 15.247 Page 22 of 67

Report No.: RSZ170927003-00B

1 GHz - 25 GHz: (Scan with GFSK, π/4-DQPSK, 8-DPSK mode, the worst case was GFSK mode)

Frequency	Ro	eceiver	Turntable		itenna		Corrected	15.247	C Part 7/205/209
(MHz)	Reading (dBµV)	PK/QP/Ave.	Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	annel (2	2402 M	Hz)			
2402.00	65.47	PK	15	2.3	Н	33.92	99.39	/	/
2402.00	54.08	Ave.	15	2.3	Н	33.92	88.00	/	/
2402.00	59.09	PK	255	2.4	V	33.92	93.01	/	/
2402.00	47.67	Ave.	255	2.4	V	33.92	81.59	/	/
2322.50	28.10	PK	282	1.7	Н	33.83	61.93	74	12.07
2322.50	13.71	Ave.	282	1.7	Н	33.83	47.54	54	6.46
2383.90	27.28	PK	158	1.4	Н	33.92	61.20	74	12.80
2383.90	13.69	Ave.	158	1.4	Н	33.92	47.61	54	6.39
2493.78	27.32	PK	166	1.8	Н	34.08	61.40	74	12.60
2493.78	13.23	Ave.	166	1.8	Н	34.08	47.31	54	6.69
4804.00	56.91	PK	14	1.8	Н	5.84	62.75	74	11.25
4804.00	36.78	Ave.	14	1.8	Н	5.84	42.62	54	11.38

FCC Part 15.247 Page 23 of 67

Frequency	Re	eceiver	Turntable	Rx An	itenna		Corrected	15.247	C Part /205/209
(MHz)	Reading (dBµV)	PK/QP/Ave.	Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBµV/m)		Margin (dB)
			Middle C	hannel	(2441 N	/IHz)			
2441.00	65.65	PK	139	1.1	Н	33.92	99.57	/	/
2441.00	55.11	Ave.	139	1.1	Н	33.92	89.03	/	/
2441.00	58.88	PK	95	2.1	V	33.92	92.80	/	/
2441.00	47.54	Ave.	95	2.1	V	33.92	81.46	/	/
2368.67	27.81	PK	330	1.9	Н	33.92	61.73	74	12.27
2368.67	13.68	Ave.	330	1.9	Н	33.92	47.60	54	6.40
2343.18	27.28	PK	170	1.8	Н	33.83	61.11	74	12.89
2343.18	13.69	Ave.	170	1.8	Н	33.83	47.52	54	6.48
2496.19	27.62	PK	79	1.1	Н	34.08	61.70	74	12.30
2496.19	13.25	Ave.	79	1.1	Н	34.08	47.33	54	6.67
4882.00	54.41	PK	241	1.7	Н	6.21	60.62	74	13.38
4882.00	35.86	Ave.	241	1.7	Н	6.21	42.07	54	11.93
	_		High Cl	annel (2	2480 M	Hz)			
2480.00	66.23	PK	36	1.9	Н	34.08	100.31	/	/
2480.00	55.64	Ave.	36	1.9	Н	34.08	89.72	/	/
2480.00	58.93	PK	63	1.4	V	34.08	93.01	/	/
2480.00	47.61	Ave.	63	1.4	V	34.08	81.69	/	/
2331.00	27.24	PK	299	1.7	Н	33.83	61.07	74	12.93
2331.00	13.70	Ave.	299	1.7	Н	33.83	47.53	54	6.47
2483.56	38.01	PK	9	1.4	Н	34.08	72.09	74	1.91
2483.56	14.65	Ave.	9	1.4	Н	34.08	48.73	54	5.27
2486.28	33.88	PK	201	2.1	Н	34.08	67.96	74	6.04
2486.28	14.57	Ave.	201	2.1	Н	34.08	48.65	54	5.35
4960.00	45.08	PK	258	2.1	Н	7.82	52.90	74	21.10
4960.00	30.53	Ave.	258	2.1	Н	7.82	38.35	54	15.65

Report No.: RSZ170927003-00B

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.


FCC Part 15.247 Page 24 of 67

Pre-scan with Low channel Horizontal

Report No.: RSZ170927003-00B



Date: 12.0CT.2017 9:44:00




Date. 12.001.2011 10.31.34


FCC Part 15.247 Page 25 of 67

Vertical

Report No.: RSZ170927003-00B



Date: 12.0CT.2017 9:34:57



12.001.2011 10.25.22

FCC Part 15.247 Page 26 of 67

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ170927003-00B

Test Procedure

- Set the EUT in transmitting mode, maxhold the channel. Set the adjacent channel of the EUT and maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2017-10-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

FCC Part 15.247 Page 27 of 67


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
	Low	2402	1.003	0.697	Pass
	Adjacent	2403	1.003	0.097	Pass
BDR	Middle	2441	1.002	0.702	Daga
(GFSK)	Adjacent	2442	1.003	0.702	Pass
	High	2480	1.002	0.600	D
	Adjacent	2479	1.003	0.699	Pass
	Low	2402	1.003	0.897 0.900 0.901	Pass
	Adjacent	2403			Pass
EDR	Middle	2441	0.999		Pass
(π/4-DQPSK)	Adjacent	2442	0.999		Pass
	High	2480	0.999		Pass
	Adjacent	2479	0.999		Pass
	Low	2402	1 002	0.965	Daga
	Adjacent	2403	1.003	0.865	Pass
EDR	Middle	2441	0.999	0.865	Pass
(8DPSK)	Adjacent	2442	0.999	0.803	rass
	High	2480	1.003	0.865	Danie
	Adjacent	2479	1.003	0.803	Pass

Note: Limit = 20 dB bandwidth *2/3

FCC Part 15.247 Page 28 of 67


BDR (GFSK): Low Channel

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:03:05

BDR (GFSK): Middle Channel




Date: 10.0CT.2017 21:06:36

FCC Part 15.247 Page 29 of 67


BDR (GFSK): High Channel

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:08:39

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 10.0CT.2017 21:11:34

FCC Part 15.247 Page 30 of 67


EDR (π /4-DQPSK): Middle Channel

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:10:47

EDR ($\pi/4$ -DQPSK): High Channel




Date: 10.0CT.2017 21:09:55

FCC Part 15.247 Page 31 of 67


EDR (8DPSK): Low Channel

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:12:52

EDR (8DPSK): Middle Channel




Date: 10.0CT.2017 21:14:38

FCC Part 15.247 Page 32 of 67

EDR (8DPSK): High Channel

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:15:32

FCC Part 15.247 Page 33 of 67

FCC $\S15.247(a)$ (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ170927003-00B

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2017-10-10.

 $EUT\ operation\ mode:\ Transmitting$


Test Result: Compliance. Please refer to following table and plots

FCC Part 15.247 Page 34 of 67

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.046
	Middle	2441	1.053
	High	2480	1.049
EDR (π/4-DQPSK)	Low	2402	1.346
	Middle	2441	1.35
	High	2480	1.351
EDR (8DPSK)	Low	2402	1.298
	Middle	2441	1.298
	High	2480	1.298

Report No.: RSZ170927003-00B

BDR (GFSK): Low Channel




Date: 10.0CT.2017 20:45:08

FCC Part 15.247 Page 35 of 67


BDR (GFSK): Middle Channel

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 20:44:24

BDR (GFSK): High Channel




Date: 10.0CT.2017 20:45:40

FCC Part 15.247 Page 36 of 67


EDR ($\pi/4$ -DQPSK): Low Channel

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 20:52:27

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 10.OCT.2017 20:51:42

FCC Part 15.247 Page 37 of 67


EDR ($\pi/4$ -DQPSK): High Channel

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 20:46:42

EDR (8DPSK): Low Channel




Date: 10.OCT.2017 20:53:22

FCC Part 15.247 Page 38 of 67


EDR (8DPSK): Middle Channel

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 20:54:16

EDR (8DPSK): High Channel



Date: 10.OCT.2017 20:54:50

FCC Part 15.247 Page 39 of 67

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ170927003-00B

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2017-10-10.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

FCC Part 15.247 Page 40 of 67

Report No.: RSZ170927003-00B

BDR (GFSK): Number of Hopping Channels




Date: 10.OCT.2017 21:20:27

FCC Part 15.247 Page 41 of 67


EDR ($\pi/4$ -DQPSK): Number of Hopping Channels

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:26:17

EDR (8DPSK): Number of Hopping Channels



Date: 10.0CT.2017 21:33:42

FCC Part 15.247 Page 42 of 67

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ170927003-00B

Test Procedure

- 1. The EUT was worked in channel hopping.
- 2. Set the RBW to: 1MHz.
- 3. Set the VBW $> 3 \times RBW$.
- 4. Set the span to 0Hz.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Simon Wang on 2017-10-10.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots


FCC Part 15.247 Page 43 of 67

Mode	e	Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result	
		Low	0.425	0.136	0.4	Pass	
	DII 1	Middle	0.425	0.136	0.4	Pass	
	DH 1	High	0.425	0.136	0.4	Pass	
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S					
BDR (GFSK)		Low	1.689	0.270	0.4	Pass	
	DII 2	Middle	1.689	0.270	0.4	Pass	
	DH 3	High	1.689	0.270	0.4	Pass	
	-	Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S					
		Low	2.947	0.314	0.4	Pass	
	DII 5	Middle	2.947	0.314	0.4	Pass	
	DH 5	High	2.947	0.314	0.4	Pass	
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S					
		Low	0.429	0.137	0.4	Pass	
		Middle	0.429	0.137	0.4	Pass	
	2DH 1	High	0.429	0.137	0.4	Pass	
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S					
	2DH 3	Low	1.689	0.270	0.4	Pass	
EDR		Middle	1.689	0.270	0.4	Pass	
$(\pi/4\text{-DQPSK})$		High	1.689	0.270	0.4	Pass	
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S					
	2DH 5	Low	2.947	0.314	0.4	Pass	
		Middle	2.947	0.314	0.4	Pass	
		High	2.947	0.314	0.4	Pass	
		Note:2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S					
EDR (8DPSK)	3DH 1	Low	0.429	0.137	0.4	Pass	
		Middle	0.429	0.137	0.4	Pass	
		High	0.429	0.137	0.4	Pass	
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S					
	3DH 3	Low	1.689		0.4	Pass	
		Middle	1.689	0.270	0.4	Pass	
		High	1.689	0.270	0.4	Pass	
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S					
	3DH 5	Low	2.947	0.314	0.4	Pass	
		Middle	2.947	0.314	0.4	Pass	
		High	2.947	0.314	0.4	Pass	
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S					

FCC Part 15.247 Page 44 of 67


BDR (GFSK): Pulse time, Low Channel, DH1

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:35:34

Pulse time, Middle Channel, DH1




Date: 10.0CT.2017 21:36:30

FCC Part 15.247 Page 45 of 67


Pulse time, High Channel, DH1

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:36:48

Pulse time, Low Channel, DH3




Date: 10.OCT.2017 21:40:54

FCC Part 15.247 Page 46 of 67


Pulse time, Middle Channel, DH3

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:40:43

Pulse time, High Channel, DH3




Date: 10.OCT.2017 21:40:26

FCC Part 15.247 Page 47 of 67


Pulse time, Low Channel, DH5

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:44:08

Pulse time, Middle Channel, DH5




Date: 10.OCT.2017 21:44:27

FCC Part 15.247 Page 48 of 67


Pulse time, High Channel, DH5

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:44:37

EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1




Date: 10.0CT.2017 21:37:58

FCC Part 15.247 Page 49 of 67


Pulse time, Middle Channel, 2DH1

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:37:46

Pulse time, High Channel, 2DH1




Date: 10.OCT.2017 21:37:27

FCC Part 15.247 Page 50 of 67


Pulse time, Low Channel, 2DH3

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:41:26

Pulse time, Middle Channel, 2DH3




Date: 10.OCT.2017 21:41:49

FCC Part 15.247 Page 51 of 67


Pulse time, High Channel, 2DH3

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:42:16

Pulse time, Low Channel, 2DH5




Date: 10.0CT.2017 21:45:32

FCC Part 15.247 Page 52 of 67


Pulse time, Middle Channel, 2DH5

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:45:21

Pulse time, High Channel, 2DH5




Date: 10.OCT.2017 21:45:11

FCC Part 15.247 Page 53 of 67


EDR (8DPSK): Pulse time, Low Channel, 3DH1

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:38:19

Pulse time, Middle Channel, 3DH1




Date: 10.0CT.2017 21:38:28

FCC Part 15.247 Page 54 of 67


Pulse time, High Channel, 3DH1

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:38:39

Pulse time, Low Channel, 3DH3




Date: 10.OCT.2017 21:43:12

FCC Part 15.247 Page 55 of 67


Pulse time, Middle Channel, 3DH3

Report No.: RSZ170927003-00B



Date: 10.OCT.2017 21:43:03

Pulse time, High Channel, 3DH3




Date: 10.OCT.2017 21:42:51

FCC Part 15.247 Page 56 of 67


Pulse time, Low Channel, 3DH5

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:45:52


Pulse time, Middle Channel, 3DH5



Date: 10.OCT.2017 21:46:04

FCC Part 15.247 Page 57 of 67

Report No.: RSZ170927003-00B



Date: 10.0CT.2017 21:46:13

FCC Part 15.247 Page 58 of 67

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Report No.: RSZ170927003-00B

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	24 ℃		
Relative Humidity:	52 %		
ATM Pressure:	101.0 kPa		

The testing was performed by Simon Wang on 2017-10-11.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

FCC Part 15.247 Page 59 of 67

Low

Middle

High

EDR

(8DPSK)

4.73

4.51

4.53

2.97

2.82

2.84

2402

2441

2480

Report No.: RSZ170927003-00B

1000

1000

FCC Part 15.247 Page 60 of 67

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RSZ170927003-00B

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24~25 ℃
Relative Humidity:	48~54 %
ATM Pressure:	100.0~101.0 kPa

The testing was performed by Simon Wang from 2017-10-10 to 2018-01-05.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following plots.

FCC Part 15.247 Page 61 of 67

BDR (GFSK): Band Edge-Left Side


Report No.: RSZ170927003-00B

Hopping



Date: 5.JAN.2018 13:10:51

Single




Date: 10.OCT.2017 21:00:24

FCC Part 15.247 Page 62 of 67

BDR (GFSK): Band Edge-Right Side


Report No.: RSZ170927003-00B

Hopping



Date: 5.JAN.2018 13:13:08

Single




Date: 10.0CT.2017 20:59:35

FCC Part 15.247 Page 63 of 67

EDR (π/4-DQPSK): Band Edge-Left Side


Report No.: RSZ170927003-00B

Hopping



Date: 5.JAN.2018 13:18:32

Single




Date: 10.OCT.2017 20:57:06

FCC Part 15.247 Page 64 of 67

EDR (π/4-DQPSK): Band Edge-Right Side


Report No.: RSZ170927003-00B

Hopping



Date: 5.JAN.2018 13:16:46

Single




Date: 10.OCT.2017 20:57:45

FCC Part 15.247 Page 65 of 67

EDR (8DPSK): Band Edge-Left Side


Report No.: RSZ170927003-00B

Hopping



Date: 5.JAN.2018 13:20:28

Single




Date: 10.OCT.2017 20:56:29

FCC Part 15.247 Page 66 of 67


EDR (8DPSK): Band Edge-Right Side Hopping

Report No.: RSZ170927003-00B



Date: 5.JAN.2018 13:22:08

Single



Date: 10.0CT.2017 20:55:47

***** END OF REPORT *****

FCC Part 15.247 Page 67 of 67