

TEST REPORT

Product Name: IP Phone
Trade Mark: GRANDSTREAM
Model No.: GRP2615
Add. Model No.: N/A
Report Number: 190515026EMC-1
Test Standards: FCC 47 CFR Part 15 Subpart B
ICES-003 Issue 6
Test Result: PASS
Date of Issue: July 20, 2019

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: _____

Henry Lu
Team Leader

Reviewed by: _____

Kevin Liang
Assistant Manager

Approved by: _____

Billy Li
Technical Director

Date: July 20, 2019

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Version

Version No.	Date	Description
V1.0	July 20, 2019	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com[Http://www.uttlab.com](http://www.uttlab.com)

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	5
1.3 DESCRIPTION OF SUPPORT UNITS	6
1.4 TEST LOCATION	6
1.5 TEST FACILITY	6
1.6 DEVIATION FROM STANDARDS	7
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
1.9 MEASUREMENT UNCERTAINTY	7
2. TEST SUMMARY	8
3. EQUIPMENT LIST	9
4. TEST CONFIGURATION	10
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	10
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	10
4.1.2 RECORD OF NORMAL ENVIRONMENT	10
4.2 TEST MODES	10
4.3 TEST SETUP	11
4.3.1 FOR RADIATED EMISSIONS TEST SETUP	11
4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP	12
4.4 SYSTEM TEST CONFIGURATION	12
5. REFERENCE DOCUMENTS FOR TESTING	13
6. EMC REQUIREMENTS SPECIFICATION	13
6.1 RADIATED EMISSION	13
6.2 CONDUCTED EMISSION	24
APPENDIX 1 PHOTOS OF TEST SETUP	33
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	33

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor, Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	IP Phone
Model No.:	GRP2615
Add. Model No.:	N/A
Trade Mark:	GRANDSTREAM
DUT Stage:	Identical Prototype
Rated Voltage:	<input checked="" type="checkbox"/> 110-240V~50/60Hz
	<input checked="" type="checkbox"/> Powered by POE port
Classification of digital devices:	Class B
Highest Internal Frequency:	5825 MHz
Software Version:	0.4.24.21
Hardware Version:	V1.1
Sample Received Date:	June 6, 2019
Sample Tested Date:	June 17, 2019 to June 26, 2019

1.2.2 Description of Accessories

Adapter (1)	
Model No.:	PEA-120100VA
Input:	100-240 V~50/60 Hz 0.3 A
Output:	12.0 V \equiv 1.0 A
AC Cable:	N/A
DC Cable:	2.5 Meter, Unshielded without ferrite

Adapter (2)	
Model No.:	F12L28-120100SPAU
Input:	100-240 V~50/60 Hz 0.3 A
Output:	12.0 V \equiv 1.0 A
AC Cable:	N/A
DC Cable:	2.5 Meter, Unshielded without ferrite

Adapter (3)	
Model No.:	F12US1200100A
Input:	100-240 V~50/60 Hz 0.5 A
Output:	12.0 V \equiv 1.0 A
AC Cable:	N/A
DC Cable:	2.5 Meter, Unshielded without ferrite

Cable (1)	
Description:	Ethernet Cable (RJ45)
Cable Type:	Unshielded without ferrite
Length:	1.5 Meter

Cable (2)	
Description:	Phone Cord (RJ9)
Cable Type:	Unshielded without ferrite
Length:	3.5 Meter

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	B40-80	MP12NEQ6	UnionTrust
Mobile Phone	Apple	A1688	N/A	UnionTrust
USB disk	Kingston	DTSE9	N/A	UnionTrust
mouse	DELL	MS111	CN-011D3V-738	UnionTrust
Wireless AP	SiZong	WN1200A3	WS1505000003	UnionTrust
Headset	YEEY	VE120-MV	N/A	UnionTrust
Standard POE Power supply	TP-LINK	TL-POE160S	N/A	UnionTrust
IP Phone	GRANDSTREAM	GRP2612W	N/A	Applicant
Expansion Module	GRANDSTREAM	GBX20	N/A	Applicant

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Ethernet Cable	RJ45	1.0 Unshielded without ferrite	UnionTrust
2	Ethernet Cable	RJ45	5.0 Unshielded without ferrite	UnionTrust
3	Ethernet Cable	RJ45	2.0 Unshielded without ferrite	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Designation Number: CN1194

Test Firm Registration Number: 259480

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	± 3.8 dB
2	Conducted emission 150KHz-30MHz	± 3.4 dB
3	Radiated emission 9KHz-30MHz	± 4.9 dB
4	Radiated emission 30MHz-1GHz	± 4.7 dB
5	Radiated emission 1GHz-18GHz	± 5.1 dB
6	Radiated emission 18GHz-26GHz	± 5.2 dB
7	Radiated emission 26GHz-40GHz	± 5.2 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	Test Requirement	Test Method	Result
Conducted Emission	FCC 47 CFR Part 15.107 ICES-003 Issue 6 Section 6.1	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109 ICES-003 Issue 6 Section 6.2	ANSI C63.4-2014	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
<input checked="" type="checkbox"/>	Receiver	R&S	ESIB26	100114	Nov. 24, 2018	Nov. 24, 2019
<input type="checkbox"/>	Loop Antenna	ETS-LINDGREN	6502	00202525	Dec. 03, 2018	Dec. 03, 2019
<input checked="" type="checkbox"/>	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Dec. 08, 2018	Dec. 08, 2019
<input checked="" type="checkbox"/>	6dB Attenuator	Talent	RA6A5-N-18	18103001	Dec. 08, 2018	Dec. 08, 2019
<input checked="" type="checkbox"/>	Preamplifier	HP	8447F	2805A02960	Nov. 24, 2018	Nov. 24, 2019
<input checked="" type="checkbox"/>	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May 18, 2019	May 18, 2020
<input checked="" type="checkbox"/>	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Jan. 05, 2019	Jan. 05, 2020
<input checked="" type="checkbox"/>	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160333		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 24, 2018	Nov. 24, 2019
<input checked="" type="checkbox"/>	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 24, 2018	Nov. 24, 2019
<input checked="" type="checkbox"/>	LISN	R&S	ESH2-Z5	860014/024	Nov. 24, 2018	Nov. 24, 2019
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160323		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage	Relative Humidity (%)
NT/NV	+15 to +35	AC 120V/60Hz or AC 240V/50Hz	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
Conducted Emission	25.3	44	99.8	Gemini Huang
Radiated Emission	24.63	52	100.01	Fire Huo

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	TM1: AC120V/60Hz (Adaptor1) + Hands Free TM2: AC120V/60Hz (Adaptor1) + Ringing TM3: AC120V/60Hz (Adaptor1) + Handset TM4: AC120V/60Hz (Adaptor1) + Headset TM5: AC240V/50Hz (Adaptor1) + Worse from mode 1~4 TM6: Worse from mode 1~5 (Adaptor2) TM7: Worse from mode 1~5 (Adaptor3) TM8: AC120V/60Hz (POE) +Worse from mode 1~4 TM9: Worse from mode 1~8 + Expansion Module x 1
Conducted Emission	TM1: AC120V/60Hz (Adaptor1) + Hands Free TM2: AC120V/60Hz (Adaptor1) + Ringing TM3: AC120V/60Hz (Adaptor1) + Handset TM4: AC120V/60Hz (Adaptor1) + Headset TM5: AC240V/50Hz (Adaptor1) + Worse from mode 1~4 TM6: Worse from mode 1~5 (Adaptor2) TM7: Worse from mode 1~5 (Adaptor3) TM8: AC120V/60Hz (POE) +Worse from mode 1~4 TM9: Worse from mode 1~8 + Expansion Module x 1

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz






Figure 2. Above 1GHz



4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 6	Information Technology Equipment (Including Digital Apparatus) —Limits and Methods of Measurement
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
5	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109
ICES-003 Issue 6 Clause 6.2

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

Frequency (MHz)	limits at 3m (dB μ V/m)		
	QP Detector	PK Detector	AV Detector
30-88	40.0	--	--
88-216	43.5	--	--
216-960	46.0	--	--
960 to 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

Test Procedures:**1. From 30 MHz to 1GHz test procedure as below:**

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:


- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:


Below 1GHz (Quasi Peak):
Test Mode 3 (Adapter 1)
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	92.346	42.76	-12.34	30.42	43.50	-13.08	QP
2	101.180	41.37	-11.72	29.65	43.50	-13.85	QP
3	135.916	41.64	-11.62	30.02	43.50	-13.48	QP
4	238.463	41.17	-8.70	32.47	46.00	-13.53	QP
5	250.486	44.61	-8.56	36.05	46.00	-9.95	QP
6	300.699	44.74	-7.22	37.52	46.00	-8.48	QP




Below 1GHz (Quasi Peak):
Test Mode 6 (Adapter 2)
Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	92.997	49.07	-12.27	36.80	43.50	-6.70	QP
2	100.471	43.25	-11.65	31.60	43.50	-11.90	QP
3	127.586	41.71	-11.59	30.12	43.50	-13.38	QP
4	250.486	43.43	-8.56	34.87	46.00	-11.13	QP
5	280.294	43.04	-7.32	35.72	46.00	-10.28	QP
6	516.565	36.67	-3.43	33.24	46.00	-12.76	QP




Below 1GHz (Quasi Peak):
Test Mode 7 (Adapter 3)
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	85.477	46.08	-13.11	32.97	40.00	-7.03	QP
2	100.471	42.54	-11.65	30.89	43.50	-12.61	QP
3	128.486	43.11	-11.63	31.48	43.50	-12.02	QP
4	181.300	40.52	-10.04	30.48	43.50	-13.02	QP
5	300.699	42.21	-7.22	34.99	46.00	-11.01	QP
6	376.523	41.78	-5.58	36.20	46.00	-9.80	QP

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	60.153	46.31	-14.41	31.90	40.00	-8.10	QP
2	85.477	48.80	-13.11	35.69	40.00	-4.31	QP
3	121.462	46.41	-11.67	34.74	43.50	-8.76	QP
4	158.640	47.20	-10.53	36.67	43.50	-6.83	QP
5	250.486	43.21	-8.56	34.65	46.00	-11.35	QP
6	502.247	37.02	-3.54	33.48	46.00	-12.52	QP

Below 1GHz (Quasi Peak):
Test Mode 8 (POE)
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	100.471	43.87	-11.65	32.22	43.50	-11.28	QP
2	135.916	45.50	-11.62	33.88	43.50	-9.62	QP
3	250.486	42.76	-8.56	34.20	46.00	-11.80	QP
4	292.364	41.52	-7.11	34.41	46.00	-11.59	QP
5	376.523	40.79	-5.58	35.21	46.00	-10.79	QP
6	754.963	33.73	0.95	34.68	46.00	-11.32	QP

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.035	47.61	-10.88	36.73	40.00	-3.27	QP
2	68.745	50.68	-13.78	36.90	40.00	-3.10	QP
3	85.477	49.85	-13.11	36.74	40.00	-3.26	QP
4	135.916	50.88	-11.62	39.26	43.50	-4.24	QP
5	502.247	36.41	-3.54	32.87	46.00	-13.13	QP
6	754.963	35.49	0.95	36.44	46.00	-9.56	QP

Above 1GHz(Peak & Average)
Test Mode 3 (Adapter 1)
Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1129.346	51.13	-11.68	39.45	74.00	-34.55	Peak
2	1465.642	50.50	-10.65	39.85	74.00	-34.15	Peak
3	3494.334	40.86	1.19	42.05	74.00	-31.95	Peak
4	7593.669	42.17	7.32	49.49	74.00	-24.51	Peak
5	10811.890	41.07	11.05	52.12	74.00	-21.88	Peak
6	17792.680	34.37	17.63	52.00	74.00	-22.00	Peak



Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.
6. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107
ICES-003 Issue 6 Section 6.2

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Quasi Peak and Average:


Test Mode 4 (Adapter 1)

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.150	25.19	10.04	35.23	56.00	-20.77	Average
2	0.150	39.49	10.04	49.53	66.00	-16.47	QP
3	0.474	32.30	9.99	42.29	46.44	-4.15	Average
4	0.474	37.80	9.99	47.79	56.44	-8.65	QP
5	7.158	23.50	10.83	34.33	50.00	-15.67	Average
6	7.158	30.80	10.83	41.63	60.00	-18.37	QP


Neutral Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.150	22.49	10.01	32.50	56.00	-23.50	Average
2	0.150	38.99	10.01	49.00	66.00	-17.00	QP
3	0.474	25.70	9.97	35.67	46.44	-10.77	Average
4	0.474	32.90	9.97	42.87	56.44	-13.57	QP
5	8.973	21.30	11.03	32.33	50.00	-17.67	Average
6	8.973	28.00	11.03	39.03	60.00	-20.97	QP


Test Mode 6 (Adapter 2)

Live Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.150	23.69	10.04	33.73	56.00	-22.27	Average
2	0.150	33.69	10.04	43.73	66.00	-22.27	QP
3	0.362	23.80	9.99	33.79	48.68	-14.89	Average
4	0.362	31.40	9.99	41.39	58.68	-17.29	QP
5	7.586	15.90	10.90	26.80	50.00	-23.20	Average
6	7.586	22.80	10.90	33.70	60.00	-26.30	QP


Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.150	20.29	10.01	30.30	56.00	-25.70	Average
2	0.150	35.79	10.01	45.80	66.00	-20.20	QP
3	0.362	17.20	9.97	27.17	48.68	-21.51	Average
4	0.362	26.70	9.97	36.67	58.68	-22.01	QP
5	14.025	11.61	12.72	24.33	50.00	-25.67	Average
6*	14.025	17.41	12.72	30.13	60.00	-29.87	QP


Test Mode 7 (Adapter 3)

Live Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.150	23.39	10.04	33.43	56.00	-22.57	Average
2	0.150	40.69	10.04	50.73	66.00	-15.27	QP
3	0.502	26.40	9.99	36.39	46.00	-9.61	Average
4	0.502	30.40	9.99	40.39	56.00	-15.61	QP
5	3.446	15.10	10.45	25.55	46.00	-20.45	Average
6	3.446	22.90	10.45	33.35	56.00	-22.65	QP


Neutral Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.154	20.10	10.00	30.10	55.78	-25.68	Average
2	0.154	38.40	10.00	48.40	65.78	-17.38	QP
3	0.502	27.10	9.97	37.07	46.00	-8.93	Average
4	0.502	22.60	9.97	32.57	56.00	-23.43	QP
5	9.773	13.31	11.12	24.43	50.00	-25.57	Average
6	9.773	18.81	11.12	29.93	60.00	-30.07	QP


Test Mode 8 (POE)

Live Line



No.	Frequency (MHz)	Reading (dBUV)	Correction factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.178	39.00	10.02	49.02	54.58	-5.56	Average
2	0.178	49.86	10.02	59.88	64.58	-4.70	QP
3	0.266	35.10	9.99	45.09	51.24	-6.15	Average
4	0.266	44.94	9.99	54.93	61.24	-6.31	QP
5	0.358	38.00	9.99	47.99	48.78	-0.79	Average
6	0.358	45.93	9.99	55.92	58.78	-2.86	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.182	36.49	10.00	46.49	54.39	-7.90	Average
2	0.182	47.99	10.00	57.99	64.39	-6.40	QP
3	0.366	35.90	9.97	45.87	48.59	-2.72	Average
4	0.366	43.30	9.97	53.27	58.59	-5.32	QP
5	9.357	29.71	11.07	40.78	50.00	-9.22	Average
6	9.357	35.41	11.07	46.48	60.00	-13.52	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
