

# FCC Part 15C




## Measurement and Test Report

For

### SHARX SECURITY, INC

8 Stoneleigh Dr Derry 03038 New Hampshire U.S.A

**FCC ID: Z2J2700**

|  |   |
|--|---|
| <b>Report Concerns:</b><br>Original Report | <b>Equipment Type:</b><br>Network Camera  |
| <b>Model:</b>                              | <u>SCNC2707</u>   |
| <b>Report No.:</b>                         | <u>STR11098119I</u>   |
| <b>Test Date:</b>                          | <u>2011-09-16 to 2011-10-17</u>   |
| <b>Issue Date:</b>                         | <u>2011-10-21</u>   |
| <b>Tested By:</b>                          | <u>Vigoss Xiong / Engineer</u>   |
| <b>Reviewed By:</b>                        | <u>Lahm Peng / EMC Manager</u>   |
| <b>Approved &amp; Authorized By:</b>       | <u>Jandy so / PSQ Manager</u>    |
| <b>Prepared By:</b>                        | <b>SEM.Test Compliance Service Co., Ltd</b><br>3/F, Jinbao Commerce Building, Xin'an Fanshen Road,<br>Bao'an District, Shenzhen, P.R.C. (518101)<br>Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: <a href="http://www.semtest.com.cn">www.semtest.com.cn</a> |

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

## **TABLE OF CONTENTS**

|   |           |
|---|-----------|
| <b>1. GENERAL INFORMATION.....</b>                          | <b>3</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3         |
| 1.2 TEST STANDARDS.....                                     | 3         |
| 1.3 TEST METHODOLOGY.....                                   | 4         |
| 1.4 TEST FACILITY.....                                      | 4         |
| 1.5 EUT EXERCISE SOFTWARE.....                              | 4         |
| 1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS.....             | 4         |
| 1.7 EUT CABLE LIST AND DETAILS.....                         | 4         |
| <b>2. SUMMARY OF TEST RESULTS.....</b>                      | <b>5</b>  |
| <b>3. CONDUCTED EMISSIONS.....</b>                          | <b>6</b>  |
| 3.1 MEASUREMENT UNCERTAINTY.....                            | 6         |
| 3.2 TEST EQUIPMENT LIST AND DETAILS.....                    | 6         |
| 3.3 TEST PROCEDURE.....                                     | 6         |
| 3.4 BASIC TEST SETUP BLOCK DIAGRAM.....                     | 6         |
| 3.5 ENVIRONMENTAL CONDITIONS.....                           | 7         |
| 3.6 SUMMARY OF TEST RESULTS/PLOTS.....                      | 7         |
| 3.7 CONDUCTED EMISSIONS TEST DATA.....                      | 7         |
| <b>4. §15.203 - ANTENNA REQUIREMENT.....</b>                | <b>10</b> |
| 4.1 STANDARD APPLICABLE.....                                | 10        |
| 4.2 TEST RESULT.....  | 10        |
| <b>5. POWER SPECTRAL DENSITY.....</b>                       | <b>11</b> |
| 5.1 STANDARD APPLICABLE.....                                | 11        |
| 5.2 TEST EQUIPMENT LIST AND DETAILS.....                    | 11        |
| 5.3 TEST PROCEDURE.....                                     | 11        |
| 5.4 ENVIRONMENTAL CONDITIONS.....                           | 11        |
| 5.5 SUMMARY OF TEST RESULTS/PLOTS.....                      | 12        |
| <b>6. 6-DB BANDWIDTH.....</b>                               | <b>16</b> |
| 6.1 STANDARD APPLICABLE.....                                | 16        |
| 6.2 TEST EQUIPMENT LIST AND DETAILS.....                    | 16        |
| 6.3 TEST PROCEDURE.....                                     | 16        |
| 6.4 ENVIRONMENTAL CONDITIONS.....                           | 16        |
| 6.5 SUMMARY OF TEST RESULTS/PLOTS.....                      | 16        |
| <b>7. POWER OUTPUT.....</b>                                 | <b>20</b> |
| 7.1 STANDARD APPLICABLE.....                                | 20        |
| 7.2 TEST EQUIPMENT LIST AND DETAILS.....                    | 20        |
| 7.3 TEST PROCEDURE.....                                     | 20        |
| 7.4 ENVIRONMENTAL CONDITIONS.....                           | 20        |
| 7.5 SUMMARY OF TEST RESULTS/PLOTS.....                      | 21        |
| <b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....</b>         | <b>25</b> |
| 8.1 MEASUREMENT UNCERTAINTY.....                            | 25        |
| 8.2 STANDARD APPLICABLE.....                                | 25        |
| 8.3 TEST EQUIPMENT LIST AND DETAILS.....                    | 25        |
| 8.4 TEST PROCEDURE.....                                     | 26        |
| 8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....           | 26        |
| 8.6 ENVIRONMENTAL CONDITIONS.....                           | 26        |
| 8.7 SUMMARY OF TEST RESULTS/PLOTS.....                      | 27        |
| <b>9. OUT OF BAND EMISSIONS.....</b>                        | <b>41</b> |
| 9.1 STANDARD APPLICABLE.....                                | 41        |
| 9.2 TEST EQUIPMENT LIST AND DETAILS.....                    | 41        |
| 9.3 TEST PROCEDURE.....                                     | 41        |
| 9.4 ENVIRONMENTAL CONDITIONS.....                           | 41        |
| 9.5 SUMMARY OF TEST RESULTS/PLOTS.....                      | 42        |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: SHARX SECURITY, INC  
Address of applicant: 8 Stoneleigh Dr Derry 03038 New Hampshire U.S.A

Manufacturer: SHARX SECURITY, INC  
Address of manufacturer: 8 Stoneleigh Dr Derry 03038 New Hampshire U.S.A

#### General Description of E.U.T

| Items               | Description                              |
|---------------------|--|
| EUT Description:    | Network Camera                           |
| Trade Name:         | SHARX                                    |
| Model No.:          | SCNC2707                                 |
| Add Models:         | SCNC2706, SCNC2707W, SCNC2700, SCNC2700W |
| Rated Voltage:      | DC 12.0V                                 |
| RF Output Power     | Max. 12.98dBm (Conducted)                |
| Antenna Gain:       | 3.0dBi                                   |
| Frequency range:    | 2412MHz~2462MHz                          |
| Number of channels: | 11                                       |
| Channel Separation: | 5MHz                                     |
| Type of Antenna:    | Integral Antenna                         |

*Note: The test data is gathered from a production sample, provided by the manufacture. The others models listed in the report have different appearance only of SCNC2707 without circuit and electronic construction changed, declared by the manufacturer.*

### 1.2 Test Standards

The following report is prepared on behalf of the SHARX SECURITY, INC in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

### 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted with Low Channel, Middle Channel and High Channel, accordingly in reference to the Operating Instructions.

### 1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

### 1.5 EUT Exercise Software

The EUT exercise program used during the testing was designed to exercise the system components.

### 1.6 Accessories Equipment List and Details

| Description | Manufacturer | Model | Serial Number |
|-------------|--------------|-------|---------------|
| /           | /            | /     | /             |

### 1.7 EUT Cable List and Details

| Cable Description | Length (M) | Shielded/Unshielded | With Core/Without Core |
|-------------------|------------|---------------------|------------------------|
| Power Cable       | 3.0        | Unshielded          | With Core              |
| /                 | /          | /                   | /                      |

## 2. SUMMARY OF TEST RESULTS

| FCC RULES                   | DESCRIPTION OF TEST    | RESULT    |
|-----------------------------|------------------------|-----------|
| § 15.203; § 15.247(c)(1)(i) | Antenna Requirement    | Compliant |
| § 15.207                    | Conducted Emission     | Compliant |
| § 15.247(e)                 | Power Spectral Density | Compliant |
| § 15.247(a)(2)              | 6 dB Bandwidth         | Compliant |
| § 15.247(b)(3)              | Power Output           | Compliant |
| § 15.209(a)(d)              | Radiated Emission      | Compliant |
| § 15.247(d)                 | Band edge              | Compliant |

### 3. CONDUCTED EMISSIONS

#### 3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

#### 3.2 Test Equipment List and Details


| Description       | Manufacturer    | Model    | Serial Number | Cal. Date  | Due. Date  |
|-------------------|-----------------|----------|---------------|------------|------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI     | 101611        | 2010-12-20 | 2011-12-19 |
| L.I.S.N           | Schwarz beck    | NSLK8126 | 8126-224      | 2010-12-20 | 2011-12-19 |
| Pulse Limiter     | Rohde & Schwarz | ESH3-Z2  | 100911        | 2010-12-20 | 2011-12-19 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

#### 3.3 Test Procedure

Test is conducting under the description of ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

#### 3.4 Basic Test Setup Block Diagram



### 3.5 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 20° C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1011 mbar |

### 3.6 Summary of Test Results/Plots

According to the data in section 3.7, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:

**-13.07 dB $\mu$ V at 0.190 MHz in the Neutral, Peak Detector, 0.15-30MHz**

### 3.7 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data

Conducted Disturbance


EUT: Network Camera

M/N: SCNC2707

Operating Condition: Operating

Test Specification: L

Comment: AC 120V/60Hz/Adapter 12V



| EDIT PEAK LIST (Prescan Results) |            |            |                |
|----------------------------------|------------|------------|----------------|
| Trace1:                          | -QP        |            |                |
| Trace2:                          | -AV        |            |                |
| Trace3:                          | ---        |            |                |
| TRACE                            | FREQUENCY  | LEVEL dBμV | DELTA LIMIT dB |
| 1 Max Peak                       | 186 kHz    | 50.89      | -13.32         |
| 2 Average                        | 186 kHz    | 40.34      | -13.87         |
| 2 Average                        | 566 kHz    | 28.58      | -17.41         |
| 1 Max Peak                       | 578 kHz    | 37.41      | -18.58         |
| 1 Max Peak                       | 12.678 MHz | 44.55      | -15.44         |
| 2 Average                        | 12.826 MHz | 34.02      | -15.97         |



**Plot of Conducted Emissions Test Data**

Conducted Disturbance


EUT: Network Camera

M/N: SCNC2707

Operating Condition: Operating

Test Specification: N

Comment: AC 120V/60Hz/Adapter 12V



| EDIT PEAK LIST (Prescan Results) |            |            |                |
|----------------------------------|------------|------------|----------------|
| Trace1:                          | -QP        |            |                |
| Trace2:                          | -AV        |            |                |
| Trace3:                          | ---        |            |                |
| TRACE                            | FREQUENCY  | LEVEL dBμV | DELTA LIMIT dB |
| 1 Max Peak                       | 190 kHz    | 50.96      | -13.07         |
| 2 Average                        | 506 kHz    | 31.64      | -14.35         |
| 1 Max Peak                       | 566 kHz    | 38.10      | -17.89         |
| 2 Average                        | 570 kHz    | 27.99      | -18.00         |
| 1 Max Peak                       | 12.714 MHz | 42.48      | -17.51         |
| 2 Average                        | 29.99 MHz  | 32.86      | -17.13         |

## **4. §15.203 - ANTENNA REQUIREMENT**

---

### **4.1 Standard Applicable**

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Test Result**

This product has a integral antenna, fulfill the requirement of this section.

## 5. POWER SPECTRAL DENSITY

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2010-12-20 | 2011-12-19 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2010-12-20 | 2011-12-19 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 5.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=3KHz, Span = 20MHz.
4. Repeat above procedures until all frequency measured was complete.

### 5.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 20° C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

**5.5 Summary of Test Results/Plots**


| Test mode | Test channel                | Reading<br>dBm/3kHz | Limit<br>dBm/3kHz |
|-----------|-----------------------------|---------------------|-------------------|
| 802.11b   | Low channel<br>(2412MHz)    | -7.05               | 8                 |
|           | Middle channel<br>(2437MHz) | -4.621              | 8                 |
|           | High channel<br>(2462MHz)   | -10.07              | 8                 |
| 802.11g   | Low channel<br>(2412MHz)    | -11.34              | 8                 |
|           | Middle channel<br>(2437MHz) | -11.7               | 8                 |
|           | High channel<br>(2462MHz)   | -12.71              | 8                 |

**For 802.11b**


Low Channel:



Middle Channel:




High Channel:




For 802.11g


Low Channel:



Middle Channel:



High Channel:



## 6. 6-dB BANDWIDTH

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2010-12-20 | 2011-12-19 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2010-12-20 | 2011-12-19 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 6.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. The spectrum analyzer as RBW=100KHz (1 % of Bandwidth.), Sweep=auto
4. Mark the peak frequency and –6dB (upper and lower) frequency.

### 6.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 24° C     |
| Relative Humidity: | 53%       |
| ATM Pressure:      | 1018 mbar |


### 6.5 Summary of Test Results/Plots

| Test mode | Frequency<br>MHz | 6 dB Bandwidth<br>kHz | Limit<br>kHz |
|-----------|------------------|-----------------------|--------------|
| 802.11b   | 2412             | 7606                  | 500          |
|           | 2437             | 7358                  | 500          |
|           | 2462             | 7128                  | 500          |
| 802.11g   | 2412             | 16509                 | 500          |
|           | 2437             | 16491                 | 500          |
|           | 2462             | 16418                 | 500          |




**For 802.11b**


Low Channel:



Mid Channel:




High Channel:




For 802.11g


Low Channel:



Mid Channel:



High Channel:



## 7. POWER OUTPUT

### 7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2010-12-20 | 2011-12-19 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2010-12-20 | 2011-12-19 |

**Statement of Traceability:** All calibrations have been performed per the NVLAP requirements traceable to the NIST.

### 7.3 Test Procedure

According to section 15.247(b)-power output of the KDB-558074 (2005), the method #1 of the power output option2 was used, the following is the measurement procedure.

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW  $\geq$  3 MHz.
3. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to “free run”.
4. Use sample detector mode if bin width (i.e., span/number of points in spectrum display)  $<$  0.5 RBW. Otherwise use peak detector mode.
5. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to “free run”.
6. Trace average 100 traces in power averaging mode.
7. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer’s band power measurement function with band limits set equal to the EBW band edges.

### 7.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 21° C     |
| Relative Humidity: | 55%       |
| ATM Pressure:      | 1011 mbar |

**7.5 Summary of Test Results/Plots**


| Test mode | Frequency<br>MHz | Reading<br>dBm | Output power<br>W | Limit<br>W |
|-----------|------------------|----------------|-------------------|------------|
| 802.11b   | 2412             | 12.90          | 0.01950           | 1          |
|           | 2437             | 12.19          | 0.01656           | 1          |
|           | 2462             | 12.98          | 0.01986           | 1          |
| 802.11g   | 2412             | 11.78          | 0.01507           | 1          |
|           | 2437             | 11.71          | 0.01483           | 1          |
|           | 2462             | 12.18          | 0.01652           | 1          |

**For 802.11b rate**


Low Channel:



Middle Channel:




High Channel:




For 802.11g rate


Low Channel:



Middle Channel:



High Channel:





## 8. FIELD STRENGTH OF SPURIOUS EMISSIONS

### 8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 8.2 Standard Applicable

According to §15.247(c), 15.205 15.209(b) & 15.35 (b), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Section 15.209:

1.705 - 30MHz 49.5 dBuV/m @3M

30 - 88 MHz 40 dBuV/m @3M

88 -216 MHz 43.5 dBuV/m @3M

216 -960 MHz 46 dBuV/m @3M

Above 960 MHz 54dBuV/m @3M

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.3 Test Equipment List and Details


| Description              | Manufacturer         | Model     | Serial Number | Cal. Date  | Due. Date  |
|--------------------------|----------------------|-----------|---------------|------------|------------|
| Spectrum Analyzer        | R&S                  | FSP       | 836079/035    | 2010-12-20 | 2011-12-19 |
| EMI Test Receiver        | R&S                  | ESVB      | 825471/005    | 2010-12-20 | 2011-12-19 |
| Positioning Controller   | C&C                  | CC-C-1F   | N/A           | 2010-12-20 | 2011-12-19 |
| RF Switch                | EM                   | EMSW18    | SW060023      | 2010-12-20 | 2011-12-19 |
| Pre-amplifier            | Agilent              | 8447F     | 3113A06717    | 2010-12-20 | 2011-12-19 |
| Pre-amplifier            | Compliance Direction | PAP-0118  | 24002         | 2010-12-20 | 2011-12-19 |
| Trilog Broadband Antenna | SCHWARZBECK          | VULB9163  | 9163-333      | 2011-01-09 | 2012-01-08 |
| Horn Antenna             | ETS                  | 3117      | 00086197      | 2011-01-09 | 2012-01-08 |
| Loop Antenna             | SCHWARZECK           | HFRA 5165 | 9365          | 2011-01-09 | 2012-01-08 |

## 8.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205, 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



## 8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

## 8.6 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 22° C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

## 8.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst margin of:

**-1.02dB $\mu$ V at 857.0247MHz in the Vertical polarization, Transmitting 802.11g Middle Channel test mode with, 9kHz to 25 GHz, 3Meters**

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*


Test Result/Plots:

Spurious Emission From 30 MHz to 1 GHz

Test mode: Transmitting (802.11b) Low Channel(2412MHz)


Comment:

Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 99.5281            | 26.47               | 8.40            | 34.87              | 43.50             | -8.63          | 360             | 100            | peak   |
| 2   | 124.5690           | 30.93               | 5.32            | 36.25              | 43.50             | -7.25          | 360             | 100            | peak   |
| 3   | 251.1804           | 31.72               | 8.72            | 40.44              | 46.00             | -5.56          | 360             | 100            | peak   |
| 4   | 366.8231           | 27.02               | 10.99           | 38.01              | 46.00             | -7.99          | 360             | 100            | peak   |
| 5   | 607.7867           | 26.69               | 16.73           | 43.42              | 46.00             | -2.58          | 360             | 100            | peak   |
| 6   | 734.4913           | 25.40               | 18.02           | 43.42              | 46.00             | -2.58          | 360             | 100            | peak   |
| 7   | 857.0247           | 22.29               | 20.08           | 42.37              | 46.00             | -3.63          | 360             | 100            | peak   |

Vertical




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 105.2718           | 26.96               | 7.99            | 34.95              | 43.50             | -8.55          | 360             | 100            | peak   |
| 2   | 124.5690           | 32.60               | 5.32            | 37.92              | 43.50             | -5.58          | 360             | 100            | peak   |
| 3   | 366.8231           | 29.39               | 10.99           | 40.38              | 46.00             | -5.62          | 360             | 100            | peak   |
| 4   | 734.4913           | 26.19               | 18.02           | 44.21              | 46.00             | -1.79          | 360             | 100            | peak   |
| 5   | 857.0247           | 24.79               | 20.08           | 44.87              | 46.00             | -1.13          | 360             | 100            | peak   |

Spurious Emission From 30 MHz to 1 GHz

Test mode: Transmitting (802.11b) Middle Channel(2437MHz)


Comment:

Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 124.5690           | 29.73               | 5.32            | 35.05              | 43.50             | -8.45          | 360             | 100            | peak   |
| 2   | 251.1804           | 31.74               | 8.72            | 40.46              | 46.00             | -5.54          | 360             | 100            | peak   |
| 3   | 277.0935           | 29.43               | 9.43            | 38.86              | 46.00             | -7.14          | 360             | 100            | peak   |
| 4   | 607.7867           | 27.69               | 16.73           | 44.42              | 46.00             | -1.58          | 360             | 100            | peak   |
| 5   | 734.4913           | 25.40               | 18.02           | 43.42              | 46.00             | -2.58          | 360             | 100            | peak   |

Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 105.2718  | 29.18    | 7.99    | 37.17    | 43.50    | -6.33  | 360    | 100    | peak   |
| 2   | 124.5690  | 32.67    | 5.32    | 37.99    | 43.50    | -5.51  | 360    | 100    | peak   |
| 3   | 249.4250  | 32.07    | 8.68    | 40.75    | 46.00    | -5.25  | 360    | 100    | peak   |
| 4   | 734.4913  | 26.53    | 18.02   | 44.55    | 46.00    | -1.45  | 360    | 100    | peak   |
| 5   | 857.0247  | 23.93    | 20.08   | 44.01    | 46.00    | -1.99  | 360    | 100    | peak   |

Spurious Emission From 30 MHz to 1 GHz

Test mode: Transmitting (802.11b) High Channel(2462MHz)


Comment:

Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 124.5690           | 29.05               | 5.32            | 34.37              | 43.50             | -9.13          | 360             | 100            | peak   |
| 2   | 251.1804           | 31.41               | 8.72            | 40.13              | 46.00             | -5.87          | 360             | 100            | peak   |
| 3   | 277.0935           | 29.90               | 9.43            | 39.33              | 46.00             | -6.67          | 360             | 100            | peak   |
| 4   | 607.7867           | 27.40               | 16.73           | 44.13              | 46.00             | -1.87          | 360             | 100            | peak   |
| 5   | 734.4913           | 25.76               | 18.02           | 43.78              | 46.00             | -2.22          | 360             | 100            | peak   |

Vertical



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 101.6443  | 28.14    | 8.29    | 36.43    | 43.50    | -7.07  | 360    | 100    | peak   |
| 2   | 124.5690  | 33.19    | 5.32    | 38.51    | 43.50    | -4.99  | 360    | 100    | peak   |
| 3   | 366.8231  | 28.74    | 10.99   | 39.73    | 46.00    | -6.27  | 360    | 100    | peak   |
| 4   | 734.4913  | 26.36    | 18.02   | 44.38    | 46.00    | -1.62  | 360    | 100    | peak   |
| 5   | 857.0247  | 22.68    | 20.08   | 42.76    | 46.00    | -3.24  | 360    | 100    | peak   |




Spurious Emission From 30 MHz to 1 GHz

Test mode: Transmitting (802.11g) Low Channel(2412MHz)


Comment:

Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 94.7601            | 24.86               | 8.01            | 32.87              | 43.50             | -10.63         | 360             | 100            | peak   |
| 2   | 125.4457           | 27.51               | 5.19            | 32.70              | 43.50             | -10.80         | 360             | 100            | peak   |
| 3   | 251.1804           | 31.52               | 8.72            | 40.24              | 46.00             | -5.76          | 360             | 100            | peak   |
| 4   | 607.7867           | 26.26               | 16.73           | 42.99              | 46.00             | -3.01          | 360             | 100            | peak   |
| 5   | 734.4913           | 25.31               | 18.02           | 43.33              | 46.00             | -2.67          | 360             | 100            | peak   |
| 6   | 857.0247           | 23.36               | 20.08           | 43.44              | 46.00             | -2.56          | 360             | 100            | peak   |

Vertical




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 101.6443           | 28.14               | 8.29            | 36.43              | 43.50             | -7.07          | 360             | 100            | peak   |
| 2   | 124.5690           | 32.63               | 5.32            | 37.95              | 43.50             | -5.55          | 360             | 100            | peak   |
| 3   | 249.4250           | 26.49               | 8.68            | 35.17              | 46.00             | -10.83         | 360             | 100            | peak   |
| 4   | 734.4913           | 26.11               | 18.02           | 44.13              | 46.00             | -1.87          | 360             | 100            | peak   |
| 5   | 857.0247           | 24.52               | 20.08           | 44.60              | 46.00             | -1.40          | 360             | 100            | peak   |

Spurious Emission From 30 MHz to 1 GHz

Test mode: Transmitting (802.11g) Middle Channel(2437MHz)


Comment:

Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 96.7749            | 26.88               | 8.19            | 35.07              | 43.50             | -8.43          | 360             | 100            | peak   |
| 2   | 124.5690           | 31.40               | 5.32            | 36.72              | 43.50             | -6.78          | 360             | 100            | peak   |
| 3   | 251.1804           | 31.07               | 8.72            | 39.79              | 46.00             | -6.21          | 360             | 100            | peak   |
| 4   | 607.7867           | 27.20               | 16.73           | 43.93              | 46.00             | -2.07          | 360             | 100            | peak   |
| 5   | 734.4913           | 26.23               | 18.02           | 44.25              | 46.00             | -1.75          | 360             | 100            | peak   |
| 6   | 857.0247           | 23.19               | 20.08           | 43.27              | 46.00             | -2.73          | 360             | 100            | peak   |

Vertical




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 101.6443           | 29.14               | 8.29            | 37.43              | 43.50             | -6.07          | 360             | 100            | peak   |
| 2   | 125.4457           | 33.41               | 5.19            | 38.60              | 43.50             | -4.90          | 360             | 100            | peak   |
| 3   | 607.7867           | 25.63               | 16.73           | 42.36              | 46.00             | -3.64          | 360             | 100            | peak   |
| 4   | 734.4913           | 26.44               | 18.02           | 44.46              | 46.00             | -1.54          | 360             | 100            | peak   |
| 5   | 857.0247           | 24.90               | 20.08           | 44.98              | 46.00             | -1.02          | 360             | 100            | peak   |

Spurious Emission From 30 MHz to 1 GHz

Test mode: Transmitting (802.11g) High Channel(2462MHz)


Comment:

Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 95.4270            | 26.46               | 8.09            | 34.55              | 43.50             | -8.95          | 360             | 100            | peak   |
| 2   | 124.5690           | 31.29               | 5.32            | 36.61              | 43.50             | -6.89          | 360             | 100            | peak   |
| 3   | 251.1804           | 31.75               | 8.72            | 40.47              | 46.00             | -5.53          | 360             | 100            | peak   |
| 4   | 366.8231           | 28.03               | 10.99           | 39.02              | 46.00             | -6.98          | 360             | 100            | peak   |
| 5   | 607.7867           | 27.57               | 16.73           | 44.30              | 46.00             | -1.70          | 360             | 100            | peak   |
| 6   | 734.4913           | 26.69               | 18.02           | 44.71              | 46.00             | -1.29          | 360             | 100            | peak   |
| 7   | 857.0247           | 22.60               | 20.08           | 42.68              | 46.00             | -3.32          | 360             | 100            | peak   |

Vertical



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 101.6443           | 30.64               | 8.29            | 38.93              | 43.50             | -4.57          | 360             | 100            | peak   |
| 2   | 124.5690           | 33.59               | 5.32            | 38.91              | 43.50             | -4.59          | 360             | 100            | peak   |
| 3   | 607.7867           | 26.13               | 16.73           | 42.86              | 46.00             | -3.14          | 360             | 100            | peak   |
| 4   | 734.4913           | 26.44               | 18.02           | 44.46              | 46.00             | -1.54          | 360             | 100            | peak   |
| 5   | 857.0247           | 24.18               | 20.08           | 44.26              | 46.00             | -1.74          | 360             | 100            | peak   |

*Spurious Emission above 1GHz**Test Mode: Transmitting (802.11b)*

| Frequency<br>MHz         | Detector | Meter<br>Reading<br>dBuV | Direction<br>Degree | Polar<br>H / V | Antenna<br>Loss<br>dB | Cable loss<br>dB | Amplifier<br>dB | Correction<br>Amplitude<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB |
|--------------------------|----------|--------------------------|---------------------|----------------|-----------------------|------------------|-----------------|-----------------------------------|-----------------|--------------|
| Low Channel (2412MHz)    |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4824.0                   | PK       | 46.04                    | 90                  | V              | 34.1                  | 5.2              | 33.0            | 52.34                             | 74              | -21.66       |
| 4824.0                   | PK       | 49.56                    | 270                 | H              | 34.1                  | 5.2              | 33.0            | 55.86                             | 74              | -18.14       |
| 7236.0                   | PK       | 36.52                    | 180                 | V              | 37.4                  | 6.1              | 33.5            | 46.52                             | 74              | -27.48       |
| 7236.0                   | PK       | 37.43                    | 45                  | H              | 37.4                  | 6.1              | 33.5            | 47.43                             | 74              | -26.57       |
| 4824.0                   | AV       | 28.62                    | 270                 | V              | 34.1                  | 5.2              | 33.0            | 34.92                             | 54              | -19.08       |
| 4824.0                   | AV       | 31.89                    | 90                  | H              | 34.1                  | 5.2              | 33.0            | 38.19                             | 54              | -15.81       |
| 7236.0                   | AV       | 25.57                    | 45                  | V              | 37.4                  | 6.1              | 33.5            | 35.57                             | 54              | -18.43       |
| 7236.0                   | AV       | 25.32                    | 60                  | H              | 37.4                  | 6.1              | 33.5            | 35.32                             | 54              | -18.68       |
| Middle Channel (2437MHz) |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4874.0                   | PK       | 50.16                    | 45                  | V              | 34.1                  | 5.2              | 33.0            | 56.46                             | 74              | -17.54       |
| 4874.0                   | PK       | 40.78                    | 270                 | H              | 34.1                  | 5.2              | 33.0            | 47.08                             | 74              | -26.92       |
| 7311.0                   | PK       | 37.00                    | 45                  | V              | 37.4                  | 6.1              | 33.5            | 47.00                             | 74              | -27.00       |
| 7311.0                   | PK       | 37.47                    | 180                 | H              | 37.4                  | 6.1              | 33.5            | 47.47                             | 74              | -26.53       |
| 4874.0                   | AV       | 32.24                    | 270                 | V              | 34.1                  | 5.2              | 33.0            | 38.54                             | 54              | -15.46       |
| 4874.0                   | AV       | 27.18                    | 90                  | H              | 34.1                  | 5.2              | 33.0            | 33.48                             | 54              | -20.52       |
| 7311.0                   | AV       | 25.44                    | 60                  | V              | 37.4                  | 6.1              | 33.5            | 35.44                             | 54              | -18.56       |
| 7311.0                   | AV       | 25.52                    | 45                  | H              | 37.4                  | 6.1              | 33.5            | 35.52                             | 54              | -18.48       |
| High Channel (2462MHz)   |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4924.0                   | PK       | 49.67                    | 270                 | V              | 34.1                  | 5.2              | 33.0            | 55.97                             | 74              | -18.03       |
| 4924.0                   | PK       | 51.11                    | 45                  | H              | 34.1                  | 5.2              | 33.0            | 57.41                             | 74              | -16.59       |
| 7386.0                   | PK       | 44.99                    | 180                 | V              | 37.4                  | 6.1              | 33.5            | 54.99                             | 74              | -19.01       |
| 7386.0                   | PK       | 37.26                    | 45                  | H              | 37.4                  | 6.1              | 33.5            | 47.26                             | 74              | -26.74       |
| 4924.0                   | AV       | 30.33                    | 90                  | V              | 34.1                  | 5.2              | 33.0            | 36.63                             | 54              | -17.37       |
| 4924.0                   | AV       | 32.57                    | 270                 | H              | 34.1                  | 5.2              | 33.0            | 38.87                             | 54              | -15.13       |
| 7386.0                   | AV       | 17.05                    | 60                  | V              | 37.4                  | 6.1              | 33.5            | 27.05                             | 54              | -26.95       |
| 7386.0                   | AV       | 25.64                    | 60                  | H              | 37.4                  | 6.1              | 33.5            | 35.64                             | 54              | -18.36       |

*Spurious Emission Above 1GHz**Test Mode: Transmitting (802.11g)*

| Frequency<br>MHz         | Detector | Meter<br>Reading<br>dBuV | Direction<br>Degree | Polar<br>H / V | Antenna<br>Loss<br>dB | Cable loss<br>dB | Amplifier<br>dB | Correction<br>Amplitude<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB |
|--------------------------|----------|--------------------------|---------------------|----------------|-----------------------|------------------|-----------------|-----------------------------------|-----------------|--------------|
| Low Channel (2412MHz)    |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4824.0                   | PK       | 42.65                    | 90                  | V              | 34.1                  | 5.2              | 33.0            | 48.95                             | 74              | 25.05        |
| 4824.0                   | PK       | 35.07                    | 270                 | H              | 34.1                  | 5.2              | 33.0            | 41.37                             | 74              | 32.63        |
| 7236.0                   | PK       | 35.34                    | 180                 | V              | 37.4                  | 6.1              | 33.5            | 45.34                             | 74              | 28.66        |
| 7236.0                   | PK       | 38.51                    | 45                  | H              | 37.4                  | 6.1              | 33.5            | 48.51                             | 74              | 25.49        |
| 4824.0                   | AV       | 28.78                    | 270                 | V              | 34.1                  | 5.2              | 33.0            | 35.08                             | 54              | 18.92        |
| 4824.0                   | AV       | 30.51                    | 90                  | H              | 34.1                  | 5.2              | 33.0            | 36.81                             | 54              | 17.19        |
| 7236.0                   | AV       | 29.21                    | 45                  | V              | 37.4                  | 6.1              | 33.5            | 39.21                             | 54              | 14.79        |
| 7236.0                   | AV       | 26.24                    | 60                  | H              | 37.4                  | 6.1              | 33.5            | 36.24                             | 54              | 17.76        |
| Middle Channel (2437MHz) |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4874.0                   | PK       | 43.31                    | 45                  | V              | 34.1                  | 5.2              | 33.0            | 49.61                             | 74              | 24.39        |
| 4874.0                   | PK       | 38.48                    | 270                 | H              | 34.1                  | 5.2              | 33.0            | 44.78                             | 74              | 29.22        |
| 7311.0                   | PK       | 46.39                    | 45                  | V              | 37.4                  | 6.1              | 33.5            | 56.39                             | 74              | 17.61        |
| 7311.0                   | PK       | 47.71                    | 180                 | H              | 37.4                  | 6.1              | 33.5            | 57.71                             | 74              | 16.29        |
| 4874.0                   | AV       | 30.41                    | 270                 | V              | 34.1                  | 5.2              | 33.0            | 36.71                             | 54              | 17.29        |
| 4874.0                   | AV       | 24.97                    | 90                  | H              | 34.1                  | 5.2              | 33.0            | 31.27                             | 54              | 22.73        |
| 7311.0                   | AV       | 25.27                    | 60                  | V              | 37.4                  | 6.1              | 33.5            | 35.27                             | 54              | 18.73        |
| 7311.0                   | AV       | 29.15                    | 45                  | H              | 37.4                  | 6.1              | 33.5            | 39.15                             | 54              | 14.85        |
| High Channel (2462MHz)   |          |                          |                     |                |                       |                  |                 |                                   |                 |              |
| 4924.0                   | PK       | 45.31                    | 270                 | V              | 34.1                  | 5.2              | 33.0            | 51.61                             | 74              | 22.39        |
| 4924.0                   | PK       | 43.27                    | 45                  | H              | 34.1                  | 5.2              | 33.0            | 49.57                             | 74              | 24.43        |
| 7386.0                   | PK       | 38.47                    | 180                 | V              | 37.4                  | 6.1              | 33.5            | 48.47                             | 74              | 25.53        |
| 7386.0                   | PK       | 39.81                    | 45                  | H              | 37.4                  | 6.1              | 33.5            | 49.81                             | 74              | 24.19        |
| 4924.0                   | AV       | 28.96                    | 90                  | V              | 34.1                  | 5.2              | 33.0            | 35.26                             | 54              | 18.74        |
| 4924.0                   | AV       | 30.54                    | 270                 | H              | 34.1                  | 5.2              | 33.0            | 36.84                             | 54              | 17.16        |
| 7386.0                   | AV       | 24.62                    | 60                  | V              | 37.4                  | 6.1              | 33.5            | 34.62                             | 54              | 19.38        |
| 7386.0                   | AV       | 25.21                    | 60                  | H              | 37.4                  | 6.1              | 33.5            | 35.21                             | 54              | 18.79        |

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5<sup>th</sup> Harmonics is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.*

*The measurements greater than 20dB below the limit from 9kHz to 30MHz..*



## 9. OUT OF BAND EMISSIONS

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 9.2 Test Equipment List and Details

| Description              | Manufacturer         | Model    | Serial Number | Cal. Date  | Due. Date  |
|--------------------------|----------------------|----------|---------------|------------|------------|
| Spectrum Analyzer        | R&S                  | FSP      | 836079/035    | 2010-12-20 | 2011-12-19 |
| EMI Test Receiver        | R&S                  | ESVB     | 825471/005    | 2010-12-20 | 2011-12-19 |
| Positioning Controller   | C&C                  | CC-C-1F  | N/A           | 2010-12-20 | 2011-12-19 |
| RF Switch                | EM                   | EMSW18   | SW060023      | 2010-12-20 | 2011-12-19 |
| Pre-amplifier            | Agilent              | 8447F    | 3113A06717    | 2010-12-20 | 2011-12-19 |
| Pre-amplifier            | Compliance Direction | PAP-0118 | 24002         | 2010-12-20 | 2011-12-19 |
| Trilog Broadband Antenna | SCHWARZBECK          | VULB9163 | 9163-333      | 2011-01-09 | 2012-01-08 |
| Horn Antenna             | ETS                  | 3117     | 00086197      | 2011-01-09 | 2012-01-08 |

### 9.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW, VBW=100KHz, Span=50MHz, Sweep = auto
3. Set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2438.5MHz, then mark the higher-level emission for comparing with the FCC rules.


### 9.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 21° C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

**9.5 Summary of Test Results/Plots**


| Test mode | Frequency<br>MHz | Limit<br>dBuV /dB | Result |
|-----------|------------------|-------------------|--------|
| 802.11b   | 2390.00          | <54dBuv           | Pass   |
|           | 2400.00          | >20dB ATT         | Pass   |
|           | 2483.50          | <54dBuv           | Pass   |
| 802.11g   | 2390.00          | <54dBuv           | Pass   |
|           | 2400.00          | >20dB ATT         | Pass   |
|           | 2483.50          | <54dBuv           | Pass   |

For 802.11b  
Lowest Bandedge




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 2310.000  | 31.46    | -4.65   | 26.81    | 54.00    | -27.19 | 360    | 100    | Ave    |
|     | 2310.000  | 53.49    | -4.65   | 48.84    | 74.00    | -25.16 | 360    | 100    | Peak   |
| 2   | 2359.920  | 35.24    | -4.53   | 30.71    | 54.00    | -23.29 | 360    | 100    | Ave    |
|     | 2359.920  | 51.22    | -4.53   | 46.69    | 74.00    | -27.31 | 360    | 100    | Peak   |
| 3   | 2390.000  | 34.51    | -4.46   | 30.05    | 54.00    | -23.95 | 360    | 100    | Ave    |
|     | 2390.000  | 53.31    | -4.46   | 48.85    | 74.00    | -25.15 | 360    | 100    | Peak   |
| 4   | 2396.640  | 42.20    | -4.44   | 37.76    | 54.00    | -16.24 | 360    | 100    | Ave    |
|     | 2396.640  | 58.18    | -4.44   | 53.74    | 74.00    | -20.26 | 360    | 100    | Peak   |
| 5   | 2400.000  | 43.26    | -4.43   | 38.83    | 54.00    | -15.17 | 360    | 100    | Ave    |
|     | 2400.000  | 55.76    | -4.43   | 51.33    | 74.00    | -21.67 | 360    | 100    | Peak   |

Highest Bandedge




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 2483.500  | 38.21    | -4.23   | 33.98    | 54.00    | -20.02 | 360    | 100    | Ave    |
|     | 2483.500  | 52.87    | -4.23   | 48.64    | 74.00    | -25.36 | 360    | 100    | Peak   |
| 2   | 2500.000  | 32.97    | -4.18   | 28.79    | 54.00    | -25.21 | 360    | 100    | Ave    |
|     | 2500.000  | 56.72    | -4.18   | 52.54    | 74.00    | -21.45 | 360    | 100    | Peak   |

For 802.11g  
Lowest Bandedge



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 2310.000  | 31.50    | -4.65   | 26.85    | 54.00    | -27.15 | 360    | 100    | Ave    |
|     | 2310.000  | 52.38    | -4.65   | 47.73    | 74.00    | -26.27 | 360    | 100    | Peak   |
| 2   | 2359.920  | 36.96    | -4.53   | 32.43    | 54.00    | -21.57 | 360    | 100    | Ave    |
|     | 2359.920  | 56.20    | -4.53   | 51.67    | 74.00    | -22.33 | 360    | 100    | Peak   |
| 3   | 2390.000  | 33.18    | -4.46   | 28.72    | 54.00    | -25.28 | 360    | 100    | Ave    |
|     | 2390.000  | 56.98    | -4.46   | 52.52    | 74.00    | -21.48 | 360    | 100    | Peak   |
| 4   | 2400.000  | 43.26    | -4.43   | 38.83    | 54.00    | -15.17 | 360    | 100    | Ave    |
|     | 2400.000  | 58.08    | -4.43   | 53.65    | 74.00    | -20.35 | 360    | 100    | Peak   |

Highest Bandedge



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 2483.500  | 38.75    | -4.23   | 34.52    | 54.00    | -19.48 | 360    | 100    | Ave    |
|     | 2483.500  | 56.99    | -4.23   | 52.76    | 74.00    | -21.24 | 360    | 100    | Peak   |
| 2   | 2500.000  | 34.02    | -4.18   | 29.84    | 54.00    | -24.16 | 360    | 100    | Ave    |
|     | 2500.000  | 59.26    | -4.18   | 55.08    | 74.00    | -18.92 | 360    | 100    | Peak   |

\*\*\*\*\* END OF REPORT \*\*\*\*\*