

封装 ( encapsulation )	元件值	数量 ( PCS )
0603电阻 ( resistance )	0R	3
	100R	7
	220R	1
	560R	1
	1K	3
	1K5	1
	3K3	3
	5K6	1
	10K	15
	15K	1
	22K	6
	33K	5
	39K	1
	47K	1
	68K	1
	100K	2
	220K	2
	1M	3
0603电容 ( capacitance )	1P	2
	1.5P	1
	2P	1
	3P	1
	4P	1
	6P	1
	10P	1
	20P	4
	22P	1
	30P	2
	47P	1
	100P	9
	102P	3
	103P	4
	104P	29
	200P	1
	222P	1
	470P	2
1206无极电容 ( Non-polar capacitor )	105	1
	106	2
0805层叠电感 ( Cascade inductance )	1UH	2
0603层叠电感 ( Cascade inductance )	8.2UH	7
0805线绕电感 ( inductance )	8N2	1
	10NH	3
	18NH	1
	68NH	2
	100uf /C 6.3V	2
	1UF /A 16V	1

钽电容 (Tantalum capacitor)	2.2UF/A 16V	1
	10UF/A 16V	18
	22UF/A 16V	2
贴片可调电容 (patch capacitance)	5-30P	1
贴片可调电阻 (patch resistance)	10K	1
	100K	1
0603二极管 (diode)	IN4148	2
贴片二极管 (patch diode)	HVC316	2
贴片三极管 (Patch transistor)	9013 (J3)	3
	2SC3585(R43)	1
	9014(J6)	1
	2907(2F)	1
	2SJ486	3
	2SC4226(R24)	2
贴片IC (patch IC)	UTC4558	1
	NE571	1
	MB15E03	1
	HX3001	1
	ATMEGA48V-10AV	1
贴片变容管 (Patch transfiguration tube)	HVC316	2
贴片升压线圈 (Patch boost coil)	2R2	1
	100UH	1
贴片晶体(49S) (Patch crystal)	10M	1
	8.192M/8M	1
900合金管 (900 Alloy tube)		2
900网头 (900 WangTou)	黑色 (black)	2
米芯 (M core)	D36	2
液晶屏 (LCD screen)	FL-1051-LB (1)	2
LED背光源 (LED back light)	BL038016-1B	2
显示屏线路板 (Display circuit board)	LB-1051LCD	2
海绵垫 (The sea MianDian)	10*10*2	2
网棉 (Nets cotton)	5.5	2
电池片 (Cells in)	Positive	2
电池片 (Cells in)	Negative	2
弹簧天 (Spring antenna)		2
8CM软排线黄白 (Soft line huangbai)	2P*8CM*19pcs	2
黑螺丝 (Black screw)		2
900开关贴纸 (900 Switch 1 paper)		2
900功能贴纸 (900 Function sticker)		2
红外接收管 (Infrared receiving tube)	HSIR38S-43	2
滴胶 (A glue)		2
贴片VCO	LCS-680	1
<b>补件：</b>		
红外接收管(Infrared receiving tube)		1
开关 (switch)	SS12D07VG4	1

开关(switch)	SK22D07VG3	1
轻触开关 (Light touch switch)	6*3*4.3	3
屏蔽壳 (Shielding shell)	17*17	1