



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No.:** CQASZ20180100001EW-02  
**Applicant:** Weccan Industrial Limited  
**Address of Applicant:** Rm209,2/F,Building W1-A, No.34 Gaoxin South 4th Street, Hi-Tech Industrial Park, Nanshan District, Shenzhen City,China  
**Manufacturer:** Weccan Industrial Limited  
**Address of Manufacturer:** Rm209,2/F,Building W1-A, No.34 Gaoxin South 4th Street, Hi-Tech Industrial Park, Nanshan District, Shenzhen City,China  
**Factory:** Dongguan Adoree Industrial Limited  
**Address of Factory:** Building 10, Fuxing Industrial Area, Fuxing Road, Xiagang Village, Changan Town, Dongguan City, Guangdong Province, China

### Equipment Under Test (EUT):


**Product:** 2.4G RC DRONE  
**Model No.:** All models please see page 2  
**Test Model No.:** SG-F8  
**Brand Name:** SKY KING  
**FCC ID:** Z3CWECCAN-RCDRONE  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06

**Date of Test:** 2018-01-10 to 2018-01-15

**Date of Issue:** 2018-01-15

**Test Result :** PASS\*


**Tested By:**

  
(Aaron Ma)

**Reviewed By:**

  
(Owen Zhou)

**Approved By:**

  
( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 2 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180100001EW-02	Rev.01	Initial report	2018-01-15

Note:

1. All Models: 64354, SG-F8, SG-F1, SG-F2, SG-F5, SG-6, SG-F7, SG-F9, SG-F10, SG-F12, SG-F16, SG-F17, SG-F18, SG-F19, SG-F20, SG-F21, SG-F22, SG-F25, SG-F26, SG-F27, SG-F28, SG-F30, SG-F31, SG-F33, SG-F35, SG-F36, SG-F37, SG-F38, SG-F39, SG-F41, SG-F42, SG-F43, SG-F45, SG-F46, SG-F47, SG-F48, SG-F49, SG-F51, SG-F52, SG-F53, SG-F54, SG-F55, SG-F57, SG-F60, SG-F62, SG-F65, SG-F66, SG-F67, SG-F70, SG-F71, SG-F72, SG-F73, SG-F74, SG-F76, SG-F77, SG-F78, SG-F79, SG-F81, SG-F88, SG-F98

Only the model SG-F8 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

### 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT .....	4
5 SAR EVALUATION .....	5
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
5.1.1 <i>Standard Requirement</i> .....	5
5.1.2 <i>Limits</i> .....	5
5.1.3 <i>EUT RF Exposure</i> .....	5

## 4 General Information

### 4.1 Client Information

Applicant:	Weccan Industrial Limited
Address of Applicant:	Rm209,2/F,Building W1-A, No.34 Gaoxin South 4th Street, Hi-Tech Industrial Park, Nanshan District, Shenzhen City,China
Manufacturer:	Weccan Industrial Limited
Address of Manufacturer:	Rm209,2/F,Building W1-A, No.34 Gaoxin South 4th Street, Hi-Tech Industrial Park, Nanshan District, Shenzhen City,China
Factory:	Dongguan Adoree Industrial Limited
Address of Factory:	Building 10, Fuxing Industrial Area, Fuxing Road, Xiagang Village, Changan Town, Dongguan City, Guangdong Province, China

### 4.2 General Description of EUT

Name:	2.4G RC DRONE
Model No.:	All models please see page 2
Test Model No.:	SG-F8
Trade Mark :	SKY KING
Hardware Version:	F8TX-2
Software Version:	V16.0
Frequency Range:	2406 MHz ~ 2473MHz
Modulation Type:	GFSK
Number of Channels:	3 (declared by the client)
Sample Type:	Portable production
Test Software of EUT:	RF test (manufacturer declare )
Antenna Type:	Integral antenna
Antenna Gain:	0.8dBi
Power Supply:	2 x AAA battery, DC3V

## 5 SAR Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{[\sqrt{f(\text{GHz})}]} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where} \right.$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 5.1.3 EUT RF Exposure

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,  $10^{((\text{dB}\mu\text{V}/\text{m})/20)}/10^6$ ,

d = measurement distance in meters (m)---3m,

$$\text{So pt} = (\text{E} \times \text{d})^2 / 30 / \text{gt}$$

The worst case (refer to report CQASZ20180100001EW-01) is below:

For 2.4G wireless:

Field strength = 97.5dB $\mu$ V/m @3m

Ant. gain 0.8dBi; so Ant numeric gain=1.2

$$\text{So pt} = \{ [10^{(97.5/20)} / 10^6 \times 3]^2 / 30 / 1.2 \} \times 1000\text{mW} = 1.403\text{mW}$$

$$\text{So } (1.403\text{mW}/5\text{mm}) \times \sqrt{2.473\text{GHz}} = 0.441,$$

0.441 < 3.0 for 1-g SAR

So the SAR report is not required.