40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate Antenna (AA222) **Engineering Specification**

1. **Explanation of Product Number**

(1) (2) (3) **(4)** (5)



Product Code:

(1) Product Applications:

P: WiFi Dual Band antenna

(2) Dimensions:

D1: 40.0 x 6.0 x 0.5(mm)

(3) Material:

A: GF

(4) Working Frequencies:

1C: 2400~2500 & 4900~5900 MHz

(5) Antenna Series:

01: serial number

Unictron Technologies Corp.

2014-06-30



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT **PERMISSION**

Prepared by : Ann **Designed by: Chinling** Checked by: Chinling Approved by : Herbert UNIT: mm TITLE: 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate

Antenna (AA222) Engineering Specification

DOCUMENT NO.

H2B1PD1A1C0100

REV. G

2. Features

- *Stable and reliable in performances
- *Compact size
- *RoHS compliance

Applications

- * IEEE802.11n (a/b/g).
- * Hand-held devices when WiFi(802.11n/a/b/g) functions are needed.

4. Description

Unictron's antenna series are specially designed for WiFi(802.11n/a/b/g) applications. Based on Unictron's proprietary design and processes, this antenna has excellent stability and sensitivity to consistently provide high signal reception efficiency.

5. Operating Condition:

Temperature -10 to +85 °C (With double-sided tape)

- 40 to +85 °C (Without double-sided tape)

Humidity 10 to 95% RH

6. Storage Condition:

Temperature -10 to +85 °C (With double-sided tape)

- 40 to +85 °C (Without double-sided tape)

Humidity 10 to 95% RH

7. Electrical Specifications

7-1. 2400~2500 MHz Band

Chara	cteristics	Specifications	Unit		
Outline Dimens	sions	40.0 x 6.0 x 0.5	mm		
Working Frequ	ency	2400~2500	MHz		
Bandwidth		100 (min)	MHz		
VSWR (@Cente	r Frequency)*	2 (max)			
Impedance		50	Ω		
Polarization		Linear Polarization			
Gain	Peak	2.6 (typical)	dBi		
Gairi	Efficiency	79 (typical)	O Unictron Technologies C		

^{*} Center frequency will be offset to another frequency according to the conditions of user's ground plane and radome 30

Document

Control Center



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann	Prepared by : Ann Designed by : Chinling Cl			Approved by : Herbert	UNIT : mm
	0.5 (mm) WiFi Dual Band PCB		DOCUMENT	H2B1PD1A1C0100	REV.
Antenna (A	A222) Engineering Specification	on	NO.	112211211100100	G

^{*} Bandwidth &VSWR are tested at Unitron test environment .

7-2. 4900~5900 MHz Band


Charac	teristics	Specifications	Unit
Working Freque	ncy	4900~5900	MHz
Bandwidth **		1000 (min)	MHz
VSWR (@Center	Frequency)*	2 (max)	
Impedance		50	Ω
Polarization		Linear Polarization	
Gain	Peak	3.3 (typical)	dBi
Gain	Efficiency	79 (typical)	%

^{*} Center frequency will be offset to another frequency according to the conditions of user's ground plane and radome.

7-3. Return Loss & VSWR

Return Loss (S₁₁)

VSWR (S₁₁)



Unictron
Technologies Corp.

2014-06-30

Document



詠業科技股份有限公司


Unictron Technologies Corporation Website:www.unictron.com


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : A	nn Designed by : Chinling	Checked	by : Chinling	Approved by : Herbert	UNIT: mm
	.0 x 0.5 (mm) WiFi Dual Band PCB		DOCUMENT	H2B1PD1A1C0100	REV.
Antenn	a (AA222) Engineering Specification	on	NO.		G

^{*} Bandwidth &VSWR are tested at Unitron test environment .

8. Antenna Dimensions (unit: mm)







Side View

Unictron
Technologies Corp.

2014-06-30

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm

TITLE: 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate
Antenna (AA222) Engineering Specification


DOCUMENT NO.


H2B1PD1A1C0100


REV.


9. Radiation Pattern

9-1.2400~2500 MHz Band 9-1-1.3D Gain Pattern @ 2442 MHz (unit: dBi)











詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm

TITLE : 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate DOCUMENT H2B1PD1A1C0100 REV.

Antenna (AA222) Engineering Specification


NO.

H2B1PD1A1C0100

G

9-1-2. 3D Efficiency Table															
Frequency(GHz)	2.400	2.412	2.417	2.422	2.427	2.432	2.437	2.442	2.447	2.452	2.457	2.462	2.467	2.472	2.484
Efficiency(dB)	-1.49	-1.45	-1.32	-1.44	-1.36	-1.15	-1.11	-0.97	-1.06	-1.02	-0.89	-0.69	-0.71	-0.89	-0.75
Efficiency(%)	70.96	71.61	73.79	71.78	73.11	76.74	77.45	79.98	78.31	79.10	81.51	85.26	84.83	81.51	84.20
Gain(dBi)	2.11	2.21	2.34	2.26	2.33	2.49	2.52	2.68	3.07	3.21	3.50	3.73	3.69	3.39	3.42

9-1-3. 3D Efficiency vs. Frequency



Unictron
Technologies Corp.

2014-06-30

Document

G



Antenna (AA222) Engineering Specification

詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm


TITLE : 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate DOCUMENT H2B1PD1A1C0100 REV.


NO.


9-2.4900~5900 MHz Band

9-2-1.3D Gain Pattern @ 5150 MHz (unit: dBi)











詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm


TITLE : 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate Antenna (AA222) Engineering Specification NO.


DOCUMENT NO.


H2B1PD1A1C0100


G

9-2-2.3D Gain Pattern @ 5350 MHz (unit: dBi)









Document Control Cente



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm


TITLE: 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate
Antenna (AA222) Engineering Specification


DOCUMENT NO.


H2B1PD1A1C0100


REV.

9-2-3.3D Gain Pattern @ 5700 MHz (unit: dBi)











詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT **PERMISSION**

Prepared by : Ann **Designed by: Chinling** Checked by: Chinling Approved by : Herbert UNIT: mm


TITLE: 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate **Antenna (AA222) Engineering Specification**


DOCUMENT NO.


H2B1PD1A1C0100


REV. G

9-2-4.3D Gain Pattern @ 5850 MHz (unit: dBi)









Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm

TITLE: 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate
Antenna (AA222) Engineering Specification

DOCUMENT NO.

H2B1PD1A1C0100


REV.

9-2-5. 3D Efficiency Table

Frequency(GHz)	4.900	4.950	5.000	5.050	5.100	5.150	5.200	5.250	5.300	5.350	5.400
Efficiency(dB)	-1.02	-1.25	-1.45	-1.41	-1.44	-1.15	-0.97	-1.07	-1.11	-0.66	-0.99
Efficiency(%)	79.07	74.99	71.61	72.28	71.78	76.74	79.98	78.10	77.50	85.95	79.62
Gain(dBi)	3.23	2.74	2.30	2.56	2.83	3.20	3.46	3.72	3.30	3.39	3.36

Frequency(GHz)	5.450	5.500	5.550	5.600	5.650	5.700	5.750	5.800	5.850	5.900
Efficiency(dB)	-1.81	-1.87	-1.41	-1.26	-1.93	-1.85	-1.53	-1.33	-0.80	-1.23
Efficiency(%)	65.92	65.01	72.28	74.82	64.09	65.37	70.31	73.62	83.11	75.34
Gain(dBi)	2.47	2.97	3.49	3.79	2.60	3.06	3.74	3.91	5.18	3.98

9-2-6. 3D Efficiency vs. Frequency



Unictron
Technologies Corp.

2014-06-30

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Ann Designed by : Chinling Checked by : Chinling Approved by : Herbert UNIT : mm

TITLE : 40.0 x 6.0 x 0.5 (mm) WiFi Dual Band PCB Substrate Antenna (AA222) Engineering Specification NO.

H2B1PD1A1C0100

G