



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	AirTies Wireless Networks
Applicant Address	Gülbahar Mah. Avni Dilligil Sok. Celik Is Merkezi ISTANBUL, 34394 Turkey
FCC ID	Z3WAIR4820
Manufacturer's company	SHENZHEN GONGJIN ELECTRONICS CO.,LTD.
Manufacturer Address	2F/3F/4F Baiying Building, 1019#Naihai RD, Nanshan Dist., Shenzhen, Guangdong, CHINA

Product Name	2 Port Gigabit Ethernet 11ac/11n Wireless Router
Brand Name	AirTies
Model No.	Air 4820
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250MHz
Received Date	Apr. 02, 2014
Final Test Date	Nov. 27, 2014
Submission Type	Original Equipment
Operating Mode	Master

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart E, KDB789033 D01 v01r04, KDB662911 D01 v02r01, KDB644545 D01 v01r02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	8
3.7. Table for Supporting Units	8
3.8. Table for Parameters of Test Software Setting	9
3.9. EUT Operation during Test	9
3.10. Duty Cycle.....	10
3.11. Test Configurations	11
4. TEST RESULT	14
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	18
4.3. Maximum Conducted Output Power Measurement.....	26
4.4. Power Spectral Density Measurement	29
4.5. Radiated Emissions Measurement	36
4.6. Band Edge Emissions Measurement	51
4.7. Frequency Stability Measurement	56
4.8. Antenna Requirements	58
5. LIST OF MEASURING EQUIPMENTS	59
6. MEASUREMENT UNCERTAINTY.....	60
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR440257-01AB	Rev. 01	Initial issue of report	Dec. 12, 2014

1. CERTIFICATE OF COMPLIANCE

Product Name : 2 Port Gigabit Ethernet 11ac/11n Wireless Router
Brand Name : AirTies
Model No. : Air 4820
Applicant : AirTies Wireless Networks
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Apr. 02, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	14.13 dB
4.2	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	0.09 dB
4.4	15.407(a)	Power Spectral Density	Complies	0.04 dB
4.5	15.407(b)	Radiated Emissions	Complies	0.10 dB
4.6	15.407(b)	Band Edge Emissions	Complies	0.22 dB
4.7	15.407(g)	Frequency Stability	Complies	-
4.8	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	5150 ~ 5250MHz
Channel Number	4 for 20MHz bandwidth ; 2 for 40MHz bandwidth 1 for 80MHz bandwidth
Channel Band Width (99%)	<u>For Beamforming Mode</u> 802.11ac MCS0/Nss1 (VHT20): 17.95 MHz ; 802.11ac MCS0/Nss1 (VHT40): 37.28 MHz ; 802.11ac MCS0/Nss1 (VHT80): 75.95 MHz
Maximum Conducted Output Power	<u>For Beamforming Mode</u> 802.11ac MCS0/Nss1 (VHT20): 16.11 dBm ; 802.11ac MCS0/Nss1 (VHT40): 16.09 dBm ; 802.11ac MCS0/Nss1 (VHT80): 16.04 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5150 ~ 5250MHz
Channel Number	4
Channel Band Width (99%)	<u>For Non Beamforming Mode</u> 16.32 MHz
Maximum Conducted Output Power	<u>For Non Beamforming Mode</u> 16.83 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Communication Mode	<input checked="" type="checkbox"/> IP Based (Load Based) <input type="checkbox"/> Frame Based
Beamforming Function	<input checked="" type="checkbox"/> With beamforming for 802.11n/ac. <input type="checkbox"/> Without beamforming

Antenna and Band width

Antenna	Four (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	4	MCS 0-31
802.11n (HT40)	4	MCS 0-31
802.11ac (VHT20)	4	MCS 0-9/Nss1-4
802.11ac (VHT40)	4	MCS 0-9/Nss1-4
802.11ac (VHT80)	4	MCS 0-9/Nss1-4

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Power	Brand	Model	Rating
Adapter	MOSO	MSP-C1500IC12.0-18W-US	Input: 100-240V ~ 50/60Hz 0.7A max Output: 12.0V, 1.5A
Other			
RJ-45 Cable*1: Non-shielded, 1.5m			


3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					5150MHz ~ 5250MHz	5725MHz ~ 5850MHz
1	Airties	Airties#1	Printed Antenna	N/A	0.44	1.03
2	Airties	Airties#1	Printed Antenna	N/A	0.44	1.03
3	Airties	Airties#1	Printed Antenna	N/A	0.44	1.03
4	Airties	Airties#1	Printed Antenna	N/A	0.44	1.03

Note: The EUT has four antennas.

Ant.1, Ant.2, Ant.3 and Ant.4 will transmit/receive the same signal simultaneously.

Ant.1, Ant.2, Ant.3 and Ant.4 can be used as transmitting/receiving antennas



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

For 80MHz bandwidth systems, use Channel 42.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Antenna
AC Power Conducted Emission	Normal Link		-	-	-
Max. Conducted Output Power	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
Power Spectral Density	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
Peak Excursion	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
Radiated Emission Below 1GHz	Normal Link		-	-	-
Radiated Emission Above 1GHz	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
Band Edge Emission	11ac VHT20	Band 1	MCS0/Nss1	36/40/48	1+2+3+4
	11ac VHT40	Band 1	MCS0/Nss1	38/46	1+2+3+4
	11ac VHT80	Band 1	MCS0/Nss1	42	1+2+3+4
	11a/BPSK	Band 1	6Mbps	36/40/48	1+2+3+4
Frequency Stability	Un-modulation		-	40	1+2+3+4

Note 1: VHT20/VHT40 covers HT20/HT40, due to same modulation.

Note 2: There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11n/ac, after evaluating, beamforming mode has been evaluated to be the worst case, so it was selected to test and record in this test report.

The following test modes were performed for all tests:

For Conducted Emission test and Radiated Emission test (Below 1G):

Mode 1. Normal Link

For Radiated Emission test (Above 1G):

Mode 1. CTX

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB (Below 1G)

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	DoC
Notebook	DELL	M1340	DoC

For Test Site No: 03CH01-CB (Above 1G)

For Non-Beamforming Mode:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	DoC

For Beamforming Mode:

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	DoC
Notebook	DELL	M1340	DoC
WLAN ac Dongle	Netgear	A6200	PY31220200

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook*2	DELL	E6430	DoC

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For Beamforming mode:

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

Test Software Version	DOS		
Frequency	5180 MHz	5200 MHz	5240 MHz
MCS0/Nss1 VHT20	12	12	12

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

Test Software Version	DOS	
Frequency	5190 MHz	5230 MHz
MCS0/Nss1 VHT40	12	12

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

Test Software Version	DOS
Frequency	5210 MHz
MCS0/Nss1 VHT80	12

For Non-Beamforming mode:

Power Parameters of IEEE 802.11a

Test Software Version	DOS		
Frequency	5180 MHz	5200 MHz	5240 MHz
802.11a	13	13	13

3.9. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.

The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe " to link with the remote workstation to receive and transmit packet by WLAN ac Dongle and transmit duty cycle no less 98%

3.10. Duty Cycle

For Beamforming Mode:


Band	Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
5G	802.11ac MCS0/Nss1 VHT20	3.880	4.000	97.00%	0.13	0.26
	802.11ac MCS0/Nss1 VHT40	1.720	1.760	97.73%	0.10	0.58
	802.11ac MCS0/Nss1 VHT80	3.820	3.940	96.95%	0.13	0.26

For Non-Beamforming Mode:

Band	Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
5G	802.11a	5.400	5.440	99.26%	0.03	0.01

3.11. Test Configurations

3.11.1. AC Power Line Conduction Emissions Test and Radiation Emissions Test (Below 1G) Configuration




Item	Connection	Shielded	Length	Remark
1	Power cable	No	1.5m	-
2	RJ-45 cable	No	1.5m	Load
3	RJ-45 cable	No	1.5m	-
4	RJ-45 cable	No	10m	-

3.11.2. Radiation Emissions Test Configuration

For Non-Beamforming mode:


Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

For Beamforming mode:

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	54%
Test Engineer	Sollo Luo	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.15000	33.87	-22.13	56.00	0.10	33.61	0.16	LINE	AVERAGE
2	0.15000	44.66	-21.34	66.00	0.10	44.40	0.16	LINE	QP
3	0.16677	43.62	-21.50	65.12	0.10	43.36	0.16	LINE	QP
4 @	0.16677	39.27	-15.85	55.12	0.10	39.01	0.16	LINE	AVERAGE
5	0.40850	34.23	-23.45	57.68	0.10	33.95	0.18	LINE	QP
6 @	0.40850	33.55	-14.13	47.68	0.10	33.27	0.18	LINE	AVERAGE
7	2.946	19.48	-36.52	56.00	0.19	19.01	0.28	LINE	QP
8	2.946	9.57	-36.43	46.00	0.19	9.10	0.28	LINE	AVERAGE
9	11.080	22.49	-37.51	60.00	0.36	21.74	0.39	LINE	QP
10	11.080	16.30	-33.70	50.00	0.36	15.55	0.39	LINE	AVERAGE
11	23.387	14.50	-45.50	60.00	0.48	13.47	0.55	LINE	QP
12	23.387	9.64	-40.36	50.00	0.48	8.61	0.55	LINE	AVERAGE

Temperature	23°C	Humidity	54%
Test Engineer	Sollo Luo	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.15403	40.59	-25.19	65.78	0.09	40.34	0.16	NEUTRAL	QP
2	0.15403	26.51	-29.27	55.78	0.09	26.26	0.16	NEUTRAL	AVERAGE
3	0.16854	42.76	-22.27	65.03	0.09	42.51	0.16	NEUTRAL	QP
4 B	0.16854	38.35	-16.68	55.03	0.09	38.10	0.16	NEUTRAL	AVERAGE
5	0.40615	30.30	-27.43	57.73	0.09	30.03	0.18	NEUTRAL	QP
6	0.40615	26.78	-20.95	47.73	0.09	26.51	0.18	NEUTRAL	AVERAGE
7	2.346	19.24	-36.76	56.00	0.15	18.83	0.26	NEUTRAL	QP
8	2.346	11.66	-34.34	46.00	0.15	11.25	0.26	NEUTRAL	AVERAGE
9	4.874	13.82	-32.18	46.00	0.22	13.28	0.32	NEUTRAL	AVERAGE
10	4.874	21.39	-34.61	56.00	0.22	20.85	0.32	NEUTRAL	QP
11	11.996	26.66	-33.34	60.00	0.35	25.91	0.40	NEUTRAL	QP
12	11.996	21.17	-28.83	50.00	0.35	20.42	0.40	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1 % of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.2.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.2.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

For Beamforming mode:

Temperature	26°C	Humidity	63%
Test Engineer	James Chou	Configurations	IEEE 802.11ac

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	22.49	17.95
40	5200 MHz	22.49	17.95
48	5240 MHz	22.49	17.95

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	43.13	37.28
46	5230 MHz	42.67	37.05

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
42	5210 MHz	81.16	75.95

For Non-Beamforming mode:


Temperature	26°C	Humidity	63%
Test Engineer	James Chou	Configurations	IEEE 802.11a

Configuration IEEE 802.11a / Ant.1 + Ant.2 + Ant.3 + Ant.4


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	19.71	16.32
40	5200 MHz	19.71	16.21
48	5240 MHz	19.59	16.21

For Beamforming mode:


26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 /
Ant.1 + Ant.2 + Ant.3 + Ant.4/ 5180 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 /
Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5200 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5240 MHz




26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5190 MHz



**26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 /
Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5230 MHz**




**26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 /
Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5210 MHz**




For Non-Beamforming mode:


26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5180 MHz



26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5200 MHz



26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5240 MHz



4.3. Maximum Conducted Output Power Measurement

4.3.1. Limit

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW (17dBm) or $4 \text{ dBm} + 10\log B$, where B is the 26 dB emissions bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D01 v01r04 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3) Measurement using a power meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Output Power

For Beamforming mode:

Temperature	26°C	Humidity	63%
Test Engineer	James Chou	Configurations	IEEE 802.11ac
Test Date	Nov. 27, 2014		

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3	Ant.4	Total		
36	5180 MHz	10.51	9.32	9.97	9.31	15.83	16.54	Complies
40	5200 MHz	10.32	9.06	10.03	9.93	15.88	16.54	Complies
48	5240 MHz	10.32	9.89	10.16	9.98	16.11	16.54	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46\text{dBi} > 6\text{dBi}$, So Band1 Limit = 17-(6.46-6)=16.54dBm

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3	Ant.4	Total		
38	5190 MHz	10.46	8.01	10.12	9.82	15.72	16.54	Complies
46	5230 MHz	10.68	8.52	10.72	10.03	16.09	16.54	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46\text{dBi} > 6\text{dBi}$, So Band1 Limit = 17-(6.46-6)=16.54dBm

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3	Ant.4	Total		
42	5210 MHz	10.36	9.75	10.38	9.54	16.04	16.54	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46\text{dBi} > 6\text{dBi}$, So Band1 Limit = 17-(6.46-6)=16.54dBm

For Non-Beamforming mode:

Temperature	26°C	Humidity	63%
Test Engineer	James Chou	Configurations	IEEE 802.11a
Test Date	Nov. 27, 2014		

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3	Ant.4	Total		
36	5180 MHz	11.59	8.98	10.97	9.46	16.40	16.95	Complies
40	5200 MHz	11.76	9.18	11.33	9.21	16.55	16.95	Complies
48	5240 MHz	11.56	9.64	11.86	9.68	16.83	16.92	Complies

Note:

5180MHz 26dB bandwidth(B)=19.71MHz < 20MHz ,so power limit= 4 + 10Log (19.71)=16.95dBm

5200MHz 26dB bandwidth(B)=19.71MHz < 20MHz ,so power limit= 4 + 10Log (19.71)=16.95dBm

5240MHz 26dB bandwidth(B)=19.59MHz < 20MHz ,so power limit= 4 + 10Log (19.59)=16.92dBm

4.4. Power Spectral Density Measurement

4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15~5.25 GHz	4

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D01 v01r04 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Peak power spectral density (PPSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

For Beamforming mode:

Temperature	26°C	Humidity	63%
Test Engineer	James Chou	Configurations	IEEE 802.11ac
Test Date	Nov. 27, 2014		

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	1.81	3.54	Complies
40	5200 MHz	2.05	3.54	Complies
48	5240 MHz	2.26	3.54	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46 \text{ dBi} > 6 \text{ dBi}$, So Band1 Limit = 4-(6.46-6)=3.54dBm/MHz

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	-0.99	3.54	Complies
46	5230 MHz	-0.62	3.54	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46 \text{ dBi} > 6 \text{ dBi}$, So Band1 Limit = 4-(6.46-6)=3.54dBm/MHz

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210 MHz	-3.35	3.54	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46 \text{ dBi} > 6 \text{ dBi}$, So Band1 Limit = 4-(6.46-6)=3.54dBm/MHz

For Non-Beamforming mode:

Temperature	26°C	Humidity	63%
Test Engineer	James Chou	Configurations	IEEE 802.11a
Test Date	Nov. 27, 2014		

Configuration IEEE 802.11a / Ant.1 + Ant.2 + Ant.3 + Ant.4

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	3.03	3.54	Complies
40	5200 MHz	3.12	3.54	Complies
48	5240 MHz	3.50	3.54	Complies


Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.46 \text{ dBi} > 6 \text{ dBi}$, So Band1 Limit = $4 - (6.46 - 6) = 3.54 \text{ dBm/MHz}$

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

For Beamforming mode:


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant.1 + Ant.2 + Ant.3 + Ant.4 /
5240 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant.1 + Ant.2 + Ant.3 + Ant.4 /
5230 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant.1 + Ant.2 + Ant.3 + Ant.4 /
5210 MHz



For Non-Beamforming mode:

Power Density Plot on Configuration IEEE 802.11a / Ant.1 + Ant.2 + Ant.3 + Ant.4 / 5240 MHz



4.5. Radiated Emissions Measurement

4.5.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	Normal Link
Test Date	Sep. 11, 2014		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	Normal Link

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	250.19	41.61	46.00	-4.39	59.29	1.90	11.91	31.49	300	169	HORIZONTAL Peak
2	375.32	38.73	46.00	-7.27	52.79	2.44	14.93	31.43	100	135	HORIZONTAL Peak
3	500.45	39.07	46.00	-6.93	50.74	2.82	16.92	31.41	100	139	HORIZONTAL Peak
4	624.61	37.47	46.00	-8.53	47.08	3.18	18.61	31.40	150	125	HORIZONTAL Peak
5	749.74	33.30	46.00	-12.70	41.45	3.53	19.69	31.37	200	123	HORIZONTAL Peak
6	874.87	40.69	46.00	-5.31	47.71	3.89	20.24	31.15	100	104	HORIZONTAL Peak

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	40.67	36.51	40.00	-3.49	55.78	0.75	11.85	31.87	100	183 VERTICAL	Peak
2	48.43	35.99	40.00	-4.01	58.64	0.83	8.32	31.80	100	246 VERTICAL	QP
3	125.06	39.54	43.50	-3.96	58.05	1.33	11.73	31.57	100	36 VERTICAL	Peak
4	250.19	44.11	46.00	-1.89	61.79	1.90	11.91	31.49	100	310 VERTICAL	QP
5	375.32	39.78	46.00	-6.22	53.84	2.44	14.93	31.43	100	216 VERTICAL	Peak
6	500.45	39.71	46.00	-6.29	51.38	2.82	16.92	31.41	125	224 VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~40GHz)

For Beamforming mode:

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Sep. 17, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10360.20	48.20	54.00	-5.80	34.45	10.15	39.01	35.41	Average	168	104	HORIZONTAL
2	10361.50	60.83	74.00	-13.17	47.08	10.15	39.01	35.41	Peak	168	104	HORIZONTAL
3	15539.90	53.53	54.00	-0.47	37.67	12.58	38.45	35.17	Average	173	85	HORIZONTAL
4	15541.50	68.35	74.00	-5.65	52.49	12.58	38.45	35.17	Peak	173	85	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	10363.30	48.35	54.00	-5.65	34.60	10.15	39.01	35.41	7	154	Average	VERTICAL
2	10364.30	62.60	74.00	-11.40	48.85	10.15	39.01	35.41	7	154	Peak	VERTICAL
3	15535.40	67.41	74.00	-6.59	51.55	12.58	38.45	35.17	7	154	Peak	VERTICAL
4	15541.30	53.68	54.00	-0.32	37.82	12.58	38.45	35.17	7	154	Average	VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 40 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 11, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	10400.20	47.21	54.00	-6.79	31.94	10.13	38.98	33.84	93	240 Average	HORIZONTAL
2	10404.00	59.88	74.00	-14.12	44.62	10.13	38.98	33.85	93	240 Peak	HORIZONTAL
3	15603.70	66.97	74.00	-7.03	50.78	12.58	38.36	34.75	58	175 Peak	HORIZONTAL
4	15603.90	53.82	54.00	-0.18	37.63	12.58	38.36	34.75	58	175 Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	10403.40	49.20	54.00	-4.80	33.94	10.13	38.98	33.85	3	171 Average	VERTICAL
2	10403.50	64.07	74.00	-9.93	48.81	10.13	38.98	33.85	3	171 Peak	VERTICAL
3	15590.10	66.77	74.00	-7.23	50.56	12.58	38.38	34.75	2	143 Peak	VERTICAL
4	15593.40	53.68	54.00	-0.32	37.47	12.58	38.38	34.75	2	143 Average	VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 48 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10479.76	53.78	74.00	-20.22	40.09	10.10	38.91	35.32	Peak	218	139 HORIZONTAL
2	10480.02	42.35	54.00	-11.65	28.66	10.10	38.91	35.32	Average	218	139 HORIZONTAL
3	15721.66	45.22	54.00	-8.78	29.67	12.57	38.19	35.21	Average	159	268 HORIZONTAL
4	15724.98	58.06	74.00	-15.94	42.51	12.57	38.19	35.21	Peak	159	268 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	10479.96	55.00	74.00	-19.00	41.31	10.10	38.91	35.32	Peak	202	102 VERTICAL
2	10480.08	48.14	54.00	-5.86	34.45	10.10	38.91	35.32	Average	202	102 VERTICAL
3	15742.90	57.25	74.00	-16.75	41.74	12.57	38.16	35.22	Peak	109	207 VERTICAL
4	15744.00	45.41	54.00	-8.59	29.90	12.57	38.16	35.22	Average	109	207 VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Sep. 19, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15563.40	45.02	54.00	-8.98	29.21	12.58	38.40	35.17	Average	182	301 HORIZONTAL
2	15567.41	54.66	74.00	-19.34	38.85	12.58	38.40	35.17	Peak	182	301 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	15564.00	44.16	54.00	-9.84	28.35	12.58	38.40	35.17	Average	155	37 VERTICAL
2	15564.00	54.86	74.00	-19.14	39.05	12.58	38.40	35.17	Peak	155	37 VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 46 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Sep. 19, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15680.80	52.08	54.00	-1.92	36.48	12.58	38.23	35.21	Average	172	75	HORIZONTAL
2	15687.00	63.65	74.00	-10.35	48.05	12.58	38.23	35.21	Peak	172	75	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	15666.60	52.29	54.00	-1.71	36.65	12.58	38.26	35.20	Average	158	22	VERTICAL
2	15666.70	65.00	74.00	-9.00	49.36	12.58	38.26	35.20	Peak	158	22	VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 11, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	10386.08	57.64	74.00	-16.36	42.32	10.14	38.99	33.81	36	227 Peak	HORIZONTAL
2	10420.00	44.27	54.00	-9.73	29.05	10.13	38.97	33.88	36	227 Average	HORIZONTAL
3	15606.48	47.37	54.00	-6.63	31.18	12.58	38.36	34.75	276	180 Average	HORIZONTAL
4	15619.60	60.22	74.00	-13.78	44.07	12.58	38.33	34.76	276	180 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	10380.00	44.84	54.00	-9.16	29.51	10.14	38.99	33.80	360	181 Average	VERTICAL
2	10433.44	58.04	74.00	-15.96	42.88	10.12	38.95	33.91	360	181 Peak	VERTICAL
3	15632.88	49.19	54.00	-4.81	33.06	12.58	38.31	34.76	5	153 Average	VERTICAL
4	15638.32	61.89	74.00	-12.11	45.76	12.58	38.31	34.76	5	153 Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Non-Beamforming mode:

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 36 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 07, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10353.11	63.62	74.00	-10.38	50.68	8.54	39.72	35.32	Peak	181	104	HORIZONTAL
2	10353.69	50.05	54.00	-3.95	37.11	8.54	39.72	35.32	Average	181	104	HORIZONTAL
3	15540.42	63.17	74.00	-10.83	49.87	10.77	38.12	35.59	Peak	165	221	HORIZONTAL
4	15542.56	51.00	54.00	-3.00	37.70	10.77	38.12	35.59	Average	165	221	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10357.69	63.54	74.00	-10.46	50.57	8.54	39.75	35.32	Peak	170	4	VERTICAL
2	10358.75	50.66	54.00	-3.34	37.69	8.54	39.75	35.32	Average	170	4	VERTICAL
3	15534.47	53.90	54.00	-0.10	40.57	10.77	38.15	35.59	Average	165	7	VERTICAL
4	15534.71	69.71	74.00	-4.29	56.38	10.77	38.15	35.59	Peak	165	7	VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 40 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 07, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10392.76	63.05	74.00	-10.95	49.99	8.55	39.81	35.30	Peak	170	105	HORIZONTAL
2	10393.88	49.57	54.00	-4.43	36.51	8.55	39.81	35.30	Average	170	105	HORIZONTAL
3	15599.71	53.55	54.00	-0.45	40.31	10.78	38.04	35.58	Average	170	133	HORIZONTAL
4	15599.87	68.39	74.00	-5.61	55.15	10.78	38.04	35.58	Peak	170	133	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10397.72	63.33	74.00	-10.67	50.25	8.55	39.81	35.28	Peak	178	0	VERTICAL
2	10398.85	50.54	54.00	-3.46	37.46	8.55	39.81	35.28	Average	178	0	VERTICAL
3	15594.68	68.78	74.00	-5.22	55.54	10.78	38.04	35.58	Peak	167	5	VERTICAL
4	15595.93	53.68	54.00	-0.32	40.44	10.78	38.04	35.58	Average	167	5	VERTICAL

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 48 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 07, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10473.72	48.85	54.00	-5.15	35.57	8.56	39.94	35.22	Average	196	104	HORIZONTAL
2	10473.94	62.76	74.00	-11.24	49.48	8.56	39.94	35.22	Peak	196	104	HORIZONTAL
3	15720.45	65.04	74.00	-8.96	51.96	10.79	37.85	35.56	Peak	166	221	HORIZONTAL
4	15722.50	51.02	54.00	-2.98	37.94	10.79	37.85	35.56	Average	166	221	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	10480.32	48.14	54.00	-5.86	34.83	8.56	39.97	35.22	Average	194	10	VERTICAL
2	10481.92	62.26	74.00	-11.74	48.95	8.56	39.97	35.22	Peak	194	10	VERTICAL
3	15714.55	68.41	74.00	-5.59	55.33	10.79	37.85	35.56	Peak	160	4	VERTICAL
4	15715.71	53.43	54.00	-0.57	40.35	10.79	37.85	35.56	Average	160	4	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed a -27dBm peak limit or average 54dBuV/m and peak 74dBuV/m limits. In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1MHz / 3MHz for Peak

4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

For Beamforming mode:

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 36, 40, 48 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Sep. 17, 2014 ~ Nov. 11, 2014		

Channel 36

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5150.00	49.85	54.00	-4.15	44.44	6.21	34.11	34.91	Average	104	189	VERTICAL
2	5150.00	66.02	74.00	-7.98	60.61	6.21	34.11	34.91	Peak	104	189	VERTICAL
3	5175.60	116.08			110.59	6.24	34.16	34.91	Peak	104	189	VERTICAL
4	5183.20	104.56			99.07	6.24	34.16	34.91	Average	104	189	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamplifier Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	5143.60	59.57	74.00	-14.43	52.87	6.17	34.11	33.58	191	272	Peak	VERTICAL
2	5150.00	47.20	54.00	-6.80	40.46	6.21	34.11	33.58	191	272	Average	VERTICAL
3	5204.00	104.75			97.86	6.27	34.18	33.56	191	272	Average	VERTICAL
4	5207.20	114.62			107.73	6.27	34.18	33.56	191	272	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5148.20	45.25	54.00	-8.75	39.84	6.21	34.11	34.91	Average	255	185	VERTICAL
2	5150.00	58.00	74.00	-16.00	52.59	6.21	34.11	34.91	Peak	255	185	VERTICAL
3	5235.80	115.78			110.16	6.30	34.23	34.91	Peak	255	185	VERTICAL
4	5238.80	104.74			99.12	6.30	34.23	34.91	Average	255	185	VERTICAL
5	5353.60	46.00	54.00	-8.00	40.05	6.47	34.39	34.91	Average	255	185	VERTICAL
6	5356.60	58.78	74.00	-15.22	52.83	6.47	34.39	34.91	Peak	255	185	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 38, 46 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Sep. 18, 2014		

Channel 38

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5150.00	53.78	54.00	-0.22	48.37	6.21	34.11	34.91	Average	196	7	VERTICAL
2	5150.00	70.46	74.00	-3.54	65.05	6.21	34.11	34.91	Peak	196	7	VERTICAL
3	5200.80	111.36			105.82	6.27	34.18	34.91	Peak	196	7	VERTICAL
4	5206.00	97.01			91.47	6.27	34.18	34.91	Average	196	7	VERTICAL

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5148.80	58.50	74.00	-15.50	53.09	6.21	34.11	34.91	Peak	193	213	HORIZONTAL
2	5149.60	46.98	54.00	-7.02	41.57	6.21	34.11	34.91	Average	193	213	HORIZONTAL
3	5226.80	103.97			98.35	6.30	34.23	34.91	Average	193	213	HORIZONTAL
4	5231.20	114.17			108.55	6.30	34.23	34.91	Peak	193	213	HORIZONTAL

Item 3, 4 are the fundamental frequency at 5230 MHz.

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Nov. 11, 2014		

Channel 42

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5146.80	69.14	74.00	-4.86	63.73	6.21	34.11	34.91	Peak	100	131 VERTICAL
2	5150.00	53.64	54.00	-0.36	48.23	6.21	34.11	34.91	Average	100	131 VERTICAL
3	5189.20	106.17			100.68	6.24	34.16	34.91	Peak	100	131 VERTICAL
4	5193.20	95.89			90.38	6.24	34.18	34.91	Average	100	131 VERTICAL
5	5350.00	44.84	54.00	-9.16	38.89	6.47	34.39	34.91	Average	100	131 VERTICAL
6	5350.00	57.35	74.00	-16.65	51.40	6.47	34.39	34.91	Peak	100	131 VERTICAL

Item 3, 4 are the fundamental frequency at 5210 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

For Non-Beamforming mode:

Temperature	24°C	Humidity	62%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 36, 40, 48 / Ant.1 + Ant.2 + Ant.3 + Ant.4
Test Date	Sep. 17, 2014		

Channel 36

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5147.60	61.81	74.00	-12.19	56.40	6.21	34.11	34.91	Peak	103	180 VERTICAL
2	5150.00	47.66	54.00	-6.34	42.25	6.21	34.11	34.91	Average	103	180 VERTICAL
3	5182.80	113.52			108.03	6.24	34.16	34.91	Peak	103	180 VERTICAL
4	5183.20	103.20			97.71	6.24	34.16	34.91	Average	103	180 VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5142.80	58.08	74.00	-15.92	52.71	6.17	34.11	34.91	Peak	102	107 VERTICAL
2	5149.60	45.41	54.00	-8.59	40.00	6.21	34.11	34.91	Average	102	107 VERTICAL
3	5192.80	103.79			98.28	6.24	34.18	34.91	Average	102	107 VERTICAL
4	5193.20	113.31			107.80	6.24	34.18	34.91	Peak	102	107 VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5148.20	57.21	74.00	-16.79	51.80	6.21	34.11	34.91	Peak	210	218 HORIZONTAL
2	5150.00	44.19	54.00	-9.81	38.78	6.21	34.11	34.91	Average	210	218 HORIZONTAL
3	5245.40	113.70			108.06	6.30	34.25	34.91	Peak	210	218 HORIZONTAL
4	5246.00	103.54			97.86	6.34	34.25	34.91	Average	210	218 HORIZONTAL
5	5350.00	45.07	54.00	-8.93	39.12	6.47	34.39	34.91	Average	210	218 HORIZONTAL
6	5351.20	58.65	74.00	-15.35	52.70	6.47	34.39	34.91	Peak	210	218 HORIZONTAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.7. Frequency Stability Measurement

4.7.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.7.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.7.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $0^\circ\text{C} \sim 40^\circ\text{C}$.

4.7.4. Test Setup Layout



4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.7.7. Test Result of Frequency Stability

Temperature	24°C	Humidity	63%
Test Engineer	James Chou	Test Date	Nov. 27, 2014

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5200 MHz
126.50	5199.9794
110.00	5199.9674
93.50	5199.9967
Max. Deviation (MHz)	0.032560
Max. Deviation (ppm)	6.26

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5200 MHz
0	5199.9794
10	5199.9369
20	5199.9674
30	5199.9466
40	5199.9367
Max. Deviation (MHz)	0.063260
Max. Deviation (ppm)	12.17

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 23, 2014	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz - 30 MHz	Dec. 02, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Oct. 28, 2014	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Apr. 22, 2014	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

NCR means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%