

Tune up Procedure

The max power output: 12 ±1dBm

The tune up is fixed by the manufacturer. The tune-up power tolerance range is ±1dBm.

BOM list

序号	material code	item name	spec	qty
1	1.11.012.0M78001	FPC key board	YG-A777-KEY-B, 42*17.82*0.78mm With adhesive ,RoHS, Ao pai	1
	1.04.012.1340006	Lithium battery	DPR395-00,PL368098 3000MAH line's length 20mm, RoHS	1
2	1.07.012.2001070	Camera	ZC-YGA777 S1.0 0V7675/0V2655 2000000+300000 Pixel, 24pin, RoHS	1
3	1.05.012.1011015	Speaker	PS1524H34U12-08-W15C-F2-G 15*24mm H=3.4mm, line's length 1.5mm, RoHS	1
4	1.11.012.0M78008	MIC	MAF-B4015W20-423-13P-4618A-G, line's length 20mm 4.0*1.5mm	1
5	1.01.012.2N04000	Main board	PCBA/YG-A777-HWZQ-4G/RoHS	1
6	1.03.012.C1AA20C	Capacitive Touch Screen	D70-N3690A-20C 182.4*113.5*1.25mm 61pin, Five point Capacitive Touch Screen RoHS	1
7	1.02.001.05ND211	LCD screen	H-B070D-21I 164.9*100*2.6mm H=2.8mm, HP, RoHS	1
	1.06.012.A070000	PVC insulation film	Used for insulation between the back of the LCD and the main board	1
8	1.10.012.1700021	DC slot	HMT-DC-02A 2PIN ￠2.1mm shrapnel model, black color, RoHS	1
9	1.06.012.N010000	Top cover	ABS material+painting +Dull UV+silk screen	1
10	1.06.012.N020005	Bottom cover	ABS material+painting+DullUV+silk screen,Rubber red-brown	1
11	1.06.012.N050000	keys	ABS material+painting+DullUV+silk screen	1
12	1.06.012.A090000	lens of camera	PC material with silk screen	1
13	1.09.001.3143508	screws of PCB	PB1.4*3.5 Thread length* nut length 0.8	4
14	1.09.001.3141605	screws of LCD	PB1.4*1.6 Thread length*nut length0.5	7
15	1.09.001.10435	screws of	KA1.4*3.5 Thread length *nut length0.5	2

	05	top&bottom cover		
16	1.06.012.00800 00	Speaker Net	stainless steel material	1
17	2.01.011.20502 20	adapter	5v 2A With magnetic ,diameter 2.0mm(Nokia adapter)	1
18	2.03.001.11200 00	earphone	3.5 special earphone frequency response : 20Hz-20KHz ; Impedance : 3	1
20	2.02.001.C8000 00	USB cable	Mini 5P Lenth:80CM	1
	2.02.002.00200 0	OTG cable	USB OTG change to USB HOST cable	1