RF EXPOSURE EVALUATION

EUT Specification

EUT	Smart Device
Frequency band (Operating)	☒WLAN: 2.412GHz ~ 2.462GHz ☐WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐WLAN: 5.745GHz ~ 5825GHz ☐Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	☐Portable (<20cm separation) ☒Mobile (>20cm separation) ☐Others ___
Antenna diversity	☒Single antenna ☐Multiple antennas ☐Tx diversity ☐Rx diversity ☐Tx/Rx diversity
Max. output power	14.77dBm(29.99mW)
Antenna gain	1dBi
Evaluation applied	☒MPE Evaluation ☐SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm^2)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	**F/300**	**6**
1500-100000	--	--	**5**	**6**
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	**F/1500**	**6**
1500-100000	--	--	**1**	**30**

Friis transmission formula: Pd=(Pout*G)\(4*pi*R^2)

Where

Pd= Power density in mW/cm^2

Pout=output power to antenna in Mw

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Gain	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/ cm^2)	Power density Limits (mW/cm^2)
Test Mode: 802.11b							
Low	1	2412	8.82	±0.5	8.55	0.0021	1
Middle	1	2437	9.52	±0.5	10.05	0.0025	1
High	1	2462	10.48	±0.5	12.53	0.0031	1
Test Mode: 802.11g							
Low	1	2412	12.28	±0.5	18.97	0.0048	1
Middle	1	2437	12.86	±0.5	21.68	0.0054	1
High	1	2462	14.71	±0.5	33.19	0.0083	1
Test Mode: 802.11n(HT20)							
Low	1	2412	13.68	±0.5	26.18	0.0066	1
Middle	1	2437	13.46	±0.5	24.89	0.0062	1
High	1	2462	14.77	±0.5	33.65	0.0084	1