

FCC TEST REPORT
for
Shenzhen Loyal Electronics Co., Ltd.

Dongle
Model No.: KG8004

Prepared for : Shenzhen Loyal Electronics Co., Ltd.
Address : 8F, Bldg. A, Huayuan Technology Park, Fenghuang Industrial
Zone, Fuyong, Bao'an, Shenzhen

Prepared By : Anbotek Compliance Laboratory Limited
Address : 1/F, 1 /Building, SEC Industrial Park, No. 4 Qianhai Road,
Nanshan District, Shenzhen, 518054, China
Tel: (86) 755-26014771
Fax: (86) 755-26014772

Report Number : 201110673F
Date of Test : Oct. 12~17, 2011
Date of Report : Oct. 18, 2011

TABLE OF CONTENTS

Description	
Test Report	Page
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Auxiliary Equipment Used during Test.....	5
1.3. Description of Test Facility	6
1.4. Measurement Uncertainty.....	6
2. MEASURING DEVICE AND TEST EQUIPMENT.....	7
3. TEST PROCEDURE	8
4. CONDUCTED LIMITS	9
4.1. Block Diagram of Test Setup	9
4.2. Power Line Conducted Emission Measurement Limits (15.207).....	9
4.3. Configuration of EUT on Measurement	9
4.4. Operating Condition of EUT	9
4.5. Test Procedure	10
4.6. Power Line Conducted Emission Measurement Results	10
5. RADIATION INTERFERENCE.....	13
5.1. Requirements (15.249, 15.209):	13
5.2 Test Procedure	13
5.3 Test Results.....	13
6. OCCUPIED BANDWIDTH.....	17
6.1. Requirements (15.249):	17
6.2. Test Procedure	17
6.3. Test Configuration:.....	17
6.4. Test Results.....	17
7. PHOTOGRAPH.....	19
7.1. Photo of Power Line Conducted Emission Measurement	19
7.2. Photo of Radiation Emission Test	19

APPENDIX I (Photos of EUT) (4 Pages)

TEST REPORT

Applicant : Shenzhen Loyal Electronics Co., Ltd.
Manufacturer : Shenzhen Loyal Electronics Co., Ltd.
EUT : Dongle
Model No. : KG8004
Serial No. : N.A.
Rating : 5.0V $\overline{\text{---}}$, 50mA max.
Trade Mark : N.A.

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.207, 15.249 & 15.209


The device described above is tested by Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Anbotek Compliance Laboratory Limited


Date of Test : Oct. 12~17, 2011



Prepared by : (Engineer / Rock Zeng)



Reviewer : (Project Manager / Coco Xiang)



Approved & Authorized Signer : (Manager / Henry Yang)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Dongle

Model Number : KG8004

Test Power Supply : DC 3 V

Frequency : 2410~2473MHz

Channels : 2410~2473MHz (A total of 64 channels with channel spacing of 1MHz. Under normal working condition, choose 20 channels of 64 randomly)

Antenna Specification : Printed Antenna:1dBi

Applicant : Shenzhen Loyal Electronics Co., Ltd.
Address : 8F, Bldg. A, Huayuan Technology Park, Fenghuang Industrial Zone, Fuyong, Bao'an, Shenzhen

Manufacturer : Shenzhen Loyal Electronics Co., Ltd.
Address : No.31, Furong Road, Gushu Village, Xixiang Town, Bao'an District, Shenzhen

Date of receiver : Oct. 11, 2011

Date of Test : Oct. 12~17, 2011

1.2.Auxiliary Equipment Used during Test

PC	: Manufacturer: DELL M/N: OPTIPLEX 380 S/N: 1J63X2X CE , FCC: DOC
MONITOR	: Manufacturer: DELL M/N: E170Sc S/N: CN-00V539-64180-055-0UPS CE , FCC: DOC
MOUSE	: Manufacturer: DELL M/N: M-UARDEL7 S/N: N/A CE , FCC: DOC Cable: 1m, unshielded
Printer	: Manufacturer: Brother M/N: MFC-3360C S/N: N/A CE, FCC: DOC
Power Line	: Non-Shielded, 1.5m
VGA Cable	: Non-Shielded, 1.5m
USB Cable	: Non-Shielded, 0.5m

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS - LAB Code: L3503

Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC-Registration No.: 752021

Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, August 20, 2010.

IC-Registration No.: 8058A-1

Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, August 30, 2010.

Test Location

All Emissions tests were performed at
Anbotek Compliance Laboratory Limited. at 1/F, 1 /Building, SEC Industrial Park,
No. 4 Qianhai Road, Nanshan District, Shenzhen, 518054, China

1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.3dB

Conduction Uncertainty : Uc = 3.4dB

2. MEASURING DEVICE AND TEST EQUIPMENT

Equipment	Manufacturer	Model #	Serial #	Data of Cal.	Due Data
EMI Test Receiver	Rohde & Schwarz	ESCI	100119	Mar.03, 2011	Mar.02, 2012
EMI Test Receiver	Rohde & Schwarz	ESIB26	100249	Sep.22, 2011	Sep.21, 2012
EMI Test Software	SHURPLE	ESK1	N/A	N/A	N/A
Spectrum Analyzer	Agilent	E7405A	MY45114970	Jun.21, 2011	Jun.20, 2012
Signal Generator	Rohde & Schwarz	SMR27	100124	Jul.06, 2010	Jul.05, 2012
Signal Generator	Rohde & Schwarz	SML03	102319	Aug.01, 2010	Aug.01, 2012
AC Power Source	Sepcial power system	YF650	N/A	N/A	N/A
Absorbing Clamp	Rohde & Schwarz	MDS21	100218	Apr.30, 2010	Apr.29, 2012
Power Meter	Rohde & Schwarz	NRVD	101287	Jul.19, 2011	Jul.18, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Coaxial Cable	N/A	N/A	N/A	May.31, 2011	May.30, 2012
Universal radio Communication tester	Rohde & Schwarz	CMU200	101724	Sep.08, 2011	Sep.07, 2012
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
BiConilog Antenna	ETS-LINDGREN	3142C	00042670	Mar.03, 2011	Mar.02, 2012
BiConilog Antenna	ETS-LINDGREN	3142C	00042673	Mar.03, 2011	Mar.02, 2012
Double-ridged Waveguide horn	ETS-LINDGREN	3117	00035926	Dec.30, 2009	Dec.29, 2011
Double-ridged Waveguide horn	ETS-LINDGREN	3117	00041545	Dec.30, 2009	Dec.29, 2011
Pre-amplifier	CD	PAM0203	804203	Jun.21, 2011	Jun.20, 2012
RF Switch	CD	RSU-M3	706543	Jun.21, 2011	Jun.20, 2012
Thermo-/Hygrometer	N/A	TH01	N/A	May.03, 2011	May.02, 2012
Shielding Room	Zhong Yu Electronic	N/A	N/A	N/A	N/A
3m Semi-Anechoic Chamber	Zhong Yu Electronic	N/A	N/A	Apr.28, 2010	Apr.27, 2012

3. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-2009 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:


Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-2009 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

4. Conducted Limits

4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



4.2. Power Line Conducted Emission Measurement Limits (15.207)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.

4.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

EUT : Dongle
 Model Number : BL-BKB83A
 Applicant : Shenzhen Loyal Electronics Co., Ltd.

4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in test mode (ON) and measure it.

4.5. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.4-2003 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9KHz.

The frequency range from 150KHz to 30MHz is checked.

The test results are reported on Section 4.6.

4.6. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150KHz to 30 MHz is investigated.

Please refer the following pages.


FCC ID: Z5X8004RX

CONDUCTED EMISSION TEST DATA

EUT: Dongle M/N: BL-BKB83A
 Operating Condition: ON
 Test Site: 1# Shielded Room
 Operator: Rock Zeng
 Test Specification: AC 120V/60Hz for PC
 Comment: Live Line
 Tem:25°C Hum:50%

SCAN TABLE: "Voltage (150K~30M) FIN"

Short Description: 150K-30M Disturbance Voltages

**MEASUREMENT RESULT: "AT1110613101_fin"**

10/12/2011 11:09AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.195000	50.10	10.1	64	13.7	QP	L1	GND
0.325500	41.80	10.1	60	17.8	QP	L1	GND
0.388500	40.90	10.1	58	17.2	QP	L1	GND
0.496500	42.90	10.1	56	13.2	QP	L1	GND
0.978000	35.70	10.2	56	20.3	QP	L1	GND
3.254500	31.80	10.4	56	24.2	QP	L1	GND

MEASUREMENT RESULT: "AT1110613101_fin2"

10/12/2011 11:09AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.195000	48.40	10.1	54	5.4	AV	L1	GND
0.262500	38.50	10.1	51	12.9	AV	L1	GND
0.325500	38.00	10.1	50	11.6	AV	L1	GND
0.388500	35.90	10.1	48	12.2	AV	L1	GND
0.496500	35.60	10.1	46	10.5	AV	L1	GND
0.627000	31.20	10.1	46	14.8	AV	L1	GND


FCC ID: Z5X8004RX

CONDUCTED EMISSION TEST DATA

EUT: Dongle M/N: BL-BKB83A
 Operating Condition: ON
 Test Site: 1# Shielded Room
 Operator: Rock Zeng
 Test Specification: AC 120V/60Hz for PC
 Comment: Neutral Line
 Tem:25°C Hum:50%

SCAN TABLE: "Voltage(150K~30M)FIN"

Short Description: 150K-30M Disturbance Voltages

**MEASUREMENT RESULT: "AT1110613102_fin"**

10/12/2011 11:14AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.195000	47.00	10.1	64	16.8	QP	N	GND
0.325500	38.00	10.1	60	21.6	QP	N	GND
0.388500	37.70	10.1	58	20.4	QP	N	GND
0.496500	40.60	10.1	56	15.5	QP	N	GND
0.982500	34.50	10.2	56	21.5	QP	N	GND
3.236500	31.90	10.4	56	24.1	QP	N	GND

MEASUREMENT RESULT: "AT1110613102_fin2"

10/12/2011 11:14AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.195000	45.00	10.1	54	8.8	AV	N	GND
0.325500	36.50	10.1	50	13.1	AV	N	GND
0.388500	34.90	10.1	48	13.2	AV	N	GND
0.483000	34.60	10.1	46	11.7	AV	N	GND
1.252000	30.70	10.2	46	15.3	AV	N	GND
13.559500	9.40	10.7	50	40.6	AV	N	GND

5. Radiation Interference

5.1. Requirements (15.249, 15.209):

FIELD STRENGTH of Fundamental:	FIELD STRENGTH of Harmonics	S15.209	
902-928 MHZ		30 - 88 MHz	40 dBuV/m @3M
2.4-2.4835 GHz		88 - 216 MHz	43.5
94 dBuV/m @3m	54 dBuV/m @3m	216 - 960 MHz	46
		ABOVE 960 MHz	54dBuV/m

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

5.2 Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9*6*6 Chamber.

The test results are listed in Section 5.3.

5.3 Test Results

PASS.

Please refer the following pages.

FCC ID: Z5X8004RX

Data:

Horizontal CH Low(2410MHz)								
Frequency	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBμV/m	dBμV/m	Limit	
	dB	dB/m	dB	dBμV			dB	
684.74	1.62	15.61	35.19	50.80	32.84	46.00	-13.16	QP
854.02	1.63	11.52	35.58	47.10	24.67	46.00	-21.33	QP
2410.00	2.20	31.23	35.29	83.28	81.42	114.0	-32.58	Peak
2410.00	2.20	31.23	35.29	80.50	78.70	94.0	-15.30	AV
4820.10	2.62	35.10	34.73	36.45	39.44	74.0	-34.56	Peak
4820.10	2.62	35.10	34.73	33.56	36.55	54.0	-17.45	AV
7230.00	3.09	36.18	35.16	36.49	40.60	74.0	-33.40	Peak
7230.00	3.09	36.18	35.16	33.25	37.36	54.0	-16.64	AV
9640.00	---	---	---	---	---	---	---	---
12050.00	---	---	---	---	---	---	---	---
14460.00	---	---	---	---	---	---	---	---
16870.00	---	---	---	---	---	---	---	---
19280.00	---	---	---	---	---	---	---	---
21690.00	---	---	---	---	---	---	---	---
24100.00	---	---	---	---	---	---	---	---

CH Middle(2442MHz)								
Frequency	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBμV/m	dBμV/m	Limit	
	dB	dB/m	dB	dBμV			dB	
455.90	1.61	13.28	22.63	47.78	40.04	46.00	-5.96	QP
2442.01	2.21	31.24	35.88	85.75	83.32	114.0	-30.68	Peak
2442.01	2.21	31.24	35.88	83.25	80.82	94.0	-13.18	AV
4884.10	2.64	35.11	34.73	38.29	41.31	74.0	-32.69	Peak
4884.10	2.64	35.11	34.73	35.50	38.52	54.0	-15.48	AV
7326.15	3.10	36.20	35.18	34.52	38.64	74.0	-35.36	Peak
7326.15	3.10	36.20	35.18	31.50	35.62	54.0	-18.38	AV
9768.05	---	---	---	---	---	---	---	---
12210.00	---	---	---	---	---	---	---	---
14652.00	---	---	---	---	---	---	---	---
17094.00	---	---	---	---	---	---	---	---
19536.00	---	---	---	---	---	---	---	---
21978.00	---	---	---	---	---	---	---	---
24420.00	---	---	---	---	---	---	---	---

FCC ID: Z5X8004RX

CH High(2473MHz)								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
420.17	1.60	13.30	23.16	48.00	39.74	46.00	-6.26	QP
2473.00	2.20	31.31	35.58	85.66	83.59	114.0	-30.41	Peak
2473.00	2.20	31.31	35.58	82.86	80.79	94.0	-13.21	AV
4946.10	2.67	35.05	34.80	37.33	40.25	74.0	-33.75	Peak
4946.10	2.67	35.05	34.80	34.38	37.30	54.0	-16.70	AV
7419.06	3.12	36.20	35.20	34.40	38.52	74.0	-35.48	Peak
7419.06	3.12	36.20	35.20	31.54	35.66	54.0	-18.34	AV
9892.00	---	---	---	---	---	---	---	---
12365.00	---	---	---	---	---	---	---	---
14838.00	---	---	---	---	---	---	---	---
17311.00	---	---	---	---	---	---	---	---
19784.00	---	---	---	---	---	---	---	---
22257.00	---	---	---	---	---	---	---	---
24730.00	---	---	---	---	---	---	---	---

Vertical CH Low(2410MHz)								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
121.65	1.56	12.43	41.41	48.22	20.81	46.00	-25.19	QP
2410.02	2.20	31.24	35.78	84.80	82.46	114.0	-31.54	Peak
2410.02	2.20	31.24	35.78	82.35	80.01	94.0	-13.99	AV
4820.10	2.66	35.10	34.77	38.71	41.70	74.0	-34.30	Peak
4820.10	2.66	35.10	34.77	36.00	38.99	54.0	-15.01	AV
7230.93	3.12	36.19	35.16	34.50	38.66	74.0	-35.35	Peak
7230.93	3.12	36.19	35.16	32.00	36.16	54.0	-17.84	AV
9640.00	---	---	---	---	---	---	---	---
12050.00	---	---	---	---	---	---	---	---
14460.00	---	---	---	---	---	---	---	---
16870.00	---	---	---	---	---	---	---	---
19280.00	---	---	---	---	---	---	---	---
21690.00	---	---	---	---	---	---	---	---
24100.00	---	---	---	---	---	---	---	---

FCC ID: Z5X8004RX

CH Middle(2442MHz)								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
413.17	1.62	13.30	41.40	52.56	26.08	43.5	-17.42	QP
2442.01	2.20	31.25	35.91	81.87	79.41	114.0	-34.59	Peak
2442.01	2.20	31.25	35.91	79.86	77.40	94.0	-16.60	AV
4884.12	2.61	35.10	34.73	36.71	39.69	74.0	-34.31	Peak
4884.12	2.61	35.10	34.73	33.75	36.73	54.0	-17.27	AV
7326.25	3.15	36.18	35.17	33.80	37.96	74.0	-36.04	Peak
7326.25	3.15	36.18	35.17	30.91	35.07	54.0	-18.93	AV
9768.00	---	---	---	---	---	---	---	---
12210.00	---	---	---	---	---	---	---	---
14652.00	---	---	---	---	---	---	---	---
17094.00	---	---	---	---	---	---	---	---
19943.00	---	---	---	---	---	---	---	---
22792.00	---	---	---	---	---	---	---	---
24420.00	---	---	---	---	---	---	---	---

CH High(2473MHz)								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
120.38	1.55	12.37	41.41	57.48	29.99	43.5	-13.51	QP
2473.00	2.23	31.35	36.00	84.26	81.84	114.0	-32.16	Peak
2473.00	2.23	31.35	36.00	81.30	78.88	94.0	-15.12	AV
4946.05	2.66	35.06	34.79	35.07	38.00	74.0	-36.00	Peak
4946.05	2.66	35.06	34.79	32.37	35.30	54.0	-18.70	AV
7419.24	3.11	36.20	35.16	35.84	39.99	74.0	-34.01	Peak
7419.24	3.11	36.20	35.16	32.70	36.85	54.0	-17.15	AV
9892.00	---	---	---	---	---	---	---	---
12365.00	---	---	---	---	---	---	---	---
14838.00	---	---	---	---	---	---	---	---
17311.00	---	---	---	---	---	---	---	---
19784.00	---	---	---	---	---	---	---	---
22257.00	---	---	---	---	---	---	---	---
24730.00	---	---	---	---	---	---	---	---

NOTE: “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6. Occupied Bandwidth


6.1. Requirements (15.249):

The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

6.2. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on an antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

6.3. Test Configuration:




6.4. Test Results

Pass.

Please refer the following plot.


(Note: Marker 2 means the highest value in 2.39GHz~2.4GHz or 2.4835~2.5GHz)

FCC ID: Z5X8004RX



Lower Band

Date: 17.OCT.2011 15:01:17



Upper Band

Date: 17.OCT.2011 15:04:35