

Report No.: FR8D1930A



FCC RADIO TEST REPORT

FCC ID : Z64-CC3235MOD

Equipment : Dual-Band Wi-Fi® Module

Brand Name: Texas Instruments

Model Name : CC3235MODSM2MOB, CC3235MODSF12MOB

Marketing : SimpleLink[™] Wi-Fi® CC3235MOD Dual-Band

Name Wireless Microcontroller Module

Applicant : Texas Instruments Incorported

12500 TI BLVD., Dallas Texas, 75243

Manufacturer : Texas Instruments Incorported

12500 TI BLVD., Dallas Texas, 75243

Standard : FCC Part 15 Subpart C §15.247

The product was received on Dec. 19, 2018 and testing was started from May 16, 2019 and completed on Aug. 06, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 34

FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Table of Contents

Hi	story o	f this test report	3
Sι	ımmary	of Test Result	4
1	Gener	al Description	5
	1.1	Product Feature of Equipment Under Test	5
	1.2	Modification of EUT	5
	1.3	Testing Location	6
	1.4	Applicable Standards	6
2	Test C	onfiguration of Equipment Under Test	7
	2.1	Carrier Frequency and Channel	7
	2.2	Test Mode	7
	2.3	Connection Diagram of Test System	8
	2.4	Support Unit used in test configuration and system	8
	2.5	EUT Operation Test Setup	8
	2.6	Measurement Results Explanation Example	9
3	Test R	esult1	0
	3.1	6dB and 99% Bandwidth Measurement1	0
	3.2	Output Power Measurement1	2
	3.3	Power Spectral Density Measurement1	3
	3.4	Conducted Band Edges and Spurious Emission Measurement	5
	3.5	Radiated Band Edges and Spurious Emission Measurement	5
	3.6	AC Conducted Emission Measurement	9
	3.7	Antenna Requirements3	1
4	List of	Measuring Equipment3	2
5	Uncer	tainty of Evaluation3	4
Αŗ	pendix	A. Conducted Test Results	
Αŗ	pendix	B. AC Conducted Emission Test Result	
Αŗ	pendix	C. Conducted Spurious Emission	
Αŗ	pendix	D. Conducted Spurious Emission Plots	
Αŗ	pendix	E. Cabinet Radiated Spurious Emission	
-	•	F. Cabinet Radiated Spurious Emission Plots	
-	•	G. Duty Cycle Plots	
Αŗ	pendix	H. Setup Photographs	

TEL: 886-3-327-3456 Page Number : 2 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Report Template No.: BU5-FR15CWL AC MA Version 2.4

Report Version : 02

Report No. : FR8D1930A

History of this test report

Report No.: FR8D1930A

Report No.	Version	Description	Issued Date
FR8D1930A	01	Initial issue of report	Jul. 19, 2019
FR8D1930A	02	Add the test result of peak power	Aug. 06, 2019

TEL: 886-3-327-3456 Page Number : 3 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Summary of Test Result

Report No.: FR8D1930A

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
0.4	45.047(1)	Conducted Band Edges	Pass	-
3.4	15.247(d)	Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 1.45 dB at 4924 MHz for Average
3.6	15.207	AC Conducted Emission	Pass	Under limit 15.59 dB at 0.15225 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Remark: Not required means after assessing, test items are not necessary to carry out.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang Report Producer: Shirley Xu

TEL: 886-3-327-3456 Page Number : 4 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

1 General Description

1.1 Product Feature of Equipment Under Test

Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a

	Antenna Information							
	Antenna Type Brand Name Model 2.4GHz Gain(dBi) 5GHz Gain(dB							
1.		Pulse	W3078	1.7	4.3			
2.	Chip	Yageo	ANT5320LL04R2455A	2.17	3.51			
3.		Cth ortropics	M830520	1	2.6			
4.		Ethertronics	1000423	-0.6	4.5			
5.	PCB	PCB Laird	CAF94504	2	4			
6.			CAF94505	2	4			
7.			001-0012	2	2			
8.	Dipole		080-0013	2	2			
9.		LSR	080-0014	2	2			
10.	PIFA		001-0016	2.5	3			
11.	FIFA	IFA	001-0021	2.5	3			
Note	e: The EUT used	a dual-band chip	antenna (Antenna 3 from	Ethertronics)				

Report No.: FR8D1930A

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

TEL: 886-3-327-3456 Page Number : 5 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton S	Site No.	
rest site NO.	TH05-HY	CO05-HY	

Report No.: FR8D1930A

Test Site SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH15-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- + ANSI C63.10-2013

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 886-3-327-3456 Page Number : 6 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

Report No.: FR8D1930A

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	1	2412	7	2442
	2	2417	8	2447
0400 0400 5 MIL	3	2422	9	2452
2400-2483.5 MHz	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

	Test Cases					
AC						
Conducted	Mode 1 :WLAN 2.4G Link + USB Cable(Charging from Notebook)					
Emission						

TEL: 886-3-327-3456 Page Number : 7 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

2.3 Connection Diagram of Test System



Report No.: FR8D1930A

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
2.	Notebook	Dell	Latitude E3340	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	Lenovo	L570	FCC DoC	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0m	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "CC31XX/CC32XX Radio Tool v1.0.3.10" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

TEL: 886-3-327-3456 Page Number : 8 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Report No.: FR8D1930A

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.1 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
=
$$1.1 + 10 = 11.1$$
 (dB)

TEL: 886-3-327-3456 Page Number : 9 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Report No.: FR8D1930A

- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 6. Measure and record the results in the test report.


3.1.4 Test Setup



TEL: 886-3-327-3456 Page Number : 10 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Report No.: FR8D1930A

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

TEL: 886-3-327-3456 Page Number : 11 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Report No.: FR8D1930A


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

- 1. For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.3 PKPM1
- 2. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
- 3. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4. Set to the maximum power setting and enable the EUT transmit continuously.
- 5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 12 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

Report No.: FR8D1930A


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz.
 Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.


3.3.4 Test Setup



TEL: 886-3-327-3456 Page Number : 13 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 14 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.

Report No.: FR8D1930A


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
- 5. Measure and record the results in the test report.
- The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




TEL: 886-3-327-3456 Page Number : 15 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :		Temperature :	21~25℃
rest Engineer.	Leo Lee	Relative Humidity :	51~54%

Report No.: FR8D1930A

Test Mode: 802.11b Test Channel: 01



TEL: 886-3-327-3456 Page Number : 16 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:08:55

Test Mode: 802.11b Test Channel: 06 100kHz PSD reference Level *RBW 100 kHz *VBW 300 kHz SWT 5 ms ❈ Date: 17.JUN.2019 15:55:07 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 17 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:09:25

Date: 6.AUG.2019 15:11:14

Test Mode: 802.11b Test Channel: 11 100kHz PSD reference Level **Channel Plot** *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz -45.34 dBm SWT 40 ms 2.503524375 GHz *RBW 100 kHz *VBW 300 kHz SWT 5 ms ❈ ≫ Date: 17.JUN.2019 16:00:15 Date: 6.AUG.2019 15:10:08 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 18 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:11:41

Date: 6.AUG.2019 15:14:40

Test Mode: 802.11g Test Channel: 01 100kHz PSD reference Level **Channel Plot** *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz -32.95 dBm SWT 40 ms 2.397901875 GHz *RBW 100 kHz *VBW 300 kHz SWT 5 ms ❈ ≫ In a facinity of the second second second portago lagalera hazalazal Date: 17.JUN.2019 16:03:43 Date: 6.AUG.2019 15:13:49 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 19 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:15:35

Date: 6.AUG.2019 15:16:39

Test Mode: 802.11g Test Channel: 06 100kHz PSD reference Level *RBW 100 kHz *VBW 300 kHz SWT 5 ms ❈ Date: 17.JUN.2019 16:11:11 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 20 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:18:06

Date: 6.AUG.2019 15:19:57

Test Mode: 802.11g Test Channel: 11 100kHz PSD reference Level **Channel Plot** *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz -44.99 dBm SWT 40 ms 2.483679375 GHz *RBW 100 kHz M: *VBW 300 kHz SWT 5 ms ❈ ≫ al and person repertment and response Date: 17.JUN.2019 16:15:16 Date: 6.AUG.2019 15:19:07 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 21 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:20:40

Date: 6.AUG.2019 15:25:20

Test Mode: 802.11n HT20 Test Channel: 01 100kHz PSD reference Level **Channel Plot** *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz -31.37 dBm SWT 40 ms 2.399926875 GHz *RBW 100 kHz M *VBW 300 kHz SWT 5 ms ❈ ≫ Independent later party Date: 17.JUN.2019 16:20:44 Date: 6.AUG.2019 15:23:12 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 22 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:26:06

Date: 6.AUG.2019 15:26:59

Test Mode: 802.11n HT20 Test Channel: 06 100kHz PSD reference Level *RBW 100 kHz *VBW 300 kHz SWT 5 ms ❈ Date: 27.JUN.2019 16:02:40 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 23 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:28:41

Date: 6.AUG.2019 15:30:51

Test Mode: 802.11n HT20 Test Channel: 11 100kHz PSD reference Level **Channel Plot** *RBW 100 kHz Marker 1 [T1] *VBW 300 kHz -43.92 dBm SWT 40 ms 2.483696250 GHz *RBW 100 kHz *VBW 300 kHz SWT 5 ms ❈ ≫ 1 may tark topped rate transfers Date: 17.JUN.2019 16:37:14 Date: 6.AUG.2019 15:30:02 Spurious Emission 30MHz~3GHz Spurious Emission 2GHz~25GHz *RBW 100 kHz Marker 2 [T1]

*VBW 300 kHz -37.11 dBm
SWT 2.3 a 24.908000000 GHz *RBW 100 kHz *VBW 300 kHz SWT 300 ms **% ※**

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 24 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Date: 6.AUG.2019 15:32:32

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Report No.: FR8D1930A

Field Strength	Measurement Distance
(microvolts/meter)	(meters)
2400/F(kHz)	300
24000/F(kHz)	30
30	30
100	3
150	3
200	3
500	3
	(microvolts/meter) 2400/F(kHz) 24000/F(kHz) 30 100 150 200

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

TEL: 886-3-327-3456 Page Number : 25 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.5.3 Test Procedures

- 1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.


Report No.: FR8D1930A

- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

TEL: 886-3-327-3456 Page Number : 26 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019


3.5.4 Test Setup

For Conducted Measurement Setup:




Report No.: FR8D1930A

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



TEL: 886-3-327-3456 Page Number : 27 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

For radiated emissions above 1GHz



Report No.: FR8D1930A

3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Conduced Spurious at Band Edges in the Restricted Band

Please refer to Appendix C and D.

3.5.7 Test Result of Conduced Spurious Emission in the Restricted Band

Please refer to Appendix C and D.

3.5.8 Test Result of Cabinet Radiated Spurious at Band Edges

Please refer to Appendix E and F.

3.5.9 Test Result of Cabinet Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix E and F.

3.5.10 Duty Cycle

Please refer to Appendix G.

TEL: 886-3-327-3456 Page Number : 28 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR8D1930A

Frequency of Emission	Conducted Limit (dBμV)				
(MHz)	Quasi-Peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

^{*}Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments


See list of measuring equipment of this test report.

3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

TEL: 886-3-327-3456 Page Number : 29 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.6.4 Test Setup



Report No.: FR8D1930A

AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 30 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

Report No.: FR8D1930A

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

TEL: 886-3-327-3456 Page Number : 31 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

4 List of Measuring Equipment

Instrument			Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor			13I00030S NO32	9kHz~6GHz	Dec. 03, 2018	May 22, 2019~ Aug. 06, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 28, 2019	May 22, 2019~ Aug. 06, 2019	Sep. 27, 2019	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GH z	Sep. 28, 2019	May 22, 2019~ Aug. 06, 2019	Sep. 27, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	May 22, 2019~ Aug. 06, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC120838 2	N/A	Mar. 27, 2019	May 22, 2019~ Aug. 06, 2019	Mar. 26, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 16, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	May 16, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	May 16, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	May 16, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	May 16, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	May 16, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter Rohde & Schwarz		ESH3-Z2	100851	N/A	Dec. 31, 2018	May 16, 2019	Dec. 30, 2019	Conduction (CO05-HY)

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : 32 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Jun. 09, 2019~ Jun. 25, 2019	Jan. 06, 2020	Radiation (03CH15-HY)
Bilog Antenna	Bilog Antenna TESEQ		41912&05	30MHz to 1GHz	Feb. 12, 2019	Jun. 09, 2019~ Jun. 25, 2019	Feb. 11, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-162 0	1G~18GHz	Oct. 17, 2018	Jun. 09, 2019~ Jun. 25, 2019	Oct. 16, 2019	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 05, 2018	Jun. 09, 2019~ Jun. 25, 2019	Dec. 04, 2019	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 28, 2018	Jun. 09, 2019~ Jun. 25, 2019	Dec. 27, 2019	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 00550006	1GHz~18GHz	Jul. 10, 2018	Jun. 20, 2019~ Jun. 28, 2019	Jul. 09, 2019	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY532701 95	1GHz~26.5GHz	Aug. 23, 2018	Jun. 09, 2019~ Jun. 25, 2019	Aug. 22, 2019	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Jun. 09, 2019~ Jun. 25, 2019	Dec. 05, 2019	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY541300 85	20Hz ~ 8.4GHz	Nov. 01, 2018	Jun. 09, 2019~ Jun. 25, 2019	Oct. 31, 2019	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	Apr. 29, 2019	Jun. 09, 2019~ Jun. 25, 2019	Apr. 28, 2020	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jun. 09, 2019~ Jun. 25, 2019	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jun. 09, 2019~ Jun. 25, 2019	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k 5)	RK-00045 1	N/A	N/A	Jun. 09, 2019~ Jun. 25, 2019	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/ 4	30M-18G	Apr. 15, 2019	Jun. 09, 2019~ Jun. 25, 2019	Apr. 14, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4	30M-18G	Apr. 15, 2019	Jun. 09, 2019~ Jun. 25, 2019	Apr. 14, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY802430 /4	30M~18GHz	May. 13, 2019	Jun. 09, 2019~ Jun. 25, 2019	May. 12, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Jun. 09, 2019~ Jun. 25, 2019	Mar. 12, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	Jun. 09, 2019~ Jun. 25, 2019	Mar. 12, 2020	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN11	1G Low Pass	Sep. 16, 2018	Jun. 09, 2019~ Jun. 25, 2019	Sep. 15, 2019	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN1	3 GHz Highpass	Sep. 16, 2018	Jun. 09, 2019~ Jun. 25, 2019	Sep. 15, 2019	Radiation (03CH15-HY)

Report No. : FR8D1930A

TEL: 886-3-327-3456 Page Number : 33 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

5 Uncertainty of Evaluation

<u>Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)</u>

Measuring Uncertainty for a Level of Confidence	2.7dB
of 95% (U = 2Uc(y))	4.5

Report No.: FR8D1930A

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

1		
	Measuring Uncertainty for a Level of Confidence	5.2dB
	of 95% (U = 2Uc(y))	J.2ub

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5.5dB
of 95% (U = 2Uc(y))	3.5UB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	5.2dB
of 95% (U = 2Uc(y))	5.2 u B

TEL: 886-3-327-3456 Page Number : 34 of 34
FAX: 886-3-328-4978 Issued Date : Aug. 06, 2019

Report Number : FR8D1930A

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Leo Lee	Temperature:	21~25	ç
Test Date:	2019/5/22~2019/8/6	Relative Humidity:	51~54	%

Report Number : FR8D1930A

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

	2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail	
					Ant 1	Ant 2	Ant 1	Ant 2			
11b	1Mbps	1	1	2412	14.30	-	9.08	-	0.50	Pass	
11b	1Mbps	1	6	2437	14.40	-	9.08	-	0.50	Pass	
11b	1Mbps	1	11	2462	14.40	-	9.12	-	0.50	Pass	
11g	6Mbps	1	1	2412	16.55	-	15.04	-	0.50	Pass	
11g	6Mbps	1	6	2437	18.75	-	15.08	-	0.50	Pass	
11g	6Mbps	1	11	2462	16.60	-	15.12	-	0.50	Pass	
HT20	MCS0	1	1	2412	17.60	-	15.08	-	0.50	Pass	
HT20	MCS0	1	6	2437	18.75	-	15.08	-	0.50	Pass	
HT20	MCS0	1	11	2462	17.55	-	15.08	-	0.50	Pass	

Report Number : FR8D1930A

TEST RESULTS DATA Peak Output Power

								2.4GH	Iz Band							
Mod.	Mod. Data Rate	NTX	CH.	Freq. (MHz)	(Peak Conducted Power (dBm)	d	Lir	ucted wer mit Bm)		G Bi)	EII Por (dE	wer	Lir	RP wer mit Bm)	Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	18.23	-	-	30.00	-	2.50	-	20.73	-	36.00	-	Pass
11b	1Mbps	1	6	2437	18.48	-	-	30.00	-	2.50	-	20.98	-	36.00	-	Pass
11b	1Mbps	1	11	2462	18.33	-	-	30.00	-	2.50	-	20.83	-	36.00	-	Pass
11g	6Mbps	1	1	2412	19.08	-	-	30.00	-	2.50	-	21.58	-	36.00	-	Pass
11g	6Mbps	1	6	2437	19.69	-	-	30.00	-	2.50	-	22.19	-	36.00	-	Pass
11g	6Mbps	1	11	2462	19.14	-	-	30.00	-	2.50	-	21.64	-	36.00	-	Pass
HT20	MCS0	1	1	2412	19.07	-	-	30.00	-	2.50	-	21.57	-	36.00	-	Pass
HT20	MCS0	1	6	2437	19.53	-	-	30.00	-	2.50	-	22.03	-	36.00	-	Pass
HT20	MCS0	1	11	2462	19.16	-	-	30.00	-	2.50	-	21.66	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

Report Number : FR8D1930A

TEST RESULTS DATA Average Output Power (Reporting Only)

	2.4GHz Band											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)							
					Ant 1	Ant 2	SUM					
11b	1Mbps	1	1	2412	16.10	-						
11b	1Mbps	1	6	2437	16.40	-						
11b	1Mbps	1	11	2462	16.50	-						
11g	6Mbps	1	1	2412	11.50	-						
11g	6Mbps	1	6	2437	16.00	-	-					
11g	6Mbps	1	11	2462	11.60	-						
HT20	MCS0	1	1	2412	11.30	-						
HT20	MCS0	1	6	2437	15.90	-						
HT20	MCS0	1	11	2462	11.40	-						

Note: Measured power (dBm) has offset with cable loss.

Report Number : FR8D1930A

<u>TEST RESULTS DATA</u> <u>Peak Power Spectral Density</u>


	2.4GHz Band												
Mod.	Data NTX		NTX CH.	CH.	Freq.		Peak PSD (dBm/3kHz)			G Bi)	Liı	r PSD mit /3kHz)	Pass/Fail
	Kale			(IVITIZ)	Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	-8.07	-	-	2.50	-	8.00	-	Pass	
11b	1Mbps	1	6	2437	-8.03	-	-	2.50	-	8.00	-	Pass	
11b	1Mbps	1	11	2462	-7.60	-	-	2.50	-	8.00	-	Pass	
11g	6Mbps	1	1	2412	-17.07	-	-	2.50	-	8.00	-	Pass	
11g	6Mbps	1	6	2437	-12.26	-	-	2.50	-	8.00	-	Pass	
11g	6Mbps	1	11	2462	-14.19	-	-	2.50	-	8.00	-	Pass	
HT20	MCS0	1	1	2412	-15.25	-	-	2.50	-	8.00	-	Pass	
HT20	MCS0	1	6	2437	-11.77	-	-	2.50	-	8.00	-	Pass	
HT20	MCS0	1	11	2462	-15.86	-	-	2.50	-	8.00	-	Pass	

Measured power density (dBm) has offset with cable loss.

Appendix B. AC Conducted Emission Test Results

Toot Engineer	limmy Chang	Temperature :	24~26 ℃
Test Engineer :	Jimmy Chang	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark:	All emissions not reported here are more that	an 10 dB below the pre	scribed limit

Report No.: FR8D1930A




Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
0.154500	46.72		65.75	19.03	L1	OFF	19.5
0.154500		33.24	55.75	22.51	L1	OFF	19.5
0.170250	45.44		64.95	19.51	L1	OFF	19.5
0.170250		32.59	54.95	22.36	L1	OFF	19.5
0.512250	33.50		56.00	22.50	L1	OFF	19.5
0.512250		25.78	46.00	20.22	L1	OFF	19.5
4.641000	35.51		56.00	20.49	L1	OFF	19.6
4.641000		22.64	46.00	23.36	L1	OFF	19.6
12.018750	26.84		60.00	33.16	L1	OFF	19.7
12.018750		22.75	50.00	27.25	L1	OFF	19.7
12.862500	25.39		60.00	34.61	L1	OFF	19.7
12.862500		21.53	50.00	28.47	L1	OFF	19.7
13.566750	24.76		60.00	35.24	L1	OFF	19.7
13.566750		20.91	50.00	29.09	L1	OFF	19.7
14.149500	23.64		60.00	36.36	L1	OFF	19.7
14.149500		20.10	50.00	29.90	L1	OFF	19.7
15.148500	22.50		60.00	37.50	L1	OFF	19.8
15.148500		19.16	50.00	30.84	L1	OFF	19.8
15.823500	21.46		60.00	38.54	L1	OFF	19.8
15.823500		18.24	50.00	31.76	L1	OFF	19.8
26.133000	16.07		60.00	43.93	L1	OFF	19.8
26.133000		14.76	50.00	35.24	L1	OFF	19.8

TEL: 886-3-327-3456 Page Number : B1 of B3

Toot Engineer	limmy Chang	Temperature :	24~26 ℃
Test Engineer :		Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
	All emissions not reported here are more that	an 10 dB below the pre	escribed limit.

Report No.: FR8D1930A




Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
0.152250	50.29		65.88	15.59	N	OFF	19.5
0.152250		35.42	55.88	20.46	N	OFF	19.5
0.186000	44.18		64.21	20.03	N	OFF	19.5
0.186000		29.19	54.21	25.02	N	OFF	19.5
0.498750	32.77		56.02	23.25	N	OFF	19.5
0.498750		26.78	46.02	19.24	N	OFF	19.5
3.815250	29.56		56.00	26.44	N	OFF	19.6
3.815250		22.45	46.00	23.55	N	OFF	19.6
4.998750	29.39		56.00	26.61	N	OFF	19.6
4.998750		20.75	46.00	25.25	N	OFF	19.6
6.261000	24.53		60.00	35.47	N	OFF	19.6
6.261000		18.99	50.00	31.01	N	OFF	19.6
6.668250	25.32		60.00	34.68	N	OFF	19.6
6.668250		19.60	50.00	30.40	N	OFF	19.6
7.705500	25.83		60.00	34.17	N	OFF	19.7
7.705500		18.52	50.00	31.48	N	OFF	19.7
8.412000	25.32		60.00	34.68	N	OFF	19.7
8.412000		19.14	50.00	30.86	N	OFF	19.7
8.457000	26.28		60.00	33.72	N	OFF	19.7
8.457000		19.18	50.00	30.82	N	OFF	19.7
8.551500	25.60		60.00	34.40	N	OFF	19.7
8.551500		19.18	50.00	30.82	N	OFF	19.7

TEL: 886-3-327-3456 Page Number: B2 of B3

Test Engineer :	limmy Chang	Temperature :	24~26 ℃
rest Engineer .	Jaminy Chang	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark:	All emissions not reported here are more that	an 10 dB below the pre	escribed limit.

Report No.: FR8D1930A



Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
9.249000	26.09		60.00	33.91	N	OFF	19.7
9.249000		19.95	50.00	30.05	N	OFF	19.7
9.789000	29.68		60.00	30.32	N	OFF	19.7
9.789000		22.32	50.00	27.68	N	OFF	19.7
9.924000	32.51		60.00	27.49	N	OFF	19.7
9.924000		22.24	50.00	27.76	N	OFF	19.7
10.000500	38.76		60.00	21.24	N	OFF	19.7
10.000500		22.62	50.00	27.38	N	OFF	19.7
10.077000	32.68		60.00	27.32	N	OFF	19.7
10.077000		22.16	50.00	27.84	N	OFF	19.7
10.207500	23.67		60.00	36.33	N	OFF	19.7
10.207500		20.18	50.00	29.82	N	OFF	19.7
10.745250	22.76		60.00	37.24	N	OFF	19.7
10.745250		19.54	50.00	30.46	N	OFF	19.7
11.445000	21.68		60.00	38.32	N	OFF	19.7
11.445000		18.80	50.00	31.20	N	OFF	19.7
12.288750	20.97		60.00	39.03	N	OFF	19.7
12.288750		18.33	50.00	31.67	N	OFF	19.7
15.024750	17.66		60.00	42.34	N	OFF	19.8
15.024750		15.63	50.00	34.37	N	OFF	19.8
29.998500	16.30		60.00	43.70	N	OFF	20.1
29.998500		15.46	50.00	34.54	N	OFF	20.1

TEL: 886-3-327-3456 Page Number : B3 of B3

Appendix C. Conducted Spurious Emission

Test Engineer :	Karl Hou	Temperature :	23~25°C
rest Engineer .		Relative Humidity :	52~58%

Report No.: FR8D1930A

2.4GHz 2400~2483.5MHz WIFI 802.11b (Band Edge)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	MIMO	Groun ding	Peak
Ant. 1		(MHz)	(dBm)	Limit (dB)	Line (dBm)	Level (dBm)	Gain (dBi)	Loss (dB)	Factor (dB)	Factor (dB)	Avg. (P/A)
000 445		2375.835	-38.45	-17.25	-21.2	-43.01	2.5	2.06	0	0	Р
802.11b		2389.695	-46.74	-5.54	-41.2	-51.3	2.5	2.06	0	0	Α
CH 01 2412MHz	*	2412	13.03	-	-	8.45	2.5	2.08	0	0	Р
2412141712	*	2412	10.56	-	-	5.98	2.5	2.08	0	0	Α
		2383.64	-40.98	-19.78	-21.2	-45.54	2.5	2.06	0	0	Р
		2357.74	-48.17	-6.97	-41.2	-52.71	2.5	2.04	0	0	Α
802.11b	*	2437	13.13	-	-	8.55	2.5	2.08	0	0	Р
CH 06 2437MHz	*	2437	10.66	-	-	6.08	2.5	2.08	0	0	Α
2437 WITZ		2490.48	-40.94	-19.74	-21.2	-45.55	2.5	2.11	0	0	Р
		2483.5	-48.73	-7.53	-41.2	-53.33	2.5	2.1	0	0	Α
	*	2462	12.62	-	-	8.02	2.5	2.1	0	0	Р
802.11b	*	2462	10.19	-	-	5.59	2.5	2.1	0	0	Α
CH 11 2462MHz		2486.56	-38.21	-17.01	-21.2	-42.81	2.5	2.1	0	0	Р
2402IVITI2		2484.56	-46.32	-5.12	-41.2	-50.92	2.5	2.1	0	0	Α
Remark		o other spurio		st Peak	and Averaç	je limit lin	e.				

TEL: 886-3-327-3456 Page Number : C1 of C9

2.4GHz 2400~2483.5MHz WIFI 802.11b (Harmonic)

Report No. : FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	МІМО	Groun ding	Peak
Ant. 1		(MHz)	(dBm)	Limit (dB)	Line (dBm)	Level (dBm)	Gain (dBi)	Loss (dB)	Factor (dB)	Factor (dB)	Avg. (P/A)
802.11b		4018.7	-45.97	-24.77	-21.2	-51.88	2.5	3.41	0	0	Р
CH 01 2412MHz		4824	-58.74	-37.54	-21.2	-64.82	2.5	3.58	0	0	Р
802.11b		4061.4	-46.19	-24.99	-21.2	-52.14	2.5	3.45	0	0	Р
CH 06		4874	-46.47	-25.27	-21.2	-52.56	2.5	3.59	0	0	Р
2437MHz		7311	-63.62	-42.42	-21.2	-70.57	2.5	4.45	0	0	Р
		4104.1	-51.7	-30.5	-21.2	-57.67	2.5	3.47	0	0	Р
802.11b		4924	-41.42	-20.22	-21.2	-47.51	2.5	3.59	0	0	Р
CH 11 2462MHz		4924	-42.29	-1.09	-41.2	-48.38	2.5	3.59	0	0	Α
2402WINZ		7386	-71.18	-49.98	-21.2	-78.21	2.5	4.53	0	0	Р
Remark		o other spurio I results are P		st Peak	and Averaç	je limit lin	e.				

TEL: 886-3-327-3456 Page Number : C2 of C9

2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge)

Report No. : FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	МІМО	Groun ding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Factor	Avg.
1		(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dBi)	(dB)	(dB)	(dB)	(P/A)
000 44		2389.59	-35.39	-14.19	-21.2	-39.95	2.5	2.06	0	0	Р
802.11g		2389.905	-43.49	-2.29	-41.2	-48.05	2.5	2.06	0	0	Α
CH 01	*	2412	11.01	-	-	6.43	2.5	2.08	0	0	Р
2412MHz	*	2412	4.37	-	-	-0.21	2.5	2.08	0	0	Α
802.11g		2323.02	-41.59	-20.39	-21.2	-46.11	2.5	2.02	0	0	Р
		2383.5	-48.13	-6.93	-41.2	-52.69	2.5	2.06	0	0	Α
	*	2437	14.93	-	-	10.35	2.5	2.08	0	0	Р
CH 06 2437MHz	*	2437	8.86	-	-	4.28	2.5	2.08	0	0	Α
2437 WIFI2		2494.82	-41.2	-20	-21.2	-45.81	2.5	2.11	0	0	Р
		2486.28	-47.67	-6.47	-41.2	-52.27	2.5	2.1	0	0	Α
	*	2462	10.4	-	-	5.8	2.5	2.1	0	0	Р
802.11g	*	2462	3.98	-	-	-0.62	2.5	2.1	0	0	Α
CH 11 2462MHz		2483.92	-35.21	-14.01	-21.2	-39.81	2.5	2.1	0	0	Р
		2483.64	-42.46	-1.26	-41.2	-47.06	2.5	2.1	0	0	Α
Remark		o other spurio		st Peak	and Averag	je limit lin	e.				

Page Number TEL: 886-3-327-3456 : C3 of C9

2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic)

Report No. : FR8D1930A

viii i oozii i g (i ai ii oo											
WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	МІМО	Groun ding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Factor	Avg.
1		(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dBi)	(dB)	(dB)	(dB)	(P/A)
802.11g		4018.7	-47.67	-26.47	-21.2	-53.58	2.5	3.41	0	0	Р
CH 01											
2412MHz		4824	-63.77	-42.57	-21.2	-69.85	2.5	3.58	0	0	Р
000 44		4061	-42.96	-21.76	-21.2	-48.91	2.5	3.45	0	0	Р
802.11g CH 06		4061	-49.99	-8.79	-41.2	-55.94	2.5	3.45	0	0	Α
2437MHz		4874	-47.86	-26.66	-21.2	-53.95	2.5	3.59	0	0	Р
240711112		7311	-61.58	-40.38	-21.2	-68.53	2.5	4.45	0	0	Р
802.11g		4104.1	-50.91	-29.71	-21.2	-56.88	2.5	3.47	0	0	Р
CH 11		4924	-52.86	-31.66	-21.2	-58.95	2.5	3.59	0	0	Р
2462MHz		7386	-73.3	-52.1	-21.2	-80.33	2.5	4.53	0	0	Р
Remark		o other spurio		st Peak	and Averaç	ge limit lin	e.				

TEL: 886-3-327-3456 Page Number : C4 of C9

2.4GHz 2400~2483.5MHz

Report No. : FR8D1930A

WIFI 802.11n HT20 (Band Edge)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	МІМО	Groun ding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Factor	Avg.
1		(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dBi)	(dB)	(dB)	(dB)	(P/A)
802.11n		2388.75	-31.54	-10.34	-21.2	-36.1	2.5	2.06	0	0	Р
HT20		2389.905	-42.22	-1.02	-41.2	-46.78	2.5	2.06	0	0	Α
CH 01	*	2412	9.78	-	-	5.2	2.5	2.08	0	0	Р
2412MHz	*	2412	3.17	-	-	-1.41	2.5	2.08	0	0	Α
		2389.94	-38.82	-17.62	-21.2	-43.38	2.5	2.06	0	0	Р
802.11n		2387.7	-48.26	-7.06	-41.2	-52.82	2.5	2.06	0	0	Α
HT20	*	2437	14.5	-	-	9.92	2.5	2.08	0	0	Р
CH 06	*	2437	8.02	-	-	3.44	2.5	2.08	0	0	Α
2437MHz		2485.02	-40.36	-19.16	-21.2	-44.96	2.5	2.1	0	0	Р
		2485.37	-47.61	-6.41	-41.2	-52.21	2.5	2.1	0	0	Α
802.11n	*	2462	10.1	-	-	5.5	2.5	2.1	0	0	Р
HT20	*	2462	3.41	-	-	-1.19	2.5	2.1	0	0	Α
CH 11		2483.84	-32.93	-11.73	-21.2	-37.53	2.5	2.1	0	0	Р
2462MHz		2483.76	-41.68	-0.48	-41.2	-46.28	2.5	2.1	0	0	Α
Remark		o other spurio I results are P		st Peak	and Averaç	je limit lin	e.				

TEL: 886-3-327-3456 Page Number : C5 of C9

2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Harmonic)

Report No.: FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	MIMO	Groun ding	Peak
Ant. 1		(MHz)	(dBm)	Limit (dB)	Line (dBm)	Level (dBm)	Gain (dBi)	Loss (dB)	Factor (dB)	Factor (dB)	Avg. (P/A)
802.11n HT20		4018.7	-46.63	-25.43	-21.2	-52.54	2.5	3.41	0	0	Р
CH 01 2412MHz		4824	-63.1	-41.9	-21.2	-69.18	2.5	3.58	0	0	Р
802.11n		4061	-43.92	-22.72	-21.2	-49.87	2.5	3.45	0	0	Р
HT20		4061	-50.86	-9.66	-41.2	-56.81	2.5	3.45	0	0	Α
CH 06		4874	-49.69	-28.49	-21.2	-55.78	2.5	3.59	0	0	Р
2437MHz		7311	-59.84	-38.64	-21.2	-66.79	2.5	4.45	0	0	Р
802.11n		4104.1	-50.64	-29.44	-21.2	-56.61	2.5	3.47	0	0	Р
HT20 CH 11		4924	-50.83	-29.63	-21.2	-56.92	2.5	3.59	0	0	Р
2462MHz		7386	-71.89	-50.69	-21.2	-78.92	2.5	4.53	0	0	Р
Remark		o other spurio I results are P		st Peak	and Averag	je limit lin	e.		1		1

TEL: 886-3-327-3456 Page Number : C6 of C9

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	МІМО	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Factor	Avg.
1		(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dBi)	(dB)	(dB)	(dB)	(P/A)
		45.12	-77.09	-21.89	-55.2	-84.55	2.5	0.26	0	4.7	Р
2.4GHz		185.25	-75.24	-23.54	-51.7	-83.15	2.5	0.71	0	4.7	Р
802.11n		232.5	-75.3	-26.1	-49.2	-83.19	2.5	0.69	0	4.7	Р
HT20		437.2	-75.59	-26.39	-49.2	-83.67	2.5	0.88	0	4.7	Р
LF		640.9	-73.12	-23.92	-49.2	-81.41	2.5	1.09	0	4.7	Р
		822.9	-69.89	-20.69	-49.2	-78.39	2.5	1.3	0	4.7	Р
Remark		o other spuric		st Peak	and Avera	ige limit li	ne.				

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: C7 of C9

Report No. : FR8D1930A

Note symbol

Report No. : FR8D1930A

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average

TEL: 886-3-327-3456 Page Number : C8 of C9

A calculation example for radiated spurious emission is shown as below:

Report No.: FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	МІМО	Groun ding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Factor	Avg.
1		(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dBi)	(dB)	(dB)	(dB)	(P/A)
802.11b		2386.545	-39.03	-17.83	-21.2	-44.06	2	3.03	0	0	Р
CH 01											
2412MHz		2386.125	-48.1	-6.9	-41.2	-53.13	2	3.03	0	0	Α

1. Level(dBm) =

Antenna Gain(dBi) + Path Loss(dB) + Read Level(dBm) + MIMO Factor(dB) + Grounding Factor(dB)

2. Over Limit(dB) = Level(dBm) - Limit Line(dBm)

For Peak Limit @ 2386.545MHz:

- 1. Level(dBm)
- = Antenna Gain(dBi) + Path Loss(dB) + Read Level(dBm) + MIMO Factor(dB) + Grounding Factor(dB)
- = 2(dB) + 3.03(dB) 44.06(dBm)
- = -39.03(dBm)
- 2. Over Limit(dB)
- = Level(dBm) Limit Line(dBm)
- = -39.03(dBm) + 21.2(dBm)
- = -17.83(dB)

For Average Limit @ 2386.125MHz:

- 1. Level(dBm)
- = Antenna Gain(dBi) + Path Loss(dB) + Read Level(dBm) + MIMO Factor(dB) + Grounding Factor(dB)
- = 2(dBi) + 3.03(dB) 53.13(dBm)
- = -48.1(dBm)
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -6.9(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

TEL: 886-3-327-3456 Page Number : C9 of C9

Appendix D. Conducted Spurious Emission Plots

Took Engineer		Temperature :	23~25°C
Test Engineer :	Karl Hou	Relative Humidity :	52~58%

Report No.: FR8D1930A


Note symbol

-L	Low channel location
-R	High channel location

TEL: 886-3-327-3456 Page Number : D1 of D20


2.4GHz 2400~2483.5MHz WIFI 802.11b (Band Edge)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : D2 of D20

CC RADIO TEST REPORT Report No. : FR8D1930A




TEL: 886-3-327-3456 Page Number: D3 of D20

WIFI 2.4GHz 2400~2483.5MHz Band Edge ANT 802.11b CH06 2437MHz - R 1 **CSE Fundamental** Peak Left blank Avg. Left blank

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number: D4 of D20


CC RADIO TEST REPORT Report No. : FR8D1930A



TEL: 886-3-327-3456 Page Number: D5 of D20


2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number: D6 of D20

CC RADIO TEST REPORT Report No. : FR8D1930A




TEL: 886-3-327-3456 Page Number: D7 of D20

WIFI 2.4GHz 2400~2483.5MHz Band Edge 802.11g CH06 2437MHz - R ANT 1 **CSE Fundamental** Peak Left blank Avg. Left blank

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : D8 of D20






TEL: 886-3-327-3456 Page Number: D9 of D20


2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Band Edge)

Report No.: FR8D1930A




TEL: 886-3-327-3456 Page Number : D10 of D20






TEL: 886-3-327-3456 Page Number : D11 of D20





TEL: 886-3-327-3456 Page Number : D12 of D20


C RADIO TEST REPORT Report No. : FR8D1930A




TEL: 886-3-327-3456 Page Number : D13 of D20

2.4GHz 2400~2483.5MHz WIFI 802.11b (Harmonic)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : D14 of D20




Report No.: FR8D1930A


TEL: 886-3-327-3456 Page Number : D15 of D20

2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : D16 of D20




Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : D17 of D20


2.4GHz 2400~2483.5MHz

Report No.: FR8D1930A

WIFI 802.11n HT20 (Harmonic)



TEL: 886-3-327-3456 Page Number : D18 of D20




Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : D19 of D20

Emission below 1GHz 2.4GHz WIFI 802.11n HT20 (LF)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : D20 of D20

Appendix E. Cabinet Radiated Spurious Emission

Test Engineer :		Temperature :	23~26°C
rest Engineer .	Karl Hou, Big Show Wang	Relative Humidity :	50~65%

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : E1 of E13

2.4GHz 2400~2483.5MHz

Report No. : FR8D1930A

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2350.32	53.86	-20.14	74	41.06	27.7	16.11	31.01	100	305	Р	Н
		2352.105	44.58	-9.42	54	31.81	27.67	16.11	31.01	100	305	Α	Н
000 446	*	2412	76.19	-	-	63.39	27.6	16.18	30.98	100	305	Р	Н
802.11b CH 01	*	2412	72.65	-	-	59.85	27.6	16.18	30.98	100	305	Α	Н
2412MHz		2332.995	53.81	-20.19	74	40.98	27.77	16.08	31.02	333	261	Р	V
24 (21911)2		2314.305	44.63	-9.37	54	31.77	27.83	16.06	31.03	333	261	Α	V
	*	2412	77.2	-	-	64.4	27.6	16.18	30.98	333	261	Р	٧
	*	2412	73.71	-	-	60.91	27.6	16.18	30.98	333	261	Α	٧
		2347.38	53.93	-20.07	74	41.14	27.7	16.1	31.01	100	302	Р	Τ
		2341.92	44.58	-9.42	54	31.8	27.7	16.09	31.01	100	302	Α	Τ
	*	2437	77.1	-	-	64.26	27.6	16.21	30.97	100	302	Р	Τ
	*	2437	73.84	-	-	61	27.6	16.21	30.97	100	302	Α	Н
		2490.55	52.57	-21.43	74	39.85	27.4	16.26	30.94	100	302	Р	Н
802.11b		2500	44.29	-9.71	54	31.56	27.4	16.27	30.94	100	302	Α	Н
CH 06 2437MHz		2314.62	54.52	-19.48	74	41.66	27.83	16.06	31.03	369	262	Р	٧
2437 WITIZ		2336.74	44.89	-9.11	54	32.12	27.7	16.09	31.02	369	262	Α	٧
	*	2437	76.68	-	-	63.84	27.6	16.21	30.97	369	262	Р	V
	*	2437	73.25	-	-	60.41	27.6	16.21	30.97	369	262	Α	V
		2492.37	52.97	-21.03	74	40.25	27.4	16.26	30.94	369	262	Р	V
		2493.14	44.16	-9.84	54	31.44	27.4	16.26	30.94	369	262	Α	٧

TEL: 886-3-327-3456 Page Number: E2 of E13



FCC RADIO TEST REPORT

	*	2462	76.59	-	-	63.79	27.53	16.23	30.96	100	299	Р	Н
	*	2462	73.18	-	-	60.38	27.53	16.23	30.96	100	299	Α	Н
222.441		2493	53.23	-20.77	74	40.51	27.4	16.26	30.94	100	299	Р	Н
802.11b CH 11		2485.04	44.6	-9.4	54	31.82	27.47	16.26	30.95	100	299	Α	Н
2462MHz	*	2462	75.72	-	-	62.92	27.53	16.23	30.96	362	260	Р	V
2402111112	*	2462	72.1	-	-	59.3	27.53	16.23	30.96	362	260	Α	V
		2487.28	53.58	-20.42	74	40.8	27.47	16.26	30.95	362	260	Р	V
		2494.88	44.68	-9.32	54	31.96	27.4	16.26	30.94	362	260	Α	V

Report No.: FR8D1930A

Remark

1. No other spurious found.

2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number : E3 of E13

2.4GHz 2400~2483.5MHz

Report No.: FR8D1930A

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg.	
-		4020	46	-28	74	67.43	29.73	8.9	60.06	100	0	P	Н
		4824	45.16	-28.84	74	63.43	31.3	9.59	59.16	100	0	Р	Н
802.11b		4020	54.4	-19.6	74	75.83	29.73	8.9	60.06	348	194	Р	V
CH 01		4020	49.67	-4.33	54	71.1	29.73	8.9	60.06	348	194	Α	V
2412MHz		4824	54.75	-19.25	74	73.02	31.3	9.59	59.16	364	138	Р	V
		4824	51.42	-2.58	54	69.69	31.3	9.59	59.16	364	138	Α	V
		4061	47.85	-26.15	74	69.12	29.8	8.91	59.98	100	0	Р	Н
		4874	48.29	-25.71	74	66.58	31.3	9.58	59.17	100	0	Р	Н
000 441		7311	44.94	-29.06	74	56.26	36.2	11.66	59.18	100	0	Р	Н
802.11b CH 06		4061	54.18	-19.82	74	75.45	29.8	8.91	59.98	303	203	Р	V
2437MHz		4061	49.35	-4.65	54	70.62	29.8	8.91	59.98	303	203	Α	V
2437111112		4874	55.68	-18.32	74	73.97	31.3	9.58	59.17	357	149	Р	V
		4874	51.71	-2.29	54	70	31.3	9.58	59.17	357	149	Α	V
		7311	47.6	-26.4	74	58.92	36.2	11.66	59.18	100	0	Р	V
		4103	48.44	-25.56	74	69.6	29.8	8.93	59.89	100	0	Р	Н
		4924	49.33	-24.67	74	67.57	31.37	9.57	59.18	100	0	Р	Н
802.11b		7386	45.37	-28.63	74	56.35	36.5	11.67	59.15	100	0	Р	Н
CH 11		4103	53.81	-20.19	74	74.97	29.8	8.93	59.89	314	207	Р	V
2462MHz		4103	48.92	-5.08	54	70.08	29.8	8.93	59.89	314	207	Α	V
		4924	55.58	-18.42	74	73.82	31.37	9.57	59.18	394	149	Р	V
		4924	52.55	-1.45	54	70.79	31.37	9.57	59.18	394	149	Α	V
		7386	47.77	-26.23	74	58.75	36.5	11.67	59.15	100	0	Р	V

Remark

1. No other spurious found.
2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number : E4 of E13

2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge @ 3m)

Report No. : FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2383.92	54.19	-19.81	74	41.4	27.63	16.15	30.99	100	304	Р	Н
		2315.775	46.09	-7.91	54	33.22	27.83	16.06	31.02	100	304	Α	Н
902 44 ~	*	2412	73.82	-	-	61.02	27.6	16.18	30.98	100	304	Р	Н
802.11g CH 01	*	2412	66.53	-	-	53.73	27.6	16.18	30.98	100	304	Α	Н
2412MHz		2324.28	53.99	-20.01	74	41.17	27.77	16.07	31.02	343	260	Р	V
2412191112		2380.245	46.21	-7.79	54	33.44	27.63	16.14	31	343	260	Α	V
	*	2412	74.19	-	-	61.39	27.6	16.18	30.98	343	260	Р	V
	*	2412	67.68	-	-	54.88	27.6	16.18	30.98	343	260	Α	V
		2338.42	53.4	-20.6	74	40.62	27.7	16.09	31.01	100	300	Р	Н
		2341.36	46.11	-7.89	54	33.33	27.7	16.09	31.01	100	300	Α	Н
	*	2437	78.85	-	-	66.01	27.6	16.21	30.97	100	300	Р	Н
	*	2437	72.3	-	-	59.46	27.6	16.21	30.97	100	300	Α	Н
		2488.52	53.63	-20.37	74	40.92	27.4	16.26	30.95	100	300	Р	Н
802.11g		2485.58	45.73	-8.27	54	32.95	27.47	16.26	30.95	100	300	Α	Н
CH 06 2437MHz		2371.74	53.88	-20.12	74	41.12	27.63	16.13	31	327	263	Р	٧
2437 WII 12		2364.88	46.27	-7.73	54	33.48	27.67	16.12	31	327	263	Α	V
	*	2437	78.16	-	-	65.32	27.6	16.21	30.97	327	263	Р	V
	*	2437	72.02	-	-	59.18	27.6	16.21	30.97	327	263	Α	٧
		2485.37	54.45	-19.55	74	41.67	27.47	16.26	30.95	327	263	Р	٧
		2496.01	45.93	-8.07	54	33.2	27.4	16.27	30.94	327	263	Α	V

TEL: 886-3-327-3456 Page Number : E5 of E13



FCC RADIO TEST REPORT

	*	2462	74.52	-	-	61.72	27.53	16.23	30.96	100	297	Р	Н
	*	2462	66.92	-	-	54.12	27.53	16.23	30.96	100	297	Α	Н
		2495.16	53.45	-20.55	74	40.72	27.4	16.27	30.94	100	297	Р	Н
802.11g		2491.84	46.04	-7.96	54	33.32	27.4	16.26	30.94	100	297	Α	Н
CH 11 2462MHz	*	2462	72.95	-	-	60.15	27.53	16.23	30.96	352	262	Р	٧
2402WIFI2	*	2462	66.09	1	-	53.29	27.53	16.23	30.96	352	262	Α	V
		2493.36	53.33	-20.67	74	40.61	27.4	16.26	30.94	352	262	Р	V
		2497	46.06	-7.94	54	33.33	27.4	16.27	30.94	352	262	Α	V
Remark		o other spurio		st Peak	and Averac	ge limit lin	e.						

Report No. : FR8D1930A

All results are PASS against Peak and Average limit line.

Page Number TEL: 886-3-327-3456 : E6 of E13

2.4GHz 2400~2483.5MHz

Report No.: FR8D1930A

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.		(MHz)	(dBµV/m)	Limit	Line (dBµV/m)	Level	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos	Avg.	
		4020	45.51	-28.49	74	66.94	29.73	8.9	60.06	100	0	Р	Н
802.11g		4824	38.5	-35.5	74	56.77	31.3	9.59	59.16	100	0	Р	Н
CH 01		4020	54.11	-19.89	74	75.54	29.73	8.9	60.06	302	195	Р	V
2412MHz		4020	46.71	-7.29	54	68.14	29.73	8.9	60.06	302	195	Α	V
		4824	43.18	-30.82	74	61.45	31.3	9.59	59.16	100	0	Р	V
		4061	46.49	-27.51	74	67.76	29.8	8.91	59.98	100	0	Р	Н
		4874	44.48	-29.52	74	62.77	31.3	9.58	59.17	100	0	Р	Н
802.11g		7311	46.15	-27.85	74	57.47	36.2	11.66	59.18	100	0	Р	Н
CH 06		4061	54.8	-19.2	74	76.07	29.8	8.91	59.98	321	213	Р	V
2437MHz		4061	47.84	-6.16	54	69.11	29.8	8.91	59.98	321	213	Α	V
		4874	48.96	-25.04	74	67.25	31.3	9.58	59.17	100	0	Р	V
		7311	48.28	-25.72	74	59.6	36.2	11.66	59.18	100	0	Р	V
		4095	45.51	-28.49	74	66.69	29.8	8.93	59.91	100	0	Р	Н
		4924	38.29	-35.71	74	56.53	31.37	9.57	59.18	100	0	Р	Н
802.11g		7386	42.64	-31.36	74	53.62	36.5	11.67	59.15	100	0	Р	Н
CH 11 2462MHz		4095	48.15	-25.85	74	69.33	29.8	8.93	59.91	100	0	Р	V
Z40ZIVI FIZ		4924	42.16	-31.84	74	60.4	31.37	9.57	59.18	100	0	Р	V
		7386	43.28	-30.72	74	54.26	36.5	11.67	59.15	100	0	Р	V

Remark

TEL: 886-3-327-3456 Page Number : E7 of E13

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Band Edge @ 3m)

Report No. : FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.		(BALL -)	(-ID)//)	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	(1100
1		(MHz)	(dBµV/m)	, ,	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)			(H/V)
		2378.46	53.48	-20.52	74	40.71	27.63	16.14	31	328	300	Р	Н
		2344.65	46.16	-7.84	54	33.37	27.7	16.1	31.01	328	300	Α	Н
802.11n	*	2412	74.16	-	-	61.36	27.6	16.18	30.98	328	300	Р	Н
HT20	*	2412	67.35	-	-	54.55	27.6	16.18	30.98	328	300	Α	Н
CH 01		2373.525	53.93	-20.07	74	41.16	27.63	16.14	31	348	261	Р	٧
2412MHz		2343.915	46.23	-7.77	54	33.44	27.7	16.1	31.01	348	261	Α	٧
	*	2412	73.7	-	-	60.9	27.6	16.18	30.98	348	261	Р	V
	*	2412	66.43	-	-	53.63	27.6	16.18	30.98	348	261	Α	V
		2344.3	53.59	-20.41	74	40.8	27.7	16.1	31.01	324	298	Р	H
		2326.24	46.2	-7.8	54	33.38	27.77	16.07	31.02	324	298	Α	H
	*	2437	78.72	-	-	65.88	27.6	16.21	30.97	324	298	Р	H
	*	2437	71.59	-	-	58.75	27.6	16.21	30.97	324	298	Α	I
802.11n		2495.87	53.03	-20.97	74	40.3	27.4	16.27	30.94	324	298	Р	Н
HT20		2499.37	45.69	-8.31	54	32.96	27.4	16.27	30.94	324	298	Α	Н
CH 06		2376.5	53.65	-20.35	74	40.88	27.63	16.14	31	367	263	Р	V
2437MHz		2364.46	46.05	-7.95	54	33.26	27.67	16.12	31	367	263	Α	V
	*	2437	76.87	-	-	64.03	27.6	16.21	30.97	367	263	Р	٧
	*	2437	69.77	-	-	56.93	27.6	16.21	30.97	367	263	Α	V
		2491.32	53.61	-20.39	74	40.89	27.4	16.26	30.94	367	263	Р	V
		2486.21	45.9	-8.1	54	33.12	27.47	16.26	30.95	367	263	Α	٧

TEL: 886-3-327-3456 Page Number : E8 of E13



FCC RADIO TEST REPORT

	*	2462	73.93	-	-	61.13	27.53	16.23	30.96	280	297	Р	Н
	*	2462	66.79	-	-	53.99	27.53	16.23	30.96	280	297	Α	Н
802.11n		2496.64	53.38	-20.62	74	40.65	27.4	16.27	30.94	280	297	Р	Н
HT20		2498	45.93	-8.07	54	33.2	27.4	16.27	30.94	280	297	Α	Н
CH 11	*	2462	72.72	-	-	59.92	27.53	16.23	30.96	360	262	Р	V
2462MHz	*	2462	65.59	-	-	52.79	27.53	16.23	30.96	360	262	Α	٧
		2496.24	53.48	-20.52	74	40.75	27.4	16.27	30.94	360	262	Р	٧
		2488.44	46.11	-7.89	54	33.4	27.4	16.26	30.95	360	262	Α	V

Report No.: FR8D1930A

Remark

. No other spurious found.

2. All results are PASS against Peak and Average limit line.

TEL: 886-3-327-3456 Page Number : E9 of E13

2.4GHz 2400~2483.5MHz

Report No.: FR8D1930A

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBµV/m)	Limit (dB)	Line (dBµV/m)	Level (dBµV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	
802.11n		4020	43.2	-30.8	74	64.63	29.73	8.9	60.06	100	0	Р	Н
HT20		4824	37.62	-36.38	74	55.89	31.3	9.59	59.16	100	0	Р	Н
CH 01		4020	49.07	-24.93	74	70.5	29.73	8.9	60.06	100	0	Р	V
2412MHz		4824	43.2	-30.8	74	61.47	31.3	9.59	59.16	100	0	Р	V
		4061	45.57	-28.43	74	66.84	29.8	8.91	59.98	100	0	Р	Н
		4874	41.76	-32.24	74	60.05	31.3	9.58	59.17	100	0	Р	Н
802.11n		7311	43.74	-30.26	74	55.06	36.2	11.66	59.18	100	0	Р	Н
HT20 CH 06		4061	53.91	-20.09	74	75.18	29.8	8.91	59.98	300	214	Р	V
2437MHz		4061	47.14	-6.86	54	68.41	29.8	8.91	59.98	300	214	Α	V
2437 WII 12		4874	46.9	-27.1	74	65.19	31.3	9.58	59.17	100	0	Р	V
		7311	47.35	-26.65	74	58.67	36.2	11.66	59.18	100	0	Р	V
		4095	43.38	-30.62	74	64.56	29.8	8.93	59.91	100	0	Р	Н
802.11n		4924	38.54	-35.46	74	56.78	31.37	9.57	59.18	100	0	Р	Н
HT20		7386	43.21	-30.79	74	54.19	36.5	11.67	59.15	100	0	Р	Н
CH 11		4095	47.3	-26.7	74	68.48	29.8	8.93	59.91	100	0	Р	V
2462MHz		4924	41.78	-32.22	74	60.02	31.37	9.57	59.18	100	0	Р	V
		7386	43.1	-30.9	74	54.08	36.5	11.67	59.15	100	0	Р	V

: E10 of E13 TEL: 886-3-327-3456 Page Number

No other spurious found.

All results are PASS against Peak and Average limit line.

Emission below 1GHz 2.4GHz WIFI 802.11b (LF)

Report No.: FR8D1930A

WIFI Note Frequency Level Over Limit Read Antenna Path Preamp Ant Table Peak Pol. Ant. Limit Line Level Factor Loss Factor Pos Pos QP 1 (MHz) (dBµV/m) | (dB) | (dBµV/m) | (dBµV) (dB/m) (dB) (dB) (cm) (deg) (P/Q) (H/V) 95.96 41.99 204 -1.51 43.5 57.78 15.4 32.52 30 Q Η 1.33 32.54 296.75 41.69 -4.31 46 52.69 19.24 2.3 100 320 Q Н 526.64 36.87 -9.13 46 42.35 24.1 3 32.58 169 41 Q Н Р 27.18 719.67 33.13 -12.8746 34.85 3.46 32.36 Η Ρ 824.43 32.04 -13.96 46 32.16 28.19 3.76 32.07 Η 2.4GHz Ρ 943.74 33.03 -12.97 46 29.73 30.52 4.05 31.27 Η 802.11b Ρ ٧ 95.96 37.33 -6.17 43.5 53.12 15.4 1.33 32.52 100 0 LF 263.77 27.58 -18.42 46 37.89 20 2.21 32.52 Ρ V 385.99 35.51 -10.49 46 44.18 21.34 2.54 32.55 Ρ ٧ 519.85 32.48 -13.5246 37.99 24.1 2.97 32.58 Ρ ٧ Ρ ٧ 32.23 785.63 30.66 -15.34 46 30.85 28.39 3.65 Ρ ٧ 872.93 32.26 -13.74 46 31.15 29 3.91 31.8

Remark

TEL: 886-3-327-3456 Page Number : E11 of E13

^{1.} No other spurious found.

^{2.} All results are PASS against limit line.

Note symbol

Report No. : FR8D1930A

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A/Q	Peak or Average or Quasi-Peak
H/V	Horizontal or Vertical

TEL: 886-3-327-3456 Page Number : E12 of E13

A calculation example for radiated spurious emission is shown as below:

Report No.: FR8D1930A

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

- 1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- 2. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

TEL: 886-3-327-3456 Page Number : E13 of E13

Appendix F. Cabinet Radiated Spurious Emission Plots

Test Engineer :	Karl Hou, Big Show Wang	Temperature :	23~26°C
rest Engineer.		Relative Humidity :	50~65%

Report No.: FR8D1930A


Note symbol

-L	Low channel location
-R	High channel location

TEL: 886-3-327-3456 Page Number : F1 of F35


2.4GHz 2400~2483.5MHz WIFI 802.11b (Band Edge @ 3m)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : F2 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A



TEL: 886-3-327-3456 Page Number : F3 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11b CH06 2437MHz - L 1 Horizontal **Fundamental** Peak Avg.

Report No.: FR8D1930A


TEL: 886-3-327-3456 Page Number : F4 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11b CH06 2437MHz - R 1 Horizontal **Fundamental** Peak Left blank : 03CH15-HY : PEAK_BE_74 3m 9120b_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto : Peak Left blank Avg. : 03CH15-HY : AV6_BE_54 3m 9120b_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto : Peak

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number : F5 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A




TEL: 886-3-327-3456 Page Number : F6 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11b CH06 2437MHz - R 1 Vertical **Fundamental** Peak Left blank : 03CH15-HY : PEAK_BE_74 3m 9120D_15_1620 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto : Peak Left blank Avg. requency (MHz)
: 03CH15-HY
: AVG_BE_54 3m 9120D_15_1620 VERTICAL
: RBW:1000,000KHz VBW:3,000KHz SWT:Auto

Report No.: FR8D1930A


TEL: 886-3-327-3456 Page Number : F7 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A



TEL: 886-3-327-3456 Page Number : F8 of F35






TEL: 886-3-327-3456 Page Number : F9 of F35


2.4GHz 2400~2483.5MHz WIFI 802.11g (Band Edge @ 3m)

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : F10 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A



TEL: 886-3-327-3456 Page Number: F11 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11g CH06 2437MHz - L 1 **Fundamental** Horizontal Peak 2400. 2400. 5 Frequency (MHz) : 03CH15-HY : PEAK_BE_74 3m 9120D_15_1620 HORIZONTAL : R8W:1000.000KHz VBW:3000.000KHz SWT:Auto : Peak Avg.

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number: F12 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11g CH06 2437MHz - R 1 Horizontal **Fundamental** Peak Left blank Frequency (MHz)

: 03CH15-HY
: PEAK_BE_74 3m 9120D_15_1620 HORIZONTAL
: R8W:1000.000KHz VBW:3000.000KHz SWT:Auto
: Peak : 03CH15-HY : AV6_BE_54 3m 9120D_15_1620 HORIZONTAL : R8W-1000.000KHz V8W-10.000KHz SWT:Auto : Peak : 8D1930 : 5 Left blank Avg.

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number: F13 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11g CH06 2437MHz - L 1 Vertical **Fundamental** Peak 2.00. 2400. Frequency (MHz)

: 03CH15-HY
: PEAK_BE_74 3m 9120D_15_1620 VERTICAL
: R8W:1000.000KHz VBW:3000.000KHz SWT:Auto
: Peak Avg.

Report No.: FR8D1930A



Frequency (MHz)

: 03CH15-HY
: AV6_BE_54 3m 9120D_15_1620 VERTICAL
: RBW:1000.000KHz VBW:10.000KHz SWT:Auto
: Peak


WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m 802.11g CH06 2437MHz - R ANT 1 Vertical **Fundamental** Peak Left Blank Frequency (MHz)

: 03CH15-HY
: PEAK_BE_74 3m 9120D_15_1620 VERTICAL
: R8W:1000.000KHz VBW:3000.000KHz SWT:Auto
: Peak Left Blank Avg. : 03CH15-HY : AV6_BE_54 3m 9120D_15_1620 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto : Peak

Report No.: FR8D1930A


TEL: 886-3-327-3456 Page Number: F15 of F35

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number: F16 of F35






TEL: 886-3-327-3456 Page Number: F17 of F35


2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Band Edge @ 3m)

Report No.: FR8D1930A




TEL: 886-3-327-3456 Page Number : F18 of F35

Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number : F19 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A



TEL: 886-3-327-3456 Page Number: F20 of F35


WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11n HT20 CH06 2437MHz - R 1 Horizontal **Fundamental** Peak Left blank Frequency (MHz)

: 03CH15-HY
: PEAK_BE_74 3m 9120D_15_1620 HORIZONTAL
: R8W:1000.000KHz VBW:3000.000KHz SWT:Auto
: Peak Left blank Avg. : 03CH15-HY : AV6_BE_54 3m 9120D_15_1620 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto : Peak

Report No.: FR8D1930A

TEL: 886-3-327-3456 Page Number: F21 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A




TEL: 886-3-327-3456 Page Number: F22 of F35

WIFI 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT 802.11n HT20 CH06 2437MHz - R 1 Vertical **Fundamental** Peak Left Blank : 03CH15-HY : PEAK_BE_74 3m 9120D_15_1620 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto : Peak Left Blank Avg. : 03CH15-HV : AV6_BE_54 3m 9120D_15_1620 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto : Peak

Report No.: FR8D1930A


TEL: 886-3-327-3456 Page Number: F23 of F35

CC RADIO TEST REPORT Report No. : FR8D1930A



TEL: 886-3-327-3456 Page Number: F24 of F35


TEST REPORT Report No. : FR8D1930A




TEL: 886-3-327-3456 Page Number: F25 of F35

2.4GHz 2400~2483.5MHz WIFI 802.11b (Harmonic @ 3m)


Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number: F26 of F35




TEL: 886-3-327-3456 Page Number : F27 of F35




TEL: 886-3-327-3456 Page Number : F28 of F35

2.4GHz 2400~2483.5MHz WIFI 802.11g (Harmonic @ 3m)


Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number: F29 of F35




TEL: 886-3-327-3456 Page Number : F30 of F35




TEL: 886-3-327-3456 Page Number : F31 of F35

2.4GHz 2400~2483.5MHz WIFI 802.11n HT20 (Harmonic @ 3m)


Report No.: FR8D1930A



TEL: 886-3-327-3456 Page Number: F32 of F35




TEL: 886-3-327-3456 Page Number: F33 of F35



TEL: 886-3-327-3456 Page Number : F34 of F35

Emission below 1GHz 2.4GHz WIFI 802.11b (LF)

Report No.: FR8D1930A




TEL: 886-3-327-3456 Page Number: F35 of F35

Appendix G. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
802.11b	51.00	430	2.33	3kHz
802.11g	30.60	158	6.33	10kHz
802.11n HT20	30.60	160	6.25	10kHz

Report No.: FR8D1930A


802.11b



Date: 5.JUN.2019 14:51:03


TEL: 886-3-327-3456 Page Number : G1 of G2

802.11g



Date: 5.JUN.2019 14:55:02

802.11n HT20



Date: 5.JUN.2019 14:58:36

TEL: 886-3-327-3456 Page Number : G2 of G2