

# FCC RF Test Report

**Applicant** : Texas Instruments Incorporated  
**EQUIPMENT** : WiFi and Bluetooth Module  
**Brand Name** : Texas Instruments  
**MODEL NAME** : WL1835MODGA  
**FCC ID** : Z64-WL1835MOD  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The product was received on Aug. 30, 2013 and testing was completed on Oct. 10, 2013. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test .....	6
1.5 Modification of EUT .....	6
1.6 Testing Site .....	7
1.7 Applied Standards .....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Carrier Frequency and Channel .....	8
2.2 Pre-Scanned RF Power .....	9
2.3 Test Mode .....	11
2.4 Connection Diagram of Test System .....	12
2.5 Support Unit used in test configuration and system .....	13
2.6 EUT Operation Test Setup .....	13
2.7 Measurement Results Explanation Example .....	13
<b>3 TEST RESULT .....</b>	<b>14</b>
3.1 6dB and 99% Bandwidth Measurement .....	14
3.2 Peak Output Power Measurement .....	18
3.3 Power Spectral Density Measurement .....	21
3.4 Conducted Band Edges and Spurious Emission Measurement .....	24
3.5 Radiated Band Edges and Spurious Emission Measurement .....	43
3.6 AC Conducted Emission Measurement .....	66
3.7 Antenna Requirements .....	70
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>72</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>73</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR383067C	Rev. 01	Initial issue of report	Oct. 25, 2013
FR383067C	Rev. 02	Update report for revising equipment name, model name, and removing marketing name.	Nov. 06, 2013

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	RSS-Gen 4.6.1	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-210 A8.4	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.53 dB at 2483.950 MHz
3.6	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 8.80 dB at 0.350 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

**Texas Instruments Incorporated**

12500 TI Boulevard M/S 8751. Dallas, TX 75243.

## 1.2 Manufacturer

**Jorjin Technologies Inc.**

17F., No.239, Sec. 1, Datong Rd, Xizhi Dist. New Taipei City 221, Taiwan. R.O.C.

## 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	WiFi and Bluetooth Module
Brand Name	Texas Instruments
Model Name	WL1835MODGA
FCC ID	Z64-WL1835MOD
EUT supports Radios application	WLAN 11b/g/n (HT20/HT40) Bluetooth v3.0 + EDR Bluetooth v4.0 + LE
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard				
Tx/Rx Channel Frequency Range		802.11b/g/n : 2412 MHz ~ 2462 MHz		
Maximum (Peak) Output Power to antenna		<Ant. 1> 802.11b : 19.55 dBm (0.902 W) 802.11g : 21.83 dBm (0.1524 W) 802.11n HT20 : 21.79 dBm (0.1510 W) 802.11n HT40 : 21.60 dBm (0.1445 W) <Ant. 2> 802.11b : 17.37 dBm (0.0546 W) 802.11g : 20.18 dBm (0.1042 W) 802.11n HT20 : 20.04 dBm (0.1009 W) 802.11n HT40 : 19.68 dBm (0.0929 W) <Ant. 1+2> 802.11n HT20 : 23.57 dBm (0.2275 W)		
99% Occupied Bandwidth		<Ant. 1> 802.11b : 14.95MHz 802.11g : 19.45MHz 802.11n HT20 : 19.75MHz 802.11n HT40 : 36.80MHz <MIMO Ant. 1+2(2)> 802.11n HT20 : 19.25MHz		
Antenna Type		<Ant. 1> 802.11b/g/n : Chip Antenna type with gain 1.22 dBi <Ant. 2> 802.11b/g/n : Chip Antenna type with gain -0.36 dBi		
Type of Modulation		802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)		
Antenna Function for Transmitter				
		Ant. 1.	Ant. 2.	
		802.11 b	V	V
		802.11 g	V	V
		802.11 n HT20 SISO	V	V
		802.11 n HT20 MIMO	V	V
802.11n HT40		V	V	

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Site

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978			
Test Site No.	Sporton Site No.			FCC/IC Registration No.
	TH02-HY	CO05-HY	03CH07-HY	722060/4086B-1

**Note:** The test site complies with ANSI C63.4 2003 requirement.

## 1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
- FCC KDB 662911 D01 Multiple Transmitter Output v02.
- ANSI C63.4-2003

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		



## 2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

<Ant. 1>

802.11b				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	19.55	19.51	19.53	19.54

802.11g								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	21.83	21.60	21.66	21.68	21.62	21.61	21.53	21.45

2.4GHz 802.11n HT20								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	21.79	21.74	21.76	21.77	21.74	21.75	21.69	21.58

2.4GHz 802.11n HT40								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	21.60	21.56	21.54	21.57	21.59	21.58	21.44	21.35

<Ant. 2>

802.11b				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	17.37	17.30	17.36	17.36

802.11g								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	20.18	20.17	20.10	20.15	20.16	20.08	19.95	19.90

2.4GHz 802.11n HT20								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	20.04	20.00	20.03	20.02	19.98	20.02	19.98	19.85

2.4GHz 802.11n HT40								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	19.68	19.65	19.64	19.66	19.67	19.67	19.56	19.66

**MIMO <Ant. 1+2>**

2.4GHz 802.11n HT20								
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Peak Power (dBm)	23.57	23.55	23.55	23.56	23.53	23.56	23.16	22.97

**Note:** MIMO Ant 1+2 is a calculated result from sum of the power MIMO Ant 1 and MIMO Ant 2.


## 2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB and 99% BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	6.5 Mbps	1/11
		802.11n HT40	13.5 Mbps	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	6.5 Mbps	1/11
		802.11n HT40	13.5 Mbps	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
AC Conducted Emission	Mode 1 : WLAN Link + Bluetooth Link + Adapter			

## 2.4 Connection Diagram of Test System

### <WLAN Tx Mode>



### <AC Conducted Emission Mode>



## 2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Adapter	Aviv Energy	HK-IP15-A05	N/A	N/A	Unshielded, 1.8 m
6.	Fixture	N/A	WG7XXXT01	N/A	N/A	N/A

## 2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "Tools HDK2.0" installed in the notebook make the EUT provides functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.7 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


##### 3.1.4 Test Setup




**3.1.5 Test Result of 6dB and 99% Occupied Bandwidth**

<b>Test Band :</b>	2.4GHz	<b>Temperature :</b>	24~26°C
<b>Test Engineer :</b>	Book Lin	<b>Relative Humidity :</b>	45~49%

Mod.	Data Rate	N <sub>TX</sub>	Channel	Freq. (MHz)	99% Bandwidth (MHz)		6dB Bandwidth (MHz)		6dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant1	Ant2	Ant1	Ant2		
11b	1Mbps	1	1	2412	14.85	-	10.04	-	0.5	Pass
11b	1Mbps	1	6	2437	14.90	-	10.04	-	0.5	Pass
11b	1Mbps	1	11	2462	14.95	-	10.08	-	0.5	Pass
11g	6Mbps	1	1	2412	18.30	-	15.08	-	0.5	Pass
11g	6Mbps	1	6	2437	19.45	-	15.08	-	0.5	Pass
11g	6Mbps	1	11	2462	18.30	-	15.08	-	0.5	Pass
HT20	MCS0	1	1	2412	19.75	-	15.08	-	0.5	Pass
HT20	MCS0	1	6	2437	19.75	-	15.08	-	0.5	Pass
HT20	MCS0	1	11	2462	19.60	-	15.08	-	0.5	Pass
HT40	MCS0	1	3	2422	36.30	-	35.04	-	0.5	Pass
HT40	MCS0	1	6	2437	36.80	-	35.04	-	0.5	Pass
HT40	MCS0	1	9	2452	36.40	-	35.04	-	0.5	Pass
HT20	MCS0	2	1	2412	18.95	19.15	16.28	15.08	0.5	Pass
HT20	MCS0	2	6	2437	19.05	19.25	15.72	15.08	0.5	Pass
HT20	MCS0	2	11	2462	18.75	18.90	15.68	15.06	0.5	Pass







## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02.

### 3.2.4 Test Setup



**3.2.5 Test Result of Peak Output Power**

<b>Test Band :</b>	2.4GHz	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Book Lin	<b>Relative Humidity :</b>	45~49%

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Max. Limit (dBm)		DG (dBi)		Pass/Fail
					Ant. 1	Ant. 2	SUM	Ant. 1	Ant. 2	Ant. 1	Ant. 2	
11b	1Mbps	1	1	2412	19.18	17.37	-	30.00	30.00	1.22	-0.36	Pass
11b	1Mbps	1	6	2437	19.55	17.08		30.00	30.00	1.22	-0.36	Pass
11b	1Mbps	1	11	2462	19.44	16.54		30.00	30.00	1.22	-0.36	Pass
11g	6Mbps	1	1	2412	21.57	20.18		30.00	30.00	1.22	-0.36	Pass
11g	6Mbps	1	6	2437	21.83	19.98		30.00	30.00	1.22	-0.36	Pass
11g	6Mbps	1	11	2462	21.50	19.47		30.00	30.00	1.22	-0.36	Pass
HT20	MCS0	1	1	2412	21.64	20.04		30.00	30.00	1.22	-0.36	Pass
HT20	MCS0	1	6	2437	21.79	19.78		30.00	30.00	1.22	-0.36	Pass
HT20	MCS0	1	11	2462	21.62	19.36		30.00	30.00	1.22	-0.36	Pass
HT40	MCS0	1	3	2422	21.05	19.68		30.00	30.00	1.22	-0.36	Pass
HT40	MCS0	1	6	2437	21.60	19.45		30.00	30.00	1.22	-0.36	Pass
HT40	MCS0	1	9	2452	21.10	19.13		30.00	30.00	1.22	-0.36	Pass
HT20	MCS0	2	1	2412	21.36	19.56	23.56	30.00		0.50		Pass
HT20	MCS0	2	6	2437	21.45	19.45	23.57	30.00		0.50		Pass
HT20	MCS0	2	11	2462	21.23	18.78	23.19	30.00		0.50		Pass

**Note:** Measured power (dBm) has offset with cable loss.

**3.2.6 Test Result of Average output Power (Reporting Only)**

<b>Test Band :</b>	2.4GHz	<b>Temperature :</b>	24~26℃
<b>Test Engineer :</b>	Book Lin	<b>Relative Humidity :</b>	45~49%

Mod.	Data Rate	N <sub>TX</sub>	Channel	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant. 1	Ant. 2	Ant. 1	Ant. 2	Sum Power
11b	1Mbps	1	1	2412	0.10	0.10	17.17	15.36	-
11b	1Mbps	1	6	2437	0.10	0.10	17.57	15.11	
11b	1Mbps	1	11	2462	0.10	0.10	17.48	14.61	
11g	6Mbps	1	1	2412	0.57	0.59	15.65	15.43	
11g	6Mbps	1	6	2437	0.57	0.59	17.46	15.12	
11g	6Mbps	1	11	2462	0.57	0.59	15.35	14.64	
HT20	MCS0	1	1	2412	0.61	0.63	16.49	14.45	
HT20	MCS0	1	6	2437	0.61	0.63	16.73	14.29	
HT20	MCS0	1	11	2462	0.61	0.63	16.53	13.92	
HT40	MCS0	1	3	2422	1.21	1.22	13.03	13.20	
HT40	MCS0	1	6	2437	1.21	1.22	15.45	12.90	
HT40	MCS0	1	9	2452	1.21	1.22	13.61	12.67	
HT20	MCS0	2	1	2412	1.14	1.17	15.17	13.37	17.37
HT20	MCS0	2	6	2437	1.14	1.17	15.92	13.53	17.90
HT20	MCS0	2	11	2462	1.14	1.17	14.91	11.96	16.69

**Note:** Measured power (dBm) has offset with cable loss and duty factor.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02.


If measurements performed using method (2) plus 10 log (N) exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (2): Measure and add 10 log (N) dB, where N is the number of outputs. (N=2)

### 3.3.4 Test Setup




### 3.3.5 Test Result of Power Spectral Density

Test Band :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Book Lin	Relative Humidity :	45~49%

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak Power Density (dBm/3kHz)			Max. Limit (dBm/3kHz)		DG (dBi)		Pass/Fail
					Ant. 1	Ant. 2	Worst +10log(2)	Ant. 1	Ant. 2	Ant. 1	Ant. 2	
11b	1Mbps	1	1	2412	-5.67	-	-	8.00	8.00	1.22	-0.36	Pass
11b	1Mbps	1	6	2437	-5.71	-		8.00	8.00	1.22	-0.36	Pass
11b	1Mbps	1	11	2462	-5.25	-		8.00	8.00	1.22	-0.36	Pass
11g	6Mbps	1	1	2412	-8.99	-		8.00	8.00	1.22	-0.36	Pass
11g	6Mbps	1	6	2437	-7.16	-		8.00	8.00	1.22	-0.36	Pass
11g	6Mbps	1	11	2462	-8.35	-		8.00	8.00	1.22	-0.36	Pass
HT20	MCS0	1	1	2412	-8.49	-		8.00	8.00	1.22	-0.36	Pass
HT20	MCS0	1	6	2437	-7.05	-		8.00	8.00	1.22	-0.36	Pass
HT20	MCS0	1	11	2462	-8.32	-		8.00	8.00	1.22	-0.36	Pass
HT40	MCS0	1	3	2422	-14.04	-		8.00	8.00	1.22	-0.36	Pass
HT40	MCS0	1	6	2437	-11.95	-		8.00	8.00	1.22	-0.36	Pass
HT40	MCS0	1	9	2452	-14.35	-		8.00	8.00	1.22	-0.36	Pass
HT20	MCS0	2	1	2412	-10.10	-10.52	-7.09	8.00		3.51		Pass
HT20	MCS0	2	6	2437	-9.17	-10.52	-6.16	8.00		3.51		Pass
HT20	MCS0	2	11	2462	-9.85	-12.53	-6.84	8.00		3.51		Pass

**Note:** Measured power density (dBm) has offset with cable loss.



### 3.4 Conducted Band Edges and Spurious Emission Measurement

#### 3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Number of TX = 1, Ant 1 (Measured)

Number of TX	1	Ant :	1
Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~49%
Test Channel :	01	Test Engineer :	Book Lin


#### WLAN 802.11b Channel 01

##### 100kHz PSD reference Level




Date: 1.OCT.2013 14:11:15

##### Low Channel Plot




Date: 1.OCT.2013 14:11:32

##### Spurious Emission 30MHz~3GHz



Date: 1.OCT.2013 14:12:41


##### Spurious Emission 2GHz~25GHz




Date: 1.OCT.2013 14:13:00




Number of TX :	1	Ant :	1
Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~49%
Test Channel :	06	Test Engineer :	Book Lin

**WLAN 802.11b Channel 06****100kHz PSD reference Level**

Date: 1.OCT.2013 14:19:08

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 14:19:35

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 14:19:53




Number of TX :	1	Ant :	1
Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~49%
Test Channel :	11	Test Engineer :	Book Lin

**WLAN 802.11b Channel 11****100kHz PSD reference Level**


Date: 1.OCT.2013 14:22:52

**High Channel Plot**

Date: 1.OCT.2013 14:23:07

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 14:26:29

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 14:26:48




Number of TX :	1	Ant :	1
Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~49%
Test Channel :	01	Test Engineer :	Book Lin

**WLAN 802.11g Channel 01****100kHz PSD reference Level**


Date: 8.OCT.2013 14:45:21

**Low Channel Plot**

Date: 8.OCT.2013 14:45:36

**Spurious Emission 30MHz~3GHz**


Date: 8.OCT.2013 16:40:04

**Spurious Emission 2GHz~25GHz**


Date: 8.OCT.2013 16:40:23




Number of TX :	1	Ant :	1
Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~49%
Test Channel :	06	Test Engineer :	Book Lin

**WLAN 802.11g Channel 06****100kHz PSD reference Level**

Date: 1.OCT.2013 14:37:11

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 14:37:32

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 14:37:50




Number of TX :	1	Ant :	1
Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~49%
Test Channel :	11	Test Engineer :	Book Lin

**WLAN 802.11g Channel 11****100kHz PSD reference Level**


Date: 8.OCT.2013 14:50:38

**High Channel Plot**

Date: 8.OCT.2013 14:50:53

**Spurious Emission 30MHz~3GHz**


Date: 8.OCT.2013 16:41:19

**Spurious Emission 2GHz~25GHz**


Date: 8.OCT.2013 16:41:38




Number of TX :	1	Ant :	1
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~49%
Test Channel :	01	Test Engineer :	Book Lin

**WLAN 802.11n HT20 Channel 01****100kHz PSD reference Level**


Date: 1.OCT.2013 15:04:09

**Low Channel Plot**

Date: 1.OCT.2013 15:04:25

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 15:04:50

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 15:05:08




Number of TX :	1	Ant :	1
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~49%
Test Channel :	06	Test Engineer :	Book Lin

**WLAN 802.11n HT20 Channel 06****100kHz PSD reference Level**

Date: 1.OCT.2013 15:08:24

**Spurious Emission 30MHz~3GHz**

Date: 1.OCT.2013 15:08:48


**Spurious Emission 2GHz~25GHz**

Date: 1.OCT.2013 15:09:07







Number of TX :	1	Ant :	1
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~49%
Test Channel :	11	Test Engineer :	Book Lin

**WLAN 802.11n HT20 Channel 11****100kHz PSD reference Level**


Date: 1.OCT.2013 15:12:17

**High Channel Plot**

Date: 1.OCT.2013 15:12:48

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 15:13:13

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 15:13:31




Number of TX :	1	Ant :	1
Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~49%
Test Channel :	03	Test Engineer :	Book Lin

**WLAN 802.11n HT40 Channel 03****100kHz PSD reference Level**


Date: 8.OCT.2013 15:35:38

**Low Channel Plot**

Date: 8.OCT.2013 15:35:56

**Spurious Emission 30MHz~3GHz**


Date: 8.OCT.2013 16:44:27

**Spurious Emission 2GHz~25GHz**


Date: 8.OCT.2013 16:44:46




Number of TX :	1	Ant :	1
Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~49%
Test Channel :	06	Test Engineer :	Book Lin

**WLAN 802.11n HT40 Channel 06****100kHz PSD reference Level**

Date: 1.OCT.2013 14:53:04

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 14:53:27

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 14:53:46




Number of TX :	1	Ant :	1
Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~49%
Test Channel :	09	Test Engineer :	Book Lin

**WLAN 802.11n HT40 Channel 09****100kHz PSD reference Level**


Date: 8.OCT.2013 15:40:30

**High Channel Plot**

Date: 8.OCT.2013 15:40:47

**Spurious Emission 30MHz~3GHz**

Date: 8.OCT.2013 16:55:15

**Spurious Emission 2GHz~25GHz**

Date: 8.OCT.2013 16:55:33




Number of TX = 2, Ant 1 (Measured)

Number of TX :	2	Ant :	1
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~49%
Test Channel :	01	Test Engineer :	Book Lin


## WLAN 802.11n HT20 Channel 01

## 100kHz PSD reference Level




Date: 8.OCT.2013 15:11:53

## Low Channel Plot




Date: 8.OCT.2013 15:12:08

## Spurious Emission 30MHz~3GHz



Date: 8.OCT.2013 16:46:04


## Spurious Emission 2GHz~25GHz




Date: 8.OCT.2013 16:46:23




Number of TX :	2	Ant :	1
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~49%
Test Channel :	06	Test Engineer :	Book Lin

**WLAN 802.11n HT20 Channel 06****100kHz PSD reference Level**

Date: 1.OCT.2013 15:56:47

**Spurious Emission 30MHz~3GHz**


Date: 1.OCT.2013 15:57:09

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 15:57:28




Number of TX :	2	Ant :	1
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~49%
Test Channel :	11	Test Engineer :	Book Lin

**WLAN 802.11n HT20 Channel 11****100kHz PSD reference Level**


Date: 8.OCT.2013 14:57:00

**High Channel Plot**

Date: 8.OCT.2013 14:57:22

**Spurious Emission 30MHz~3GHz**

Date: 8.OCT.2013 16:49:20

**Spurious Emission 2GHz~25GHz**

Date: 8.OCT.2013 16:49:39




Number of TX = 2, Ant 2 (Measured)

Number of TX :	2	Ant :	2
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~49%
Test Channel :	01	Test Engineer :	Book Lin


## WLAN 802.11n HT20 Channel 01

## 100kHz PSD reference Level




Date: 8.OCT.2013 15:08:03

## Low Channel Plot




Date: 8.OCT.2013 15:08:28

## Spurious Emission 30MHz~3GHz



Date: 8.OCT.2013 16:47:05

## Spurious Emission 2GHz~25GHz




Date: 8.OCT.2013 16:47:23







Number of TX :	2	Ant :	2
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~49%
Test Channel :	06	Test Engineer :	Book Lin

**WLAN 802.11n HT20 Channel 06****100kHz PSD reference Level**

Date: 1.OCT.2013 15:51:31

**Spurious Emission 30MHz~3GHz**

Date: 1.OCT.2013 15:51:51

**Spurious Emission 2GHz~25GHz**


Date: 1.OCT.2013 15:52:10



Number of TX :	2	Ant :	2
Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~49%
Test Channel :	11	Test Engineer :	Book Lin


## WLAN 802.11n HT20 Channel 11

## 100kHz PSD reference Level




Date: 8.OCT.2013 15:02:33

## High Channel Plot




Date: 8.OCT.2013 15:02:59

## Spurious Emission 30MHz~3GHz



Date: 8.OCT.2013 16:48:28

## Spurious Emission 2GHz~25GHz



Date: 8.OCT.2013 16:48:46

### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.5.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - $VBW = 10$  Hz, when duty cycle is no less than 98 percent.
    - $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11b	97.72	16474.36	0.06	100Hz
2	802.11b	97.72	16474.36	0.06	100Hz
1	802.11g	87.69	2740.39	0.36	1kHz
2	802.11 g	87.24	2740.39	0.36	1kHz
1	2.4G 802.11n HT20	86.89	2548.08	0.39	1kHz
2	2.4G 802.11n HT20	86.41	2548.08	0.39	1kHz
1	2.4G 802.11n HT40	75.73	1250.00	0.80	1kHz
2	2.4G 802.11n HT40	75.49	1233.97	0.81	1kHz
1+2	2.4G 802.11n HT20 for Ant. 1	76.92	1300.00	0.77	1kHz
1+2	2.4G 802.11n HT20 for Ant. 2	76.42	1296.00	0.77	1kHz

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

**3.5.6 Test Result of Radiated Spurious at Band Edges**

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	Low	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	01	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2385.78	56.52	-17.48	74	51.58	32.3	6.91	34.27	168	132	Peak
2386.5	45.75	-8.25	54	40.81	32.3	6.91	34.27	168	132	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2387.13	56.43	-17.57	74	51.49	32.3	6.91	34.27	101	51	Peak
2386.86	45.21	-8.79	54	40.27	32.3	6.91	34.27	101	51	Average

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	High	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	11	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2486.71	57.85	-16.15	74	52.84	32.38	7.06	34.43	107	145	Peak
2487.28	45.97	-8.03	54	40.96	32.38	7.06	34.43	107	145	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2488.12	57.95	-16.05	74	52.92	32.4	7.06	34.43	100	50	Peak
2487.34	46.67	-7.33	54	41.66	32.38	7.06	34.43	100	50	Average



<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	Low	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	01	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.29	72.38	-1.62	74	67.44	32.3	6.91	34.27	169	134	Peak
2390	51.76	-2.24	54	46.85	32.3	6.91	34.3	169	134	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.65	71.67	-2.33	74	66.73	32.3	6.91	34.27	100	51	Peak
2390	50.68	-3.32	54	45.77	32.3	6.91	34.3	100	51	Average

<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	High	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	11	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.8	73.18	-0.82	74	68.17	32.38	7.06	34.43	106	148	Peak
2483.62	50.28	-3.72	54	45.27	32.38	7.06	34.43	106	148	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2484.1	71.57	-2.43	74	66.56	32.38	7.06	34.43	100	50	Peak
2483.5	50.83	-3.17	54	45.82	32.38	7.06	34.43	100	50	Average

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	Low	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	01	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.92	71.55	-2.45	74	66.64	32.3	6.91	34.3	107	151	Peak
2390	52.6	-1.4	54	47.69	32.3	6.91	34.3	107	151	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.56	69.66	-4.34	74	64.72	32.3	6.91	34.27	100	52	Peak
2390	51.08	-2.92	54	46.17	32.3	6.91	34.3	100	52	Average

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	High	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	11	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.59	72.38	-1.62	74	67.37	32.38	7.06	34.43	106	147	Peak
2483.65	51.53	-2.47	54	46.52	32.38	7.06	34.43	106	147	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.59	70.64	-3.36	74	65.63	32.38	7.06	34.43	100	64	Peak
2483.59	51	-3	54	45.99	32.38	7.06	34.43	100	64	Average



<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	Low	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	03	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2382.63	73.46	-0.54	74	68.54	32.28	6.91	34.27	110	149	Peak
2389.74	51.89	-2.11	54	46.95	32.3	6.91	34.27	110	149	Average
2489.23	56.27	-17.73	74	51.24	32.4	7.06	34.43	110	149	Peak
2487.49	43.4	-10.6	54	38.39	32.38	7.06	34.43	110	149	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.2	68.94	-5.06	74	64	32.3	6.91	34.27	100	50	Peak
2389.11	50.12	-3.88	54	45.18	32.3	6.91	34.27	100	50	Average
2486.53	57.89	-16.11	74	52.88	32.38	7.06	34.43	100	50	Peak
2498.56	43.46	-10.54	54	38.48	32.4	7.06	34.48	100	50	Average



<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Band :</b>	High	<b>Relative Humidity :</b>	51~53%
<b>Test Channel :</b>	09	<b>Test Engineer :</b>	Ken Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2377.5	56.37	-17.63	74	51.48	32.28	6.88	34.27	106	148	Peak
2336.1	43.82	-10.18	54	38.96	32.24	6.84	34.22	106	148	Average
2483.95	73.47	-0.53	74	68.46	32.38	7.06	34.43	106	148	Peak
2483.68	52.63	-1.37	54	47.62	32.38	7.06	34.43	106	148	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2388.84	60.82	-13.18	74	55.88	32.3	6.91	34.27	100	60	Peak
2388.57	43.96	-10.04	54	39.02	32.3	6.91	34.27	100	60	Average
2487.52	72.61	-1.39	74	67.58	32.4	7.06	34.43	100	60	Peak
2483.83	52.28	-1.72	54	47.27	32.38	7.06	34.43	100	60	Average

### 3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

**Note:** Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2414 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2414	98.24	-	-	93.28	32.31	6.95	34.3	168	132	Average
2414	102.92	-	-	97.96	32.31	6.95	34.3	168	132	Peak
4824	48.16	-25.84	74	64.35	33.97	8.77	58.93	100	0	Peak

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2414 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2414	97.36	-	-	92.4	32.31	6.95	34.3	101	51	Average
2414	102.11	-	-	97.15	32.31	6.95	34.3	101	51	Peak
4824	48.99	-5.01	54	65.18	33.97	8.77	58.93	100	66	Average
4824	51.03	-22.97	74	67.22	33.97	8.77	58.93	100	66	Peak

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	99.71	-	-	94.72	32.35	6.99	34.35	161	9	Average
2439	104.23	-	-	99.24	32.35	6.99	34.35	161	9	Peak
4875	50.04	-23.96	74	66.1	33.95	8.82	58.83	100	0	Peak
7311	46.92	-27.08	74	58.2	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	98.86	-	-	93.87	32.35	6.99	34.35	100	65	Average
2439	103.65	-	-	98.66	32.35	6.99	34.35	100	65	Peak
4875	53.16	-0.84	54	69.22	33.95	8.82	58.83	151	227	Average
4875	55.26	-18.74	74	71.32	33.95	8.82	58.83	151	227	Peak
7313	48.29	-25.71	74	59.57	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2462	99.26	-	-	94.26	32.37	7.02	34.39	107	145	Average
2462	104	-	-	99	32.37	7.02	34.39	107	145	Peak
4926	49.3	-4.7	54	65.2	33.93	8.9	58.73	106	157	Average
4926	51.13	-22.87	74	67.03	33.93	8.9	58.73	106	157	Peak
7388	45.44	-28.56	74	56.73	35.52	10.99	57.8	100	0	Peak

<b>Test Mode :</b>	802.11b for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2462	99.15	-	-	94.15	32.37	7.02	34.39	100	50	Average
2462	103.69	-	-	98.69	32.37	7.02	34.39	100	50	Peak
4926	53.25	-0.75	54	69.15	33.93	8.9	58.73	100	57	Average
4926	55.45	-18.55	74	71.35	33.93	8.9	58.73	100	57	Peak
7386	47.41	-26.59	74	58.7	35.52	10.99	57.8	100	0	Peak

<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2414 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2414	94.8	-	-	89.84	32.31	6.95	34.3	169	134	Average
2414	104.66	-	-	99.7	32.31	6.95	34.3	169	134	Peak
4826	43.95	-30.05	74	60.14	33.97	8.77	58.93	100	0	Peak

<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2414 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2414	94.01	-	-	89.05	32.31	6.95	34.3	100	51	Average
2414	103.8	-	-	98.84	32.31	6.95	34.3	100	51	Peak
4822	47.61	-26.39	74	63.8	33.97	8.77	58.93	100	0	Peak



<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	97.27	-	-	92.28	32.35	6.99	34.35	135	8	Average
2439	106.97	-	-	101.98	32.35	6.99	34.35	135	8	Peak
4876	46.21	-27.79	74	62.24	33.95	8.85	58.83	100	0	Peak
7309	46.04	-27.96	74	57.32	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	96.44	-	-	91.45	32.35	6.99	34.35	100	65	Average
2439	106.37	-	-	101.38	32.35	6.99	34.35	100	65	Peak
4876	49.51	-24.49	74	65.54	33.95	8.85	58.83	100	0	Peak
7313	49.32	-24.68	74	60.6	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2460 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2460	95.56	-	-	90.56	32.37	7.02	34.39	106	148	Average
2460	105.24	-	-	100.24	32.37	7.02	34.39	106	148	Peak
4926	47.06	-26.94	74	62.96	33.93	8.9	58.73	100	0	Peak
7386	43.07	-30.93	74	54.36	35.52	10.99	57.8	100	0	Peak

<b>Test Mode :</b>	802.11g for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2464 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2464	94.84	-	-	89.84	32.37	7.02	34.39	100	50	Average
2464	104.27	-	-	99.27	32.37	7.02	34.39	100	50	Peak
4926	50.3	-23.7	74	66.2	33.93	8.9	58.73	100	0	Peak
7386	46.76	-27.24	74	58.05	35.52	10.99	57.8	100	0	Peak

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2414 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2414	93.62	-	-	88.66	32.31	6.95	34.3	107	151	Average
2414	104.06	-	-	99.1	32.31	6.95	34.3	107	151	Peak
4826	49.83	-24.17	74	66.02	33.97	8.77	58.93	100	0	Peak

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2414 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2414	92.38	-	-	87.42	32.31	6.95	34.3	100	52	Average
2414	102.24	-	-	97.28	32.31	6.95	34.3	100	52	Peak
4824	50.64	-23.36	74	66.83	33.97	8.77	58.93	100	0	Peak

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2438 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2438	95.43	-	-	90.44	32.35	6.99	34.35	137	130	Average
2438	104.97	-	-	99.98	32.35	6.99	34.35	137	130	Peak
4872	48.67	-25.33	74	64.73	33.95	8.82	58.83	100	0	Peak
7309	45.84	-28.16	74	57.12	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	94.2	-	-	89.21	32.35	6.99	34.35	100	51	Average
2439	104.67	-	-	99.68	32.35	6.99	34.35	100	51	Peak
4875	50.18	-23.82	74	66.24	33.95	8.82	58.83	100	0	Peak
7309	49.32	-24.68	74	60.6	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2460 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2460	94.5	-	-	89.5	32.37	7.02	34.39	106	147	Average
2460	104.91	-	-	99.91	32.37	7.02	34.39	106	147	Peak
4923	47.21	-26.79	74	63.14	33.93	8.87	58.73	100	0	Peak
7386	42.61	-31.39	74	53.9	35.52	10.99	57.8	100	0	Peak

<b>Test Mode :</b>	802.11n HT20 for MIMO Ant. 1+2	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2464 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2464	93.19	-	-	88.19	32.37	7.02	34.39	100	64	Average
2464	103.33	-	-	98.33	32.37	7.02	34.39	100	64	Peak
4926	47.8	-26.2	74	63.7	33.93	8.9	58.73	100	0	Peak
7386	44.55	-29.45	74	55.84	35.52	10.99	57.8	100	0	Peak

<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	03	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2426 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2426	90.26	-	-	85.33	32.33	6.95	34.35	110	149	Average
2426	100.47	-	-	95.54	32.33	6.95	34.35	110	149	Peak
4845	39.79	-34.21	74	55.92	33.96	8.8	58.89	100	0	Peak
7266	42.58	-31.42	74	53.87	35.54	10.86	57.69	100	0	Peak

<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	03	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2424 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2424	89.33	-	-	84.4	32.33	6.95	34.35	100	50	Average
2424	98.38	-	-	93.45	32.33	6.95	34.35	100	50	Peak
4845	40.47	-33.53	74	56.6	33.96	8.8	58.89	100	0	Peak
7266	43.3	-30.7	74	54.59	35.54	10.86	57.69	100	0	Peak

<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	93.78	-	-	88.79	32.35	6.99	34.35	136	356	Average
2439	103.75	-	-	98.76	32.35	6.99	34.35	136	356	Peak
4876	43.33	-30.67	74	59.36	33.95	8.85	58.83	100	0	Peak
7311	42.76	-31.24	74	54.04	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2439 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2439	92.96	-	-	87.97	32.35	6.99	34.35	100	60	Average
2439	103.36	-	-	98.37	32.35	6.99	34.35	100	60	Peak
4876	44.54	-29.46	74	60.57	33.95	8.85	58.83	100	0	Peak
7309	45.33	-28.67	74	56.61	35.54	10.91	57.73	100	0	Peak

<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	09	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2460 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
50.25	31.4	-8.6	40	53.8	8.1	0.7	31.2	100	17	Peak
114.24	23.01	-20.49	43.5	41.93	11.16	1.07	31.15	-	-	Peak
209.82	30.74	-12.76	43.5	50.71	9.77	1.36	31.1	-	-	Peak
398.7	33.79	-12.21	46	46.59	15.97	2.14	30.91	-	-	Peak
666.8	33.18	-12.82	46	40.45	20.33	2.87	30.47	-	-	Peak
831.3	31.03	-14.97	46	35.76	22.41	3.22	30.36	-	-	Peak
2460	91.02	-	-	86.02	32.37	7.02	34.39	106	148	Average
2460	100.91	-	-	95.91	32.37	7.02	34.39	106	148	Peak
4905	40.02	-33.98	74	55.98	33.93	8.87	58.76	100	0	Peak
7356	43.32	-30.68	74	54.6	35.53	10.96	57.77	100	0	Peak



<b>Test Mode :</b>	802.11n HT40 for Ant. 1	<b>Temperature :</b>	21~24°C
<b>Test Channel :</b>	09	<b>Relative Humidity :</b>	51~53%
<b>Test Engineer :</b>	Ken Wu	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2460 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
102.36	26.57	-16.93	43.5	46.61	10.07	1.01	31.12	-	-	Peak
158.52	24.79	-18.71	43.5	44.12	10.64	1.22	31.19	-	-	Peak
211.71	25.93	-17.57	43.5	45.74	9.91	1.37	31.09	-	-	Peak
399.4	30.57	-15.43	46	43.33	16	2.14	30.9	-	-	Peak
664	35.25	-10.75	46	42.54	20.31	2.87	30.47	100	185	Peak
887.3	28.53	-17.47	46	32.57	22.97	3.32	30.33	-	-	Peak
2460	90.1	-	-	85.11	32.35	6.99	34.35	100	60	Average
2460	100.64	-	-	95.65	32.35	6.99	34.35	100	60	Peak
4905	39.24	-34.76	74	55.2	33.93	8.87	58.76	100	0	Peak
7356	40.75	-33.25	74	52.03	35.53	10.96	57.77	100	0	Peak

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	20~22℃
<b>Test Engineer :</b>	Slash Huang	<b>Relative Humidity :</b>	45~47%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	WLAN Link + Bluetooth Link + Adapter		




#### Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	51.2	Off	L1	19.4	14.8	66.0
0.198000	44.1	Off	L1	19.3	19.6	63.7
0.350000	43.5	Off	L1	19.4	15.5	59.0
0.550000	38.1	Off	L1	19.4	17.9	56.0
0.998000	37.5	Off	L1	19.4	18.5	56.0
2.558000	37.9	Off	L1	19.6	18.1	56.0

#### Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	40.5	Off	L1	19.4	15.5	56.0
0.198000	34.1	Off	L1	19.3	19.6	53.7
0.350000	40.2	Off	L1	19.4	8.8	49.0
0.550000	33.8	Off	L1	19.4	12.2	46.0
0.998000	29.9	Off	L1	19.4	16.1	46.0
2.558000	32.0	Off	L1	19.6	14.0	46.0

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	20~22°C
<b>Test Engineer :</b>	Slash Huang	<b>Relative Humidity :</b>	45~47%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	WLAN Link + Bluetooth Link + Adapter		


**Final Result : Quasi-Peak**

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	51.2	Off	N	19.4	14.8	66.0
0.190000	42.8	Off	N	19.4	21.2	64.0
0.294000	43.7	Off	N	19.4	16.7	60.4
0.342000	42.7	Off	N	19.4	16.5	59.2
0.550000	39.2	Off	N	19.4	16.8	56.0
0.982000	37.5	Off	N	19.5	18.5	56.0
2.534000	38.4	Off	N	19.6	17.6	56.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	37.0	Off	N	19.4	19.0	56.0
0.190000	28.7	Off	N	19.4	25.3	54.0
0.294000	40.4	Off	N	19.4	10.0	50.4
0.342000	38.3	Off	N	19.4	10.9	49.2
0.550000	31.6	Off	N	19.4	14.4	46.0
0.982000	30.1	Off	N	19.5	15.9	46.0
2.534000	32.3	Off	N	19.6	13.7	46.0

### 3.7 Antenna Requirements

#### 3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### 3.7.2 Antenna Anti-Replacement Construction

Non-standard antenna connector is used.

#### 3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02

For CDD transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log \left[ \frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

$N_{SS}$  = the number of independent spatial streams of data;

$N_{ANT}$  = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$  if the  $k$ th antenna is being fed by spatial stream  $j$ , or zero if it is not;

$G_k$  is the gain in dBi of the  $k$ th antenna.

The EUT supports CDD mode.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	1.22	-0.36	0.50	3.51	0.00	0.00

$$\text{Power Limit Reduction} = \text{DG(Power)} - 6\text{dBi}, (\text{min} = 0)$$

$$\text{PSD Limit Reduction} = \text{DG(PSD)} - 6\text{dBi}, (\text{min} = 0)$$

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Sep. 18, 2013 ~ Oct. 08, 2013	Jun. 06, 2014	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 17, 2013	Sep. 18, 2013 ~ Oct. 08, 2013	Aug. 16, 2014	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 17, 2013	Sep. 18, 2013 ~ Oct. 08, 2013	Aug. 16, 2014	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 13, 2012	Oct. 07, 2013	Nov. 12, 2013	Conduction (CO05-HY)
Two-LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2012	Oct. 07, 2013	Dec. 11, 2013	Conduction (CO05-HY)
Two-LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 06, 2012	Oct. 07, 2013	Dec. 05, 2013	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	Oct. 07, 2013	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 06, 2013	Oct. 10, 2013	Sep. 05, 2014	Radiation (03CH07-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz~30GHz	Nov. 30, 2012	Oct. 05, 2013 ~ Oct. 10, 2013	Nov. 29, 2013	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	860004/0001	9kHz~30MHz	Jul. 03, 2012	Oct. 05, 2013 ~ Oct. 10, 2013	Jul. 03, 2014	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 10, 2013	Oct. 10, 2013	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 22, 2013	Oct. 05, 2013 ~ Oct. 10, 2013	Aug. 21, 2014	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 03, 2013	Oct. 05, 2013 ~ Oct. 10, 2013	Oct. 02, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	30MHz~1GHz	Feb. 26, 2013	Oct. 10, 2013	Feb. 25, 2014	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~26.5GHz	Dec. 01, 2012	Oct. 05, 2013 ~ Oct. 10, 2013	Nov. 30, 2013	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	159088	DC~18G High Gain	Feb. 27, 2013	Oct. 05, 2013 ~ Oct. 10, 2013	Feb. 26, 2014	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Oct. 05, 2013 ~ Oct. 10, 2013	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	Oct. 05, 2013 ~ Oct. 10, 2013	N/A	Radiation (03CH07-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.54
---	------

### Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.72
---	------

