



RF Exposure Evaluation Report

Equipment : cnPilot E410 Indoor
Brand Name : Cambium Networks
Model No. : cnPilot E410 Indoor
FCC ID : Z8H89FT0035
Standard : 47 CFR Part 2.1091
Applicant : Cambium Networks Inc.
3800 Golf Road, Suite 360 Rolling Meadows, IL
60008, USA
Manufacturer : Cambium Networks Inc.
3800 Golf Road, Suite 360 Rolling Meadows, IL
60008, USA

The product sample received on Apr. 06, 2017 and completely tested on May 09, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Cliff Chang
SPORTON INTERNATIONAL INC.





TABLE OF CONTENTS

| | | |
|-------------------------------|---|----------|
| 1 | GENERAL DESCRIPTION | 4 |
| 1.1 | EUT General Information | 4 |
| 1.2 | Testing Location | 4 |
| 2 | MAXIMUM PERMISSIBLE EXPOSURE | 5 |
| 2.1 | Limit of Maximum Permissible Exposure | 5 |
| 2.2 | MPE Calculation Method | 5 |
| 2.3 | Calculated Result and Limit | 6 |
| PHOTOGRAPHS OF EUT V01 | | |

REVISION HISTORY

[illegible]

1 General Description

1.1 EUT General Information

| RF General Information | | | |
|------------------------|------------------------|---------------------------|---|
| Evaluation Mode | Frequency Range (MHz) | Operating Frequency (MHz) | Modulation Type |
| 2.4GHz WLAN | 2400-2483.5 | 2412-2462 | 802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) |
| 5GHz WLAN | 5150-5250 5725-5850 | 5180-5240 5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |

1.2 Testing Location

| Testing Location | | |
|-------------------------------------|--------|---|
| <input type="checkbox"/> | HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973 |
| <input checked="" type="checkbox"/> | JHUBEI | ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085 |

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | EIRP (W) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) | Ratio (S/Limit) |
|----------|-------------|----------------|---------------|-------------|------------------|----------------------------|----------------------------------|--------------------|
| 2.4G;G1D | 5.24 | 25.14 | 30.38 | 1.09144 | 20 | 0.21714 | 1.00000 | 0.21714 |
| 5.8G;D1D | 5.47 | 28.34 | 33.81 | 2.40436 | 20 | 0.47833 | 1.00000 | 0.47833 |
| | | | | | | | Sum Ratio | 0.69547 |
| | | | | | | | Ratio Limit | 1 |