

# Compliance with safety standards

---

This section lists the safety specifications against which the PMP 450 has been tested and certified. It also describes how to keep RF exposure within safe limits.

## Electrical safety compliance

The PMP 450 hardware has been tested for compliance to the electrical safety specifications listed in [Table 1](#).

**Table 1** PMP 450 safety compliance specifications

Region	Specification
USA	UL 60950
Canada	CSA C22.2 No.60950
International	CB certified & certificate to IEC 60950

## Electromagnetic compatibility (EMC) compliance

[Table 2](#) lists the EMC specification type approvals that have been granted for PMP 450.

**Table 2** EMC emissions compliance

Variant	Region	Specification (Type Approvals)
PMP 450	USA	FCC Part 15 Class B
	Canada	RSS Gen and RSS 210
	International	EN 301 489-1 V1.9.2 EN 301 489-17 V2.1.1

# Human exposure to radio frequency energy

## Standards

Relevant standards (USA and EC) applicable when working with RF equipment are:

- ANSI IEEE C95.1-1991, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
- Council recommendation of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) (1999/519/EC) and respective national regulations.
- Directive 2004/40/EC of the European Parliament and of the Council of 29 April 2004 on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (electromagnetic fields) (18th individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC).
- US FCC limits for the general population. See the FCC web site at <http://www.fcc.gov>, and the policies, guidelines, and requirements in Part 1 of Title 47 of the Code of Federal Regulations, as well as the guidelines and suggestions for evaluating compliance in FCC OET Bulletin 65.
- Health Canada limits for the general population. See the Health Canada web site at [http://www.hc-sc.gc.ca/ewh-semt/pubs/radiation/99ehd-dhm237/limits-limitations\\_e.html](http://www.hc-sc.gc.ca/ewh-semt/pubs/radiation/99ehd-dhm237/limits-limitations_e.html) and Safety Code 6.
- EN 50383:2002 Basic standard for the calculation and measurement of electromagnetic field strength and SAR related to human exposure from radio base stations and fixed terminal stations for wireless telecommunication systems (110 MHz - 40 GHz).
- BS EN 50385:2002 Product standard to demonstrate the compliances of radio base stations and fixed terminal stations for wireless telecommunication systems with the basic restrictions or the reference levels related to human exposure to radio frequency electromagnetic fields (110 MHz – 40 GHz) – general public.
- ICNIRP (International Commission on Non-Ionizing Radiation Protection) guidelines for the general public. See the ICNIRP web site at <http://www.icnirp.de/> and Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields.

## Power density exposure limit

Install the radios for the PMP 450 family of PMP wireless solutions so as to provide and maintain the minimum separation distances from all persons.

The applicable power density exposure limit from the standards (see [Human exposure to radio frequency energy](#) on page 2) is:

- **10 W/m<sup>2</sup>** for RF energy in the 2.4, 3.5GHz, 3.6 GHz, 5.4-GHz and 5.8-GHz frequency bands.

## Calculation of power density



The following calculation is based on the ANSI IEEE C95.1-1991 method, as that provides a worst case analysis. Details of the assessment to EN50383:2002 can be provided, if required.

Peak power density in the far field of a radio frequency point source is calculated as follows:

$$S = \frac{P \cdot G}{4\pi d^2}$$

**Where:**

**Is:**

S	power density in W/m <sup>2</sup>
P	maximum average transmit power capability of the radio, in W
G	total Tx gain as a factor, converted from dB
d	distance from point source, in m

Rearranging terms to solve for distance yields:

$$d = \sqrt{\frac{P \cdot G}{4\pi \cdot S}}$$

## Calculated distances and power compliance margins

[Table 3](#) shows calculated minimum separation distances, recommended distances and resulting margins for each frequency band and antenna combination. These are conservative distances that include compliance margins. At these and greater separation distances, the power density from the RF field is below generally accepted limits for the general population.

PMP 450 equipment adheres to all applicable EIRP limits for transmit power when operating in MIMO mode. Separation distances and compliance margins include compensation for both transmitters.

Explanation of terms used in [Table 3](#):

- Tx burst – maximum average transmit power in burst (Watt)
- P – maximum average transmit power capability of the radio (Watt) (combined transmitters)
- G – total transmit gain as a factor, converted from dB
- S – power density (W/m<sup>2</sup>)
- d – minimum distance from point source (meters)
- R – recommended distances (meters)
- C – compliance factor

**Table 3** Power Compliance Margins

Frequency Band	Antenna	Variable			<i>d</i>	Recommended Separation Distance	Power Compliance Margin
		P	G	S			
5 GHz OFDM	Integrated SM, 9 dBi patch	0.158 W (22 dBm)	7.9 (9 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	10 cm	20 cm (8 in)	40.27
	Integrated SM, 9 dBi patch with 8 dBi CLIP	0.158 W (22 dBm)	50 (17 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	25 cm	50 cm (20 in)	39.7
	Integrated SM, 9 dBi patch with 5.5 dBi LENS	0.158 W (22 dBm)	28 (14.5 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	18.7 cm	50 cm (20 in)	71.01
	Integrated SM, 9 dBi patch with 14 dBi Reflector Dish	0.158 W (22 dBm)	199 (23 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	50 cm	100 cm (40 in)	40
2.4 GHz OFDM	Integrated SM, 8 dBi patch	0.158 W (22 dBm)	6.3 (8 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	8.9 cm	20 cm (8 in)	50.5
	Integrated SM, 8 dBi patch with 12 dBi Reflector Dish	0.158 W (22 dBm)	100 (20 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	35 cm	100 cm (40 in)	79.5
3.5, 3.6 GHz OFDM	Integrated SM, 8 dBi patch	0.316 W (25 dBm)	6.3 (8 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	12.5 cm	50 cm (8 in)	160
	Integrated SM, 8 dBi patch with 11 dBi Reflector Dish	0.316 W (25 dBm)	79.4 (19 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	44.6 cm	100 cm (40 in)	50.2
2.4, 5 GHz OFDM	Connectorized AP, with 17 dBi Sector Antenna	0.158 W (22 dBm)	50 (17 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	25.1 cm	50 cm (20 in)	39.8
3.5, 3.6 GHz OFDM	Connectorized AP, with 17 dBi Sector Antenna	0.316 W (25 dBm)	50 (17 dB)	10 W/m <sup>2</sup> or 1 mW/cm <sup>2</sup>	35.4 cm	100 cm (40 in)	79.7

**NOTE**

Gain of antenna in dBi =  $10 \cdot \log(G)$ . The regulations require that the power used for the calculations is the maximum power in the transmit burst subject to allowance for source-based time-averaging. If there are no EIRP limits in the country of deployment, use the distance calculations for FCC 5.8 GHz for all frequency bands.