



# FCC RADIO TEST REPORT

**FCC ID** : Z8H89FT0051  
**Equipment** : cnPilot e510 Outdoor  
**Brand Name** : Cambium Networks  
**Model Name** : REG-PL-E510  
**Applicant** : Cambium Networks Inc.  
3800 Golf Road, Suite 360 Rolling Meadows, IL  
60008, USA  
**Manufacturer** : Cambium Networks, Ltd.  
Ashburton, TQ13 7UP, UK  
**Standard** : 47 CFR FCC Part 15.407

The product was received on Nov. 01, 2018, and testing was started from Nov. 01, 2018 and completed on Feb. 14, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

  
Approved by: Cliff Chang

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description .....</b>	<b>5</b>
1.1 Information.....	5
1.2 Testing Applied Standards .....	7
1.3 Testing Location Information .....	7
1.4 Measurement Uncertainty .....	7
<b>2 Test Configuration of EUT .....</b>	<b>8</b>
2.1 Test Channel Mode .....	8
2.2 The Worst Case Measurement Configuration.....	9
2.3 EUT Operation during Test .....	10
2.4 Accessories .....	10
2.5 Support Equipment.....	10
2.6 Test Setup Diagram .....	11
<b>3 Transmitter Test Result .....</b>	<b>14</b>
3.1 AC Power-line Conducted Emissions .....	14
3.2 Emission Bandwidth .....	16
3.3 Maximum Conducted Output Power .....	17
3.4 Peak Power Spectral Density.....	19
3.5 Unwanted Emissions.....	22
<b>4 Test Equipment and Calibration Data .....</b>	<b>27</b>
<b>Appendix A. Test Results of AC Power-line Conducted Emissions</b>	
<b>Appendix B. Test Results of Emission Bandwidth</b>	
<b>Appendix C. Test Results of Maximum Conducted Output Power</b>	
<b>Appendix D. Test Results of Peak Power Spectral Density</b>	
<b>Appendix E. Test Results of Unwanted Emissions</b>	
<b>Appendix F. Test Photos</b>	
<b>Photographs of EUT v02</b>	





## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.407(a)	Emission Bandwidth	PASS	-
3.3	15.407(a)	Maximum Conducted Output Power	PASS	-
3.4	15.407(a)	Peak Power Spectral Density	PASS	-
3.5	15.407(b)	Unwanted Emissions	PASS	-

**Declaration of Conformity:**

The judgment of conformity in the report is based on the measurement results excluding the measurement uncertainty.

**Comments and Explanations:**

1. The test configuration, test mode and test software were written in this test report are declared by the manufacturer.
2. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Sam Chen**

**Report Producer: Wendy Pan**

# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
5150-5250	a, n (HT20), ac (VHT20)	5180-5240	36-48 [4]
5725-5850		5745-5825	149-165 [5]
5150-5250	n (HT40), ac (VHT40)	5190-5230	38-46 [2]
5725-5850		5755-5795	151-159 [2]
5150-5250	ac (VHT80)	5210	42 [1]
5725-5850		5775	155 [1]

Band	Mode	BWch (MHz)	Nant
5.15-5.25GHz	802.11a	20	2TX
5.15-5.25GHz	802.11n HT20	20	2TX
5.15-5.25GHz	802.11ac VHT20	20	2TX
5.15-5.25GHz	802.11n HT40	40	2TX
5.15-5.25GHz	802.11ac VHT40	40	2TX
5.15-5.25GHz	802.11ac VHT80	80	2TX
5.725-5.85GHz	802.11a	20	2TX
5.725-5.85GHz	802.11n HT20	20	2TX
5.725-5.85GHz	802.11ac VHT20	20	2TX
5.725-5.85GHz	802.11n HT40	40	2TX
5.725-5.85GHz	802.11ac VHT40	40	2TX
5.725-5.85GHz	802.11ac VHT80	80	2TX

**Note:**

- ♦ 11a, HT20 and HT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- ♦ VHT20, VHT40 and VHT80 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM modulation.
- ♦ BWch is the nominal channel bandwidth.
- ♦ Nss-Min is the minimum number of spatial streams.
- ♦ Nant is the number of outputs. e.g., 2(2,3) means have 2 outputs for port 2 and port 3. 2 means have 2 outputs for port 1 and port 2.

**1.1.2 Antenna Information**

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	1	Accton	120G00000194A	PCB Antenna	I-PEX	8.4
2	2	Accton	120G00000195A	PCB Antenna	I-PEX	8.4
3	3	Accton	120G00000196A	PCB Antenna	I-PEX	8.9
4	4	Accton	120G00000197A	PCB Antenna	I-PEX	8.9

Note: The EUT has four antennas.

**For 2.4GHz function:**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

**For 5GHz function:**

Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 3 and Port 4 could transmit/receive simultaneously.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
802.11a	0.963	0.164	2.066m	1k
802.11ac VHT20	0.983	0.074	n/a (DC>=0.98)	n/a (DC>=0.98)
802.11ac VHT40	0.96	0.177	2.43m	1k
802.11ac VHT80	0.916	0.381	1.142m	1k

**1.1.4 EUT Operational Condition**

<b>EUT Power Type</b>	From PoE			
<b>Beamforming Function</b>	<input type="checkbox"/>	With beamforming	<input checked="" type="checkbox"/>	Without beamforming
<b>Function</b>	<input checked="" type="checkbox"/>	Outdoor P2M	<input type="checkbox"/>	Indoor P2M
	<input type="checkbox"/>	Fixed P2P	<input type="checkbox"/>	Client
<b>Test Software Version</b>	QRCT: 3.0.187.0			



## 1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 789033 D02 v02r01
- ♦ FCC KDB 662911 D01 v02r01
- ♦ FCC KDB 412172 D01 v01r01

## 1.3 Testing Location Information

Testing Location				
<input type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	TEL : 886-3-327-3456	FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.	TEL : 886-3-656-9065	FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-CB	Serway Li	25°C / 60%	Nov. 02, 2018 ~ Feb. 14, 2019
Radiated Above 1GHz For Cabinet test	03CH01-CB	Eason Chen	25°C / 60%	Nov. 12, 2018
Radiated Above 1GHz For Others test	03CH01-CB	Eason Chen	25 ~ 26°C / 60~62%	Feb. 14, 2019
Radiated Below 1GHz	03CH01-CB	Jay Luo	25°C / 60%	Nov. 01, 2018
AC Conduction	CO01-CB	Howard Liu	22°C / 55%	Nov. 08, 2018

Test site Designation No. TW0006 with FCC

Test site registered number IC 4086B with Industry Canada.

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%
Output Power Measurement	1.33 dB	Confidence levels of 95%
Power Density Measurement	1.27 dB	Confidence levels of 95%
Bandwidth Measurement	9.74 x10 <sup>-8</sup>	Confidence levels of 95%



## 2 Test Configuration of EUT

### 2.1 Test Channel Mode

Based on conducted spurious emission test:

Mode	Power Setting
802.11a_Nss1,(6Mbps)_2TX	-
5180MHz	14.5
5200MHz	14.5
5240MHz	14.5
5745MHz	23.5
5785MHz	24
5825MHz	24
802.11ac VHT20_Nss1,(MCS0)_2TX	-
5180MHz	14.5
5200MHz	14.5
5240MHz	14.5
5745MHz	23.5
5785MHz	24
5825MHz	24
802.11ac VHT40_Nss1,(MCS0)_2TX	-
5190MHz	13.5
5230MHz	14
5755MHz	23.5
5795MHz	23.5
802.11ac VHT80_Nss1,(MCS0)_2TX	-
5210MHz	13
5775MHz	20

Based For radiated spurious emission:

Mode	PowerSetting
802.11ac VHT20_Nss1,(MCS0)_2TX	-
5180MHz	18.5
802.11ac VHT80_Nss1,(MCS0)_2TX	-
5775MHz	21

Note: 1. VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.

2. For the test result is for manufacturer's reference only and is not applicable to certificated.



## 2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral
<b>Operating Mode</b>	Normal Link
1	EUT with PoE

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Emission Bandwidth Maximum Conducted Output Power Peak Power Spectral Density Unwanted Emissions (Above 1GHz)
<b>Test Condition</b>	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Unwanted Emissions
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
<b>Operating Mode &lt; 1GHz</b>	Normal Link
1	EUT with PoE
<b>Operating Mode &gt; 1GHz</b>	CTX

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
<b>Operating Mode</b>	
1	WLAN 2.4GHz + WLAN 5GHz
Refer to Sporton Test Report No.: FA870416-03 for Co-location RF Exposure Evaluation.	

Note 1: The EUT can only be used in Y axis positon.

Note 2: PoE information as below:

The EUT was powered by PoE, and the PoE was for measurement only, would not be marked.

Support Unit	Brand Name	Model Name
PoE	Cambium Networks	NET-P15-56IN



## 2.3 EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.

For Normal Link:

During the test, the EUT operation to normal function.

## 2.4 Accessories

N/A

## 2.5 Support Equipment

For Test Site No: CO01-CB

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	LAN NB	DELL	E6430	N/A
B	PoE	Cambium Networks	NET-P15-56IN	N/A
C	2.4G NB	DELL	E6430	N/A
D	5G NB	DELL	E6430	N/A

For Test Site No: 03CH01-CB (below 1GHz)

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	2.4G NB	DELL	E4300	N/A
B	5G NB	DELL	E4300	N/A
C	LAN NB	DELL	E4300	N/A
D	PoE	Cambium Networks	NET-P15-56IN	N/A


For Test Site No: 03CH01-CB (above 1GHz)


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A
B	PoE	Cambium Networks	NET-P15-56IN	N/A

For Test Site No: TH01-CB


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A
B	PoE	Cambium Networks	NET-P15-56IN	N/A

## 2.6 Test Setup Diagram



**Test Setup Diagram - Radiated Test < 1GHz**


Item	Connection	Shielded	Length
1	Power cable	No	0.9m
2	RJ-45 cable	No	1.5m
3	RJ-45 cable	No	10m

**Test Setup Diagram - Radiated Test > 1GHz**


Item	Connection	Shielded	Length
1	Power cable	No	0.9m
2	RJ-45 cable	No	1.5m
3	RJ-45 cable	No	10m



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

### 3.1.4 Test Setup



### 3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

## 3.2 Emission Bandwidth

### 3.2.1 Emission Bandwidth Limit

Emission Bandwidth Limit	
<b>UNII Devices</b>	
<input checked="" type="checkbox"/>	For the 5.15-5.25 GHz band, N/A
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.
<input type="checkbox"/>	For the 5.47-5.725 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.
<input checked="" type="checkbox"/>	For the 5.725-5.85 GHz band, 6 dB emission bandwidth $\geq$ 500kHz.
<b>LE-LAN Devices</b>	
<input type="checkbox"/>	For the band 5.15-5.25 GHz, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz
<input type="checkbox"/>	For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz
<input type="checkbox"/>	For the 5.725-5.85 GHz band, 6 dB emission bandwidth $\geq$ 500kHz.


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> <li>For the emission bandwidth shall be measured using one of the options below:</li> </ul>	
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause C for EBW and clause D for OBW measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input type="checkbox"/>	Refer as IC RSS-Gen, clause 4.6 for bandwidth testing.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B





### 3.3 Maximum Conducted Output Power

#### 3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
<b>UNII Devices</b>	
<input checked="" type="checkbox"/> For the 5.15-5.25 GHz band:	
<input type="checkbox"/>	<ul style="list-style-type: none"><li>Outdoor AP: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math>. e.i.r.p. at any elevation angle above 30 degrees <math>\leq 125</math>mW [21dBm]</li><li>Indoor AP: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math></li><li>Point-to-point AP: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 23</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 23)</math>.</li><li>Mobile or Portable Client: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 250 mW. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 24 - (G_{TX} - 6)</math>.</li></ul>
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum conducted output power ( $P_{Out}$ ) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$ .
<input type="checkbox"/>	For the 5.47-5.725 GHz band, the maximum conducted output power ( $P_{Out}$ ) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$ .
<input checked="" type="checkbox"/> For the 5.725-5.85 GHz band:	
<input type="checkbox"/>	<ul style="list-style-type: none"><li>Point-to-multipoint systems (P2M): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math>.</li><li>Point-to-point systems (P2P): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W.</li></ul>
<b>LE-LAN Devices</b>	
<input type="checkbox"/>	For the 5.15-5.25 GHz band, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz
<input type="checkbox"/>	For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz
<input type="checkbox"/> For the 5.725-5.85 GHz band:	
<input type="checkbox"/>	<ul style="list-style-type: none"><li>Point-to-multipoint systems (P2M): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math>.</li><li>Point-to-point systems (P2P): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W.</li></ul>
$P_{Out}$ = maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi.	


### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> <li>Maximum Conducted Output Power</li> </ul>	
	Average over on/off periods with duty factor
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
	Wideband RF power meter and average over on/off periods with duty factor
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause E Method PM-G (using an RF average power meter).
<ul style="list-style-type: none"> <li>For conducted measurement.</li> </ul>	
	<ul style="list-style-type: none"> <li>If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.</li> </ul>
	<ul style="list-style-type: none"> <li>If multiple transmit chains, EIRP calculation could be following as methods:  <math display="block">P_{total} = P_1 + P_2 + \dots + P_n</math> (calculated in linear unit [mW] and transfer to log unit [dBm])  <math display="block">EIRP_{total} = P_{total} + DG</math> </li> </ul>

### 3.3.4 Test Setup



### 3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



### 3.4 Peak Power Spectral Density

#### 3.4.1 Peak Power Spectral Density Limit

Peak Power Spectral Density Limit	
<b>UNII Devices</b>	
<input checked="" type="checkbox"/> For the 5.15-5.25 GHz band:	
<input type="checkbox"/>	<ul style="list-style-type: none"> <li>Outdoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 17 - (G_{TX} - 6)</math>.</li> <li>Indoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 17 - (G_{TX} - 6)</math>.</li> <li>Point-to-point AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If <math>G_{TX} &gt; 23</math> dBi, then <math>P_{Out} = 17 - (G_{TX} - 23)</math>.</li> <li>Mobile or Portable Client: the peak power spectral density (PPSD) <math>\leq 11</math> dBm/MHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>PPSD = 11 - (G_{TX} - 6)</math>.</li> </ul>
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$ .
<input type="checkbox"/>	For the 5.47-5.725 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$ .
<input checked="" type="checkbox"/> For the 5.725-5.85 GHz band:	
<input type="checkbox"/>	<ul style="list-style-type: none"> <li>Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>PPSD = 30 - (G_{TX} - 6)</math>.</li> <li>Point-to-point systems (P2P): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz.</li> </ul>
<b>LE-LAN Devices</b>	
<input type="checkbox"/>	For the 5.15-5.25 GHz band, the e.i.r.p. peak power spectral density (PPSD) $\leq 10$ dBm/MHz.
<input type="checkbox"/>	For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz.
<input type="checkbox"/>	<ul style="list-style-type: none"> <li>e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where <math>\theta</math> is the angle above the local horizontal plane (of the Earth) as shown below:            -13 dBW/MHz for <math>0^\circ \leq \theta &lt; 8^\circ</math> ; -13 - 0.716 (<math>\theta</math>-8) dBW/MHz for <math>8^\circ \leq \theta &lt; 40^\circ</math>            -35.9 - 1.22 (<math>\theta</math>-40) dBW/MHz for <math>40^\circ \leq \theta \leq 45^\circ</math> ; -42 dBW/MHz for <math>\theta &gt; 45^\circ</math></li> </ul>
<input type="checkbox"/>	For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz.
<input type="checkbox"/> For the 5.725-5.85 GHz band:	
<input type="checkbox"/>	<ul style="list-style-type: none"> <li>Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>PPSD = 30 - (G_{TX} - 6)</math>.</li> <li>Point-to-point systems (P2P): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz.</li> </ul>
<p><b>PPSD</b> = peak power spectral density that he same method as used to determine the conducted output power shall be used to determine the power spectral density. And power spectral density in dBm/MHz</p> <p><b>G<sub>TX</sub></b> = the maximum transmitting antenna directional gain in dBi.</p>	

#### 3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



### 3.4.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> <li>Peak power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the peak power spectral density and use the peak search function on the spectrum analyzer to find the peak of the spectrum. For the peak power spectral density shall be measured using below options:</li> </ul>	
<input type="checkbox"/>	Refer as FCC KDB 789033, F)5) power spectral density can be measured using resolution bandwidths < 1 MHz provided that the results are integrated over 1 MHz bandwidth
[duty cycle ≥ 98% or external video / power trigger]	
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)
duty cycle < 98% and average over on/off periods with duty factor	
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
<ul style="list-style-type: none"> <li>For conducted measurement.</li> </ul>	
<ul style="list-style-type: none"> <li>If the EUT supports multiple transmit chains using options given below:</li> </ul>	
<input checked="" type="checkbox"/>	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/>	Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,
<input type="checkbox"/>	Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.
<ul style="list-style-type: none"> <li>If multiple transmit chains, EIRP PPSD calculation could be following as methods:  <math>PPSD_{total} = PPSD_1 + PPSD_2 + \dots + PPSD_n</math>                      (calculated in linear unit [mW] and transfer to log unit [dBm])  <math>EIRP_{total} = PPSD_{total} + DG</math> </li> </ul>	

### 3.4.4 Test Setup



### 3.4.5 Test Result of Peak Power Spectral Density

Refer as Appendix D



### 3.5 Unwanted Emissions

#### 3.5.1 Transmitter Radiated Unwanted Emissions Limit

Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.



Un-restricted band emissions above 1GHz Limit	
Operating Band	Limit
<input checked="" type="checkbox"/> 5.15 - 5.25 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
<input type="checkbox"/> 5.25 - 5.35 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
<input type="checkbox"/> 5.47 - 5.725 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
<input checked="" type="checkbox"/> 5.725 - 5.85 GHz	all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).	

### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.5.3 Test Procedures

Test Method	
<ul style="list-style-type: none"><li>Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).</li></ul>	
<ul style="list-style-type: none"><li>The average emission levels shall be measured in [duty cycle <math>\geq</math> 98 or duty factor].</li></ul>	
<ul style="list-style-type: none"><li>For the transmitter unwanted emissions shall be measured using following options below:</li></ul>	
<div></div>	<ul style="list-style-type: none"><li>Refer as FCC KDB 789033, clause H)2) for unwanted emissions into non-restricted bands.</li></ul>
	<ul style="list-style-type: none"><li>Refer as FCC KDB 789033, clause H)1) for unwanted emissions into restricted bands.</li></ul>
	<input type="checkbox"/> Refer as FCC KDB 789033, H)6) Method AD (Trace Averaging).
	<input checked="" type="checkbox"/> Refer as FCC KDB 789033, H)6) Method VB (Reduced VBW).
	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq$ 1/T, where T is pulse time.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
	<input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause H)5) measurement procedure peak limit.
<div></div>	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.2 measurement procedure peak limit.
	<ul style="list-style-type: none"><li>For radiated measurement.</li></ul>






Test Method	
	<ul style="list-style-type: none"><li>Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.</li><li>Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.</li><li>Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz.</li></ul>
	<ul style="list-style-type: none"><li>The any unwanted emissions level shall not exceed the fundamental emission level.</li></ul>
	<ul style="list-style-type: none"><li>All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.</li></ul>

Test Method	
	<ul style="list-style-type: none"><li>For conducted and cabinet radiation measurement, refer as FCC KDB 789033, clause H)3).</li></ul>
	<ul style="list-style-type: none"><li>For conducted unwanted emissions into non-restricted bands (relative emission limits). Devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding 10 log(N) if the measurements are made relative to the in-band emissions on the individual outputs.</li><li>For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB</li><li>For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.</li></ul>



### 3.5.4 Test Setup





### 3.5.5 Transmitter Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

### 3.5.6 Test Result of Transmitter Unwanted Emissions

Refer as Appendix E



## 4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 31, 2018	Jan. 30, 2019	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 20, 2017	Dec. 19, 2018	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 29, 2017	Dec. 28, 2018	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	150kHz ~ 30MHz	May 22, 2018	May 21, 2019	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA with 6dB Attenuator	TESEQ & EMCI	CBL6112D & N-6-06	37880 & AT-N0609	20MHz ~ 2GHz	Aug. 27, 2018	Aug. 26, 2019	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2018	Mar. 15, 2019	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Nov. 20, 2017	Nov. 19, 2018	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Nov. 13, 2018	Nov. 12, 2019	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 28, 2018	Jun. 27, 2019	Radiation (03CH01-CB)
Pre-Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	May 02, 2018	May 01, 2019	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 09, 2018	Jan. 08, 2019	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 08, 2019	Jan. 07, 2020	Radiation (03CH01-CB)
Pre-Amplifier	MITEQ	TTA1840-35-H G	1864479	18GHz ~ 40GHz	Jul. 04, 2018	Jul. 03, 2019	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Nov. 23, 2017	Nov. 22, 2018	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Jan. 31, 2019	Jan. 30, 2020	Radiation (03CH01-CB)
EMI Test	R&S	ESCS	100354	9kHz ~ 2.75GHz	Dec. 08, 2017	Dec. 07, 2018	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS	100359	9kHz ~ 2.75GHz	Jul. 03, 2018	Jul. 02, 2019	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-16+17	N/A	30 MHz ~ 1 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16+17	N/A	1 GHz ~ 18 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G#1	N/A	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	High Cable-40G#2	N/A	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 21, 2017	Dec. 20, 2018	Conducted (TH01-CB)
Spectrum Analyzer	R&S	FSP-40	100019	9kHz ~ 40GHz	Apr. 25, 2018	Apr. 24, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-06	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-07	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-08	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-09	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY54320014	50MHz~18GHz	Apr. 17, 2018	Apr. 16, 2019	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.



## AC Conduction Result

Appendix A

### Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition
Mode 1	Pass	AV	3.971M	27.14	46.00	-18.86	10.11	Neutral

### Mode Configure

Mode	Configure
Mode 1	EUT with PoE

### Mode 1

08/11/2018




NO : H  
EUT : cnPilot Outdoor E510  
Power : 120V  
Mode : normal+POE  
Memo :

Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	AF (dB)	CL (dB)	AT (dB)			
QP	154.5k	45.88	65.75	-19.87	10.07	Line	-	35.81	9.91	0.16	-			
AV	154.5k	30.70	55.75	-25.05	10.07	Line	-	20.63	9.91	0.16	-			
QP	258k	39.33	61.49	-22.16	10.04	Line	-	29.29	9.91	0.13	-			
AV	258k	30.29	51.49	-21.20	10.04	Line	-	20.25	9.91	0.13	-			
QP	303k	36.67	60.17	-23.50	10.04	Line	-	26.63	9.91	0.13	-			
AV	303k	25.34	50.17	-24.83	10.04	Line	-	15.30	9.91	0.13	-			
QP	3.327M	30.10	56.00	-25.90	10.13	Line	-	19.97	9.97	0.16	-			
AV	3.327M	21.90	46.00	-24.10	10.13	Line	-	11.77	9.97	0.16	-			
QP	3.84M	34.16	56.00	-21.84	10.12	Line	-	24.04	9.98	0.14	-			
AV	3.84M	26.86	46.00	-19.14	10.12	Line	"Worst"	16.74	9.98	0.14	-			
QP	29.747M	35.62	60.00	-24.38	10.94	Line	-	24.68	10.65	0.29	-			
AV	29.747M	28.87	50.00	-21.13	10.94	Line	-	17.93	10.65	0.29	-			

### Mode 1

08/11/2018



NO : H  
EUT : cnPilot Outdoor E510  
Power : 120V  
Mode : normal+POE  
Memo :

Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor	Condition	Comment	Raw (dBuV)	AF (dB)	CL (dB)	AT (dB)			
QP	150k	46.35	66.00	-19.65	10.08	Neutral	-	36.27	9.92	0.16	-			
AV	150k	31.99	56.00	-24.01	10.08	Neutral	-	21.91	9.92	0.16	-			
QP	168k	43.14	65.06	-21.92	10.07	Neutral	-	33.07	9.92	0.15	-			
AV	168k	28.72	55.06	-26.34	10.07	Neutral	-	18.65	9.92	0.15	-			
QP	253.5k	41.82	61.64	-19.82	10.05	Neutral	-	31.77	9.92	0.13	-			
AV	253.5k	30.43	51.64	-21.21	10.05	Neutral	-	20.38	9.92	0.13	-			
QP	2.954M	33.82	56.00	-22.18	10.14	Neutral	-	23.68	9.97	0.17	-			
AV	2.954M	26.59	46.00	-19.41	10.14	Neutral	-	16.45	9.97	0.17	-			
QP	3.971M	34.49	56.00	-21.51	10.11	Neutral	-	24.38	9.98	0.13	-			
AV	3.971M	27.14	46.00	-18.86	10.11	Neutral	"Worst"	17.03	9.98	0.13	-			
QP	29.747M	35.71	60.00	-24.29	10.74	Neutral	-	24.97	10.45	0.29	-			
AV	29.747M	28.87	50.00	-21.13	10.74	Neutral	-	18.13	10.45	0.29	-			

**Summary**

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.15-5.25GHz	-	-	-	-	-
802.11a_Nss1,(6Mbps)_2TX	19.075M	16.417M	16M4D1D	18.9M	16.392M
802.11ac VHT20_Nss1,(MCS0)_2TX	20M	17.616M	17M6D1D	19.8M	17.566M
802.11ac VHT40_Nss1,(MCS0)_2TX	39.55M	36.032M	36M0D1D	39.45M	35.982M
802.11ac VHT80_Nss1,(MCS0)_2TX	83.7M	75.862M	75M9D1D	83.3M	75.662M
5.725-5.85GHz	-	-	-	-	-
802.11a_Nss1,(6Mbps)_2TX	16.35M	16.442M	16M4D1D	16.325M	16.442M
802.11ac VHT20_Nss1,(MCS0)_2TX	17.6M	17.641M	17M6D1D	17.55M	17.616M
802.11ac VHT40_Nss1,(MCS0)_2TX	35.55M	36.132M	36M1D1D	34.45M	35.982M
802.11ac VHT80_Nss1,(MCS0)_2TX	76.4M	75.962M	76M0D1D	76.4M	75.862M

**Max-N dB** = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;

**Max-OBW** = Maximum 99% occupied bandwidth;

**Min-N dB** = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;

**Min-OBW** = Minimum 99% occupied bandwidth;



**Result**


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11a_Nss1,(6Mbps)_2TX	-	-	-	-	-	-
5180MHz	Pass	Inf	19.025M	16.392M	18.925M	16.417M
5200MHz	Pass	Inf	19.075M	16.392M	18.925M	16.392M
5240MHz	Pass	Inf	19.075M	16.392M	18.9M	16.417M
5745MHz	Pass	500k	16.35M	16.442M	16.325M	16.442M
5785MHz	Pass	500k	16.325M	16.442M	16.325M	16.442M
5825MHz	Pass	500k	16.325M	16.442M	16.325M	16.442M
802.11ac_VHT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5180MHz	Pass	Inf	19.975M	17.616M	19.925M	17.591M
5200MHz	Pass	Inf	19.975M	17.566M	19.8M	17.591M
5240MHz	Pass	Inf	20M	17.591M	19.85M	17.591M
5745MHz	Pass	500k	17.575M	17.616M	17.6M	17.616M
5785MHz	Pass	500k	17.575M	17.616M	17.6M	17.616M
5825MHz	Pass	500k	17.55M	17.641M	17.55M	17.616M
802.11ac_VHT40_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5190MHz	Pass	Inf	39.5M	35.982M	39.45M	35.982M
5230MHz	Pass	Inf	39.55M	35.982M	39.45M	36.032M
5755MHz	Pass	500k	35.05M	36.032M	35.55M	36.132M
5795MHz	Pass	500k	35.3M	35.982M	34.45M	36.032M
802.11ac_VHT80_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5210MHz	Pass	Inf	83.7M	75.862M	83.3M	75.662M
5775MHz	Pass	500k	76.4M	75.962M	76.4M	75.862M

**Port X-N dB** = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band


**Port X-OBW** = Port X 99% occupied bandwidth;

**802.11a\_Nss1,(6Mbps)\_2TX**
**EBW**
**5180MHz**


08/11/2018


**802.11a\_Nss1,(6Mbps)\_2TX**
**EBW**
**5200MHz**

08/11/2018



**802.11a\_Nss1,(6Mbps)\_2TX**
**EBW**
**5240MHz**

08/11/2018




**802.11a\_Nss1,(6Mbps)\_2TX**
**EBW**
**5745MHz**


08/11/2018


**802.11a\_Nss1,(6Mbps)\_2TX**
**EBW**
**5785MHz**

08/11/2018



**802.11a\_Nss1,(6Mbps)\_2TX**
**EBW**
**5825MHz**

08/11/2018




**802.11ac VHT20\_Nss1,(MCS0)\_2TX**
**EBW**
**5180MHz**


08/11/2018


**802.11ac VHT20\_Nss1,(MCS0)\_2TX**
**EBW**
**5200MHz**

08/11/2018



**802.11ac VHT20\_Nss1,(MCS0)\_2TX**
**EBW**
**5240MHz**

08/11/2018




**802.11ac VHT20\_Nss1,(MCS0)\_2TX**
**EBW**
**5745MHz**


08/11/2018


**802.11ac VHT20\_Nss1,(MCS0)\_2TX**
**EBW**
**5785MHz**

08/11/2018



**802.11ac VHT20\_Nss1,(MCS0)\_2TX**
**EBW**
**5825MHz**

08/11/2018




**802.11ac VHT40\_Nss1,(MCS0)\_2TX**
**EBW**
**5190MHz**


08/11/2018


**802.11ac VHT40\_Nss1,(MCS0)\_2TX**
**EBW**
**5230MHz**

08/11/2018



**802.11ac VHT40\_Nss1,(MCS0)\_2TX**
**EBW**
**5755MHz**

08/11/2018




**802.11ac VHT40\_Nss1,(MCS0)\_2TX**
**EBW**
**5795MHz**


08/11/2018


**802.11ac VHT80\_Nss1,(MCS0)\_2TX**
**EBW**
**5210MHz**

08/11/2018


**802.11ac VHT80\_Nss1,(MCS0)\_2TX**
**EBW**
**5775MHz**

08/11/2018



**Based on conducted spurious emission  
Summary**

Mode	Total Power (dBm)	Total Power (W)	EIRP /EIRP- Elevation 30° (dBm)	EIRP /EIRP- Elevation 30° (W)
5.15-5.25GHz	-	-	-	-
802.11a_Nss1,(6Mbps)_2TX	18.33	0.06808	27.23/16.10	0.52845/0.04074
802.11ac VHT20_Nss1,(MCS0)_2TX	18.42	0.06950	27.32/16.19	0.53951/0.04159
802.11ac VHT40_Nss1,(MCS0)_2TX	18.02	0.06339	26.92/15.79	0.49204/0.03793
802.11ac VHT80_Nss1,(MCS0)_2TX	16.67	0.04645	25.57/14.44	0.36058/0.02780

**Result**

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP /EIRP- Elevation 30° (dBm)	EIRP Limit / EIRP Limit- Elevation 30° (dBm)
802.11a_Nss1,(6Mbps)_2TX	-	-	-	-	-	-	-	-
5180MHz	Pass	8.90	15.13	15.04	18.10	27.10	27.00/15.87	36.00/21.00
5200MHz	Pass	8.90	15.30	15.24	18.28	27.10	27.18/16.05	36.00/21.00
5240MHz	Pass	8.90	15.42	15.22	18.33	27.10	27.23/16.10	36.00/21.00
802.11ac VHT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5180MHz	Pass	8.90	15.45	15.19	18.33	27.10	27.23/16.10	36.00/21.00
5200MHz	Pass	8.90	15.42	15.38	18.41	27.10	27.31/16.18	36.00/21.00
5240MHz	Pass	8.90	15.51	15.31	18.42	27.10	27.32/16.19	36.00/21.00
802.11ac VHT40_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5190MHz	Pass	8.90	14.64	14.32	17.49	27.10	26.39/15.26	36.00/21.00
5230MHz	Pass	8.90	15.06	14.96	18.02	27.10	26.92/15.79	36.00/21.00
802.11ac VHT80_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5210MHz	Pass	8.90	13.75	13.56	16.67	27.10	25.57/14.44	36.00/21.00

**DG** = Directional Gain; **Port X** = Port X output power



**Based on conducted spurious emission**
**Summary**

Mode	Total Power (dBm)	Total Power (W)
5.725-5.85GHz	-	-
802.11a_Nss1,(6Mbps)_2TX	27.00	0.50119
802.11ac VHT20_Nss1,(MCS0)_2TX	27.03	0.50466
802.11ac VHT40_Nss1,(MCS0)_2TX	27.04	0.50582
802.11ac VHT80_Nss1,(MCS0)_2TX	23.34	0.21577

**Result**

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	Power Limit (dBm)
802.11a_Nss1,(6Mbps)_2TX	-	-	-	-	-	-
5745MHz	Pass	8.90	23.81	24.06	26.95	27.10
5785MHz	Pass	8.90	23.87	23.84	26.87	27.10
5825MHz	Pass	8.90	23.63	24.32	27.00	27.10
802.11ac VHT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5745MHz	Pass	8.90	23.69	24.07	26.89	27.10
5785MHz	Pass	8.90	23.87	23.85	26.87	27.10
5825MHz	Pass	8.90	23.67	24.34	27.03	27.10
802.11ac VHT40_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5755MHz	Pass	8.90	23.83	24.19	27.02	27.10
5795MHz	Pass	8.90	23.88	24.18	27.04	27.10
802.11ac VHT80_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5775MHz	Pass	8.90	20.22	20.43	23.34	27.10

**DG** = Directional Gain; **Port X** = Port X output power



Elevation angle above 30 degree Max Gain(dBi)		-2.23
Freq. (MHz)	Gain(dBi)	Elevation Angle Define
1500	-8.20	Above 30 degree
1490	-8.73	
1480	-9.43	
1470	-9.82	
1460	-9.86	
1450	-9.97	
1440	-10.06	
1430	-10.13	
1420	-10.18	
1410	-10.21	
1400	-10.23	
1390	-10.24	
1380	-10.25	
1370	-10.25	
1360	-10.25	
1350	-10.25	
1340	-10.25	
1330	-10.25	
1320	-10.25	
1310	-10.25	
1300	-10.25	
1290	-10.25	
1280	-10.25	
1270	-10.25	
1260	-10.25	
1250	-10.25	
1240	-10.25	
1230	-10.25	
1220	-10.25	
1210	-10.25	
1200	-10.25	
1190	-10.25	
1180	-10.25	
1170	-10.25	
1160	-10.25	
1150	-10.25	
1140	-10.25	
1130	-10.25	
1120	-10.25	
1110	-10.25	
1100	-10.25	
1090	-10.25	
1080	-10.25	
1070	-10.25	
1060	-10.25	
1050	-10.25	
1040	-10.25	
1030	-10.25	
1020	-10.25	
1010	-10.25	
1000	-10.25	
990	-10.25	
980	-10.25	
970	-10.25	
960	-10.25	
950	-10.25	
940	-10.25	
930	-10.25	
920	-10.25	
910	-10.25	
900	-10.25	
890	-10.25	
880	-10.25	
870	-10.25	
860	-10.25	
850	-10.25	
840	-10.25	
830	-10.25	
820	-10.25	
810	-10.25	
800	-10.25	
790	-10.25	
780	-10.25	
770	-10.25	
760	-10.25	
750	-10.25	
740	-10.25	
730	-10.25	
720	-10.25	
710	-10.25	
700	-10.25	
690	-10.25	
680	-10.25	
670	-10.25	
660	-10.25	
650	-10.25	
640	-10.25	
630	-10.25	
620	-10.25	
610	-10.25	
600	-10.25	
590	-10.25	
580	-10.25	
570	-10.25	
560	-10.25	
550	-10.25	
540	-10.25	
530	-10.25	
520	-10.25	
510	-10.25	
500	-10.25	
490	-10.25	
480	-10.25	
470	-10.25	
460	-10.25	
450	-10.25	
440	-10.25	
430	-10.25	
420	-10.25	
410	-10.25	
400	-10.25	
390	-10.25	
380	-10.25	
370	-10.25	
360	-10.25	
350	-10.25	
340	-10.25	
330	-10.25	
320	-10.25	
310	-10.25	
300	-10.25	
290	-10.25	
280	-10.25	
270	-10.25	
260	-10.25	
250	-10.25	
240	-10.25	
230	-10.25	
220	-10.25	
210	-10.25	
200	-10.25	
190	-10.25	
180	-10.25	
170	-10.25	
160	-10.25	
150	-10.25	
140	-10.25	
130	-10.25	
120	-10.25	
110	-10.25	
100	-10.25	
90	-10.25	
80	-10.25	
70	-10.25	
60	-10.25	
50	-10.25	
40	-10.25	
30	-10.25	
20	-10.25	
10	-10.25	
0	-10.25	
-10	-10.25	
-20	-10.25	
-30	-10.25	
-40	-10.25	
-50	-10.25	
-60	-10.25	
-70	-10.25	
-80	-10.25	
-90	-10.25	
-100	-10.25	
-110	-10.25	
-120	-10.25	
-130	-10.25	
-140	-10.25	
-150	-10.25	
-160	-10.25	
-170	-10.25	
-180	-10.25	
-190	-10.25	
-200	-10.25	
-210	-10.25	
-220	-10.25	
-230	-10.25	
-240	-10.25	
-250	-10.25	
-260	-10.25	
-270	-10.25	
-280	-10.25	
-290	-10.25	
-300	-10.25	
-310	-10.25	
-320	-10.25	
-330	-10.25	
-340	-10.25	
-350	-10.25	
-360	-10.25	
-370	-10.25	
-380	-10.25	
-390	-10.25	
-400	-10.25	
-410	-10.25	
-420	-10.25	
-430	-10.25	
-440	-10.25	
-450	-10.25	
-460	-10.25	
-470	-10.25	
-480	-10.25	
-490	-10.25	
-500	-10.25	
-510	-10.25	
-520	-10.25	
-530	-10.25	
-540	-10.25	
-550	-10.25	
-560	-10.25	
-570	-10.25	
-580	-10.25	
-590	-10.25	
-600	-10.25	
-610	-10.25	
-620	-10.25	
-630	-10.25	
-640	-10.25	
-650	-10.25	
-660	-10.25	
-670	-10.25	
-680	-10.25	
-690	-10.25	
-700	-10.25	
-710	-10.25	
-720	-10.25	
-730	-10.25	
-740	-10.25	
-750	-10.25	
-760	-10.25	
-770	-10.25	
-780	-10.25	
-790	-10.25	
-800	-10.25	
-810	-10.25	
-820	-10.25	
-830	-10.25	
-840	-10.25	
-850	-10.25	
-860	-10.25	
-870	-10.25	
-880	-10.25	
-890	-10.25	
-900	-10.25	
-910	-10.25	
-920	-10.25	
-930	-10.25	
-940	-10.25	
-950	-10.25	
-960	-10.25	
-970	-10.25	
-980	-10.25	
-990	-10.25	
-1000	-10.25	
-1010	-10.25	
-1020	-10.25	
-1030	-10.25	
-1040	-10.25	
-1050	-10.25	
-1060	-10.25	
-1070	-10.25	
-1080	-10.25	
-1090	-10.25	
-1100	-10.25	
-1110	-10.25	
-1120	-10.25	
-1130	-10.25	
-1140	-10.25	
-1150	-10.25	
-1160	-10.25	
-1170	-10.25	
-1180	-10.25	
-1190	-10.25	
-1200	-10.25	
-1210	-10.25	
-1220	-10.25	
-1230	-10.25	
-1240	-10.25	
-1250	-10.25	
-1260	-10.25	
-1270	-10.25	
-1280	-10.25	
-1290	-10.25	
-1300	-10.25	
-1310	-10.25	
-1320	-10.25	
-1330	-10.25	
-1340	-10.25	
-1350	-10.25	
-1360	-10.25	
-1370	-10.25	
-1380	-10.25	
-1390	-10.25	
-1400	-10.25	
-1410	-10.25	
-1420	-10.25	
-1430	-10.25	
-1440	-10.25	
-1450	-10.25	
-1460	-10.25	
-1470	-10.25	
-1480	-10.25	
-1490	-10.25	
-1500	-10.25	
-1510	-10.25	
-1520	-10.25	
-1530	-10.25	
-1540	-10.25	
-1550	-10.25	
-1560	-10.25	
-1570	-10.25	
-1580	-10.25	
-1590	-10.25	
-1600	-10.25	
-1610	-10.25	
-1620	-10.25	
-1630	-10.25	
-1640	-10.25	
-1650	-10.25	
-1660	-10.25	
-1670	-10.25	
-1680	-10.25	
-1690	-10.25	
-1700	-10.25	
-1710	-10.25	
-1720	-10.25	
-1730	-10.25	
-1740	-10.25	
-1750	-10.25	
-1760	-10.25	
-1770	-10.25	
-1780	-10.25	
-1790	-10.25	
-1800	-10.25	
-1810	-10.25	
-1820	-10.25	
-1830	-10.25	
-1840	-10.25	
-1850	-10.25	
-1860	-10.25	
-1870	-10.25	
-1880	-10.25	
-1890	-10.25	
-1900	-10.25	
-1910	-10.25	
-1920	-10.25	
-1930	-10.25	
-1940	-10.25	
-1950	-10.25	
-1960	-10.25	
-1970	-10.25	
-1980	-10.25	
-1990	-10.25	
-2000	-10.25	
-2010	-10.25	
-2020	-10.25	
-2030	-10.25	
-2040	-10.25	
-2050	-10.25	
-2060	-10.25	
-2070	-10.25	
-2080	-10.25	
-2090	-10.25	
-2100	-10.25	
-2110	-10.25	
-2120	-10.25	
-2130	-10.25	
-2140	-10.25	
-2150	-10.25	
-2160	-10.25	
-2170	-10.25	
-2180	-10.25	
-2190	-10.25	
-2200	-10.25	
-2210	-10.25	
-2220	-10.25	
-2230	-10.25	
-2240	-10.25	
-2250	-10.25	
-2260	-10.25	
-2270	-10.25	
-2280	-10.25	
-2290	-10.25	
-2300	-10.25	
-2310	-10.25	
-2320	-10.25	
-2330	-10.25	
-2340	-10.25	
-2350	-10.25	
-2360	-10.25	
-2370	-10.25	
-2380	-10.25	
-2390	-10.25	
-2400	-10.25	
-2410	-10.25	
-2420	-10.25	
-2430	-10.25	
-2440	-10.25	
-2450	-10.25	
-2460	-10.25	
-2470	-10.25	
-2480	-10.25	
-2490	-10.25	
-2500	-10.25	
-2510	-10.25	
-2520	-10.25	
-2530	-10.25	
-2540	-10.25	
-2550	-10.25	
-2560	-10.25	
-2570	-10.25	
-2580	-10.25	
-2590	-10.25	
-2600	-10.25	
-2610	-10.25	
-2620	-10.25	
-2630	-10.25	
-2640	-10.25	
-2650	-10.25	
-2660	-10.25	
-2670	-10.25	
-2680	-10.25	
-2690	-10.25	
-2700	-10.25	
-2710	-10.25	
-2720	-10.25	
-2730	-10.25	
-2740	-10.25	
-2750	-10.25	
-2760	-10.25	
-2770	-10.25	
-2780	-10.25	
-2790	-10.25	
-2800	-10.25	
-2810	-10.25	
-2820	-10.25	
-2830	-10.25	
-2840	-10.25	
-2850	-10.25	
-2860	-10.25	
-2870	-10.25	
-2880	-10.25	
-2890	-10.25	
-2900	-10.25	
-2910	-10.25	
-2920	-10.25	
-2930	-10.25	
-2940	-10.25	
-2950	-10.25	
-2960	-10.25	
-2970	-10.25	
-2980	-10.25	
-2990	-10.25	
-3000	-10.25	
-3010	-10.25	
-3020	-10.25	
-3030	-10.25	
-3040	-10.25	
-3050	-10.25	
-3060	-10.25	
-3070	-10.25	
-3080	-10.25	
-3090	-10.25	
-3100	-10.25	
-3110	-10.25	
-3120	-10.25	
-3130	-10.25	
-3140	-10.25	
-3150	-10.25	
-3160	-10.25	
-3170	-10.25	
-3180	-10.25	
-3190	-10.25	
-3200	-10.25	
-3210	-10.25	
-3220	-10.25	
-3230	-10.25	
-3240	-10.25	
-3250	-10.25	
-3260	-10.25	
-3270	-10.25	
-3280	-10.25	
-3290	-10.25	
-3300	-10.25	
-3310	-10.25	
-3320	-10.25	
-3330	-10.25	
-3340	-10.25	
-3350	-10.25	
-3360	-10.25	
-3370	-10.25	
-3380	-10.25	
-3390	-10.25	
-3400	-10.25	
-3410	-10.25	
-3420	-10.25	
-3430	-10.25	
-3440	-10.25	
-3450	-10.25	
-3460	-10.25	
-3470	-10.25	
-3480	-10.25	
-3490	-10.25	
-3500	-10.25	
-3510	-10.25	
-3520	-10.25	
-3530	-10.25	
-3540	-10.25	
-3550	-10.25	
-3560	-10.25	
-3570	-10.25	
-3580	-10.25	
-3590	-10.25	
-3600	-10.25	
-3610	-10.25	
-3620	-10.25	
-3630	-10.25	
-3640	-10.25	
-3650	-10.25	
-3660	-10.25	
-3670	-10.25	
-3680	-10.25	
-3690	-10.25	
-3700	-10.25	
-3710	-10.25	
-3720	-10.25	
-3730	-10.25	
-3740	-10.25	
-3750	-10.25	
-3760	-10.25	
-3770	-10.25	
-3780	-10.25	
-3790	-10.25	
-3800	-10.25	
-3810	-10.25	
-3820	-10.25	
-3830	-10.25	
-3840	-10.25	
-3850	-10.25	
-3860	-10.25	
-3870	-10.25	
-3880	-10.25	
-3890	-10.25	
-3900	-10.25	
-3910	-10.25	
-3920	-10.25	
-3930	-10.25	
-3940	-10.25	



## Elevation angle above 30 degree Max Gain

16	-1.43	0° reference angle
16	-1.81	
17	-2.21	
18	-2.48	
19	-3.10	
20	-3.85	
21	-4.80	
22	-5.77	
23	-6.31	
24	-6.42	
25	-6.88	
26	-8.41	
27	-9.01	
28	-9.53	
29	-9.96	
30	-11.18	
31	-13.97	
32	-11.60	
33	-11.33	
34	-13.02	
35	-14.77	
36	-16.30	
37	-16.53	
38	-14.58	
39	-13.88	
40	-15.77	
41	-16.32	
42	-16.86	
43	-16.46	
44	-16.79	
45	-16.85	
46	-15.23	0° - 30°
47	-8.67	
48	-10.56	
49	-12.35	
50	-14.04	
51	-13.81	
52	-14.88	
53	-10.05	
54	-6.47	
55	-9.21	
56	-8.09	
57	-6.77	
58	-7.28	
59	-6.80	
60	-6.87	
61	-5.96	
62	-6.35	
63	-6.18	
64	-5.96	
65	-6.51	
66	-5.98	
67	-5.28	
68	-4.20	
69	-5.14	
70	-4.53	
71	-4.17	
72	-3.73	
73	-3.81	
74	-3.66	
75	-3.33	
76	-3.23	
77	-2.51	
78	-2.78	
79	-3.16	
80	-3.68	
81	-3.66	
82	-3.79	
83	-4.32	
84	-7.85	
85	-7.42	
86	-7.78	
87	-8.30	
88	-8.83	
89	-8.56	
90	-9.33	
91	-10.85	
92	-11.86	
93	-13.33	
94	-15.72	
95	-23.49	
96	-29.09	
97	-36.16	
98	-35.86	
99	-19.53	
100	-15.11	
101	-16.45	
102	-11.86	
103	-13.07	
104	-13.26	
105	-13.13	
106	-11.46	
107	-10.86	
108	-10.90	
109	-13.33	
110	-10.51	
111	-13.83	
112	-11.01	
113	-10.98	
114	-10.52	
115	-10.01	
116	-9.47	
117	-8.23	
118	-8.78	
119	-16.16	
120	-10.86	
121	-11.15	
122	-11.36	
123	-11.04	
124	-11.64	
125	-11.53	
126	-11.86	
127	-12.79	
128	-12.65	
129	-13.64	
130	-12.35	
131	-12.10	
132	-11.21	
133	-10.28	
134	-8.49	
135	-8.57	
136	-8.30	
137	-7.78	
138	-6.11	
139	-5.65	
140	-6.34	
141	-6.39	
142	-5.60	
143	-4.96	
144	-4.56	
145	-4.59	
146	-4.55	
147	-4.66	
148	-4.52	
149	-3.51	
150	-3.21	
151	-3.47	
152	-3.86	
153	-4.34	
154	-4.13	
155	-3.97	
156	-4.91	
157	-5.51	
158	-6.72	
159	-6.88	
160	-6.33	
161	-6.43	
162	-7.33	
163	-7.85	
164	-7.88	
165	-7.58	
166	-7.39	
167	-6.89	
168	-6.13	
169	-6.06	
170	-6.07	
171	-7.97	
172	-7.78	
173	-8.03	
174	-7.86	
175	-7.29	
176	-6.75	
177	-6.79	
178	-7.59	
179	-8.88	

**Based on radiated spurious emission**
**Summary**

Mode	Total Power (dBm)	Total Power (W)
5.15-5.25GHz	-	-
802.11ac VHT20_Nss1,(MCS0)_2TX	21.43	0.13900
5.725-5.85GHz	-	-
802.11ac VHT80_Nss1,(MCS0)_2TX	23.99	0.25061

**Result**

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	Power Limit (dBm)
802.11ac VHT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5180MHz	Pass	8.90	18.65	18.18	21.43	27.10
802.11ac VHT80_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5775MHz	Pass	8.90	20.84	21.12	23.99	27.10

**Note : 1. DG = Directional Gain;Port X = Port X output power**

**2. For the test result is for manufacturer's reference only and is not applicable to certificated.**

**Summary**

Mode	PD (dBm/RBW)
5.15-5.25GHz	-
802.11a_Nss1,(6Mbps)_2TX	5.50
802.11ac VHT20_Nss1,(MCS0)_2TX	5.46
802.11ac VHT40_Nss1,(MCS0)_2TX	2.42
802.11ac VHT80_Nss1,(MCS0)_2TX	-2.46
5.725-5.85GHz	-
802.11a_Nss1,(6Mbps)_2TX	13.11
802.11ac VHT20_Nss1,(MCS0)_2TX	12.80
802.11ac VHT40_Nss1,(MCS0)_2TX	10.26
802.11ac VHT80_Nss1,(MCS0)_2TX	2.34

**RBW** = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

**Result**

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
802.11a_Nss1,(6Mbps)_2TX	-	-	-	-	-	-
5180MHz	Pass	8.90	2.41	2.29	5.23	14.10
5200MHz	Pass	8.90	2.58	2.51	5.35	14.10
5240MHz	Pass	8.90	2.63	2.60	5.50	14.10
5745MHz	Pass	8.90	9.44	9.84	12.56	27.10
5785MHz	Pass	8.90	9.70	10.05	12.83	27.10
5825MHz	Pass	8.90	9.76	10.74	13.11	27.10
802.11ac VHT20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5180MHz	Pass	8.90	2.40	2.12	5.15	14.10
5200MHz	Pass	8.90	2.35	2.40	5.33	14.10
5240MHz	Pass	8.90	2.53	2.44	5.46	14.10
5745MHz	Pass	8.90	9.16	9.85	12.53	27.10
5785MHz	Pass	8.90	9.31	9.70	12.44	27.10
5825MHz	Pass	8.90	9.40	10.47	12.80	27.10
802.11ac VHT40_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5190MHz	Pass	8.90	-1.06	-1.27	1.70	14.10
5230MHz	Pass	8.90	-0.49	-0.64	2.42	14.10
5755MHz	Pass	8.90	7.28	7.46	10.26	27.10
5795MHz	Pass	8.90	6.80	7.39	9.92	27.10
802.11ac VHT80_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5210MHz	Pass	8.90	-5.25	-5.39	-2.46	14.10
5775MHz	Pass	8.90	-0.37	-0.42	2.34	27.10

**DG** = Directional Gain; **RBW** = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


**PD** = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port Xpower density;

### 802.11a\_Nss1,(6Mbps)\_2TX

### PSD

5180MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)
5.23	5.23	2.41	2.29

### 802.11a\_Nss1,(6Mbps)\_2TX

### PSD

5200MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)
5.35	5.35	2.58	2.51

### 802.11a\_Nss1,(6Mbps)\_2TX

### PSD

5240MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)	(dBm/100kHz)
5.50	5.50	2.63	2.60

### 802.11a\_Nss1,(6Mbps)\_2TX

### PSD

5745MHz

08/11/2018




### 802.11a\_Nss1,(6Mbps)\_2TX

### PSD

5785MHz

08/11/2018




### 802.11a\_Nss1,(6Mbps)\_2TX

### PSD

5825MHz

08/11/2018






### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

### PSD

5180MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
5.15	5.15	2.40	2.12

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

### PSD

5200MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
5.33	5.33	2.35	2.40

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

### PSD

5240MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
5.46	5.46	2.53	2.44

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

### PSD

5745MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
12.53	12.53	9.16	9.85

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

### PSD

5785MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
12.44	12.44	9.31	9.70

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

### PSD

5825MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
12.80	12.80	9.40	10.47

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

### PSD

5190MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
1.70	1.70	-1.06	-1.27

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

### PSD

5230MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
2.42	2.42	-0.49	-0.64

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

### PSD

5755MHz

08/11/2018




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
10.26	10.26	7.28	7.46

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

PSD

5795MHz

08/11/2018




### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

PSD

5210MHz

08/11/2018




### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

PSD


5775MHz

08/11/2018




Test Mode	Mode 1	Frequency Range	30 MHz to 1,000 MHz
-----------	--------	-----------------	---------------------

## Vertical 30 MHz to 1,000 MHz



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	34.85	33.13	40.00	-6.87	40.51	1.01	23.06	31.45	300	0 Peak	VERTICAL
2	44.55	36.17	40.00	-3.83	48.85	1.36	17.54	31.58	300	0 Peak	VERTICAL
3	85.29	31.34	40.00	-8.66	48.13	0.76	14.17	31.72	300	0 Peak	VERTICAL
4	128.94	28.38	43.50	-15.12	40.26	1.15	18.70	31.73	300	0 Peak	VERTICAL
5	145.43	28.81	43.50	-14.69	42.09	1.12	17.35	31.75	300	0 Peak	VERTICAL
6	156.10	29.80	43.50	-13.70	43.73	1.03	16.80	31.76	300	0 Peak	VERTICAL

## Horizontal 30 MHz to 1,000 MHz



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	30.97	27.28	40.00	-12.72	32.22	0.98	25.40	31.32	100	360 Peak	HORIZONTAL
2	98.87	23.10	43.50	-20.40	36.87	0.83	17.10	31.70	100	360 Peak	HORIZONTAL
3	145.43	38.08	43.50	-5.42	51.36	1.12	17.35	31.75	100	360 Peak	HORIZONTAL
4	226.91	30.28	46.00	-15.72	43.16	2.19	16.73	31.80	100	360 Peak	HORIZONTAL
5	250.19	28.50	46.00	-17.50	39.24	2.38	18.70	31.82	100	360 Peak	HORIZONTAL
6	958.29	30.97	46.00	-15.03	31.51	3.95	27.70	32.19	100	360 Peak	HORIZONTAL

**Summary**


Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Type	Freq (Hz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	DG (dBi)	Refl (dB)	Psum (dBm)	P1 (dBm)	P2 (dBm)
5.15-5.25GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-
802.11ac VHT80_Nss1,(MCS0)_2TX	Pass	1G	5.15G	1M	AV	5.14896G	-41.23	-41.20	-0.03	8.90	0.00	-50.13	-52.54	-53.84

DG = Directional Gain;  
PX=Port X; Psum=P1+..P2+..PX

### 802.11a\_Nss1,(6Mbps)\_2TX

5180MHz


CSE-PK



### 802.11a\_Nss1,(6Mbps)\_2TX

5180MHz


CSE-AV



### 802.11a\_Nss1,(6Mbps)\_2TX

5200MHz

CSE-PK






### 802.11a\_Nss1,(6Mbps)\_2TX

5200MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	4.9923G	-42.63	-41.20	-1.43	8.90	0.00	-51.53	-51.83	-62.08
1G	5.15G	1M	AV	5.11981G	-46.08	-41.20	-4.88	8.90	0.00	-54.99	-56.74	-57.57
5.35G	5.46G	1M	AV	5.37596G	-45.09	-41.20	-3.89	8.90	0.00	-53.99	-54.74	-61.96
5.46G	8G	1M	AV	5.46G	-51.59	-41.20	-10.39	8.90	0.00	-60.49	-63.32	-63.69

### 802.11a\_Nss1,(6Mbps)\_2TX

5240MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	8G	1M	PK	5.13963G	-36.61	-21.20	-15.41	8.90	0.00	-45.51	-48.41	-48.63
1G	8G	1M	PK	5.466G	-38.73	-27.00	-11.73	8.90	0.00	-47.63	-52.14	-49.52

### 802.11a\_Nss1,(6Mbps)\_2TX

5240MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	4.9923G	-42.52	-41.20	-1.32	8.90	0.00	-51.42	-52.23	-59.13
1G	5.15G	1M	AV	5.12095G	-45.02	-41.20	-3.82	8.90	0.00	-53.92	-58.81	-55.62
5.35G	5.46G	1M	AV	5.37596G	-44.67	-41.20	-3.47	8.90	0.00	-53.57	-54.76	-59.77
5.46G	8G	1M	AV	5.46G	-50.65	-41.20	-9.45	8.90	0.00	-59.55	-63.19	-62.01

### 802.11a\_Nss1,(6Mbps)\_2TX

5745MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	8G	1M	PK	562963G	-32.23	-27.00	5.23	8.90	0.00	-41.13	-43.71	-44.61
1G	8G	1M	PK	5963G	-31.59	-27.00	4.59	8.90	0.00	-40.49	-42.64	-44.57
1G	8G	1M	PK	686338G	-30.17	-27.00	-3.17	8.90	0.00	-39.07	-40.80	-43.90

### 802.11a\_Nss1,(6Mbps)\_2TX

5745MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	1.5395G	-43.26	-41.20	-2.06	8.90	0.00	-52.16	-55.39	-54.96
5.15G	5.35G	1M	AV	5.15G	-44.61	-41.20	-3.41	8.90	0.00	-53.51	-56.30	-56.76
5.35G	5.46G	1M	AV	5.37959G	-42.74	-41.20	-1.54	8.90	0.00	-52.64	-54.72	-56.84
5.46G	8G	1M	AV	5.46G	-44.57	-41.20	-3.37	8.90	0.00	-53.47	-56.26	-56.71

### 802.11a\_Nss1,(6Mbps)\_2TX

5785MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.94G	1M	PK	5.58638G	-31.69	-27.00	-4.69	8.90	0.00	-40.59	-41.79	-46.75
1G	8G	1M	PK	5.949G	-31.08	-27.00	-4.08	8.90	0.00	-39.98	-42.82	-43.16
1G	8G	1M	PK	6.89663G	-30.08	-27.00	-3.08	8.90	0.00	-38.98	-42.61	-41.44

### 802.11a\_Nss1,(6Mbps)\_2TX

5785MHz

### CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	1.57996G	-43.75	-41.20	-2.55	8.90	0.00	-52.65	-55.47	-53.86
5.15G	5.35G	1M	AV	5.15G	-44.82	-41.20	-3.62	8.90	0.00	-53.82	-56.76	-56.81
5.35G	5.46G	1M	AV	5.37574G	-43.99	-41.20	-2.79	8.90	0.00	-52.89	-55.00	-57.05
5.46G	8G	1M	AV	5.46G	-44.52	-41.20	-3.32	8.90	0.00	-53.42	-56.65	-56.23

### 802.11a\_Nss1,(6Mbps)\_2TX

5825MHz

### CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	8G	1M	PK	5.55G	-31.95	-27.00	-4.95	8.90	0.00	-40.85	-43.85	-43.88
1G	8G	1M	PK	5.863G	-30.21	-27.00	-3.21	8.90	0.00	-39.13	-40.92	-43.83
1G	8G	1M	PK	6.76888G	-30.10	-27.00	-3.10	8.90	0.00	-39.00	-44.22	-40.55

### 802.11a\_Nss1,(6Mbps)\_2TX

5825MHz

### CSE-AV


07/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	1.61939G	-42.37	-41.20	-1.17	8.90	0.00	-51.27	-54.39	-54.18
5.15G	5.35G	1M	AV	5.15G	-44.98	-41.20	-3.78	8.90	0.00	-53.88	-56.83	-56.95
5.35G	5.46G	1M	AV	5.37596G	-44.21	-41.20	-3.01	8.90	0.00	-53.11	-55.63	-56.68
5.46G	8G	1M	AV	5.46G	-44.93	-41.20	-3.73	8.90	0.00	-53.83	-56.78	-56.91


### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5180MHz

CSE-PK




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5180MHz

CSE-AV



### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5200MHz

CSE-PK




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5200MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	515G	1M	AV	4.9923G	-42.76	-41.20	-1.56	8.90	0.00	-51.66	-52.04	-62.38
1G	515G	1M	AV	5.11981G	-46.21	-41.20	-5.01	8.90	0.00	-55.11	-57.80	-58.56
5.35G	5.46G	1M	AV	5.37596G	-45.13	-41.20	-3.93	8.90	0.00	-54.03	-54.82	-61.83
5.46G	8G	1M	AV	5.46G	-51.63	-41.20	-10.43	8.90	0.00	-60.53	-63.16	-63.95

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5240MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	8G	1M	PK	5.12038G	-36.39	-21.20	-15.19	8.90	0.00	-45.29	-51.12	-46.61
1G	8G	1M	PK	5.48788G	-38.90	-27.00	-11.90	8.90	0.00	-47.80	-51.60	-50.15

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5240MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	515G	1M	AV	4.9923G	-42.76	-41.20	-1.56	8.90	0.00	-51.66	-52.04	-62.38
1G	515G	1M	AV	5.11981G	-44.74	-41.20	-3.54	8.90	0.00	-53.64	-58.70	-55.27
5.35G	5.46G	1M	AV	5.37607G	-44.50	-41.20	-3.30	8.90	0.00	-53.40	-54.76	-59.09
5.46G	8G	1M	AV	5.46G	-50.59	-41.20	-9.39	8.90	0.00	-59.49	-62.94	-62.11

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5745MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	BG	1M	PK	5.68075G	-32.04	-27.00	5.04	8.90	0.00	-40.04	-43.53	-44.42
1G	BG	1M	PK	5.98138G	-31.23	-27.00	4.23	8.90	0.00	-40.13	-44.78	-41.96
1G	BG	1M	PK	6.8065G	-30.13	-27.00	-3.13	8.90	0.00	-39.03	-43.33	-41.04

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5745MHz

CSE-AV

07/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	1.5395G	-43.33	-41.20	-2.13	8.90	0.00	-52.23	-55.51	-54.99
5.15G	5.35G	1M	AV	5.15G	-44.86	-41.20	-3.66	8.90	0.00	-53.76	-56.72	-56.82
5.35G	5.46G	1M	AV	5.37986G	-43.53	-41.20	-2.33	8.90	0.00	-52.43	-54.43	-56.77
5.46G	BG	1M	AV	5.46G	-44.78	-41.20	-3.58	8.90	0.00	-53.68	-56.61	-56.77

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5785MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	BG	1M	PK	5.61125G	-31.72	-27.00	4.72	8.90	0.00	-40.62	-43.68	-43.39
1G	BG	1M	PK	5.94725G	-30.90	-27.00	-3.90	8.90	0.00	-39.80	-42.79	-42.83
1G	BG	1M	PK	6.698G	-30.32	-27.00	-3.32	8.90	0.00	-39.22	-41.69	-42.84

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5785MHz

#### CSE-AV

07/11/2018

Limit:AV  
Sum:AV  
Port 1  
Port 2




PK=Port X  
Psum=P1+...PK

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5825MHz

#### CSE-PK

07/11/2018

Limit:PK  
Sum:PK  
Port 1  
Port 2




PK=Port X  
Psum=P1+...PK

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX 5825MHz

#### CSE-AV

07/11/2018

Limit:AV  
Sum:AV  
Port 1  
Port 2




PK=Port X  
Psum=P1+...PK

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5190MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	BG	1M	PK	5.14025G	-31.83	-21.20	-10.63	8.90	0.00	-40.73	-43.01	-44.63
1G	BG	1M	PK	5.94288G	-40.24	-27.00	-13.24	8.90	0.00	-49.14	-51.30	-53.21
1G	BG	1M	PK	6.92025G	-36.29	-27.00	-9.29	8.90	0.00	-45.19	-48.26	-48.15

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5190MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.150	1M	AV	5.14096G	-42.48	-41.20	-1.28	8.90	0.00	-51.38	-53.96	-54.86
5.150	5.460	1M	AV	5.37586G	-45.04	-41.20	-3.84	8.90	0.00	-53.94	-54.72	-40.76
5.460	BG	1M	AV	5.46G	-51.86	-41.20	-10.66	8.90	0.00	-60.76	-63.57	-63.99

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5230MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	BG	1M	PK	5.14663G	-35.59	-21.20	-14.39	8.90	0.00	-44.49	-50.93	-45.61
1G	BG	1M	PK	5.46338G	-39.25	-27.00	-12.25	8.90	0.00	-48.15	-53.04	-49.86
1G	BG	1M	PK	6.97363G	-37.62	-27.00	-10.62	8.90	0.00	-46.52	-50.49	-48.74



### 802.11ac VHT40\_Nss1,(MCS0)\_2TX 5230MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	4.9923G	-42.33	-41.20	-1.13	8.90	0.00	-51.23	-52.16	-58.39
1G	5.15G	1M	AV	5.12895G	-44.25	-41.20	-3.15	8.90	0.00	-53.25	-58.78	-54.67
5.35G	5.46G	1M	AV	5.37596G	-44.46	-41.20	-3.26	8.90	0.00	-53.36	-54.68	-59.19
5.46G	8G	1M	AV	5.46G	-50.28	-41.20	-9.08	8.90	0.00	-59.18	-62.63	-61.80

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX 5755MHz

CSE-PK

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	8G	1M	PK	5.64886G	-28.65	-27.00	-1.65	8.90	0.00	-37.55	-41.60	-39.72
1G	8G	1M	PK	5.828G	-30.28	-27.00	-3.28	8.90	0.00	-39.18	-41.50	-43.02

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX 5755MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	4.9923G	-44.16	-41.20	-2.96	8.90	0.00	-53.16	-55.63	-56.82
5.15G	5.35G	1M	AV	5.15G	-44.90	-41.20	-3.72	8.90	0.00	-53.82	-56.92	-56.74
5.35G	5.46G	1M	AV	5.37618G	-43.37	-41.20	-2.17	8.90	0.00	-52.27	-54.26	-56.62
5.46G	8G	1M	AV	5.46G	-44.36	-41.20	-3.16	8.90	0.00	-53.26	-56.20	-56.35

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5795MHz


CSE-PK



### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5795MHz


CSE-AV



### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5210MHz

CSE-PK




### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5210MHz

CSE-AV

07/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	5.14896G	-41.23	-41.20	-0.03	8.90	0.00	-50.13	-52.54	-53.84
5.35G	5.46G	1M	AV	5.37996G	-44.72	-41.20	-3.52	8.90	0.00	-53.62	-54.76	-60.00
5.46G	8G	1M	AV	5.46G	-51.03	-41.20	-9.83	8.90	0.00	-59.93	-62.61	-63.30

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5775MHz

CSE-PK

08/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	8G	1M	PK	5.64713G	-27.05	-27.00	-0.05	8.90	0.00	-35.95	-38.04	-40.14
1G	8G	1M	PK	5.9245G	-26.73	-26.63	-0.10	8.90	0.00	-35.63	-37.62	-39.99

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5775MHz

CSE-AV

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
1G	5.15G	1M	AV	4.82319G	-43.68	-41.20	-2.40	8.90	0.00	-52.30	-57.08	-54.36
5.15G	5.35G	1M	AV	5.15G	-44.49	-41.20	-3.29	8.90	0.00	-53.39	-56.88	-55.97
5.35G	5.46G	1M	AV	5.37807G	-43.31	-41.20	-2.11	8.90	0.00	-52.21	-54.11	-56.71
5.46G	8G	1M	AV	5.46G	-44.29	-41.20	-3.09	8.90	0.00	-53.19	-56.11	-56.29



Summary

Mode	Result	F-Start (Hz)	F-Stop (Hz)	RBW (Hz)	Type	Freq (Hz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	DG (dBi)	Refl (dB)	Psum (dBm)	P1 (dBm)	P2 (dBm)
5.725-5.85GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-
802.11ac VHT80_Nss1,(MCS0)_2TX	Pass	8G	40G	1M	AV	39.994G	-54.33	-41.20	-13.13	8.90	0.00	-63.23	-66.05	-66.44


DG = Directional Gain;  
PX=Port X; Psum=P1+..P2+..PX

### 802.11a\_Nss1,(6Mbps)\_2TX

5180MHz

CSE-PK

08/11/2018




### 802.11a\_Nss1,(6Mbps)\_2TX

5180MHz

CSE-AV

08/11/2018




### 802.11a\_Nss1,(6Mbps)\_2TX

5200MHz

CSE-PK

08/11/2018




### 802.11a\_Nss1,(6Mbps)\_2TX

5200MHz

CSE-AV

08/11/2018



Limit.AV  
Sum.AV  
Port 1  
Port 2

PX=Port X  
Psum=P1+...PX


F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	39.998G	-54.68	-41.20	-13.48	8.90	0.00	-63.58	-66.61	-66.58

### 802.11a\_Nss1,(6Mbps)\_2TX

5240MHz

CSE-PK

08/11/2018



Limit.PK  
Sum.PK  
Port 1  
Port 2

PX=Port X  
Psum=P1+...PX


F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	10.476G	-54.38	-27.00	-27.38	8.90	0.00	-63.28	-66.04	-66.55
8G	40G	1M	PK	37.316G	-44.32	-27.00	-17.32	8.90	0.00	-53.22	-55.71	-56.83

### 802.11a\_Nss1,(6Mbps)\_2TX

5240MHz

CSE-AV

08/11/2018



Limit.AV  
Sum.AV  
Port 1  
Port 2

PX=Port X  
Psum=P1+...PX



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	ERP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	39.994G	-54.71	-41.20	-13.51	8.90	0.00	-63.61	-66.42	-66.82

### 802.11a\_Nss1,(6Mbps)\_2TX

5745MHz

CSE-PK

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	11.492G	-53.17	-21.20	-31.97	8.90	0.00	-62.07	-64.22	-66.15
8G	40G	1M	PK	37.24G	-44.58	-27.00	-17.58	8.90	0.00	-53.48	-56.33	-56.65



PX=Port X  
Psum=P1+...PX

### 802.11a\_Nss1,(6Mbps)\_2TX

5745MHz

CSE-AV

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	11.491G	-64.52	-41.20	-23.32	8.90	0.00	-73.42	-76.08	-76.81
8G	40G	1M	AV	39.996G	-54.70	-41.20	-13.50	8.90	0.00	-63.60	-66.62	-66.61



PX=Port X  
Psum=P1+...PX

### 802.11a\_Nss1,(6Mbps)\_2TX

5785MHz

CSE-PK

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	Ref(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	11.564G	-52.48	-21.20	-31.28	8.90	0.00	-61.38	-64.36	-64.43
8G	40G	1M	PK	37.212G	-44.08	-27.00	-17.08	8.90	0.00	-52.98	-55.51	-56.54


PX=Port X  
Psum=P1+...PX

## 802.11a\_Nss1,(6Mbps)\_2TX

5785MHz

CSE-AV

08/11/2018




## 802.11a\_Nss1,(6Mbps)\_2TX

5825MHz

CSE-PK

08/11/2018




## 802.11a\_Nss1,(6Mbps)\_2TX

5825MHz

CSE-AV

08/11/2018






### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5180MHz

CSE-PK

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5180MHz

CSE-AV

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5200MHz

CSE-PK

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5200MHz

CSE-AV

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5240MHz

CSE-PK

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5240MHz

CSE-AV

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5745MHz

CSE-PK

08/11/2018



Limit.PK  
Sum.PK  
Port 1  
Port 2  
PX=Port X  
Psum=P1+...PX


F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	11.484G	-54.30	-21.20	-33.10	8.90	0.00	-63.20	-64.57	-68.89
8G	40G	1M	PK	37.344G	-44.52	-27.00	-17.52	8.90	0.00	-53.42	-58.24	-55.15

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5745MHz

CSE-AV

08/11/2018



Limit.AV  
Sum.AV  
Port 1  
Port 2  
PX=Port X  
Psum=P1+...PX


F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	11.495G	-65.04	-41.20	-23.84	8.90	0.00	-73.94	-76.82	-77.08
8G	40G	1M	AV	39.995G	-54.75	-41.20	-13.55	8.90	0.00	-63.65	-66.69	-66.64

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5785MHz

CSE-PK

08/11/2018



Limit.PK  
Sum.PK  
Port 1  
Port 2  
PX=Port X  
Psum=P1+...PX


F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	11.572G	-52.45	-21.20	-31.25	8.90	0.00	-61.35	-65.90	-63.22
8G	40G	1M	PK	37.152G	-44.43	-27.00	-17.43	8.90	0.00	-53.33	-57.62	-55.35

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5785MHz

CSE-AV

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5825MHz

CSE-PK

08/11/2018




### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

5825MHz

CSE-AV

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5190MHz

CSE-PK

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5190MHz

CSE-AV

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5230MHz

CSE-PK

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5230MHz

CSE-AV

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5755MHz

CSE-PK

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5755MHz

CSE-AV

08/11/2018




### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5795MHz

CSE-PK

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	11.588G	-53.45	-21.20	-32.25	8.90	0.00	-63.35	-64.49	-66.46
8G	40G	1M	PK	37.212G	-44.31	-27.00	-17.31	8.90	0.00	-53.21	-55.94	-56.51


PX=Port X  
Psum=P1+...PX

### 802.11ac VHT40\_Nss1,(MCS0)\_2TX

5795MHz

CSE-AV

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	11.59G	-64.26	-41.20	-23.06	8.90	0.00	-73.16	-76.12	-76.23
8G	40G	1M	AV	39.999G	-54.45	-41.20	-13.25	8.90	0.00	-63.35	-66.49	-66.23


PX=Port X  
Psum=P1+...PX

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5210MHz

CSE-PK

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	10.452G	-53.15	-27.00	-26.15	8.90	0.00	-62.05	-63.81	-66.81
8G	40G	1M	PK	37.236G	-44.33	-27.00	-17.33	8.90	0.00	-53.23	-58.06	-54.96


PX=Port X  
Psum=P1+...PX

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5210MHz

CSE-AV

08/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	39.993G	-54.44	-41.20	-13.24	8.90	0.00	-63.34	-66.16	-66.55

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5775MHz

CSE-PK

08/11/2018




F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	PK	11.564G	-54.12	-21.20	-32.92	8.90	0.00	-63.02	-65.18	-67.10
8G	40G	1M	PK	37.328G	-44.59	-27.00	-17.59	8.90	0.00	-53.49	-57.48	-55.70

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

5775MHz

CSE-AV

08/11/2018



F-Start(Hz)	F-Stop(Hz)	RBW(Hz)	Type	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Margin(dB)	DG(dB)	RefI(dB)	Psum(dBm)	P1(dBm)	P2(dBm)
8G	40G	1M	AV	11.563G	-64.67	-41.20	-23.47	8.90	0.00	-73.57	-76.62	-76.55
8G	40G	1M	AV	39.994G	-54.33	-41.20	-13.13	8.90	0.00	-63.23	-66.05	-66.44




**Summary**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Pol. (H/V)	Azimuth (°)	Height (m)	Comments
5.725-5.85GHz	-	-	-	-	-	-	-	-	-	-	-	-
802.11ac VHT40_Nss1,(MCS0)_2TX	Pass	AV	12.49996G	52.26	54.00	-1.74	15.57	3	Horizontal	83	1.20	-

## 802.11ac VHT40\_Nss1,(MCS0)\_2TX

12/11/2018

## 5795MHz\_TX




EUT Y\_2TX  
Setting 23.5  
04-E-2  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Pol. (H/V)	Azimuth (°)	Height (m)	Comments						
PK	12.50019G	60.16	74.00	-13.84	15.58	3	Vertical	185	1.63	-						
AV	12.49994G	51.58	54.00	-2.42	15.57	3	Vertical	185	1.63	-						

## 802.11ac VHT40\_Nss1,(MCS0)\_2TX

12/11/2018

## 5795MHz\_TX



EUT Y\_2TX  
Setting 23.5  
04-E-2  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Pol. (H/V)	Azimuth (°)	Height (m)	Comments						
PK	12.49992G	60.30	74.00	-13.70	15.57	3	Horizontal	83	1.20	-						
AV	12.49996G	52.26	54.00	-1.74	15.57	3	Horizontal	83	1.20	-						

**Summary**


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.15-5.25GHz	-	-	-	-	-	-	-	-	-	-	-	-
802.11ac VHT20_Nss1,(MCS0)_2TX	Pass	AV	5.1499G	53.87	54.00	-0.13	7.85	3	Horizontal	359	1.88	-

**Note : For the test result is for manufacturer's reference only and is not applicable to certificated.**

## 802.11ac VHT20\_Nss1,(MCS0)\_2TX

14/02/2019

## 5180MHz\_TX




EUT V\_2TX  
Setting 18.5  
04-R-4-10  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	5.1431G	64.73	74.00	-9.27	7.84	3	Vertical	33	1.75	-
AV	5.1459G	49.47	54.00	-4.53	7.85	3	Vertical	33	1.75	-
PK	5.1816G	117.71	Inf	-Inf	7.90	3	Vertical	33	1.75	-
AV	5.1817G	106.06	Inf	-Inf	7.90	3	Vertical	33	1.75	-

## 802.11ac VHT20\_Nss1,(MCS0)\_2TX

14/02/2019

## 5180MHz\_TX




EUT Y\_2TX  
Setting 18.5  
04-R-4-10  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	5.1499G	69.12	74.00	-4.88	7.85	3	Horizontal	359	1.88	-
AV	5.1499G	53.87	54.00	-0.13	7.85	3	Horizontal	359	1.88	-
PK	5.1737G	118.59	Inf	-Inf	7.89	3	Horizontal	359	1.88	-
AV	5.172G	107.82	Inf	-Inf	7.89	3	Horizontal	359	1.88	-

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

14/02/2019

### 5180MHz\_TX




EUT Y\_2TX  
Setting 18.5  
04-R-4  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	10.37075G	57.47	68.20	-10.73	15.11	3	Vertical	252	1.50	-
PK	15.5619G	60.00	74.00	-14.00	16.00	3	Vertical	23	1.50	-
AV	15.5605G	46.31	54.00	-7.69	16.00	3	Vertical	23	1.50	-

### 802.11ac VHT20\_Nss1,(MCS0)\_2TX

14/02/2019

### 5180MHz\_TX



EUT Y\_2TX  
Setting 18.5  
04-R-4  
FSP(100142)


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	10.37565G	56.68	68.20	-11.52	15.12	3	Horizontal	220	1.50	-
PK	15.54025G	59.05	74.00	-14.95	16.02	3	Horizontal	295	1.50	-
AV	15.5605G	45.13	54.00	-8.87	16.00	3	Horizontal	295	1.50	-



## 802.11ac VHT80\_Nss1,(MCS0)\_2TX

14/02/2019

## 5775MHz\_TX




EUT Y\_2TX  
Setting Z1  
04-R-4-10  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	5.6325G	65.03	68.20	-3.17	9.32	3	Vertical	353	1.83	-
PK	5.758G	112.01	Inf	-Inf	9.38	3	Vertical	353	1.83	-
AV	5.757G	102.04	Inf	-Inf	9.37	3	Vertical	353	1.83	-
PK	5.9405G	64.95	68.20	-3.25	10.29	3	Vertical	353	1.83	-

## 802.11ac VHT80\_Nss1,(MCS0)\_2TX

14/02/2019

## 5775MHz\_TX




EUT Y\_2TX  
Setting 21  
04-R-4-10  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	5.6515G	69.07	69.31	-0.24	9.32	3	Horizontal	17	1.68	-
PK	5.7525G	114.18	Inf	-Inf	9.36	3	Horizontal	17	1.68	-
AV	5.7535G	104.39	Inf	-Inf	9.37	3	Horizontal	17	1.68	-
PK	5.9315G	65.59	68.20	-2.61	10.24	3	Horizontal	17	1.68	-

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

14/02/2019

### 5775MHz\_TX




EUT Y\_2TX  
Setting Z1  
04-R-4  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	11.5482G	55.91	74.00	-18.09	15.19	3	Vertical	340	1.50	-
AV	11.5259G	42.27	54.00	-11.73	15.20	3	Vertical	340	1.50	-
PK	17.3362G	61.20	68.20	-7.00	18.31	3	Vertical	359	1.50	-

### 802.11ac VHT80\_Nss1,(MCS0)\_2TX

14/02/2019

### 5775MHz\_TX



EUT Y\_2TX  
Setting 21  
04-R-4  
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	11.54076G	56.59	74.00	-17.41	15.19	3	Horizontal	22	2.17	-
AV	11.54994G	43.76	54.00	-10.24	15.19	3	Horizontal	22	2.17	-
PK	17.31219G	61.37	68.20	-6.83	18.27	3	Horizontal	89	1.50	-